



LEARN JAVA DESIGN PATTERNS

problem solving approaches

Design Patterns Tutorial

- Design Patterns - Home
- Design Patterns - Overview
- Design Patterns - Factory Pattern
- Abstract Factory Pattern
- Design Patterns - Singleton Pattern
- Design Patterns - Builder Pattern
- Design Patterns - Prototype Pattern
- Design Patterns - Adapter Pattern
- Design Patterns - Bridge Pattern
- Design Patterns - Filter Pattern
- Design Patterns - Composite Pattern
- Design Patterns - Decorator Pattern
- Design Patterns - Facade Pattern
- Design Patterns - Flyweight Pattern
- Design Patterns - Proxy Pattern
- Chain of Responsibility Pattern
- Design Patterns - Command Pattern
- Design Patterns - Interpreter Pattern
- Design Patterns - Iterator Pattern
- Design Patterns - Mediator Pattern
- Design Patterns - Memento Pattern
- Design Patterns - Observer Pattern
- Design Patterns - State Pattern
- Design Patterns - Null Object Pattern
- Design Patterns - Strategy Pattern
- Design Patterns - Template Pattern
- Design Patterns - Visitor Pattern
- Design Patterns - MVC Pattern
- Business Delegate Pattern
- Composite Entity Pattern
- Data Access Object Pattern
- Front Controller Pattern
- Intercepting Filter Pattern
- Service Locator Pattern
- Transfer Object Pattern

Design Patterns Resources

- Design Patterns - Questions/Answers
- Design Patterns - Quick Guide

Design Patterns - Prototype Pattern

[Previous Page](#)

[Next Page](#)


Prototype pattern refers to creating duplicate object while keeping performance in mind. This type of design pattern comes under creational pattern as this pattern provides one of the best ways to create an object.

This pattern involves implementing a prototype interface which tells to create a clone of the current object. This pattern is used when creation of object directly is costly. For example, an object is to be created after a costly database operation. We can cache the object, returns its clone on next request and update the database as and when needed thus reducing database calls.

Implementation

We're going to create an abstract class *Shape* and concrete classes extending the *Shape* class. A class *ShapeCache* is defined as a next step which stores shape objects in a *Hashtable* and returns their clone when requested.

PrototypPatternDemo, our demo class will use *ShapeCache* class to get a *Shape* object.



Step 1

Create an abstract class implementing *Cloneable* interface.

Shape.java

```

public abstract class Shape implements Cloneable {

    private String id;
    protected String type;

    abstract void draw();

    public String getType(){
        return type;
    }

    public String getId() {
        return id;
    }

    public void setId(String id) {
        this.id = id;
    }

    public Object clone() {
        Object clone = null;

        try {
            clone = super.clone();
        } catch (CloneNotSupportedException e) {
            e.printStackTrace();
        }
    }
}
    
```

- Design Patterns - Useful Resources

- Design Patterns - Discussion

Selected Reading

- UPSC IAS Exams Notes

- Developer's Best Practices

- Questions and Answers

- Effective Resume Writing

- HR Interview Questions

- Computer Glossary

- Who is Who

```
}

    return clone;
}
}
```

Step 2

Create concrete classes extending the above class.

Rectangle.java

```
public class Rectangle extends Shape {

    public Rectangle(){
        type = "Rectangle";
    }

    @Override
    public void draw() {
        System.out.println("Inside Rectangle::draw() method.");
    }
}
```

Square.java

```
public class Square extends Shape {

    public Square(){
        type = "Square";
    }

    @Override
    public void draw() {
        System.out.println("Inside Square::draw() method.");
    }
}
```

Circle.java

```
public class Circle extends Shape {

    public Circle(){
        type = "Circle";
    }

    @Override
    public void draw() {
        System.out.println("Inside Circle::draw() method.");
    }
}
```

Step 3

Create a class to get concrete classes from database and store them in a *Hashtable*.

ShapeCache.java

```
import java.util.Hashtable;

public class ShapeCache {

    private static Hashtable<String, Shape> shapeMap = new Hashtable<String, Shape>();

    public static Shape getShape(String shapeId) {
        Shape cachedShape = shapeMap.get(shapeId);
        return (Shape) cachedShape.clone();
    }

    // for each shape run database query and create shape
    // shapeMap.put(shapeKey, shape);
    // for example, we are adding three shapes

    public static void loadCache() {
        Circle circle = new Circle();
        circle.setId("1");
        shapeMap.put(circle.getId(),circle);

        Square square = new Square();
        square.setId("2");
        shapeMap.put(square.getId(),square);
    }
}
```

```
Rectangle rectangle = new Rectangle();
rectangle.setId("3");
shapeMap.put(rectangle.getId(), rectangle);
}
}
```

Step 4

PrototypePatternDemo uses *ShapeCache* class to get clones of shapes stored in a *Hashtable*.

PrototypePatternDemo.java

```
public class PrototypePatternDemo {
    public static void main(String[] args) {
        ShapeCache.loadCache();

        Shape clonedShape = (Shape) ShapeCache.getShape("1");
        System.out.println("Shape : " + clonedShape.getType());

        Shape clonedShape2 = (Shape) ShapeCache.getShape("2");
        System.out.println("Shape : " + clonedShape2.getType());

        Shape clonedShape3 = (Shape) ShapeCache.getShape("3");
        System.out.println("Shape : " + clonedShape3.getType());
    }
}
```

Step 5

Verify the output.

```
Shape : Circle
Shape : Square
Shape : Rectangle
```

[⏪ Previous Page](#) [🖨 Print Page](#)

[Next Page ⏩](#)



[🌐 About us](#)

[✳ Terms of use](#)

[🛡 Privacy Policy](#)

[❓ FAQ's](#)

[👉 Helping](#)

[📍 Contact](#)

© Copyright 2020. All Rights Reserved.