

Reporting API

How to request report data — a quick start guide.

1. The endpoint

Send a **POST** request with a JSON body to:

```
POST https:///reporting_api/v1/reporting/stats/json
```

The response is a JSON object with your requested metrics, described in section 5.

2. Authentication & headers

Authenticate with an API key sent as a Bearer token.

HEADER	VALUE
Authorization	Bearer <your API key>
Content-Type	application/json
Accept	application/json

3. The request body

The body tells the API *what* to measure, *over what period*, and *for which mailboxes/people*.

FIELD	REQUIRED	DESCRIPTION
community_id	Yes	Your workspace / community ID.
event_types	Yes	List of metrics to return, e.g. ["resolved","new_tickets"] . See 3a.

<code>time_type</code>	Yes	Period preset: <code>today</code> , <code>yesterday</code> , <code>all</code> , <code>custom</code> , or a dynamic value like <code>7d</code> .
<code>time_unit</code>	Yes	Bucket size: <code>minute</code> , <code>hour</code> , <code>day</code> , <code>week</code> , or <code>month</code> .
<code>time_period</code>	Yes	How many <code>time_units</code> per bucket (usually <code>1</code>).
<code>from_date</code>	Yes	Start of the window (ISO 8601 UTC), e.g. <code>2026-07-18T04:00:00.000Z</code> .
<code>to_date</code>	Yes	End of the window (ISO 8601 UTC).
<code>timezone</code>	Yes	IANA timezone used to align buckets, e.g. <code>America/New_York</code> .
<code>scope</code>	No	The main set of mailboxes/people to report on. See 3b.
<code>filters</code>	No	Additional filters, same shape as scope. Empty list <code>[]</code> for none.

3A. AVAILABLE METRICS (EVENT_TYPES)

Pass any combination of these values. Counts are whole numbers; time metrics are in seconds.

```
actioned_emails, resolved, new_tickets, open, replies, new_emails,
replies_to_resolve, resolve_time, response_time, time_to_first_reply,
resolve_time_business_hours, response_time_business_hours,
time_to_first_reply_business_hours, sla_breaches, handle_time
```

3B. SCOPE & FILTERS

A scope (or filter) narrows the report to specific mailboxes, tags, people, or customers. It has an

`id` (what to filter on), an `operator`, and a list of `values`:

```
"scope": {
  "id": "mailboxes",
  "operator": { "id": "is" },
  "values": [
    { "id": "ACf0kWdEPNiYSou98PwFYiKQfWq9c0T", "name": "Returns" },
    { "id": "ACqMGljMqLCOAZJ9ZYNz4oNZkF91D0T", "name": "Partnerships" }
```

```
]
}
```

FILTER ID

OPERATOR ID

`user`, `labels`, `topics`, `categories`, `allMailboxes`,
`mailbox`, `mailboxes`, `privateMailboxes`, `customerEmail`,
`customerDomain`

`is`, `is_not`, `or`,
`or_not`, `and`,
`and_not`

4. Full example request

Resolved tickets for a custom inbox:

```
{
  "community_id": "demo-community",
  "event_types": ["resolved"],
  "time_type": "today",
  "time_unit": "day",
  "time_period": 1,
  "timezone": "America/New_York",
  "from_date": "2026-07-18T04:00:00.000Z",
  "to_date": "2026-07-20T03:59:59.999Z",
  "filters": [],
  "scope": {
    "id": "mailboxes",
    "operator": { "id": "is" },
    "values": [
      { "id": "ACf0kWdEPNiYSou98PwFYiKQfWq9c0T", "name": "Returns" }
    ]
  }
}
```

4B. EXAMPLE: YEAR-TO-DATE SCORECARD

A custom date range for replies, resolved and handle time, across several shared inboxes. Agent-level numbers come back in the `actors` array.

```
{
  "community_id": "demo-community",
```

```

"event_types": ["replies", "resolved", "handle_time"],
"time_type": "custom",
"time_unit": "day",
"time_period": 1,
"timezone": "America/New_York",
"from_date": "2026-07-10T05:00:00.000Z",
"to_date": "2026-07-23T03:59:59.999Z",
"filters": [],
"scope": {
  "id": "mailboxes",
  "operator": { "id": "is" },
  "values": [
    { "id": "ACf0kWdEPNiYSou98PwFYiKQfWq9c0T", "name": "Returns" },
    { "id": "ACqMGljMqLCOAZJ9ZYNz4oNZkF91D0T", "name": "Partnerships" },
    { "id": "ACpw3ge04EDYzOsUMhVHgYGqpn2wq0T", "name": "Compliance" },
    { "id": "ACn0hYoSiro8YwtJVsn48DFDtyHyQ0T", "name": "Fax" },
    { "id": "ACSzkQ6eDUuigSwb0AFR4r7Z19wog0T", "name": "Outbound" }
  ]
}

```

5. Understanding the response

The response contains a `ticks` array (bucket boundaries) and one array per requested metric. Each value sits *between* two ticks, so there is always **one more tick than there are metric values**. Time metrics also return a matching `<metric>_count` array so you can compute weighted averages.

```

{
  "ticks": ["2026-07-16T22:00:00Z", "2026-07-17T22:00:00Z"],
  "resolved": [3],
  "new_tickets": [5],
  "actors": [ ... per-user breakdown ... ],
  "mailbox": [ ... per-inbox breakdown ... ]
}

```

Alongside the top-level totals, the response breaks the same metrics down by `actors` (people) and `mailbox`.

Tip: all dates are UTC (ISO 8601). Use the `timezone` field to control how days and weeks are bucketed for your team.