


```
## Loading required package: Matrix
## Loading required package: coda
## Loading required package: ape
```

```
setPar()
plot(SelAByYear, x=2006:2015, ylim=c(min( CIselAByYear), max( CIselAByYear)), xlab="Year", y
abline(h=0)
arrows(x0 = 2006:2015,x1 = 2006:2015,code = 3, y0 = CIselAByYear[1,],
       y1 = CIselAByYear[2,], angle = 90,length = 0.1)
abline(h=coefficients(m0all)[2], lty=2, lwd=5)
lowm0all <- coefficients(m0all)[2]+1.96*sm0all$coefficients[2,2]
highm0all <- coefficients(m0all)[2]-1.96*sm0all$coefficients[2,2]
polygon(x=c(2005,2016,2016,2005),y=c(lowm0all,lowm0all, highm0all, highm0all),
       fillOddEven = TRUE, col=rgb(0.1,0.1,0.1,0.3), lty=2)
```




```
#points(x=2006:2015,y=unlist(coefficients(mmRnoCorfitness)$Year["StMass"]), pch=17)
```

```
setPar()
plot(SelAByYearRho, x=2006:2015, ylim=c(min( CIselAByYearRho), max( CIselAByYearRho)), xlab="Year", y
abline(h=0)
arrows(x0 = 2006:2015,x1 = 2006:2015,code = 3, y0 = CIselAByYearRho[1,],
       y1 = CIselAByYearRho[2,], angle = 90,length = 0.1)
```

```

abline(h=coefficients(mOallRho)[2], lty=2, lwd=5)
smOallRho <- summary(mOallRho)
lowmOallRho <- coefficients(mOallRho)[2]+1.96*smOallRho$coefficients[2,2]
highmOallRho <- coefficients(mOallRho)[2]-1.96*smOallRho$coefficients[2,2]
polygon(x=c(2005,2016,2016,2005),y=c(lowmOallRho,lowmOallRho, highmOallRho, highmOallRho),
       fillOddEven = TRUE, col=rgb(0.1,0.1,0.1,0.5), lty=2)

```



```

setPar()
plot(SelABByYearPhi, x=2006:2015, ylim=c(min( CIselABByYearPhi, na.rm=TRUE), max( CIselABByYearPhi, na.rm=TRUE)),
     abline(h=0)
arrows(x0 = 2006:2015,x1 = 2006:2015,code = 3, y0 = CIselABByYearPhi[1,],
       y1 = CIselABByYearPhi[2,], angle = 90,length = 0.1)
abline(h=coefficients(mOallphi)[2], lty=2, lwd=5)
lowmOallphi <- coefficients(mOallphi)[2]+1.96*smOallphi$coefficients[2,2]
highmOallphi <- coefficients(mOallphi)[2]-1.96*smOallphi$coefficients[2,2]
polygon(x=c(2005,2016,2016,2005),y=c(lowmOallphi,lowmOallphi, highmOallphi, highmOallphi),
       fillOddEven = TRUE, col=rgb(0.1,0.1,0.1,0.5), lty=2 )

```



```

      paste(round(smmRnoCorrho$coefficients[2,1],rounding)," (" ,round(smmRnoCorrho$coe
      paste(round(smmRnoCorphi$coefficients[2,1],rounding)," (" ,round(smmRnoCorphi$coe
SigmaA <- c(sqrt(as.numeric(smmARnoCorfitness$varcor$Year.1)),
      sqrt(as.numeric(smmRnoCorrho$varcor$Year.1)),
sqrt(as.numeric(smmRnoCorphi$varcor$Year.1)))
SigRat <- c(sqrt(as.numeric(smmARnoCorfitness$varcor$Year.1))/smmARnoCorfitness$coefficients
      sqrt(as.numeric(smmRnoCorrho$varcor$Year.1))/smmRnoCorrho$coefficients[2,1],
sqrt(as.numeric(smmRnoCorphi$varcor$Year.1))/smmRnoCorphi$coefficients[2,1])

psigmaA <- c(fitnessAanova$`Pr(>Chisq)`[2]/2, RhoAanova$`Pr(>Chisq)`[2]/2, PhiAanova$`Pr(>Ch
confsigma <- c(paste("[",round(CImmARnoCorfitness[2,1],rounding),";",round(CImmARnoCorfitnes
      paste("[",round(CImmRnoCorrho[2,1],rounding),";",round(CImmRnoCorrho[2,2],rou
      paste("[",round(CImmRnoCorphi[2,1],rounding),";",round(CImmRnoCorphi[2,2],rou

TabSel <- data.frame(BetaGlm = BetaGlm, B=SDyears, C=SEyears , D=BetaGLMM , E=SigmaA, DD =co

```

Table 1:

0.082 (0.028)	0.167	0.097	0.036 (0.044)	0.117	[0.063;0.218]	8.1E-06	3.241
0.1 (0.034)	0.160	0.117	0.052 (0.044)	0.111	[0.053;0.212]	2.5E-04	2.145
-0.248 (0.089)	0.484	0.319	-0.217 (0.098)	0.109	[0;0.425]	3.6E-01	-0.501

```

szgr <- 2
szax <- 1.3
marr <- c(4, 4, 1, 1) + 0.1
par(las=1,mar=marr, cex=szgr, cex.lab=szax , cex.axis=szax, lwd=2 , las=1)

bbv <- boxplot(bvpairwise,ylab="Change in breeding values (g)", xlab="Year", range = 1,cex=1)
bbv$stats

##           [,1]           [,2]           [,3]           [,4]           [,5]
## [1,] -0.280501568 -0.257383635 -0.347173588 -0.267832000 -0.357132486
## [2,] -0.143366410 -0.087176846 -0.178386364 -0.095028840 -0.114692786
## [3,] -0.067520536 -0.003132208 -0.094707610  0.002214962  0.005447066
## [4,] -0.003739138  0.086721131 -0.008337006  0.082918931  0.130138872
## [5,]  0.134012211  0.260359089  0.161244353  0.260692898  0.371425991
##           [,6]           [,7]           [,8]           [,9]
## [1,] -0.8321504 -0.17794910 -0.382623528 -0.29096950
## [2,] -0.4928537  0.06339068 -0.130565493 -0.07342106
## [3,] -0.3192183  0.19033674 -0.004056911  0.03549705
## [4,] -0.1519085  0.31816724  0.122591670  0.14822783
## [5,]  0.1872504  0.57031481  0.374995899  0.36644027

bbv$group


```



```
## Median :-0.1036 Median :0.424183
## Mean :-0.1036 Mean :1.107278
## 3rd Qu.: 0.1219 3rd Qu.:2.109751
## Max. : 0.3475 Max. :3.900320
```

```
setPar()
par(mar=c(4, 6, 1, 1) + 0.1)
Betas <- matrix(sapply(X = list(BetaP1, BetaE1, BetaG1, BetaP2, BetaE2, BetaG2), posterior.m
BetasCI <- sapply(X = list(BetaP1, BetaE1, BetaG1, BetaP2, BetaE2, BetaG2), HPDinterval)

x <- barplot(Betas, beside=TRUE, ylim=c(min(BetasCI),max(BetasCI)),names.arg = c("Positive se
abline(h=0)
arrows(x0 = x, y0=BetasCI[1,],y1=BetasCI[2,],angle = 90,code = 3)
mtext(side=2, "Selection gradients", line=4, las=0, cex=szax*szgr)
```



```
posterior.mode(BetaG1 - BetaE1)

##          var1
## -0.1234186

HPDinterval(BetaG1 - BetaE1)

##          lower      upper
## var1 -0.2180723 -0.02770633
```

```

## attr("Probability")
## [1] 0.95

mean((BetaG1 - BetaE1)>0)*2
## [1] 0.006

posterior.mode(BetaG2 - BetaE2)
##          var1
## -0.009610168

HPDinterval(BetaG2 - BetaE2)
##          lower      upper
## var1 -0.1379426 0.05755331
## attr("Probability")
## [1] 0.95

mean((BetaG2 - BetaE2)>0)*2
## [1] 0.424

posterior.mode(BetaE1 - BetaE2)
##          var1
## 0.07575993

HPDinterval(BetaE1 - BetaE2)
##          lower      upper
## var1 0.03828845 0.1372658
## attr("Probability")
## [1] 0.95

mean((BetaE1 - BetaE2)<0)*2
## [1] 0

posterior.mode(BetaG1 - BetaG2)
##          var1
## -0.003689573

HPDinterval(BetaG1 - BetaG2)
##          lower      upper
## var1 -0.08005378 0.07575714
## attr("Probability")
## [1] 0.95

mean((BetaG1 - BetaG2)>0)*2
## [1] 0.908

```