```
PS C:\Users\Anurodh Saxena\Documents\MGIT\Sem-IV\9. Node\TASK11> npm init -y
PS C:\Users\Anurodh Saxena\Documents\MGIT\Sem-IV\9. Node\TASK11> npm install express mysql2 jsonwebtoken
added 90 packages, and audited 91 packages in 6s
```

```
mysql> use college_db_5r4;
Database changed
mysql> CREATE TABLE s_details (
    ->     id INT AUTO_INCREMENT PRIMARY KEY,
    ->     name VARCHAR(100),
    ->     course VARCHAR(100)
    -> );
Query OK, 0 rows affected (0.06 sec)
```

```
mysql> INSERT INTO s_details(name,course) VALUES ("Tim", "CSE");
Query OK, 1 row affected (0.01 sec)

mysql> INSERT INTO s_details(name,course) VALUES ("Sam", "ECE");
Query OK, 1 row affected (0.00 sec)

mysql> SELECT * FROM s_details;
+----+------+--------+
| id | name | course |
+----+------+--------+
|  1 | Tim  | CSE    |
|  2 | Sam  | ECE    |
+----+------+--------+
2 rows in set (0.00 sec)
```

```
PS C:\Users\Anurodh Saxena\Documents\MGIT\Sem-IV\9. Node\TASK11> node app.js
Server running on port 3000
```

```
mysql> SELECT * FROM s_details;
+----+------+--------+
| id | name | course |
+----+------+--------+
|  1 | Tim  | CSE    |
|  2 | Sam  | ECE    |
|  3 | John | EEE    |
+----+------+--------+
3 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM s_details;
+----+------+--------+
| id | name | course |
+----+------+--------+
|  1 | Tim  | CSE    |
|  2 | Sam  | ECE    |
|  3 | John | EEE    |
+----+------+--------+
3 rows in set (0.00 sec)
```

http://localhost:3000/login

Save | Share

POST http://localhost:3000/login Send

Docs Params Authorization Headers 9 Body Scripts Settings Cookies

none form-data x-www-form-urlencoded raw binary GraphQL JSON Schema Beautify

```
1 {
2   "username": "admin",
3   "password": "password123"
4 }
```

Body Cookies Headers 7 Test Results 200 OK • 11 ms • 401 B •

JSON Preview Visualize


```
1 {
2   "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1c2VybmFtZSI6ImFkbWluIiwiaWF0IjoxNzc3NDE1MzI1LCJleHAiOjE3NzgwMjAxMjV9.
      aOgjsCYIZlQ3o1Xj3kprw8_gKufoO_8BgmU0DWeS4eU"
3 }
```


http://localhost:3000/login

Save | Share

POST http://localhost:3000/login Send

Docs Params Authorization Headers 10 Body Scripts Settings Cookies

Auth Type

Bearer Token

The authorization header will be automatically generated when you send the request. Learn more about Bearer Token authorization.

Token ••••••••••••••••••••••••••••••••

Body Cookies Headers 7 Test Results 200 OK • 11 ms • 401 B •

JSON Preview Visualize


```
1 {
2   "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1c2VybmFtZSI6ImFkbWluIiwiaWF0IjoxNzc3NDE1MzI1LCJleHAiOjE3NzgwMjAxMjV9.
      aOgjsCYIZlQ3o1Xj3kprw8_gKufoO_8BgmU0DWeS4eU"
3 }
```


http://127.0.0.1:3000/s_details

POST http://127.0.0.1:3000/s_details

Docs Params Authorization Headers 10 Body Scripts Settings

none form-data x-www-form-urlencoded raw binary GraphQL JSON

```
1 {
2   "name": "John",
3   "course": "EEE"
4 }
```

Body Cookies Headers 7 Test Results

JSON Preview Visualize

```
1 {
2   "id": 3,
3   "name": "John",
4   "course": "EEE"
5 }
```

http://127.0.0.1:3000/s_details

GET http://127.0.0.1:3000/s_details

Docs Params Authorization Headers 8 Body Scripts Settings

Auth Type: Bearer Token

Token: ••••••••••••••••••••••••••••••••

Body Cookies Headers 7 Test Results 20

JSON Preview Visualize


```
[
    {
        "id": 1,
        "name": "Tim",
        "course": "CSE"
    },
    {
        "id": 2,
        "name": "Sam",
        "course": "ECE"
    },
    {
        "id": 3,
        "name": "John",
        "course": "EEE"
```


http://127.0.0.1:3000/s_details/1

PUT http://127.0.0.1:3000/s_details/1

Docs Params Authorization Headers 10 Body Scripts Settings

none form-data x-www-form-urlencoded raw binary GraphQL JSON


```
{
  "name": "Timothy Updated",
  "course": "AI"
}
```


Body Cookies Headers 7 Test Results

JSON Preview Visualize


```
{
    "message": "Updated successfully",
    "id": "1"
}
```

http://127.0.0.1:3000/s_details/1

Save

DELETE http://127.0.0.1:3000/s_details/1

Docs Params Authorization Headers 8 Body Scripts Settings

Auth Type

Bearer Token

Token

The authorization header will be automatically generated when you send the request. Learn more about

Body Cookies Headers 7 Test Results

200 OK • 11 ms • 2

JSON Preview Visualize

```
{
    "message": "Student 1 deleted"
}
```

```
mysql> SELECT * FROM s_details;
+----+----------------+--------+
| id | name           | course |
+----+----------------+--------+
|  1 | Timothy Updated | AI     |
|  2 | Sam            | ECE    |
|  3 | John           | EEE    |
+----+----------------+--------+
3 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM s_details;
+----+------+--------+
| id | name | course |
+----+------+--------+
|  2 | Sam  | ECE    |
|  3 | John | EEE    |
+----+------+--------+
2 rows in set (0.00 sec)
```