

```

1  -- Procedure to add two numbers
2  CREATE OR REPLACE PROCEDURE add_numbers(
3      a IN NUMBER,
4      b IN NUMBER
5  )
6  AS
7      sum_result NUMBER;
8  BEGIN
9      sum_result := a + b;
10     DBMS_OUTPUT.PUT_LINE('Sum = ' || sum_result);
11 END;
12 /
13
14 -- Calling the procedure
15 BEGIN
16     add_numbers(10, 20);
17 END;
18 /
19
20 -- Create Employee Table
21 CREATE TABLE emp (
22     emp_id NUMBER,
23     sal    NUMBER
24 );
25
26 -- Insert Sample Data
27 INSERT INTO emp VALUES (1, 100);
28 INSERT INTO emp VALUES (2, 200);
29
30 COMMIT;
31
32 -- Procedure to update salary
33 CREATE OR REPLACE PROCEDURE update_sal(
34     emp_id_check IN NUMBER,
35     new_sal      IN NUMBER
36 )
37 AS
38 BEGIN
39     UPDATE emp
40     SET sal = new_sal
41     WHERE emp_id = emp_id_check;
42
43     DBMS_OUTPUT.PUT_LINE('Salary updated to ' || new_sal);
44 END;
45 /
46
47 -- Calling the procedure
48 BEGIN
49     update_sal(2, 102324);
50 END;
51 /
52
53 -- Procedure using IN OUT and also DECLARE keyword
54 CREATE OR REPLACE PROCEDURE CUBE_NUM(
55     num IN OUT NUMBER
56 )
57 AS
58 BEGIN
59     num := num ** 3;
60 END;
61 /
62
63 -- Calling the procedure
64 DECLARE
65     num NUMBER := 9;
66 BEGIN
67     CUBE_NUM(num);
68     DBMS_OUTPUT.PUT_LINE(num);
69 END;
70 /
71
72 -- creating student table for trigger
73 CREATE TABLE student(
74     sid NUMBER,
75     sname VARCHAR2(20)
76 );
77

```

```

1  --creating trigger
2  CREATE OR REPLACE TRIGGER student_trigger
3  AFTER INSERT
4  ON student
5  FOR EACH ROW
6  BEGIN
7      DBMS_OUTPUT.PUT_LINE('New Student Added');
8  END;
9  /
10 --
11 DECLARE
12     CURSOR c IS
13         SELECT boyname FROM boys;
14     var boys.boyname%TYPE;
15 BEGIN
16     OPEN c;
17     LOOP
18         FETCH c INTO var;
19         EXIT WHEN c%NOTFOUND;
20         DBMS_OUTPUT.PUT_LINE(var);
21     END LOOP;
22     CLOSE c;
23 END;
24 /

```