

```

1  #include <stdio.h>
2  #include <stdlib.h>
3  #include <string.h>
4  #include <sys/ipc.h>
5  #include <sys/msg.h>
6
7  #define MAX 512
8
9  struct msg {
10     long type;
11     char text[MAX];
12 };
13
14 int main() {
15     int msgid;
16     msgid = msgget(12345, 0666 | IPC_CREAT);
17     if (msgid == -1) {
18         perror("msgget");
19         exit(1);
20     }
21
22     struct msg m;
23
24     while (1) {
25         printf("Enter message: ");
26         fgets(m.text, MAX, stdin);
27
28         m.type = 1;
29
30         msgsnd(msgid, &m, strlen(m.text) + 1, 0);
31
32         if (strncmp(m.text, "end", 3) == 0) break;
33     }
34 }
35 #####
36 include <stdio.h>
37 #include <stdlib.h>
38 #include <string.h>
39 #include <sys/ipc.h>
40 #include <sys/msg.h>
41
42 #define MAX 512
43
44 struct msg {
45     long type;
46     char text[MAX];
47 };
48
49 int main() {
50     int msgid;
51     msgid = msgget(12345, 0666 | IPC_CREAT);
52
53     if (msgid == -1) {
54         perror("msgget");
55         exit(1);
56     }
57     struct msg m;
58     while (1) {
59         msgrcv(msgid, &m, MAX, 0, 0);
60
61         printf("Received: %s", m.text);
62
63         if (strncmp(m.text, "end", 3) == 0) break;
64     }
65
66     msgctl(msgid, IPC_RMID, NULL);
67 }

```