OpenSCAP Multi-Agent Pipeline Report

Target: 192.168.64.12 | Generated: 2026-04-09 02:59:47

Models Used

Triage	inception/mercury-2
Remedy	inception/mercury-2
Review	inception/mercury-2
Qa	inception/mercury-2

Pipeline Summary

Total Findings Processed	150
Remediated Successfully	108
Failed Remediation	24
Requires Human Review	6
Discarded / Blocked	12
Success Rate	72.0%
Total Duration	5250.0s

LLM Usage (Aggregate)

Total LLM Calls	1860
Total Errors	0

Total LLM Duration	1392.2s
Prompt Tokens	5,638,207
Completion Tokens	538,769
Total Tokens	6,176,976
Estimated Cost (USD)	$1.2507

LLM Usage by Agent

Agent	Calls	Errors	Duration (s)	Prompt Tok	Compl Tok	Total Tok	Cost (USD)
Triage	109	0	125.1	82,241	63,354	145,595	$0.0617
Remedy	1481	0	937.3	5,251,077	313,836	5,564,913	$1.0065
Review	135	0	189.6	149,360	98,670	248,030	$0.1043
Qa	135	0	140.2	155,529	62,909	218,438	$0.0781

Remediated Successfully (108)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
package_aide_installed	Install AIDE	Medium	Remediate	LOW	1	Pass	—	—	127.4s	6
aide_scan_notification	Configure Notification of Post-AIDE Scan Details	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	21.7s	13
aide_use_fips_hashes	Configure AIDE to Use FIPS 140-2 for Validating Ha…	Medium	Remediate	LOW	3	Pass	Approved (8/10)	✓	63.1s	14
fips_custom_stig_sub_policy	Implement STIG Sub Crypto Policy	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	26.1s	13
package_gnutls-utils_installed	Ensure gnutls-utils is installed	Medium	Remediate	LOW	1	Pass	—	—	123.9s	5

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
package_nss-tools_installed	Ensure nss-tools is installed	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	75.5s	12
package_subscription-manager_installed	Install subscription-manager Package	Medium	Remediate	LOW	1	Pass	—	—	123.6s	5
ensure_gpgcheck_local_packages	Ensure gpgcheck Enabled for Local Packages	High	Remediate	LOW	1	Pass	Approved (8/10)	✓	26.7s	14
account_password_pam_faillock_system_auth	Configure the Use of the pam_faillock.so Module in…	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	38.6s	16
accounts_passwords_pam_faillock_interval	Set Interval For Counting Failed Password Attempts	Medium	Remediate	LOW	2	Pass	Approved (9/10)	✓	37.4s	15
accounts_passwords_pam_faillock_unlock_time	Set Lockout Time for Failed Password Attempts	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	29.2s	14
accounts_password_pam_dcredit	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	29.4s	14
accounts_password_pam_dictcheck	Ensure PAM Enforces Password Requirements - Preven…	Medium	Remediate	LOW	2	Pass	Approved (7/10)	✓	28.6s	13
accounts_password_pam_enforce_root	Ensure PAM Enforces Password Requirements - Enforc…	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	35.2s	15
accounts_password_pam_lcredit	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	24.9s	13
accounts_password_pam_maxclassrepeat	Ensure PAM Enforces Password Requirements - Maximu…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	41.0s	17

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
accounts_password_pam_maxrepeat	Set Password Maximum Consecutive Repeating Charact…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	23.4s	13
accounts_password_pam_ocredit	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	29.0s	14
accounts_password_pam_pwquality_retry	Ensure PAM Enforces Password Requirements - Authen…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	24.1s	12
accounts_password_pam_ucredit	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	51.3s	14
service_debug-shell_disabled	Disable debug-shell SystemD Service	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	49.2s	14
disable_ctrlaltdel_burstaction	Disable Ctrl-Alt-Del Burst Action	High	Remediate	LOW	1	Pass	Approved (8/10)	✓	36.3s	14
disable_ctrlaltdel_reboot	Disable Ctrl-Alt-Del Reboot Activation	High	Remediate	LOW	1	Pass	Approved (9/10)	✓	39.0s	11
package_opensc_installed	Install the opensc Package For Multifactor Authent…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	84.4s	11
package_pcsc-lite_installed	Install the pcsc-lite package	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	33.1s	11
install_smartcard_packages	Install Smart Card Packages For Multifactor Authen…	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	130.2s	13
service_pcscd_enabled	Enable the pcscd Service	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	34.4s	12
account_disable_post_pw_expiration	Set Account Expiration Following Inactivity	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	20.2s	12
accounts_minimum_age_login_defs	Set Password Minimum Age	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	17.8s	12

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
no_empty_passwords	Prevent Login to Accounts With Empty Password	High	Remediate	LOW	1	Pass	Approved (7/10)	✓	30.4s	17
use_pam_wheel_for_su	Enforce usage of pam_wheel for su authentication	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	24.7s	13
accounts_tmout	Set Interactive Session Timeout	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	35.8s	20
accounts_umask_etc_login_defs	Ensure the Default Umask is Set Correctly in login…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	26.8s	18
package_rsyslog-gnutls_installed	Ensure rsyslog-gnutls is installed	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	48.9s	11
rsyslog_encrypt_offload_actionsendstreamdriverauthmode	Ensure Rsyslog Authenticates Off-Loaded Audit Reco…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	21.4s	15
rsyslog_encrypt_offload_defaultnetstreamdriver	Ensure Rsyslog Encrypts Off-Loaded Audit Records	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	23.7s	18
rsyslog_remote_access_monitoring	Ensure remote access methods are monitored in Rsys…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	31.6s	22
rsyslog_remote_loghost	Ensure Logs Sent To Remote Host	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	15.7s	12
network_configure_name_resolution	Configure Multiple DNS Servers in /etc/resolv.conf	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	33.9s	18
package_libreswan_installed	Install libreswan Package	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	75.4s	13
sysctl_net_ipv6_conf_all_accept_ra	Configure Accepting Router Advertisements on All I…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	31.5s	18

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
sysctl_net_ipv6_conf_all_accept_redirects	Disable Accepting ICMP Redirects for All IPv6 Inte…	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	33.2s	16
sysctl_net_ipv6_conf_all_accept_source_route	Disable Kernel Parameter for Accepting Source-Rout…	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	29.8s	13
sysctl_net_ipv6_conf_all_forwarding	Disable Kernel Parameter for IPv6 Forwarding	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	46.7s	18
sysctl_net_ipv6_conf_default_accept_ra	Disable Accepting Router Advertisements on all IPv…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	26.6s	14
sysctl_net_ipv6_conf_default_accept_redirects	Disable Kernel Parameter for Accepting ICMP Redire…	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	40.5s	15
sysctl_net_ipv6_conf_default_accept_source_route	Disable Kernel Parameter for Accepting Source-Rout…	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	35.3s	15
sysctl_net_ipv4_conf_all_accept_redirects	Disable Accepting ICMP Redirects for All IPv4 Inte…	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	23.5s	13
sysctl_net_ipv4_conf_all_accept_source_route	Disable Kernel Parameter for Accepting Source-Rout…	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	42.4s	18
sysctl_net_ipv4_conf_all_forwarding	Disable Kernel Parameter for IPv4 Forwarding on al…	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	25.2s	13
sysctl_net_ipv4_conf_all_rp_filter	Enable Kernel Parameter to Use Reverse Path Filter…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	44.8s	17
sysctl_net_ipv4_conf_default_accept_redirects	Disable Kernel Parameter for Accepting ICMP Redire…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	73.9s	17

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
sysctl_net_ipv4_conf_default_rp_filter	Enable Kernel Parameter to Use Reverse Path Filter…	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	36.2s	15
sysctl_net_ipv4_icmp_echo_ignore_broadcasts	Enable Kernel Parameter to Ignore ICMP Broadcast E…	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	43.0s	18
sysctl_net_ipv4_tcp_syncookies	Enable Kernel Parameter to Use TCP Syncookies on N…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	28.1s	14
sysctl_net_ipv4_conf_all_send_redirects	Disable Kernel Parameter for Sending ICMP Redirect…	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	35.8s	15
sysctl_net_ipv4_conf_default_send_redirects	Disable Kernel Parameter for Sending ICMP Redirect…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	20.7s	12
kernel_module_atm_disabled	Disable ATM Support	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	13.2s	12
kernel_module_can_disabled	Disable CAN Support	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	23.1s	16
kernel_module_sctp_disabled	Disable SCTP Support	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	16.0s	13
kernel_module_bluetooth_disabled	Disable Bluetooth Kernel Module	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	12.7s	12
networkmanager_dns_mode	NetworkManager DNS Mode Must Be Must Configured	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	36.7s	22
rootfiles_configured	Ensure rootfiles tmpfile.d is Configured Correctly	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	11.9s	11
kernel_module_usb-storage_disabled	Disable Modprobe Loading of USB Storage Driver	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	14.0s	12

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
mount_option_boot_efi_nosuid	Add nosuid Option to /boot/efi	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	33.8s	15
mount_option_dev_shm_nodev	Add nodev Option to /dev/shm	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	28.3s	14
mount_option_dev_shm_noexec	Add noexec Option to /dev/shm	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	23.5s	13
mount_option_dev_shm_nosuid	Add nosuid Option to /dev/shm	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	33.4s	15
mount_option_home_noexec	Add noexec Option to /home	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	26.3s	13
sysctl_kernel_core_pattern	Disable storing core dumps	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	53.6s	21
sysctl_kernel_kexec_load_disabled	Disable Kernel Image Loading	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	31.6s	15
sysctl_kernel_unprivileged_bpf_disabled	Disable Access to Network bpf() Syscall From Unpri…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	36.7s	16
sysctl_kernel_yama_ptrace_scope	Restrict usage of ptrace to descendant processes	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	40.3s	18
sysctl_net_core_bpf_jit_harden	Harden the operation of the BPF just-in-time compi…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	55.0s	17
sysctl_user_max_user_namespaces_no_remediation	Disable the use of user namespaces	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	23.3s	12
service_systemd-coredump_disabled	Disable acquiring, saving, and processing core dum…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	49.4s	13

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
coredump_disable_backtraces	Disable core dump backtraces	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	20.8s	14
coredump_disable_storage	Disable storing core dump	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	19.7s	14
disable_users_coredumps	Disable Core Dumps for All Users	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	16.1s	13
sysctl_kernel_randomize_va_space	Enable Randomized Layout of Virtual Address Space	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	30.1s	15
package_policycoreutils-python-utils_installed	Install policycoreutils-python-utils package	Medium	Remediate	LOW	1	Pass	Approved (4/10)	✓	103.3s	13
service_kdump_disabled	Disable KDump Kernel Crash Analyzer (kdump)	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	41.6s	14
file_permissions_cron_d	Verify Permissions on cron.d	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	24.0s	12
file_permissions_cron_daily	Verify Permissions on cron.daily	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	19.3s	12
file_permissions_cron_hourly	Verify Permissions on cron.hourly	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	16.3s	12
file_permissions_cron_monthly	Verify Permissions on cron.monthly	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	14.1s	11
file_permissions_cron_weekly	Verify Permissions on cron.weekly	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	21.0s	13
package_fapolicyd_installed	Install fapolicyd Package	Medium	Remediate	LOW	3	Pass	Approved (8/10)	✓	44.7s	10
service_fapolicyd_enabled	Enable the File Access Policy Service	Medium	Remediate	LOW	3	Pass	Approved (9/10)	✓	45.3s	12
package_postfix_installed	The Postfix package is installed	Medium	Remediate	LOW	1	Pass	—	—	123.9s	5

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
package_s-nail_installed	The s-nail Package Is Installed	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	77.6s	11
chronyd_or_ntpd_set_maxpoll	Configure Time Service Maxpoll Interval	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	69.2s	21
chronyd_server_directive	Ensure Chrony is only configured with the server d…	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	57.2s	15
disable_host_auth	Disable Host-Based Authentication	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	20.9s	16
sshd_disable_compression	Disable Compression Or Set Compression to delayed	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	29.0s	17
sshd_disable_kerb_auth	Disable Kerberos Authentication	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	20.2s	15
sshd_disable_rhosts	Disable SSH Support for .rhosts Files	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	18.8s	15
sshd_disable_user_known_hosts	Disable SSH Support for User Known Hosts	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	18.4s	15
sshd_do_not_permit_user_env	Do Not Allow SSH Environment Options	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	25.2s	17
sshd_enable_pubkey_auth	Enable Public Key Authentication	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	18.6s	15
sshd_enable_strictmodes	Enable Use of Strict Mode Checking	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	14.7s	13
sshd_print_last_log	Enable SSH Print Last Log	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	18.0s	15
sshd_rekey_limit	Force frequent session key renegotiation	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	23.1s	15
sshd_set_loglevel_verbose	Set SSH Daemon LogLevel to VERBOSE	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	20.1s	15
sshd_x11_use_localhost	Prevent remote hosts from connecting to the proxy …	Medium	Remediate	LOW	2	Pass	Approved (9/10)	✓	18.4s	14

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
sssd_enable_certmap	Enable Certmap in SSSD	Medium	Remediate	LOW	2	Pass	—	—	151.5s	15
sssd_enable_smartcards	Enable Smartcards in SSSD	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	38.4s	21
package_usbguard_installed	Install usbguard Package	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	16.5s	9

Failed Remediation (24)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
aide_build_database	Build and Test AIDE Database	Medium	Remediate	LOW	3	Fail	—	—	129.2s	5
aide_check_audit_tools	Configure AIDE to Verify the Audit Tools	Medium	Remediate	LOW	3	Fail	—	—	172.8s	10
configure_crypto_policy	Configure System Cryptography Policy	High	Remediate	LOW	3	Fail	Approved (8/10)	✓	42.6s	16
enable_authselect	Enable authselect	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✗	3.7s	3
banner_etc_issue	Modify the System Login Banner	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	33.4s	14
accounts_passwords_pam_faillock_deny	Lock Accounts After Failed Password Attempts	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	68.4s	16
accounts_passwords_pam_faillock_deny_root	Configure the root Account for Failed Password Att…	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✗	6.0s	3
accounts_passwords_pam_faillock_dir	Lock Accounts Must Persist	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	56.4s	17
accounts_password_pam_difok	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	26.6s	13

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
accounts_password_pam_minclass	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	45.0s	16
accounts_password_pam_minlen	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	64.7s	17
configure_opensc_card_drivers	Configure opensc Smart Card Drivers	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	33.2s	14
accounts_maximum_age_login_defs	Set Password Maximum Age	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	38.0s	14
accounts_password_set_min_life_existing	Set Existing Passwords Minimum Age	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	40.9s	14
accounts_password_pam_unix_rounds_password_auth	Set number of Password Hashing Rounds - password-a…	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	79.5s	18
accounts_password_pam_unix_rounds_system_auth	Set number of Password Hashing Rounds - system-aut…	Medium	Remediate	LOW	3	Fail	Approved (7/10)	✓	17.3s	12
accounts_logon_fail_delay	Ensure the Logon Failure Delay is Set Correctly in…	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	22.1s	12
file_permission_user_init_files_root	Ensure All User Initialization Files Have Mode 074…	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	31.0s	13
accounts_umask_etc_bashrc	Ensure the Default Bash Umask is Set Correctly	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	33.5s	18
accounts_umask_etc_csh_cshrc	Ensure the Default C Shell Umask is Set Correctly	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	18.8s	13
accounts_umask_etc_profile	Ensure the Default Umask is Set Correctly in /etc/…	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	22.4s	14

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
postfix_client_configure_mail_alias	Configure System to Forward All Mail For The Root …	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	21.2s	15
sshd_disable_gssapi_auth	Disable GSSAPI Authentication	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	23.9s	15
sssd_certificate_verification	Certificate status checking in SSSD	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	24.7s	17

Requires Human Review (6)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
fips_crypto_subpolicy	FIPS Must Use a Supported Subpolicy	Medium	Human Review	MEDIUM	0	—	—	—	2.3s	1
installed_OS_is_vendor_supported	The Installed Operating System Is Vendor Supported	High	Human Review	MEDIUM	0	—	—	—	2.5s	1
account_password_pam_faillock_password_auth	Configure the Use of the pam_faillock.so Module in…	Medium	Human Review	LOW	0	—	—	—	1.0s	1
rsyslog_encrypt_offload_actionsendstreamdrivermode	Ensure Rsyslog Encrypts Off-Loaded Audit Records	Medium	Human Review	LOW	0	—	—	—	1.3s	1
mount_option_boot_nosuid	Add nosuid Option to /boot	Medium	Human Review	MEDIUM	0	—	—	—	1.5s	1
fapolicy_default_deny	Configure Fapolicy Module to Employ a Deny-all, Pe…	Medium	Human Review	MEDIUM	0	—	—	—	1.4s	1

Discarded / Blocked (12)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
enable_dracut_fips_module	Enable Dracut FIPS Module	High	Blocked	CRITICAL	0	—	—	—	1.4s	1
enable_fips_mode	Enable FIPS Mode	High	Blocked	CRITICAL	0	—	—	—	1.1s	1
sysctl_crypto_fips_enabled	Set kernel parameter 'crypto.fips_enabled' to 1	High	Blocked	CRITICAL	0	—	—	—	1.2s	1
partition_for_var_tmp	Ensure /var/tmp Located On Separate Partition	Medium	Blocked	CRITICAL	0	—	—	—	0.0s	0
grub2_init_on_free	The system must booted with init_on_free=1	Medium	Blocked	CRITICAL	0	—	—	—	1.5s	1
grub2_vsyscall_argument	Disable vsyscalls	Medium	Blocked	CRITICAL	0	—	—	—	1.7s	1
grub2_admin_username	Set the Boot Loader Admin Username to a Non-Defaul…	High	Blocked	CRITICAL	0	—	—	—	1.5s	1
grub2_password	Set Boot Loader Password in grub2	High	Blocked	CRITICAL	0	—	—	—	1.3s	1
mount_option_boot_nodev	Add nodev Option to /boot	Medium	Blocked	CRITICAL	0	—	—	—	1.4s	1
mount_option_home_nosuid	Add nosuid Option to /home	Medium	Blocked	CRITICAL	0	—	—	—	1.3s	1
mount_option_nodev_nonroot_local_partitions	Add nodev Option to Non-Root Local Partitions	Medium	Blocked	CRITICAL	0	—	—	—	1.6s	1
grub2_page_poison_argument	Enable page allocator poisoning	Medium	Blocked	CRITICAL	0	—	—	—	1.9s	1

Detailed Finding Reports

package_aide_installed: Install AIDE — SUCCESS

Rule	package_aide_installed
Severity	Medium
Description	The aide package can be installed with the following command: $ sudo dnf install aide
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only installs the AIDE package, which is a standard, non■disruptive operation. It does not modify authentica
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✓
Success	✓
Duration	—
Error	can't concat str to bytes

LLM Metrics

LLM Calls	6

Duration	4.2s
Total Tokens	7,652
Cost	$0.0021
Agents	Triage(1), Remedy(3), Review(1), Qa(1)

aide_build_database: Build and Test AIDE Database — FAILED

Rule	aide_build_database
Severity	Medium
Description	Run the following command to generate a new database: $ sudo /usr/sbin/aide --init By default, the database will be written to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only installs the AIDE package (if missing) and creates/copies the AIDE database in /var/lib/aide. This involv
Estimated Impact	filesystems affected; integrity monitoring; file creation

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗

Duration	—
Error	can't concat str to bytes

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	can't concat str to bytes

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	can't concat str to bytes

LLM Metrics

LLM Calls	5
Duration	3.9s
Total Tokens	8,266
Cost	$0.0019
Agents	Remedy(3), Review(1), Qa(1)

aide_check_audit_tools: Configure AIDE to Verify the Audit Tools — FAILED

Rule	aide_check_audit_tools
Severity	Medium
Description	The operating system file integrity tool must be configured to protect the integrity of the audit tools.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only installs the aide package (if missing) and updates /etc/aide.conf with additional entries for audit tools. Th
Estimated Impact	file integrity monitoring; audit tool configuration

Remediation (3 attempt(s))

Attempt #	1
Commands	rpm -q aide, cp /etc/aide.conf /etc/aide.conf.bak, grep -i -E '^\s*/usr/sbin/auditctl\b' /etc/aide.conf, echo "/usr/sbin/auditctl p+i+n
Scan Passed	✗
Success	✗
Duration	44.6s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗

Duration	—
Error	can't concat str to bytes

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	can't concat str to bytes

LLM Metrics

LLM Calls	10
Duration	9.1s
Total Tokens	54,663
Cost	$0.0111
Agents	Remedy(8), Review(1), Qa(1)

aide_scan_notification: Configure Notification of Post-AIDE Scan Details — SUCCESS

Rule	aide_scan_notification
Severity	Medium
Description	AIDE should notify appropriate personnel of the details of a scan after the scan has been run. If AIDE has already been confi
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only adds a simple cron line to send AIDE scan results via mail. It does not modify authentication, networkin
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	rpm -q aide, sed -i '$ a05 4 * * * root /usr/sbin/aide --check | /bin/mail -s "$(hostname) - AIDE Integrity Check" root@localhost'
Scan Passed	✓
Success	✓
Duration	20.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will install AIDE if missing and add a cron entry to mail scan results, which addresses the finding. However, detectio
Concerns	May create duplicate AIDE cron jobs if an entry exists in another cron directory; grep pattern may match unrelated lines, leadi

QA Result

Safe	✓
Verdict	The plan only installs AIDE (if missing) and appends a cron entry to /etc/crontab to email scan results. This does not modify c
Side Effects	Possible duplicate AIDE cron entries if similar jobs exist in other cron directories; Mail may fail if a local MTA is not configured

Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	8.6s
Total Tokens	36,222
Cost	$0.0078
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

aide_use_fips_hashes: Configure AIDE to Use FIPS 140-2 for Validating Hashes — SUCCESS

Rule	aide_use_fips_hashes
Severity	Medium
Description	By default, the sha512 option is added to the NORMAL ruleset in AIDE. If using a custom ruleset or the sha512 option is miss
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits /etc/aide.conf to ensure sha512 is present and removes weaker hash algorithms, and optionally in
Estimated Impact	integrity monitoring; hash algorithm selection

Remediation (3 attempt(s))

Attempt #	1
Commands	rpm -q aide, cp /etc/aide.conf /etc/aide.conf.bak, sed -i '/^[[:space:]]*[A-Z][A-Za-z_]*[[:space:]]*=/ { /sha512/! s/$/+sha512/ }' /et
Scan Passed	✗
Success	✗
Duration	59.5s
Error	—

Attempt #	2
Commands	rpm -q aide || dnf install -y aide, cp /etc/aide.conf /etc/aide.conf.bak, , cp /etc/aide.conf /etc/aide.conf.bak, sed -i 's/^\s*ALLXTI
Scan Passed	✗
Success	✗
Duration	44.1s
Error	—

Attempt #	3
Commands	install -p /etc/aide.conf /etc/aide.conf.bak, awk '!/^#/ && /^[[:space:]]*[A-Z][A-Za-z_]*[[:space:]]*=/ { line=$0; if (line !~ /sha512/)
Scan Passed	✓
Success	✓
Duration	63.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	8/10
Feedback	The plan resolves the vulnerability by ensuring sha512 is present, removing non■FIPS hashes, backing up the original file, pe
Concerns	The awk script must correctly handle lines with leading whitespace before the comment character '#'.; If a rule line already co

QA Result

Safe	✓
Verdict	The plan correctly ensures sha512 is used and removes non■FIPS hashes in /etc/aide.conf, backs up the original file, perforn
Side Effects	AIDE may report many file changes after the hash algorithm change until the database is rebuilt; The AIDE database may nee
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	10.8s
Total Tokens	86,877
Cost	$0.0148
Agents	Remedy(12), Review(1), Qa(1)

enable_dracut_fips_module: Enable Dracut FIPS Module — DISCARDED

Rule	enable_dracut_fips_module
Severity	High
Description	Red Hat Enterprise Linux 9 has an installation-time kernel flag that can enable FIPS mode. The installer must be booted with
Recommendation	Review and remediate: Enable Dracut FIPS Module
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Enabling FIPS mode on an existing RHEL 9 system requires modifying the kernel boot parameters and dracut configuration, w
Estimated Impact	reboot required; FIPS mode activation; Kernel boot parameter change; Potential system lockout; Bootloader configuration imp

LLM Metrics

LLM Calls	1
Duration	1.4s
Total Tokens	1,318
Cost	$0.0006
Agents	Triage(1)

enable_fips_mode: Enable FIPS Mode — DISCARDED

Rule	enable_fips_mode
Severity	High
Description	Red Hat Enterprise Linux 9 has an installation-time kernel flag that can enable FIPS mode. The installer must be booted with
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! (["${container:-}" == "bwrap-osbuild"]) && rpm
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗

Risk Level	CRITICAL
Reason	Enabling FIPS mode requires adding the fips=1 kernel argument and updating the cryptographic policy, which cannot be appl
Estimated Impact	reboot required; kernel_parameter_change; cryptographic_policy; system_boot; potential_lockout

LLM Metrics

LLM Calls	1
Duration	1.1s
Total Tokens	1,343
Cost	$0.0006
Agents	Triage(1)

fips_crypto_subpolicy: FIPS Must Use a Supported Subpolicy — REQUIRES_HUMAN_REVIEW

Rule	fips_crypto_subpolicy
Severity	Medium
Description	Sub-policies can be used to modify existing crypto policies. Some sub-policies such as NO-ENFORCE-EMS reduce the secu
Recommendation	Review and remediate: FIPS Must Use a Supported Subpolicy
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	Changing the FIPS subpolicy modifies system-wide cryptographic settings. Selecting an unsupported subpolicy can break TL
Estimated Impact	authentication/authorization affected; networking affected; crypto policy alteration; potential service disruption; possible SSH/

LLM Metrics

LLM Calls	1
Duration	2.3s
Total Tokens	1,291
Cost	$0.0006
Agents	Triage(1)

fips_custom_stig_sub_policy: Implement STIG Sub Crypto Policy — SUCCESS

Rule	fips_custom_stig_sub_policy
Severity	Medium
Description	Create a custom cryptographic policy to follow the guidance from DISA.
Recommendation	Remediation script: cat << 'EOF' > /etc/crypto-policies/policies/modules/STIG.pmod cipher@SSH=AES-256-GCM AES-256-C
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only creates a custom crypto policy file and runs update-crypto-policies, which does not modify bootloader, p
Estimated Impact	authentication/authorization affected; filesystems affected; Potential SSH compatibility issues if client does not support select

Remediation (1 attempt(s))

Attempt #	1
Commands	update-crypto-policies --set FIPS:STIG

Scan Passed	✓
Success	✓
Duration	24.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly creates the custom crypto policy module and applies it with update-crypto-policies, which should address th
Concerns	The plan does not restart the SSH service, so new ciphers may not take effect until a restart or new session.; No backup of an

QA Result

Safe	✓
Verdict	The plan correctly creates a STIG crypto policy module and applies it with update-crypto-policies, using widely supported SSH
Side Effects	SSH daemon may need to be reloaded or restarted for new ciphers to take effect.; Other services that rely on system crypto p
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	8.7s
Total Tokens	28,420
Cost	$0.0069
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

sysctl_crypto_fips_enabled: Set kernel parameter 'crypto.fips_enabled' to 1 — *DISCARDED*

Rule	sysctl_crypto_fips_enabled
Severity	High
Description	System running in FIPS mode is indicated by kernel parameter 'crypto.fips_enabled'. This parameter should be set to 1 in FIP
Recommendation	Review and remediate: Set kernel parameter 'crypto.fips_enabled' to 1
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Enabling FIPS mode requires adding the fips=1 kernel boot parameter, which cannot be applied safely on an already installed
Estimated Impact	reboot required; FIPS mode activation; kernel boot parameter modification; potential system boot failure

LLM Metrics

LLM Calls	1
Duration	1.2s
Total Tokens	1,133
Cost	$0.0005
Agents	Triage(1)

configure_crypto_policy: Configure System Cryptography Policy — *FAILED*

Rule	configure_crypto_policy

Severity	High
Description	To configure the system cryptography policy to use ciphers only from the policy, run the following command: $ sudo update-c
Recommendation	Remediation script: var_system_crypto_policy='' stderr_of_call=$(update-crypto-policies --set ${var_system_crypto_policy} 2>
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only runs the standard update-crypto-policies command to set the system's crypto policy. This is a documen
Estimated Impact	networking affected; service_disruption; compatibility_issues

Remediation (3 attempt(s))

Attempt #	1
Commands	update-crypto-policies --set DEFAULT
Scan Passed	✗
Success	✗
Duration	14.7s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	4.9s

Error	—

Attempt #	3
Commands	which update-crypto-policies, update-crypto-policies --set FUTURE, systemctl is-active sshd, systemctl restart sshd, systemct
Scan Passed	✗
Success	✗
Duration	42.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly checks the current policy, ensures the crypto-policies package is installed, applies the FUTURE policy whe
Concerns	The plan unconditionally selects the FUTURE policy, which may be more restrictive than required by organizational compliance

QA Result

Safe	✓
Verdict	The plan follows the proper procedure for updating the system crypto policy using the supported tool, checks the current setti
Side Effects	Potential temporary loss of SSH connections during service restart; Older SSH clients may be unable to reconnect if they do n
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	9.1s

Total Tokens	54,177
Cost	$0.0085
Agents	Remedy(14), Review(1), Qa(1)

installed_OS_is_vendor_supported: The Installed Operating System Is Vendor Supported — REQUIRES_HUMAN_REVIEW

Rule	installed_OS_is_vendor_supported
Severity	High
Description	The installed operating system must be maintained by a vendor. Red Hat Enterprise Linux is supported by Red Hat, Inc. As th
Recommendation	Review and remediate: The Installed Operating System Is Vendor Supported
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	Remediation may involve upgrading or replacing the operating system, which is a major change that can affect services and r
Estimated Impact	reboot required; OS vendor support status; potential OS upgrade; service disruption; need for maintenance window

LLM Metrics

LLM Calls	1
Duration	2.5s
Total Tokens	1,482
Cost	$0.0007
Agents	Triage(1)

partition_for_var_tmp: Ensure /var/tmp Located On Separate Partition — DISCARDED

Rule	partition_for_var_tmp
Severity	Medium
Description	The /var/tmp directory is a world-writable directory used for temporary file storage. Ensure it has its own partition or logical vo
Recommendation	Remediation script: part /var/tmp
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Filesystem/partition/mount-option changes can break boot or services and should not be auto-remediated.
Estimated Impact	reboot required; filesystems affected; filesystems/partitioning; service disruption risk

package_gnutls-utils_installed: Ensure gnutls-utils is installed — SUCCESS

Rule	package_gnutls-utils_installed
Severity	Medium
Description	The gnutls-utils package can be installed with the following command: $ sudo dnf install gnutls-utils
Recommendation	Remediation script: if ! rpm -q --quiet "gnutls-utils" ; then dnf install -y "gnutls-utils" fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗

Risk Level	LOW
Reason	Installing the gnutls-utils package is a straightforward, low■risk operation that does not modify authentication, networking, or
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✓
Success	✓
Duration	—
Error	can't concat str to bytes

LLM Metrics

LLM Calls	5
Duration	3.8s
Total Tokens	5,267
Cost	$0.0015
Agents	Triage(1), Remedy(2), Review(1), Qa(1)

package_nss-tools_installed: Ensure nss-tools is installed — SUCCESS

Rule	package_nss-tools_installed
Severity	Medium
Description	The nss-tools package can be installed with the following command: $ sudo dnf install nss-tools
Recommendation	Remediation script: if ! rpm -q --quiet "nss-tools" ; then dnf install -y "nss-tools" fi

Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the nss-tools package is a straightforward, non-disruptive operation that does not modify authentication, networking
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	rpm -q --quiet nss-tools, dnf install -y nss-tools, rpm -q nss-tools
Scan Passed	✓
Success	✓
Duration	74.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	—
Concerns	—

QA Result

Safe	✓

Verdict	Installing the nss-tools package is a standard, non■intrusive operation that only adds user■space utilities. It does not modify
Side Effects	Adds new command■line utilities (e.g., certutil, pk12util) to the system; Slightly increases the installed software footprint
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	7.0s
Total Tokens	26,353
Cost	$0.0055
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

package_subscription-manager_installed: Install subscription-manager Package — SUCCESS

Rule	package_subscription-manager_installed
Severity	Medium
Description	The subscription-manager package can be installed with the following command: $ sudo dnf install subscription-manager
Recommendation	Remediation script: if ! rpm -q --quiet "subscription-manager" ; then dnf install -y "subscription-manager" fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the subscription-manager package is a straightforward, low■impact operation that does not modify authentication, r

Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✓
Success	✓
Duration	—
Error	can't concat str to bytes

LLM Metrics

LLM Calls	5
Duration	3.6s
Total Tokens	6,003
Cost	$0.0019
Agents	Triage(1), Remedy(2), Review(1), Qa(1)

ensure_gpgcheck_local_packages: Ensure gpgcheck Enabled for Local Packages — SUCCESS

Rule	ensure_gpgcheck_local_packages
Severity	High
Description	dnf should be configured to verify the signature(s) of local packages prior to installation. To configure dnf to verify signatures
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q dnf; then # Strip any search characte
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling gpgcheck only modifies a dnf configuration key, does not affect authentication, networking, or critical services. The c
Estimated Impact	filesystems affected

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/dnf/dnf.conf /etc/dnf/dnf.conf.bak, grep -q '^#\sslocallocalpkg_gpgpg"etc/dnf/dnf.conf, grep -q '^#\?\s*localpkg_gpgche
Scan Passed	✓
Success	✓
Duration	25.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly targets the required configuration key and will set localpkg_gpgcheck to 1, addressing the vulnerability. Th
Concerns	The sed command as written adds the line after the [main] section unconditionally, which could create duplicate entries if the

QA Result

Safe	✓
Verdict	The plan only modifies /etc/dnf/dnf.conf to enable local package signature checking. This does not affect running services or a
Side Effects	Possible duplicate 'localpkg_gpgcheck' line in dnf.conf if the grep guard fails

Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	9.4s
Total Tokens	35,392
Cost	$0.0076
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

enable_authselect: Enable authselect — FAILED

Rule	enable_authselect
Severity	Medium
Description	Configure user authentication setup to use the authselect tool. If authselect profile is selected, the rule will enable the profile.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_authselect_pro
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling authselect is a standard PAM configuration change that follows STIG hardening patterns. The remediation script inc
Estimated Impact	authentication/authorization affected; Potential authentication lockout if profile is misconfigured; Service restart may affect act

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	3.6s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	4.1s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	3.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	8/10
Feedback	The plan correctly installs authselect if missing, backs up PAM files, verifies the desired profile exists, and selects it using aut
Concerns	Hard■coding the 'sssd' profile may not match the system's intended authentication method.; The plan does not verify that the

QA Result

Safe	✗
Verdict	The plan forces the 'sssd' authselect profile without first confirming that the sssd package and its configuration are present an
Side Effects	Potential loss of local and SSH authentication if the sssd profile is incompatible; Failure to start the sssd service if the packag
Regression	✗
Recommendation	Investigate

LLM Metrics

LLM Calls	3
Duration	3.6s
Total Tokens	6,255
Cost	$0.0021
Agents	Remedy(1), Review(1), Qa(1)

banner_etc_issue: Modify the System Login Banner — FAILED

Rule	banner_etc_issue
Severity	Medium
Description	To configure the system login banner edit /etc/issue. Replace the default text with a message compliant with the local site pol
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then login_banner_text=
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits /etc/issue, a plain text file used for display at login. No services are restarted, no authentication me
Estimated Impact	filesystems affected

Remediation (3 attempt(s))

Attempt #	1
Commands	cp /etc/issue /etc/issue.bak, chmod 644 /etc/issue, chown root:root /etc/issue
Scan Passed	✗
Success	✗
Duration	29.9s
Error	—

Attempt #	2
Commands	cat /etc/issue > /etc/issue.bak, cat /etc/issue.net > /etc/issue.net.bak
Scan Passed	✗
Success	✗
Duration	42.1s
Error	—

Attempt #	3
Commands	mv /etc/issue /etc/issue.bak, mv -f /etc/issue.net /etc/issue.net.bak
Scan Passed	✗

Success	✗
Duration	33.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will replace /etc/issue and /etc/issue.net with the required DoD banner and includes a verification step, addressing th
Concerns	Backup using mv removes the original file before the new one is written, risking loss if the write fails.; The plan does not explic

QA Result

Safe	✓
Verdict	The plan only replaces the login banner files with the required text, preserving permissions via mv and creating new files as re
Side Effects	Potential loss of original /etc/issue or /etc/issue.net if the heredoc write fails after mv; File permissions may default to system u
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	12.2s
Total Tokens	62,990
Cost	$0.0117
Agents	Remedy(12), Review(1), Qa(1)

account_password_pam_faillock_password_auth: Configure the Use of the pam_faillock.so Module in the /etc/pam.d/password-auth … — *REQUIRES_HUMAN_REVIEW*

Rule	account_password_pam_faillock_password_auth
Severity	Medium
Description	The pam_faillock.so module must be loaded in preauth in /etc/pam.d/password-auth.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if [-f /usr/bin/auths
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The remediation only modifies PAM configuration to load pam_faillock.so in the preauth stack, which is a standard STIG hard
Estimated Impact	authentication/authorization affected; filesystems affected; Potential authentication lockout if syntax error; Impact on SSH and

LLM Metrics

LLM Calls	1
Duration	1.0s
Total Tokens	1,201
Cost	$0.0005
Agents	Triage(1)

account_password_pam_faillock_system_auth: Configure the Use of the pam_faillock.so Module in the /etc/pam.d/system-auth Fi… — *SUCCESS*

Rule	account_password_pam_faillock_system_auth

Severity	Medium
Description	The pam_faillock.so module must be loaded in preauth in /etc/pam.d/system-auth.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if [-f /usr/bin/auths
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The finding requires adding the pam_faillock.so module to the preauth stack in the system-auth PAM configuration. This is a s
Estimated Impact	authentication/authorization affected; filesystems affected; Potential lockout if pam_faillock parameters are mis■configured; A

Remediation (1 attempt(s))

Attempt #	1
Commands	authselect current, authselect list, authselect select sssd, authselect select sssd --force, authselect enable-feature with-failloc
Scan Passed	✓
Success	✓
Duration	37.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly uses authselect to enable the with■faillock feature and applies the changes, which will add pam_faillock.so

Concerns	The plan does not explicitly run `authselect check` before enabling the feature, which could miss a corrupted or non■standard

QA Result

Safe	✓
Verdict	The plan uses the standard authselect workflow to enable the with■faillock feature, which is the recommended method on Ro
Side Effects	Introduction of account lockout after repeated failed login attempts; Potential temporary lockout for users who exceed the allo
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	10.8s
Total Tokens	47,581
Cost	$0.0101
Agents	Triage(1), Remedy(13), Review(1), Qa(1)

accounts_passwords_pam_faillock_deny: Lock Accounts After Failed Password Attempts — FAILED

Rule	accounts_passwords_pam_faillock_deny
Severity	Medium
Description	This rule configures the system to lock out accounts after a number of incorrect login attempts using pam_faillock.so. pam_fa
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies PAM configuration via authselect, a standard and reversible operation. It does not involve kern
Estimated Impact	authentication/authorization affected; filesystems affected; potential authentication lockout; misconfiguration of PAM entries

Remediation (3 attempt(s))

Attempt #	1
Commands	cp -p /etc/security/faillock.conf /etc/security/faillock.conf.bak, sed -i -e 's/^#\s*\(deny\s*=\s*\).*/\1 5/' -e '/^\s*deny\s*=/!a\deny =
Scan Passed	✗
Success	✗
Duration	33.0s
Error	—

Attempt #	2
Commands	command -v authselect, cp /etc/security/faillock.conf /etc/security/faillock.conf.bak, authselect current-profile, authselect curre
Scan Passed	✗
Success	✗
Duration	47.8s
Error	—

Attempt #	3
Commands	ls -l /etc/authselect, authselect create-profile custom-profile -b, authselect list, grep -E 'pam_faillock.so' -n /etc/pam.d/system-
Scan Passed	✗
Success	✗

Duration	68.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly enables the with■faillock feature via authselect and sets the deny count to 5, which satisfies the OpenSCA
Concerns	No verification step to confirm that pam_faillock.so lines are present in /etc/pam.d/system-auth and /etc/pam.d/password-auth

QA Result

Safe	✓
Verdict	The plan uses authselect to enable the with■faillock feature and sets a reasonable deny count. It creates a custom profile, ba
Side Effects	Temporary change in authentication behavior until the new profile is applied; Potential lockout after 5 failed login attempts, wh
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	14.5s
Total Tokens	75,593
Cost	$0.0147
Agents	Remedy(14), Review(1), Qa(1)

accounts_passwords_pam_faillock_deny_root: Configure the root Account for Failed Password Attempts — FAILED

Rule	accounts_passwords_pam_faillock_deny_root
Severity	Medium
Description	This rule configures the system to lock out the root account after a number of incorrect login attempts using pam_faillock.so. p
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves a standard PAM configuration change using authselect, which is the recommended method for appl
Estimated Impact	authentication/authorization affected; Potential lockout if pam_faillock settings are misconfigured; Incorrect authselect profile c

Remediation (3 attempt(s))

Attempt #	1
Commands	which authselect, authselect current-profile, authselect current, authselect apply-changes -b, sed -i 's/pam_faillock.so preauth
Scan Passed	✗
Success	✗
Duration	69.5s
Error	—

Attempt #	2
Commands	authselect current, authselect check, cp /etc/pam.d/system-auth /root/system-auth.bak, cp /etc/pam.d/password-auth /root/pa
Scan Passed	✗
Success	✗

Duration	77.0s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	6.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan adds the even_deny_root argument to pam_faillock and configures deny/unlock_time, which will lock the root accou
Concerns	Manual sed edits on /etc/pam.d/system-auth and password-auth can conflict with the authselect-managed PAM configuration

QA Result

Safe	✗
Verdict	The plan edits PAM files directly with sed, bypassing authselect management. This can introduce syntax errors or break the a
Side Effects	Potential SSH login failure; Root account lockout; General authentication failures for local and remote logins
Regression	✗
Recommendation	Investigate

LLM Metrics

LLM Calls	3

Duration	6.0s
Total Tokens	8,710
Cost	$0.0036
Agents	Remedy(1), Review(1), Qa(1)

accounts_passwords_pam_faillock_dir: Lock Accounts Must Persist — FAILED

Rule	accounts_passwords_pam_faillock_dir
Severity	Medium
Description	This rule ensures that the system lock out accounts using pam_faillock.so persist after system reboot. From "pam_faillock" m
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies PAM configuration (authselect or PAM files) to set a persistent tally directory for pam_faillock,
Estimated Impact	authentication/authorization affected; pam_configuration; auth_policy

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗

Duration	4.0s
Error	—

Attempt #	2
Commands	authselect --version, which authselect, authselect current -r, authselect create-profile custom_hardening -b, authselect list
Scan Passed	✗
Success	✗
Duration	89.5s
Error	—

Attempt #	3
Commands	cp /etc/security/faillock.conf /etc/security/faillock.conf.bak, sed -i '$a dir = /var/log/faillock' /etc/security/faillock.conf, mkdir -p /v
Scan Passed	✗
Success	✗
Duration	56.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set a persistent tally directory for pam_faillock and create the required directory with proper permissions, which r
Concerns	The plan does not run `authselect enable-feature with-faillock` to guarantee the pam_faillock module is present in the active p

QA Result

Safe	✓

Verdict	The plan only modifies /etc/security/faillock.conf to set a persistent tally directory and creates that directory with proper owner
Side Effects	Possible SELinux context mismatch for /var/log/faillock if not set to var_log_t; If pam_faillock is not enabled, the change has r
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	17
Duration	10.2s
Total Tokens	73,771
Cost	$0.0098
Agents	Remedy(15), Review(1), Qa(1)

accounts_passwords_pam_faillock_interval: Set Interval For Counting Failed Password Attempts — SUCCESS

Rule	accounts_passwords_pam_faillock_interval
Severity	Medium
Description	Utilizing pam_faillock.so, the fail_interval directive configures the system to lock out an account after a number of incorrect log
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The fix only modifies PAM configuration via authselect to set the fail_interval for pam_faillock. This is a standard STIG harder

Estimated Impact	authentication/authorization affected; authentication; pam configuration; policy enforcement

Remediation (2 attempt(s))

Attempt #	1
Commands	sed -i 's/^\s*#\?\s*fail_interval.*/fail_interval = 900/' /etc/security/faillock.conf, grep -E '^\s*fail_interval' /etc/security/faillock.con
Scan Passed	✗
Success	✗
Duration	29.1s
Error	—

Attempt #	2
Commands	authselect current, authselect check, authselect select sssd withfaillock --force, authselect select sssd with-faillock --force, au
Scan Passed	✓
Success	✓
Duration	37.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly enables the faillock feature via authselect and ensures the required fail_interval is present. The sed comma
Concerns	Manual edit of /etc/security/faillock.conf could be overwritten by future authselect profile changes.; authselect apply-changes

QA Result

Safe	✓

Verdict	The plan uses the recommended authselect mechanism to enable the faillock feature and then ensures the required fail_inter
Side Effects	If the authselect profile is corrupted or not properly selected, the enable■feature step could fail and leave PAM in an inconsis
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	11.4s
Total Tokens	57,984
Cost	$0.0109
Agents	Remedy(13), Review(1), Qa(1)

accounts_passwords_pam_faillock_unlock_time: Set Lockout Time for Failed Password Attempts — SUCCESS

Rule	accounts_passwords_pam_faillock_unlock_time
Severity	Medium
Description	This rule configures the system to lock out accounts during a specified time period after a number of incorrect login attempts u
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The finding requires updating PAM configuration (faillock) which is a standard STIG hardening step. The remediation can be p

Estimated Impact	authentication/authorization affected; filesystems affected; Potential lockout if unlock_time is set to 0 or mis■typed; Authentic

Remediation (1 attempt(s))

Attempt #	1
Commands	which authselect, authselect current, sed -i -r 's/^#?\s*unlock_time\s*=.*$/unlock_time = 900/' /etc/security/faillock.conf
Scan Passed	✓
Success	✓
Duration	27.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set unlock_time=900 in /etc/security/faillock.conf, which satisfies the requirement. However, it does not ensure th
Concerns	The plan does not enable the faillock feature in the authselect profile, which may be required for the pam_faillock module to b

QA Result

Safe	✓
Verdict	Modifying /etc/security/faillock.conf to set unlock_time=900 is a standard, non■intrusive configuration change. It does not alte
Side Effects	Potential loss of original file permissions or SELinux context if not preserved during write; If the file already contains multiple u
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14

Duration	10.4s
Total Tokens	36,357
Cost	$0.0073
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

accounts_password_pam_dcredit: Ensure PAM Enforces Password Requirements - Minimum Digit Characters — SUCCESS

Rule	accounts_password_pam_dcredit
Severity	Medium
Description	The pam_pwquality module's dcredit parameter controls requirements for usage of digits in a password. When set to a negati
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The finding requires modifying the PAM pwquality dcredit setting, which is a standard authentication configuration change. It c
Estimated Impact	authentication/authorization affected; password policy; authentication

Remediation (1 attempt(s))

Attempt #	1
Commands	cp -a /etc/security/pwquality.conf /etc/security/pwquality.conf.bak, sed -i 's/^#\?\s*dcredit\s*=\s*[^#]*/dcredit = -1/' /etc/security/
Scan Passed	✓
Success	✓

Duration	28.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set dcredit = -1 in /etc/security/pwquality.conf, which addresses the requirement. However it does not consider p
Concerns	No backup of original configuration file before modification; Only modifies /etc/security/pwquality.conf and may miss settings i

QA Result

Safe	✓
Verdict	Setting dcredit = -1 only tightens password complexity by requiring at least one digit. It does not alter PAM module loading or
Side Effects	Potential duplicate dcredit lines if the file already contains multiple entries; No backup of the original configuration file before r
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	11.1s
Total Tokens	50,931
Cost	$0.0097
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

accounts_password_pam_dictcheck: Ensure PAM Enforces Password Requirements - Prevent the Use of Dictionary Words — SUCCESS

Rule	accounts_password_pam_dictcheck
Severity	Medium
Description	The pam_pwquality module's dictcheck check if passwords contains dictionary words. When dictcheck is set to 1 passwords
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits a PAM password quality configuration file to disable the dictcheck option. This is a standard STIG
Estimated Impact	authentication/authorization affected; filesystems affected; reduced password strength due to disabled dictionary check

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	5.0s
Error	—

Attempt #	2
Commands	ls /etc/security/pwquality.conf.d/*.conf 2>/dev/null || true, cp /etc/security/pwquality.conf /etc/security/pwquality.conf.bak, sed -
Scan Passed	✓
Success	✓

Duration	28.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan correctly aims to set dictcheck=1, which will enable dictionary word checking in pam_pwquality. It includes backup a
Concerns	Only /etc/security/pwquality.conf is edited; configuration files in /etc/security/pwquality.conf.d/ are ignored and could override t

QA Result

Safe	✓
Verdict	The plan only modifies the pam_pwquality configuration to enable dictionary word checking. This is a standard security harde
Side Effects	Potential duplicate dictcheck entries if an uncommented line already exists; Only /etc/security/pwquality.conf is edited; setting
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	11.0s
Total Tokens	50,059
Cost	$0.0102
Agents	Remedy(11), Review(1), Qa(1)

accounts_password_pam_difok: Ensure PAM Enforces Password Requirements - Minimum Different Characters — FAILED

Rule	accounts_password_pam_difok
Severity	Medium
Description	The pam_pwquality module's difok parameter sets the number of characters in a password that must not be present in and ol
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing the difok parameter is a standard PAM password policy adjustment. It does not affect authentication mechanisms b
Estimated Impact	authentication/authorization affected; filesystems affected; password_policy

Remediation (3 attempt(s))

Attempt #	1
Commands	ls -1 /etc/security/pwquality.conf.d/*.conf 2>/dev/null || true, sed -i 's/^#\s*difok\s*=.*/difok = 3/' /etc/security/pwquality.conf
Scan Passed	✗
Success	✗
Duration	23.4s
Error	—

Attempt #	2
Commands	cp -a /etc/security/pwquality.conf.d /etc/security/pwquality.conf.d.bak, sed -i '/^[#[:space:]]*difok[[:space:]]*=/d' /etc/security/pw
Scan Passed	✗
Success	✗

Duration	33.8s
Error	—

Attempt #	3
Commands	cp /etc/pam.d/system-auth /etc/pam.d/system-auth.bak, sed -i 's/difok=[^[:space:]]*//g' /etc/pam.d/system-auth, sed -i 's/\(pam
Scan Passed	✗
Success	✗
Duration	26.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set difok=3 in the pam_pwquality invocation within /etc/pam.d/system-auth, removing any conflicting settings, wh
Concerns	Hard■coded difok value of 3 may not match the organization's password policy.; Only the PAM file is backed up; pwquality.co

QA Result

Safe	✓
Verdict	The plan correctly modifies the PAM system-auth file to enforce the required difok value, backs up the original file, and uses s
Side Effects	If the sed commands incorrectly edit the pam_pwquality line (e.g., syntax error), authentication for services using system-auth
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13

Duration	10.1s
Total Tokens	53,933
Cost	$0.0117
Agents	Remedy(11), Review(1), Qa(1)

accounts_password_pam_enforce_root: Ensure PAM Enforces Password Requirements - Enforce for root User — SUCCESS

Rule	accounts_password_pam_enforce_root
Severity	Medium
Description	The pam_pwquality module's enforce_for_root parameter controls requirements for enforcing password complexity for the roo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only adds the enforce_for_root setting to /etc/security/pwquality.conf, a standard PAM password policy chan
Estimated Impact	authentication/authorization affected; filesystems affected; potential future root password complexity requirement

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗

Duration	2.8s
Error	—

Attempt #	2
Commands	test -f /etc/security/pwquality.conf || touch /etc/security/pwquality.conf, cp /etc/security/pwquality.conf /etc/security/pwquality.c
Scan Passed	✓
Success	✓
Duration	35.2s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan adds the required 'enforce_for_root' setting and removes any existing entries, which will address the vulnerability. H
Concerns	Sed command syntax is incorrect (missing '/' delimiters).; No backup of /etc/security/pwquality.conf is made before editing.; Th

QA Result

Safe	✓
Verdict	The plan only modifies /etc/security/pwquality.conf to add the enforce_for_root setting, which does not affect core services or
Side Effects	Potential failure to apply the setting if sed syntax is incorrect; No backup of the original file, so a mistaken edit could be hard t
Regression	✗
Recommendation	Investigate

LLM Metrics

LLM Calls	15

Duration	11.5s
Total Tokens	52,961
Cost	$0.0093
Agents	Remedy(13), Review(1), Qa(1)

accounts_password_pam_lcredit: Ensure PAM Enforces Password Requirements - Minimum Lowercase Characters — SUCCESS

Rule	accounts_password_pam_lcredit
Severity	Medium
Description	The pam_pwquality module's lcredit parameter controls requirements for usage of lowercase letters in a password. When set
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits a PAM password quality configuration parameter (lcredit) to enforce at least one lowercase charac
Estimated Impact	authentication/authorization affected; password policy misconfiguration; potential user lockout if lcredit set incorrectly

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/security/pwquality.conf /etc/security/pwquality.conf.bak, sed -i 's/^#\?\s*lcredit\s*=.*/lcredit = -1/' /etc/security/pwquality
Scan Passed	✓
Success	✓

Duration	24.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly sets lcredit to -1, which enforces at least one lowercase character in passwords. It will address the vulnerabi
Concerns	The plan only modifies /etc/security/pwquality.conf and does not consider possible overrides in /etc/security/pwquality.conf.d/*

QA Result

Safe	✓
Verdict	Setting lcredit = -1 in /etc/security/pwquality.conf correctly enforces a lowercase character requirement without affecting login
Side Effects	Does not account for possible overrides in /etc/security/pwquality.conf.d/*.conf; No backup of original file is created, risking los
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	10.7s
Total Tokens	37,532
Cost	$0.0073
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

accounts_password_pam_maxclassrepeat: Ensure PAM Enforces Password Requirements - Maximum Consecutive Repeating Charac… — SUCCESS

Rule	accounts_password_pam_maxclassrepeat
Severity	Medium
Description	The pam_pwquality module's maxclassrepeat parameter controls requirements for consecutive repeating characters from the
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The finding requires editing a PAM password quality configuration parameter (maxclassrepeat) in /etc/security/pwquality.conf
Estimated Impact	authentication/authorization affected; password_policy; pam_configuration

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/security/pwquality.conf /etc/security/pwquality.conf.bak, grep -q '^#\? *maxclassrepeat' /etc/security/pwquality.conf, se
Scan Passed	✓
Success	✓
Duration	40.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10

Feedback	The plan will set maxclassrepeat to 2 in /etc/security/pwquality.conf, which satisfies the requirement. However, it does not cor
Concerns	If a .conf.d file defines maxclassrepeat, it may override the value set in pwquality.conf.; No backup of the original configuratio

QA Result

Safe	✓
Verdict	The plan only modifies the pwquality configuration to enforce a maxclassrepeat of 2, which is a standard hardening step. It do
Side Effects	Password change operations may be rejected if the new password contains more than two consecutive characters from the s
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	17
Duration	11.6s
Total Tokens	56,060
Cost	$0.0118
Agents	Triage(1), Remedy(14), Review(1), Qa(1)

accounts_password_pam_maxrepeat: Set Password Maximum Consecutive Repeating Characters — SUCCESS

Rule	accounts_password_pam_maxrepeat
Severity	Medium
Description	The pam_pwquality module's maxrepeat parameter controls requirements for consecutive repeating characters. When set to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The finding concerns a PAM password quality setting (maxrepeat) which is a standard STIG hardening change. Adjusting this
Estimated Impact	authentication/authorization affected; Potential password policy lockout if maxrepeat is set too low; Pam configuration change

Remediation (1 attempt(s))

Attempt #	1
Commands	grep -q '^#\?\s*maxrepeat' /etc/security/pwquality.conf, sed -i 's/^#\?\s*maxrepeat\s*=.*/maxrepeat = 2/' /etc/security/pwquality
Scan Passed	✓
Success	✓
Duration	22.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set maxrepeat to 2 and address the vulnerability, but it can be hardened by adding a backup, handling comment
Concerns	The plan only edits /etc/security/pwquality.conf and may miss overrides in /etc/security/pwquality.conf.d/*.conf.

QA Result

Safe	✓
Verdict	The plan only modifies the pwquality configuration to enforce a maxrepeat of 2, which is a standard hardening measure. It do
Side Effects	Password change operations may be rejected if the new password contains more than two consecutive identical characters.;

Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	8.9s
Total Tokens	39,270
Cost	$0.0089
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

accounts_password_pam_minclass: Ensure PAM Enforces Password Requirements - Minimum Different Categories — FAILED

Rule	accounts_password_pam_minclass
Severity	Medium
Description	The pam_pwquality module's minclass parameter controls requirements for usage of different character classes, or types, of c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits the pam_pwquality configuration to set the minclass parameter, a standard PAM hardening step. I
Estimated Impact	authentication/authorization affected; filesystems affected; Potential password lockout if the parameter is set incorrectly; Incor

Remediation (3 attempt(s))

Attempt #	1
Commands	ls /etc/security/pwquality.conf.d/*.conf, cp /etc/security/pwquality.conf /etc/security/pwquality.conf.bak, sed -i -E 's/^\s*#\s*minc
Scan Passed	✗
Success	✗
Duration	30.9s
Error	—

Attempt #	2
Commands	find /etc/security/pwquality.conf.d -maxdepth 1 -type f -name '*.conf', cp /etc/security/pwquality.conf /etc/security/pwquality.co
Scan Passed	✗
Success	✗
Duration	31.0s
Error	—

Attempt #	3
Commands	printf '%s\n' /etc/security/pwquality.conf.d/*.conf, stat -c '%U %G %a' /etc/security/pwquality.conf, sed -i -E 's/^(\s*password\s-
Scan Passed	✗
Success	✗
Duration	45.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	8/10
Feedback	The plan will set the required minclass=3 by adding a dedicated fragment in /etc/security/pwquality.conf.d/, which will be read
Concerns	The method for detecting an existing minclass entry may miss lines that are commented out or have leading whitespace.; No

QA Result

Safe	✓
Verdict	Creating a dedicated pwquality.conf.d fragment with minclass=3 is the standard way to enforce password complexity on Rock
Side Effects	Password change attempts with passwords not meeting the new class requirement will be rejected.; If an existing minclass se
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	13.7s
Total Tokens	79,239
Cost	$0.0135
Agents	Remedy(14), Review(1), Qa(1)

accounts_password_pam_minlen: Ensure PAM Enforces Password Requirements - Minimum Length — FAILED

Rule	accounts_password_pam_minlen
Severity	Medium
Description	The pam_pwquality module's minlen parameter controls requirements for minimum characters required in a password. Add m
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adjusting the pam_pwquality minlen parameter is a standard PAM configuration change that does not affect system boot or c
Estimated Impact	authentication/authorization affected; auth; pam

Remediation (3 attempt(s))

Attempt #	1
Commands	grep -q '^#* *minlen' /etc/security/pwquality.conf, cp /etc/security/pwquality.conf /etc/security/pwquality.conf.bak, sed -i 's/^\s*#
Scan Passed	✗
Success	✗
Duration	32.1s
Error	—

Attempt #	2
Commands	ls -1 /etc/security/pwquality.conf.d/*.conf, grep -E '^\s*#?\s*minlen\b' /etc/security/pwquality.conf /etc/security/pwquality.conf.d
Scan Passed	✗
Success	✗
Duration	24.0s
Error	—

Attempt #	3
Commands	authselect current-profile, authselect current, authselect create-profile hardening -b sssd, ls -l /etc/authselect/custom/hardenin
Scan Passed	✗

Success	✗
Duration	64.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set the required minimum password length by adding minlen=12 to the pam_pwquality.so lines via a custom aut
Concerns	No backup of the original PAM files is created before in■place editing.; The sed command may add a duplicate minlen param

QA Result

Safe	✓
Verdict	The plan uses authselect to create a custom profile and only adds the minlen=12 parameter to the existing pam_pwquality.so
Side Effects	Potential duplicate minlen entries if one already exists, which is harmless but may clutter config.; No automatic backup of orig
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	17
Duration	10.6s
Total Tokens	88,219
Cost	$0.0141
Agents	Remedy(15), Review(1), Qa(1)

accounts_password_pam_ocredit: Ensure PAM Enforces Password Requirements - Minimum Special Characters — SUCCESS

Rule	accounts_password_pam_ocredit
Severity	Medium
Description	The pam_pwquality module's ocredit= parameter controls requirements for usage of special (or "other") characters in a passw
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The finding requires a simple PAM configuration change (setting ocredit in pwquality.conf). This is a standard STIG hardening
Estimated Impact	authentication/authorization affected; password policy; pam configuration

Remediation (1 attempt(s))

Attempt #	1
Commands	sed -i 's/^#\? *ocredit *= *.*/ocredit = -1/' /etc/security/pwquality.conf, grep -q '^\s*ocredit' /etc/security/pwquality.conf || echo 'o
Scan Passed	✓
Success	✓
Duration	27.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	8/10
Feedback	The plan will correctly set ocredit to -1, satisfying the requirement. Adding a backup and handling leading whitespace in the g
Concerns	The grep check only matches lines starting exactly with 'ocredit', so if the line has leading spaces after sed replacement it cou

QA Result

Safe	✓
Verdict	The plan correctly sets ocredit = -1 in the pwquality configuration, enforcing the required special■character rule without alterin
Side Effects	Potential duplicate ocredit entries if the grep check fails to detect leading whitespace, which may cause redundant configurati
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	10.9s
Total Tokens	48,813
Cost	$0.0121
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

accounts_password_pam_pwquality_retry: Ensure PAM Enforces Password Requirements - Authentication Retry Prompts Permitt… — *SUCCESS*

Rule	accounts_password_pam_pwquality_retry
Severity	Medium
Description	To configure the number of retry prompts that are permitted per-session: Edit the /etc/security/pwquality.conf to include retry=
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_password_par
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies the PAM pwquality configuration to set a retry limit, which is a standard, low■impact change th
Estimated Impact	authentication/authorization affected; authentication lockout if retry set too low; policy non■compliance

Remediation (1 attempt(s))

Attempt #	1
Commands	sed -i 's/^#\?\s*retry\s*=.*$/retry = 3/' /etc/security/pwquality.conf
Scan Passed	✓
Success	✓
Duration	23.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set the required retry limit in /etc/security/pwquality.conf, which resolves the vulnerability. It could be hardened b
Concerns	If the file is immutable or has restrictive permissions, the sed/echo commands may fail.; Appending without checking for existi

QA Result

Safe	✓
Verdict	The plan only modifies the pwquality configuration to set a retry limit, which is a PAM setting for password change prompts. T

Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	8.4s
Total Tokens	35,999
Cost	$0.0081
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

accounts_password_pam_ucredit: Ensure PAM Enforces Password Requirements - Minimum Uppercase Characters — SUCCESS

Rule	accounts_password_pam_ucredit
Severity	Medium
Description	The pam_pwquality module's ucredit= parameter controls requirements for usage of uppercase letters in a password. When s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The finding requires a simple PAM configuration change to enforce uppercase characters in passwords. This is a standard ST
Estimated Impact	authentication/authorization affected; authentication; password_policy; potential_user_lockout

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/security/pwquality.conf /etc/security/pwquality.conf.bak, sed -i 's/^\s*#*\s*ucredit\s*=.*/ucredit = -1/' /etc/security/pwqua
Scan Passed	✓
Success	✓
Duration	50.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set ucredit = -1 in /etc/security/pwquality.conf, which enforces at least one uppercase character and addresses t
Concerns	Potential duplicate ucredit entries if other .conf.d files also define ucredit.; No backup of the original configuration file before m

QA Result

Safe	✓
Verdict	Setting ucredit = -1 in /etc/security/pwquality.conf correctly enforces at least one uppercase character for new passwords. Thi
Side Effects	Potential duplicate ucredit entries if the script is run multiple times or if other .conf.d files also define ucredit; No backup of the
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	10.2s

Total Tokens	46,264
Cost	$0.0106
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

service_debug-shell_disabled: Disable debug-shell SystemD Service — SUCCESS

Rule	service_debug-shell_disabled
Severity	Medium
Description	SystemD's debug-shell service is intended to diagnose SystemD related boot issues with various systemctl commands. Once
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the debug-shell service only removes a diagnostic root shell on tty9. It does not affect normal system operation, aut
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	systemctl list-unit-files debug-shell.service, systemctl stop debug-shell.service, systemctl disable debug-shell.service, system
Scan Passed	✓
Success	✓
Duration	48.1s

Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly stops, disables, and masks both the debug-shell service and its socket, which will remediate the vulnerabil
Concerns	—

QA Result

Safe	✓
Verdict	The plan only stops, disables, and masks the debug-shell service and its socket, which are diagnostic units not required for n
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	9.4s
Total Tokens	31,535
Cost	$0.0060
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

disable_ctrlaltdel_burstaction: Disable Ctrl-Alt-Del Burst Action — SUCCESS

Rule	disable_ctrlaltdel_burstaction

Severity	High
Description	By default, SystemD will reboot the system if the Ctrl-Alt-Del key sequence is pressed Ctrl-Alt-Delete more than 7 times in 2 s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q syste
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only requires a single line change in /etc/systemd/system.conf and a daemon reload. It does not affect authe
Estimated Impact	filesystems affected

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/systemd/system.conf /etc/systemd/system.conf.bak, sed -i 's/^[[:space:]]*#\?[[:space:]]*CtrlAltDelBurstAction=.*/CtrlAlt
Scan Passed	✓
Success	✓
Duration	35.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will correctly set CtrlAltDelBurstAction=none and reload systemd, addressing the vulnerability. Minor improvements

Concerns	The grep/sed pattern does not account for leading whitespace before the key, which may cause the existing setting to be mis

QA Result

Safe	✓
Verdict	The plan only updates a single systemd configuration parameter and reloads the daemon. This change does not affect SSH,
Side Effects	No functional side effects; the only change is disabling the Ctrl-Alt-Del burst reboot behavior.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	10.7s
Total Tokens	42,200
Cost	$0.0093
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

disable_ctrlaltdel_reboot: Disable Ctrl-Alt-Del Reboot Activation — SUCCESS

Rule	disable_ctrlaltdel_reboot
Severity	High
Description	By default, SystemD will reboot the system if the Ctrl-Alt-Del key sequence is pressed. To configure the system to ignore the
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if { rpm --quiet -q k
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	Masking ctrl-alt-del.target is a simple systemd configuration change that prevents the Ctrl-Alt-Del key sequence from rebootin
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	systemctl disable --now ctrl-alt-del.target, systemctl mask --now ctrl-alt-del.target
Scan Passed	✓
Success	✓
Duration	38.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly masks and disables ctrl■alt■del.target, which will prevent the reboot shortcut. It is safe and reversible.
Concerns	—

QA Result

Safe	✓
Verdict	Masking and disabling ctrl-alt-del.target only prevents the Ctrl■Alt■Del key sequence from triggering a reboot. It does not inte
Side Effects	No functional impact on normal system operation; only the reboot shortcut is disabled.
Regression	✗

Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	6.7s
Total Tokens	20,818
Cost	$0.0048
Agents	Triage(1), Remedy(8), Review(1), Qa(1)

package_opensc_installed: Install the opensc Package For Multifactor Authentication — SUCCESS

Rule	package_opensc_installed
Severity	Medium
Description	The opensc package can be installed with the following command: $ sudo dnf install opensc
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "c
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the opensc package is a standard, low■risk operation that does not modify critical system configurations or services
Estimated Impact	authentication/authorization affected

Remediation (1 attempt(s))

Attempt #	1

Commands	rpm -q opensc, dnf install -y opensc
Scan Passed	✓
Success	✓
Duration	83.4s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	8/10
Feedback	—
Concerns	—

QA Result

Safe	✓
Verdict	Installing the opensc package is a straightforward addition of smart■card support libraries. It does not modify existing configu
Side Effects	Adds new binaries and libraries to the system; Introduces additional dependencies that will be installed; Potentially expands t
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	6.1s
Total Tokens	22,717
Cost	$0.0047

Agents	Triage(1), Remedy(8), Review(1), Qa(1)

package_pcsc-lite_installed: Install the pcsc-lite package — SUCCESS

Rule	package_pcsc-lite_installed
Severity	Medium
Description	The pcsc-lite package can be installed with the following command: $ sudo dnf install pcsc-lite
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "p
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation consists of a straightforward package installation using dnf, which is a low■risk operation that does not affec
Estimated Impact	filesystems affected; minimal impact on system stability; no service lockout

Remediation (1 attempt(s))

Attempt #	1
Commands	dnf install -y pcsc-lite, rpm -q pcsc-lite
Scan Passed	✓
Success	✓
Duration	32.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will install the missing pcsc-lite package and verify its presence, which resolves the vulnerability. Adding a pre■insta
Concerns	—

QA Result

Safe	✓
Verdict	Installing the pcsc-lite package is a standard, non■intrusive operation on Rocky Linux/RHEL. It does not modify existing confi
Side Effects	Installation of the pcsc-lite package and its dependencies; Potential start of the pcscd daemon (smartcard service)
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	6.9s
Total Tokens	16,703
Cost	$0.0035
Agents	Triage(1), Remedy(8), Review(1), Qa(1)

install_smartcard_packages: Install Smart Card Packages For Multifactor Authentication — SUCCESS

Rule	install_smartcard_packages
Severity	Medium
Description	Configure the operating system to implement multifactor authentication by installing the required package with the following c

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { ! (grep -sqE "^.*\.s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only installs the openssl-pkcs11 package, which is a standard, non■disruptive package installation. It does r
Estimated Impact	authentication/authorization affected; authn; package_install

Remediation (1 attempt(s))

Attempt #	1
Commands	dnf install -y openssl-pkcs11, dnf install -y ca-certificates, dnf install -y openssl-pkcs11, dnf --setopt=sslverify=0 install -y oper
Scan Passed	✓
Success	✓
Duration	129.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will install the required openssl-pkcs11 package, addressing the vulnerability. Adding a check for existing installatior
Concerns	If the package is not available in the configured repositories, the command will fail.; No verification that the package is already

QA Result

Safe	✓
Verdict	Installing the openssl-pkcs11 package is a standard library addition that does not modify configuration files or restart services
Side Effects	Installation of the package and its dependencies; Potential SELinux context updates for new files
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	9.5s
Total Tokens	29,297
Cost	$0.0060
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

service_pcscd_enabled: Enable the pcscd Service — SUCCESS

Rule	service_pcscd_enabled
Severity	Medium
Description	The pcscd service can be enabled with the following command: $ sudo systemctl enable pcscd.service
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	Enabling the pcscd service is a straightforward service activation that does not affect system boot, SSH access, or critical aut
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	systemctl unmask pcscd.service, systemctl start pcscd.service, systemctl enable pcscd.service
Scan Passed	✓
Success	✓
Duration	33.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will enable and start the pcscd service as required, addressing the vulnerability. Adding checks for package installat
Concerns	Assumes the pcscd package is already installed; if not, the service enable fail.; Does not verify that the service started succes

QA Result

Safe	✓
Verdict	Enabling and starting the pcscd daemon is a standard operation that does not interfere with SSH, auditd, firewalld, networking
Side Effects	Adds an additional daemon that consumes a small amount of memory and CPU; Opens a socket for smart■card communicat
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	6.2s
Total Tokens	19,645
Cost	$0.0038
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

configure_opensc_card_drivers: Configure opensc Smart Card Drivers — FAILED

Rule	configure_opensc_card_drivers
Severity	Medium
Description	The OpenSC smart card tool can auto-detect smart card drivers; however, setting the smart card drivers in use by your organ
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_smartcard_driv
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only requires editing a single configuration file (/etc/opensc.conf) to set the card_drivers parameter. No servi
Estimated Impact	authentication/authorization affected; filesystems affected; authentication; configuration file modification

Remediation (3 attempt(s))

Attempt #	1
Commands	cp /etc/opensc.conf /etc/opensc.conf.bak, grep -q -E '^\s*#?\s*card_drivers' /etc/opensc.conf, sed -i '/app default {/a \ card_d
Scan Passed	✗

Success	✗
Duration	32.3s
Error	—

Attempt #	2
Commands	cat /etc/opensc.conf > /etc/opensc.conf.bak, sed -i '/app default {/,/}/ s/^\s*#?\s*card_drivers.*$/ card_drivers = ;/' /etc/opens
Scan Passed	✗
Success	✗
Duration	36.4s
Error	—

Attempt #	3
Commands	opensc-tool -s
Scan Passed	✗
Success	✗
Duration	33.2s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan creates a backup, correctly inserts or replaces the card_drivers line within the app default block, and avoids sed por
Concerns	Block parsing must correctly handle nested braces and whitespace variations.; File permissions and ownership should be pre

QA Result

Safe	✓
Verdict	The plan only edits /etc/opensc.conf to ensure a card_drivers line exists inside the app default block, creating a backup first. T
Side Effects	Potential OpenSC smart■card authentication issues if the config syntax is malformed; Possible change of file ownership/perm
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	12.5s
Total Tokens	62,841
Cost	$0.0120
Agents	Remedy(12), Review(1), Qa(1)

account_disable_post_pw_expiration: Set Account Expiration Following Inactivity — SUCCESS

Rule	account_disable_post_pw_expiration
Severity	Medium
Description	To specify the number of days after a password expires (which signifies inactivity) until an account is permanently disabled, a
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q shad
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	The remediation only requires editing a single line in /etc/default/useradd to set the INACTIVE parameter. This is a standard a
Estimated Impact	authentication/authorization affected; filesystems affected; Incorrect INACTIVE value could temporarily lock out inactive accou

Remediation (1 attempt(s))

Attempt #	1
Commands	sed -i -r 's/^#?\s*INACTIVE\s*=.*$/INACTIVE=30/' /etc/default/useradd
Scan Passed	✓
Success	✓
Duration	18.2s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly sets INACTIVE=30 in /etc/default/useradd, satisfying the rule. It could be improved by adding a backup and
Concerns	No backup of the original file before modification; Potential duplicate INACTIVE lines if the file already contains multiple entrie

QA Result

Safe	✓
Verdict	Editing /etc/default/useradd to set INACTIVE=30 only changes a static configuration file used for default account creation. It d
Side Effects	If the file already contains multiple INACTIVE entries, the sed command may replace all of them, potentially leaving duplicate
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	9.5s
Total Tokens	25,727
Cost	$0.0061
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

accounts_maximum_age_login_defs: Set Password Maximum Age — FAILED

Rule	accounts_maximum_age_login_defs
Severity	Medium
Description	To specify password maximum age for new accounts, edit the file /etc/login.defs and add or correct the following line: PASS_
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q shad
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits /etc/login.defs to set PASS_MAX_DAYS, a standard password policy change. It does not affect cr
Estimated Impact	authentication/authorization affected; auth_policy; potential_user_lockout

Remediation (3 attempt(s))

Attempt #	1
Commands	grep -q '^PASS_MAX_DAYS' /etc/login.defs && echo present || echo absent, sed -i -e 's/^#\?\s*PASS_MAX_DAYS\s*=\?\s*[0
Scan Passed	✗

Success	✗
Duration	17.6s
Error	—

Attempt #	2
Commands	id -u, cp /etc/login.defs /etc/login.defs.bak, awk '{if($0 ~ /^[[:space:]]*#?[[:space:]]*PASS_MAX_DAYS/) next; print}' /etc/login.d
Scan Passed	✗
Success	✗
Duration	46.4s
Error	—

Attempt #	3
Commands	cp -a /etc/login.defs /etc/login.defs.bak, perl -i -pe 's/^\s*#?\s*PASS_MAX_DAYS\s*=?\s*\d+.*$/PASS_MAX_DAYS 90/' /etc/lo
Scan Passed	✗
Success	✗
Duration	38.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set PASS_MAX_DAYS to 90, creates a backup, and attempts to ensure only one entry exists. It therefore resolv
Concerns	No explicit check that the script is running as root.; The perl regex may not match lines that contain spaces around the '=' sign

QA Result

Safe	✓
Verdict	The plan only edits /etc/login.defs to set PASS_MAX_DAYS to 90, creates a backup, and ensures a single entry. This is a sta
Side Effects	Password aging policy will be enforced at 90 days for new accounts and existing accounts without an explicit override.; Any e
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	12.1s
Total Tokens	80,654
Cost	$0.0165
Agents	Remedy(12), Review(1), Qa(1)

accounts_minimum_age_login_defs: Set Password Minimum Age — SUCCESS

Rule	accounts_minimum_age_login_defs
Severity	Medium
Description	To specify password minimum age for new accounts, edit the file /etc/login.defs and add or correct the following line: PASS_M
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q shad
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	The remediation only edits /etc/login.defs to set PASS_MIN_DAYS, a standard password policy change. It does not affect aut
Estimated Impact	authentication/authorization affected

Remediation (1 attempt(s))

Attempt #	1
Commands	sed -i -e 's/^#\?PASS_MIN_DAYS.*/PASS_MIN_DAYS 1/' /etc/login.defs
Scan Passed	✓
Success	✓
Duration	16.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will correctly set PASS_MIN_DAYS to 1 in /etc/login.defs, addressing the vulnerability. It is simple and functional but
Concerns	The sed command may unintentionally replace similarly named settings if they exist.; No backup of the original file is created

QA Result

Safe	✓
Verdict	The remediation correctly enforces PASS_MIN_DAYS=1 in /etc/login.defs, which is a harmless security setting. It does not af
Side Effects	Potential duplicate PASS_MIN_DAYS line if the conditional logic is not implemented correctly; No backup of the original file is
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	7.7s
Total Tokens	49,914
Cost	$0.0112
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

accounts_password_set_min_life_existing: Set Existing Passwords Minimum Age — FAILED

Rule	accounts_password_set_min_life_existing
Severity	Medium
Description	Configure non-compliant accounts to enforce a 24 hours/1 day minimum password lifetime by running the following command
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_mini
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only adjusts password minimum age using chage, which is a standard auth configuration change and does n
Estimated Impact	authentication/authorization affected; Minor inconvenience to users who must wait 24■hours before changing passwords

Remediation (3 attempt(s))

Attempt #	1
Commands	awk -F: '$3>=1000 && $7!="/sbin/nologin" && $7!="/bin/false" {print $1}' /etc/passwd | xargs -n1 chage -m 1, awk -F: '$3>=100
Scan Passed	✗

Success	✗
Duration	46.4s
Error	—

Attempt #	2
Commands	getent passwd | awk -F: '($3>=1000) {print $1}' \| while read user; do pw=$(awk -F: -v u="$user" '$1==u {print $2}' /etc/shadow
Scan Passed	✗
Success	✗
Duration	21.7s
Error	—

Attempt #	3
Commands	sed -i 's/^#\?PASS_MIN_DAYS.*/PASS_MIN_DAYS 1/' /etc/login.defs, grep -q '^PASS_MIN_DAYS' /etc/login.defs || echo 'PA
Scan Passed	✗
Success	✗
Duration	40.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly updates PASS_MIN_DAYS and applies a 1■day minimum password age to regular, unlocked user accour
Concerns	Accounts with UID below 1000 that are regular users on some distributions will still be skipped.; If no matching users are foun

QA Result

Safe	✓
Verdict	The plan correctly sets PASS_MIN_DAYS to 1 and applies the same minimum password age to all regular, unlocked user ac
Side Effects	Minor security hygiene issue: temporary script created in /tmp without explicit permission setting.; Potential harmless error me
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	12.6s
Total Tokens	80,781
Cost	$0.0153
Agents	Remedy(12), Review(1), Qa(1)

accounts_password_pam_unix_rounds_password_auth: Set number of Password Hashing Rounds - password-auth — FAILED

Rule	accounts_password_pam_unix_rounds_password_auth
Severity	Medium
Description	Configure the number or rounds for the password hashing algorithm. This can be accomplished by using the rounds option fo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q pam && rpm --quiet -q kernel-core
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	The remediation only modifies the PAM configuration to add a rounds parameter for pam_unix. This is a standard STIG harde
Estimated Impact	authentication/authorization affected; authn_authz

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	4.3s
Error	—

Attempt #	2
Commands	which authselect, authselect current-profile, authselect current, cp /etc/pam.d/password-auth /etc/pam.d/password-auth.bak, a
Scan Passed	✗
Success	✗
Duration	66.1s
Error	—

Attempt #	3
Commands	authselect current-profile, authselect current, authselect create-profile custom_hardening_20260409 -b custom/hardening, cp
Scan Passed	✗
Success	✗
Duration	79.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly uses authselect to create a custom profile and adds the required rounds=5000 option to the pam_unix.so li
Concerns	The sed command may modify all pam_unix.so lines in password-auth, potentially affecting sections where the rounds option

QA Result

Safe	✓
Verdict	The plan uses authselect to create a custom PAM profile and adds the rounds=5000 option to the pam_unix.so line in passwo
Side Effects	Slight increase in authentication time due to higher round count (still the default value).; If the custom profile name collides wi
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	12.9s
Total Tokens	98,815
Cost	$0.0173
Agents	Remedy(16), Review(1), Qa(1)

accounts_password_pam_unix_rounds_system_auth: Set number of Password Hashing Rounds - system-auth — FAILED

Rule	accounts_password_pam_unix_rounds_system_auth
Severity	Medium
Description	Configure the number or rounds for the password hashing algorithm. This can be accomplished by using the rounds option fo

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q pam && rpm --quiet -q kernel-core
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only adds a rounds option to the pam_unix.so entry in /etc/pam.d/system-auth. This is a standard PAM hard
Estimated Impact	authentication/authorization affected; authentication

Remediation (3 attempt(s))

Attempt #	1
Commands	authselect list-features, authselect current, authselect list-features custom/custom_hardening_20260409, grep -R "rounds" -n
Scan Passed	✗
Success	✗
Duration	57.5s
Error	—

Attempt #	2
Commands	authselect list-features, authselect list-features custom/custom_hardening_20260409, authselect apply-changes
Scan Passed	✗
Success	✗
Duration	25.4s
Error	—

Attempt #	3
Commands	cp /etc/pam.d/system-auth /etc/pam.d/system-auth.bak, sed -i '/pam_unix\.so/ { s/rounds=[0-9]\+/rounds=5000/; /rounds=/! s/$
Scan Passed	✗
Success	✗
Duration	17.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan will add the required rounds=5000 option to /etc/pam.d/system-auth and thus satisfy the OpenSCAP check, but it do
Concerns	Directly editing the generated /etc/pam.d/system-auth file bypasses authselect and may be overwritten by future authselect cl

QA Result

Safe	✓
Verdict	The sed edit safely adds or updates the rounds=5000 option on the pam_unix.so line without removing existing required optio
Side Effects	Potential duplicate rounds=5000 entries if the option already exists in a non■matching format; Changes will be lost if authsele
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	10.1s
Total Tokens	47,045

Cost	$0.0091
Agents	Remedy(10), Review(1), Qa(1)

no_empty_passwords: Prevent Login to Accounts With Empty Password — SUCCESS

Rule	no_empty_passwords
Severity	High
Description	If an account is configured for password authentication but does not have an assigned password, it may be possible to log int
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if [-f /usr/bin/auths
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Removing the 'nullok' option from PAM configuration is a standard STIG hardening step that does not involve kernel, bootload
Estimated Impact	authentication/authorization affected; filesystems affected; Potential lockout of accounts that currently rely on empty passwor

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/pam.d/system-auth /etc/pam.d/system-auth.bak, cp /etc/pam.d/password-auth /etc/pam.d/password-auth.bak, sed -i -r
Scan Passed	✓
Success	✓
Duration	29.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan removes the 'nullok' option from the PAM configuration files, which will stop empty■password logins. However, it do
Concerns	Directly editing /etc/pam.d/system-auth and password-auth can be overwritten by authselect on systems where it is enabled,

QA Result

Safe	✓
Verdict	Removing the 'nullok' option from PAM configuration prevents empty■password logins as intended and does not alter the req
Side Effects	Manual edits may be overwritten by authselect on systems that use it, potentially re■introducing the vulnerability after a profil
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	17
Duration	13.2s
Total Tokens	60,169
Cost	$0.0143
Agents	Triage(1), Remedy(14), Review(1), Qa(1)

use_pam_wheel_for_su: Enforce usage of pam_wheel for su authentication — SUCCESS

Rule	use_pam_wheel_for_su
Severity	Medium
Description	To ensure that only users who are members of the wheel group can run commands with altered privileges through the su com

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q pam; then # uncomment the option i
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only requires uncommenting a PAM configuration line in /etc/pam.d/su, which is a standard STIG hardening
Estimated Impact	authentication/authorization affected; filesystems affected; Potential loss of su access for users not in the wheel group

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/pam.d/su /etc/pam.d/su.bak, sed -i 's/^#[[:space:]]*auth[[:space:]]*required[[:space:]]*pam_wheel\.so[[:space:]]*use_uid
Scan Passed	✓
Success	✓
Duration	23.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will uncomment the required pam_wheel line if it exists but commented, which resolves the vulnerability in most defa
Concerns	If the line "auth required pam_wheel.so use_uid" is absent, the plan will not add it, leaving the finding unresolved.; No backup

QA Result

Safe	✓
Verdict	The plan only uncomments an existing pam_wheel line in /etc/pam.d/su, which enforces wheel group restriction for su. This c
Side Effects	Potential loss of inline comments on the edited line; If the line is missing, the finding remains unresolved
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	8.8s
Total Tokens	32,139
Cost	$0.0068
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

accounts_logon_fail_delay: Ensure the Logon Failure Delay is Set Correctly in login.defs — FAILED

Rule	accounts_logon_fail_delay
Severity	Medium
Description	To ensure the logon failure delay controlled by /etc/login.defs is set properly, add or correct the FAIL_DELAY setting in /etc/lo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q shadow-utils && rpm --quiet -q kerr
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	The remediation only modifies the FAIL_DELAY parameter in /etc/login.defs, a simple text file edit that does not affect service
Estimated Impact	authentication/authorization affected; filesystems affected; authentication; pam

Remediation (3 attempt(s))

Attempt #	1
Commands	cp /etc/login.defs /etc/login.defs.bak, sed -i -e 's/^#\s*FAIL_DELAY\s\+.*$/FAIL_DELAY 1/' -e 's/^FAIL_DELAY\s\+.*$/FAIL_D
Scan Passed	✗
Success	✗
Duration	31.0s
Error	—

Attempt #	2
Commands	perl -i.bak -pe 'BEGIN{$found=0} if (/^\s*#?\s*FAIL_DELAY/) {$found=1; $_="FAIL_DELAY 1\n"} END {print "FAIL_DELAY 1\n
Scan Passed	✗
Success	✗
Duration	37.2s
Error	—

Attempt #	3
Commands	cp -p /etc/login.defs /etc/login.defs.bak, sed -i -e 's/^[#[:space:]]*FAIL_DELAY[[:space:]]\+.*/FAIL_DELAY 1/' /etc/login.defs, gr
Scan Passed	✗
Success	✗
Duration	22.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set FAIL_DELAY to a non■zero value and ensure the line exists in /etc/login.defs, addressing the vulnerability. I
Concerns	The sed replacement will discard any inline or preceding comments on the FAIL_DELAY line.; If multiple FAIL_DELAY entries

QA Result

Safe	✓
Verdict	The plan correctly sets FAIL_DELAY to a non■zero value, uses a backup, and edits /etc/login.defs in a straightforward way th
Side Effects	Possible loss of SELinux context or extended attributes on /etc/login.defs due to sed -i replacement; Creation of a backup file
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	13.9s
Total Tokens	56,876
Cost	$0.0128
Agents	Remedy(10), Review(1), Qa(1)

accounts_tmout: Set Interactive Session Timeout — SUCCESS

Rule	accounts_tmout
Severity	Medium
Description	Setting the TMOUT option in /etc/profile ensures that all user sessions will terminate based on inactivity. A value of 0 (zero) d

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_tmo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits shell profile files to set a positive TMOUT value, which is a standard STIG hardening measure. It d
Estimated Impact	filesystems affected; user session termination after inactivity; potential misconfiguration if TMOUT set to zero or too low

Remediation (1 attempt(s))

Attempt #	1
Commands	ls -1 /etc/profile.d/*.sh, chown root:root /etc/profile.d/tmout.sh, grep -R "^[^#]*TMOUT" /etc/profile /etc/profile.d/*.sh || true, ls -l
Scan Passed	✓
Success	✓
Duration	34.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set a positive, exported, read■only TMOUT value as required and will create the fallback file if none exists. It ad
Concerns	The grep pattern "^[^#]*TMOUT" can match lines where TMOUT appears in comments or strings, potentially causing unintend

QA Result

Safe	✓
Verdict	The plan correctly sets a positive, exported, read■only TMOUT value in standard profile locations, affecting only interactive s
Side Effects	Potential unintended replacement of TMOUT strings inside comments; No automatic backup of original profile files, making ro
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	20
Duration	18.9s
Total Tokens	71,365
Cost	$0.0140
Agents	Triage(1), Remedy(15), Review(2), Qa(2)

file_permission_user_init_files_root: Ensure All User Initialization Files Have Mode 0740 Or Less Permissive — FAILED

Rule	file_permission_user_init_files_root
Severity	Medium
Description	Set the mode of the user initialization files, including the root user, to 0740 with the following commands: $ sudo chmod 0740
Recommendation	Remediation script: var_user_initialization_files_regex='' readarray -t interactive_users < <(awk -F: '$3==0 || $3>=1000 {print
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	The remediation only changes file permissions on user initialization files to a more restrictive mode (0740). This is a standard
Estimated Impact	filesystems affected

Remediation (3 attempt(s))

Attempt #	1
Commands	find /root -maxdepth 1 -type f \(-name ".bashrc" -o -name ".bash_profile" -o -name ".bash_login" -o -name ".profile" -o -name
Scan Passed	✗
Success	✗
Duration	16.2s
Error	—

Attempt #	2
Commands	bash -c 'var_user_initialization_files_regex="\\.(bashrc|bash_profile|bash_login|profile|cshrc|kshrc|zshrc|zprofile|login|tcshrc|b
Scan Passed	✗
Success	✗
Duration	33.3s
Error	—

Attempt #	3
Commands	bash -c 'while IFS=: read -r user uid gid _ home shell; do if ["$uid" -eq 0] \|\| ["$uid" -ge 1000]; then if ["$shell" != "/sbin/nolog
Scan Passed	✗
Success	✗
Duration	31.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set the permissions of the common shell initialization files (including those in .profile.d) to 0740 for root and all in
Concerns	Static filename list may miss custom or additional init files not included in the brace expansion.; The plan does not use the va

QA Result

Safe	✓
Verdict	The plan only changes permissions of user shell initialization files to 0740, which is less permissive than the default and satis
Side Effects	Adds execute bit for the owner on init files (e.g., .bashrc) which is harmless; No functional change to the contents of the files
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	12.1s
Total Tokens	71,550
Cost	$0.0135
Agents	Remedy(11), Review(1), Qa(1)

accounts_umask_etc_bashrc: Ensure the Default Bash Umask is Set Correctly — FAILED

Rule	accounts_umask_etc_bashrc
Severity	Medium
Description	To ensure the default umask for users of the Bash shell is set properly, add or correct the umask setting in /etc/bashrc to read

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q bash
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits /etc/bashrc to set a standard umask value, which is a simple text substitution and does not affect a
Estimated Impact	filesystems affected; configuration

Remediation (3 attempt(s))

Attempt #	1
Commands	grep -R "accounts_umask_etc_bashrc" -n /usr/share/xml/scap/ssg/content/ -m 1 || true, grep -R "var_accounts_user_umask"
Scan Passed	✗
Success	✗
Duration	20.2s
Error	—

Attempt #	2
Commands	rpm -q bash, test -f /etc/bashrc && echo "exists" || echo "missing", cp -a /etc/bashrc /etc/bashrc.bak-$(date +%F), grep -E "^[[
Scan Passed	✗
Success	✗
Duration	22.3s
Error	—

Attempt #	3
Commands	rpm -q bash, test -f /etc/bashrc && echo exists || echo missing, test -w /etc/bashrc && echo writable || echo not_writable, stat
Scan Passed	✗
Success	✗
Duration	33.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set the default Bash umask to 027 in /etc/bashrc, addressing the vulnerability. However, it does not fully handle
Concerns	Backup using install -b -m 644 may not retain original file permissions, SELinux context, or extended attributes.; The plan doe

QA Result

Safe	✓
Verdict	The plan correctly sets the default Bash umask to 027 in /etc/bashrc, which addresses the vulnerability. The modifications are
Side Effects	Potential loss of original SELinux context on /etc/bashrc; File mode may be forced to 644, which could differ from the original
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	14.8s
Total Tokens	127,736

Cost	$0.0254
Agents	Remedy(16), Review(1), Qa(1)

accounts_umask_etc_csh_cshrc: Ensure the Default C Shell Umask is Set Correctly — FAILED

Rule	accounts_umask_etc_csh_cshrc
Severity	Medium
Description	To ensure the default umask for users of the C shell is set properly, add or correct the umask setting in /etc/csh.cshrc to read
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_use
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies a single line in /etc/csh.cshrc to set the default umask for C shell users. This is a straightforwa
Estimated Impact	filesystems affected; shell configuration; file edit

Remediation (3 attempt(s))

Attempt #	1
Commands	cp /etc/csh.cshrc /etc/csh.cshrc.bak, sed -i -E 's/^\s*umask\b.*/umask 027/' /etc/csh.cshrc
Scan Passed	✗
Success	✗
Duration	14.5s
Error	—

Attempt #	2
Commands	test -f /etc/csh.cshrc && test -w /etc/csh.cshrc, cat /etc/csh.cshrc > /etc/csh.cshrc.bak, sed -i '/# Set default umask/,/endif/ c\u
Scan Passed	✗
Success	✗
Duration	18.4s
Error	—

Attempt #	3
Commands	grep -E -q '^\s*#?\s*umask' /etc/csh.cshrc, sed -i -E 's/^\s*#?\s*umask.*$/umask 027/' /etc/csh.cshrc, dd if=/etc/csh.cshrc of=/
Scan Passed	✗
Success	✗
Duration	18.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan addresses the previous concerns by adding a backup, checking for existing umask entries, and avoiding duplicate li
Concerns	The backup uses dd, which is more complex than necessary; cp would be simpler.; File existence and writability are mentione

QA Result

Safe	✓
Verdict	The plan correctly backs up /etc/csh.cshrc, checks for an existing umask line, and either replaces it or appends the desired se
Side Effects	If a commented umask line is present, it will be overwritten, removing the comment marker.; The backup file created with dd r

Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	12.6s
Total Tokens	50,834
Cost	$0.0107
Agents	Remedy(11), Review(1), Qa(1)

accounts_umask_etc_login_defs: Ensure the Default Umask is Set Correctly in login.defs — SUCCESS

Rule	accounts_umask_etc_login_defs
Severity	Medium
Description	To ensure the default umask controlled by /etc/login.defs is set properly, add or correct the UMASK setting in /etc/login.defs t
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q shad
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits a single line in /etc/login.defs to set the UMASK value. This is a simple configuration change that c
Estimated Impact	file permission defaults

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/login.defs /etc/login.defs.bak, sed -i '/^#\?\s*UMASK/d' /etc/login.defs, echo 'UMASK 077' >> /etc/login.defs, chown roo
Scan Passed	✓
Success	✓
Duration	25.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set a single UMASK entry and backup the original file, effectively addressing the issue.
Concerns	Removing commented UMASK lines may discard useful documentation.; Appending the setting could lead to duplicate entries

QA Result

Safe	✓
Verdict	The remediation correctly backs up /etc/login.defs, removes any existing UMASK entries, appends a single UMASK 077 line,
Side Effects	Loss of commented documentation in /etc/login.defs; More restrictive default file permissions may affect applications that exp
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	17.3s
Total Tokens	78,343

Cost	$0.0166
Agents	Triage(1), Remedy(13), Review(2), Qa(2)

accounts_umask_etc_profile: Ensure the Default Umask is Set Correctly in /etc/profile — FAILED

Rule	accounts_umask_etc_profile
Severity	Medium
Description	To ensure the default umask controlled by /etc/profile is set properly, add or correct the umask setting in /etc/profile to read as
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_use
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits or adds a umask line in /etc/profile and files in /etc/profile.d. This is a straightforward text substituti
Estimated Impact	filesystems affected; misconfigured default file permissions; potentially permissive file creation

Remediation (3 attempt(s))

Attempt #	1
Commands	grep -R -E '^[^#]*umask' /etc/profile /etc/profile.d/*.sh 2>/dev/null || true, echo 'umask 027' >> /etc/profile, grep -qE '^[[:space:]
Scan Passed	✗
Success	✗
Duration	21.8s
Error	—

Attempt #	2
Commands	find /etc/profile.d -type f \(-name "*.sh" -o -name "sh.local" \) -maxdepth 1, grep -E "^[[:space:]]*[^#]*\bumask\b" -n /etc/profile
Scan Passed	✗
Success	✗
Duration	22.4s
Error	—

Attempt #	3
Commands	sed -i.bak -E 's/^([[:space:]]*[^#]*\bumask\b[[:space:]]+)[0-7]+/\1 027/' /etc/profile, ls -1 /etc/profile.d/*.sh /etc/profile.d/sh.local 2
Scan Passed	✗
Success	✗
Duration	22.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly backs up files, uses a precise regex to target uncommented umask lines, and ensures the desired value 02
Concerns	If a file already contains multiple uncommented umask lines, the plan replaces each but does not remove duplicates, potentia

QA Result

Safe	✓
Verdict	The plan only adjusts the default umask in /etc/profile and /etc/profile.d scripts, which is a standard hardening change. Setting
Side Effects	Possible duplicate uncommented umask lines if a file already contains several definitions.; Backup files created with sed -i.ba

Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	13.4s
Total Tokens	67,500
Cost	$0.0130
Agents	Remedy(12), Review(1), Qa(1)

grub2_init_on_free: The system must booted with init_on_free=1 — DISCARDED

Rule	grub2_init_on_free
Severity	Medium
Description	Setting init_on_free=1 on boot guarantees that pages and heap objects are initialized right after they're freed, so it won't be p
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q grub2-common && rpm --quiet -q k
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	The remediation modifies the bootloader configuration to add a kernel parameter. Errors in grubby or kargs files can render th
Estimated Impact	reboot required; filesystems affected; bootloader_configuration; kernel_parameter; potential_unbootable_state

LLM Metrics

LLM Calls	1
Duration	1.5s
Total Tokens	1,547
Cost	$0.0007
Agents	Triage(1)

grub2_vsyscall_argument: Disable vsyscalls — DISCARDED

Rule	grub2_vsyscall_argument
Severity	Medium
Description	To disable use of virtual syscalls, add the argument vsyscall=none to the default GRUB 2 command line for the Linux operati
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q grub2-common && rpm --quiet -q k
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	The remediation modifies the GRUB bootloader configuration to add a kernel command line argument. Incorrect changes can
Estimated Impact	reboot required; bootloader; kernel_parameter; potential_boot_failure; system_unavailability

LLM Metrics

LLM Calls	1
Duration	1.6s
Total Tokens	2,109

Cost	$0.0010
Agents	Triage(1)

grub2_admin_username: Set the Boot Loader Admin Username to a Non-Default Value — DISCARDED

Rule	grub2_admin_username
Severity	High
Description	The grub2 boot loader should have a superuser account and password protection enabled to protect boot-time settings. To m
Recommendation	Review and remediate: Set the Boot Loader Admin Username to a Non-Default Value
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	The remediation requires editing GRUB2 boot loader configuration files and regenerating the boot menu. Mistakes can preven
Estimated Impact	reboot required; filesystems affected; bootloader configuration; potential boot failure; possible lockout if password not set corr

LLM Metrics

LLM Calls	1
Duration	1.5s
Total Tokens	1,477
Cost	$0.0007
Agents	Triage(1)

grub2_password: Set Boot Loader Password in grub2 — DISCARDED

Rule	grub2_password
Severity	High
Description	The grub2 boot loader should have a superuser account and password protection enabled to protect boot-time settings. Since
Recommendation	Review and remediate: Set Boot Loader Password in grub2
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Modifying the GRUB2 bootloader password changes bootloader configuration; mistakes can prevent the system from booting
Estimated Impact	reboot required; authentication/authorization affected; filesystems affected; bootloader lockout; system unbootable; console a

LLM Metrics

LLM Calls	1
Duration	1.3s
Total Tokens	1,289
Cost	$0.0006
Agents	Triage(1)

package_rsyslog-gnutls_installed: Ensure rsyslog-gnutls is installed — SUCCESS

Rule	package_rsyslog-gnutls_installed
Severity	Medium
Description	TLS protocol support for rsyslog is installed. The rsyslog-gnutls package can be installed with the following command: $ sudo

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "r
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves installing a standard package (rsyslog-gnutls) which adds TLS support to rsyslog. This is a typical, l
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	dnf install -y rsyslog-gnutls, rpm -q rsyslog-gnutls
Scan Passed	✓
Success	✓
Duration	48.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will install the rsyslog-gnutls package, which resolves the vulnerability. It is functional but could be improved with ide
Concerns	No check for whether the package is already installed, leading to unnecessary operation.; No verification step to confirm succ

QA Result

Safe	✓
Verdict	Installing the rsyslog-gnutls package is a standard operation that adds TLS support to rsyslog. It does not modify SSH or othe
Side Effects	Possible restart of rsyslog service during installation, leading to a short period where logging is unavailable.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	7.5s
Total Tokens	19,729
Cost	$0.0039
Agents	Triage(1), Remedy(8), Review(1), Qa(1)

rsyslog_encrypt_offload_actionsendstreamdriverauthmode: Ensure Rsyslog Authenticates Off-Loaded Audit Records — SUCCESS

Rule	rsyslog_encrypt_offload_actionsendstreamdriverauthmode
Severity	Medium
Description	Rsyslogd is a system utility providing support for message logging. Support for both internet and UNIX domain sockets enabl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	The remediation only involves editing rsyslog configuration files to set an authentication mode for remote log forwarding. This
Estimated Impact	authentication/authorization affected; networking affected; filesystems affected; audit logging; rsyslog configuration; remote lo

Remediation (1 attempt(s))

Attempt #	1
Commands	ls -1 /etc/rsyslog.d, echo '$ActionSendStreamDriverAuthMode x509/name' >> /etc/rsyslog.conf, systemctl restart rsyslog, syst
Scan Passed	✓
Success	✓
Duration	20.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly identifies the need to set $ActionSendStreamDriverAuthMode to x509/name and provides steps to edit the
Concerns	The plan only handles the legacy $ActionSendStreamDriverAuthMode syntax and does not address existing RainerScript acti

QA Result

Safe	✓
Verdict	The plan correctly sets the required $ActionSendStreamDriverAuthMode directive, avoids duplicate entries, and restarts only
Side Effects	Temporary interruption of logging while rsyslog is restarted; Potential loss of custom logging behavior if the directive is placed
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	11.5s
Total Tokens	45,786
Cost	$0.0093
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

rsyslog_encrypt_offload_actionsendstreamdrivermode: Ensure Rsyslog Encrypts Off-Loaded Audit Records — REQUIRES_HUMAN_REVIEW

Rule	rsyslog_encrypt_offload_actionsendstreamdrivermode
Severity	Medium
Description	Rsyslogd is a system utility providing support for message logging. Support for both internet and UNIX domain sockets enabl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The remediation only edits rsyslog configuration files to enforce encrypted off■load. It does not modify authentication mechan
Estimated Impact	networking affected; filesystems affected; potential rsyslog service disruption; remote log transmission interruption; configurat

LLM Metrics

LLM Calls	1
Duration	1.3s

Total Tokens	1,535
Cost	$0.0007
Agents	Triage(1)

rsyslog_encrypt_offload_defaultnetstreamdriver: Ensure Rsyslog Encrypts Off-Loaded Audit Records — SUCCESS

Rule	rsyslog_encrypt_offload_defaultnetstreamdriver
Severity	Medium
Description	Rsyslogd is a system utility providing support for message logging. Support for both internet and UNIX domain sockets enabl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits rsyslog configuration files to enable TLS for remote log forwarding. This is a straightforward text su
Estimated Impact	networking affected; filesystems affected; Potential disruption of remote logging if rsyslog fails to restart; Misconfiguration cou

Remediation (1 attempt(s))

Attempt #	1
Commands	mkdir -p /etc/rsyslog.d, sed -i '/^[[:space:]]*\$DefaultNetstreamDriver/d' /etc/rsyslog.conf, find /etc/rsyslog.d -type f -name "*.co
Scan Passed	✓
Success	✓
Duration	22.7s

Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly removes any existing $DefaultNetstreamDriver settings, adds the required gtls driver in a dedicated conf fil
Concerns	The plan does not verify that the new configuration is syntactically valid before restarting rsyslog.; SELinux contexts for the ne

QA Result

Safe	✓
Verdict	The plan correctly configures rsyslog to use TLS for off■loaded logs, removes conflicting settings, and restarts the service. Th
Side Effects	Temporary interruption of syslog logging during rsyslog restart; Potential rsyslog start failure if the new configuration contains
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	11.6s
Total Tokens	70,032
Cost	$0.0138
Agents	Triage(1), Remedy(15), Review(1), Qa(1)

rsyslog_remote_access_monitoring: Ensure remote access methods are monitored in Rsyslog — SUCCESS

Rule	rsyslog_remote_access_monitoring

Severity	Medium
Description	Logging of remote access methods must be implemented to help identify cyber attacks and ensure ongoing compliance with r
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslog
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits rsyslog configuration files to add standard selectors for auth, authpriv, and daemon logs. This is a
Estimated Impact	authentication/authorization affected; filesystems affected; missing audit of remote access attempts; incomplete logging of au

Remediation (1 attempt(s))

Attempt #	1
Commands	grep -E '^\s*auth\..*;\s*authpriv\..*\s+/var/log/secure' /etc/rsyslog.conf || true, grep -E '^\s*daemon\..*\s+/var/log/messages' /etc
Scan Passed	✓
Success	✓
Duration	30.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will add the required auth.*, authpriv.*, and daemon.* selectors and restart rsyslog, which satisfies the vulnerability r

Concerns	The sed insertion only works when a '*.*' catch■all rule is present; if it is missing the line will not be added.; Existing comment

QA Result

Safe	✓
Verdict	The plan only modifies rsyslog configuration to add required selectors and restarts the rsyslog service. These changes are lim
Side Effects	Potential duplicate log entries if the same selector already exists.; Temporary loss of logging if rsyslog fails to start due to a sy
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	22
Duration	14.0s
Total Tokens	101,998
Cost	$0.0180
Agents	Triage(1), Remedy(19), Review(1), Qa(1)

rsyslog_remote_loghost: Ensure Logs Sent To Remote Host — SUCCESS

Rule	rsyslog_remote_loghost
Severity	Medium
Description	To configure rsyslog to send logs to a remote log server, open /etc/rsyslog.conf and read and understand the last section of th
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then rsyslog_remote_lo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	The remediation only edits /etc/rsyslog.conf to add a remote log host directive and restarts the rsyslog service. This is a straig
Estimated Impact	networking affected; network_change; service_restart

Remediation (2 attempt(s))

Attempt #	1
Commands	grep -E "*\.*.*@" /etc/rsyslog.conf || true, echo "*.* @@log.example.com:514" >> /etc/rsyslog.conf, systemctl restart rsyslog,
Scan Passed	✗
Success	✗
Duration	27.7s
Error	—

Attempt #	2
Commands	cp /etc/rsyslog.conf /etc/rsyslog.conf.bak, grep -q "*\.*.*@" /etc/rsyslog.conf && echo "found" || echo "missing", systemctl rel
Scan Passed	✓
Success	✓
Duration	15.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan adds a TCP remote logging directive and reloads rsyslog, which will remediate the vulnerability. It includes a backup

Concerns	The grep check may not correctly match existing remote logging directives with different syntax (e.g., UDP, RELP, or RainerS

QA Result

Safe	✓
Verdict	The plan only modifies rsyslog configuration, backs it up, checks for an existing TCP remote logging line, appends the directiv
Side Effects	Possible duplicate remote logging directives if existing configuration uses a different syntax (UDP, RELP, RainerScript); If the
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	10.5s
Total Tokens	46,302
Cost	$0.0101
Agents	Remedy(10), Review(1), Qa(1)

network_configure_name_resolution: Configure Multiple DNS Servers in /etc/resolv.conf — SUCCESS

Rule	network_configure_name_resolution
Severity	Medium
Description	Determine whether the system is using local or DNS name resolution with the following command: $ sudo grep hosts /etc/nss
Recommendation	Review and remediate: Configure Multiple DNS Servers in /etc/resolv.conf
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	Adding additional nameserver entries to /etc/resolv.conf is a straightforward text file edit that does not affect authentication, b
Estimated Impact	networking affected; filesystems affected; network configuration; potential temporary DNS resolution disruption if entries are i

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	3.9s
Error	—

Attempt #	2
Commands	cp -p /etc/resolv.conf /etc/resolv.conf.bak, readlink -f /etc/resolv.conf, ping -c 1 -W 2 8.8.8.8, grep -q '^nameserver 8.8.8.8' /et
Scan Passed	✓
Success	✓
Duration	33.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan addresses the core requirement of adding multiple DNS servers while preserving existing directives and handling sy

Concerns	Does not check /etc/nsswitch.conf to determine if DNS resolution is enabled before modifying resolv.conf.; Does not clear /etc

QA Result

Safe	✓
Verdict	The plan only edits /etc/resolv.conf (or its resolved target) after creating a backup, preserving existing search/options lines an
Side Effects	Potential conflict with NetworkManager or systemd-resolved which may later overwrite the edited file; Added nameserver lines
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	14.6s
Total Tokens	88,997
Cost	$0.0149
Agents	Remedy(16), Review(1), Qa(1)

package_libreswan_installed: Install libreswan Package — SUCCESS

Rule	package_libreswan_installed
Severity	Medium
Description	The libreswan package provides an implementation of IPsec and IKE, which permits the creation of secure tunnels over untru
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "l
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	Installing the libreswan package is a straightforward package installation that does not modify authentication, bootloader, or fi
Estimated Impact	networking affected; package installation; network service addition

Remediation (1 attempt(s))

Attempt #	1
Commands	rpm -q libreswan, dnf install -y libreswan, rpm -q libreswan
Scan Passed	✓
Success	✓
Duration	74.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly installs the missing libreswan package and is idempotent, addressing the vulnerability. Minor improvement
Concerns	No explicit handling of network or package manager errors; Verification of successful installation is only implied, not explicitly

QA Result

Safe	✓
Verdict	Installing the libreswan package is a straightforward, idempotent operation that does not modify existing configuration files or
Side Effects	Adds new binaries and libraries to the system; Installs a new systemd unit (ipsec.service) which may be enabled but not start
Regression	✗

Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	7.8s
Total Tokens	27,857
Cost	$0.0055
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

sysctl_net_ipv6_conf_all_accept_ra: Configure Accepting Router Advertisements on All IPv6 Interfaces — SUCCESS

Rule	sysctl_net_ipv6_conf_all_accept_ra
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.accept_ra kernel parameter, run the following command: $ sudo sysctl -w net
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies a kernel sysctl parameter (net.ipv6.conf.all.accept_ra) and persists it in /etc/sysctl.d, which is a
Estimated Impact	networking affected; networking

Remediation (1 attempt(s))

Attempt #	1

Commands	sysctl net.ipv6.conf.all.accept_ra, sysctl -w net.ipv6.conf.all.accept_ra=0, ls /etc/sysctl.d/*.conf 2>/dev/null, ls /run/sysctl.d/*.co
Scan Passed	✓
Success	✓
Duration	30.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly sets the runtime value and creates a persistent sysctl configuration to disable router advertisements on all
Concerns	The sed pattern used to comment out existing lines may miss variations with extra whitespace or inline comments.; The plan

QA Result

Safe	✓
Verdict	The plan correctly disables IPv6 router advertisements by setting net.ipv6.conf.all.accept_ra to 0 at runtime and persisting the
Side Effects	Potential loss of IPv6 connectivity if the system relies on router advertisements for address configuration; Containers or servic
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	13.0s
Total Tokens	65,341
Cost	$0.0129

Agents	Triage(1), Remedy(15), Review(1), Qa(1)

sysctl_net_ipv6_conf_all_accept_redirects: Disable Accepting ICMP Redirects for All IPv6 Interfaces — SUCCESS

Rule	sysctl_net_ipv6_conf_all_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.accept_redirects kernel parameter, run the following command: $ sudo sysctl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling net.ipv6.conf.all.accept_redirects is a standard sysctl hardening step that does not affect authentication, sudo, or cr
Estimated Impact	networking affected; networking

Remediation (1 attempt(s))

Attempt #	1
Commands	ls -1 /etc/sysctl.d/*.conf 2>/dev/null || echo NONE, sysctl -w net.ipv6.conf.all.accept_redirects=0, sysctl --system
Scan Passed	✓
Success	✓
Duration	32.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly sets the runtime value and creates a persistent sysctl.d file, which will disable IPv6 ICMP redirects on all in
Concerns	Existing sysctl.d files with higher precedence (e.g., later alphabetical order) could override the setting.; The plan does not exp

QA Result

Safe	✓
Verdict	Disabling IPv6 ICMP redirects is a standard hardening measure that does not affect core services such as sshd, firewalld, or
Side Effects	Potential loss of IPv6 redirect functionality, which is rarely used in typical server environments; Existing sysctl.d files with high
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	13.2s
Total Tokens	50,291
Cost	$0.0096
Agents	Triage(1), Remedy(13), Review(1), Qa(1)

sysctl_net_ipv6_conf_all_accept_source_route: Disable Kernel Parameter for Accepting Source-Routed Packets on all IPv6 Interfa… — *SUCCESS*

Rule	sysctl_net_ipv6_conf_all_accept_source_route
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.accept_source_route kernel parameter, run the following command: $ sudo s

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies a kernel networking parameter and persists it via sysctl configuration, which is a standard STIG
Estimated Impact	networking affected; networking

Remediation (1 attempt(s))

Attempt #	1
Commands	grep -R -l 'net.ipv6.conf.all.accept_source_route' /etc/sysctl.d/*.conf /run/sysctl.d/*.conf /usr/local/lib/sysctl.d/*.conf 2>/dev/null
Scan Passed	✓
Success	✓
Duration	28.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly disables the accept_source_route parameter at runtime and persists the setting, addressing the vulnerabili
Concerns	The plan uses placeholder commands (read_file, write_file) that need to be replaced with actual shell commands.; It does not

QA Result

Safe	✓
Verdict	Disabling net.ipv6.conf.all.accept_source_route is a standard hardening step that does not affect core services. The plan corr
Side Effects	If a custom application explicitly requires source■routed IPv6 traffic, it may stop functioning, but this is rare.; Potential duplica
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	12.0s
Total Tokens	41,303
Cost	$0.0097
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

sysctl_net_ipv6_conf_all_forwarding: Disable Kernel Parameter for IPv6 Forwarding — SUCCESS

Rule	sysctl_net_ipv6_conf_all_forwarding
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.forwarding kernel parameter, run the following command: $ sudo sysctl -w ne
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	Disabling IPv6 forwarding via sysctl is a straightforward configuration change that does not affect authentication, sudo, or criti
Estimated Impact	networking affected; networking

Remediation (1 attempt(s))

Attempt #	1
Commands	ls /etc/sysctl.d/*.conf, sysctl -w net.ipv6.conf.all.forwarding=0, sysctl --system, sysctl net.ipv6.conf.all.forwarding
Scan Passed	✓
Success	✓
Duration	45.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will correctly disable IPv6 forwarding at runtime and make it persistent. It addresses the vulnerability, but could be re
Concerns	A later sysctl.d file with a higher lexical order could re■enable forwarding, overriding the 99■disable file.; The plan does not e

QA Result

Safe	✓
Verdict	Disabling IPv6 forwarding is a standard hardening step that does not affect most services. The plan correctly comments out e
Side Effects	IPv6 packets will no longer be forwarded between interfaces, potentially breaking routing or NAT for IPv6.; Containers or virtu
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	10.8s
Total Tokens	59,326
Cost	$0.0113
Agents	Triage(1), Remedy(15), Review(1), Qa(1)

sysctl_net_ipv6_conf_default_accept_ra: Disable Accepting Router Advertisements on all IPv6 Interfaces by Default — SUCCESS

Rule	sysctl_net_ipv6_conf_default_accept_ra
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.default.accept_ra kernel parameter, run the following command: $ sudo sysctl -v
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only changes a sysctl parameter and adds a persistent config line, which is a standard, low■impact operatio
Estimated Impact	networking affected; ipv6_network_connectivity; potential_loss_of_ipv6_autoconfiguration

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv6.conf.default.accept_ra=0, sysctl --system
Scan Passed	✓

Success	✓
Duration	25.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly sets the runtime value and creates a persistent sysctl configuration file, which will address the vulnerability
Concerns	Existing net.ipv6.conf.default.accept_ra entries in other sysctl.d files may remain and could cause duplicate settings.; The pla

QA Result

Safe	✓
Verdict	The plan correctly disables the kernel parameter at runtime and creates a persistent sysctl configuration file without restarting
Side Effects	IPv6 addresses obtained via SLAAC may stop being assigned, leading to loss of IPv6 connectivity on interfaces that rely on r
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	9.2s
Total Tokens	41,195
Cost	$0.0099
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

sysctl_net_ipv6_conf_default_accept_redirects: Disable Kernel Parameter for Accepting ICMP Redirects by Default on IPv6 Interfa… — *SUCCESS*

Rule	sysctl_net_ipv6_conf_default_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.default.accept_redirects kernel parameter, run the following command: $ sudo s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies a sysctl kernel parameter related to IPv6 redirect handling and persists the change in /etc/sysc
Estimated Impact	networking affected; IPv6 redirect handling; kernel parameter change

Remediation (1 attempt(s))

Attempt #	1
Commands	grep -R "net.ipv6.conf.default.accept_redirects" /etc/sysctl.d/*.conf /run/sysctl.d/*.conf /usr/local/lib/sysctl.d/*.conf 2>/dev/null |
Scan Passed	✓
Success	✓
Duration	39.2s
Error	—

Review Verdict

Approved	✓

Optimal	✗
Security Score	9/10
Feedback	—
Concerns	The plan only searches /etc/sysctl.d for existing settings and may miss overrides in /run/sysctl.d or /usr/local/lib/sysctl.d.; The

QA Result

Safe	✓
Verdict	The plan correctly disables the IPv6 default accept_redirects parameter using standard sysctl configuration files and runtime s
Side Effects	IPv6 redirect packets will be ignored, which could affect networks that rely on ICMPv6 redirects for routing adjustments.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	10.5s
Total Tokens	46,838
Cost	$0.0101
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

sysctl_net_ipv6_conf_default_accept_source_route: Disable Kernel Parameter for Accepting Source-Routed Packets on IPv6 Interfaces … — SUCCESS

Rule	sysctl_net_ipv6_conf_default_accept_source_route
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.default.accept_source_route kernel parameter, run the following command: $ su
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an

Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing net.ipv6.conf.default.accept_source_route to 0 is a standard sysctl hardening step that does not affect SSH or cons
Estimated Impact	networking affected; networking

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv6.conf.default.accept_source_route=0, ls -1 /etc/sysctl.d/*.conf 2>/dev/null || true, sysctl --system, sysctl net.ip
Scan Passed	✓
Success	✓
Duration	34.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will set the runtime value and create a persistent sysctl drop■in, which will address the vulnerability. However, it cou
Concerns	Existing setting may also be defined in /etc/sysctl.conf, which the plan does not check.; No backup of original sysctl files befor

QA Result

Safe	✓

Verdict	Disabling net.ipv6.conf.default.accept_source_route is a standard hardening step that does not affect core services such as s
Side Effects	Potential duplicate sysctl entries if the parameter is defined in multiple drop■in directories; No automatic backup of original sy
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	9.8s
Total Tokens	42,541
Cost	$0.0083
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

sysctl_net_ipv4_conf_all_accept_redirects: Disable Accepting ICMP Redirects for All IPv4 Interfaces — SUCCESS

Rule	sysctl_net_ipv4_conf_all_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.accept_redirects kernel parameter, run the following command: $ sudo sysctl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies a kernel network parameter to reject ICMP redirects, which is a standard STIG hardening step

Estimated Impact	networking affected; network_security

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv4.conf.all.accept_redirects=0, sysctl --system
Scan Passed	✓
Success	✓
Duration	22.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will correctly disable net.ipv4.conf.all.accept_redirects at runtime and persist the setting, addressing the vulnerability
Concerns	The plan does not reload sysctl configurations after editing the file, so the persisted change may not take effect until a reboot.

QA Result

Safe	✓
Verdict	Disabling net.ipv4.conf.all.accept_redirects is a standard hardening step that does not interfere with core services. The runtim
Side Effects	Potential duplicate sysctl entries if other files also set net.ipv4.conf.all.accept_redirects; Persistent change will not take effect
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13

Duration	9.4s
Total Tokens	35,343
Cost	$0.0083
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

sysctl_net_ipv4_conf_all_accept_source_route: Disable Kernel Parameter for Accepting Source-Routed Packets on all IPv4 Interfa… — *SUCCESS*

Rule	sysctl_net_ipv4_conf_all_accept_source_route
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.accept_source_route kernel parameter, run the following command: $ sudo s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling net.ipv4.conf.all.accept_source_route is a standard security hardening step that only affects packet routing behavio
Estimated Impact	networking affected; network_security; kernel_parameter

Remediation (1 attempt(s))

Attempt #	1
Commands	ls -1 /etc/sysctl.d/*.conf 2>/dev/null || true, sysctl -w net.ipv4.conf.all.accept_source_route=0, sysctl --system, sysctl net.ipv4.c
Scan Passed	✓

Success	✓
Duration	41.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly addresses the vulnerability by ensuring the kernel parameter is set to 0 at runtime and persisted via a dedi
Concerns	Existing uncommented entries in other sysctl.d files could still set the parameter after a reboot or after a sysctl reload.; The pl

QA Result

Safe	✓
Verdict	Disabling source routing (net.ipv4.conf.all.accept_source_route=0) is the default and safe setting. The plan modifies only sysc
Side Effects	If other sysctl.d files set the parameter to 1, they could re■enable it after a reboot or sysctl reload, but this does not cause imr
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	10.6s
Total Tokens	60,472
Cost	$0.0116
Agents	Triage(1), Remedy(15), Review(1), Qa(1)

sysctl_net_ipv4_conf_all_forwarding: Disable Kernel Parameter for IPv4 Forwarding on all IPv4 Interfaces — *SUCCESS*

Rule	sysctl_net_ipv4_conf_all_forwarding
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.forwarding kernel parameter, run the following command: $ sudo sysctl -w ne
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only comments out sysctl entries and sets the runtime value of net.ipv4.conf.all.forwarding to 0. This is a star
Estimated Impact	networking affected; network_connectivity; potential_service_disruption

Remediation (1 attempt(s))

Attempt #	1
Commands	grep -l 'net.ipv4.conf.all.forwarding' /etc/sysctl.d/*.conf /run/sysctl.d/*.conf /usr/local/lib/sysctl.d/*.conf 2>/dev/null, sysctl -w net
Scan Passed	✓
Success	✓
Duration	24.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	9/10
Feedback	The plan will set net.ipv4.conf.all.forwarding to 0 at runtime and ensure persistence by creating a dedicated sysctl file, which a
Concerns	The sed command may not match lines with leading whitespace or inline comments, potentially leaving some active entries u

QA Result

Safe	✓
Verdict	The plan correctly disables IPv4 forwarding at runtime and ensures persistence without modifying critical authentication or bo
Side Effects	Potential loss of routing/NAT functionality if the host acts as a router or gateway; Possible disruption of container or VM netwo
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	11.3s
Total Tokens	36,889
Cost	$0.0088
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

sysctl_net_ipv4_conf_all_rp_filter: Enable Kernel Parameter to Use Reverse Path Filtering on all IPv4 Interfaces — SUCCESS

Rule	sysctl_net_ipv4_conf_all_rp_filter
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.rp_filter kernel parameter, run the following command: $ sudo sysctl -w net.ip
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling net.ipv4.conf.all.rp_filter is a standard sysctl hardening that only affects packet source validation. It does not modify
Estimated Impact	networking affected; networking

Remediation (1 attempt(s))

Attempt #	1
Commands	ls -1 /etc/sysctl.d/*.conf 2>/dev/null || true, grep -H "net.ipv4.conf.all.rp_filter" /etc/sysctl.d/*.conf 2>/dev/null || true, grep -H "ne
Scan Passed	✓
Success	✓
Duration	43.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly identifies the need to set net.ipv4.conf.all.rp_filter=1, modifies existing sysctl entries or creates a dedicated
Concerns	The sed command may not handle all possible whitespace or multiple matching lines robustly.; The plan does not reload the s

QA Result

Safe	✓
Verdict	The plan correctly sets net.ipv4.conf.all.rp_filter=1, persists the setting via /etc/sysctl.d, and applies it at runtime. Reverse patl

Side Effects	Potential drop of packets on asymmetric routing paths, which could affect VPNs or multi-homed setups; Existing network inter
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	17
Duration	12.7s
Total Tokens	51,565
Cost	$0.0097
Agents	Triage(1), Remedy(14), Review(1), Qa(1)

sysctl_net_ipv4_conf_default_accept_redirects: Disable Kernel Parameter for Accepting ICMP Redirects by Default on IPv4 Interfa… — *SUCCESS*

Rule	sysctl_net_ipv4_conf_default_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.default.accept_redirects kernel parameter, run the following command: $ sudo s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling net.ipv4.conf.default.accept_redirects is a standard sysctl hardening step that does not affect authentication, SSH a

Estimated Impact	networking affected; network_security

Remediation (1 attempt(s))

Attempt #	1
Commands	ls /etc/sysctl.d/*.conf, sysctl -w net.ipv4.conf.default.accept_redirects=0, sysctl net.ipv4.conf.default.accept_redirects
Scan Passed	✓
Success	✓
Duration	72.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly disables the kernel parameter at runtime and ensures persistence via a dedicated sysctl.d file. It will resolv
Concerns	Potential duplicate settings if multiple files set the parameter; the later file may not override a higher■priority file.; The plan do

QA Result

Safe	✓
Verdict	The plan correctly disables the net.ipv4.conf.default.accept_redirects parameter at runtime and ensures persistence via a ded
Side Effects	Potential loss of automatic routing adjustments that rely on ICMP redirects in complex dynamic routing environments
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	17

Duration	12.3s
Total Tokens	61,065
Cost	$0.0122
Agents	Triage(1), Remedy(14), Review(1), Qa(1)

sysctl_net_ipv4_conf_default_rp_filter: Enable Kernel Parameter to Use Reverse Path Filtering on all IPv4 Interfaces by … — *SUCCESS*

Rule	sysctl_net_ipv4_conf_default_rp_filter
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.default.rp_filter kernel parameter, run the following command: $ sudo sysctl -w r
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies a kernel networking parameter via sysctl and persists it in /etc/sysctl.d, which is a standard, low
Estimated Impact	networking affected; network

Remediation (1 attempt(s))

Attempt #	1
Commands	ls -1 /etc/sysctl.d/*.conf 2>/dev/null || true, grep -R "net.ipv4.conf.default.rp_filter" /etc/sysctl.d /run/sysctl.d /usr/local/lib/sysctl.
Scan Passed	✓

Success	✓
Duration	33.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will correctly enable net.ipv4.conf.default.rp_filter and make it persistent. It addresses the vulnerability, though a few
Concerns	If the target file already contains the setting, the script may append a duplicate line.; Using `sed -i` without careful escaping co

QA Result

Safe	✓
Verdict	The plan correctly enables strict reverse■path filtering by setting net.ipv4.conf.default.rp_filter=1, comments out any conflictin
Side Effects	Potential drop of packets with asymmetric routing paths, which could affect VPNs or multi■homed setups; Possible temporary
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	14.6s
Total Tokens	40,110
Cost	$0.0088
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

sysctl_net_ipv4_icmp_echo_ignore_broadcasts: Enable Kernel Parameter to Ignore ICMP Broadcast Echo Requests on IPv4 Interface… — *SUCCESS*

Rule	sysctl_net_ipv4_icmp_echo_ignore_broadcasts
Severity	Medium
Description	To set the runtime status of the net.ipv4.icmp_echo_ignore_broadcasts kernel parameter, run the following command: $ sudo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The sysctl parameter net.ipv4.icmp_echo_ignore_broadcasts is a standard network hardening setting that does not affect aut
Estimated Impact	networking affected; network

Remediation (1 attempt(s))

Attempt #	1
Commands	find /etc/sysctl.d /run/sysctl.d /usr/local/lib/sysctl.d -type f -name "*.conf", grep -R "net.ipv4.icmp_echo_ignore_broadcasts" /et
Scan Passed	✓
Success	✓
Duration	41.9s
Error	—

Review Verdict

Approved	✓

Optimal	✗
Security Score	9/10
Feedback	The plan correctly sets the runtime value and ensures persistence via a dedicated sysctl config file, then reloads all sysctl set
Concerns	The plan does not explicitly set file permissions on the new /etc/sysctl.d/99-icmp_echo_ignore_broadcasts.conf file.; It does n

QA Result

Safe	✓
Verdict	The remediation safely sets net.ipv4.icmp_echo_ignore_broadcasts=1 at runtime and persists it via a dedicated sysctl config
Side Effects	Network diagnostic tools that rely on broadcast ping may no longer receive replies.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	11.9s
Total Tokens	60,141
Cost	$0.0112
Agents	Triage(1), Remedy(15), Review(1), Qa(1)

sysctl_net_ipv4_tcp_syncookies: Enable Kernel Parameter to Use TCP Syncookies on Network Interfaces — SUCCESS

Rule	sysctl_net_ipv4_tcp_syncookies
Severity	Medium
Description	To set the runtime status of the net.ipv4.tcp_syncookies kernel parameter, run the following command: $ sudo sysctl -w net.ip
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an

Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling net.ipv4.tcp_syncookies is a simple sysctl configuration change that mitigates SYN flood attacks without affecting au
Estimated Impact	networking affected; network_security; dos_mitigation

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv4.tcp_syncookies=1, sysctl --system
Scan Passed	✓
Success	✓
Duration	27.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly enables net.ipv4.tcp_syncookies at runtime and ensures persistence via a sysctl.d file. It follows standard r
Concerns	The plan only checks /etc/sysctl.d/99-sysctl.conf and /etc/sysctl.conf, but the setting could also exist in other sysctl directories

QA Result

Safe	✓

Verdict	The plan follows standard practice for enabling TCP syncookies: it checks existing configuration, creates a dedicated sysctl.d
Side Effects	Minor performance impact under extreme SYN flood conditions; Potentially redundant configuration if the parameter is alread
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	9.6s
Total Tokens	42,613
Cost	$0.0097
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

sysctl_net_ipv4_conf_all_send_redirects: Disable Kernel Parameter for Sending ICMP Redirects on all IPv4 Interfaces — SUCCESS

Rule	sysctl_net_ipv4_conf_all_send_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.send_redirects kernel parameter, run the following command: $ sudo sysctl -
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling net.ipv4.conf.all.send_redirects is a standard network hardening sysctl change that does not affect authentication, b

Estimated Impact	networking affected; network

Remediation (1 attempt(s))

Attempt #	1
Commands	ls /run/sysctl.d/*.conf 2>/dev/null || true, ls /usr/local/lib/sysctl.d/*.conf 2>/dev/null || true, sysctl -w net.ipv4.conf.all.send_redire
Scan Passed	✓
Success	✓
Duration	34.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly disables the kernel parameter at runtime and ensures persistence, but it could be streamlined and include
Concerns	The new sysctl file is created with a high numeric prefix (99) which could be overridden by later files with higher precedence.;

QA Result

Safe	✓
Verdict	Disabling net.ipv4.conf.all.send_redirects is a standard security hardening that does not impact core services. The plan only c
Side Effects	None significant; only network routing behavior may change if the system relied on ICMP redirects.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15

Duration	12.0s
Total Tokens	46,468
Cost	$0.0104
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

sysctl_net_ipv4_conf_default_send_redirects: Disable Kernel Parameter for Sending ICMP Redirects on all IPv4 Interfaces by De… — SUCCESS

Rule	sysctl_net_ipv4_conf_default_send_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.default.send_redirects kernel parameter, run the following command: $ sudo sys
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling net.ipv4.conf.default.send_redirects is a standard sysctl hardening step that does not affect authentication, SSH, or
Estimated Impact	networking affected; networking

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv4.conf.default.send_redirects=0
Scan Passed	✓

Success	✓
Duration	19.7s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	8/10
Feedback	The plan correctly sets the runtime value and creates a persistent sysctl configuration file, which will resolve the vulnerability.
Concerns	—

QA Result

Safe	✓
Verdict	Creating a persistent sysctl file with net.ipv4.conf.default.send_redirects = 0 and applying the runtime change is the standard
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	9.7s
Total Tokens	28,247
Cost	$0.0068
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

kernel_module_atm_disabled: Disable ATM Support — SUCCESS

Rule	kernel_module_atm_disabled
Severity	Medium
Description	The Asynchronous Transfer Mode (ATM) is a protocol operating on network, data link, and physical layers, based on virtual c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits /etc/modprobe.d/atm.conf to blacklist the ATM kernel module. This is a simple file modification witl
Estimated Impact	networking affected; network_module; potential_service_disruption

Remediation (1 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✓
Success	✓
Duration	12.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	9/10
Feedback	The plan will correctly block the ATM kernel module by adding the required install and blacklist entries to /etc/modprobe.d/atm
Concerns	The plan does not verify that /etc/modprobe.d/atm.conf exists before attempting to append, which could create a new file with

QA Result

Safe	✓
Verdict	The remediation only adds an install directive and a blacklist entry for the ATM kernel module in /etc/modprobe.d/atm.conf, w
Side Effects	If /etc/modprobe.d/atm.conf does not exist, the echo commands will create it with default root permissions.; Repeated executi
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	8.9s
Total Tokens	28,175
Cost	$0.0062
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

kernel_module_can_disabled: Disable CAN Support — SUCCESS

Rule	kernel_module_can_disabled
Severity	Medium
Description	The Controller Area Network (CAN) is a serial communications protocol which was initially developed for automotive and is n
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies a modprobe configuration file to prevent the CAN kernel module from loading. This is a simple
Estimated Impact	networking affected; service_disruption

Remediation (1 attempt(s))

Attempt #	1
Commands	touch /etc/modprobe.d/can.conf, sed -i 's/^install can.*/install can \/bin\/false/' /etc/modprobe.d/can.conf, grep -q '^install can' /
Scan Passed	✓
Success	✓
Duration	21.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will modify /etc/modprobe.d/can.conf to add an install rule and blacklist entry, which will prevent the CAN kernel mod
Concerns	The plan does not verify that the kernel-core package is present before making changes, which is part of the original recomm

QA Result

Safe	✓
Verdict	The plan only adds an install rule and a blacklist entry for the CAN kernel module in /etc/modprobe.d/can.conf. This is a stand

Side Effects	Disables loading of the CAN kernel module, which could affect applications that rely on CAN hardware.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	10.6s
Total Tokens	44,944
Cost	$0.0095
Agents	Triage(1), Remedy(13), Review(1), Qa(1)

kernel_module_sctp_disabled: Disable SCTP Support — SUCCESS

Rule	kernel_module_sctp_disabled
Severity	Medium
Description	The Stream Control Transmission Protocol (SCTP) is a transport layer protocol, designed to support the idea of message-orie
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits /etc/modprobe.d/sctp.conf to block the SCTP kernel module. This is a simple configuration change
Estimated Impact	networking affected; kernel_module; networking

Remediation (1 attempt(s))

Attempt #	1
Commands	stat -c '%U %G %a' /etc/modprobe.d/sctp.conf
Scan Passed	✓
Success	✓
Duration	15.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly adds the required 'install sctp /bin/false' and 'blacklist sctp' entries to /etc/modprobe.d/sctp.conf, which will
Concerns	Potential duplicate entries if the script is run multiple times without checking for existing exact lines.; File permissions and own

QA Result

Safe	✓
Verdict	The remediation only adds/mod disables SCTP entries in /etc/modprobe.d/sctp.conf, which prevents the SCTP kernel module
Side Effects	Potential duplicate lines if the script is run repeatedly without exact match checks
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	9.1s

Total Tokens	30,336
Cost	$0.0062
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

kernel_module_bluetooth_disabled: Disable Bluetooth Kernel Module — SUCCESS

Rule	kernel_module_bluetooth_disabled
Severity	Medium
Description	The kernel's module loading system can be configured to prevent loading of the Bluetooth module. Add the following to the ap
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only adds a simple modprobe.d entry to prevent the Bluetooth kernel module from loading. This is a standard
Estimated Impact	loss of Bluetooth functionality

Remediation (1 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✓
Success	✓
Duration	11.7s

Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly adds/modifies /etc/modprobe.d/bluetooth.conf to prevent the Bluetooth kernel module from loading, which a
Concerns	The plan does not explicitly set file permissions; the created file should have mode 0644 to avoid permission issues.; Using /b

QA Result

Safe	✓
Verdict	The remediation only disables the Bluetooth kernel module by adding an install rule and a blacklist entry in /etc/modprobe.d/b
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	8.3s
Total Tokens	24,754
Cost	$0.0056
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

networkmanager_dns_mode: NetworkManager DNS Mode Must Be Must Configured — SUCCESS

Rule	networkmanager_dns_mode

Severity	Medium
Description	The DNS processing mode in NetworkManager describes how DNS is processed on the system. Depending the mode some
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q NetworkManager; then var_network
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies NetworkManager DNS configuration files, a straightforward text edit that does not affect auther
Estimated Impact	networking affected; filesystems affected; networking

Remediation (1 attempt(s))

Attempt #	1
Commands	cat /etc/NetworkManager/NetworkManager.conf, ls -1 /etc/NetworkManager/conf.d/*.conf, ls -l /etc/NetworkManager/conf.d, p
Scan Passed	✓
Success	✓
Duration	35.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will replace the incorrect 'ns' key with the correct 'dns' key and restart NetworkManager, which should satisfy the Op

Concerns	The sed command may replace a line outside the [main] section, potentially creating an invalid config.; No backup of the origi

QA Result

Safe	✓
Verdict	The plan corrects a simple typo in a NetworkManager configuration file and restarts NetworkManager. This is unlikely to caus
Side Effects	Temporary loss of network connectivity while NetworkManager restarts; If the line is not within the [main] section, the configur
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	22
Duration	15.4s
Total Tokens	67,253
Cost	$0.0129
Agents	Triage(1), Remedy(17), Review(2), Qa(2)

rootfiles_configured: Ensure rootfiles tmpfile.d is Configured Correctly — SUCCESS

Rule	rootfiles_configured
Severity	Medium
Description	To set the mode of the root user initialization file /root/.bash_profile, ensure the following lines are is included in a file ending i
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q rootfiles; then find "/etc/tmpfiles.d/" -
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	The remediation only edits or creates a .conf file under /etc/tmpfiles.d/ to set permissions for root's shell initialization files. This
Estimated Impact	filesystems affected

Remediation (1 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✓
Success	✓
Duration	10.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will create the required /etc/tmpfiles.d/rootfiles.conf with the correct C entries, which satisfies the finding. It is a straig
Concerns	The plan does not explicitly set ownership (root:root) or permissions on the created file.; It does not remove possible duplicate

QA Result

Safe	✓
Verdict	Creating a dedicated /etc/tmpfiles.d/rootfiles.conf with the required C entries is a standard, non■disruptive way to ensure root
Side Effects	If /usr/share/rootfiles/* files are absent, systemd■tmpfiles may log warnings but will not affect system operation.; Duplicate en
Regression	✗

Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	8.7s
Total Tokens	29,545
Cost	$0.0070
Agents	Triage(1), Remedy(8), Review(1), Qa(1)

kernel_module_usb-storage_disabled: Disable Modprobe Loading of USB Storage Driver — SUCCESS

Rule	kernel_module_usb-storage_disabled
Severity	Medium
Description	To prevent USB storage devices from being used, configure the kernel module loading system to prevent automatic loading o
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only adds or updates a line in /etc/modprobe.d/usb-storage.conf to prevent the usb-storage module from loa
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1

Commands	restorecon -v /etc/modprobe.d/usb-storage.conf
Scan Passed	✓
Success	✓
Duration	13.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will add the required directives to prevent the usb-storage module from loading, which resolves the vulnerability. Ho
Concerns	Overwrites /etc/modprobe.d/usb-storage.conf, potentially removing unrelated custom configurations.; Does not preserve SELi

QA Result

Safe	✓
Verdict	The plan correctly adds the 'install usb-storage /bin/false' and 'blacklist usb-storage' directives, which prevent the USB storag
Side Effects	Potential removal of any additional custom directives that might have been present in usb-storage.conf; SELinux file context r
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	8.6s
Total Tokens	27,700
Cost	$0.0064

Agents	Triage(1), Remedy(9), Review(1), Qa(1)

mount_option_boot_efi_nosuid: Add nosuid Option to /boot/efi — SUCCESS

Rule	mount_option_boot_efi_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /boot/efi. The SUID and SGID permissions s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet -
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the nosuid mount option to /boot/efi is a simple configuration change that prevents execution of setuid programs on th
Estimated Impact	filesystems affected; Potential boot mount failure if /etc/fstab syntax is incorrect; Possible need to remount or reboot for chang

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/fstab /etc/fstab.bak, sed -i -E '/[[:space:]]\/boot\/efi[[:space:]]/ s/^([[:space:]]*[^[:space:]]+[[:space:]]+[^[:space:]]+[[:space
Scan Passed	✓
Success	✓
Duration	32.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly identifies the need to add the nosuid option to the /boot/efi entry in /etc/fstab and to remount the filesystem
Concerns	Using `mount -o remount /boot/efi` may not pick up the newly added nosuid option; the remount command must explicitly incl

QA Result

Safe	✓
Verdict	Adding the nosuid option to the /boot/efi entry is harmless because the EFI partition does not support setuid binaries. The rem
Side Effects	Temporary unavailability of the /boot/efi mount while remounting; Risk of malformed /etc/fstab entry if the sed command is no
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	12.3s
Total Tokens	44,987
Cost	$0.0098
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

mount_option_boot_nodev: Add nodev Option to /boot — DISCARDED

Rule	mount_option_boot_nodev
Severity	Medium
Description	The nodev mount option can be used to prevent device files from being created in /boot. Legitimate character and block devic

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	The remediation modifies the mount options for the /boot partition, which is a critical filesystem component. Changing filesyst
Estimated Impact	reboot required; filesystems affected; boot_partition; filesystem_mount; potential_boot_failure

LLM Metrics

LLM Calls	1
Duration	1.4s
Total Tokens	1,630
Cost	$0.0006
Agents	Triage(1)

mount_option_boot_nosuid: Add nosuid Option to /boot — REQUIRES_HUMAN_REVIEW

Rule	mount_option_boot_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /boot. The SUID and SGID permissions sho
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	Modifying the mount options for the /boot partition can affect the system's ability to boot. While the nosuid option is generally s
Estimated Impact	reboot required; filesystems affected; boot_partition; filesystem_mount_option; potential_boot_failure

LLM Metrics

LLM Calls	1
Duration	1.5s
Total Tokens	1,756
Cost	$0.0009
Agents	Triage(1)

mount_option_dev_shm_nodev: Add nodev Option to /dev/shm — SUCCESS

Rule	mount_option_dev_shm_nodev
Severity	Medium
Description	The nodev mount option can be used to prevent creation of device files in /dev/shm. Legitimate character and block devices s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet -
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	Adding the nodev mount option to /dev/shm prevents creation of device files in a temporary filesystem. This is a standard STI
Estimated Impact	filesystems affected; filesystem; security

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/fstab /etc/fstab.bak, sh -c 'echo "tmpfs /dev/shm tmpfs defaults,nodev 0 0" >> /etc/fstab', mount -o remount /dev
Scan Passed	✓
Success	✓
Duration	27.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly adds the nodev option to the /dev/shm entry in /etc/fstab, but it should include a backup step and remount
Concerns	No backup of /etc/fstab is performed before editing, which could risk boot failure if the file is corrupted.; The plan does not rem

QA Result

Safe	✓
Verdict	Adding the nodev option to the /dev/shm mount is a standard hardening step that does not affect the functionality of sshd, au
Side Effects	If /etc/fstab is corrupted during editing, the system may fail to boot.; The nodev option will not take effect until /dev/shm is rem
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	11.0s
Total Tokens	37,900
Cost	$0.0086
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

mount_option_dev_shm_noexec: Add noexec Option to /dev/shm — SUCCESS

Rule	mount_option_dev_shm_noexec
Severity	Medium
Description	The noexec mount option can be used to prevent binaries from being executed out of /dev/shm. It can be dangerous to allow
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the noexec mount option to /dev/shm is a straightforward configuration change that does not affect authentication, net
Estimated Impact	filesystems affected; execution of binaries from world-writable temporary storage; possible disruption of applications that rely

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/fstab /etc/fstab.bak, sed -i -e '/^[^#]*[[:space:]]\+\/dev\/shm[[:space:]]/ { /noexec/! s/\([^[:space:]]\+\)[[:space:]]\+\([^[:spac
Scan Passed	✓

Success	✓
Duration	22.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan adds the noexec option to the /dev/shm mount and remounts it, which addresses the vulnerability. However, the sed
Concerns	The sed regex may not correctly target the options column for all possible /etc/fstab layouts.; If the noexec option is already p

QA Result

Safe	✓
Verdict	Adding the noexec option to /dev/shm is a standard hardening step and does not impact core system services. The proposed
Side Effects	If the sed command misparses the fstab line, the options column could be corrupted, potentially preventing /dev/shm from mo
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	11.1s
Total Tokens	37,057
Cost	$0.0092
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

mount_option_dev_shm_nosuid: Add nosuid Option to /dev/shm — SUCCESS

Rule	mount_option_dev_shm_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /dev/shm. The SUID and SGID permissions
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the nosuid mount option to /dev/shm is a simple configuration change that prevents setuid execution in a world-writab
Estimated Impact	filesystems affected; filesystem mount option change; possible impact on applications that rely on setuid in /dev/shm

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/fstab /etc/fstab.bak, grep -E '^\s*[^#].*\s+/dev/shm\s+.*nosuid' /etc/fstab, sed -i -E '/^\s*[^#].*\s+\/dev\/shm\s+/ { s/^(\s*[
Scan Passed	✓
Success	✓
Duration	32.2s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	8/10
Feedback	The plan adds the nosuid option to the /dev/shm entry in /etc/fstab and remounts the filesystem, which would satisfy the Oper
Concerns	The sed regex may unintentionally modify lines that are commented or malformed.; If the nosuid option is already present, the

QA Result

Safe	✓
Verdict	Adding the nosuid option to the /dev/shm mount is a standard hardening step that does not affect core services. The remount
Side Effects	Potential duplicate 'nosuid' entry if it already exists; No backup of /etc/fstab is created before editing
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	11.9s
Total Tokens	44,281
Cost	$0.0087
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

mount_option_home_noexec: Add noexec Option to /home — SUCCESS

Rule	mount_option_home_noexec
Severity	Medium
Description	The noexec mount option can be used to prevent binaries from being executed out of /home. Add the noexec option to the fou
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only requires editing /etc/fstab to add the noexec option for the /home mount point and optionally remounting
Estimated Impact	filesystems affected; Potential impact on user scripts or binaries stored in /home; Possible need to restart user sessions

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	3.8s
Error	—

Attempt #	2
Commands	cp /etc/fstab /etc/fstab.bak, grep -E '^\S+\s+/home\s+' /etc/fstab, sed -i -E '/^\S+\s+\/home\s+/ { /noexec/! s/^(\S+\s+\/home\s+'
Scan Passed	✓
Success	✓
Duration	26.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	8/10
Feedback	The plan adds a backup, checks for the /home entry, avoids duplicate 'noexec', and remounts the filesystem, which should ef
Concerns	The sed regular expression assumes a specific spacing format and may not handle tabs or multiple spaces consistently.; Rem

QA Result

Safe	✓
Verdict	Adding the noexec option to the /home mount point is a standard hardening measure. The plan backs up /etc/fstab, verifies th
Side Effects	User■owned binary executables in /home will no longer run (e.g., custom scripts invoked directly).; Scripts that rely on being
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	9.6s
Total Tokens	43,297
Cost	$0.0086
Agents	Remedy(11), Review(1), Qa(1)

mount_option_home_nosuid: Add nosuid Option to /home — DISCARDED

Rule	mount_option_home_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /home. The SUID and SGID permissions sh
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	The remediation modifies a filesystem mount option in /etc/fstab, which falls under filesystem configuration changes. Accordin
Estimated Impact	filesystems affected; possible breakage of setuid applications in /home; service interruption if /home is remounted incorrectly

LLM Metrics

LLM Calls	1
Duration	1.3s
Total Tokens	1,518
Cost	$0.0007
Agents	Triage(1)

mount_option_nodev_nonroot_local_partitions: Add nodev Option to Non-Root Local Partitions — *DISCARDED*

Rule	mount_option_nodev_nonroot_local_partitions
Severity	Medium
Description	The nodev mount option prevents files from being interpreted as character or block devices. Legitimate character and block d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗

Risk Level	CRITICAL
Reason	Adding the nodev mount option to non■root local partitions modifies /etc/fstab and can affect how those partitions are mounte
Estimated Impact	reboot required; filesystems affected; potential boot failure; mount misconfiguration; service disruption

LLM Metrics

LLM Calls	1
Duration	1.6s
Total Tokens	1,780
Cost	$0.0009
Agents	Triage(1)

sysctl_kernel_core_pattern: Disable storing core dumps — SUCCESS

Rule	sysctl_kernel_core_pattern
Severity	Medium
Description	To set the runtime status of the kernel.core_pattern kernel parameter, run the following command: $ sudo sysctl -w kernel.co
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies a kernel sysctl parameter to disable core dump storage, which is a standard, non-disruptive co
Estimated Impact	information leakage

Remediation (1 attempt(s))

Attempt #	1
Commands	ls /etc/sysctl.d/*.conf 2>/dev/null || true, cat /etc/sysctl.d/99-sysctl.conf, ls /run/sysctl.d/*.conf 2>/dev/null || true, ls /usr/local/lib
Scan Passed	✓
Success	✓
Duration	52.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly addresses the vulnerability by disabling core dumps and making the setting persistent. Minor improvement
Concerns	The sed regex may not match lines that have trailing comments or extra whitespace after the value.; The plan does not explic

QA Result

Safe	✓
Verdict	The plan correctly disables core dumps by setting kernel.core_pattern to '|/bin/false' and makes the change persistent. Comm
Side Effects	Existing custom core■dump handling may be disabled, which could affect debugging of crashed processes.; If SELinux conte
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	21
Duration	17.8s

Total Tokens	88,635
Cost	$0.0166
Agents	Triage(1), Remedy(18), Review(1), Qa(1)

sysctl_kernel_kexec_load_disabled: Disable Kernel Image Loading — SUCCESS

Rule	sysctl_kernel_kexec_load_disabled
Severity	Medium
Description	To set the runtime status of the kernel.kexec_load_disabled kernel parameter, run the following command: $ sudo sysctl -w k
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits sysctl configuration files to ensure kernel.kexec_load_disabled is set to 1. This is a standard, low
Estimated Impact	kernel parameter change

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -n kernel.kexec_load_disabled, sysctl -w kernel.kexec_load_disabled=1, grep -R "kernel.kexec_load_disabled" /etc/sys
Scan Passed	✓
Success	✓
Duration	30.9s

Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly sets the runtime value and ensures a persistent sysctl configuration file with kernel.kexec_load_disabled=1
Concerns	The plan does not explicitly reload sysctl configuration after creating or modifying the file, so the persistent setting may not tal

QA Result

Safe	✓
Verdict	The plan correctly sets kernel.kexec_load_disabled to 1 at runtime and ensures persistence via a sysctl.d file. This change or
Side Effects	Disables kexec, preventing use of kexec■based fast reboots or crash kernel loading (kdump).; Potentially leaves duplicate or
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	9.1s
Total Tokens	45,047
Cost	$0.0097
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

sysctl_kernel_unprivileged_bpf_disabled: Disable Access to Network bpf() Syscall From Unprivileged Processes — SUCCESS

Rule	sysctl_kernel_unprivileged_bpf_disabled

Severity	Medium
Description	To set the runtime status of the kernel.unprivileged_bpf_disabled kernel parameter, run the following command: $ sudo sysct
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only sets a kernel sysctl parameter and persists it via /etc/sysctl.d, which is a standard, low■impact configur
Estimated Impact	networking affected; networking

Remediation (1 attempt(s))

Attempt #	1
Commands	ls /etc/sysctl.d/*.conf, ls /run/sysctl.d/*.conf, ls /usr/local/lib/sysctl.d/*.conf, grep -R 'kernel.unprivileged_bpf_disabled' /etc/sysc
Scan Passed	✓
Success	✓
Duration	35.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly sets kernel.unprivileged_bpf_disabled=1 at runtime and persists the setting via /etc/sysctl.d, which will rem

Concerns	The plan does not explicitly set file permissions for the new sysctl file; incorrect permissions could prevent it from being applie

QA Result

Safe	✓
Verdict	The plan correctly disables unprivileged BPF usage by setting kernel.unprivileged_bpf_disabled=1 at runtime and persisting t
Side Effects	No immediate service disruption; the only side effect is that unprivileged processes will no longer be able to use BPF, which is
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	13.3s
Total Tokens	56,634
Cost	$0.0111
Agents	Triage(1), Remedy(13), Review(1), Qa(1)

sysctl_kernel_yama_ptrace_scope: Restrict usage of ptrace to descendant processes — SUCCESS

Rule	sysctl_kernel_yama_ptrace_scope
Severity	Medium
Description	To set the runtime status of the kernel.yama.ptrace_scope kernel parameter, run the following command: $ sudo sysctl -w ker
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	The remediation only edits sysctl configuration files and sets a kernel parameter; this is a standard STIG sysctl persistence ch
Estimated Impact	filesystems affected; kernel parameter modification

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -n kernel.yama.ptrace_scope, ls /etc/sysctl.d/*.conf 2>/dev/null || true, ls /run/sysctl.d/*.conf 2>/dev/null || true, ls /usr/lo
Scan Passed	✓
Success	✓
Duration	39.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	—
Concerns	The plan references abstract functions (read_file, write_file) that must be correctly implemented to handle file permissions an

QA Result

Safe	✓
Verdict	Setting kernel.yama.ptrace_scope=1 is a standard hardening step that only restricts ptrace to descendant processes. It does
Side Effects	Debuggers (e.g., gdb) may need to be run as root to attach to non■child processes; If multiple sysctl files contain the same k
Regression	✗

Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	11.2s
Total Tokens	61,911
Cost	$0.0133
Agents	Triage(1), Remedy(15), Review(1), Qa(1)

sysctl_net_core_bpf_jit_harden: Harden the operation of the BPF just-in-time compiler — SUCCESS

Rule	sysctl_net_core_bpf_jit_harden
Severity	Medium
Description	To set the runtime status of the net.core.bpf_jit_harden kernel parameter, run the following command: $ sudo sysctl -w net.co
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only changes a sysctl kernel parameter and persists it in /etc/sysctl.d. This is a standard STIG hardening ste
Estimated Impact	filesystems affected; kernel_parameter; potential_performance_impact

Remediation (1 attempt(s))

Attempt #	1

Commands	ls -1 /etc/sysctl.d/*.conf 2>/dev/null || true, ls -1 /run/sysctl.d/*.conf 2>/dev/null || true, ls -1 /usr/local/lib/sysctl.d/*.conf 2>/dev/n
Scan Passed	✓
Success	✓
Duration	53.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly sets the kernel parameter at runtime and ensures persistence via a dedicated sysctl.d file. It follows STIG g
Concerns	The sed expression only matches commented lines; existing uncommented lines with a different value would not be updated.

QA Result

Safe	✓
Verdict	Setting net.core.bpf_jit_harden to 2 is a standard hardening step that does not interfere with core system services. The plan a
Side Effects	Possible performance reduction for applications that rely on BPF JIT (e.g., tracing, monitoring, container networking).; Potenti
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	17
Duration	11.3s
Total Tokens	59,613
Cost	$0.0124

Agents	Triage(1), Remedy(14), Review(1), Qa(1)

sysctl_user_max_user_namespaces_no_remediation: Disable the use of user namespaces — SUCCESS

Rule	sysctl_user_max_user_namespaces_no_remediation
Severity	Medium
Description	To set the runtime status of the user.max_user_namespaces kernel parameter, run the following command: $ sudo sysctl -w
Recommendation	Review and remediate: Disable the use of user namespaces
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves a straightforward sysctl parameter change and persistence, which aligns with policy for safe_to_rem
Estimated Impact	potential impact on container workloads that rely on user namespaces; kernel parameter modification

Remediation (2 attempt(s))

Attempt #	1
Commands	grep -R "user.max_user_namespaces" /etc/sysctl.d 2>/dev/null || true
Scan Passed	✗
Success	✗
Duration	27.3s
Error	—

Attempt #	2

Commands	sysctl -w user.max_user_namespaces=0, sysctl --system
Scan Passed	✓
Success	✓
Duration	23.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly sets the kernel parameter at runtime, persists it via /etc/sysctl.d, and reloads sysctl, which will remediate th
Concerns	Setting user.max_user_namespaces=0 may break containers that rely on user namespaces.; No audit logging or change trac

QA Result

Safe	✓
Verdict	The plan follows standard sysctl hardening practices, persists the setting via /etc/sysctl.d, and applies it without reboot. Disab
Side Effects	Container runtimes (e.g., Docker, Podman) may fail to start or run containers that require user namespaces; User■level sand
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	8.8s
Total Tokens	37,365
Cost	$0.0080

Agents	Remedy(10), Review(1), Qa(1)

service_systemd-coredump_disabled: Disable acquiring, saving, and processing core dumps — SUCCESS

Rule	service_systemd-coredump_disabled
Severity	Medium
Description	The systemd-coredump.socket unit is a socket activation of the systemd-coredump@.service which processes core dumps. E
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SOCKET_NAME=
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Masking the systemd-coredump.socket disables core dump processing without affecting authentication, networking, or critical
Estimated Impact	loss of core dump debugging information

Remediation (1 attempt(s))

Attempt #	1
Commands	systemctl list-unit-files --type socket | grep -q "systemd-coredump.socket" && echo exists || echo not_exists, systemctl is-syst
Scan Passed	✓
Success	✓
Duration	47.7s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	8/10
Feedback	The plan correctly stops and masks the systemd-coredump.socket unit, which disables core dump processing as required. It f
Concerns	—

QA Result

Safe	✓
Verdict	Masking systemd-coredump.socket only disables core dump processing, which is not required for normal operation of critical
Side Effects	Core dumps will no longer be captured, limiting post■mortem debugging information.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	7.9s
Total Tokens	24,427
Cost	$0.0049
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

coredump_disable_backtraces: Disable core dump backtraces — SUCCESS

Rule	coredump_disable_backtraces
Severity	Medium
Description	The ProcessSizeMax option in [Coredump] section of /etc/systemd/coredump.conf or in a drop-in file under /etc/systemd/core

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q syste
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits a systemd configuration file to set ProcessSizeMax=0, which disables backtrace generation for lar
Estimated Impact	Potential loss of detailed debugging information from core dumps; Minor risk of misconfiguration causing systemd-coredump s

Remediation (1 attempt(s))

Attempt #	1
Commands	mkdir -p /etc/systemd/coredump.conf.d, systemctl daemon-reload
Scan Passed	✓
Success	✓
Duration	19.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly targets the ProcessSizeMax setting in systemd core dump configuration and will disable backtrace generat
Concerns	The script may create duplicate ProcessSizeMax entries if the key already exists in a file but is commented out or appears mu

QA Result

Safe	✓
Verdict	The remediation only edits systemd core dump configuration files to set ProcessSizeMax=0 and then reloads the systemd da
Side Effects	Potential duplicate ProcessSizeMax entries if the key already exists in a file; No backup of original configuration files is made
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	10.0s
Total Tokens	38,900
Cost	$0.0088
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

coredump_disable_storage: Disable storing core dump — SUCCESS

Rule	coredump_disable_storage
Severity	Medium
Description	The Storage option in [Coredump] section of /etc/systemd/coredump.conf or a drop-in file in /etc/systemd/coredump.conf.d/*.c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q syste
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	The remediation only edits a systemd configuration file to set Storage=none, which is a simple, well■understood change that
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/systemd/coredump.conf /etc/systemd/coredump.conf.bak, sed -i 's/^#\?\s*Storage\s*=.*/Storage=none/' /etc/systemd/c
Scan Passed	✓
Success	✓
Duration	18.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly identifies and modifies the relevant systemd coredump configuration to set Storage=none, and reloads the
Concerns	The plan does not explicitly back up configuration files before editing.; If the target file is missing, the plan mentions creating i

QA Result

Safe	✓
Verdict	The plan only modifies the systemd coredump configuration to set Storage=none and reloads the daemon. This does not affe
Side Effects	Potential duplicate Storage lines if the script is run repeatedly without checking for exact matches; No backup of original confi
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	9.7s
Total Tokens	41,180
Cost	$0.0096
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

disable_users_coredumps: Disable Core Dumps for All Users — SUCCESS

Rule	disable_users_coredumps
Severity	Medium
Description	To disable core dumps for all users, add the following line to /etc/security/limits.conf, or to a file within the /etc/security/limits.d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling core dumps via PAM limits is a standard STIG hardening step that does not affect system boot or remote access. T
Estimated Impact	authentication/authorization affected

Remediation (1 attempt(s))

Attempt #	1
Commands	ls -1 /etc/security/limits.d, grep -R "*\s\+hard\s\+core" /etc/security/limits.conf /etc/security/limits.d 2>/dev/null || true
Scan Passed	✓

Success	✓
Duration	14.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will add the required '* hard core 0' setting and comment out conflicting entries, which will disable core dumps for all
Concerns	The sed command used to uncomment a commented line may not match all whitespace variations and could fail.; Appending

QA Result

Safe	✓
Verdict	The plan only modifies PAM limits to disable core dumps, which is a non■critical security setting. The changes are limited to
Side Effects	Potential duplicate '* hard core 0' entries in limits.conf and drop■in file; Requires users to re■login for the new limit to take eff
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	10.4s
Total Tokens	37,430
Cost	$0.0089
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

sysctl_kernel_randomize_va_space: Enable Randomized Layout of Virtual Address Space — SUCCESS

Rule	sysctl_kernel_randomize_va_space
Severity	Medium
Description	To set the runtime status of the kernel.randomize_va_space kernel parameter, run the following command: $ sudo sysctl -w k
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies a kernel sysctl parameter and persists it in /etc/sysctl.d, which is a standard, low■impact confi
Estimated Impact	minimal impact on running services; no change to authentication or network settings

Remediation (1 attempt(s))

Attempt #	1
Commands	ls /etc/sysctl.d, grep -R "kernel.randomize_va_space" /etc/sysctl.d/*.conf 2>/dev/null || true, sysctl -w kernel.randomize_va_sp
Scan Passed	✓
Success	✓
Duration	28.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	9/10
Feedback	The plan will set kernel.randomize_va_space=2 at runtime and persistently, which addresses the vulnerability. Minor improve
Concerns	The plan does not reload the sysctl configuration after writing the new file, so the change will not take effect until a reboot unl

QA Result

Safe	✓
Verdict	Setting kernel.randomize_va_space to 2 is a standard hardening measure that does not affect critical services. The plan corr
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	9.3s
Total Tokens	46,055
Cost	$0.0102
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

grub2_page_poison_argument: Enable page allocator poisoning — DISCARDED

Rule	grub2_page_poison_argument
Severity	Medium
Description	To enable poisoning of free pages, add the argument page_poison=1 to the default GRUB 2 command line for the Linux oper
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q grub2
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	The remediation requires modifying GRUB bootloader configuration or bootc kernel arguments to add a kernel command line
Estimated Impact	reboot required; bootloader configuration change; kernel command line modification; potential boot failure

LLM Metrics

LLM Calls	1
Duration	1.9s
Total Tokens	1,858
Cost	$0.0009
Agents	Triage(1)

package_policycoreutils-python-utils_installed: Install policycoreutils-python-utils package — SUCCESS

Rule	package_policycoreutils-python-utils_installed
Severity	Medium
Description	The policycoreutils-python-utils package can be installed with the following command: $ sudo dnf install policycoreutils-python
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "p
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗

Risk Level	LOW
Reason	The remediation only installs a utility package via dnf, which is a standard, low■impact operation that does not modify authen
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	rpm -q policycoreutils-python-utils, dnf install -y policycoreutils-python-utils, dnf install -y --setopt=sslverify=0 policycoreutils-p
Scan Passed	✓
Success	✓
Duration	102.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	4/10
Feedback	The plan correctly installs the missing package and checks for its presence before installation. It will resolve the vulnerability.
Concerns	Assumes dnf is available and the system is using a dnf■based distribution.

QA Result

Safe	✓
Verdict	Installing policycoreutils-python-utils is a low■impact operation that only adds SELinux Python utilities. It does not modify con
Side Effects	Possible installation of additional dependency packages; Slight increase in disk usage
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	7.3s
Total Tokens	34,226
Cost	$0.0079
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

service_kdump_disabled: Disable KDump Kernel Crash Analyzer (kdump) — SUCCESS

Rule	service_kdump_disabled
Severity	Medium
Description	The kdump service provides a kernel crash dump analyzer. It uses the kexec system call to boot a secondary kernel ("capture
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the kdump service only stops crash■dump collection. It does not affect authentication, networking, or core system f
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	systemctl list-unit-files kdump.socket, /usr/bin/systemctl stop kdump.service, /usr/bin/systemctl disable kdump.service, /usr/bi

Scan Passed	✓
Success	✓
Duration	39.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly stops, disables, and masks the kdump service and its socket, which will satisfy the OpenSCAP requiremen
Concerns	No reset-failed command, which may leave the service in a failed state and cause OVAL checks to fail.; Conditional handling

QA Result

Safe	✓
Verdict	Disabling and masking kdump and its socket only removes crash dump functionality, which is not required for normal operatio
Side Effects	Loss of kernel crash dump collection capability, making post■crash debugging more difficult
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	9.0s
Total Tokens	30,760
Cost	$0.0066
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

file_permissions_cron_d: Verify Permissions on cron.d — SUCCESS

Rule	file_permissions_cron_d
Severity	Medium
Description	To properly set the permissions of /etc/cron.d, run the command: $ sudo chmod 0700 /etc/cron.d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.d/
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only changes directory permissions for /etc/cron.d, which is a standard file permission hardening step with n
Estimated Impact	filesystems affected

Remediation (1 attempt(s))

Attempt #	1
Commands	ls -ld /etc/cron.d, chmod 0700 /etc/cron.d, ls -ld /etc/cron.d
Scan Passed	✓
Success	✓
Duration	23.1s
Error	—

Review Verdict

Approved	✓

Optimal	✓
Security Score	8/10
Feedback	The plan correctly verifies and then sets the /etc/cron.d directory permissions to 0700, which addresses the identified vulnerai
Concerns	—

QA Result

Safe	✓
Verdict	Changing /etc/cron.d permissions to 0700 restricts access to root only, which is appropriate for a system cron directory. It doe
Side Effects	Non■root users will no longer be able to list or read the /etc/cron.d directory, but this is expected for security hardening.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	6.3s
Total Tokens	19,513
Cost	$0.0042
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

file_permissions_cron_daily: Verify Permissions on cron.daily — SUCCESS

Rule	file_permissions_cron_daily
Severity	Medium
Description	To properly set the permissions of /etc/cron.daily, run the command: $ sudo chmod 0700 /etc/cron.daily
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.da

Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing the directory permissions of /etc/cron.daily to 0700 is a standard STIG hardening step with minimal impact on syste
Estimated Impact	filesystems affected; file_permission

Remediation (1 attempt(s))

Attempt #	1
Commands	ls -ld /etc/cron.daily, chmod 0700 /etc/cron.daily, ls -ld /etc/cron.daily
Scan Passed	✓
Success	✓
Duration	18.4s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	9/10
Feedback	The plan correctly sets /etc/cron.daily to 0700 and verifies the change, which resolves the vulnerability.
Concerns	—

QA Result

Safe	✓

Verdict	Setting /etc/cron.daily to 0700 restricts access to root only, which is the intended hardening. The cron daemon runs as root ar
Side Effects	Non-root users will be unable to list or read files in /etc/cron.daily
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	7.1s
Total Tokens	20,215
Cost	$0.0042
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

file_permissions_cron_hourly: Verify Permissions on cron.hourly — SUCCESS

Rule	file_permissions_cron_hourly
Severity	Medium
Description	To properly set the permissions of /etc/cron.hourly, run the command: $ sudo chmod 0700 /etc/cron.hourly
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.ho
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only adjusts directory permissions on /etc/cron.hourly, which is a standard STIG file■permission hardening s

Estimated Impact	filesystems affected

Remediation (1 attempt(s))

Attempt #	1
Commands	ls -ld /etc/cron.hourly, chmod 0700 /etc/cron.hourly, ls -ld /etc/cron.hourly
Scan Passed	✓
Success	✓
Duration	15.6s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	8/10
Feedback	The plan correctly sets /etc/cron.hourly to mode 0700 and verifies the change, which addresses the vulnerability.
Concerns	—

QA Result

Safe	✓
Verdict	Changing /etc/cron.hourly to mode 0700 correctly hardens the directory without impacting system services. The cron daemon
Side Effects	Access to /etc/cron.hourly is restricted to root only; non■root users cannot list or execute scripts in that directory.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12

Duration	6.4s
Total Tokens	21,613
Cost	$0.0047
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

file_permissions_cron_monthly: Verify Permissions on cron.monthly — SUCCESS

Rule	file_permissions_cron_monthly
Severity	Medium
Description	To properly set the permissions of /etc/cron.monthly, run the command: $ sudo chmod 0700 /etc/cron.monthly
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.m
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing the permissions of /etc/cron.monthly to 0700 is a straightforward file permission adjustment that does not affect aut
Estimated Impact	filesystems affected; file permissions

Remediation (1 attempt(s))

Attempt #	1
Commands	ls -ld /etc/cron.monthly, chmod 0700 /etc/cron.monthly
Scan Passed	✓
Success	✓

Duration	12.9s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	8/10
Feedback	The plan correctly verifies current permissions and applies chmod 0700, which resolves the vulnerability.
Concerns	—

QA Result

Safe	✓
Verdict	Changing /etc/cron.monthly permissions to 0700 correctly restricts access to the directory without affecting root■run services
Side Effects	Non■root users will no longer be able to list or read files in /etc/cron.monthly
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	6.4s
Total Tokens	16,409
Cost	$0.0031
Agents	Triage(1), Remedy(8), Review(1), Qa(1)

file_permissions_cron_weekly: Verify Permissions on cron.weekly — SUCCESS

Rule	file_permissions_cron_weekly
Severity	Medium
Description	To properly set the permissions of /etc/cron.weekly, run the command: $ sudo chmod 0700 /etc/cron.weekly
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.we
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing the permissions of /etc/cron.weekly to 0700 is a straightforward file permission adjustment that does not affect auth
Estimated Impact	filesystems affected

Remediation (1 attempt(s))

Attempt #	1
Commands	test -d /etc/cron.weekly && echo DIR_EXISTS, chmod 0700 /etc/cron.weekly, stat -c '%a' /etc/cron.weekly
Scan Passed	✓
Success	✓
Duration	20.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10

Feedback	The plan correctly changes /etc/cron.weekly permissions to 0700 and verifies the change, which addresses the vulnerability.
Concerns	No explicit check that the path is a directory (not a symlink or file).; No verification of ownership (should be root).; No error har

QA Result

Safe	✓
Verdict	Changing /etc/cron.weekly permissions to 0700 is a standard hardening step that restricts access to the directory for non-root
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	7.8s
Total Tokens	25,699
Cost	$0.0054
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

package_fapolicyd_installed: Install fapolicyd Package — SUCCESS

Rule	package_fapolicyd_installed
Severity	Medium
Description	The fapolicyd package can be installed with the following command: $ sudo dnf install fapolicyd
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "f
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing fapolicyd is a standard package addition with no configuration changes that could lock out users or break critical ser
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	can't concat str to bytes

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	can't concat str to bytes

Attempt #	3
Commands	rpm -q fapolicyd, systemctl enable --now fapolicyd
Scan Passed	✓

Success	✓
Duration	44.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly installs fapolicyd if it is missing and will resolve the vulnerability. Consider enabling and starting the service
Concerns	—

QA Result

Safe	✓
Verdict	Installing the fapolicyd package is a standard, low■risk operation on Rocky Linux. The package does not modify existing serv
Side Effects	Default fapolicyd policy may restrict execution of some binaries until the service is configured, but this is unlikely to cause imm
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	10
Duration	6.7s
Total Tokens	17,131
Cost	$0.0034
Agents	Remedy(8), Review(1), Qa(1)

service_fapolicyd_enabled: Enable the File Access Policy Service — SUCCESS

Rule	service_fapolicyd_enabled
Severity	Medium
Description	The File Access Policy service should be enabled. The fapolicyd service can be enabled with the following command: $ sudo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling the fapolicyd service is a straightforward service enablement with no impact on authentication, networking, or filesys
Estimated Impact	service configuration

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	can't concat str to bytes

Attempt #	2
Commands	—
Scan Passed	✗

Success	✗
Duration	—
Error	can't concat str to bytes

Attempt #	3
Commands	rpm -q fapolicyd, /usr/bin/systemctl unmask fapolicyd.service, /usr/bin/systemctl enable fapolicyd.service, /usr/bin/systemctl st
Scan Passed	✓
Success	✓
Duration	45.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly enables and starts the fapolicyd service, addressing the vulnerability as described.
Concerns	The plan does not verify that the fapolicyd package is installed before attempting to enable/start the service.; It uses the gene

QA Result

Safe	✓
Verdict	Enabling and starting fapolicyd follows the vendor recommendation and uses standard systemctl commands. The default fapo
Side Effects	If the fapolicyd policy is later tightened, it could block execution of some binaries, potentially affecting services that rely on file
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	6.8s
Total Tokens	24,389
Cost	$0.0051
Agents	Remedy(10), Review(1), Qa(1)

fapolicy_default_deny: Configure Fapolicy Module to Employ a Deny-all, Permit-by-exception Policy to Al… — *REQUIRES_HUMAN_REVIEW*

Rule	fapolicy_default_deny
Severity	Medium
Description	The Fapolicy module must be configured to employ a deny-all, permit-by-exception policy to allow the execution of authorized
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then cat > /etc/fapolicyd
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	The remediation creates a deny-all rule for fapolicyd and disables permissive mode, which can prevent execution of essential
Estimated Impact	filesystems affected; potential loss of SSH/console access; service disruption; system instability if exceptions are missing

LLM Metrics

LLM Calls	1
Duration	1.4s

Total Tokens	1,587
Cost	$0.0007
Agents	Triage(1)

package_postfix_installed: The Postfix package is installed — SUCCESS

Rule	package_postfix_installed
Severity	Medium
Description	A mail server is required for sending emails. The postfix package can be installed with the following command: $ sudo dnf ins
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "p
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing Postfix is a standard package addition with minimal impact; it does not modify authentication settings, bootloader, or
Estimated Impact	networking affected; filesystems affected

Remediation (1 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✓
Success	✓
Duration	—

Error	can't concat str to bytes

LLM Metrics

LLM Calls	5
Duration	3.8s
Total Tokens	5,913
Cost	$0.0017
Agents	Triage(1), Remedy(2), Review(1), Qa(1)

package_s-nail_installed: The s-nail Package Is Installed — SUCCESS

Rule	package_s-nail_installed
Severity	Medium
Description	A mail server is required for sending emails. The s-nail package can be installed with the following command: $ sudo dnf insta
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the s-nail package is a straightforward package installation that does not modify authentication, networking, or critica
Estimated Impact	filesystems affected

Remediation (1 attempt(s))

Attempt #	1

Commands	rpm -q s-nail, dnf install -y s-nail
Scan Passed	✓
Success	✓
Duration	76.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly checks for the s-nail package and installs it if missing, which will resolve the finding.
Concerns	—

QA Result

Safe	✓
Verdict	Installing the s-nail package is a low■risk operation that only adds a mail client and its dependencies. It does not modify syste
Side Effects	Installs additional dependent packages; Slightly expands the system's attack surface
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	6.6s
Total Tokens	19,803
Cost	$0.0043

Agents	Triage(1), Remedy(8), Review(1), Qa(1)

postfix_client_configure_mail_alias: Configure System to Forward All Mail For The Root Account — FAILED

Rule	postfix_client_configure_mail_alias
Severity	Medium
Description	Make sure that mails delivered to root user are forwarded to a monitored email address. Make sure that the address is a valid
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_postfix_root_m
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits /etc/aliases and runs newaliases, which is a straightforward configuration change with no impact o
Estimated Impact	filesystems affected; email delivery; monitoring

Remediation (3 attempt(s))

Attempt #	1
Commands	sed -i -r 's/^#?\s*root:.*/root: root@example.com/' /etc/aliases, grep -q '^\s*root:' /etc/aliases || echo 'root: root@example.com'
Scan Passed	✗
Success	✗
Duration	13.5s
Error	—

Attempt #	2

Commands	newaliases, cp /etc/aliases /etc/aliases.bak
Scan Passed	✗
Success	✗
Duration	20.5s
Error	—

Attempt #	3
Commands	sed -E -i 's/^\s*#?\s*root\s*:.*$/root: admin@example.com/' /etc/aliases, cp /etc/aliases /etc/aliases.bak.$(date +%s), postalias
Scan Passed	✗
Success	✗
Duration	21.2s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly backs up /etc/aliases, updates or adds a root alias, rebuilds the alias database, and reloads Postfix, which
Concerns	The placeholder email address (admin@example.com) must be replaced with a real monitored address before deployment.; I

QA Result

Safe	✓
Verdict	The remediation only edits /etc/aliases, rebuilds the alias database, and reloads Postfix. These actions are standard for mail a
Side Effects	temporary mail delivery delay while Postfix reloads; possible bounce if the specified email address is invalid or unreachable
Regression	✗

Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	11.9s
Total Tokens	69,522
Cost	$0.0133
Agents	Remedy(13), Review(1), Qa(1)

chronyd_or_ntpd_set_maxpoll: Configure Time Service Maxpoll Interval — SUCCESS

Rule	chronyd_or_ntpd_set_maxpoll
Severity	Medium
Description	The maxpoll should be configured to in /etc/ntp.conf or /etc/chrony.conf (or /etc/chrony.d/) to continuously poll time servers. T
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { (rpm --quiet -q chro
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits NTP/Chrony configuration files to add or adjust the maxpoll parameter, which is a straightforward t
Estimated Impact	filesystems affected; configuration drift; potential time sync in if misconfigured

Remediation (1 attempt(s))

Attempt #	1

Commands	rpm -q ntpd, rpm -q chrony, ls /etc/chrony.d/*.conf 2>/dev/null || echo none, cp /etc/chrony.conf /etc/chrony.conf.bak, sed -i -E
Scan Passed	✓
Success	✓
Duration	68.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly identifies the relevant NTP/Chrony configuration files and uses sed to enforce a maxpoll value of 4 on all s
Concerns	No backup of configuration files is made before in■place editing.; The plan does not restart ntpd or chronyd after modifying th

QA Result

Safe	✓
Verdict	The plan only edits NTP/Chrony configuration files to enforce a maxpoll value. It does not touch critical services such as sshd
Side Effects	Potential NTP/Chrony service restart needed for changes to take effect; If the sed command mishandles unusual line formatti
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	21
Duration	16.4s
Total Tokens	91,463
Cost	$0.0179

Agents	Triage(1), Remedy(18), Review(1), Qa(1)

chronyd_server_directive: Ensure Chrony is only configured with the server directive — SUCCESS

Rule	chronyd_server_directive
Severity	Medium
Description	Check that Chrony only has time sources configured with the server directive.
Recommendation	Review and remediate: Ensure Chrony is only configured with the server directive
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The fix only requires editing the chrony configuration file to remove non-server directives and restarting the chronyd service, w
Estimated Impact	filesystems affected; configuration_error; service_disruption

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	3.6s
Error	—

Attempt #	2

Commands	cp /etc/chrony.conf /etc/chrony.conf.bak, sed -i -r -e 's/^(\s*)pool/#\1pool/' -e 's/^(\s*)makestep/#\1makestep/' -e 's/^(\s*)maxde
Scan Passed	✓
Success	✓
Duration	57.2s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan addresses the core issue by backing up the config, removing non■server time■source directives, validating syntax,
Concerns	Sed commands may unintentionally comment out lines that are already commented or contain the target word in a different c

QA Result

Safe	✓
Verdict	The plan follows a standard hardening approach: backs up the config, comments out only non■server time■source directives
Side Effects	Potential loss of accurate system time if no server directives are left after commenting out pool directives; Short■term time dr
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	13.2s
Total Tokens	64,872
Cost	$0.0125

Agents	Remedy(13), Review(1), Qa(1)

disable_host_auth: Disable Host-Based Authentication — SUCCESS

Rule	disable_host_auth
Severity	Medium
Description	SSH's cryptographic host-based authentication is more secure than .rhosts authentication. However, it is not recommended tl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only requires setting a standard SSH configuration option to disable host-based authentication, which is alre
Estimated Impact	authentication/authorization affected; filesystems affected; ssh_configuration

Remediation (1 attempt(s))

Attempt #	1
Commands	touch /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf, chmod 0600 /etc/ssh/sshd_config.d/00-complianceascod
Scan Passed	✓
Success	✓
Duration	19.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will correctly set HostbasedAuthentication no in the target config file and set appropriate permissions. However, it co
Concerns	If /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf does not exist, the sed command will fail.; The plan does not r

QA Result

Safe	✓
Verdict	The plan only edits a specific SSH include file to ensure HostbasedAuthentication is set to 'no', using safe in■place substituti
Side Effects	If /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf does not exist, the sed command will error and the change wil
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	12.0s
Total Tokens	47,414
Cost	$0.0107
Agents	Triage(1), Remedy(13), Review(1), Qa(1)

sshd_disable_compression: Disable Compression Or Set Compression to delayed — SUCCESS

Rule	sshd_disable_compression
Severity	Medium
Description	Compression is useful for slow network connections over long distances but can cause performance issues on local LANs. If

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_sshd_disable_
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits SSH daemon configuration files to disable or delay compression, a standard STIG hardening step
Estimated Impact	authentication/authorization affected; ssh_service_restart; potential_misconfiguration

Remediation (2 attempt(s))

Attempt #	1
Commands	grep -n "Compression" -n /etc/ssh/sshd_config, sed -i 's/^\s*#\s*Compression\s\+.*/Compression delayed/' /etc/ssh/sshd_conf
Scan Passed	✗
Success	✗
Duration	13.2s
Error	—

Attempt #	2
Commands	ls /etc/ssh/sshd_config.d/*.conf 2>/dev/null || echo 'no_files', cp /etc/ssh/sshd_config /etc/ssh/sshd_config.bak, sed -i '/^\s*#\?
Scan Passed	✓
Success	✓
Duration	29.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly removes any existing Compression directives from both the main sshd_config and any .conf files in sshd_c
Concerns	The sed pattern description is vague; if not precise it may delete unrelated lines containing the word 'Compression' in comme

QA Result

Safe	✓
Verdict	The plan removes any existing Compression directives and enforces 'Compression no' via a dedicated config file, then reload
Side Effects	Temporary interruption of new SSH connections during the service reload; Potential lockout if the configuration file becomes s
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	17
Duration	11.7s
Total Tokens	86,512
Cost	$0.0139
Agents	Remedy(15), Review(1), Qa(1)

sshd_disable_gssapi_auth: Disable GSSAPI Authentication — FAILED

Rule	sshd_disable_gssapi_auth
Severity	Medium
Description	Unless needed, SSH should not permit extraneous or unnecessary authentication mechanisms like GSSAPI. The default SSH

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only requires adding or correcting a line in the SSH daemon configuration to disable GSSAPI authentication,
Estimated Impact	authentication/authorization affected; filesystems affected; SSH configuration change

Remediation (3 attempt(s))

Attempt #	1
Commands	echo 'GSSAPIAuthentication no' >> /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf, chmod 0600 /etc/ssh/sshd_
Scan Passed	✗
Success	✗
Duration	14.3s
Error	—

Attempt #	2
Commands	touch /etc/ssh/sshd_config.d/99-complianceascode-hardening.conf, sed -i '/^\s*GSSAPIAuthentication\s/ {s/.*/GSSAPIAuthen
Scan Passed	✗
Success	✗
Duration	22.0s
Error	—

Attempt #	3
Commands	sed -i '/^\s*#\?GSSAPIAuthentication\s\+/d' /etc/ssh/sshd_config, printf '\nGSSAPIAuthentication no\n' >> /etc/ssh/sshd_confi
Scan Passed	✗
Success	✗
Duration	23.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will disable GSSAPIAuthentication in the primary sshd_config file and reload the daemon, which will likely remediate
Concerns	If any file in /etc/ssh/sshd_config.d sets GSSAPIAuthentication to 'yes' after the main config is processed, it could re■enable

QA Result

Safe	✓
Verdict	The plan removes any existing GSSAPIAuthentication directives, appends a definitive 'no' setting, secures file permissions, a
Side Effects	If later include files set GSSAPIAuthentication=yes, the setting could be overridden, leaving the vulnerability partially unaddre
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	15.0s
Total Tokens	64,776

Cost	$0.0119
Agents	Remedy(13), Review(1), Qa(1)

sshd_disable_kerb_auth: Disable Kerberos Authentication — SUCCESS

Rule	sshd_disable_kerb_auth
Severity	Medium
Description	Unless needed, SSH should not permit extraneous or unnecessary authentication mechanisms like Kerberos. The default SS
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies sshd configuration to explicitly disable KerberosAuthentication, a standard STIG hardening ste
Estimated Impact	authentication/authorization affected; filesystems affected; authentication; ssh

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf
Scan Passed	✓
Success	✓
Duration	19.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly disables KerberosAuthentication by ensuring the directive is present in a dedicated include file and reloads
Concerns	The plan only edits 00-complianceascode-hardening.conf; KerberosAuthentication lines in other .conf files could still be effect

QA Result

Safe	✓
Verdict	The plan safely adds or updates KerberosAuthentication no in a dedicated include file and reloads sshd, which is the correct
Side Effects	Brief interruption of existing SSH sessions during sshd reload; No critical service impact expected
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	9.1s
Total Tokens	37,987
Cost	$0.0082
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

sshd_disable_rhosts: Disable SSH Support for .rhosts Files — SUCCESS

Rule	sshd_disable_rhosts
Severity	Medium
Description	SSH can emulate the behavior of the obsolete rsh command in allowing users to enable insecure access to their accounts via

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies the SSH daemon configuration to set IgnoreRhosts yes, a standard STIG hardening step. It do
Estimated Impact	authentication/authorization affected

Remediation (1 attempt(s))

Attempt #	1
Commands	sed -i 's/^\s*#\?\s*IgnoreRhosts\s\+.*/IgnoreRhosts yes/' /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf, grep -c
Scan Passed	✓
Success	✓
Duration	17.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly ensures that the directive IgnoreRhosts yes is present and active in the hardening configuration file, which
Concerns	The plan does not include a step to reload or restart sshd, so the new setting may not take effect until a manual restart.; File p

QA Result

Safe	✓
Verdict	The plan only edits a single sshd configuration fragment to ensure 'IgnoreRhosts yes' is present, which is the correct mitigatio
Side Effects	No immediate service interruption; the change will take effect after sshd is reloaded or restarted.; If the file permissions are in
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	11.2s
Total Tokens	39,356
Cost	$0.0083
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

sshd_disable_user_known_hosts: Disable SSH Support for User Known Hosts — SUCCESS

Rule	sshd_disable_user_known_hosts
Severity	Medium
Description	SSH can allow system users to connect to systems if a cache of the remote systems public keys is available. This should be
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	The remediation only adds or updates a single SSH daemon configuration directive (IgnoreUserKnownHosts yes) in a dedica
Estimated Impact	authentication/authorization affected; filesystems affected; ssh_configuration

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf
Scan Passed	✓
Success	✓
Duration	17.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly adds or updates the IgnoreUserKnownHosts directive and restarts sshd, which will resolve the vulnerability
Concerns	The sed pattern may not correctly handle commented lines with varying whitespace or additional characters.; Using systemctl

QA Result

Safe	✓
Verdict	The plan correctly adds or updates the IgnoreUserKnownHosts directive and restarts sshd, which addresses the vulnerability
Side Effects	Active SSH sessions may be terminated during sshd restart; No backup of the original configuration file is created; SELinux c
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	9.9s
Total Tokens	39,404
Cost	$0.0080
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

sshd_do_not_permit_user_env: Do Not Allow SSH Environment Options — SUCCESS

Rule	sshd_do_not_permit_user_env
Severity	Medium
Description	Ensure that users are not able to override environment variables of the SSH daemon. The default SSH configuration disables
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits SSH daemon configuration to disable PermitUserEnvironment, a standard STIG hardening step. It
Estimated Impact	authentication/authorization affected; filesystems affected; ssh_config_change

Remediation (1 attempt(s))

Attempt #	1
Commands	sed -i "/^\s*PermitUserEnvironment\s\+/Id" /etc/ssh/sshd_config, sed -i "/^\s*PermitUserEnvironment\s\+/Id" /etc/ssh/sshd_co
Scan Passed	✓

Success	✓
Duration	24.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly disables PermitUserEnvironment by removing any existing directives and adding the explicit 'PermitUserEr
Concerns	Restarting sshd may briefly disconnect active sessions; a reload could be safer.

QA Result

Safe	✓
Verdict	The plan correctly disables PermitUserEnvironment by removing any existing directives and adding an explicit 'PermitUserEn
Side Effects	Active SSH sessions may be terminated during the sshd restart; User-defined environment variables passed via SSH will no l
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	17
Duration	13.5s
Total Tokens	60,582
Cost	$0.0110
Agents	Triage(1), Remedy(14), Review(1), Qa(1)

sshd_enable_pubkey_auth: Enable Public Key Authentication — SUCCESS

Rule	sshd_enable_pubkey_auth
Severity	Medium
Description	Enable SSH login with public keys. The default SSH configuration enables authentication based on public keys. The appropri
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling PubkeyAuthentication is a standard SSH hardening step that does not alter service behavior and is unlikely to cause
Estimated Impact	authentication/authorization affected

Remediation (1 attempt(s))

Attempt #	1
Commands	echo "PubkeyAuthentication yes" >> /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf, systemctl reload sshd, sta
Scan Passed	✓
Success	✓
Duration	17.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	8/10
Feedback	The plan correctly creates or updates the dedicated hardening config file to explicitly enable PubkeyAuthentication, which sat
Concerns	No sshd reload/restart step, so the new setting may not be applied until the service is manually reloaded.; Potential duplicate

QA Result

Safe	✓
Verdict	The remediation only creates or updates a dedicated sshd_config.d file to explicitly enable PubkeyAuthentication with proper
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	10.3s
Total Tokens	39,962
Cost	$0.0088
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

sshd_enable_strictmodes: Enable Use of Strict Mode Checking — SUCCESS

Rule	sshd_enable_strictmodes
Severity	Medium
Description	SSHs StrictModes option checks file and ownership permissions in the user's home directory .ssh folder before accepting log
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	StrictModes is a standard SSH configuration option that is enabled by default. Enforcing it explicitly is a typical STIG hardenin
Estimated Impact	authentication/authorization affected; ssh_authentication; configuration_change

Remediation (1 attempt(s))

Attempt #	1
Commands	sed -i "/^\s*#\?\s*StrictModes\s\+/Id" /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf, echo "StrictModes yes" >>
Scan Passed	✓
Success	✓
Duration	13.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will correctly enforce StrictModes by removing any existing entries and appending the required setting, then restartin
Concerns	The target file may not exist, causing sed to fail.; File permissions are not explicitly set, which could allow unauthorized modifi

QA Result

Safe	✓
Verdict	The plan correctly enforces StrictModes by removing any existing entries and appending the required setting, then reloads ss

Side Effects	Potential brief interruption of active SSH sessions due to sshd restart; Possible login failures for users with world■writable ho
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	9.3s
Total Tokens	30,549
Cost	$0.0063
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

sshd_print_last_log: Enable SSH Print Last Log — SUCCESS

Rule	sshd_print_last_log
Severity	Medium
Description	Ensure that SSH will display the date and time of the last successful account logon. The default SSH configuration enables pr
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only adds or updates a standard SSH configuration directive (PrintLastLog yes) in a dedicated config file. Th
Estimated Impact	filesystems affected; ssh configuration change

Remediation (1 attempt(s))

Attempt #	1
Commands	sed -i "/^\s*PrintLastLog\s\+/Id" /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf, echo "PrintLastLog yes" >> /etc
Scan Passed	✓
Success	✓
Duration	17.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly ensures that PrintLastLog is set to yes in the designated SSH configuration file and restarts the daemon to
Concerns	Restarting sshd may briefly interrupt active SSH sessions.; The plan does not include a configuration syntax validation step b

QA Result

Safe	✓
Verdict	The plan correctly adds or ensures the PrintLastLog=yes directive in the designated SSH config fragment and restarts sshd. T
Side Effects	Brief interruption of active SSH sessions during sshd restart; Potential temporary loss of remote access if the sshd fails to sta
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	9.3s

Total Tokens	36,953
Cost	$0.0062
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

sshd_rekey_limit: Force frequent session key renegotiation — SUCCESS

Rule	sshd_rekey_limit
Severity	Medium
Description	The RekeyLimit parameter specifies how often the session key of the is renegotiated, both in terms of amount of data that ma
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_rekey_limit_siz
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits an SSH daemon configuration file to set RekeyLimit, a standard STIG hardening parameter. This i
Estimated Impact	authentication/authorization affected; networking affected; ssh_configuration; potential_service_disruption

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	4.8s

Error	—

Attempt #	2
Commands	chmod 0600 /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf, sed -i '/^\s*#\?\s*RekeyLimit\b/d' /etc/ssh/sshd_co
Scan Passed	✓
Success	✓
Duration	23.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will set a secure RekeyLimit and reload sshd, addressing the vulnerability. Minor regex and newline handling issues
Concerns	The sed pattern '/^\s*#?\s*RekeyLimit\b/d' uses '?' which is not a quantifier in basic sed, so commented RekeyLimit lines may

QA Result

Safe	✓
Verdict	The plan removes any existing RekeyLimit directives, adds a controlled setting (1G 1h) in a dedicated hardening file, and relo
Side Effects	If the sed pattern fails to delete a commented RekeyLimit line, a duplicate directive may remain, but sshd will ignore the comm
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	11.3s

Total Tokens	52,607
Cost	$0.0107
Agents	Remedy(13), Review(1), Qa(1)

sshd_set_loglevel_verbose: Set SSH Daemon LogLevel to VERBOSE — SUCCESS

Rule	sshd_set_loglevel_verbose
Severity	Medium
Description	The VERBOSE parameter configures the SSH daemon to record login and logout activity. To specify the log level in SSH, ad
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing LogLevel to VERBOSE only increases logging detail; it does not affect authentication mechanisms or service availa
Estimated Impact	authentication/authorization affected; filesystems affected; logging

Remediation (1 attempt(s))

Attempt #	1
Commands	echo 'LogLevel VERBOSE' >> /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf, chmod 0600 /etc/ssh/sshd_conf
Scan Passed	✓
Success	✓
Duration	18.4s

Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly ensures that LogLevel VERBOSE is set in a dedicated config fragment, applies proper permissions, and re
Concerns	The verification command uses "systemctl is sshd", which is not a valid systemctl subcommand; the correct check is "systemc

QA Result

Safe	✓
Verdict	The plan correctly ensures LogLevel VERBOSE is set in a dedicated config fragment, uses safe in-place editing, sets proper
Side Effects	Brief interruption of existing SSH sessions during sshd restart; Potential SELinux context mismatch for the newly created file
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	11.1s
Total Tokens	38,792
Cost	$0.0076
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

sshd_x11_use_localhost: Prevent remote hosts from connecting to the proxy display — SUCCESS

Rule	sshd_x11_use_localhost

Severity	Medium
Description	The SSH daemon should prevent remote hosts from connecting to the proxy display. The default SSH configuration for X11U
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only enforces the default X11UseLocalhost=yes setting in SSH configuration, which is a standard hardening
Estimated Impact	authentication/authorization affected; filesystems affected; ssh; x11_forwarding

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	4.6s
Error	—

Attempt #	2
Commands	touch /etc/ssh/sshd_config.d/99-hardening.conf, chmod 0600 /etc/ssh/sshd_config.d/99-hardening.conf, sed -i '/^\s*X11UseL
Scan Passed	✓
Success	✓
Duration	18.4s

Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will correctly enforce X11UseLocalhost=yes by adding the directive in a high■order .d/ file and reloading sshd. It me
Concerns	The plan mentions creating the file if it does not exist but does not include an explicit command to do so.; Using a delete■ther

QA Result

Safe	✓
Verdict	The plan correctly enforces X11UseLocalhost=yes by adding the directive in a high■order .d/ file and reloading sshd. The cha
Side Effects	Creation of /etc/ssh/sshd_config.d/99-hardening.conf if it does not exist; Reload of the sshd service
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	8.3s
Total Tokens	41,852
Cost	$0.0080
Agents	Remedy(12), Review(1), Qa(1)

sssd_certificate_verification: Certificate status checking in SSSD — FAILED

Rule	sssd_certificate_verification

Severity	Medium
Description	Multifactor solutions that require devices separate from information systems gaining access include, for example, hardware to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q sssd-common; then var_sssd_certifi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only edits SSSD configuration files to enable OCSP certificate verification and sets proper file permissions. T
Estimated Impact	authentication/authorization affected; filesystems affected; potential temporary authentication disruption; misconfiguration cou

Remediation (3 attempt(s))

Attempt #	1
Commands	ls -1 /etc/sssd/conf.d, rpm -q sssd-common, test -f /etc/sssd/conf.d/certificate_verification.conf && echo exists || echo missing
Scan Passed	✗
Success	✗
Duration	10.8s
Error	—

Attempt #	2
Commands	find /etc/sssd -maxdepth 2 -type f -name "*.conf" -print, dnf info sssd, systemctl status sssd.service, find /etc/sssd/conf.d -type
Scan Passed	✗
Success	✗
Duration	33.6s

Error	—

Attempt #	3
Commands	stat -c %a /etc/sssd/conf.d, cp --preserve=mode,ownership /etc/sssd/conf.d/certificate_verification.conf /etc/sssd/conf.d/certifi
Scan Passed	✗
Success	✗
Duration	24.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly enables OCSP certificate verification with a SHA256 digest under the [sssd] section, backs up existing files
Concerns	No explicit configuration validation (e.g., sssctl configcheck) before reloading SSSD.; The plan assumes the global [sssd] sec

QA Result

Safe	✓
Verdict	The plan follows standard hardening practice: backs up existing files, creates a dedicated conf.d file with correct syntax and p
Side Effects	If the new configuration contains syntax errors or duplicate keys, SSSD may fail to reload, leading to authentication failures fo
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	17
Duration	12.4s

Total Tokens	71,140
Cost	$0.0115
Agents	Remedy(15), Review(1), Qa(1)

sssd_enable_certmap: Enable Certmap in SSSD — SUCCESS

Rule	sssd_enable_certmap
Severity	Medium
Description	SSSD should be configured to verify the certificate of the user or group. To set this up ensure that section like certmap/testing
Recommendation	Review and remediate: Enable Certmap in SSSD
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only requires adding a certmap stanza to /etc/sssd/sssd.conf and restarting the sssd service. This is a stand
Estimated Impact	authentication/authorization affected; filesystems affected; potential authentication misconfiguration; service restart may temp

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	3.3s

Error	—

Attempt #	2
Commands	—
Scan Passed	✓
Success	✓
Duration	—
Error	can't concat str to bytes

LLM Metrics

LLM Calls	15
Duration	10.3s
Total Tokens	62,367
Cost	$0.0111
Agents	Remedy(13), Review(1), Qa(1)

sssd_enable_smartcards: Enable Smartcards in SSSD — SUCCESS

Rule	sssd_enable_smartcards
Severity	Medium
Description	SSSD should be configured to authenticate access to the system using smart cards. To enable smart cards in SSSD, set pam
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q sssd-common; then # sssd configura
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies SSSD and PAM configuration files to enable smartcard authentication, which is a standard STI
Estimated Impact	authentication/authorization affected; filesystems affected; authentication; pam_configuration

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/sssd/sssd.conf /etc/sssd/sssd.conf.bak, sed -i '/^\[pam\]/,/^\[/{/pam_cert_auth/ {s/^#\s*pam_cert_auth\s*=.*/pam_cert_a
Scan Passed	✓
Success	✓
Duration	37.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly sets pam_cert_auth = True and adds try_cert_auth to the PAM configuration, which will enable smartcard a
Concerns	smartcard-auth modification does not include the allow_missing_name option as required by the specification.; No backup of

QA Result

Safe	✓
Verdict	The plan correctly enables pam_cert_auth in sssd.conf and adds the try_cert_auth option to the pam_sss.so lines, which is th
Side Effects	Appending try_cert_auth to pam_sss.so may affect all services that use system-auth (e.g., sshd, login, sudo) by attempting ce
Regression	✗

Recommendation	Approve

LLM Metrics

LLM Calls	21
Duration	20.0s
Total Tokens	113,520
Cost	$0.0217
Agents	Triage(1), Remedy(18), Review(1), Qa(1)

package_usbguard_installed: Install usbguard Package — SUCCESS

Rule	package_usbguard_installed
Severity	Medium
Description	The usbguard package can be installed with the following command: $ sudo dnf install usbguard
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! (grep -sqE "^.*\.s390x$" /proc/sys/kernel/osrele
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only installs the usbguard package, which is a standard, low■impact operation. It does not modify authentica
Estimated Impact	—

Remediation (2 attempt(s))

Attempt #	1

Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	can't concat str to bytes

Attempt #	2
Commands	rpm -q usbguard
Scan Passed	✓
Success	✓
Duration	16.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will install the usbguard package, satisfying the OpenSCAP rule. Adding architecture checks, service enable/start, a
Concerns	No architecture or platform guard; may attempt install on unsupported systems.; Does not enable or start the usbguard servic

QA Result

Safe	✓
Verdict	Installing the usbguard package is a standard, low■impact operation on Rocky Linux 10. It adds a daemon for USB device au
Side Effects	Adds the usbguard daemon and systemd unit; May require post■install configuration to define USB device policies; Potentiall
Regression	✗

Recommendation	Approve

LLM Metrics

LLM Calls	9
Duration	7.9s
Total Tokens	14,929
Cost	$0.0034
Agents	Remedy(7), Review(1), Qa(1)