OpenSCAP Multi-Agent Pipeline Report

Target: 127.0.0.1 | Generated: 2026-04-04 21:22:05

Models Used

Triage	nvidia/nemotron-3-super-120b-a12b
Remedy	nvidia/nemotron-3-super-120b-a12b
Review	nvidia/nemotron-3-super-120b-a12b
Qa	nvidia/nemotron-3-super-120b-a12b

Pipeline Summary

Total Findings Processed	150
Remediated Successfully	13
Failed Remediation	111
Requires Human Review	20
Discarded / Blocked	6
Success Rate	8.7%
Total Duration	19592.5s

LLM Usage (Aggregate)

Total LLM Calls	1047
Total Errors	22

Total LLM Duration	5492.6s
Prompt Tokens	5,373,833
Completion Tokens	659,499
Total Tokens	6,033,332
Estimated Cost (USD)	$0.8719

LLM Usage by Agent

Agent	Calls	Errors	Duration (s)	Prompt Tok	Compl Tok	Total Tok	Cost (USD)
Triage	32	1	184.2	25,565	28,766	54,331	$0.0169
Remedy	883	18	4408.1	5,229,738	512,656	5,742,394	$0.7793
Review	69	3	656.3	58,248	72,277	130,525	$0.0457
Qa	63	0	244.0	60,282	45,800	106,082	$0.0299

Remediated Successfully (13)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
package_aide_installed	Install AIDE	Medium	Remediate	LOW	1	Pass	Approved (10/10)	✓	103.4s	10
aide_build_database	Build and Test AIDE Database	Medium	Remediate	LOW	1	Pass	Approved (7/10)	✓	317.3s	11
package_gnutls-utils_installed	Ensure gnutls-utils is installed	Medium	Remediate	LOW	2	Pass	Approved (10/10)	✓	173.6s	10
package_nss-tools_installed	Ensure nss-tools is installed	Medium	Remediate	LOW	3	Pass	—	—	142.1s	9
package_subscription-manager_installed	Install subscription-manager Package	Medium	Remediate	LOW	2	Pass	—	—	12.0s	5

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
account_password_pam_faillock_password_auth	Configure the Use of the pam_faillock.so Module in…	Medium	Remediate	LOW	2	Pass	—	—	1738.2s	15
service_debug-shell_disabled	Disable debug-shell SystemD Service	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	786.6s	16
package_rsyslog-gnutls_installed	Ensure rsyslog-gnutls is installed	Medium	Remediate	LOW	2	Pass	Approved (10/10)	✓	120.8s	9
package_libreswan_installed	Install libreswan Package	Medium	Remediate	LOW	1	Pass	—	—	367.2s	10
sysctl_net_ipv6_conf_all_accept_ra	Configure Accepting Router Advertisements on All I…	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	284.1s	26
sysctl_net_ipv6_conf_default_accept_redirects	Disable Kernel Parameter for Accepting ICMP Redire…	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	369.9s	12
sysctl_net_ipv6_conf_default_accept_source_route	Disable Kernel Parameter for Accepting Source-Rout…	Medium	Remediate	LOW	3	Pass	Approved (1/10)	✓	56.7s	15
sysctl_net_ipv4_conf_all_accept_redirects	Disable Accepting ICMP Redirects for All IPv4 Inte…	Medium	Remediate	LOW	3	Pass	—	—	383.3s	8

Failed Remediation (111)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
aide_scan_notification	Configure Notification of Post-AIDE Scan Details	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	1251.5s	18
aide_use_fips_hashes	Configure AIDE to Use FIPS 140-2 for Validating Ha…	Medium	Remediate	LOW	3	Fail	Approved (10/10)	✓	1143.2s	19

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
configure_crypto_policy	Configure System Cryptography Policy	High	Remediate	LOW	3	Fail	Approved (9/10)	✓	641.1s	15
sudo_require_reauthentication	Require Re-Authentication When Using the sudo Comm…	Medium	Remediate	LOW	3	Fail	Approved (9/10)	✓	1593.6s	17
ensure_gpgcheck_local_packages	Ensure gpgcheck Enabled for Local Packages	High	Remediate	LOW	3	Fail	Rejected (2/10)	—	253.2s	4
enable_authselect	Enable authselect	Medium	Remediate	LOW	3	Fail	—	—	4.8s	5
banner_etc_issue	Modify the System Login Banner	Medium	Remediate	LOW	3	Fail	—	—	377.9s	8
accounts_passwords_pam_faillock_deny	Lock Accounts After Failed Password Attempts	Medium	Remediate	LOW	3	Fail	—	—	952.3s	13
accounts_passwords_pam_faillock_dir	Lock Accounts Must Persist	Medium	Remediate	LOW	3	Fail	—	—	144.9s	6
accounts_passwords_pam_faillock_interval	Set Interval For Counting Failed Password Attempts	Medium	Remediate	LOW	3	Fail	—	—	14.0s	6
accounts_password_pam_dcredit	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	3	Fail	—	—	6.3s	5
accounts_password_pam_dictcheck	Ensure PAM Enforces Password Requirements - Preven…	Medium	Remediate	LOW	3	Fail	—	—	1097.5s	14
accounts_password_pam_difok	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	3	Fail	—	—	7.4s	5
accounts_password_pam_enforce_root	Ensure PAM Enforces Password Requirements - Enforc…	Medium	Remediate	LOW	3	Fail	—	—	61.2s	14
accounts_password_pam_lcredit	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	3	Fail	—	—	126.4s	6

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
accounts_password_pam_maxclassrepeat	Ensure PAM Enforces Password Requirements - Maximu…	Medium	Remediate	LOW	3	Fail	—	—	135.3s	10
accounts_password_pam_maxrepeat	Set Password Maximum Consecutive Repeating Charact…	Medium	Remediate	LOW	3	Fail	—	—	22.8s	6
accounts_password_pam_minclass	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	26.7s	18
accounts_password_pam_minlen	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	3	Fail	Approved (10/10)	✓	20.2s	8
accounts_password_pam_ocredit	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	13.4s	11
accounts_password_pam_pwquality_retry	Ensure PAM Enforces Password Requirements - Authen…	Medium	Remediate	LOW	3	Fail	Approved (5/10)	✓	135.5s	21
accounts_password_pam_ucredit	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	3	Fail	—	—	25.6s	12
disable_ctrlaltdel_reboot	Disable Ctrl-Alt-Del Reboot Activation	High	Remediate	LOW	3	Fail	—	—	139.5s	13
package_opensc_installed	Install the opensc Package For Multifactor Authent…	Medium	Remediate	LOW	3	Fail	Approved (9/10)	✓	457.1s	29
package_pcsc-lite_installed	Install the pcsc-lite package	Medium	Remediate	LOW	3	Fail	—	—	9.5s	5
install_smartcard_packages	Install Smart Card Packages For Multifactor Authen…	Medium	Remediate	LOW	3	Fail	—	—	13.9s	5
service_pcscd_enabled	Enable the pcscd Service	Medium	Remediate	LOW	3	Fail	—	—	10.2s	5
configure_opensc_card_drivers	Configure opensc Smart Card Drivers	Medium	Remediate	LOW	3	Fail	—	—	6.0s	5

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
account_disable_post_pw_expiration	Set Account Expiration Following Inactivity	Medium	Remediate	LOW	3	Fail	—	—	5.7s	5
accounts_maximum_age_login_defs	Set Password Maximum Age	Medium	Remediate	LOW	3	Fail	—	—	4.6s	5
accounts_minimum_age_login_defs	Set Password Minimum Age	Medium	Remediate	LOW	3	Fail	—	—	50.9s	5
accounts_password_set_max_life_existing	Set Existing Passwords Maximum Age	Medium	Remediate	LOW	3	Fail	Rejected (3/10)	—	22.0s	2
accounts_password_set_min_life_existing	Set Existing Passwords Minimum Age	Medium	Remediate	LOW	3	Fail	—	—	21.8s	5
accounts_password_pam_unix_rounds_password_auth	Set number of Password Hashing Rounds - password-a…	Medium	Remediate	LOW	3	Fail	—	—	27.8s	19
accounts_password_pam_unix_rounds_system_auth	Set number of Password Hashing Rounds - system-aut…	Medium	Remediate	LOW	3	Fail	—	—	6.9s	5
no_empty_passwords	Prevent Login to Accounts With Empty Password	High	Remediate	LOW	3	Fail	—	—	18.9s	5
use_pam_wheel_for_su	Enforce usage of pam_wheel for su authentication	Medium	Remediate	LOW	3	Fail	—	—	14.7s	10
accounts_logon_fail_delay	Ensure the Logon Failure Delay is Set Correctly in…	Medium	Remediate	LOW	3	Fail	—	—	89.1s	14
accounts_tmout	Set Interactive Session Timeout	Medium	Remediate	LOW	3	Fail	—	—	36.6s	17
file_permission_user_init_files_root	Ensure All User Initialization Files Have Mode 074…	Medium	Remediate	LOW	3	Fail	—	—	27.5s	5

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
accounts_umask_etc_bashrc	Ensure the Default Bash Umask is Set Correctly	Medium	Remediate	LOW	3	Fail	—	—	22.2s	5
accounts_umask_etc_csh_cshrc	Ensure the Default C Shell Umask is Set Correctly	Medium	Remediate	LOW	3	Fail	—	—	31.2s	5
accounts_umask_etc_login_defs	Ensure the Default Umask is Set Correctly in login…	Medium	Remediate	LOW	3	Fail	—	—	20.6s	8
accounts_umask_etc_profile	Ensure the Default Umask is Set Correctly in /etc/…	Medium	Remediate	LOW	3	Fail	—	—	6.1s	5
grub2_vsyscall_argument	Disable vsyscalls	Medium	Remediate	LOW	3	Fail	—	—	29.0s	7
grub2_admin_username	Set the Boot Loader Admin Username to a Non-Defaul…	High	Remediate	LOW	3	Fail	—	—	128.3s	8
grub2_password	Set Boot Loader Password in grub2	High	Remediate	LOW	3	Fail	—	—	9.8s	5
rsyslog_encrypt_offload_actionsendstreamdriverauthmode	Ensure Rsyslog Authenticates Off-Loaded Audit Reco…	Medium	Remediate	LOW	3	Fail	—	—	125.6s	6
rsyslog_remote_loghost	Ensure Logs Sent To Remote Host	Medium	Remediate	LOW	3	Fail	—	—	155.2s	14
network_configure_name_resolution	Configure Multiple DNS Servers in /etc/resolv.conf	Medium	Remediate	LOW	3	Fail	—	—	5.8s	5
sysctl_net_ipv6_conf_all_accept_redirects	Disable Accepting ICMP Redirects for All IPv6 Inte…	Medium	Remediate	LOW	3	Fail	—	—	12.2s	5
sysctl_net_ipv6_conf_all_accept_source_route	Disable Kernel Parameter for Accepting Source-Rout…	Medium	Remediate	LOW	3	Fail	—	—	10.9s	5
sysctl_net_ipv6_conf_all_forwarding	Disable Kernel Parameter for IPv6 Forwarding	Medium	Remediate	LOW	3	Fail	—	—	1540.9s	5

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
sysctl_net_ipv6_conf_default_accept_ra	Disable Accepting Router Advertisements on all IPv…	Medium	Remediate	LOW	3	Fail	—	—	11.5s	5
sysctl_net_ipv4_conf_all_accept_source_route	Disable Kernel Parameter for Accepting Source-Rout…	Medium	Remediate	LOW	3	Fail	Approved (7/10)	✓	1458.4s	11
sysctl_net_ipv4_conf_all_forwarding	Disable Kernel Parameter for IPv4 Forwarding on al…	Medium	Remediate	LOW	3	Fail	—	—	5.3s	5
sysctl_net_ipv4_conf_all_rp_filter	Enable Kernel Parameter to Use Reverse Path Filter…	Medium	Remediate	LOW	3	Fail	Rejected (1/10)	—	284.2s	26
sysctl_net_ipv4_conf_default_accept_redirects	Disable Kernel Parameter for Accepting ICMP Redire…	Medium	Remediate	LOW	3	Fail	—	—	5.4s	5
sysctl_net_ipv4_icmp_echo_ignore_broadcasts	Enable Kernel Parameter to Ignore ICMP Broadcast E…	Medium	Remediate	LOW	3	Fail	—	—	247.5s	7
sysctl_net_ipv4_tcp_syncookies	Enable Kernel Parameter to Use TCP Syncookies on N…	Medium	Remediate	LOW	3	Fail	—	—	8.4s	6
sysctl_net_ipv4_conf_all_send_redirects	Disable Kernel Parameter for Sending ICMP Redirect…	Medium	Remediate	LOW	3	Fail	—	—	8.5s	5
sysctl_net_ipv4_conf_default_send_redirects	Disable Kernel Parameter for Sending ICMP Redirect…	Medium	Remediate	LOW	3	Fail	—	—	248.8s	7
kernel_module_atm_disabled	Disable ATM Support	Medium	Remediate	LOW	3	Fail	—	—	4.2s	5
kernel_module_can_disabled	Disable CAN Support	Medium	Remediate	LOW	3	Fail	—	—	5.6s	5
kernel_module_sctp_disabled	Disable SCTP Support	Medium	Remediate	LOW	3	Fail	Approved (9/10)	✓	22.8s	13

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
networkmanager_dns_mode	NetworkManager DNS Mode Must Be Must Configured	Medium	Remediate	LOW	3	Fail	Rejected (3/10)	—	133.5s	3
kernel_module_usb-storage_disabled	Disable Modprobe Loading of USB Storage Driver	Medium	Remediate	LOW	3	Fail	—	—	4.3s	5
mount_option_boot_efi_nosuid	Add nosuid Option to /boot/efi	Medium	Remediate	LOW	3	Fail	Approved (10/10)	✓	11.6s	8
mount_option_boot_nodev	Add nodev Option to /boot	Medium	Remediate	LOW	3	Fail	—	—	4.2s	5
mount_option_boot_nosuid	Add nosuid Option to /boot	Medium	Remediate	LOW	3	Fail	—	—	4.8s	5
mount_option_dev_shm_nodev	Add nodev Option to /dev/shm	Medium	Remediate	LOW	3	Fail	—	—	5.6s	5
mount_option_dev_shm_nosuid	Add nosuid Option to /dev/shm	Medium	Remediate	LOW	3	Fail	Approved (10/10)	✗	25.6s	3
mount_option_home_noexec	Add noexec Option to /home	Medium	Remediate	LOW	3	Fail	—	—	29.2s	5
mount_option_home_nosuid	Add nosuid Option to /home	Medium	Remediate	LOW	3	Fail	—	—	3.9s	5
mount_option_nodev_nonroot_local_partitions	Add nodev Option to Non-Root Local Partitions	Medium	Remediate	LOW	3	Fail	—	—	9.8s	7
sysctl_kernel_core_pattern	Disable storing core dumps	Medium	Remediate	LOW	3	Fail	—	—	12.5s	8
sysctl_kernel_kexec_load_disabled	Disable Kernel Image Loading	Medium	Remediate	LOW	3	Fail	Approved (10/10)	✓	136.2s	9
sysctl_kernel_yama_ptrace_scope	Restrict usage of ptrace to descendant processes	Medium	Remediate	LOW	3	Fail	—	—	3.8s	5

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
sysctl_net_core_bpf_jit_harden	Harden the operation of the BPF just-in-time compi…	Medium	Remediate	LOW	3	Fail	—	—	125.6s	6
sysctl_user_max_user_namespaces_no_remediation	Disable the use of user namespaces	Medium	Remediate	LOW	3	Fail	—	—	4.9s	5
service_systemd-coredump_disabled	Disable acquiring, saving, and processing core dum…	Medium	Remediate	LOW	3	Fail	Approved (9/10)	✓	12.6s	8
coredump_disable_backtraces	Disable core dump backtraces	Medium	Remediate	LOW	3	Fail	—	—	5.6s	5
coredump_disable_storage	Disable storing core dump	Medium	Remediate	LOW	3	Fail	—	—	21.7s	5
disable_users_coredumps	Disable Core Dumps for All Users	Medium	Remediate	LOW	3	Fail	—	—	32.8s	18
sysctl_kernel_randomize_va_space	Enable Randomized Layout of Virtual Address Space	Medium	Remediate	LOW	3	Fail	—	—	9.1s	5
selinux_context_elevation_for_sudo	Elevate The SELinux Context When An Administrator …	Medium	Remediate	LOW	3	Fail	—	—	4.0s	5
service_kdump_disabled	Disable KDump Kernel Crash Analyzer (kdump)	Medium	Remediate	LOW	3	Fail	—	—	3.8s	5
file_permissions_cron_d	Verify Permissions on cron.d	Medium	Remediate	LOW	3	Fail	—	—	7.2s	5
file_permissions_cron_daily	Verify Permissions on cron.daily	Medium	Remediate	LOW	3	Fail	Rejected (1/10)	—	11.1s	2
file_permissions_cron_hourly	Verify Permissions on cron.hourly	Medium	Remediate	LOW	3	Fail	—	—	5.2s	5
file_permissions_cron_monthly	Verify Permissions on cron.monthly	Medium	Remediate	LOW	3	Fail	Approved (9/10)	✗	25.8s	4

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
file_permissions_cron_weekly	Verify Permissions on cron.weekly	Medium	Remediate	LOW	3	Fail	—	—	8.6s	5
package_fapolicyd_installed	Install fapolicyd Package	Medium	Remediate	LOW	3	Fail	—	—	17.8s	5
service_fapolicyd_enabled	Enable the File Access Policy Service	Medium	Remediate	LOW	3	Fail	Approved (7/10)	✓	64.0s	27
fapolicy_default_deny	Configure Fapolicy Module to Employ a Deny-all, Pe…	Medium	Remediate	LOW	3	Fail	Rejected (None/10)	—	4.0s	2
package_postfix_installed	The Postfix package is installed	Medium	Remediate	LOW	3	Fail	Approved (10/10)	✗	24.8s	6
package_s-nail_installed	The s-nail Package Is Installed	Medium	Remediate	LOW	3	Fail	—	—	5.3s	5
postfix_client_configure_mail_alias	Configure System to Forward All Mail For The Root …	Medium	Remediate	LOW	3	Fail	—	—	8.7s	5
chronyd_server_directive	Ensure Chrony is only configured with the server d…	Medium	Remediate	LOW	3	Fail	—	—	17.1s	5
disable_host_auth	Disable Host-Based Authentication	Medium	Remediate	LOW	3	Fail	—	—	15.0s	5
sshd_disable_compression	Disable Compression Or Set Compression to delayed	Medium	Remediate	LOW	3	Fail	—	—	17.9s	5
sshd_disable_gssapi_auth	Disable GSSAPI Authentication	Medium	Remediate	LOW	3	Fail	—	—	5.3s	5
sshd_disable_kerb_auth	Disable Kerberos Authentication	Medium	Remediate	LOW	3	Fail	—	—	6.3s	5
sshd_disable_rhosts	Disable SSH Support for .rhosts Files	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	34.0s	8
sshd_disable_user_known_hosts	Disable SSH Support for User Known Hosts	Medium	Remediate	LOW	3	Fail	—	—	9.7s	8
sshd_enable_pubkey_auth	Enable Public Key Authentication	Medium	Remediate	LOW	3	Fail	—	—	19.0s	5

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
sshd_enable_strictmodes	Enable Use of Strict Mode Checking	Medium	Remediate	LOW	3	Fail	—	—	143.4s	6
sshd_print_last_log	Enable SSH Print Last Log	Medium	Remediate	LOW	3	Fail	—	—	3.1s	5
sshd_rekey_limit	Force frequent session key renegotiation	Medium	Remediate	LOW	3	Fail	—	—	23.3s	5
sshd_set_loglevel_verbose	Set SSH Daemon LogLevel to VERBOSE	Medium	Remediate	LOW	3	Fail	—	—	13.7s	5
sshd_x11_use_localhost	Prevent remote hosts from connecting to the proxy …	Medium	Remediate	LOW	3	Fail	—	—	61.0s	9

Requires Human Review (20)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
aide_check_audit_tools	Configure AIDE to Verify the Audit Tools	Medium	Human Review	LOW	0	—	—	—	3.9s	1
fips_custom_stig_sub_policy	Implement STIG Sub Crypto Policy	Medium	Human Review	MEDIUM	0	—	—	—	5.0s	1
installed_OS_is_vendor_supported	The Installed Operating System Is Vendor Supported	High	Human Review	MEDIUM	0	—	—	—	3.9s	1
sudoers_validate_passwd	Ensure invoking users password for privilege escal…	Medium	Human Review	LOW	0	—	—	—	64.8s	2
account_password_pam_faillock_system_auth	Configure the Use of the pam_faillock.so Module in…	Medium	Human Review	LOW	0	—	—	—	3.8s	1
accounts_passwords_pam_faillock_deny_root	Configure the root Account for Failed Password Att…	Medium	Human Review	LOW	0	—	—	—	3.9s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
accounts_passwords_pam_faillock_unlock_time	Set Lockout Time for Failed Password Attempts	Medium	Human Review	LOW	0	—	—	—	3.9s	1
disable_ctrlaltdel_burstaction	Disable Ctrl-Alt-Del Burst Action	High	Human Review	LOW	0	—	—	—	2.7s	1
rsyslog_encrypt_offload_actionsendstreamdrivermode	Ensure Rsyslog Encrypts Off-Loaded Audit Records	Medium	Human Review	LOW	0	—	—	—	3.2s	1
rsyslog_encrypt_offload_defaultnetstreamdriver	Ensure Rsyslog Encrypts Off-Loaded Audit Records	Medium	Human Review	LOW	0	—	—	—	1.8s	1
rsyslog_remote_access_monitoring	Ensure remote access methods are monitored in Rsys…	Medium	Human Review	LOW	0	—	—	—	2.6s	1
sysctl_net_ipv4_conf_default_rp_filter	Enable Kernel Parameter to Use Reverse Path Filter…	Medium	Human Review	MEDIUM	0	—	—	—	4.1s	1
kernel_module_bluetooth_disabled	Disable Bluetooth Kernel Module	Medium	Human Review	LOW	0	—	—	—	2.0s	1
rootfiles_configured	Ensure rootfiles tmpfile.d is Configured Correctly	Medium	Human Review	LOW	0	—	—	—	4.8s	1
mount_option_dev_shm_noexec	Add noexec Option to /dev/shm	Medium	Human Review	MEDIUM	0	—	—	—	3.7s	1
sysctl_kernel_unprivileged_bpf_disabled	Disable Access to Network bpf() Syscall From Unpri…	Medium	Human Review	LOW	0	—	—	—	2.6s	1
grub2_page_poison_argument	Enable page allocator poisoning	Medium	Human Review	LOW	0	—	—	—	3.0s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
package_policycoreutils-python-utils_installed	Install policycoreutils-python-utils package	Medium	Human Review	MEDIUM	0	—	—	—	5.7s	1
chronyd_or_ntpd_set_maxpoll	Configure Time Service Maxpoll Interval	Medium	Human Review	LOW	0	—	—	—	2.9s	1
sshd_do_not_permit_user_env	Do Not Allow SSH Environment Options	Medium	Human Review	LOW	0	—	—	—	2.9s	1

Discarded / Blocked (6)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
enable_dracut_fips_module	Enable Dracut FIPS Module	High	Blocked	CRITICAL	0	—	—	—	4.5s	1
enable_fips_mode	Enable FIPS Mode	High	Blocked	CRITICAL	0	—	—	—	5.5s	1
fips_crypto_subpolicy	FIPS Must Use a Supported Subpolicy	Medium	Blocked	CRITICAL	0	—	—	—	5.2s	1
sysctl_crypto_fips_enabled	Set kernel parameter 'crypto.fips_enabled' to 1	High	Blocked	CRITICAL	0	—	—	—	6.3s	1
partition_for_var_tmp	Ensure /var/tmp Located On Separate Partition	Medium	Blocked	CRITICAL	0	—	—	—	0.0s	0
grub2_init_on_free	The system must booted with init_on_free=1	Medium	Blocked	CRITICAL	0	—	—	—	2.0s	1

Detailed Finding Reports

package_aide_installed: Install AIDE — SUCCESS

Rule	package_aide_installed
Severity	Medium
Description	The aide package can be installed with the following command: $ sudo dnf install aide
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing AIDE provides file integrity checking capabilities.
Estimated Impact	filesystems affected

Remediation (1 attempt(s))

Attempt #	1
Commands	dnf install -y aide
Scan Passed	✓
Success	✓
Duration	96.5s
Error	—

Review Verdict

Approved	✓

Optimal	✓
Security Score	10/10
Feedback	The plan conditionally installs the AIDE package only if it is not already installed, ensuring idempotency and resolving the vulr
Concerns	—

QA Result

Safe	✓
Verdict	Installing the AIDE package via dnf is a standard package installation that does not modify critical service configurations or de
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	10
Duration	43.7s
Total Tokens	44,143
Cost	$0.0068
Agents	Triage(1), Remedy(7), Review(1), Qa(1)

aide_build_database: Build and Test AIDE Database — SUCCESS

Rule	aide_build_database
Severity	Medium
Description	Run the following command to generate a new database: $ sudo /usr/sbin/aide --init By default, the database will be written to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a

Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the AIDE package and initializing its database is a standard file integrity hardening step that does not modify authen
Estimated Impact	filesystems affected

Remediation (1 attempt(s))

Attempt #	1
Commands	dnf install -y aide, /usr/sbin/aide --init, cp /var/lib/aide/aide.db.new.gz /var/lib/aide/aide.db.gz, dnf install -y aide, /usr/sbin/aide
Scan Passed	✓
Success	✓
Duration	310.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan installs AIDE, kills existing processes, initializes the database, and copies it to the correct location, which should res
Concerns	—

QA Result

Safe	✓

Verdict	The plan installs AIDE, stops any stray AIDE processes, initializes the database, and moves it into place. These actions are c
Side Effects	Possible interruption of an ongoing AIDE check if one is running, but this is non■critical and will be retried.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	48.4s
Total Tokens	34,634
Cost	$0.0063
Agents	Triage(1), Remedy(6), Review(2), Qa(2)

aide_check_audit_tools: Configure AIDE to Verify the Audit Tools — REQUIRES_HUMAN_REVIEW

Rule	aide_check_audit_tools
Severity	Medium
Description	The operating system file integrity tool must be configured to protect the integrity of the audit tools.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The operating system file integrity tool must be configured to protect the integrity of the audit tools; without proper configuratio

Estimated Impact	filesystems affected; AIDE integrity verification not configured; File integrity tool missing or misconfigured

LLM Metrics

LLM Calls	1
Duration	3.9s
Total Tokens	1,654
Cost	$0.0005
Agents	Triage(1)

aide_scan_notification: Configure Notification of Post-AIDE Scan Details — FAILED

Rule	aide_scan_notification
Severity	Medium
Description	AIDE should notify appropriate personnel of the details of a scan after the scan has been run. If AIDE has already been confi
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	This finding involves configuring a notification mechanism for AIDE scan results via cron and email. It does not grant new priv
Estimated Impact	filesystems affected

Remediation (3 attempt(s))

Attempt #	1

Commands	dnf install -y aide, sed -i '@/usr/sbin/aide.*--check@d' /etc/crontab, sed -i '\\/usr\\/sbin\\/aide.*--check/d' /etc/crontab, dnf instal
Scan Passed	✗
Success	✗
Duration	263.6s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	15.9s
Error	—

Attempt #	3
Commands	rpm -q aide, echo '05 4 * * * root /usr/sbin/aide --check | /bin/mail -s "$(hostname) - AIDE Integrity Check" root@localhost' >>
Scan Passed	✗
Success	✗
Duration	1251.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10

Feedback	The plan correctly ensures AIDE is installed and adds a cron job with email notification, which satisfies the requirement. Howe
Concerns	May create duplicate cron jobs if run multiple times; Hardcodes recipient as root@localhost; may not be appropriate in all env

QA Result

Safe	✓
Verdict	The remediation installs AIDE and ensures a cron job for integrity checks with email notification, which is unlikely to disrupt sy
Side Effects	Potential duplicate cron jobs if the remediation is applied multiple times
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	72.9s
Total Tokens	97,379
Cost	$0.0122
Agents	Remedy(16), Review(1), Qa(1)

aide_use_fips_hashes: Configure AIDE to Use FIPS 140-2 for Validating Hashes — FAILED

Rule	aide_use_fips_hashes
Severity	Medium
Description	By default, the sha512 option is added to the NORMAL ruleset in AIDE. If using a custom ruleset or the sha512 option is miss
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The change involves configuring the AIDE audit tool to use a stronger hash (sha512) for file integrity monitoring. This is an au
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	13.0s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	15.1s
Error	—

Attempt #	3
Commands	rpm -q aide, bash /tmp/remediate_aide.sh, ['A-Z][A-Za-z_]*[[:space:]]*=/ { split($0, a, "="); key=a[1]; value=a[2]; gsub(/^[[:spac
Scan Passed	✗

Success	✗
Duration	1143.1s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	10/10
Feedback	Plan ensures sha512 is present in all ruleset groups by conditionally appending if missing.
Concerns	—

QA Result

Safe	✓
Verdict	The remediation only modifies AIDE configuration to ensure SHA-512 is present in rulesets, does not affect critical services, a
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	19
Duration	162.6s
Total Tokens	210,696
Cost	$0.0334
Agents	Remedy(15), Review(2), Qa(2)

enable_dracut_fips_module: Enable Dracut FIPS Module — *DISCARDED*

Rule	enable_dracut_fips_module
Severity	High
Description	Red Hat Enterprise Linux 9 has an installation-time kernel flag that can enable FIPS mode. The installer must be booted with
Recommendation	Review and remediate: Enable Dracut FIPS Module
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Enabling FIPS mode requires adding the fips module to dracut and regenerating the initramfs with the fips=1 kernel paramete
Estimated Impact	reboot required; filesystems affected; System may become unbootable if dracut regenerated incorrectly; FIPS mode requires

LLM Metrics

LLM Calls	1
Duration	4.4s
Total Tokens	1,297
Cost	$0.0004
Agents	Triage(1)

enable_fips_mode: Enable FIPS Mode — *DISCARDED*

Rule	enable_fips_mode
Severity	High

Description	Red Hat Enterprise Linux 9 has an installation-time kernel flag that can enable FIPS mode. The installer must be booted with
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! (["${container:-}" == "bwrap-osbuild"]) && rpm
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	The finding concerns enabling FIPS mode via a kernel boot flag, which is a bootloader/kernel parameter. Incorrect configurati
Estimated Impact	reboot required; FIPS mode not enabled reduces cryptographic assurance; System may fail to meet FIPS 140-2 or other com

LLM Metrics

LLM Calls	1
Duration	5.5s
Total Tokens	2,174
Cost	$0.0008
Agents	Triage(1)

fips_crypto_subpolicy: FIPS Must Use a Supported Subpolicy — DISCARDED

Rule	fips_crypto_subpolicy
Severity	Medium
Description	Sub-policies can be used to modify existing crypto policies. Some sub-policies such as NO-ENFORCE-EMS reduce the secu
Recommendation	Review and remediate: FIPS Must Use a Supported Subpolicy
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Modifying the FIPS cryptographic subpolicy can alter the set of allowed cryptographic algorithms, potentially breaking service
Estimated Impact	reboot required; authentication/authorization affected; networking affected; May break cryptographic validation for services su

LLM Metrics

LLM Calls	1
Duration	5.2s
Total Tokens	1,857
Cost	$0.0007
Agents	Triage(1)

fips_custom_stig_sub_policy: Implement STIG Sub Crypto Policy — REQUIRES_HUMAN_REVIEW

Rule	fips_custom_stig_sub_policy
Severity	Medium
Description	Create a custom cryptographic policy to follow the guidance from DISA.
Recommendation	Remediation script: cat << 'EOF' > /etc/crypto-policies/policies/modules/STIG.pmod cipher@SSH=AES-256-GCM AES-256-C
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: Validation/JSON error with nvidia/nemotron-3-super-120b Invalid JSON: control character (\u0000-\u001F) found while parsing a string at lin…
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	5.0s
Total Tokens	1,771
Cost	$0.0006
Agents	Triage(1)

sysctl_crypto_fips_enabled: Set kernel parameter 'crypto.fips_enabled' to 1 — *DISCARDED*

Rule	sysctl_crypto_fips_enabled
Severity	High
Description	System running in FIPS mode is indicated by kernel parameter 'crypto.fips_enabled'. This parameter should be set to 1 in FIP
Recommendation	Review and remediate: Set kernel parameter 'crypto.fips_enabled' to 1
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Enabling FIPS mode via sysctl crypto.fips_enabled on a running system is not supported; FIPS mode must be enabled at boo
Estimated Impact	reboot required; Loss of cryptographic functionality; System boot failure if FIPS mode mismatched; Unsupported state leading

LLM Metrics

LLM Calls	1
Duration	6.3s
Total Tokens	1,356
Cost	$0.0004
Agents	Triage(1)

configure_crypto_policy: Configure System Cryptography Policy — FAILED

Rule	configure_crypto_policy
Severity	High
Description	To configure the system cryptography policy to use ciphers only from the policy, run the following command: $ sudo update-c
Recommendation	Remediation script: var_system_crypto_policy='' stderr_of_call=$(update-crypto-policies --set ${var_system_crypto_policy} 2>
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The update-crypto-policies command sets system-wide cryptographic policy via symlinks in /etc/crypto-policies/back-ends, wh
Estimated Impact	authentication/authorization affected; Legacy applications that depend on disabled cipher algorithms may fail; Services using

Remediation (3 attempt(s))

Attempt #	1
Commands	update-crypto-policies --set DEFAULT

Scan Passed	✗
Success	✗
Duration	390.3s
Error	—

Attempt #	2
Commands	update-crypto-policies --set DEFAULT, update-crypto-policies --set DEFAULT, update-crypto-policies --set DEFAULT, update
Scan Passed	✗
Success	✗
Duration	1726.4s
Error	—

Attempt #	3
Commands	dnf install -y crypto-policies, update-crypto-policies --set FIPS, update-crypto-policies --reset, update-crypto-policies --check,
Scan Passed	✗
Success	✗
Duration	641.0s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	9/10
Feedback	—

Concerns	—

QA Result

Safe	✓
Verdict	Setting the system crypto policy to FIPS via update-crypto-policies is a hardening change that does not disrupt essential servi
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	45.5s
Total Tokens	71,708
Cost	$0.0089
Agents	Remedy(13), Review(1), Qa(1)

installed_OS_is_vendor_supported: The Installed Operating System Is Vendor Supported — REQUIRES_HUMAN_REVIEW

Rule	installed_OS_is_vendor_supported
Severity	High
Description	The installed operating system must be maintained by a vendor. Red Hat Enterprise Linux is supported by Red Hat, Inc. As th
Recommendation	Review and remediate: The Installed Operating System Is Vendor Supported
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗

Human Review	✓
Risk Level	MEDIUM
Reason	The rule verifies that the running OS is vendor-supported. Remediation would require confirming the OS version and potentia
Estimated Impact	Incorrect OS version identification; Unsupported OS state after change; Potential need for system reboot or service disruption

LLM Metrics

LLM Calls	1
Duration	3.9s
Total Tokens	1,287
Cost	$0.0004
Agents	Triage(1)

partition_for_var_tmp: Ensure /var/tmp Located On Separate Partition — DISCARDED

Rule	partition_for_var_tmp
Severity	Medium
Description	The /var/tmp directory is a world-writable directory used for temporary file storage. Ensure it has its own partition or logical vo
Recommendation	Remediation script: part /var/tmp
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Filesystem/partition/mount-option changes can break boot or services and should not be auto-remediated.

Estimated Impact	reboot required; filesystems affected; filesystems/partitioning; service disruption risk

sudo_require_reauthentication: Require Re-Authentication When Using the sudo Command — FAILED

Rule	sudo_require_reauthentication
Severity	Medium
Description	The sudo timestamp_timeout tag sets the amount of time sudo password prompt waits. The default timestamp_timeout value
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q sudo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The sudo timestamp_timeout parameter controls how long the sudo password prompt waits before requiring re-authentication
Estimated Impact	authentication/authorization affected; filesystems affected; sudo misconfiguration; timestamp_timeout not set or negative; pot

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	21.7s
Error	—

Attempt #	2

Commands	grep -r "Defaults timestamp_timeout" /etc/sudoers.d/, ['eq 0] && sed -i \'/Defaults timestamp_timeout/d\' /etc/sudoers.d/ || ech
Scan Passed	✗
Success	✗
Duration	1658.6s
Error	—

Attempt #	3
Commands	ls -l /etc/sudoers, cp /etc/sudoers /etc/sudoers.bak, sed -i '/timestamp_timeout/d' /etc/sudoers, echo "Defaults timestamp_time
Scan Passed	✗
Success	✗
Duration	1593.6s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	9/10
Feedback	The plan correctly ensures a single timestamp_timeout line set to 5 minutes, validates sudoers syntax, and restores on failure
Concerns	—

QA Result

Safe	✓
Verdict	The plan backs up /etc/sudoers, removes any existing timestamp_timeout lines, adds a single line setting it to 5, validates syn
Side Effects	If a Defaults line contains timestamp_timeout together with other options, those other options will be lost when the line is rem
Regression	✗

Recommendation	Approve

LLM Metrics

LLM Calls	17
Duration	76.7s
Total Tokens	327,106
Cost	$0.0380
Agents	Remedy(15), Review(1), Qa(1)

sudoers_validate_passwd: Ensure invoking users password for privilege escalation when using sudo — REQUIRES_HUMAN_REVIEW

Rule	sudoers_validate_passwd
Severity	Medium
Description	The sudoers security policy requires that users authenticate themselves before they can use sudo. When sudoers requires au
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q sudo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The sudoers security policy mandates that users authenticate before using sudo; failure to enforce this could allow unauthoriz
Estimated Impact	authentication/authorization affected; Missing authentication requirement in sudoers; Potential privilege escalation via sudo

LLM Metrics

LLM Calls	2

Duration	64.3s
Total Tokens	2,149
Cost	$0.0007
Agents	Triage(2)

package_gnutls-utils_installed: Ensure gnutls-utils is installed — SUCCESS

Rule	package_gnutls-utils_installed
Severity	Medium
Description	The gnutls-utils package can be installed with the following command: $ sudo dnf install gnutls-utils
Recommendation	Remediation script: if ! rpm -q --quiet "gnutls-utils" ; then dnf install -y "gnutls-utils" fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The gnutls-utils package can be installed with the command: $ sudo dnf install gnutls-utils
Estimated Impact	networking affected; Package not installed

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗

Duration	19.9s
Error	—

Attempt #	2
Commands	dnf install -y gnutls-utils
Scan Passed	✓
Success	✓
Duration	173.6s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	10/10
Feedback	—
Concerns	—

QA Result

Safe	✓
Verdict	Installing gnutls-utils via dnf adds only the package utilities; no configuration files are modified, so it is unlikely to disrupt critica
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	10

Duration	20.3s
Total Tokens	26,047
Cost	$0.0030
Agents	Remedy(8), Review(1), Qa(1)

package_nss-tools_installed: Ensure nss-tools is installed — SUCCESS

Rule	package_nss-tools_installed
Severity	Medium
Description	The nss-tools package can be installed with the following command: $ sudo dnf install nss-tools
Recommendation	Remediation script: if ! rpm -q --quiet "nss-tools" ; then dnf install -y "nss-tools" fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the nss-tools package adds only utility libraries and command-line tools for Network Security Services; it does not m
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗

Duration	11.8s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	76.6s
Error	—

Attempt #	3
Commands	dnf install -y nss-tools, dnf install -y nss-tools, :, dnf install -y nss-tools
Scan Passed	✓
Success	✓
Duration	142.0s
Error	—

LLM Metrics

LLM Calls	9
Duration	104.7s
Total Tokens	199,200
Cost	$0.0364
Agents	Remedy(9)

package_subscription-manager_installed: Install subscription-manager Package — SUCCESS

Rule	package_subscription-manager_installed
Severity	Medium
Description	The subscription-manager package can be installed with the following command: $ sudo dnf install subscription-manager
Recommendation	Remediation script: if ! rpm -q --quiet "subscription-manager" ; then dnf install -y "subscription-manager" fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The subscription-manager package can be installed with the command: $ sudo dnf install subscription-manager
Estimated Impact	—

Remediation (2 attempt(s))

Attempt #	1
Commands	rpm -q --quiet subscription-manager, dnf install -y subscription-manager, rpm -q --quiet subscription-manager
Scan Passed	✗
Success	✗
Duration	343.7s
Error	—

Attempt #	2
Commands	—
Scan Passed	✓
Success	✓

Duration	11.9s
Error	—

LLM Metrics

LLM Calls	5
Duration	11.9s
Total Tokens	10,255
Cost	$0.0012
Agents	Remedy(5)

ensure_gpgcheck_local_packages: Ensure gpgcheck Enabled for Local Packages — FAILED

Rule	ensure_gpgcheck_local_packages
Severity	High
Description	dnf should be configured to verify the signature(s) of local packages prior to installation. To configure dnf to verify signatures
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q dnf; then # Strip any search characte
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling gpgcheck in DNF ensures that local packages are verified for signatures before installation, mitigating the risk of ins
Estimated Impact	filesystems affected; Package tampering; Unsigned package installation

Remediation (3 attempt(s))

Attempt #	1
Commands	grep -i localpkg_gpgcheck /etc/dnf/dnf.conf, echo 'localpkg_gpgcheck=1' >> /etc/dnf/dnf.conf
Scan Passed	✗
Success	✗
Duration	441.6s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	125.7s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	253.1s
Error	—

Review Verdict

Approved	✗
Optimal	✗

Security Score	2/10
Feedback	The plan only reads and rewrites the existing config without making any changes, so it will not ensure localpkg_gpgcheck=1 i
Concerns	Plan does not specify any modification to the configuration file; reading and writing back the same content leaves the setting u

LLM Metrics

LLM Calls	4
Duration	19.8s
Total Tokens	10,547
Cost	$0.0025
Agents	Remedy(3), Review(1)

enable_authselect: Enable authselect — FAILED

Rule	enable_authselect
Severity	Medium
Description	Configure user authentication setup to use the authselect tool. If authselect profile is selected, the rule will enable the profile.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_authselect_pro
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The finding describes enabling the authselect tool for user authentication setup, which is a configuration change that does not
Estimated Impact	authentication/authorization affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	185.9s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	125.2s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	4.8s
Error	—

LLM Metrics

LLM Calls	5
Duration	4.8s

Total Tokens	9,375
Cost	$0.0011
Agents	Remedy(5)

banner_etc_issue: Modify the System Login Banner — FAILED

Rule	banner_etc_issue
Severity	Medium
Description	To configure the system login banner edit /etc/issue. Replace the default text with a message compliant with the local site pol
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then login_banner_text=
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Editing /etc/issue to set a login banner is a simple configuration change that does not alter authentication mechanisms, servic
Estimated Impact	filesystems affected; Incorrect banner text could lead to non■compliance with policy; Improper file permissions could affect fil

Remediation (3 attempt(s))

Attempt #	1
Commands	echo 'Authorized use only.' > /etc/issue, printf 'Authorized use only.\n' > /etc/issue, :, printf 'Authorized use only.\n' > /etc/issue
Scan Passed	✗
Success	✗
Duration	1563.3s

Error	—

Attempt #	2
Commands	echo You are accessing a U.S. Government (USG) Information System (IS) that is provided for USG-authorized use only. By
Scan Passed	✗
Success	✗
Duration	738.0s
Error	—

Attempt #	3
Commands	ls -l /etc/issue
Scan Passed	✗
Success	✗
Duration	377.8s
Error	—

LLM Metrics

LLM Calls	8
Duration	23.0s
Total Tokens	31,995
Cost	$0.0038
Agents	Remedy(8)

account_password_pam_faillock_password_auth: Configure the Use of the pam_faillock.so Module in the /etc/pam.d/password-auth … — *SUCCESS*

Rule	account_password_pam_faillock_password_auth
Severity	Medium
Description	The pam_faillock.so module must be loaded in preauth in /etc/pam.d/password-auth.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if [-f /usr/bin/auths
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling pam_faillock.so in the preauth section of password-auth implements account lockout after failed authentication atter
Estimated Impact	authentication/authorization affected; Potential lockout if pam_faillock.so parameters are misconfigured (e.g., too low unlock t

Remediation (2 attempt(s))

Attempt #	1
Commands	['x /usr/bin/authselect ']']
Scan Passed	✗
Success	✗
Duration	134.4s
Error	—

Attempt #	2
Commands	which authselect, authselect list, authselect enable-feature with-faillock, authselect select minimal, authselect enable-feature w
Scan Passed	✓
Success	✓

Duration	1738.2s
Error	—

LLM Metrics

LLM Calls	15
Duration	39.8s
Total Tokens	59,933
Cost	$0.0066
Agents	Remedy(15)

account_password_pam_faillock_system_auth: Configure the Use of the pam_faillock.so Module in the /etc/pam.d/system-auth Fi… — REQUIRES_HUMAN_REVIEW

Rule	account_password_pam_faillock_system_auth
Severity	Medium
Description	The pam_faillock.so module must be loaded in preauth in /etc/pam.d/system-auth.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if [-f /usr/bin/auths
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The pam_faillock.so module must be loaded in the preauth stack of /etc/pam.d/system-auth to enforce proper authentication l
Estimated Impact	authentication/authorization affected; filesystems affected; misconfiguration; authentication bypass

LLM Metrics

LLM Calls	1
Duration	3.8s
Total Tokens	1,598
Cost	$0.0005
Agents	Triage(1)

accounts_passwords_pam_faillock_deny: Lock Accounts After Failed Password Attempts — FAILED

Rule	accounts_passwords_pam_faillock_deny
Severity	Medium
Description	This rule configures the system to lock out accounts after a number of incorrect login attempts using pam_faillock.so. pam_fa
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	This rule locks accounts after a threshold of failed password attempts to mitigate brute-force attacks, following pam_faillock.s
Estimated Impact	authentication/authorization affected; Brute-force password guessing; Account lockout bypass

Remediation (3 attempt(s))

Attempt #	1
Commands	["f /etc/security/faillock.conf]; then mkdir -p /etc/security; echo -e '[pam_faillock]\n deny = 3' > /etc/security/faillock.conf; else .
Scan Passed	✗

Success	✗
Duration	769.3s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	11.0s
Error	—

Attempt #	3
Commands	sed -i 's/^#\?\s*deny\s*=.*/deny = 3/' /etc/security/faillock.conf, which authselect
Scan Passed	✗
Success	✗
Duration	952.3s
Error	—

LLM Metrics

LLM Calls	13
Duration	154.2s
Total Tokens	59,287
Cost	$0.0065
Agents	Remedy(13)

accounts_passwords_pam_faillock_deny_root: Configure the root Account for Failed Password Attempts — REQUIRES_HUMAN_REVIEW

Rule	accounts_passwords_pam_faillock_deny_root
Severity	Medium
Description	This rule configures the system to lock out the root account after a number of incorrect login attempts using pam_faillock.so. p
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The finding configures pam_faillock to lock out the root account after a number of failed login attempts, which is a standard au
Estimated Impact	authentication/authorization affected; Misconfiguration could lock out root access; Requires pam_faillock.so module to be pre

LLM Metrics

LLM Calls	1
Duration	3.9s
Total Tokens	1,563
Cost	$0.0005
Agents	Triage(1)

accounts_passwords_pam_faillock_dir: Lock Accounts Must Persist — FAILED

Rule	accounts_passwords_pam_faillock_dir
Severity	Medium

Description	This rule ensures that the system lock out accounts using pam_faillock.so persist after system reboot. From "pam_faillock" m
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The rule ensures that the pam_faillock module uses a persistent directory for storing failure timestamps, so that account locko
Estimated Impact	authentication/authorization affected; filesystems affected; Misconfiguration could cause pam_faillock to fail, disabling lockout

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	137.5s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	13.7s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	144.9s
Error	—

LLM Metrics

LLM Calls	6
Duration	25.2s
Total Tokens	47,982
Cost	$0.0076
Agents	Remedy(6)

accounts_passwords_pam_faillock_interval: Set Interval For Counting Failed Password Attempts — FAILED

Rule	accounts_passwords_pam_faillock_interval
Severity	Medium
Description	Utilizing pam_faillock.so, the fail_interval directive configures the system to lock out an account after a number of incorrect log
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗

Risk Level	LOW
Reason	Configuring pam_faillock's fail_interval is a standard PAM hardening step that does not modify authentication mechanisms in
Estimated Impact	authentication/authorization affected; Incorrect fail_interval value could lead to premature account lockout if set too low; Manu

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	11.0s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	69.9s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	13.9s

Error	—

LLM Metrics

LLM Calls	6
Duration	13.9s
Total Tokens	14,784
Cost	$0.0018
Agents	Remedy(6)

accounts_passwords_pam_faillock_unlock_time: Set Lockout Time for Failed Password Attempts — REQUIRES_HUMAN_REVIEW

Rule	accounts_passwords_pam_faillock_unlock_time
Severity	Medium
Description	This rule configures the system to lock out accounts during a specified time period after a number of incorrect login attempts
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	Configuring lockout time for failed password attempts mitigates brute-force attacks by limiting consecutive failed login attempt
Estimated Impact	authentication/authorization affected; filesystems affected; CWE-259: Use of Hard-coded Credentials; CWE-307: Improper Re

LLM Metrics

LLM Calls	1

Duration	3.8s
Total Tokens	1,637
Cost	$0.0005
Agents	Triage(1)

accounts_password_pam_dcredit: Ensure PAM Enforces Password Requirements - Minimum Digit Characters — FAILED

Rule	accounts_password_pam_dcredit
Severity	Medium
Description	The pam_pwquality module's dcredit parameter controls requirements for usage of digits in a password. When set to a negati
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adjusting the dcredit parameter in pam_pwquality enforces a minimum number of digits in passwords, a standard password c
Estimated Impact	authentication/authorization affected; Users with existing passwords lacking sufficient digits will be prompted to change them

Remediation (3 attempt(s))

Attempt #	1
Commands	sed -i -e '/^\s*#\s*dcredit\s*=.*/d' -e '/^\s*dcredit\s*=.*/d' /etc/security/pwquality.conf, sed -i '/dcredit/d' /etc/security/pwquality.co
Scan Passed	✗
Success	✗

Duration	1740.5s
Error	—

Attempt #	2
Commands	sed -i '/^\s*#\?\s*dcredit\s*=.*/d' /etc/security/pwquality.conf, awk '/^\s*#\?\s*dcredit\s*=.*/d/{nextfile}' /etc/security/pwquality.co
Scan Passed	✗
Success	✗
Duration	1218.7s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	6.3s
Error	—

LLM Metrics

LLM Calls	5
Duration	6.3s
Total Tokens	14,325
Cost	$0.0018
Agents	Remedy(5)

accounts_password_pam_dictcheck: Ensure PAM Enforces Password Requirements - Prevent the Use of Dictionary Words — FAILED

Rule	accounts_password_pam_dictcheck
Severity	Medium
Description	The pam_pwquality module's dictcheck check if passwords contains dictionary words. When dictcheck is set to 1 passwords
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Modifying the pam_pwquality dictcheck setting is a standard password hardening change that does not affect system access
Estimated Impact	authentication/authorization affected; Users may experience password rejection if chosen password contains dictionary words

Remediation (3 attempt(s))

Attempt #	1
Commands	['d /etc/security/pwquality.conf.d]; then find /etc/security/pwquality.conf.d -name "*.conf", "type f -exec sed -i '/dictcheck/d' {} +
Scan Passed	✗
Success	✗
Duration	1539.6s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗

Duration	30.1s
Error	—

Attempt #	3
Commands	sed -i 's/\bdictcheck=0\b/dictcheck=1/g' /etc/security/pwquality.conf.d/pwquality.conf, sed -i 's/\\bdictcheck=0\\b/dictcheck=1/g
Scan Passed	✗
Success	✗
Duration	1097.5s
Error	—

LLM Metrics

LLM Calls	14
Duration	162.2s
Total Tokens	152,869
Cost	$0.0190
Agents	Remedy(14)

accounts_password_pam_difok: Ensure PAM Enforces Password Requirements - Minimum Different Characters — FAILED

Rule	accounts_password_pam_difok
Severity	Medium
Description	The pam_pwquality module's difok parameter sets the number of characters in a password that must not be present in and ol
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The pam_pwquality module's difok parameter controls how many characters must differ between the old and new password c
Estimated Impact	authentication/authorization affected; Weak password complexity; Password reuse; Increased susceptibility to brute-force atta

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	21.0s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	10.1s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗

Success	✗
Duration	7.4s
Error	—

LLM Metrics

LLM Calls	5
Duration	7.4s
Total Tokens	13,515
Cost	$0.0018
Agents	Remedy(5)

accounts_password_pam_enforce_root: Ensure PAM Enforces Password Requirements - Enforce for root User — FAILED

Rule	accounts_password_pam_enforce_root
Severity	Medium
Description	The pam_pwquality module's enforce_for_root parameter controls requirements for enforcing password complexity for the roo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The pam_pwquality module's enforce_for_root parameter controls requirements for enforcing password complexity for the roo
Estimated Impact	authentication/authorization affected; filesystems affected; weak_password_policy; missing_enforcement

Remediation (3 attempt(s))

Attempt #	1
Commands	[["space:]]*enforce_for_root[[:space:]]*$' /etc/security/pwquality.conf"]], enforce_for_root /etc/security/pwquality.conf, grep 'enf
Scan Passed	✗
Success	✗
Duration	163.7s
Error	—

Attempt #	2
Commands	[["space:]]*=.*/enforce_for_root = 1/' /etc/security/pwquality.conf"]], [["space:]]*=.*/enforce_for_root = 1/' /etc/security/pwquality
Scan Passed	✗
Success	✗
Duration	152.4s
Error	—

Attempt #	3
Commands	[["space:]]*#[[:space:]]*enforce_for_root[[:space:]]*/enforce_for_root/' /etc/security/pwquality.conf"]], [["space:]]*#[[:space:]]*enf
Scan Passed	✗
Success	✗
Duration	61.2s
Error	—

LLM Metrics

LLM Calls	14
Duration	58.8s

Total Tokens	192,884
Cost	$0.0257
Agents	Remedy(14)

accounts_password_pam_lcredit: Ensure PAM Enforces Password Requirements - Minimum Lowercase Characters — FAILED

Rule	accounts_password_pam_lcredit
Severity	Medium
Description	The pam_pwquality module's lcredit parameter controls requirements for usage of lowercase letters in a password. When set
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The pam_pwquality module's lcredit parameter controls the requirement for lowercase letters in passwords. Setting lcredit to a
Estimated Impact	authentication/authorization affected; weak_password_complexity

Remediation (3 attempt(s))

Attempt #	1
Commands	sed -i -E 's/^\s*#\s*lcredit\s*=.*/lcredit = -1/' /etc/security/pwquality.conf, grep -E '^\s*lcredit\s*=\s*-1' /etc/security/pwquality.co
Scan Passed	✗
Success	✗
Duration	21.9s

Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	49.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	126.4s
Error	—

LLM Metrics

LLM Calls	6
Duration	125.4s
Total Tokens	12,910
Cost	$0.0016
Agents	Remedy(6)

accounts_password_pam_maxclassrepeat: Ensure PAM Enforces Password Requirements - Maximum Consecutive Repeating Charac… — FAILED

Rule	accounts_password_pam_maxclassrepeat
Severity	Medium
Description	The pam_pwquality module's maxclassrepeat parameter controls requirements for consecutive repeating characters from the
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The pam_pwquality module's maxclassrepeat parameter controls requirements for consecutive repeating characters from the
Estimated Impact	authentication/authorization affected; Weak password policy; Potential for brute-force attacks

Remediation (3 attempt(s))

Attempt #	1
Commands	rpm -q kernel-core && rpm -q libpwquality && grep -sq maxclassrepeat /etc/security/pwquality.conf.d/*.conf, sed -i "/maxclass
Scan Passed	✗
Success	✗
Duration	27.9s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗

Duration	35.9s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	135.3s
Error	—

LLM Metrics

LLM Calls	10
Duration	133.3s
Total Tokens	67,898
Cost	$0.0077
Agents	Remedy(10)

accounts_password_pam_maxrepeat: Set Password Maximum Consecutive Repeating Characters — FAILED

Rule	accounts_password_pam_maxrepeat
Severity	Medium
Description	The pam_pwquality module's maxrepeat parameter controls requirements for consecutive repeating characters. When set to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adjusting the pam_pwquality maxrepeat parameter is a standard password complexity hardening step. It only affects passwo
Estimated Impact	authentication/authorization affected; Potential user lockout if maxrepeat is set too low, causing legitimate passwords to be re

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	8.9s
Error	—

Attempt #	2
Commands	sed -i 's/^# maxrepeat = 0$/maxrepeat = 3/' /etc/security/pwquality.conf
Scan Passed	✗
Success	✗
Duration	133.6s
Error	—

Attempt #	3
Commands	sed -i '/^\s*#\?\s*maxrepeat\s*=.*/d' /etc/security/pwquality.conf, echo "maxrepeat = 3" >> /etc/security/pwquality.conf, sed -i '/
Scan Passed	✗

Success	✗
Duration	22.8s
Error	—

LLM Metrics

LLM Calls	6
Duration	18.6s
Total Tokens	42,904
Cost	$0.0062
Agents	Remedy(6)

accounts_password_pam_minclass: Ensure PAM Enforces Password Requirements - Minimum Different Categories — FAILED

Rule	accounts_password_pam_minclass
Severity	Medium
Description	The pam_pwquality module's minclass parameter controls requirements for usage of different character classes, or types, of c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adjusting pam_pwquality minclass enforces password complexity as per STIG; it is a standard PAM hardening change that d
Estimated Impact	authentication/authorization affected; Users with existing passwords not meeting the new class requirement will be forced to c

Remediation (3 attempt(s))

Attempt #	1
Commands	sed -i 's/^\s*minclass\s*=.*/minclass = 3/' /etc/security/pwquality.conf, sed -i 's/^\s*minclass\s*=.*/minclass = 3/' /etc/security/p
Scan Passed	✗
Success	✗
Duration	146.1s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	5.8s
Error	—

Attempt #	3
Commands	ls /etc/security/pwquality.conf.d/ 2>/dev/null, grep -n 'minclass' /etc/security/pwquality.conf.d/pwquality.conf, ls -la /etc/security
Scan Passed	✗
Success	✗
Duration	26.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	8/10
Feedback	The plan correctly identifies the need to set minclass in the appropriate PAM pwquality configuration file and would resolve th
Concerns	The plan does not specify exactly which file will be edited when multiple candidates exist, potentially leading to inconsistent c

QA Result

Safe	✓
Verdict	The remediation only changes PAM password quality configuration to enforce stricter password policies; it does not modify or
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	24.4s
Total Tokens	89,921
Cost	$0.0108
Agents	Remedy(16), Review(1), Qa(1)

accounts_password_pam_minlen: Ensure PAM Enforces Password Requirements - Minimum Length — FAILED

Rule	accounts_password_pam_minlen
Severity	Medium
Description	The pam_pwquality module's minlen parameter controls requirements for minimum characters required in a password. Add m
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adjusting the pam_pwquality minlen parameter is a standard password hardening change that does not require a reboot and
Estimated Impact	authentication/authorization affected; Setting minlen too high could lock out existing users whose passwords do not meet the

Remediation (3 attempt(s))

Attempt #	1
Commands	sed -i 's/^#\s*minlen\s*=.*/minlen = 14/' /etc/security/pwquality.conf, ls -la /etc/security/pwquality.conf.d/ 2>/dev/null || echo "D
Scan Passed	✗
Success	✗
Duration	137.7s
Error	—

Attempt #	2
Commands	mkdir -p /etc/security/pwquality.conf.d/, echo "minlen = 14" > /etc/security/pwquality.conf.d/99-minlen.conf, cat /etc/security/pw
Scan Passed	✗
Success	✗
Duration	39.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗

Success	✗
Duration	20.2s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	10/10
Feedback	The plan creates the required directory and sets pam_pwquality minlen to 14, enforcing a minimum password length of 14 ch
Concerns	—

QA Result

Safe	✓
Verdict	The remediation creates the required directory and sets pam_pwquality minlen to 14, enforcing a minimum password length o
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	8
Duration	20.2s
Total Tokens	41,036
Cost	$0.0064
Agents	Remedy(6), Review(1), Qa(1)

accounts_password_pam_ocredit: Ensure PAM Enforces Password Requirements - Minimum Special Characters — *FAILED*

Rule	accounts_password_pam_ocredit
Severity	Medium
Description	The pam_pwquality module's ocredit= parameter controls requirements for usage of special (or "other") characters in a passw
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The pam_pwquality module's ocredit parameter controls special character usage in passwords; negative values require a min
Estimated Impact	authentication/authorization affected; Weak password policy

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	10.1s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗

Success	✗
Duration	7.4s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	13.4s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	8/10
Feedback	Plan sets ocredit to -1, enforcing at least one special character requirement in passwords.
Concerns	—

QA Result

Safe	✓
Verdict	The remediation sets ocredit to -1 in /etc/security/pwquality.conf, enforcing at least one special character requirement for pas
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	13.4s
Total Tokens	22,211
Cost	$0.0035
Agents	Remedy(7), Review(2), Qa(2)

accounts_password_pam_pwquality_retry: Ensure PAM Enforces Password Requirements - Authentication Retry Prompts Permitt… — *FAILED*

Rule	accounts_password_pam_pwquality_retry
Severity	Medium
Description	To configure the number of retry prompts that are permitted per-session: Edit the /etc/security/pwquality.conf to include retry=
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_password_par
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adjusting the retry limit in /etc/security/pwquality.conf is a standard password policy hardening step that only affects the numb
Estimated Impact	authentication/authorization affected; Setting retry too low could cause legitimate users to be locked out after mistyped passw

Remediation (3 attempt(s))

Attempt #	1
Commands	sed -i -e 's/^retry\s*=.*/retry = 3/' -e '$a\nretry = 3/' /etc/security/pwquality.conf, if grep -q '^retry\s*=' /etc/security/pwquality.con

Scan Passed	✗
Success	✗
Duration	36.9s
Error	—

Attempt #	2
Commands	sed -i -e 's/retry = 3/retry=3/g' /etc/security/pwquality.conf
Scan Passed	✗
Success	✗
Duration	258.1s
Error	—

Attempt #	3
Commands	sed -i '/^retry\s*=/d' /etc/security/pwquality.conf, echo "retry=3" >> /etc/security/pwquality.conf, sed -i '/^retry\\s*=/d' /etc/securi
Scan Passed	✗
Success	✗
Duration	135.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	5/10
Feedback	Review error, auto-approving: HTTPSConnectionPool(host='openrouter.ai', port=443): Read timed out. (read timeout=90)

Concerns	—

QA Result

Safe	✓
Verdict	The remediation edited /etc/security/pwquality.conf but produced duplicate retry=3 lines, which is harmless and does not brea
Side Effects	duplicate lines in configuration file
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	21
Duration	133.2s
Total Tokens	177,404
Cost	$0.0220
Agents	Remedy(17), Review(2), Qa(2)

accounts_password_pam_ucredit: Ensure PAM Enforces Password Requirements - Minimum Uppercase Characters — FAILED

Rule	accounts_password_pam_ucredit
Severity	Medium
Description	The pam_pwquality module's ucredit= parameter controls requirements for usage of uppercase letters in a password. When s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	Adjusting the ucredit parameter in /etc/security/pwquality.conf enforces a password complexity requirement for uppercase cha
Estimated Impact	authentication/authorization affected; Existing passwords lacking an uppercase character will be rejected at the next passwor

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	16.5s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	68.6s
Error	—

Attempt #	3
Commands	sed -i 's/^\s*ucredit\s*=.*/ucredit = -1/' /etc/security/pwquality.conf, sed -i 's/^\s*ucredit\s*=.*/ucredit = -1/' /etc/security/pwquali
Scan Passed	✗
Success	✗

Duration	25.6s
Error	—

LLM Metrics

LLM Calls	12
Duration	22.3s
Total Tokens	87,989
Cost	$0.0109
Agents	Remedy(12)

service_debug-shell_disabled: Disable debug-shell SystemD Service — SUCCESS

Rule	service_debug-shell_disabled
Severity	Medium
Description	SystemD's debug-shell service is intended to diagnose SystemD related boot issues with various systemctl commands. Once
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The debug-shell service provides a root shell on tty9 if enabled, increasing attack surface. Disabling, stopping, and masking t
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	systemctl mask --now debug-shell.service, systemctl mask --now debug-shell.service, systemctl mask --now debug-shell.serv
Scan Passed	✓
Success	✓
Duration	783.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	—
Concerns	Plan does not explicitly mention stopping and masking the debug-shell.socket unit; Plan does not verify current state before a

QA Result

Safe	✓
Verdict	Disabling the debug-shell SystemD service is a security hardening measure that does not interfere with core services such as
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	60.4s
Total Tokens	36,906

Cost	$0.0078
Agents	Triage(1), Remedy(5), Review(5), Qa(5)

disable_ctrlaltdel_burstaction: Disable Ctrl-Alt-Del Burst Action — REQUIRES_HUMAN_REVIEW

Rule	disable_ctrlaltdel_burstaction
Severity	High
Description	By default, SystemD will reboot the system if the Ctrl-Alt-Del key sequence is pressed Ctrl-Alt-Delete more than 7 times in 2 s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q syste
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	By default, SystemD will reboot the system if the Ctrl-Alt-Del key sequence is pressed more than 7 times in 2 seconds, which
Estimated Impact	filesystems affected; Configuration weakness leading to reboot (availability impact)

LLM Metrics

LLM Calls	1
Duration	2.7s
Total Tokens	1,527
Cost	$0.0004
Agents	Triage(1)

disable_ctrlaltdel_reboot: Disable Ctrl-Alt-Del Reboot Activation — FAILED

Rule	disable_ctrlaltdel_reboot
Severity	High
Description	By default, SystemD will reboot the system if the Ctrl-Alt-Del key sequence is pressed. To configure the system to ignore the
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if { rpm --quiet -q k
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The default action of Ctrl-Alt-Del triggers a reboot, which can be undesirable; disabling it prevents unintended reboots and is a
Estimated Impact	misconfiguration; unintended reboot

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	5.8s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗

Duration	21.3s
Error	—

Attempt #	3
Commands	systemctl mask ctrl-alt-del.target, systemctl unmask ctrl-alt-del.target, systemctl mask ctrl-alt-del.target, ls -l /etc/systemd/syst
Scan Passed	✗
Success	✗
Duration	139.5s
Error	—

LLM Metrics

LLM Calls	13
Duration	135.4s
Total Tokens	39,795
Cost	$0.0046
Agents	Remedy(13)

package_opensc_installed: Install the opensc Package For Multifactor Authentication — FAILED

Rule	package_opensc_installed
Severity	Medium
Description	The opensc package can be installed with the following command: $ sudo dnf install opensc
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "c
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The opensc package can be installed with the following command: $ sudo dnf install opensc
Estimated Impact	authentication/authorization affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	25.2s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	12.3s
Error	—

Attempt #	3
Commands	dnf install opensc, dnf install opensc, dnf install opensc
Scan Passed	✗

Success	✗
Duration	457.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	Plan installs opensc but does not check for existing installation or platform suitability; consider adding rpm -q opensc check a
Concerns	May attempt to install on unsupported platforms; May re-install already installed package

QA Result

Safe	✓
Verdict	The proposed remediation plan installs the opensc package via dnf install opensc, which is a standard remediation action tha
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	29
Duration	96.8s
Total Tokens	132,497
Cost	$0.0183
Agents	Remedy(15), Review(7), Qa(7)

package_pcsc-lite_installed: Install the pcsc-lite package — FAILED

Rule	package_pcsc-lite_installed
Severity	Medium
Description	The pcsc-lite package can be installed with the following command: $ sudo dnf install pcsc-lite
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "p
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The pcsc-lite package can be installed via dnf; this is a routine package installation with low risk and does not affect authentic
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	22.5s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗

Success	✗
Duration	10.1s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	9.5s
Error	—

LLM Metrics

LLM Calls	5
Duration	9.5s
Total Tokens	7,390
Cost	$0.0008
Agents	Remedy(5)

install_smartcard_packages: Install Smart Card Packages For Multifactor Authentication — FAILED

Rule	install_smartcard_packages
Severity	Medium
Description	Configure the operating system to implement multifactor authentication by installing the required package with the following c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { ! (grep -sqE "^.*\.s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Configure the operating system to implement multifactor authentication by installing the required package openssl-pkcs11 via
Estimated Impact	authentication/authorization affected; networking affected; filesystems affected; missing multifactor authentication

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	5.8s
Error	—

Attempt #	2
Commands	dnf install -y openssl-pkcs11
Scan Passed	✗
Success	✗
Duration	7.8s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗

Success	✗
Duration	13.9s
Error	—

LLM Metrics

LLM Calls	5
Duration	13.9s
Total Tokens	22,455
Cost	$0.0034
Agents	Remedy(5)

service_pcscd_enabled: Enable the pcscd Service — FAILED

Rule	service_pcscd_enabled
Severity	Medium
Description	The pcscd service can be enabled with the following command: $ sudo systemctl enable pcscd.service
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling the pcscd service starts the smart card daemon, which is a low-risk operation that does not affect system boot or ac
Estimated Impact	authentication/authorization affected; Potential increase in attack surface if smart card functionality is not required

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	12.6s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	21.9s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	10.2s
Error	—

LLM Metrics

LLM Calls	5
Duration	10.1s

Total Tokens	8,100
Cost	$0.0009
Agents	Remedy(5)

configure_opensc_card_drivers: Configure opensc Smart Card Drivers — FAILED

Rule	configure_opensc_card_drivers
Severity	Medium
Description	The OpenSC smart card tool can auto-detect smart card drivers; however, setting the smart card drivers in use by your organ
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_smartcard_driv
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The OpenSC smart card tool can auto-detect smart card drivers; however, setting the smart card drivers in use by your organ
Estimated Impact	filesystems affected; Misconfiguration of smart card drivers could allow unauthorized smart card usage.

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	8.6s

Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	5.0s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	6.0s
Error	—

LLM Metrics

LLM Calls	5
Duration	6.0s
Total Tokens	11,890
Cost	$0.0015
Agents	Remedy(5)

account_disable_post_pw_expiration: Set Account Expiration Following Inactivity — FAILED

Rule	account_disable_post_pw_expiration

Severity	Medium
Description	To specify the number of days after a password expires (which signifies inactivity) until an account is permanently disabled, a
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q shad
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling accounts after password expiration reduces the attack surface by ensuring inactive accounts cannot be used.
Estimated Impact	authentication/authorization affected; filesystems affected; Accounts remain enabled after password expiration; Inactive accou

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	19.7s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	162.5s

Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	5.7s
Error	—

LLM Metrics

LLM Calls	5
Duration	5.7s
Total Tokens	12,115
Cost	$0.0015
Agents	Remedy(5)

accounts_maximum_age_login_defs: Set Password Maximum Age — FAILED

Rule	accounts_maximum_age_login_defs
Severity	Medium
Description	To specify password maximum age for new accounts, edit the file /etc/login.defs and add or correct the following line: PASS_
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q shad
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	The PASS_MAX_DAYS parameter in /etc/login.defs defines the maximum password age. If not set, passwords may never ex
Estimated Impact	authentication/authorization affected; filesystems affected; Credential exposure; Password expiration bypass; Privilege escala

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	6.2s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	7.6s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗

Duration	4.6s
Error	—

LLM Metrics

LLM Calls	5
Duration	4.6s
Total Tokens	10,675
Cost	$0.0013
Agents	Remedy(5)

accounts_minimum_age_login_defs: Set Password Minimum Age — FAILED

Rule	accounts_minimum_age_login_defs
Severity	Medium
Description	To specify password minimum age for new accounts, edit the file /etc/login.defs and add or correct the following line: PASS_M
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q shad
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting PASS_MIN_DAYS in /etc/login.defs is a standard password policy hardening that only restricts how soon a user may
Estimated Impact	authentication/authorization affected; User inconvenience if they need to change password sooner than the allowed minimum

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	29.9s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	16.0s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	50.9s
Error	—

LLM Metrics

LLM Calls	5
Duration	50.9s

Total Tokens	76,952
Cost	$0.0133
Agents	Remedy(5)

accounts_password_set_max_life_existing: Set Existing Passwords Maximum Age — FAILED

Rule	accounts_password_set_max_life_existing
Severity	Medium
Description	Configure non-compliant accounts to enforce a -day maximum password lifetime restriction by running the following comman
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_max
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Configures a maximum password lifetime to limit the time window in which a compromised password can be used, reducing t
Estimated Impact	authentication/authorization affected; Passwords never expire; Increased risk of credential compromise

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	4.1s

Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	6.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	22.0s
Error	—

Review Verdict

Approved	✗
Optimal	✗
Security Score	3/10
Feedback	The plan does not validate that PASS_MAX_DAYS is a positive integer, which could lead to incorrect behavior if PASS_MAX
Concerns	Missing validation of PASS_MAX_DAYS to ensure it is a positive integer

LLM Metrics

LLM Calls	2
Duration	22.0s

Total Tokens	9,011
Cost	$0.0036
Agents	Remedy(1), Review(1)

accounts_password_set_min_life_existing: Set Existing Passwords Minimum Age — FAILED

Rule	accounts_password_set_min_life_existing
Severity	Medium
Description	Configure non-compliant accounts to enforce a 24 hours/1 day minimum password lifetime by running the following command
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_mini
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adjusting the minimum password age via chage is a standard authentication hardening action that does not affect login ability
Estimated Impact	authentication/authorization affected; Users who recently changed their password may be temporarily prevented from changin

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	5.3s

Error	—

Attempt #	2
Commands	rpm -q kernel-core
Scan Passed	✗
Success	✗
Duration	29.6s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	21.8s
Error	—

LLM Metrics

LLM Calls	5
Duration	21.8s
Total Tokens	33,111
Cost	$0.0053
Agents	Remedy(5)

accounts_password_pam_unix_rounds_password_auth: Set number of Password Hashing Rounds - password-auth — *FAILED*

Rule	accounts_password_pam_unix_rounds_password_auth

Severity	Medium
Description	Configure the number or rounds for the password hashing algorithm. This can be accomplished by using the rounds option fo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q pam && rpm --quiet -q kernel-core
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The number of rounds for the PAM password hashing algorithm is set too low, reducing the work factor and making brute-forc
Estimated Impact	authentication/authorization affected; Weak password hashing configuration; Insufficient work factor

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	54.7s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	13.2s

Error	—

Attempt #	3
Commands	authselect list, authselect current, authselect info pam_unix.so, authselect list-features, authselect list-features minimal
Scan Passed	✗
Success	✗
Duration	27.8s
Error	—

LLM Metrics

LLM Calls	19
Duration	24.5s
Total Tokens	109,200
Cost	$0.0124
Agents	Remedy(19)

accounts_password_pam_unix_rounds_system_auth: Set number of Password Hashing Rounds - system-auth — FAILED

Rule	accounts_password_pam_unix_rounds_system_auth
Severity	Medium
Description	Configure the number or rounds for the password hashing algorithm. This can be accomplished by using the rounds option fo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q pam && rpm --quiet -q kernel-core
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	Configure the number or rounds for the password hashing algorithm. This can be accomplished by using the rounds option fo
Estimated Impact	authentication/authorization affected; filesystems affected; low iteration count

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	17.3s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	31.7s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗

Duration	6.9s
Error	—

LLM Metrics

LLM Calls	5
Duration	6.9s
Total Tokens	15,037
Cost	$0.0021
Agents	Remedy(5)

no_empty_passwords: Prevent Login to Accounts With Empty Password — FAILED

Rule	no_empty_passwords
Severity	High
Description	If an account is configured for password authentication but does not have an assigned password, it may be possible to log int
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if [-f /usr/bin/auths
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Accounts configured for password authentication without an assigned password allow login without authentication. Remediati
Estimated Impact	authentication/authorization affected; filesystems affected; empty password; PAM misconfiguration

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	127.2s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	12.1s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	18.9s
Error	—

LLM Metrics

LLM Calls	5
Duration	18.9s

Total Tokens	36,820
Cost	$0.0060
Agents	Remedy(5)

use_pam_wheel_for_su: Enforce usage of pam_wheel for su authentication — FAILED

Rule	use_pam_wheel_for_su
Severity	Medium
Description	To ensure that only users who are members of the wheel group can run commands with altered privileges through the su com
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q pam; then # uncomment the option i
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding pam_wheel.so use_uid to /etc/pam.d/su restricts su to wheel group members, a standard STIG hardening step that do
Estimated Impact	authentication/authorization affected; If wheel group is missing or admin users are not members, su may be blocked for legitin

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	22.2s

Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	6.2s
Error	—

Attempt #	3
Commands	echo 'auth required pam_wheel.so use_uid' >> /etc/pam.d/su, echo 'auth required pam_wheel.so use_uid' >> /etc/pam.d/su
Scan Passed	✗
Success	✗
Duration	14.7s
Error	—

LLM Metrics

LLM Calls	10
Duration	13.4s
Total Tokens	45,480
Cost	$0.0054
Agents	Remedy(10)

accounts_logon_fail_delay: Ensure the Logon Failure Delay is Set Correctly in login.defs — FAILED

Rule	accounts_logon_fail_delay

Severity	Medium
Description	To ensure the logon failure delay controlled by /etc/login.defs is set properly, add or correct the FAIL_DELAY setting in /etc/lo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q shadow-utils && rpm --quiet -q kern
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The logon failure delay setting in /etc/login.defs controls how long a user must wait after a failed login attempt before another
Estimated Impact	reboot required; authentication/authorization affected; CWE-307: Improper Restriction of Excessive Authentication Attempts;

Remediation (3 attempt(s))

Attempt #	1
Commands	[["space:]]*#?[[:space:]]*FAIL_DELAY[[:space:]].*/FAIL_DELAY\t4/' /etc/login.defs"]], [["space:]]*#?[[:space:]]*FAIL_DELAY[[:s
Scan Passed	✗
Success	✗
Duration	126.1s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	11.2s

Error	—

Attempt #	3
Commands	sed -i '/^#*FAIL_DELAY/s/FAIL_DELAY\t.*/FAIL_DELAY\t4/' /etc/login.defs, sed -i '/^#*FAIL_DELAY/s/FAIL_DELAY\\t.*/FAIL_
Scan Passed	✗
Success	✗
Duration	89.1s
Error	—

LLM Metrics

LLM Calls	14
Duration	86.6s
Total Tokens	364,268
Cost	$0.0492
Agents	Remedy(14)

accounts_tmout: Set Interactive Session Timeout — FAILED

Rule	accounts_tmout
Severity	Medium
Description	Setting the TMOUT option in /etc/profile ensures that all user sessions will terminate based on inactivity. A value of 0 (zero) d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_tmo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	Setting the TMOUT option in /etc/profile ensures that all user sessions will terminate based on inactivity. A value of 0 disables
Estimated Impact	filesystems affected; misconfiguration

Remediation (3 attempt(s))

Attempt #	1
Commands	grep -n 'TMOUT' /etc/profile, grep -n 'TMOUT' /etc/profile.d/*.sh
Scan Passed	✗
Success	✗
Duration	131.6s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	4.8s
Error	—

Attempt #	3
Commands	grep 'TMOUT' /etc/profile, grep 'TMOUT' /etc/profile.d/*.sh, grep 'TMOUT' /etc/bashrc, grep 'TMOUT' /etc/bash.bashrc 2>/dev
Scan Passed	✗
Success	✗

Duration	36.6s
Error	—

LLM Metrics

LLM Calls	17
Duration	33.2s
Total Tokens	132,508
Cost	$0.0156
Agents	Remedy(17)

file_permission_user_init_files_root: Ensure All User Initialization Files Have Mode 0740 Or Less Permissive — FAILED

Rule	file_permission_user_init_files_root
Severity	Medium
Description	Set the mode of the user initialization files, including the root user, to 0740 with the following commands: $ sudo chmod 0740
Recommendation	Remediation script: var_user_initialization_files_regex='' readarray -t interactive_users < <(awk -F: '$3==0 || $3>=1000 {print
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	User initialization files (e.g., .profile, .bashrc, .bash_login) are executed during user login and can be leveraged for persistenc
Estimated Impact	authentication/authorization affected; filesystems affected; Unauthorized modification of user initialization files; Potential privil

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	29.5s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	24.7s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	27.4s
Error	—

LLM Metrics

LLM Calls	5
Duration	27.4s

Total Tokens	47,895
Cost	$0.0080
Agents	Remedy(5)

accounts_umask_etc_bashrc: Ensure the Default Bash Umask is Set Correctly — FAILED

Rule	accounts_umask_etc_bashrc
Severity	Medium
Description	To ensure the default umask for users of the Bash shell is set properly, add or correct the umask setting in /etc/bashrc to reac
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q bash
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting umask in /etc/bashrc is a standard hardening step that only affects default file permissions for newly created files; it do
Estimated Impact	If umask is set too restrictively, it could cause permission issues for applications or users expecting default permissions.; Inco

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	37.6s

Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	4.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	22.2s
Error	—

LLM Metrics

LLM Calls	5
Duration	21.9s
Total Tokens	49,235
Cost	$0.0083
Agents	Remedy(5)

accounts_umask_etc_csh_cshrc: Ensure the Default C Shell Umask is Set Correctly — FAILED

Rule	accounts_umask_etc_csh_cshrc

Severity	Medium
Description	To ensure the default umask for users of the C shell is set properly, add or correct the umask setting in /etc/csh.cshrc to read
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_use
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The default umask for C shell is not set correctly, which can result in overly permissive file creation permissions and potential
Estimated Impact	authentication/authorization affected; filesystems affected; C shell umask misconfiguration; excessive permissions

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	4.9s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	4.5s

Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	31.2s
Error	—

LLM Metrics

LLM Calls	5
Duration	31.2s
Total Tokens	56,465
Cost	$0.0096
Agents	Remedy(5)

accounts_umask_etc_login_defs: Ensure the Default Umask is Set Correctly in login.defs — FAILED

Rule	accounts_umask_etc_login_defs
Severity	Medium
Description	To ensure the default umask controlled by /etc/login.defs is set properly, add or correct the UMASK setting in /etc/login.defs t
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q shad
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	To ensure the default umask controlled by /etc/login.defs is set properly, add or correct the UMASK setting in /etc/login.defs t
Estimated Impact	authentication/authorization affected; filesystems affected; UMASK misconfiguration

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	47.0s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	6.5s
Error	—

Attempt #	3
Commands	[["space:]]*.*/UMASK 027/' /etc/login.defs"]]
Scan Passed	✗
Success	✗

Duration	20.6s
Error	—

LLM Metrics

LLM Calls	8
Duration	19.8s
Total Tokens	66,609
Cost	$0.0086
Agents	Remedy(8)

accounts_umask_etc_profile: Ensure the Default Umask is Set Correctly in /etc/profile — FAILED

Rule	accounts_umask_etc_profile
Severity	Medium
Description	To ensure the default umask controlled by /etc/profile is set properly, add or correct the umask setting in /etc/profile to read as
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_use
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting a proper umask in /etc/profile ensures that newly created files and directories receive appropriate default permissions
Estimated Impact	filesystems affected; misconfiguration; excessive permissions

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	21.8s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	5.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	6.1s
Error	—

LLM Metrics

LLM Calls	5
Duration	6.1s

Total Tokens	13,355
Cost	$0.0018
Agents	Remedy(5)

grub2_init_on_free: The system must booted with init_on_free=1 — *DISCARDED*

Rule	grub2_init_on_free
Severity	Medium
Description	Setting init_on_free=1 on boot guarantees that pages and heap objects are initialized right after they're freed, so it won't be p
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q grub2-common && rpm --quiet -q k
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Modifying kernel boot parameters via grubby can affect the system's ability to boot; an incorrect setting could prevent boot or
Estimated Impact	reboot required; boot failure; system inaccessible; kernel panic

LLM Metrics

LLM Calls	1
Duration	1.8s
Total Tokens	1,403
Cost	$0.0004
Agents	Triage(1)

grub2_vsyscall_argument: Disable vsyscalls — FAILED

Rule	grub2_vsyscall_argument
Severity	Medium
Description	To disable use of virtual syscalls, add the argument vsyscall=none to the default GRUB 2 command line for the Linux operati
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q grub2-common && rpm --quiet -q k
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling vsyscalls removes the virtual system call interface, reducing the kernel's attack surface and preventing potential priv
Estimated Impact	reboot required; Privilege escalation via syscalls; Increased kernel attack surface

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	3.3s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗

Success	✗
Duration	3.6s
Error	—

Attempt #	3
Commands	sed -i '/^GRUB_CMDLINE_LINUX=/s/"$/ vsyscall=none"/' /etc/default/grub, grub2-mkconfig
Scan Passed	✗
Success	✗
Duration	29.0s
Error	—

LLM Metrics

LLM Calls	7
Duration	24.2s
Total Tokens	56,213
Cost	$0.0085
Agents	Remedy(7)

grub2_admin_username: Set the Boot Loader Admin Username to a Non-Default Value — FAILED

Rule	grub2_admin_username
Severity	High
Description	The grub2 boot loader should have a superuser account and password protection enabled to protect boot-time settings. To m
Recommendation	Review and remediate: Set the Boot Loader Admin Username to a Non-Default Value
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing the boot loader admin username from the default 'root' to a unique, non-default value reduces the risk of unauthoriz
Estimated Impact	reboot required; authentication/authorization affected; filesystems affected; Default credentials; Boot loader configuration

Remediation (3 attempt(s))

Attempt #	1
Commands	cat /etc/grub.d/01_users, grep superusers /etc/grub.d/01_users, ls -l /etc/grub.d/01_users
Scan Passed	✗
Success	✗
Duration	137.7s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	8.2s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗

Success	✗
Duration	128.3s
Error	—

LLM Metrics

LLM Calls	8
Duration	126.5s
Total Tokens	19,178
Cost	$0.0023
Agents	Remedy(8)

grub2_password: Set Boot Loader Password in grub2 — FAILED

Rule	grub2_password
Severity	High
Description	The grub2 boot loader should have a superuser account and password protection enabled to protect boot-time settings. Since
Recommendation	Review and remediate: Set Boot Loader Password in grub2
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The grub2 boot loader should have a superuser account and password protection enabled to protect boot-time settings. Since
Estimated Impact	reboot required; authentication/authorization affected; plaintext passwords in boot loader; lack of password protection

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	55.7s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	3.9s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	9.8s
Error	—

LLM Metrics

LLM Calls	5
Duration	9.8s

Total Tokens	19,365
Cost	$0.0029
Agents	Remedy(5)

package_rsyslog-gnutls_installed: Ensure rsyslog-gnutls is installed — SUCCESS

Rule	package_rsyslog-gnutls_installed
Severity	Medium
Description	TLS protocol support for rsyslog is installed. The rsyslog-gnutls package can be installed with the following command: $ sudo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "r
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The rsyslog-gnutls package provides TLS support for rsyslog, enabling encrypted transmission of log messages. Installing thi
Estimated Impact	—

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	15.7s

Error	—

Attempt #	2
Commands	dnf install -y rsyslog-gnutls
Scan Passed	✓
Success	✓
Duration	120.7s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	10/10
Feedback	—
Concerns	—

QA Result

Safe	✓
Verdict	Installing the rsyslog-gnutls package via dnf is a standard package installation that does not modify configuration files or disru
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	9
Duration	32.9s

Total Tokens	18,945
Cost	$0.0028
Agents	Remedy(7), Review(1), Qa(1)

rsyslog_encrypt_offload_actionsendstreamdriverauthmode: Ensure Rsyslog Authenticates Off-Loaded Audit Records — FAILED

Rule	rsyslog_encrypt_offload_actionsendstreamdriverauthmode
Severity	Medium
Description	Rsyslogd is a system utility providing support for message logging. Support for both internet and UNIX domain sockets enabl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The change only adds a TLS authentication mode for remote logging in rsyslog configuration. It does not affect local authenti
Estimated Impact	networking affected; Incorrect TLS settings could prevent remote log forwarding; Missing or misnamed certificate could cause

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	9.2s

Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	126.0s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	125.6s
Error	—

LLM Metrics

LLM Calls	6
Duration	124.6s
Total Tokens	10,130
Cost	$0.0012
Agents	Remedy(6)

rsyslog_encrypt_offload_actionsendstreamdrivermode: Ensure Rsyslog Encrypts Off-Loaded Audit Records — REQUIRES_HUMAN_REVIEW

Rule	rsyslog_encrypt_offload_actionsendstreamdrivermode
Severity	Medium
Description	Rsyslogd is a system utility providing support for message logging. Support for both internet and UNIX domain sockets enabl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	To protect the integrity and confidentiality of audit logs, ensuring they cannot be altered or intercepted during off■loading tran
Estimated Impact	networking affected; Log tampering; Unauthorized access to log data; Data leakage during transmission

LLM Metrics

LLM Calls	1
Duration	3.2s
Total Tokens	1,826
Cost	$0.0005
Agents	Triage(1)

rsyslog_encrypt_offload_defaultnetstreamdriver: Ensure Rsyslog Encrypts Off-Loaded Audit Records — REQUIRES_HUMAN_REVIEW

Rule	rsyslog_encrypt_offload_defaultnetstreamdriver
Severity	Medium

Description	Rsyslogd is a system utility providing support for message logging. Support for both internet and UNIX domain sockets enabl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	Rsyslog should encrypt off-loaded audit records to protect log integrity and confidentiality. Without encryption, logs are vulner
Estimated Impact	log tampering; information disclosure; audit bypass

LLM Metrics

LLM Calls	1
Duration	1.8s
Total Tokens	1,541
Cost	$0.0004
Agents	Triage(1)

rsyslog_remote_access_monitoring: Ensure remote access methods are monitored in Rsyslog — REQUIRES_HUMAN_REVIEW

Rule	rsyslog_remote_access_monitoring
Severity	Medium
Description	Logging of remote access methods must be implemented to help identify cyber attacks and ensure ongoing compliance with r
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	Monitoring remote access methods in rsyslog helps detect unauthorized access attempts and supports compliance with remo
Estimated Impact	authentication/authorization affected; networking affected; Insufficient logging of remote access attempts; Undetected brute fo

LLM Metrics

LLM Calls	1
Duration	2.6s
Total Tokens	1,792
Cost	$0.0005
Agents	Triage(1)

rsyslog_remote_loghost: Ensure Logs Sent To Remote Host — FAILED

Rule	rsyslog_remote_loghost
Severity	Medium
Description	To configure rsyslog to send logs to a remote log server, open /etc/rsyslog.conf and read and understand the last section of tl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then rsyslog_remote_lo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗

Risk Level	LOW
Reason	The rsyslog configuration must be adjusted to forward logs to a remote log server; failure to do so may result in logs not being
Estimated Impact	networking affected; filesystems affected; misconfiguration; incomplete rsyslog.conf

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	20.4s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	6.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	155.2s

Error	—

LLM Metrics

LLM Calls	14
Duration	152.6s
Total Tokens	124,645
Cost	$0.0155
Agents	Remedy(14)

network_configure_name_resolution: Configure Multiple DNS Servers in /etc/resolv.conf — FAILED

Rule	network_configure_name_resolution
Severity	Medium
Description	Determine whether the system is using local or DNS name resolution with the following command: $ sudo grep hosts /etc/nss
Recommendation	Review and remediate: Configure Multiple DNS Servers in /etc/resolv.conf
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Editing /etc/resolv.conf to add DNS server entries is a straightforward network configuration change that does not affect authe
Estimated Impact	networking affected; Incorrect DNS IP addresses could break name resolution; If /etc/resolv.conf is managed by NetworkMan

Remediation (3 attempt(s))

Attempt #	1

Commands	grep -x 'nameserver 8.8.8.8' /etc/resolv.conf, echo "nameserver 8.8.8.8" >> /etc/resolv.conf
Scan Passed	✗
Success	✗
Duration	264.0s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	65.1s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	5.8s
Error	—

LLM Metrics

LLM Calls	5
Duration	5.8s
Total Tokens	14,990

Cost	$0.0019
Agents	Remedy(5)

package_libreswan_installed: Install libreswan Package — SUCCESS

Rule	package_libreswan_installed
Severity	Medium
Description	The libreswan package provides an implementation of IPsec and IKE, which permits the creation of secure tunnels over untru
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "l
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the libreswan package provides an implementation of IPsec and IKE, which permits the creation of secure tunnels o
Estimated Impact	networking affected

Remediation (1 attempt(s))

Attempt #	1
Commands	dnf install -y libreswan, dnf install -y libreswan
Scan Passed	✓
Success	✓
Duration	363.8s
Error	—

LLM Metrics

LLM Calls	10
Duration	142.8s
Total Tokens	20,608
Cost	$0.0025
Agents	Triage(1), Remedy(9)

sysctl_net_ipv6_conf_all_accept_ra: Configure Accepting Router Advertisements on All IPv6 Interfaces — SUCCESS

Rule	sysctl_net_ipv6_conf_all_accept_ra
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.accept_ra kernel parameter, run the following command: $ sudo sysctl -w net
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling acceptance of IPv6 router advertisements prevents rogue RA messages, reducing the risk of unauthorized IPv6 rou
Estimated Impact	networking affected; IPv6 router advertisement acceptance

Remediation (1 attempt(s))

Attempt #	1
Commands	["net.ipv6.conf.all.accept_ra.*/#1net.ipv6.conf.all.accept_ra = 0/' {} +"], echo "net.ipv6.conf.all.accept_ra = 0" >> /etc/sysctl.d/9

Scan Passed	✓
Success	✓
Duration	279.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly disables IPv6 router advertisement acceptance and makes the change persistent. It addresses the vulnera
Concerns	Plan does not check for or remove existing conflicting net.ipv6.conf.all.accept_ra entries in sysctl.d files, which could lead to c

QA Result

Safe	✓
Verdict	Disabling IPv6 router advertisement acceptance is a low-impact change; it does not directly affect critical services like sshd, a
Side Effects	Possible loss of IPv6 stateless address autoconfiguration (SLAAC); Potential minor impact on IPv6 network connectivity if IPv
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	26
Duration	193.3s
Total Tokens	143,216
Cost	$0.0203
Agents	Triage(1), Remedy(15), Review(5), Qa(5)

sysctl_net_ipv6_conf_all_accept_redirects: Disable Accepting ICMP Redirects for All IPv6 Interfaces — FAILED

Rule	sysctl_net_ipv6_conf_all_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.accept_redirects kernel parameter, run the following command: $ sudo sysctl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The fix involves setting a kernel parameter (net.ipv6.conf.all.accept_redirects) to 0 via sysctl, which is a straightforward config
Estimated Impact	networking affected; IPv6 redirect functionality may be disrupted, but this is the intended security outcome of the fix.

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	9.4s
Error	—

Attempt #	2
Commands	—

Scan Passed	✗
Success	✗
Duration	28.9s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	12.1s
Error	—

LLM Metrics

LLM Calls	5
Duration	12.1s
Total Tokens	11,665
Cost	$0.0015
Agents	Remedy(5)

sysctl_net_ipv6_conf_all_accept_source_route: Disable Kernel Parameter for Accepting Source-Routed Packets on all IPv6 Interfa… — *FAILED*

Rule	sysctl_net_ipv6_conf_all_accept_source_route
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.accept_source_route kernel parameter, run the following command: $ sudo s

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	To set the runtime status of the net.ipv6.conf.all.accept_source_route kernel parameter to 0 and ensure persistence via a file
Estimated Impact	networking affected; Kernel parameter modification; IPv6 source-routed packet acceptance

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	13.2s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	15.7s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	10.9s
Error	—

LLM Metrics

LLM Calls	5
Duration	10.9s
Total Tokens	10,215
Cost	$0.0012
Agents	Remedy(5)

sysctl_net_ipv6_conf_all_forwarding: Disable Kernel Parameter for IPv6 Forwarding — FAILED

Rule	sysctl_net_ipv6_conf_all_forwarding
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.forwarding kernel parameter, run the following command: $ sudo sysctl -w ne
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗

Risk Level	LOW
Reason	Disabling IPv6 forwarding is a standard hardening step that does not affect system authentication or essential services; it can
Estimated Impact	networking affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	13.9s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	14.3s
Error	—

Attempt #	3
Commands	sysctl -w net.ipv6.conf.all.forwarding=0, sysctl -w net.ipv6.conf.all.forwarding=0, sysctl -w net.ipv6.conf.all.forwarding=0, sysct
Scan Passed	✗
Success	✗
Duration	1540.9s

Error	—

LLM Metrics

LLM Calls	5
Duration	15.2s
Total Tokens	18,835
Cost	$0.0025
Agents	Remedy(5)

sysctl_net_ipv6_conf_default_accept_ra: Disable Accepting Router Advertisements on all IPv6 Interfaces by Default — FAILED

Rule	sysctl_net_ipv6_conf_default_accept_ra
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.default.accept_ra kernel parameter, run the following command: $ sudo sysctl -v
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the acceptance of router advertisements on IPv6 interfaces prevents rogue IPv6 routers from advertising routes, rec
Estimated Impact	networking affected; If net.ipv6.conf.default.accept_ra is left at its default value of 1, the system will accept router advertiseme

Remediation (3 attempt(s))

Attempt #	1

Commands	—
Scan Passed	✗
Success	✗
Duration	18.3s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	10.3s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	11.5s
Error	—

LLM Metrics

LLM Calls	5
Duration	11.4s
Total Tokens	10,100

Cost	$0.0012
Agents	Remedy(5)

sysctl_net_ipv6_conf_default_accept_redirects: Disable Kernel Parameter for Accepting ICMP Redirects by Default on IPv6 Interfa… — *SUCCESS*

Rule	sysctl_net_ipv6_conf_default_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.default.accept_redirects kernel parameter, run the following command: $ sudo s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The finding involves disabling a kernel parameter via sysctl, which relates to sysctl persistence and is best addressed by safe
Estimated Impact	networking affected; IPv6 network configuration; kernel parameter modification

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv6.conf.default.accept_redirects=0, sysctl net.ipv6.conf.default.accept_redirects
Scan Passed	✓
Success	✓
Duration	362.7s

Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	9/10
Feedback	Plan correctly addresses the vulnerability.
Concerns	—

QA Result

Safe	✓
Verdict	The plan only modifies a kernel sysctl parameter to disable IPv6 ICMP redirects, which is a standard hardening measure and
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	40.3s
Total Tokens	37,364
Cost	$0.0056
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

sysctl_net_ipv6_conf_default_accept_source_route: Disable Kernel Parameter for Accepting Source-Routed Packets on IPv6 Interfaces … — SUCCESS

Rule	sysctl_net_ipv6_conf_default_accept_source_route

Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.default.accept_source_route kernel parameter, run the following command: $ su
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting net.ipv6.conf.default.accept_source_route to 0 disables acceptance of source-routed IPv6 packets, a hardening step t
Estimated Impact	networking affected; Rare legitimate use of IPv6 source routing could be broken

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	10.6s
Error	—

Attempt #	2
Commands	echo 0 > /proc/sys/net/ipv6/conf/default/accept_source_route, echo 0 > /proc/sys/net/ipv6/conf/default/accept_source_route,
Scan Passed	✗
Success	✗
Duration	315.8s

Error	—

Attempt #	3
Commands	—
Scan Passed	✓
Success	✓
Duration	56.7s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	1/10
Feedback	—
Concerns	—

QA Result

Safe	✓
Verdict	The remediation plan correctly addresses the vulnerability by disabling source-routed packet acceptance, which is a security
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	56.6s

Total Tokens	43,076
Cost	$0.0071
Agents	Remedy(9), Review(3), Qa(3)

sysctl_net_ipv4_conf_all_accept_redirects: Disable Accepting ICMP Redirects for All IPv4 Interfaces — SUCCESS

Rule	sysctl_net_ipv4_conf_all_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.accept_redirects kernel parameter, run the following command: $ sudo sysctl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling ICMP redirects is a standard network hardening step that does not affect authentication, authorization, or filesystem
Estimated Impact	networking affected; Minimal risk if ICMP redirects are legitimately used for network optimization

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	7.6s

Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	29.9s
Error	—

Attempt #	3
Commands	sysctl -w net.ipv4.conf.all.accept_redirects=0
Scan Passed	✓
Success	✓
Duration	383.3s
Error	—

LLM Metrics

LLM Calls	8
Duration	24.5s
Total Tokens	32,232
Cost	$0.0041
Agents	Remedy(8)

sysctl_net_ipv4_conf_all_accept_source_route: Disable Kernel Parameter for Accepting Source-Routed Packets on all IPv4 Interfa… — *FAILED*

Rule	sysctl_net_ipv4_conf_all_accept_source_route
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.accept_source_route kernel parameter, run the following command: $ sudo s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the kernel parameter net.ipv4.conf.all.accept_source_route prevents the system from accepting source-routed pack
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	sysctl net.ipv4.conf.all.accept_source_route, sysctl net.ipv4.conf.all.accept_source_route, touch /etc/sysctl.d/99-sysctl.conf, ls
Scan Passed	✗
Success	✗
Duration	986.7s
Error	—

Attempt #	2
Commands	sed -i '$anet.ipv4.conf.all.accept_source_route=0' /etc/sysctl.d/99-sysctl.conf, sed -i '$anet.ipv4.conf.all.accept_source_route=
Scan Passed	✗
Success	✗

Duration	1709.5s
Error	—

Attempt #	3
Commands	sysctl -w net.ipv4.conf.all.accept_source_route=0, sysctl -w net.ipv4.conf.all.accept_source_route=0, sysctl -w net.ipv4.conf.a
Scan Passed	✗
Success	✗
Duration	1458.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan correctly sets net.ipv4.conf.all.accept_source_route to 0 at runtime and persists it via /etc/sysctl.d/99-disable-source
Concerns	No verification that the sysctl -w command succeeded; No idempotency check to ensure the setting is applied correctly

QA Result

Safe	✓
Verdict	The remediation plan sets the kernel parameter to 0 and persists it, which is the correct action to disable acceptance of sourc
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11

Duration	67.1s
Total Tokens	37,890
Cost	$0.0086
Agents	Remedy(5), Review(3), Qa(3)

sysctl_net_ipv4_conf_all_forwarding: Disable Kernel Parameter for IPv4 Forwarding on all IPv4 Interfaces — FAILED

Rule	sysctl_net_ipv4_conf_all_forwarding
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.forwarding kernel parameter, run the following command: $ sudo sysctl -w ne
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	To set the runtime status of the net.ipv4.conf.all.forwarding kernel parameter to 0 and make it persistent via /etc/sysctl.d/.
Estimated Impact	networking affected; IPv4 forwarding can be used for spoofing attacks; May allow unauthorized packet injection or amplificatio

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗

Duration	5.4s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	24.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	5.3s
Error	—

LLM Metrics

LLM Calls	5
Duration	5.3s
Total Tokens	10,475
Cost	$0.0013
Agents	Remedy(5)

sysctl_net_ipv4_conf_all_rp_filter: Enable Kernel Parameter to Use Reverse Path Filtering on all IPv4 Interfaces — FAILED

Rule	sysctl_net_ipv4_conf_all_rp_filter
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.rp_filter kernel parameter, run the following command: $ sudo sysctl -w net.ip
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The setting enables reverse path filtering (rp_filter) which is a standard network hardening measure. Applying it via sysctl doe
Estimated Impact	networking affected; May drop packets in environments with asymmetric routing; Could affect legitimate multihomed or load■

Remediation (3 attempt(s))

Attempt #	1
Commands	sysctl net.ipv4.conf.all.rp_filter, grep -r net.ipv4.conf.all.rp_filter /etc/sysctl.d, ls -la /etc/sysctl.d, sysctl -w net.ipv4.conf.all.rp_fi
Scan Passed	✗
Success	✗
Duration	706.3s
Error	—

Attempt #	2
Commands	cat /proc/sys/net/ipv4/conf/all/rp_filter, echo 1 > /proc/sys/net/ipv4/conf/all/rp_filter, echo 1 > /proc/sys/net/ipv4/conf/all/rp_filte
Scan Passed	✗
Success	✗

Duration	823.1s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	284.2s
Error	—

Review Verdict

Approved	✗
Optimal	✗
Security Score	1/10
Feedback	The remediation plan comments out the kernel parameter setting, which would disable reverse path filtering rather than enabl
Concerns	May disable intended security hardening (reverse path filtering); Could lead to misconfiguration if applied incorrectly

LLM Metrics

LLM Calls	26
Duration	279.0s
Total Tokens	298,920
Cost	$0.0564
Agents	Remedy(9), Review(9), Qa(8)

sysctl_net_ipv4_conf_default_accept_redirects: Disable Kernel Parameter for Accepting ICMP Redirects by Default on IPv4 Interfa… — *FAILED*

Rule	sysctl_net_ipv4_conf_default_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.default.accept_redirects kernel parameter, run the following command: $ sudo s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the acceptance of ICMP redirects by default reduces the attack surface for ICMP-based spoofing and amplification
Estimated Impact	networking affected; ICMP redirect acceptance could be leveraged for network reconnaissance or amplification attacks.

Remediation (3 attempt(s))

Attempt #	1
Commands	sed -i -a -e '/^net\.ipv4\.conf\.default\.accept_redirects/s' -e 's/.*/net.ipv4.conf.default.accept_redirects = 0/' /etc/sysctl.d/99-sys
Scan Passed	✗
Success	✗
Duration	26.3s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗

Duration	8.4s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	5.4s
Error	—

LLM Metrics

LLM Calls	5
Duration	5.4s
Total Tokens	11,680
Cost	$0.0013
Agents	Remedy(5)

sysctl_net_ipv4_conf_default_rp_filter: Enable Kernel Parameter to Use Reverse Path Filtering on all IPv4 Interfaces by … — *REQUIRES_HUMAN_REVIEW*

Rule	sysctl_net_ipv4_conf_default_rp_filter
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.default.rp_filter kernel parameter, run the following command: $ sudo sysctl -w r
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: Validation/JSON error with nvidia/nemotron-3-super-120b finding_id Field required [type=missing, input_value={}, input_type=dict] For …
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	4.1s
Total Tokens	2,212
Cost	$0.0007
Agents	Triage(1)

sysctl_net_ipv4_icmp_echo_ignore_broadcasts: Enable Kernel Parameter to Ignore ICMP Broadcast Echo Requests on IPv4 Interface… — *FAILED*

Rule	sysctl_net_ipv4_icmp_echo_ignore_broadcasts
Severity	Medium
Description	To set the runtime status of the net.ipv4.icmp_echo_ignore_broadcasts kernel parameter, run the following command: $ sudo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The kernel parameter net.ipv4.icmp_echo_ignore_broadcasts controls whether the kernel logs ICMP echo request packets. S
Estimated Impact	networking affected

Remediation (3 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv4.icmp_echo_ignore_broadcasts=0, [["space:]]*)net.ipv4.icmp_echo_ignore_broadcasts.*$/#1net.ipv4.icmp_e
Scan Passed	✗
Success	✗
Duration	14.4s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	142.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗

Success	✗
Duration	247.5s
Error	—

LLM Metrics

LLM Calls	7
Duration	245.5s
Total Tokens	16,215
Cost	$0.0022
Agents	Remedy(7)

sysctl_net_ipv4_tcp_syncookies: Enable Kernel Parameter to Use TCP Syncookies on Network Interfaces — FAILED

Rule	sysctl_net_ipv4_tcp_syncookies
Severity	Medium
Description	To set the runtime status of the net.ipv4.tcp_syncookies kernel parameter, run the following command: $ sudo sysctl -w net.ip
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling the net.ipv4.tcp_syncookies kernel parameter is a configuration change that activates TCP syncookies, a networking
Estimated Impact	networking affected; Kernel parameter modification; Networking configuration

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	4.5s
Error	—

Attempt #	2
Commands	sysctl -w net.ipv4.tcp_syncookies=1
Scan Passed	✗
Success	✗
Duration	19.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	8.4s
Error	—

LLM Metrics

LLM Calls	6
Duration	8.1s

Total Tokens	18,043
Cost	$0.0023
Agents	Remedy(6)

sysctl_net_ipv4_conf_all_send_redirects: Disable Kernel Parameter for Sending ICMP Redirects on all IPv4 Interfaces — *FAILED*

Rule	sysctl_net_ipv4_conf_all_send_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.send_redirects kernel parameter, run the following command: $ sudo sysctl -
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling ICMP redirect sending prevents host from revealing routing information; change is localized to networking stack and
Estimated Impact	networking affected; In rare environments that rely on ICMP redirects for routing, disabling may cause suboptimal routing unti

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	142.0s

Error	—

Attempt #	2
Commands	sysctl -w net.ipv4.conf.all.send_redirects=0, sysctl -w net.ipv4.conf.all.send_redirects=0, sysctl -w net.ipv4.conf.all.send_redir
Scan Passed	✗
Success	✗
Duration	21.9s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	8.5s
Error	—

LLM Metrics

LLM Calls	5
Duration	8.5s
Total Tokens	14,460
Cost	$0.0019
Agents	Remedy(5)

sysctl_net_ipv4_conf_default_send_redirects: Disable Kernel Parameter for Sending ICMP Redirects on all IPv4 Interfaces by De… — *FAILED*

Rule	sysctl_net_ipv4_conf_default_send_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.default.send_redirects kernel parameter, run the following command: $ sudo sys
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	To set the runtime status of the net.ipv4.conf.default.send_redirects kernel parameter, run the following command: $ sudo sys
Estimated Impact	networking affected

Remediation (3 attempt(s))

Attempt #	1
Commands	sysctl net.ipv4.conf.default.send_redirects, sysctl -w net.ipv4.conf.default.send_redirects=0, grep -r '^.*net\.ipv4\.conf\.default\
Scan Passed	✗
Success	✗
Duration	18.2s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗

Duration	68.2s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	248.8s
Error	—

LLM Metrics

LLM Calls	7
Duration	245.8s
Total Tokens	12,915
Cost	$0.0014
Agents	Remedy(7)

kernel_module_atm_disabled: Disable ATM Support — FAILED

Rule	kernel_module_atm_disabled
Severity	Medium
Description	The Asynchronous Transfer Mode (ATM) is a protocol operating on network, data link, and physical layers, based on virtual c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the ATM kernel module via modprobe.d configuration is a straightforward administrative change that does not affec
Estimated Impact	reboot required; networking affected; Kernel module may not load, causing loss of ATM functionality; If ATM is required for ce

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	5.6s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	8.4s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗

Success	✗
Duration	4.2s
Error	—

LLM Metrics

LLM Calls	5
Duration	4.2s
Total Tokens	9,660
Cost	$0.0011
Agents	Remedy(5)

kernel_module_can_disabled: Disable CAN Support — FAILED

Rule	kernel_module_can_disabled
Severity	Medium
Description	The Controller Area Network (CAN) is a serial communications protocol which was initially developed for automotive and is no
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the CAN kernel module removes support for the Controller Area Network bus, reducing the attack surface that could
Estimated Impact	reboot required; networking affected; CAN bus exploitation; Unnecessary kernel module loading

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	29.1s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	19.0s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	5.6s
Error	—

LLM Metrics

LLM Calls	5
Duration	5.6s

Total Tokens	12,485
Cost	$0.0016
Agents	Remedy(5)

kernel_module_sctp_disabled: Disable SCTP Support — FAILED

Rule	kernel_module_sctp_disabled
Severity	Medium
Description	The Stream Control Transmission Protocol (SCTP) is a transport layer protocol, designed to support the idea of message-orie
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the SCTP kernel module via modprobe configuration prevents the module from being loaded. This is a low■risk cha
Estimated Impact	networking affected; May break applications that rely on SCTP transport protocol; Kernel module may be required for certain

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	12.8s

Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	5.3s
Error	—

Attempt #	3
Commands	["f /etc/modprobe.d/sctp.conf]; then sed -i 's|^install sctp.*|install sctp /bin/true|' /etc/modprobe.d/sctp.conf; else echo 'install s
Scan Passed	✗
Success	✗
Duration	22.8s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	9/10
Feedback	The proposed remediation plan adds a modprobe line that installs sctp with /bin/false, which ensures the SCTP module rema
Concerns	Plan does not address the vulnerability; it keeps SCTP disabled.

QA Result

Safe	✓
Verdict	The remediation correctly enables the SCTP kernel module via modprobe configuration, addressing the vulnerability of SCTP

Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	21.8s
Total Tokens	66,161
Cost	$0.0085
Agents	Remedy(11), Review(1), Qa(1)

kernel_module_bluetooth_disabled: Disable Bluetooth Kernel Module — REQUIRES_HUMAN_REVIEW

Rule	kernel_module_bluetooth_disabled
Severity	Medium
Description	The kernel's module loading system can be configured to prevent loading of the Bluetooth module. Add the following to the ap
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The kernel's module loading system can be configured to prevent loading of the Bluetooth module. Adding the appropriate lin
Estimated Impact	reboot required; Bluetooth kernel module could be loaded inadvertently, leading to potential wireless exposure.

LLM Metrics

LLM Calls	1
Duration	2.0s
Total Tokens	1,486
Cost	$0.0004
Agents	Triage(1)

networkmanager_dns_mode: NetworkManager DNS Mode Must Be Must Configured — FAILED

Rule	networkmanager_dns_mode
Severity	Medium
Description	The DNS processing mode in NetworkManager describes how DNS is processed on the system. Depending the mode some
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q NetworkManager; then var_networkı
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing the DNS mode in NetworkManager is a configuration adjustment that does not affect authentication, authorization,
Estimated Impact	networking affected; Potential temporary DNS resolution disruption if the selected mode is incompatible with the network envi

Remediation (3 attempt(s))

Attempt #	1
Commands	—

Scan Passed	✗
Success	✗
Duration	17.6s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	11.6s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	133.5s
Error	—

Review Verdict

Approved	✗
Optimal	✗
Security Score	3/10
Feedback	The proposed remediation attempts to configure NetworkManager's DNS mode but does so unsafely and ineffectively. It risks

Concerns	The sed pattern 's/dns[^( )]*/dns=$var_networkmanager_dns_mode/' adds an unintended trailing slash to DNS values, likely causing DNS lookup failur

LLM Metrics

LLM Calls	3
Duration	132.5s
Total Tokens	5,190
Cost	$0.0017
Agents	Remedy(2), Review(1)

rootfiles_configured: Ensure rootfiles tmpfile.d is Configured Correctly — REQUIRES_HUMAN_REVIEW

Rule	rootfiles_configured
Severity	Medium
Description	To set the mode of the root user initialization file /root/.bash_profile, ensure the following lines are is included in a file ending i
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q rootfiles; then find "/etc/tmpfiles.d/" -
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	To set the mode of the root user initialization file /root/.bash_profile, ensure required lines are included in .conf files under /etc
Estimated Impact	reboot required; authentication/authorization affected; filesystems affected; /etc/tmpfiles.d/; /root/.bash_logout; /root/.bash_pro

LLM Metrics

LLM Calls	1

Duration	4.8s
Total Tokens	2,663
Cost	$0.0009
Agents	Triage(1)

kernel_module_usb-storage_disabled: Disable Modprobe Loading of USB Storage Driver — FAILED

Rule	kernel_module_usb-storage_disabled
Severity	Medium
Description	To prevent USB storage devices from being used, configure the kernel module loading system to prevent automatic loading c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	To prevent USB storage devices from being used, the kernel module loading system must be configured to prevent automatic
Estimated Impact	filesystems affected; USB storage devices could be used to exfiltrate data; Unauthorized kernel module loading could lead to

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗

Duration	35.4s
Error	—

Attempt #	2
Commands	grep -i "Rocky" /etc/os-release, test -f /etc/modprobe.d/usb-storage.conf, sh -c "echo 'blacklist usb-storage' >> /etc/modprobe
Scan Passed	✗
Success	✗
Duration	145.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	4.3s
Error	—

LLM Metrics

LLM Calls	5
Duration	4.3s
Total Tokens	11,730
Cost	$0.0014
Agents	Remedy(5)

mount_option_boot_efi_nosuid: Add nosuid Option to /boot/efi — FAILED

Rule	mount_option_boot_efi_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /boot/efi. The SUID and SGID permissions s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the nosuid mount option to /boot/efi prevents setuid execution on the EFI system partition, which is not required for no
Estimated Impact	filesystems affected; Potential interference with rare EFI applications that rely on suid bits (unlikely)

Remediation (3 attempt(s))

Attempt #	1
Commands	[["space:]]+[^[:space:]]+[[:space:]]+[^[:space:]]+[[:space:]]+)([^[:space:]]*)/1,nosuid2/' /etc/fstab"]], sed -i \"s|UUID=4FDC-64F8
Scan Passed	✗
Success	✗
Duration	1221.6s
Error	—

Attempt #	2
Commands	{'nosuid': 4, ',nosuid': ''}, {'nosuid': 4, ',nosuid': ''}, {'nosuid': 4, ',nosuid': ''}, awk -i inplace '$2 == \"/boot/efi\" && !/^#/ && $4 !~ \/
Scan Passed	✗
Success	✗

Duration	1473.0s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	11.6s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	10/10
Feedback	—
Concerns	—

QA Result

Safe	✓
Verdict	Adding the nosuid mount option to /boot/efi is a standard security hardening measure that does not affect critical services suc
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	8

Duration	11.6s
Total Tokens	22,719
Cost	$0.0031
Agents	Remedy(6), Review(1), Qa(1)

mount_option_boot_nodev: Add nodev Option to /boot — FAILED

Rule	mount_option_boot_nodev
Severity	Medium
Description	The nodev mount option can be used to prevent device files from being created in /boot. Legitimate character and block devic
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The nodev mount option can be used to create device files in /boot, which could allow unauthorized device access. Disabling
Estimated Impact	filesystems affected; CWE-255: Improper Neutralization of Input

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗

Duration	24.2s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	145.1s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	4.2s
Error	—

LLM Metrics

LLM Calls	5
Duration	4.2s
Total Tokens	9,920
Cost	$0.0011
Agents	Remedy(5)

mount_option_boot_nosuid: Add nosuid Option to /boot — FAILED

Rule	mount_option_boot_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /boot. The SUID and SGID permissions sho
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the nosuid mount option to /boot prevents execution of setuid programs in the boot partition, thereby reducing privileg
Estimated Impact	reboot required; authentication/authorization affected; filesystems affected; privilege_escalation; unauthorized_execution

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	14.1s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗

Duration	7.9s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	4.8s
Error	—

LLM Metrics

LLM Calls	5
Duration	4.8s
Total Tokens	8,970
Cost	$0.0010
Agents	Remedy(5)

mount_option_dev_shm_nodev: Add nodev Option to /dev/shm — FAILED

Rule	mount_option_dev_shm_nodev
Severity	Medium
Description	The nodev mount option can be used to prevent creation of device files in /dev/shm. Legitimate character and block devices s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The fix adds the nodev mount option to /dev/shm in /etc/fstab to prevent creation of device files in temporary directories. This
Estimated Impact	filesystems affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	15.7s
Error	—

Attempt #	2
Commands	[["space:]]*[^#].*[[:space:]]/dev/shm[[:space:]]' /etc/fstab || echo 'tmpfs /dev/shm tmpfs defaults,nodev,nosuid,noexec 0 0
Scan Passed	✗
Success	✗
Duration	505.3s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗

Success	✗
Duration	5.6s
Error	—

LLM Metrics

LLM Calls	5
Duration	5.6s
Total Tokens	12,000
Cost	$0.0014
Agents	Remedy(5)

mount_option_dev_shm_noexec: Add noexec Option to /dev/shm — REQUIRES_HUMAN_REVIEW

Rule	mount_option_dev_shm_noexec
Severity	Medium
Description	The noexec mount option can be used to prevent binaries from being executed out of /dev/shm. It can be dangerous to allow
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	The noexec mount option prevents execution of binaries from /dev/shm. Omitting it allows execution of arbitrary code from thi
Estimated Impact	filesystems affected; privilege_escalation; unauthorized_code_execution

LLM Metrics

LLM Calls	1
Duration	3.7s
Total Tokens	1,765
Cost	$0.0005
Agents	Triage(1)

mount_option_dev_shm_nosuid: Add nosuid Option to /dev/shm — FAILED

Rule	mount_option_dev_shm_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /dev/shm. The SUID and SGID permissions
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The nosuid mount option prevents execution of setuid programs in /dev/shm, reducing the risk of privilege escalation from sha
Estimated Impact	authentication/authorization affected; filesystems affected; privilege escalation; unauthorized execution

Remediation (3 attempt(s))

Attempt #	1
Commands	—

Scan Passed	✗
Success	✗
Duration	7.4s
Error	—

Attempt #	2
Commands	mount | grep /dev/shm
Scan Passed	✗
Success	✗
Duration	92.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	25.6s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	10/10
Feedback	—

Concerns	—

QA Result

Safe	✗
Verdict	The remediation plan does not include error checking for the awk command. If the awk command fails (e.g., due to a typo in t
Side Effects	Boot failure
Regression	✗
Recommendation	Rollback

LLM Metrics

LLM Calls	3
Duration	25.6s
Total Tokens	10,250
Cost	$0.0037
Agents	Remedy(1), Review(1), Qa(1)

mount_option_home_noexec: Add noexec Option to /home — FAILED

Rule	mount_option_home_noexec
Severity	Medium
Description	The noexec mount option can be used to prevent binaries from being executed out of /home. Add the noexec option to the fo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	Adding the noexec mount option to /home prevents execution of binaries from user home directories, which is a hardening me
Estimated Impact	filesystems affected; User scripts or applications that rely on executing binaries from /home may break; Legacy software that

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	5.1s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	14.0s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗

Duration	29.2s
Error	—

LLM Metrics

LLM Calls	5
Duration	29.2s
Total Tokens	38,585
Cost	$0.0063
Agents	Remedy(5)

mount_option_home_nosuid: Add nosuid Option to /home — FAILED

Rule	mount_option_home_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /home. The SUID and SGID permissions sh
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the nosuid mount option to /home prevents execution of setuid programs in that directory, reducing the risk of privileg
Estimated Impact	filesystems affected; Privilege escalation via setuid binaries in /home; Unauthorized execution of elevated privileges

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	5.8s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	161.6s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	3.8s
Error	—

LLM Metrics

LLM Calls	5
Duration	3.8s

Total Tokens	9,350
Cost	$0.0010
Agents	Remedy(5)

mount_option_nodev_nonroot_local_partitions: Add nodev Option to Non-Root Local Partitions — FAILED

Rule	mount_option_nodev_nonroot_local_partitions
Severity	Medium
Description	The nodev mount option prevents files from being interpreted as character or block devices. Legitimate character and block d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The nodev mount option prevents files from being interpreted as character or block devices. Legitimate character and block d
Estimated Impact	filesystems affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	6.0s

Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	10.1s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	9.8s
Error	—

LLM Metrics

LLM Calls	7
Duration	9.3s
Total Tokens	21,694
Cost	$0.0028
Agents	Remedy(7)

sysctl_kernel_core_pattern: Disable storing core dumps — FAILED

Rule	sysctl_kernel_core_pattern

Severity	Medium
Description	To set the runtime status of the kernel.core_pattern kernel parameter, run the following command: $ sudo sysctl -w kernel.cor
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting kernel.core_pattern to |/bin/false disables core dumps without affecting authentication, networking, or filesystems. This
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	3.7s
Error	—

Attempt #	2
Commands	sysctl -w kernel.core_pattern=|/bin/false, sysctl kernel.core_pattern, sysctl -w kernel.core_pattern=|/bin/false, [["space:]]*\\)ker
Scan Passed	✗
Success	✗
Duration	59.1s

Error	—

Attempt #	3
Commands	mkdir -p /etc/sysctl.d
Scan Passed	✗
Success	✗
Duration	12.5s
Error	—

LLM Metrics

LLM Calls	8
Duration	11.8s
Total Tokens	32,687
Cost	$0.0041
Agents	Remedy(8)

sysctl_kernel_kexec_load_disabled: Disable Kernel Image Loading — FAILED

Rule	sysctl_kernel_kexec_load_disabled
Severity	Medium
Description	To set the runtime status of the kernel.kexec_load_disabled kernel parameter, run the following command: $ sudo sysctl -w k
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	Setting kernel.kexec_load_disabled=1 prevents arbitrary kernel image loading via kexec, a hardening change that does not a
Estimated Impact	May break legitimate kexec-based recovery mechanisms (e.g., kdump, kexec reboot) if they are in use

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	6.5s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	5.7s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗

Duration	136.2s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	10/10
Feedback	—
Concerns	—

QA Result

Safe	✓
Verdict	Remediation only sets kernel.kexec_load_disabled=1 to disable kexec load; this does not affect core services like sshd, audit
Side Effects	May break kdump crash kernel loading; May prevent kexec-based fast reboot
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	9
Duration	135.1s
Total Tokens	23,331
Cost	$0.0035
Agents	Remedy(7), Review(1), Qa(1)

sysctl_kernel_unprivileged_bpf_disabled: Disable Access to Network bpf() Syscall From Unprivileged Processes — REQUIRES_HUMAN_REVIEW

Rule	sysctl_kernel_unprivileged_bpf_disabled
Severity	Medium
Description	To set the runtime status of the kernel.unprivileged_bpf_disabled kernel parameter, run the following command: $ sudo sysctl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	Disabling the kernel.unprivileged_bpf_disabled parameter prevents unprivileged BPF programs from loading, reducing attack
Estimated Impact	networking affected; CVE-2020-10788; Kernel hardening bypass

LLM Metrics

LLM Calls	1
Duration	2.5s
Total Tokens	1,754
Cost	$0.0005
Agents	Triage(1)

sysctl_kernel_yama_ptrace_scope: Restrict usage of ptrace to descendant processes — FAILED

Rule	sysctl_kernel_yama_ptrace_scope
Severity	Medium
Description	To set the runtime status of the kernel.yama.ptrace_scope kernel parameter, run the following command: $ sudo sysctl -w ke

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The kernel.yama.ptrace_scope parameter enables ptrace tracing for descendant processes. Allowing this may expose kernel
Estimated Impact	filesystems affected; Kernel ptrace exposure; Information disclosure; Privilege escalation

Remediation (3 attempt(s))

Attempt #	1
Commands	sysctl -w kernel.yama.ptrace_scope=1, sysctl -w kernel.yama.ptrace_scope=1, sysctl -w kernel.yama.ptrace_scope=1, sysctl
Scan Passed	✗
Success	✗
Duration	12.4s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	5.4s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	3.7s
Error	—

LLM Metrics

LLM Calls	5
Duration	3.7s
Total Tokens	10,210
Cost	$0.0011
Agents	Remedy(5)

sysctl_net_core_bpf_jit_harden: Harden the operation of the BPF just-in-time compiler — FAILED

Rule	sysctl_net_core_bpf_jit_harden
Severity	Medium
Description	To set the runtime status of the net.core.bpf_jit_harden kernel parameter, run the following command: $ sudo sysctl -w net.co
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗

Risk Level	LOW
Reason	Setting net.core.bpf_jit_harden=2 is a kernel sysctl tweak that enhances BPF JIT security without altering authentication, critic
Estimated Impact	networking affected; Potential performance impact on BPF-heavy workloads; Possible incompatibility with custom BPF progra

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	16.0s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	124.7s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	125.6s

Error	—

LLM Metrics

LLM Calls	6
Duration	124.6s
Total Tokens	9,220
Cost	$0.0010
Agents	Remedy(6)

sysctl_user_max_user_namespaces_no_remediation: Disable the use of user namespaces — FAILED

Rule	sysctl_user_max_user_namespaces_no_remediation
Severity	Medium
Description	To set the runtime status of the user.max_user_namespaces kernel parameter, run the following command: $ sudo sysctl -w
Recommendation	Review and remediate: Disable the use of user namespaces
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting user.max_user_namespaces=0 is a kernel sysctl change that disables user namespaces. It does not affect authentica
Estimated Impact	May affect container runtime if containers rely on user namespaces; May break applications that require user namespaces

Remediation (3 attempt(s))

Attempt #	1

Commands	—
Scan Passed	✗
Success	✗
Duration	8.6s
Error	—

Attempt #	2
Commands	sysctl -w user.max_user_namespaces=0
Scan Passed	✗
Success	✗
Duration	133.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	4.9s
Error	—

LLM Metrics

LLM Calls	5
Duration	4.9s
Total Tokens	9,890

Cost	$0.0012
Agents	Remedy(5)

service_systemd-coredump_disabled: Disable acquiring, saving, and processing core dumps — FAILED

Rule	service_systemd-coredump_disabled
Severity	Medium
Description	The systemd-coredump.socket unit is a socket activation of the systemd-coredump@.service which processes core dumps. E
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SOCKET_NAME=
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the systemd-coredump socket only stops core dump collection; it does not affect authentication, networking, or files
Estimated Impact	Loss of core dump data for post■mortem analysis

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	3.5s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	7.1s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	12.6s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	9/10
Feedback	—
Concerns	—

QA Result

Safe	✓
Verdict	Disabling systemd-coredump.socket only stops core dump processing; does not interfere with SSH, auditd, firewalld, or netwo
Side Effects	—

Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	8
Duration	12.6s
Total Tokens	18,883
Cost	$0.0027
Agents	Remedy(6), Review(1), Qa(1)

coredump_disable_backtraces: Disable core dump backtraces — FAILED

Rule	coredump_disable_backtraces
Severity	Medium
Description	The ProcessSizeMax option in [Coredump] section of /etc/systemd/coredump.conf or in a drop-in file under /etc/systemd/core
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q syste
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting ProcessSizeMax=0 in coredump.conf only affects the size of core dumps processed by systemd-coredump; it does no
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	6.4s
Error	—

Attempt #	2
Commands	['z "$content"] || [! -f /etc/systemd/coredump.conf]; then\n mkdir -p /etc/systemd/coredump.conf.d\n echo \'ProcessSizeM
Scan Passed	✗
Success	✗
Duration	71.6s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	5.6s
Error	—

LLM Metrics

LLM Calls	5
Duration	5.6s

Total Tokens	13,840
Cost	$0.0018
Agents	Remedy(5)

coredump_disable_storage: Disable storing core dump — FAILED

Rule	coredump_disable_storage
Severity	Medium
Description	The Storage option in [Coredump] section of /etc/systemd/coredump.conf or a drop-in file in /etc/systemd/coredump.conf.d/*.c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q syste
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The Storage option in [Coredump] section of /etc/systemd/coredump.conf or a drop-in file in /etc/systemd/coredump.conf.d/*.c
Estimated Impact	filesystems affected; Coredump storage disabled; Potential loss of debugging information

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	5.3s

Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	7.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	21.7s
Error	—

LLM Metrics

LLM Calls	5
Duration	21.6s
Total Tokens	43,439
Cost	$0.0072
Agents	Remedy(5)

disable_users_coredumps: Disable Core Dumps for All Users — FAILED

Rule	disable_users_coredumps

Severity	Medium
Description	To disable core dumps for all users, add the following line to /etc/security/limits.conf, or to a file within the /etc/security/limits.d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling core dumps prevents sensitive memory contents from being written to disk, reducing information leakage and aligni
Estimated Impact	May hinder post■mortem debugging of application crashes

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	3.8s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	6.6s

Error	—

Attempt #	3
Commands	ls -la /etc/security/limits.d/, ls -la /etc/security/limits.d/, echo "* hard core 0" > /etc/security/limits.d/10-ssg-hardening.conf, ls -la
Scan Passed	✗
Success	✗
Duration	32.8s
Error	—

LLM Metrics

LLM Calls	18
Duration	30.1s
Total Tokens	130,156
Cost	$0.0153
Agents	Remedy(18)

sysctl_kernel_randomize_va_space: Enable Randomized Layout of Virtual Address Space — FAILED

Rule	sysctl_kernel_randomize_va_space
Severity	Medium
Description	To set the runtime status of the kernel.randomize_va_space kernel parameter, run the following command: $ sudo sysctl -w k
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	Enabling ASLR via kernel.randomize_va_space=2 is a standard hardening measure that does not affect system stability, auth
Estimated Impact	Potential incompatibility with legacy applications that depend on deterministic memory layout

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	4.2s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	5.2s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗

Duration	9.1s
Error	—

LLM Metrics

LLM Calls	5
Duration	9.1s
Total Tokens	16,805
Cost	$0.0024
Agents	Remedy(5)

grub2_page_poison_argument: Enable page allocator poisoning — REQUIRES_HUMAN_REVIEW

Rule	grub2_page_poison_argument
Severity	Medium
Description	To enable poisoning of free pages, add the argument page_poison=1 to the default GRUB 2 command line for the Linux oper
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q grub2
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The GRUB 2 bootloader can be manipulated via kernel command line arguments, allowing an attacker to inject malicious cod
Estimated Impact	reboot required; authentication/authorization affected; filesystems affected; CWE-200: Exposure of sensitive information; CW

LLM Metrics

LLM Calls	1
Duration	3.0s
Total Tokens	1,999
Cost	$0.0006
Agents	Triage(1)

package_policycoreutils-python-utils_installed: Install policycoreutils-python-utils package — REQUIRES_HUMAN_REVIEW

Rule	package_policycoreutils-python-utils_installed
Severity	Medium
Description	The policycoreutils-python-utils package can be installed with the following command: $ sudo dnf install policycoreutils-pythor
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "p
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: Validation/JSON error with nvidia/nemotron-3-super-120b Invalid JSON: expected value at line 1 column 1 [type=json_invalid, input_value='sa…
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	5.7s
Total Tokens	2,594

Cost	$0.0010
Agents	Triage(1)

selinux_context_elevation_for_sudo: Elevate The SELinux Context When An Administrator Calls The Sudo Command — FAILED

Rule	selinux_context_elevation_for_sudo
Severity	Medium
Description	Configure the operating system to elevate the SELinux context when an administrator calls the sudo command. Edit a file in t
Recommendation	Review and remediate: Elevate The SELinux Context When An Administrator Calls The Sudo Command
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The finding describes elevating SELinux context via sudo command by editing /etc/sudoers.d. This could allow privilege escal
Estimated Impact	authentication/authorization affected; filesystems affected; SELinux context elevation; Improper sudoers configuration

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	125.2s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	4.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	3.7s
Error	—

LLM Metrics

LLM Calls	5
Duration	3.7s
Total Tokens	8,984
Cost	$0.0010
Agents	Remedy(5)

service_kdump_disabled: Disable KDump Kernel Crash Analyzer (kdump) — FAILED

Rule	service_kdump_disabled
Severity	Medium

Description	The kdump service provides a kernel crash dump analyzer. It uses the kexec system call to boot a secondary kernel ("capture
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The kdump service provides a kernel crash dump analyzer. Disabling it removes this debugging capability but does not cause
Estimated Impact	Disabling kdump eliminates kernel crash dump capability; May hinder post-mortem debugging after system crashes

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	4.1s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	8.1s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	3.8s
Error	—

LLM Metrics

LLM Calls	5
Duration	3.8s
Total Tokens	9,310
Cost	$0.0011
Agents	Remedy(5)

file_permissions_cron_d: Verify Permissions on cron.d — FAILED

Rule	file_permissions_cron_d
Severity	Medium
Description	To properly set the permissions of /etc/cron.d, run the command: $ sudo chmod 0700 /etc/cron.d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.d/
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗

Risk Level	LOW
Reason	Setting /etc/cron.d permissions to 0700 restricts directory access to root, which is appropriate for security and does not interfe
Estimated Impact	filesystems affected; Potential breakage if cron jobs rely on group/other access to the directory; If cron daemon runs as a non

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	11.8s
Error	—

Attempt #	2
Commands	ls -ld /etc/cron.d, chmod 0700 /etc/cron.d, ls -ld /etc/cron.d
Scan Passed	✗
Success	✗
Duration	38.6s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	7.2s

Error	—

LLM Metrics

LLM Calls	5
Duration	7.2s
Total Tokens	12,665
Cost	$0.0017
Agents	Remedy(5)

file_permissions_cron_daily: Verify Permissions on cron.daily — FAILED

Rule	file_permissions_cron_daily
Severity	Medium
Description	To properly set the permissions of /etc/cron.daily, run the command: $ sudo chmod 0700 /etc/cron.daily
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.da
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	To properly set the permissions of /etc/cron.daily, run the command: $ sudo chmod 0700 /etc/cron.daily.
Estimated Impact	filesystems affected

Remediation (3 attempt(s))

Attempt #	1

Commands	chmod 0700 /etc/cron.daily, ls -ld /etc/cron.daily
Scan Passed	✗
Success	✗
Duration	7.4s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	23.7s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	11.0s
Error	—

Review Verdict

Approved	✗
Optimal	✗
Security Score	1/10

Feedback	The proposed plan inspects current permissions and, if they are not 0700, attempts to set them using symbolic chmod mode
Concerns	The plan may not set the correct permissions (0700) on /etc/cron.daily.; Reliance on indirect chmod methods could lead to inc

LLM Metrics

LLM Calls	2
Duration	11.0s
Total Tokens	5,457
Cost	$0.0018
Agents	Remedy(1), Review(1)

file_permissions_cron_hourly: Verify Permissions on cron.hourly — FAILED

Rule	file_permissions_cron_hourly
Severity	Medium
Description	To properly set the permissions of /etc/cron.hourly, run the command: $ sudo chmod 0700 /etc/cron.hourly
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.ho
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The /etc/cron.hourly file should have restrictive permissions (e.g., 0640) to prevent unauthorized modification; current permiss
Estimated Impact	authentication/authorization affected; filesystems affected; excessive_permissions; unauthorized_modification; privilege_esca

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	5.9s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	5.1s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	5.2s
Error	—

LLM Metrics

LLM Calls	5
Duration	5.2s

Total Tokens	10,244
Cost	$0.0013
Agents	Remedy(5)

file_permissions_cron_monthly: Verify Permissions on cron.monthly — FAILED

Rule	file_permissions_cron_monthly
Severity	Medium
Description	To properly set the permissions of /etc/cron.monthly, run the command: $ sudo chmod 0700 /etc/cron.monthly
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.m
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting the correct permissions on /etc/cron.monthly ensures that only privileged users can read or modify the cron configurat
Estimated Impact	authentication/authorization affected; filesystems affected; Incorrect permissions could allow non■privileged users to modify c

Remediation (3 attempt(s))

Attempt #	1
Commands	stat -c "%a" /etc/cron.monthly, chmod 0700 /etc/cron.monthly, stat -c "%a" /etc/cron.monthly
Scan Passed	✗
Success	✗
Duration	36.7s

Error	—

Attempt #	2
Commands	find /etc/cron.monthly -maxdepth 0 -type d -exec chmod 0700 {} \;, ls -ld /etc/cron.monthly
Scan Passed	✗
Success	✗
Duration	38.6s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	25.8s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	9/10
Feedback	The plan correctly sets the required permissions but uses an unnecessary find command; could be simplified.
Concerns	—

QA Result

Safe	✗
Verdict	Setting permissions 0700 removes owner read access, likely breaking cron daemon readability.

Side Effects	Cron daemon may fail to read /etc/cron.monthly; Loss of scheduled cron jobs; Potential service disruption
Regression	✗
Recommendation	Rollback

LLM Metrics

LLM Calls	4
Duration	25.7s
Total Tokens	12,328
Cost	$0.0041
Agents	Remedy(2), Review(1), Qa(1)

file_permissions_cron_weekly: Verify Permissions on cron.weekly — FAILED

Rule	file_permissions_cron_weekly
Severity	Medium
Description	To properly set the permissions of /etc/cron.weekly, run the command: $ sudo chmod 0700 /etc/cron.weekly
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.we
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves setting strict permissions (0700) on /etc/cron.weekly and removing special bits (setuid, setgid, sticky
Estimated Impact	If custom cron jobs rely on non-root users having read/execute access to /etc/cron.weekly (highly unusual and against best pr

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	30.2s
Error	—

Attempt #	2
Commands	chmod 0700 /etc/cron.weekly, chmod 0700 /etc/cron.weekly, chmod 0700 /etc/cron.weekly, chmod 0700 /etc/cron.weekly, chr
Scan Passed	✗
Success	✗
Duration	11.4s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	8.6s
Error	—

LLM Metrics

LLM Calls	5
Duration	8.6s

Total Tokens	18,355
Cost	$0.0025
Agents	Remedy(5)

package_fapolicyd_installed: Install fapolicyd Package — FAILED

Rule	package_fapolicyd_installed
Severity	Medium
Description	The fapolicyd package can be installed with the following command: $ sudo dnf install fapolicyd
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "f
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the fapolicyd package adds the application whitelisting daemon without modifying authentication, networking, or exis
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	rpm -q fapolicyd, dnf install -y fapolicyd, dnf reinstall dnf, dnf install -y fapolicyd, ["main]\ngpgcheck=1\ninstallonly_limit=3\ncle
Scan Passed	✗
Success	✗
Duration	48.0s

Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	5.6s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	17.8s
Error	—

LLM Metrics

LLM Calls	5
Duration	17.7s
Total Tokens	28,784
Cost	$0.0045
Agents	Remedy(5)

service_fapolicyd_enabled: Enable the File Access Policy Service — FAILED

Rule	service_fapolicyd_enabled

Severity	Medium
Description	The File Access Policy service should be enabled. The fapolicyd service can be enabled with the following command: $ sudo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling the File Access Policy service is a configuration change that does not typically cause system lockout or break critica
Estimated Impact	filesystems affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	8.6s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	10.8s

Error	—

Attempt #	3
Commands	systemctl enable fapolicyd.service, systemctl enable fapolicyd, systemctl start fapolicyd, ['Unit]\nDescription=File Access Poli
Scan Passed	✗
Success	✗
Duration	64.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan correctly enables and starts fapolicyd.service, which addresses the vulnerability.
Concerns	Plan does not verify that the fapolicyd package is installed before attempting to enable the service.; No error handling for case

QA Result

Safe	✓
Verdict	The plan enables and starts the fapolicyd service, which is a standard system service; enabling it does not disrupt core servic
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	27
Duration	61.0s

Total Tokens	81,710
Cost	$0.0126
Agents	Remedy(15), Review(6), Qa(6)

fapolicy_default_deny: Configure Fapolicy Module to Employ a Deny-all, Permit-by-exception Policy to Al… — *FAILED*

Rule	fapolicy_default_deny
Severity	Medium
Description	The Fapolicy module must be configured to employ a deny-all, permit-by-exception policy to allow the execution of authorized
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then cat > /etc/fapolicyd
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The Fapolicy module must be configured to enforce a deny-all, permit-by-exception policy to ensure only authorized software
Estimated Impact	authentication/authorization affected; filesystems affected; misconfiguration; insufficient policy enforcement

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	134.9s

Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	135.0s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	4.0s
Error	—

Review Verdict

Approved	✗
Optimal	✗
Security Score	None/10
Feedback	Review output was not valid JSON. Raw: { "finding_id": "fapolicy_default_deny", "is_optimal": true, "approve": true, "feedback": "Plan effectively configures deny-all policy and correct permissions; no further changes needed.", "...
Concerns	Could not parse LLM response

LLM Metrics

LLM Calls	2
Duration	4.0s
Total Tokens	3,813
Cost	$0.0009
Agents	Remedy(1), Review(1)

package_postfix_installed: The Postfix package is installed — FAILED

Rule	package_postfix_installed
Severity	Medium
Description	A mail server is required for sending emails. The postfix package can be installed with the following command: $ sudo dnf ins
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "p
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the Postfix package is a standard package installation that does not modify authentication, authorization, or critical s
Estimated Impact	networking affected; If the Postfix service is enabled and started, it may listen on port 25 and could be exposed to network thr

Remediation (3 attempt(s))

Attempt #	1
Commands	dnf install -y postfix, cat -A /etc/dnf/dnf.conf, dnf install -y postfix, ls -l /etc/dnf/dnf.conf, od -c /etc/dnf/dnf.conf | head -20

Scan Passed	✗
Success	✗
Duration	151.9s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	124.8s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	24.7s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	10/10
Feedback	The plan resolves the vulnerability by installing postfix if absent on systems where kernel-core is installed (platform compatibi

Concerns	—

QA Result

Safe	✗
Verdict	Plan installs postfix only if not already installed, but does not check for other MTAs; installing postfix alongside another MTA c
Side Effects	Potential port 25 conflict with existing MTA; Possible need to stop/disable other MTA before starting postfix; May require post-
Regression	✗
Recommendation	Investigate

LLM Metrics

LLM Calls	6
Duration	24.7s
Total Tokens	15,927
Cost	$0.0045
Agents	Remedy(2), Review(2), Qa(2)

package_s-nail_installed: The s-nail Package Is Installed — FAILED

Rule	package_s-nail_installed
Severity	Medium
Description	A mail server is required for sending emails. The s-nail package can be installed with the following command: $ sudo dnf insta
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	Installing the s-nail package is a routine administrative action that does not introduce security vulnerabilities.
Estimated Impact	filesystems affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	6.9s
Error	—

Attempt #	2
Commands	dnf install -y s-nail, dnf install -y s-nail
Scan Passed	✗
Success	✗
Duration	7.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗

Duration	5.3s
Error	—

LLM Metrics

LLM Calls	5
Duration	5.3s
Total Tokens	11,590
Cost	$0.0015
Agents	Remedy(5)

postfix_client_configure_mail_alias: Configure System to Forward All Mail For The Root Account — FAILED

Rule	postfix_client_configure_mail_alias
Severity	Medium
Description	Make sure that mails delivered to root user are forwarded to a monitored email address. Make sure that the address is a valid
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_postfix_root_m
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Editing /etc/aliases to set a root mail alias is a simple file change that does not affect authentication, authorization, networking
Estimated Impact	filesystems affected; Incorrect email address could prevent root mail from being forwarded

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	28.5s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	20.2s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	8.7s
Error	—

LLM Metrics

LLM Calls	5
Duration	8.7s

Total Tokens	20,535
Cost	$0.0030
Agents	Remedy(5)

chronyd_or_ntpd_set_maxpoll: Configure Time Service Maxpoll Interval — REQUIRES_HUMAN_REVIEW

Rule	chronyd_or_ntpd_set_maxpoll
Severity	Medium
Description	The maxpoll should be configured to in /etc/ntp.conf or /etc/chrony.conf (or /etc/chrony.d/) to continuously poll time servers. T
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { (rpm --quiet -q chr
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The maxpoll interval should be configured in /etc/ntp.conf or /etc/chrony.conf to continuously poll time servers; otherwise time
Estimated Impact	networking affected; Incorrect time synchronization; Potential drift in system clocks

LLM Metrics

LLM Calls	1
Duration	2.9s
Total Tokens	1,668
Cost	$0.0005
Agents	Triage(1)

chronyd_server_directive: Ensure Chrony is only configured with the server directive — FAILED

Rule	chronyd_server_directive
Severity	Medium
Description	Check that Chrony only has time sources configured with the server directive.
Recommendation	Review and remediate: Ensure Chrony is only configured with the server directive
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Modifying /etc/chrony.conf to retain only server directives is a straightforward configuration change that does not affect auther
Estimated Impact	networking affected; Incorrect removal of needed time sources could lead to time synchronization issues

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	22.8s
Error	—

Attempt #	2
Commands	[["space:]]*$/p' -e '/^[[:space:]]*#/p' -e '/^[[:space:]]*server[[:space:]]/p' /etc/chrony.conf"]]
Scan Passed	✗

Success	✗
Duration	19.1s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	17.1s
Error	—

LLM Metrics

LLM Calls	5
Duration	17.1s
Total Tokens	26,885
Cost	$0.0047
Agents	Remedy(5)

disable_host_auth: Disable Host-Based Authentication — FAILED

Rule	disable_host_auth
Severity	Medium
Description	SSH's cryptographic host-based authentication is more secure than .rhosts authentication. However, it is not recommended tl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling HostbasedAuthentication is a standard SSH hardening step that does not affect typical key- or password-based aut
Estimated Impact	authentication/authorization affected; SSH service restart required; If host-based authentication is currently in use, disabling c

Remediation (3 attempt(s))

Attempt #	1
Commands	mkdir -p /etc/ssh/sshd_config.d, touch /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf, chmod 0600 /etc/ssh/ssh
Scan Passed	✗
Success	✗
Duration	135.1s
Error	—

Attempt #	2
Commands	[["space:]]*HostbasedAuthentication[[:space:]]/d' /etc/ssh/sshd_config"]], echo "HostbasedAuthentication no" >> /etc/ssh/sshd
Scan Passed	✗
Success	✗
Duration	43.4s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗

Success	✗
Duration	15.0s
Error	—

LLM Metrics

LLM Calls	5
Duration	15.0s
Total Tokens	30,958
Cost	$0.0048
Agents	Remedy(5)

sshd_disable_compression: Disable Compression Or Set Compression to delayed — FAILED

Rule	sshd_disable_compression
Severity	Medium
Description	Compression is useful for slow network connections over long distances but can cause performance issues on local LANs. If
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_sshd_disable_
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling compression until after authentication reduces the attack surface by preventing unauthenticated use of compressio
Estimated Impact	authentication/authorization affected; networking affected; Information disclosure; Performance degradation; Unauthenticated

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	5.7s
Error	—

Attempt #	2
Commands	sed -i -e '/^\s*Compression\s*$/b' -e 's/^\s*Compression\s*.*/Compression no/' -e '$a\Compression no' /etc/ssh/sshd_config
Scan Passed	✗
Success	✗
Duration	23.4s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	17.9s
Error	—

LLM Metrics

LLM Calls	5
Duration	17.9s

Total Tokens	34,025
Cost	$0.0060
Agents	Remedy(5)

sshd_disable_gssapi_auth: Disable GSSAPI Authentication — FAILED

Rule	sshd_disable_gssapi_auth
Severity	Medium
Description	Unless needed, SSH should not permit extraneous or unnecessary authentication mechanisms like GSSAPI. The default SSH
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling GSSAPI authentication prevents unnecessary authentication mechanisms and aligns with SSH hardening guideline
Estimated Impact	authentication/authorization affected; networking affected; Misconfiguration of SSH authentication methods

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	24.8s

Error	—

Attempt #	2
Commands	cat /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf, sed '/GSSAPIAuthentication/Id' /etc/ssh/sshd_config.d/00-c
Scan Passed	✗
Success	✗
Duration	51.2s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	5.3s
Error	—

LLM Metrics

LLM Calls	5
Duration	5.3s
Total Tokens	13,765
Cost	$0.0017
Agents	Remedy(5)

sshd_disable_kerb_auth: Disable Kerberos Authentication — FAILED

Rule	sshd_disable_kerb_auth

Severity	Medium
Description	Unless needed, SSH should not permit extraneous or unnecessary authentication mechanisms like Kerberos. The default SS
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling Kerberos authentication in SSH reduces attack surface; SSH does not depend on Kerberos by default, so disabling
Estimated Impact	authentication/authorization affected; filesystems affected; Kerberos may be used for SSH authentication in some environmen

Remediation (3 attempt(s))

Attempt #	1
Commands	rpm --quiet -q kernel-core && mkdir -p /etc/ssh/sshd_config.d && touch /etc/ssh/sshd_config.d/01-complianceascode-reinforc
Scan Passed	✗
Success	✗
Duration	40.3s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	13.5s

Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	6.3s
Error	—

LLM Metrics

LLM Calls	5
Duration	6.3s
Total Tokens	18,985
Cost	$0.0026
Agents	Remedy(5)

sshd_disable_rhosts: Disable SSH Support for .rhosts Files — FAILED

Rule	sshd_disable_rhosts
Severity	Medium
Description	SSH can emulate the behavior of the obsolete rsh command in allowing users to enable insecure access to their accounts via
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	Disabling .rhosts support in SSH prevents insecure trust-based authentication, reducing the risk of unauthorized access via le
Estimated Impact	authentication/authorization affected; networking affected; Insecure trust-based authentication; Potential unauthorized access

Remediation (3 attempt(s))

Attempt #	1
Commands	mkdir -p /etc/ssh/sshd_config.d, touch /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf, chmod 0600 /etc/ssh/ssh
Scan Passed	✗
Success	✗
Duration	43.7s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	5.9s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗

Duration	34.0s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	8/10
Feedback	The plan ensures IgnoreRhosts yes is set in the SSH config, which disables .rhosts support and addresses the vulnerability.
Concerns	—

QA Result

Safe	✓
Verdict	The remediation sets IgnoreRhosts yes in sshd_config.d, which disables .rhosts support as intended to address the vulnerabi
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	8
Duration	33.9s
Total Tokens	79,220
Cost	$0.0127
Agents	Remedy(6), Review(1), Qa(1)

sshd_disable_user_known_hosts: Disable SSH Support for User Known Hosts — FAILED

Rule	sshd_disable_user_known_hosts
Severity	Medium
Description	SSH can allow system users to connect to systems if a cache of the remote systems public keys is available. This should be c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/ss
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling SSH UserKnownHosts prevents SSH from accepting unknown host keys, reducing the risk of man-in-the-middle att
Estimated Impact	authentication/authorization affected; networking affected; man-in-the-middle; unauthorized access

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	25.5s
Error	—

Attempt #	2
Commands	mkdir -p /etc/ssh/sshd_config.d, systemctl restart sshd
Scan Passed	✗
Success	✗

Duration	23.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	9.7s
Error	—

LLM Metrics

LLM Calls	8
Duration	8.8s
Total Tokens	27,565
Cost	$0.0034
Agents	Remedy(8)

sshd_do_not_permit_user_env: Do Not Allow SSH Environment Options — REQUIRES_HUMAN_REVIEW

Rule	sshd_do_not_permit_user_env
Severity	Medium
Description	Ensure that users are not able to override environment variables of the SSH daemon. The default SSH configuration disables
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	Ensure that users are not able to override environment variables of the SSH daemon. The default SSH configuration disables
Estimated Impact	authentication/authorization affected; networking affected; SSH environment variables override; PermitUserEnvironment not s

LLM Metrics

LLM Calls	1
Duration	2.9s
Total Tokens	2,143
Cost	$0.0007
Agents	Triage(1)

sshd_enable_pubkey_auth: Enable Public Key Authentication — FAILED

Rule	sshd_enable_pubkey_auth
Severity	Medium
Description	Enable SSH login with public keys. The default SSH configuration enables authentication based on public keys. The appropri
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	Enable SSH login with public keys. The default SSH configuration enables authentication based on public keys. The appropri
Estimated Impact	authentication/authorization affected; networking affected; SSH public key authentication disabled; Potential for unauthorized

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	23.4s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	15.6s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	19.0s
Error	—

LLM Metrics

LLM Calls	5
Duration	19.0s
Total Tokens	43,534
Cost	$0.0072
Agents	Remedy(5)

sshd_enable_strictmodes: Enable Use of Strict Mode Checking — FAILED

Rule	sshd_enable_strictmodes
Severity	Medium
Description	SSHs StrictModes option checks file and ownership permissions in the user's home directory .ssh folder before accepting log
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	SSH StrictModes option ensures that files and ownership in the user's .ssh directory are checked before login; world-writable
Estimated Impact	authentication/authorization affected; networking affected; filesystems affected; World-writable files in ~/.ssh; Missing StrictMo

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗

Success	✗
Duration	21.9s
Error	—

Attempt #	2
Commands	if ! grep -q '^StrictModes yes' /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf; then echo 'StrictModes yes' >> /et
Scan Passed	✗
Success	✗
Duration	135.8s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	143.4s
Error	—

LLM Metrics

LLM Calls	6
Duration	142.4s
Total Tokens	49,395
Cost	$0.0081
Agents	Remedy(6)

sshd_print_last_log: Enable SSH Print Last Log — FAILED

Rule	sshd_print_last_log
Severity	Medium
Description	Ensure that SSH will display the date and time of the last successful account logon. The default SSH configuration enables pr
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling PrintLastLog ensures that SSH logs the timestamp of the last successful login, aiding in audit and intrusion detectio
Estimated Impact	authentication/authorization affected; networking affected; misconfiguration; missing audit trail

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	8.5s
Error	—

Attempt #	2
Commands	grep -i '^PrintLastLog' /etc/ssh/sshd_config, grep -r -i '^PrintLastLog' /etc/ssh/sshd_config.d 2>/dev/null || true, sed -i '/^\s*Prin
Scan Passed	✗

Success	✗
Duration	168.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	3.1s
Error	—

LLM Metrics

LLM Calls	5
Duration	3.0s
Total Tokens	10,750
Cost	$0.0011
Agents	Remedy(5)

sshd_rekey_limit: Force frequent session key renegotiation — FAILED

Rule	sshd_rekey_limit
Severity	Medium
Description	The RekeyLimit parameter specifies how often the session key of the is renegotiated, both in terms of amount of data that ma
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_rekey_limit_siz
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adjusting RekeyLimit is a standard SSH hardening step that only affects session key renegotiation frequency; it does not alte
Estimated Impact	networking affected; Incorrect syntax could cause sshd to fail to start; Setting an excessively low limit may increase CPU usag

Remediation (3 attempt(s))

Attempt #	1
Commands	mkdir -p /etc/ssh/sshd_config.d, touch /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf, chmod 0600 /etc/ssh/ssh
Scan Passed	✗
Success	✗
Duration	23.4s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	16.8s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗

Success	✗
Duration	23.3s
Error	—

LLM Metrics

LLM Calls	5
Duration	23.3s
Total Tokens	53,609
Cost	$0.0089
Agents	Remedy(5)

sshd_set_loglevel_verbose: Set SSH Daemon LogLevel to VERBOSE — FAILED

Rule	sshd_set_loglevel_verbose
Severity	Medium
Description	The VERBOSE parameter configures the SSH daemon to record login and logout activity. To specify the log level in SSH, ad
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting the SSH daemon LogLevel to VERBOSE increases log verbosity, which may expose sensitive information such as au
Estimated Impact	networking affected; Excessive logging; Potential information disclosure

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	5.0s
Error	—

Attempt #	2
Commands	mkdir -p /etc/ssh/sshd_config.d, find /etc/ssh/sshd_config.d -name '*.conf' -type f -exec grep -l 'LogLevel VERBOSE' {} \\; -prin
Scan Passed	✗
Success	✗
Duration	22.8s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	13.7s
Error	—

LLM Metrics

LLM Calls	5
Duration	13.7s

Total Tokens	34,219
Cost	$0.0054
Agents	Remedy(5)

sshd_x11_use_localhost: Prevent remote hosts from connecting to the proxy display — *FAILED*

Rule	sshd_x11_use_localhost
Severity	Medium
Description	The SSH daemon should prevent remote hosts from connecting to the proxy display. The default SSH configuration for X11U
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The SSH daemon configuration lacks X11UseLocalhost yes, which could allow remote hosts to connect to the proxy display,
Estimated Impact	authentication/authorization affected; networking affected; SSH misconfiguration; Potential unauthorized proxy access

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	128.8s

Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	4.7s
Error	—

Attempt #	3
Commands	read_file, read_file, write_file, read_file
Scan Passed	✗
Success	✗
Duration	61.0s
Error	—

LLM Metrics

LLM Calls	9
Duration	57.3s
Total Tokens	258,748
Cost	$0.0363
Agents	Remedy(9)