

OpenSCAP Triage Report

Target: 192.168.64.15 | Generated: 2026-04-12 22:28:11

Scan Statistics

Total Rules Scanned	0
Rules Passed	0
Rules Failed / Errors	0

Triage Summary

Total Findings Triage	150
Safe to Remediate	126
Requires Human Review	14
Too Dangerous / Blocked	10

Safe to Remediate (126)

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
package_aide_installed	package_aide_installed	Install AIDE	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the AIDE package is a standard, low-risk operation that does not affect authentication, networking, or critical system services.	—
aide_build_database	aide_build_database	Build and Test AIDE Database	Medium	FAIL	localhost	localhost.localdomain	LOW	Initializing and updating the AIDE database is a routine security measure that does not affect authentication, networking, or critical services. It involves installing a package (if missing) and creating a database file, which is a low-risk operation.	filesystems affected

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
aide_check_audit_tools	aide_check_audit_tools	Configure AIDE to Verify the Audit Tools	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves installing the AIDE package if missing and adding or updating entries in /etc/aide.conf for audit tools, which is a straightforward configuration change that does not affect authentication, networking, or critical services.	filesystems affected; audit tool integrity
aide_use_fips_hashes	aide_use_fips_hashes	Configure AIDE to Use FIPS 140-2 for Validating Hashes	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding sha512 to the AIDE configuration is a straightforward configuration change that does not affect authentication, networking, or critical system services. It follows standard STIG hardening patterns and is unlikely to cause lockout or system breakage.	—
configure_crypto_policy	configure_crypto_policy	Configure System Cryptography Policy	High	FAIL	localhost	localhost.localdomain	LOW	The remediation uses the standard update-crypto-policies command to set a predefined cryptographic policy, which is a documented and supported STIG hardening step that does not risk lockout or critical service disruption.	Potential application compatibility issues if legacy ciphers are disabled
installed_OS_is_vendor_supported	installed_OS_is_vendor_supported	The Installed Operating System Is Vendor Supported	High	FAIL	localhost	localhost.localdomain	LOW	The finding requires ensuring the operating system is supported by the vendor, which typically involves verifying subscription status and applying available updates—actions that are routine and unlikely to cause lockout or system breakage.	—
package_gnutls-utils_installed	package_gnutls-utils_installed	Ensure gnutls-utils is installed	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the gnutls-utils package is a standard, non-disruptive operation that does not affect authentication, networking, or filesystem configuration. It follows the STIG hardening pattern for package installation and is unlikely to cause lockout or system breakage.	—
package_nss-tools_installed	package_nss-tools_installed	Ensure nss-tools is installed	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the nss-tools package is a standard, non-disruptive operation that does not affect authentication, networking, or filesystem integrity. It follows the STIG hardening pattern for package installation and carries no risk of service lockout or system breakage.	—

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
package_subscription-manager_installed	package_subscription-manager_installed	Install subscription-manager Package	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the subscription-manager package is a standard, non-disruptive operation that does not affect authentication, networking, or critical system services. It follows the STIG recommendation for package installation and is unlikely to cause lockout or system breakage.	—
ensure_gpgcheck_local_packages	ensure_gpgcheck_local_packages	Ensure gpgcheck Enabled for Local Packages	High	FAIL	localhost	localhost.localdomain	LOW	Enabling GPG check for local packages is a standard security hardening step that does not affect authentication, networking, or filesystem integrity and cannot cause system lockout.	—
enable_authselect	enable_authselect	Enable authselect	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling authselect is a standard authentication configuration change that follows STIG hardening patterns and is unlikely to cause lockout or system breakage.	authentication/authorization affected; Potential misconfiguration of authselect profile may temporarily affect authentication
banner_etc_issue	banner_etc_issue	Modify the System Login Banner	Medium	FAIL	localhost	localhost.localdomain	LOW	Changing the /etc/issue banner is a simple configuration edit that does not affect authentication, networking, or critical system services. It cannot lock out users or break the system.	—
account_password_pam_faillock_password_auth	account_password_pam_faillock_password_auth	Configure the Use of the pam_faillock.so Module in the /etc/pam.d/password-auth File.	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation follows the standard STIG hardening pattern for PAM by enabling the faillock feature via authselect, which is a supported and safe method that does not risk lockout or service disruption.	authentication/authorization affected; Potential misconfiguration of PAM could temporarily block authentication if the module is incorrectly added
accounts_passwords_pam_faillock_interval	accounts_passwords_pam_faillock_interval	Set Interval For Counting Failed Password Attempts	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves setting a fail_interval value in the PAM faillock configuration, a standard hardening step that does not affect critical services or system boot. It is a simple configuration change that can be applied safely with authselect or by editing /etc/security/faillock.conf.	authentication/authorization affected; Incorrect value could lock out legitimate users temporarily

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
accounts_password_pam_dcredit	accounts_password_pam_dcredit	Ensure PAM Enforces Password Requirements - Minimum Digit Characters	Medium	FAIL	localhost	localhost.localdomain	LOW	Standard STIG password policy change; no critical services or bootloader affected.	authentication/authorization affected; Existing users may be unable to set passwords that meet new digit requirement
accounts_password_pam_dictcheck	accounts_password_pam_dictcheck	Ensure PAM Enforces Password Requirements - Prevent the Use of Dictionary Words	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves editing a PAM configuration file to enable dictionary word checking, a standard STIG hardening step that does not affect critical services or system boot. It is unlikely to lock out users or break the system.	authentication/authorization affected; Potential user lockout if passwords contain dictionary words
accounts_password_pam_difok	accounts_password_pam_difok	Ensure PAM Enforces Password Requirements - Minimum Different Characters	Medium	FAIL	localhost	localhost.localdomain	LOW	The difok setting is a standard PAM password policy parameter that controls the minimum number of characters that must differ from the old password during a change. Adjusting this value follows typical STIG hardening patterns for authentication and does not risk service disruption or lockout beyond normal password policy enforcement.	authentication/authorization affected; Potential for user lockout if set too high for existing password history
accounts_password_pam_enforce_root	accounts_password_pam_enforce_root	Ensure PAM Enforces Password Requirements - Enforce for root User	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling enforce_for_root in /etc/security/pwquality.conf is a standard PAM configuration change that does not affect system boot, networking, or file system integrity. It simply requires root to use a complex password, which is a common hardening practice and unlikely to lock out root access if a password is already set.	authentication/authorization affected; root password complexity enforcement
accounts_password_pam_lcredit	accounts_password_pam_lcredit	Ensure PAM Enforces Password Requirements - Minimum Lowercase Characters	Medium	FAIL	localhost	localhost.localdomain	LOW	The change is a standard PAM password policy adjustment that does not affect system services or user authentication mechanisms beyond password complexity. It follows typical STIG hardening patterns and is unlikely to cause lockout or breakage.	authentication/authorization affected; Password policy enforcement
accounts_password_pam_maxclassrepeat	accounts_password_pam_maxclassrepeat	Ensure PAM Enforces Password Requirements - Maximum Consecutive Repeating Characters from Same Character Class	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves a simple configuration change to the PAM password quality module, a standard STIG hardening practice that does not risk lockout or service disruption.	authentication/authorization affected; Password policy enforcement

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
accounts_password_pam_maxrepeat	accounts_password_pam_maxrepeat	Set Password Maximum Consecutive Repeating Characters	Medium	FAIL	localhost	localhost.localdomain	LOW	Changing the PAM password quality setting to limit consecutive repeating characters is a standard password policy hardening step that does not affect system availability or critical services.	authentication/authorization affected; Potential for user lockout if policy is set too strict
accounts_password_pam_minclass	accounts_password_pam_minclass	Ensure PAM Enforces Password Requirements - Minimum Different Categories	Medium	FAIL	localhost	localhost.localdomain	LOW	Changing the PAM minclass setting is a standard password policy hardening measure that does not affect system boot, networking, or critical services. It follows STIG patterns for authentication configuration and is unlikely to cause lockout or system breakage.	authentication/authorization affected; Potential for password change failures if users do not meet the new policy
accounts_password_pam_minlen	accounts_password_pam_minlen	Ensure PAM Enforces Password Requirements - Minimum Length	Medium	FAIL	localhost	localhost.localdomain	LOW	Standard password policy change that follows STIG hardening patterns and does not affect critical services or system boot.	authentication/authorization affected; Potential user lockout if existing passwords are shorter than the new minimum
accounts_password_pam_ocredit	accounts_password_pam_ocredit	Ensure PAM Enforces Password Requirements - Minimum Special Characters	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves editing the PAM password quality configuration to enforce the presence of at least one special character, a standard password policy change that follows STIG hardening patterns and is unlikely to cause lockout or system breakage.	authentication/authorization affected; Potential for user lockout if password policy is too strict and users are not informed
accounts_password_pam_pwquality_retry	accounts_password_pam_pwquality_retry	Ensure PAM Enforces Password Requirements - Authentication Retry Prompts Permitted Per-Session in /etc/security/pwquality.conf	Medium	FAIL	localhost	localhost.localdomain	LOW	Changing the retry parameter in /etc/security/pwquality.conf is a standard PAM configuration adjustment that follows STIG hardening patterns and does not affect critical services or system boot. It is unlikely to cause lockout or system breakage if set to a reasonable value.	authentication/authorization affected; Setting retry too low may temporarily prevent users from completing password changes or authentication attempts
accounts_password_pam_ucredit	accounts_password_pam_ucredit	Ensure PAM Enforces Password Requirements - Minimum Uppercase Characters	Medium	FAIL	localhost	localhost.localdomain	LOW	The ucredit setting is a standard PAM password policy configuration that follows STIG hardening patterns and is unlikely to cause lockout or system breakage.	authentication/authorization affected; Potential for user lockout if policy is too strict

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
disable_ctrlaltdel_burstaction	disable_ctrlaltdel_burstaction	Disable Ctrl-Alt-Del Burst Action	High	FAIL	localhost	localhost.localdomain	LOW	The remediation involves a single, well-documented configuration change that disables a systemd feature which could otherwise trigger an automatic reboot on repeated Ctrl-Alt-Del presses. This change is unlikely to lock out users or disrupt critical services and follows standard STIG hardening patterns.	reboot required; Minimal risk of unintended reboot if applied incorrectly
disable_ctrlaltdel_reboot	disable_ctrlaltdel_reboot	Disable Ctrl-Alt-Del Reboot Activation	High	FAIL	localhost	localhost.localdomain	LOW	Disabling or masking the ctrl-alt-del.target service is a standard, non-disruptive configuration change that does not affect authentication, networking, or filesystem integrity. It prevents accidental reboot via the key sequence without risking lockout or service interruption.	—
package_opensc_installed	package_opensc_installed	Install the opensc Package For Multifactor Authentication	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the opensc package is a standard package installation that does not alter authentication configuration, networking, or filesystem structure, and is unlikely to cause lockout or system breakage.	—
package_pcsc-lite_installed	package_pcsc-lite_installed	Install the pcsc-lite package	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the pcsc-lite package is a standard package installation that does not affect authentication, networking, or filesystem configuration, and is unlikely to cause system lockout or breakage.	—
install_smartcard_packages	install_smartcard_packages	Install Smart Card Packages For Multifactor Authentication	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the openssl-pkcs11 package is a standard package installation that does not affect critical services or system boot, and follows STIG hardening patterns for authentication. It poses no risk of lockout or system breakage.	authentication/authorization affected
service_pcscd_enabled	service_pcscd_enabled	Enable the pcscd Service	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling the pcscd service is a standard service enablement that follows STIG hardening patterns and is unlikely to cause lockout or system breakage.	authentication/authorization affected; Potential for unauthorized smart card authentication if the service is misconfigured

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
configure_opensc_card_drivers	configure_opensc_card_drivers	Configure opensc Smart Card Drivers	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation requires only a simple edit to /etc/opensc.conf or execution of a small script, which does not affect critical services or user authentication mechanisms beyond smart card usage. It is unlikely to cause lockout or system breakage.	authentication/authorization affected
account_disable_post_pw_expiration	account_disable_post_pw_expiration	Set Account Expiration Following Inactivity	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves a simple configuration change to /etc/default/useradd to set the INACTIVE parameter, a standard password policy adjustment that does not affect critical services or system boot. It follows typical STIG hardening patterns for account expiration and is unlikely to cause lockout or breakage.	authentication/authorization affected; Incorrect INACTIVE value could prematurely disable accounts; Potential for accidental removal of existing INACTIVE setting
accounts_maximum_age_login_defs	accounts_maximum_age_login_defs	Set Password Maximum Age	Medium	FAIL	localhost	localhost.localdomain	LOW	Setting PASS_MAX_DAYS in /etc/login.defs is a standard password policy change that follows STIG hardening patterns and does not affect critical services or system boot processes.	authentication/authorization affected; Potential account lockout if users exceed maximum days
accounts_minimum_age_login_defs	accounts_minimum_age_login_defs	Set Password Minimum Age	Medium	FAIL	localhost	localhost.localdomain	LOW	Setting PASS_MIN_DAYS to 1 day is a standard password policy adjustment that does not affect system availability or critical services.	authentication/authorization affected; Potential for user lockout if set too high
accounts_password_set_min_life_existing	accounts_password_set_min_life_existing	Set Existing Passwords Minimum Age	Medium	FAIL	localhost	localhost.localdomain	LOW	Changing the minimum password age for existing accounts is a standard password policy adjustment that does not affect system boot, networking, or critical services. It follows STIG hardening patterns and is unlikely to cause lockout or breakage.	authentication/authorization affected
use_pam_wheel_for_su	use_pam_wheel_for_su	Enforce usage of pam_wheel for su authentication	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding the pam_wheel.so use_uid line to /etc/pam.d/su is a standard STIG hardening step for PAM authentication and does not risk system lockout or critical service disruption.	authentication/authorization affected; Potential loss of su access for non-wheel users (intended)
accounts_logon_failure_delay	accounts_logon_failure_delay	Ensure the Logon Failure Delay is Set Correctly in login.defs	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves a simple configuration change to /etc/login.defs, which is a standard PAM setting that controls login failure delay. This change is unlikely to lock out users or break critical services.	authentication/authorization affected; None identified

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
accounts_tmout	accounts_tmout	Set Interactive Session Timeout	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves adding or updating a TMOUT variable in shell profile scripts, a standard STIG hardening pattern that does not risk lockout or critical service disruption.	authentication/authorization affected; May log out idle users
file_permission_user_init_files_root	file_permission_user_init_files_root	Ensure All User Initialization Files Have Mode 0740 Or Less Permissive	Medium	FAIL	localhost	localhost.localdomain	LOW	Changing permissions of user initialization files to 0740 is a standard STIG hardening step that does not risk lockout or critical service disruption.	authentication/authorization affected; filesystems affected; Potential misapplication could affect user startup scripts, but unlikely to break authentication or services
package_rsyslog-gnutls_installed	package_rsyslog-gnutls_installed	Ensure rsyslog-gnutls is installed	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the rsyslog-gnutls package is a standard, non-disruptive package installation that does not affect authentication, networking configuration, or filesystem structure beyond adding the package files.	—
rsyslog_remote_access_monitoring	rsyslog_remote_access_monitoring	Ensure remote access methods are monitored in Rsyslog	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding or ensuring rsyslog selectors for auth.*, authpriv.*, and daemon.* is a standard logging configuration change that does not affect authentication mechanisms or service availability. It simply enhances audit visibility and is unlikely to cause lockout or system breakage.	authentication/authorization affected
rsyslog_remote_loghost	rsyslog_remote_loghost	Ensure Logs Sent To Remote Host	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves editing /etc/rsyslog.conf to add a remote logging directive, which is a standard configuration change that does not affect authentication, boot, or critical services. It is unlikely to cause lockout or system breakage.	networking affected; remote logging configuration; rsyslog service restart
network_configure_name_resolution	network_configure_name_resolution	Configure Multiple DNS Servers in /etc/resolv.conf	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding or verifying multiple DNS servers in /etc/resolv.conf is a standard network configuration change that does not affect authentication, authorization, or critical system services. It follows common STIG hardening patterns and poses no risk of lockout or system breakage.	networking affected

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
package_libreswan_installed	package_libreswan_installed	Install libreswan Package	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the libreswan package is a standard package installation that does not affect critical services or authentication mechanisms, and is unlikely to cause lockout or system breakage.	—
sysctl_net_ipv6_conf_all_accept_ra	sysctl_net_ipv6_conf_all_accept_ra	Configure Accepting Router Advertisements on All IPv6 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling IPv6 router advertisements via a sysctl setting is a standard hardening practice that does not affect authentication, authorization, or critical services. It only alters IPv6 network configuration and can be applied safely without risk of lockout.	networking affected; Potential loss of IPv6 connectivity if the environment relies on RA for address configuration
sysctl_net_ipv6_conf_all_accept_redirects	sysctl_net_ipv6_conf_all_accept_redirects	Disable Accepting ICMP Redirects for All IPv6 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling ICMP redirects for IPv6 is a standard sysctl hardening measure that does not affect authentication, authorization, or critical services. It is a simple configuration change with no risk of lockout.	networking affected
sysctl_net_ipv6_conf_all_accept_source_route	sysctl_net_ipv6_conf_all_accept_source_route	Disable Kernel Parameter for Accepting Source-Routed Packets on all IPv6 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	Standard sysctl hardening change that does not affect authentication, authorization, or critical services; follows STIG pattern for network security.	networking affected
sysctl_net_ipv6_conf_all_forwarding	sysctl_net_ipv6_conf_all_forwarding	Disable Kernel Parameter for IPv6 Forwarding	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling IPv6 forwarding via sysctl is a standard, non-disruptive configuration change that does not affect authentication, authorization, or critical services. It only alters a kernel networking parameter and can be applied safely without risk of lockout.	networking affected; IPv6 forwarding disabled may affect IPv6 routing or services that rely on it
sysctl_net_ipv6_conf_default_accept_ra	sysctl_net_ipv6_conf_default_accept_ra	Disable Accepting Router Advertisements on all IPv6 Interfaces by Default	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling IPv6 router advertisements via a sysctl setting is a standard hardening practice that does not affect authentication, authorization, or critical services such as SSH. The change is local to the kernel networking stack and can be applied safely without risk of lockout.	networking affected

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
sysctl_net_ipv6_conf_default_accept_redirects	sysctl_net_ipv6_conf_default_accept_redirects	Disable Kernel Parameter for Accepting ICMP Redirects by Default on IPv6 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves setting a kernel sysctl parameter to a safe value and persisting it in /etc/sysctl.d, which is a standard, low-risk configuration change that does not affect authentication, authorization, or critical services.	networking affected
sysctl_net_ipv6_conf_default_accept_source_route	sysctl_net_ipv6_conf_default_accept_source_route	Disable Kernel Parameter for Accepting Source-Routed Packets on IPv6 Interfaces by Default	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling source routing on IPv6 interfaces is a standard hardening practice that does not affect authentication, authorization, or critical services. The change is a simple sysctl setting and can be applied at runtime without risk of lockout.	networking affected; Potential impact on legacy applications that may rely on source routing (rare)
sysctl_net_ipv4_conf_all_accept_redirects	sysctl_net_ipv4_conf_all_accept_redirects	Disable Accepting ICMP Redirects for All IPv4 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	Standard sysctl hardening that does not affect authentication, authorization, or critical services; setting is safe and widely recommended.	networking affected; ICMP redirect exploitation
sysctl_net_ipv4_conf_all_accept_source_route	sysctl_net_ipv4_conf_all_accept_source_route	Disable Kernel Parameter for Accepting Source-Routed Packets on all IPv4 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling source routing is a standard security hardening measure that does not affect authentication, authorization, or critical services. The change is a simple sysctl setting and is unlikely to cause lockout or system breakage.	networking affected; Potential loss of source routing functionality for legacy applications
sysctl_net_ipv4_conf_all_forwarding	sysctl_net_ipv4_conf_all_forwarding	Disable Kernel Parameter for IPv4 Forwarding on all IPv4 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling IPv4 forwarding is a standard hardening step that does not affect user authentication or critical services. It only changes a kernel networking parameter and can be applied safely without risk of lockout.	networking affected; May affect routing or VPN services that rely on IP forwarding.
sysctl_net_ipv4_conf_all_rp_filter	sysctl_net_ipv4_conf_all_rp_filter	Enable Kernel Parameter to Use Reverse Path Filtering on all IPv4 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling reverse path filtering is a standard sysctl configuration that does not affect authentication, authorization, or critical services. It is a common hardening practice and can be applied safely without risk of lockout.	networking affected
sysctl_net_ipv4_conf_default_accept_redirects	sysctl_net_ipv4_conf_default_accept_redirects	Disable Kernel Parameter for Accepting ICMP Redirects by Default on IPv4 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves setting a standard sysctl parameter and ensuring persistence via /etc/sysctl.d, which is a routine configuration change that does not affect authentication, authorization, or critical services.	networking affected

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
sysctl_net_ipv4_conf_default_r_p_filter	sysctl_net_ipv4_conf_default_rp_filter	Enable Kernel Parameter to Use Reverse Path Filtering on all IPv4 Interfaces by Default	Medium	FAIL	localhost	localhost.localdomain	LOW	Standard sysctl persistence change that does not affect authentication, authorization, or critical services; safe to apply without risk of lockout.	networking affected
sysctl_net_ipv4_tcp_syncookies	sysctl_net_ipv4_tcp_syncookies	Enable Kernel Parameter to Use TCP Syncookies on Network Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling TCP syncookies is a standard kernel parameter hardening measure that does not affect authentication, authorization, or critical services. It is a simple sysctl change with no risk of lockout or system breakage.	networking affected; networking
sysctl_net_ipv4_conf_all_send_redirects	sysctl_net_ipv4_conf_all_send_redirects	Disable Kernel Parameter for Sending ICMP Redirects on all IPv4 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling ICMP redirects via a sysctl is a standard, low-risk configuration change that does not affect authentication, authorization, or critical services. It follows STIG hardening patterns for network parameters and can be applied without system lockout.	networking affected
sysctl_net_ipv4_conf_default_send_redirects	sysctl_net_ipv4_conf_default_send_redirects	Disable Kernel Parameter for Sending ICMP Redirects on all IPv4 Interfaces by Default	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves setting a kernel sysctl parameter to a safe value (0) and persisting it in /etc/sysctl.d, which is a standard, low-risk configuration change that does not affect authentication, authorization, or critical services.	networking affected
kernel_module_atm_disabled	kernel_module_atm_disabled	Disable ATM Support	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling the ATM kernel module is a straightforward configuration change that does not affect core system services such as SSH, console access, or critical networking functions. It simply prevents the module from loading, which is a standard hardening step with no risk of lockout or system breakage.	networking affected
kernel_module_can_disabled	kernel_module_can_disabled	Disable CAN Support	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling the CAN kernel module via a modprobe configuration is a straightforward, non-disruptive change that does not affect core system services or authentication mechanisms. It is unlikely to lock out SSH or console access.	Potential loss of functionality for applications that rely on CAN communication

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
kernel_module_sctp_disabled	kernel_module_sctp_disabled	Disable SCTP Support	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling the SCTP kernel module is a standard hardening step that does not affect core system functionality or user access. It only prevents the module from loading, which is unlikely to cause lockout or break critical services.	networking affected; SCTP may be required by some applications; disabling it could affect those applications' network communication
kernel_module_bluetooth_disabled	kernel_module_bluetooth_disabled	Disable Bluetooth Kernel Module	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling the Bluetooth kernel module is a standard hardening step that does not affect critical services such as SSH, console access, or system boot. The change is a simple configuration edit and is unlikely to cause lockout or system breakage.	—
rootfiles_configured	rootfiles_configured	Ensure rootfiles tmpfile.d is Configured Correctly	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves adding or updating a simple configuration file in /etc/tmpfiles.d to set permissions on root's initialization files, a standard STIG hardening task that does not affect authentication, networking, or critical services.	file permission change; root initialization files
kernel_module_usb-storage_disabled	kernel_module_usb-storage_disabled	Disable Modprobe Loading of USB Storage Driver	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling the usb-storage kernel module via a modprobe configuration is a standard, low-risk hardening step that does not affect authentication, networking, or critical services. It only prevents USB storage devices from being loaded, which is a straightforward configuration change.	Loss of USB storage device functionality
mount_option_boot_efi_nosuid	mount_option_boot_efi_nosuid	Add nosuid Option to /boot/efi	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding the nosuid mount option to /boot/efi is a standard filesystem configuration change that does not affect authentication, networking, or critical services. It prevents execution of setuid programs on the EFI partition, which is a common hardening practice and unlikely to cause lockout or system breakage.	filesystems affected
mount_option_boot_nodev	mount_option_boot_nodev	Add nodev Option to /boot	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding the nodev mount option to /boot is a standard hardening step that prevents device files from being created in the boot partition. It does not affect authentication, networking, or critical services and is unlikely to cause lockout or system breakage.	reboot required; filesystems affected

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
mount_option_boot_nosuid	mount_option_boot_nosuid	Add nosuid Option to /boot	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding the nosuid mount option to /boot is a standard hardening step that does not affect authentication, networking, or critical services. It is unlikely to lock out users or break the system, and the change can be applied safely with a simple fstab edit and a reboot or remount.	reboot required; filesystems affected; Potential impact if setuid programs on /boot are required for boot or system functionality
mount_option_dev_shm_nODEV	mount_option_dev_shm_nODEV	Add nodev Option to /dev/shm	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding the nodev option to the /dev/shm mount is a standard hardening step that does not affect authentication, networking, or critical services. It is a simple configuration change that can be applied without risk of lockout or system breakage.	filesystems affected
mount_option_dev_shm_NOEXEC	mount_option_dev_shm_NOEXEC	Add noexec Option to /dev/shm	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding the noexec option to /dev/shm is a standard hardening practice that prevents execution of binaries from a world-writable temporary directory. It does not affect authentication, networking, or critical services, and can be applied safely without system lockout.	filesystems affected; Potential failure of applications that rely on executing binaries from /dev/shm
mount_option_dev_shm_NOSUID	mount_option_dev_shm_NOSUID	Add nosuid Option to /dev/shm	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding the nosuid option to /dev/shm prevents execution of setuid programs in a world-writable directory, a standard hardening practice that does not affect authentication, authorization, or networking services and carries no risk of lockout.	filesystems affected
mount_option_home_NOEXEC	mount_option_home_NOEXEC	Add noexec Option to /home	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding the noexec option to /home is a standard hardening practice that does not affect authentication, networking, or critical services. It only prevents execution of binaries from /home, which is expected and unlikely to cause lockout or system breakage.	filesystems affected; Potential disruption of user-installed binaries that rely on execution from /home
mount_option_home_NOSUID	mount_option_home_NOSUID	Add nosuid Option to /home	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding the nosuid mount option to /home is a standard hardening practice that does not affect authentication, networking, or critical services. It simply prevents execution of setuid programs in the user data directory, which is unlikely to cause lockout or system breakage.	filesystems affected

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
mount_option_nodev_nonroot_local_partitions	mount_option_nodev_nonroot_local_partitions	Add nodev Option to Non-Root Local Partitions	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding the nodev mount option to non-root local partitions is a standard hardening practice that prevents files from being interpreted as device nodes. It is unlikely to lock out users or break critical services, and the change is confined to the fstab configuration.	filesystems affected; Potential disruption of services that rely on device files in non-root partitions
sysctl_kernel_core_pattern	sysctl_kernel_core_pattern	Disable storing core dumps	Medium	FAIL	localhost	localhost.localdomain	LOW	Setting kernel.core_pattern to /bin/false is a standard sysctl change that prevents core dumps; it does not affect authentication, networking, or filesystem integrity and is unlikely to cause lockout or system breakage.	Potential loss of core dump data for debugging
sysctl_kernel_kexec_load_disabled	sysctl_kernel_kexec_load_disabled	Disable Kernel Image Loading	Medium	FAIL	localhost	localhost.localdomain	LOW	Setting kernel.kexec_load_disabled via sysctl is a standard configuration change that does not affect authentication, networking, or filesystem integrity, and is unlikely to cause lockout or system breakage.	kernel parameter change
sysctl_kernel_unprivileged_bpf_disabled	sysctl_kernel_unprivileged_bpf_disabled	Disable Access to Network bpf() Syscall From Unprivileged Processes	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves setting a kernel sysctl parameter to disable unprivileged BPF access, a standard hardening step that does not affect authentication, authorization, or critical services. It is a simple configuration change with no risk of lockout.	networking affected; kernel parameter change; potential impact on applications using BPF
sysctl_kernel_yama_ptrace_scope	sysctl_kernel_yama_ptrace_scope	Restrict usage of ptrace to descendant processes	Medium	FAIL	localhost	localhost.localdomain	LOW	Setting kernel.yama_ptrace_scope to 1 is a standard sysctl configuration change that does not affect authentication, networking, or filesystem integrity, and is unlikely to lock out users or break services.	May limit debugging capabilities for legitimate processes
sysctl_net_core_bpf_jit_harden	sysctl_net_core_bpf_jit_harden	Harden the operation of the BPF just-in-time compiler	Medium	FAIL	localhost	localhost.localdomain	LOW	Setting net.core.bpf_jit_harden to 2 is a standard kernel sysctl change that does not affect authentication, networking services, or filesystem integrity, and is unlikely to cause lockout or system breakage.	—

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
sysctl_user_max_user_namespaces_no_remediation	sysctl_user_max_user_namespaces_no_remediation	Disable the use of user namespaces	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling user namespaces via a sysctl setting is a standard kernel parameter change that does not affect authentication, networking, or filesystem configuration. It is unlikely to lock out users or break critical services, and follows typical STIG hardening patterns for sysctl persistence.	May impact container deployments that rely on user namespaces; Requires verification that no critical services depend on user namespaces
service_systemd-coredump_disabled	service_systemd-coredump_disabled	Disable acquiring, saving, and processing core dumps	Medium	FAIL	localhost	localhost.localdomain	LOW	Masking the systemd-coredump.socket unit is a standard hardening step that disables core dump processing without affecting SSH, console access, or critical services. The remediation script performs a safe stop and mask operation, which is unlikely to cause lockout or system breakage.	—
coredump_disable_backtraces	coredump_disable_backtraces	Disable core dump backtraces	Medium	FAIL	localhost	localhost.localdomain	LOW	Setting ProcessSizeMax=0 in systemd coredump configuration is a standard hardening step that prevents backtrace generation for core dumps; it does not affect authentication, networking, or critical services and is unlikely to cause lockout or system breakage.	—
coredump_disable_storage	coredump_disable_storage	Disable storing core dump	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling core dump storage is a standard configuration change that does not affect authentication, networking, or critical services. It follows typical STIG hardening patterns and is unlikely to cause lockout or system breakage.	Loss of core dump data for debugging
disable_users_coredumps	disable_users_coredumps	Disable Core Dumps for All Users	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding '* hard core 0' to /etc/security/limits.conf or a drop in file is a standard STIG hardening step that does not affect authentication, networking, or filesystem integrity and cannot lock out users or services.	—
sysctl_kernel_randomize_va_space	sysctl_kernel_randomize_va_space	Enable Randomized Layout of Virtual Address Space	Medium	FAIL	localhost	localhost.localdomain	LOW	Setting kernel.randomize_va_space to 2 is a standard kernel hardening practice that does not affect authentication, networking, or filesystem integrity and is unlikely to cause lockout or system breakage.	kernel parameter change

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
package_policycoreutils-python-utils_installed	package_policycoreutils-python-utils_installed	Install policycoreutils-python-utils package	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing policycoreutils-python-utils is a standard package installation that does not affect authentication, networking, or filesystem configuration, and is unlikely to cause lockout or system breakage.	—
service_kdump_disabled	service_kdump_disabled	Disable KDump Kernel Crash Analyzer (kdump)	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling the kdump service is a standard service disable operation that does not affect authentication, networking, or filesystem integrity. It follows typical STIG hardening patterns for service management and is unlikely to cause lockout or system breakage.	Loss of kernel crash dump data for forensic analysis
file_permissions_cron_d	file_permissions_cron_d	Verify Permissions on cron.d	Medium	FAIL	localhost	localhost.localdomain	LOW	Changing permissions to 0700 on /etc/cron.d is a standard STIG hardening step that does not affect authentication, networking, or filesystem integrity beyond the target directory, and is unlikely to cause lockout or service disruption.	Potential for cron jobs to fail if permissions are too restrictive
file_permissions_cron_daily	file_permissions_cron_daily	Verify Permissions on cron.daily	Medium	FAIL	localhost	localhost.localdomain	LOW	Changing permissions to 0700 on /etc/cron.daily is a standard hardening step that does not affect system services or authentication; it only restricts access to the directory, which is safe.	filesystems affected; May prevent non-root users from adding cron jobs to /etc/cron.daily
file_permissions_cron_hourly	file_permissions_cron_hourly	Verify Permissions on cron.hourly	Medium	FAIL	localhost	localhost.localdomain	LOW	Setting /etc/cron.hourly to 0700 is a standard STIG hardening step that does not affect authentication, networking, or critical services. It simply restricts access to root, which is the intended owner of system cron jobs.	Cron jobs may fail if permissions are too restrictive, but 0700 is the recommended setting for system cron directories.
file_permissions_cron_monthly	file_permissions_cron_monthly	Verify Permissions on cron.monthly	Medium	FAIL	localhost	localhost.localdomain	LOW	Setting /etc/cron.monthly to 0700 is a standard file permission hardening step that does not affect authentication, networking, or critical services. It follows STIG guidelines for file permissions and is unlikely to cause lockout or system breakage.	—
file_permissions_cron_weekly	file_permissions_cron_weekly	Verify Permissions on cron.weekly	Medium	FAIL	localhost	localhost.localdomain	LOW	Changing the permissions of /etc/cron.weekly to 0700 is a standard hardening step that does not affect authentication, networking, or critical services. It simply restricts access to the directory to the root user, which is expected behavior for cron job directories.	filesystems affected

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
package_fapolicyd_installed	package_fapolicyd_installed	Install fapolicyd Package	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the fapolicyd package is a standard package installation that does not affect authentication, networking, or filesystem configuration in a way that could lock out users or break critical services.	package installation
service_fapolicyd_enabled	service_fapolicyd_enabled	Enable the File Access Policy Service	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling the fapolicyd service is a standard service enablement that does not affect authentication, networking, or filesystem integrity. It follows typical STIG hardening patterns and is unlikely to cause lockout or system breakage.	—
package_postfix_installed	package_postfix_installed	The Postfix package is installed	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the Postfix package is a standard package installation that does not affect authentication, critical services, or system boot. It follows the STIG recommendation for required mail services and poses no risk of lockout or system breakage.	networking affected
package_s-nail_installed	package_s-nail_installed	The s-nail Package Is Installed	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the s-nail package is a standard package installation that does not affect authentication, networking, or critical services, and follows STIG guidelines for package management.	—
postfix_client_configure_mail_alias	postfix_client_configure_mail_alias	Configure System to Forward All Mail For The Root Account	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding or updating the root mail alias in /etc/aliases is a straightforward configuration change that does not affect authentication, networking, or critical system services. It simply ensures root mail is forwarded to a monitored address.	filesystems affected; Potential misconfiguration of alias could result in root mail not being forwarded
chronyd_or_ntpd_set_maxpoll	chronyd_or_ntpd_set_maxpoll	Configure Time Service Maxpoll Interval	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only modifies the maxpoll setting in the NTP/chrony configuration files, a standard and low-risk configuration change that does not affect authentication, authorization, or critical system services.	—
chronyd_server_directive	chronyd_server_directive	Ensure Chrony is only configured with the server directive	Medium	FAIL	localhost	localhost.localdomain	LOW	The fix involves editing the chrony configuration file to remove non-server directives, which is a straightforward configuration change that does not risk service lockout or system breakage.	networking affected; Potential time synchronization issues if misconfigured

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
disable_host_auth	disable_host_auth	Disable Host-Based Authentication	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves adding or ensuring a single SSH configuration directive (HostbasedAuthentication no) in a dedicated sshd_config.d file, a standard STIG hardening pattern for SSH that does not risk lockout or critical service disruption.	authentication/authorization affected; SSH configuration change; Potential misconfiguration if syntax is incorrect
sshd_disable_compression	sshd_disable_compression	Disable Compression Or Set Compression to delayed	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling or delaying SSH compression is a standard SSH configuration change that follows STIG hardening patterns and does not risk lockout or critical service disruption.	authentication/authorization affected
sshd_disable_gssapi_auth	sshd_disable_gssapi_auth	Disable GSSAPI Authentication	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling GSSAPIAuthentication is a standard SSH hardening step that does not risk lockout or critical service disruption.	authentication/authorization affected; SSH authentication mechanism
sshd_disable_rhosts	sshd_disable_rhosts	Disable SSH Support for .rhosts Files	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling IgnoreRhosts is a standard SSH hardening step that does not risk lockout or system breakage.	authentication/authorization affected; SSH configuration change
sshd_disable_user_known_hosts	sshd_disable_user_known_hosts	Disable SSH Support for User Known Hosts	Medium	FAIL	localhost	localhost.localdomain	LOW	The change is a standard SSH configuration tweak that disables caching of user known hosts, following STIG hardening patterns and unlikely to cause lockout or system breakage.	authentication/authorization affected; SSH configuration change
sshd_do_not_permit_user_env	sshd_do_not_permit_user_env	Do Not Allow SSH Environment Options	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling PermitUserEnvironment is a standard SSH hardening step that does not affect authentication or service availability; it simply prevents users from overriding environment variables. The change is local to the SSH daemon configuration and is unlikely to cause lockout or system breakage.	authentication/authorization affected; Potential misconfiguration of sshd_config may lead to SSH service restart failure
sshd_enable_pubkey_auth	sshd_enable_pubkey_auth	Enable Public Key Authentication	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling PubkeyAuthentication is a standard SSH configuration change that does not risk lockout or system breakage; it follows STIG hardening patterns for authentication.	authentication/authorization affected
sshd_enable_strictmodes	sshd_enable_strictmodes	Enable Use of Strict Mode Checking	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling StrictModes is a standard SSH configuration change that is already the default; it does not risk lockout or system breakage.	authentication/authorization affected; SSH authentication

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
sshd_print_last_log	sshd_print_last_log	Enable SSH Print Last Log	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling PrintLastLog is a standard SSH configuration change that does not affect authentication flow or system stability; it simply displays the last login time.	authentication/authorization affected
sshd_rekey_limit	sshd_rekey_limit	Force frequent session key renegotiation	Medium	FAIL	localhost	localhost.localdomain	LOW	The RekeyLimit setting is a standard SSH configuration parameter that can be safely adjusted without risking lockout or system breakage. It follows typical STIG hardening patterns for SSH session management.	authentication/authorization affected; networking affected; Potential temporary SSH session disruption if misconfigured
sshd_set_loglevel_verb	sshd_set_loglevel_verb	Set SSH Daemon LogLevel to VERBOSE	Medium	FAIL	localhost	localhost.localdomain	LOW	Setting LogLevel to VERBOSE is a standard SSH configuration change that only increases logging verbosity and does not affect authentication or service availability. It follows STIG hardening patterns and poses no risk of lockout or system breakage.	—
package_usbguard_installed	package_usbguard_installed	Install usbguard Package	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the usbguard package is a standard, non-disruptive package installation that does not affect authentication, networking, or filesystem configuration. It follows the STIG hardening pattern for package installs and is unlikely to cause lockout or system breakage.	—
service_usbguard_enabled	service_usbguard_enabled	Enable the USBGuard Service	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling the usbguard service is a standard service enablement that does not affect authentication, networking, or filesystem integrity, and is unlikely to cause lockout or system breakage.	USB device access control
package_audispd-plugins_installed	package_audispd-plugins_installed	Install audispd-plugins Package	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the audispd-plugins package is a standard, low-risk operation that does not affect authentication, networking, or filesystem integrity. It follows typical STIG hardening patterns for package installation.	—
audit_rules_etc_cron_d	audit_rules_etc_cron_d	Ensure auditd Collects Changes to Cron Jobs - /etc/cron.d/	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding an audit rule for /etc/cron.d/ is a standard configuration change that does not affect authentication, networking, or filesystem integrity, and it follows STIG hardening patterns for auditd.	—

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
audit_rules_immutable	audit_rules_immutable	Make the auditd Configuration Immutable	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding the immutable flag (-e 2) to auditd rules is a standard STIG hardening step that does not affect authentication, networking, or filesystem operation and only requires a reboot to take effect.	reboot required
audit_rules_sudoers	audit_rules_sudoers	Ensure auditd Collects System Administrator Actions - /etc/sudoers	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding an audit rule for /etc/sudoers is a standard STIG hardening step that does not affect system operation or access. It simply enables logging of sudo activity and follows the recommended pattern for audit rule configuration.	authentication/authorization affected; Potential for missing audit logs if rule is incorrectly configured
audit_rules_sudoers_d	audit_rules_sudoers_d	Ensure auditd Collects System Administrator Actions - /etc/sudoers.d/	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding an audit rule to monitor changes to /etc/sudoers.d/ is a standard STIG hardening action that does not alter system functionality or security posture beyond enabling logging. It follows the policy for safe remediation of audit rules.	authentication/authorization affected; None
audit_rules_suid_privilege_function	audit_rules_suid_privilege_function	Record Events When Privileged Executables Are Run	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves adding audit rules for execve on setuid/setgid binaries, which is a standard configuration change that does not affect system operation or security services. It follows STIG hardening patterns for audit rules and is unlikely to cause lockout or breakage.	filesystems affected; Missing audit logs for privileged executions; Potential misconfiguration of audit rule syntax
audit_rules_system_shutdown	audit_rules_system_shutdown	Shutdown System When Auditing Failures Occur	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding the '-f' option to audit rules is a standard STIG hardening step that configures auditd to halt the system on audit failures; it does not affect authentication, networking, or filesystem configuration and is unlikely to cause lockout.	Audit failure mode may halt the system if auditd encounters errors
audit_rules_usergroup_modification_group	audit_rules_usergroup_modification_group	Record Events that Modify User/Group Information - /etc/group	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding an audit rule to monitor changes to /etc/group is a standard configuration change that does not affect authentication, networking, or filesystem operation. It follows STIG hardening patterns for audit rules and carries no risk of service lockout or system breakage.	—

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
audit_rules_usergroup_modification_gshadow	audit_rules_usergroup_modification_gshadow	Record Events that Modify User/Group Information - /etc/gshadow	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding an audit rule to monitor changes to /etc/gshadow is a standard configuration change that does not affect authentication, authorization, or system functionality. It follows STIG hardening patterns for audit rules and carries no risk of lockout or service disruption.	authentication/authorization affected; audit configuration; auditd service
audit_rules_usergroup_modification_opasswd	audit_rules_usergroup_modification_opasswd	Record Events that Modify User/Group Information - /etc/security/opasswd	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding an audit rule to monitor changes to /etc/security/opasswd does not alter system functionality or security posture; it only enables logging of events. The change is a simple configuration edit that can be applied without risk of service disruption or lockout.	authentication/authorization affected; No impact on authentication or authorization mechanisms; No risk of losing SSH or console access; No effect on critical services
audit_rules_usergroup_modification_passwd	audit_rules_usergroup_modification_passwd	Record Events that Modify User/Group Information - /etc/passwd	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding an audit rule to monitor changes to /etc/passwd is a standard, low-risk configuration change that follows STIG hardening patterns and does not affect system functionality or access.	—

Requires Human Review (14)

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
aide_scan_notification	aide_scan_notification	Configure Notification of Post-AIDE Scan Details	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding a cron job to send AIDE scan results via mail is a straightforward configuration change that does not affect authentication, networking services, or critical system components. It is unlikely to cause lockout or system breakage.	—

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
fips_crypto_subpolicy	fips_crypto_subpolicy	FIPS Must Use a Supported Subpolicy	Medium	FAIL	localhost	localhost.localdomain	LOW	The rule requires the system to use one of the allowed crypto subpolicies (OSPP, NO-SHA1, NO-CAMELLIA, ECDHE-ONLY). Changing the subpolicy is a configuration change that does not inherently lock out SSH or break critical services, and can be tested locally before deployment. The policy explicitly allows safe remediation for such configuration changes.	authentication/authorization affected; networking affected; Potential temporary loss of SSH connectivity if the new subpolicy disables ciphers currently in use
account_password_pam_faillock_system_auth	account_password_pam_faillock_system_auth	Configure the Use of the pam_faillock.so Module in the /etc/pam.d/system-auth File.	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling pam_faillock via authselect follows standard STIG hardening patterns for PAM and does not risk lockout or service disruption when applied correctly.	authentication/authorization affected; Potential account lockout if misconfigured; Requires correct authselect profile
accounts_passwords_pam_faillock_deny	accounts_passwords_pam_faillock_deny	Lock Accounts After Failed Password Attempts	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation follows standard STIG hardening for PAM faillock configuration, using authselect or controlled edits, and does not risk critical service disruption.	authentication/authorization affected; Potential misconfiguration could lock out legitimate users if deny count is set incorrectly
accounts_passwords_pam_faillock_dir	accounts_passwords_pam_faillock_dir	Lock Accounts Must Persist	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation follows standard STIG hardening patterns for PAM configuration and can be applied safely using authselect or controlled edits to PAM files. It does not involve critical system components such as bootloader or filesystem changes.	authentication/authorization affected; Potential misconfiguration could lock out accounts if the dir option is set incorrectly; Requires correct PAM file syntax
accounts_passwords_pam_faillock_unlock_time	accounts_passwords_pam_faillock_unlock_time	Set Lockout Time for Failed Password Attempts	Medium	FAIL	localhost	localhost.localdomain	LOW	The rule requires a standard PAM configuration change that follows STIG hardening patterns. When applied correctly via authselect or by editing /etc/security/faillock.conf, it does not risk disabling critical services or causing system breakage.	authentication/authorization affected; Potential misconfiguration could lock out users temporarily

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
service_debug-shell_disabled	service_debug-shell_disabled	Disable debug-shell SystemD Service	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling the debug-shell service is a standard, non-critical systemd service change that does not affect authentication, networking, or filesystem integrity. It follows typical STIG hardening patterns for service disablement and is unlikely to cause lockout or system breakage.	Debug-shell may be used for troubleshooting; disabling could hinder debugging efforts
rsyslog_encrypt_offloaded_actionsendstreamdriverauthmode	rsyslog_encrypt_offloaded_actionsendstreamdriverauthmode	Ensure Rsyslog Authenticates Off-Loaded Audit Records	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves editing rsyslog configuration files to enforce authentication of off-loaded audit records, a standard configuration change that does not affect core system services or user authentication mechanisms.	authentication/authorization affected; networking affected; Potential loss of remote audit log delivery if misconfigured
rsyslog_encrypt_offloaded_actionsendstreamdrivermode	rsyslog_encrypt_offloaded_actionsendstreamdrivermode	Ensure Rsyslog Encrypts Off-Loaded Audit Records	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves editing rsyslog configuration files to enable encryption for offloaded audit records, a standard configuration change that does not affect authentication, critical services, or system boot. It is unlikely to cause lockout or system breakage.	networking affected
rsyslog_encrypt_offloaded_defaultnetstreamdriver	rsyslog_encrypt_offloaded_defaultnetstreamdriver	Ensure Rsyslog Encrypts Off-Loaded Audit Records	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves editing rsyslog configuration files to set the DefaultNetstreamDriver to gtls, a standard security hardening step that does not affect authentication, authorization, or critical system services. It is unlikely to cause lockout or system breakage.	networking affected; Potential temporary disruption of rsyslog service if configuration syntax is incorrect
sysctl_net_ipv4_icmp_echo_ignore_broadcasts	sysctl_net_ipv4_icmp_echo_ignore_broadcasts	Enable Kernel Parameter to Ignore ICMP Broadcast Echo Requests on IPv4 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	Setting net.ipv4.icmp_echo_ignore_broadcasts to 1 is a standard network hardening measure that does not affect authentication, authorization, or critical services. It only changes a kernel parameter and can be applied safely without risk of lockout.	—

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
networkmanager_dns_mode	networkmanager_dns_mode	NetworkManager DNS Mode Must Be Configured	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves editing NetworkManager configuration files to set the DNS mode, a standard network configuration change that is unlikely to lock out users or break critical services. It follows typical STIG hardening patterns for network settings.	networking affected; Potential temporary loss of network connectivity during restart of NetworkManager; Incorrect value may cause DNS resolution failures
fapolicy_default_deny	fapolicy_default_deny	Configure Fapolicy Module to Employ a Deny-all, Permit-by-exception Policy to Allow the Execution of Authorized Software Programs.	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation script applies a standard deny-all rule and sets permissive mode to 0, a common STIG hardening practice that does not affect critical services or authentication mechanisms. It is a straightforward configuration change with minimal risk of system breakage.	Potential to block execution of system binaries if allow rules are not properly configured
usbguard_generate_policy	usbguard_generate_policy	Generate USBGuard Policy	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation script only generates a policy file and restarts the usbguard service, which is a standard service enablement and configuration change that does not risk lockout or critical service disruption.	filesystems affected

Too Dangerous to Remediate (10)

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
enable_dracut_fips_module	enable_dracut_fips_module	Enable Dracut FIPS Module	High	FAIL	localhost	localhost.localdomain	CRITICAL	Enabling FIPS mode on a pre-existing RHEL 9 system is unsupported and can render the system inoperable. The rule indicates the finding is permanent and cannot be fixed without reinstalling or reinstalling with FIPS enabled at install time.	reboot required; authentication/authorization affected; FIPS mode activation; kernel boot parameter change; potential loss of bootability; system breakage

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
enable_fips_mode	enable_fips_mode	Enable FIPS Mode	High	FAIL	localhost	localhost.localdomain	CRITICAL	Enabling FIPS mode requires a kernel boot parameter (fips=1) and is not supported on an existing system; attempting to remediate can render the system unusable or permanently non-compliant. The change involves critical bootloader/kernel configuration and can affect all cryptographic operations, making it a high-risk modification.	reboot required; FIPS mode change; kernel boot parameter alteration; potential system instability; permanent finding on installed systems
fips_custom_stig_sub_policy	fips_custom_stig_sub_policy	Implement STIG Sub Crypto Policy	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	Enabling FIPS mode via a custom crypto policy can lock out services, break compatibility, and may require a reboot. The policy explicitly marks FIPS changes as too dangerous to remediate without human review.	reboot required; authentication/authorization affected; networking affected; FIPS mode activation; SSH cipher changes; potential service breakage; system lockout
sysctl_crypto_fips_enabled	sysctl_crypto_fips_enabled	Set kernel parameter 'crypto.fips_enabled' to 1	High	FAIL	localhost	localhost.localdomain	CRITICAL	Enabling FIPS mode requires adding the fips=1 kernel boot parameter during installation; it cannot be enabled on a pre-existing system without reinstalling or reconfiguring the bootloader, which is a high-risk operation that may lock out the system or break critical services.	reboot required; authentication/authorization affected; Bootloader modification; System reboot required; Potential loss of SSH/console access; FIPS mode enforcement
partition_for_var_tmp	partition_for_var_tmp	Ensure /var/tmp Located On Separate Partition	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	Filesystem/partition/mount-option changes can break boot or services and should not be auto-remediated.	reboot required; filesystems affected; filesystems/partitioning; service disruption risk
grub2_init_on_free	grub2_init_on_free	The system must booted with init_on_free=1	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	Changing the kernel boot parameter via the bootloader can render the system unbootable or lock out remote access if applied incorrectly. The remediation script modifies GRUB or bootc configuration, which is a bootloader change and falls under the policy's definition of too dangerous to remediate without human review.	reboot required; Boot failure; Loss of SSH/console access; System breakage

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
grub2_vsycall_argument	grub2_vsycall_argument	Disable vsyscalls	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	Disabling vsyscalls requires modifying the GRUB2 kernel command line, a bootloader configuration change that can prevent the system from booting or cause service disruption if misconfigured. Such changes are considered too dangerous to remediate automatically without human oversight.	reboot required; bootloader configuration; kernel parameter change; potential boot failure; service disruption
grub2_admin_username	grub2_admin_username	Set the Boot Loader Admin Username to a Non-Default Value	High	FAIL	localhost	localhost.localdomain	CRITICAL	Changing the boot loader superuser account directly modifies the boot configuration; a misconfiguration can render the system unbootable or lock out all administrative access. This is a bootloader change, which the policy marks as too dangerous to remediate without careful review.	reboot required; authentication/authorization affected; Bootloader misconfiguration; Loss of boot capability; Administrative lockout
grub2_password	grub2_password	Set Boot Loader Password in grub2	High	FAIL	localhost	localhost.localdomain	CRITICAL	Setting a boot loader password is a bootloader change that can lock out the system if misconfigured, potentially preventing boot and console access. The policy explicitly marks bootloader changes as too dangerous to remediate without careful review.	reboot required; authentication/authorization affected; boot failure; loss of console access; bootloader misconfiguration
grub2_page_poison_argument	grub2_page_poison_argument	Enable page allocator poisoning	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	Modifying the GRUB configuration to add a kernel command line argument changes the bootloader settings, which can render the system unbootable if misconfigured. This falls under the policy's definition of bootloader changes that are considered too dangerous to remediate automatically.	reboot required; Boot failure; Potential loss of console access; System unbootable