

OpenSCAP Triage Report

Target: 192.168.64.13 | Generated: 2026-04-09 22:33:27

Scan Statistics

Total Rules Scanned	0
Rules Passed	0
Rules Failed / Errors	0

Triage Summary

Total Findings Triage	150
Safe to Remediate	122
Requires Human Review	10
Too Dangerous / Blocked	18

Safe to Remediate (122)

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
package_aide_installed	package_aide_installed	Install AIDE	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only installs the aide package, which is a standard integrity checking tool. Installing a package does not modify authentication, networking, or filesystem layout and poses minimal risk of lockout or service disruption.	—

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
aide_build_database	aide_build_database	Build and Test AIDE Database	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only installs the aide package (if missing), initializes the AIDE database, and copies the new database into place. These actions are standard, low-impact operations that do not affect authentication, networking, or boot configuration, and they do not require a reboot.	filesystems affected
aide_check_audit_tools	aide_check_audit_tools	Configure AIDE to Verify the Audit Tools	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only installs the AIDE package (if missing) and appends or updates simple lines in /etc/aide.conf. These actions are standard STIG hardening steps, involve no service restarts that could disrupt critical functionality, and do not affect authentication, networking, or filesystem layout. The change is low-complexity and unlikely to cause lockout or system breakage.	Potential for AIDE false positives if the configuration is incorrect; If AIDE database is not reinitialized, integrity checks may fail
aide_scan_notification	aide_scan_notification	Configure Notification of Post-AIDE Scan Details	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adds or updates a cron entry to pipe AIDE output to the local mail command. This is a straightforward file edit and optional package install, with no impact on authentication, networking, or critical services, and does not require a reboot.	filesystems affected
aide_use_fips_hashes	aide_use_fips_hashes	Configure AIDE to Use FIPS 140-2 for Validating Hashes	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits /etc/aide.conf to ensure sha512 is present and removes disallowed hashes, and optionally installs the aide package. This is a straightforward file edit that does not affect authentication, networking, or boot processes, and does not require a reboot. The change follows standard STIG guidance and carries minimal risk of system lockout or service disruption.	Incorrect syntax in /etc/aide.conf could cause AIDE to fail on next run; Removal of a hash algorithm that might be referenced elsewhere in custom rules
package_gnutils-utils_installed	package_gnutils-utils_installed	Ensure gnutils-utils is installed	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only installs a user-space utility package. Installing gnutils-utils does not modify authentication, bootloader, or critical system services, and it is unlikely to cause lockout or system instability.	—

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
package_nss-tools_installed	package_nss-tools_installed	Ensure nss-tools is installed	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the nss-tools package is a simple, non-disruptive operation that does not affect authentication, networking, or filesystem layout, and it follows the policy allowing package installs to be classified as safe.	—
package_subscription-manager_installed	package_subscription-manager_installed	Install subscription-manager Package	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the subscription-manager package is a straightforward, low-impact operation that does not modify authentication, networking, or filesystem structures and is explicitly listed as a safe remediation type.	—
ensure_gpgcheck_local_packages	ensure_gpgcheck_local_packages	Ensure gpgcheck Enabled for Local Packages	High	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits /etc/dnf/dnf.conf to set localpkg_gpgcheck=1, a straightforward configuration change that does not affect authentication, networking, or critical services. It is low risk and aligns with standard STIG hardening practices.	Potential misconfiguration of dnf.conf could affect package installation; Incorrect syntax could cause dnf errors
enable_authselect	enable_authselect	Enable authselect	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only runs authselect to apply a predefined authentication profile. This is a standard STIG hardening step for PAM/authentication and does not modify bootloader, kernel, or filesystem structures. While an incorrect profile could lock out users, the risk is typical for PAM changes and can be mitigated with pre-checks, so it is classified as safe to remediate.	authentication/authorization affected; potential PAM misconfiguration; possible loss of SSH or console authentication if profile is incorrect
banner_etc_issue	banner_etc_issue	Modify the System Login Banner	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only requires editing /etc/issue to replace the banner text. This is a straightforward file modification that does not affect authentication mechanisms, networking, or boot processes, and it carries no risk of locking out SSH or console access.	filesystems affected

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
account_password_pam_faillock_password_auth	account_password_pam_faillock_password_auth	Configure the Use of the pam_faillock.so Module in the /etc/pam.d/password-auth File.	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation uses the standard authselect feature to enable pam_faillock, which is a well-documented STIG hardening step. It does not require reboot and only modifies PAM configuration, making it low risk when applied correctly.	authentication/authorization affected; Potential account lockout if pam_faillock parameters are misconfigured; Failure of authselect integrity check could abort remediation
account_password_pam_faillock_system_auth	account_password_pam_faillock_system_auth	Configure the Use of the pam_faillock.so Module in the /etc/pam.d/system-auth File.	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation involves enabling the pam_faillock feature via authselect or editing PAM configuration, which is a standard STIG hardening step. The change is well-documented, does not modify boot or filesystem layout, and the authselect tool guards against corrupt profiles, making the risk of lockout low when performed correctly.	authentication/authorization affected; Potential lockout if authselect profile is incorrect or PAM syntax error introduced; Requires correct execution on systems using authselect
accounts_passwords_pam_faillock_dir	accounts_passwords_pam_faillock_dir	Lock Accounts Must Persist	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation uses the standard authselect tool to enable the with-faillock feature and optionally edits PAM files. This is a typical STIG-approved PAM hardening step with minimal risk when performed via authselect, and it does not involve kernel, bootloader, or filesystem changes.	authentication/authorization affected; Potential lockout if PAM configuration is applied incorrectly; Loss of remote SSH access if changes are not validated locally
accounts_passwords_pam_faillock_interval	accounts_passwords_pam_faillock_interval	Set Interval For Counting Failed Password Attempts	Medium	FAIL	localhost	localhost.localdomain	LOW	The fix only modifies PAM fail_interval via authselect or direct PAM file edit, which is a standard STIG hardening step and does not normally cause system lockout if applied correctly.	authentication/authorization affected; Misconfiguration could temporarily lock out accounts; Requires correct authselect profile selection
accounts_password_pam_dcredit	accounts_password_pam_dcredit	Ensure PAM Enforces Password Requirements - Minimum Digit Characters	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only modifies the pam_pwquality dcredit setting, a standard PAM configuration change that does not affect system boot, networking, or critical services. It is a low-complexity edit and is commonly applied in STIG hardening without risk of lockout if the change is applied correctly.	authentication/authorization affected; Incorrect syntax could cause PAM to reject all logins; Existing passwords may not meet the new digit requirement

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
accounts_password_pam_dictcheck	accounts_password_pam_dictcheck	Ensure PAM Enforces Password Requirements - Prevent the Use of Dictionary Words	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits PAM password quality configuration files to set the dictcheck option. This is a standard STIG hardening step, does not modify kernel, bootloader, or partitioning, and is unlikely to cause loss of access. The change is reversible and can be validated with a test password.	authentication/authorization affected; Potential for users to be forced to change passwords that contain dictionary words; Misconfiguration could weaken password policy if dictcheck is incorrectly set
accounts_password_pam_difok	accounts_password_pam_difok	Ensure PAM Enforces Password Requirements - Minimum Different Characters	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits a PAM password quality configuration parameter (difok) to enforce a minimum number of differing characters when changing passwords. This is a standard STIG hardening step, does not affect system boot or critical services, and is unlikely to cause lockout if set to a reasonable value.	authentication/authorization affected; Improperly low difok value could reduce password strength; Improperly high difok value could cause user password change failures
accounts_password_pam_enforce_root	accounts_password_pam_enforce_root	Ensure PAM Enforces Password Requirements - Enforce for root User	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits /etc/security/pwquality.conf to add the 'enforce_for_root' option, a standard PAM password policy change. It does not modify kernel parameters, bootloader, or filesystem layout, and it does not require a reboot. While it will require the root password to meet the configured complexity rules, this risk is minimal and can be mitigated by ensuring the root password is updated accordingly before the change takes effect.	authentication/authorization affected; Root password may no longer meet complexity requirements, potentially causing authentication failures if not updated; Incorrect file syntax could break PAM password checks
accounts_password_pam_lcredit	accounts_password_pam_lcredit	Ensure PAM Enforces Password Requirements - Minimum Lowercase Characters	Medium	FAIL	localhost	localhost.localdomain	LOW	The finding requires a simple edit to the PAM pwquality configuration to enforce a minimum number of lowercase characters. This is a standard STIG hardening step, does not require a reboot, and carries minimal risk of system breakage. Proper testing and backup mitigate any chance of user lockout.	authentication/authorization affected; Potential user password policy change; Possible temporary login issues if users are unaware of new requirement

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
accounts_password_pam_maxclassrepeat	accounts_password_pam_maxclassrepeat	Ensure PAM Enforces Password Requirements - Maximum Consecutive Repeating Characters from Same Character Class	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits a PAM password quality configuration file to set maxclassrepeat. This is a standard STIG hardening change that does not affect system boot, networking, or critical services, and it will not lock out existing users; it only tightens password composition rules.	authentication/authorization affected; Potential for legitimate passwords to be rejected if they contain too many consecutive characters from the same class; Possible user confusion if the new policy is stricter than current practice
accounts_password_pam_maxrepeat	accounts_password_pam_maxrepeat	Set Password Maximum Consecutive Repeating Characters	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits a PAM password quality configuration file to set the maxrepeat parameter. This is a standard STIG hardening change, does not modify critical services, and will take effect on the next authentication without requiring a reboot. The risk of lockout is minimal if the value is set to a reasonable number.	authentication/authorization affected; Potential user lockout if maxrepeat is set too low; Password change failures for passwords with repeated characters
accounts_password_pam_minclass	accounts_password_pam_minclass	Ensure PAM Enforces Password Requirements - Minimum Different Categories	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits a PAM password quality configuration file to enforce a minimum number of character classes. This is a standard STIG hardening step, does not require a reboot, and carries minimal risk of locking out users if the chosen value is reasonable.	authentication/authorization affected; Potential password change failures for users whose passwords do not meet the new class requirement; Possible user confusion or support tickets after policy change
accounts_password_pam_minlen	accounts_password_pam_minlen	Ensure PAM Enforces Password Requirements - Minimum Length	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits PAM password quality configuration files to set the minlen parameter. This is a standard STIG hardening step, does not modify kernel, bootloader, or filesystem layout, and carries minimal risk of lockout if the desired length is reasonable. Therefore it is safe to apply automatically.	authentication/authorization affected; Potential for users to be unable to set passwords shorter than the new minimum if the value is set too high; Misconfiguration could affect password change operations

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
accounts_password_pam_ocr edit	accounts_password_pam_ocr edit	Ensure PAM Enforces Password Requirements - Minimum Special Characters	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits a PAM password quality configuration file to enforce a minimum number of special characters. This is a standard STIG hardening step, does not affect system boot or critical services, and is unlikely to cause lockout if applied correctly.	authentication/authorization affected; Incorrect ocredit value could weaken password complexity; Misconfiguration could prevent password changes
accounts_password_pam_pwquality_retry	accounts_password_pam_pwquality_retry	Ensure PAM Enforces Password Requirements - Authentication Retry Prompts Permitted Per-Session in /etc/security/pwquality.conf	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits /etc/security/pwquality.conf (or its .d fragments) to set or remove the 'retry' parameter, a standard PAM password policy change. This is a low impact configuration edit that does not affect service startup, kernel parameters, or bootloader settings, and is unlikely to cause loss of SSH or console access.	authentication/authorization affected; Potential lockout if 'retry' is set to an overly restrictive value; Misconfiguration could leave the setting unset, relying on defaults
accounts_password_pam_ucredit	accounts_password_pam_ucredit	Ensure PAM Enforces Password Requirements - Minimum Uppercase Characters	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only modifies the PAM pwquality configuration to enforce an uppercase character requirement. This is a standard STIG hardening step, does not affect boot or networking, and is unlikely to lock out users if the change is applied correctly.	authentication/authorization affected; Potential for users to be unable to set passwords that meet the new requirement; Misconfiguration could cause pam_pwquality to reject all passwords
service_debug-shell_disabled	service_debug-shell_disabled	Disable debug-shell SystemD Service	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling and masking the debug-shell service is a standard STIG remediation that does not affect authentication, networking, or filesystem layout. The service is optional and typically disabled by default, so remediation is low risk and unlikely to cause lockout or system breakage.	Loss of on-console debug shell (acceptable in production environments); Potential need to re-enable for future SystemD troubleshooting
disable_ctrlaltdel_burstaction	disable_ctrlaltdel_burstaction	Disable Ctrl-Alt-Del Burst Action	High	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits a single line in /etc/systemd/system.conf to set CtrlAltDelBurstAction=none, which is a standard STIG hardening step. It does not affect authentication, networking, or filesystem layout, and the change is low risk. The only impact is that the system may need a daemon reload or reboot for the setting to take effect.	reboot required; Misconfiguration could leave the Ctrl-Alt-Del key sequence functional; Change may require a systemd daemon reload or reboot to apply

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
disable_ctrlaltdel_reboot	disable_ctrlaltdel_reboot	Disable Ctrl-Alt-Del Reboot Activation	High	FAIL	localhost	localhost.localdomain	LOW	The remediation only masks and disables a systemd target, which does not affect authentication, networking, or filesystem layout. It is a standard STIG hardening step with minimal risk of lockout or service disruption.	—
package_opensc_installed	package_opensc_installed	Install the opensc Package For Multifactor Authentication	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only installs the opensc package, a standard repository package, which does not modify system configuration, services, or boot settings. Package installation is low risk and aligns with policy for safe remediation.	authentication/authorization affected; possible dependency conflicts
package_pcsc-lite_installed	package_pcsc-lite_installed	Install the pcsc-lite package	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only installs the pcsc-lite package, which is a standard, low-impact operation that does not modify authentication, authorization, networking, or critical filesystem structures. It follows the policy allowing package installs to be classified as safe.	—
install_smartcard_packages	install_smartcard_packages	Install Smart Card Packages For Multifactor Authentication	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only installs the openssl-pkcs11 package, which adds smartcard support for MFA. Package installation is a standard, low-impact STIG remediation and does not modify authentication configuration, bootloader, or filesystem layout, so it is unlikely to cause lockout or service disruption.	authentication/authorization affected
service_pcscd_enabled	service_pcscd_enabled	Enable the pcscd Service	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling the pcscd service is a standard, low-impact remediation (service enablement). It does not modify authentication, networking, or filesystem structures and is unlikely to cause lockout or system breakage.	—
configure_opensc_card_drivers	configure_opensc_card_drivers	Configure opensc Smart Card Drivers	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only requires adding a line to /etc/opensc.conf and optionally invoking opensc-tool to verify the setting. This is a simple file edit that does not affect system boot, networking, or critical services, and follows standard STIG hardening practices for authentication configuration.	authentication/authorization affected; unauthorized smart card usage if drivers are not restricted; potential misconfiguration leading to smart card authentication failure

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
account_disable_post_pw_expiration	account_disable_post_pw_expiration	Set Account Expiration Following Inactivity	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits a single line in /etc/default/useradd to set the INACTIVE value. This is a standard STIG hardening step, does not modify kernel, bootloader, or partitioning, and carries minimal risk of service disruption. Properly setting a numeric value will not lock out existing sessions and can be validated quickly.	authentication/authorization affected; Potential account lockout if an inappropriate INACTIVE value is set; Misconfiguration could affect future password expiration handling
accounts_maximum_age_login_defs	accounts_maximum_age_login_defs	Set Password Maximum Age	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits /etc/login.defs to set PASS_MAX_DAYS, a straightforward configuration change that does not affect system boot, networking, or filesystem layout. Such password policy adjustments are standard STIG hardening actions and carry minimal risk of lockout or service disruption.	authentication/authorization affected; Incorrect or empty value could result in no password expiration enforcement; Potential for user confusion if existing passwords are not updated
accounts_minimum_age_login_defs	accounts_minimum_age_login_defs	Set Password Minimum Age	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits a single line in /etc/login.defs to set PASS_MIN_DAYS. This is a standard password policy change that does not affect system boot, networking, or critical services, and is unlikely to cause lockout if the value is reasonable (e.g., 1 day).	authentication/authorization affected; Improper value could prevent immediate password changes; Potential user confusion if minimum age is set too high
accounts_password_set_min_life_existing	accounts_password_set_min_life_existing	Set Existing Passwords Minimum Age	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adjusts password minimum age via the standard 'chage' utility, a common STIG hardening step. It does not modify critical services, boot settings, or filesystem layouts, and the change (1 day minimum) is unlikely to cause lockout or system breakage.	authentication/authorization affected; User inconvenience if a password change is needed immediately; Potential for scripts that force immediate password change to fail

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
use_pam_wheel_for_su	use_pam_wheel_for_su	Enforce usage of pam_wheel for su authentication	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits a single PAM configuration line in /etc/pam.d/su to require the pam_wheel module. This is a standard STIG hardening step, does not modify bootloader or filesystem structures, and is unlikely to cause system lockout if the wheel group exists. Therefore it is considered safe to remediate automatically.	authentication/authorization affected; Potential loss of su access if wheel group is empty or misconfigured; Impact on local privilege escalation workflows
accounts_logon_failure_delay	accounts_logon_failure_delay	Ensure the Logon Failure Delay is Set Correctly in login.defs	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits a single line in /etc/login.defs, a standard authentication configuration file. The change does not affect service startup, kernel parameters, or bootloader settings, and it does not require a reboot. Such edits are routine in STIG compliance and carry minimal risk of lockout.	authentication/authorization affected; Incorrect syntax could prevent login.defs from being parsed; Setting an excessively high delay could impact user experience
accounts_tmout	accounts_tmout	Set Interactive Session Timeout	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits or creates a small shell script in /etc/profile.d to set TMOUT to a positive integer. This change does not affect bootloader, kernel, or filesystem layout and is a standard STIG hardening step. It will not lock out SSH or console access.	authentication/authorization affected; incorrect TMOUT value could cause premature session termination; potential user inconvenience if timeout is too short
package_rsyslog_gnutls_installed	package_rsyslog_gnutls_installed	Ensure rsyslog-gnutls is installed	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only installs the rsyslog-gnutls package, a standard, non-intrusive operation that adds TLS support to rsyslog. It does not modify authentication, bootloader, or critical system files, and is unlikely to cause lockout or service disruption.	networking affected
rsyslog_remote_access_monitoring	rsyslog_remote_access_monitoring	Ensure remote access methods are monitored in Rsyslog	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adds or verifies selector lines in /etc/rsyslog.conf to log auth, authpriv, and daemon facilities. This is a straightforward configuration edit that does not affect authentication mechanisms, network services, or boot processes, and it does not require a reboot. The risk of causing lockout or service disruption is minimal.	authentication/authorization affected; filesystems affected; Potential for mistyped selector causing missing logs; Incorrect file permissions could prevent rsyslog from reading the config

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
rsyslog_remote_loghost	rsyslog_remote_loghost	Ensure Logs Sent To Remote Host	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits /etc/rsyslog.conf to add or modify a remote logging directive and restarts the rsyslog service. This is a straightforward configuration change that does not affect authentication, boot process, or critical system services, making it safe to apply automatically.	networking affected; Incorrect remote host address could stop log forwarding; Network connectivity issues may prevent logs from reaching the remote server
network_configure_name_resolution	network_configure_name_resolution	Configure Multiple DNS Servers in /etc/resolv.conf	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only requires editing a plain text configuration file (/etc/resolv.conf) to add additional 'nameserver' entries and optionally ensuring 'dns' is present in /etc/nsswitch.conf. This change does not affect authentication, boot process, or critical services, and can be applied without risking loss of access.	networking affected
package_libreswan_installed	package_libreswan_installed	Install libreswan Package	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only installs the libreswan package, which adds IPsec/IKE functionality. Package installation on RHEL 9 is a standard, low-impact operation that does not modify authentication, bootloader, or critical system files, and it does not require a reboot.	networking affected; adds a new network service (IPsec); potential firewall rule adjustments may be needed
sysctl_net_ipv6_conf_all_accept_ra	sysctl_net_ipv6_conf_all_accept_ra	Configure Accepting Router Advertisements on All IPv6 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits sysctl configuration files to disable IPv6 router advertisements and applies the change at runtime. This does not affect authentication, bootloader, or critical services, and the change can be applied without reboot. The risk is limited to possible loss of IPv6 connectivity, which is acceptable in most hardened environments.	networking affected; possible loss of IPv6 network functionality; impact on services that rely on IPv6 router advertisements
sysctl_net_ipv6_conf_all_accept_redirects	sysctl_net_ipv6_conf_all_accept_redirects	Disable Accepting ICMP Redirects for All IPv6 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only modifies a kernel networking parameter via sysctl and adds a persistent entry in /etc/sysctl.d. This is a standard STIG hardening step, does not affect authentication, bootloader, or filesystem layout, and does not risk loss of remote access.	networking affected; network security; potential impact on IPv6 routing if misconfigured

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
sysctl_net_ipv6_conf_all_accept_source_route	sysctl_net_ipv6_conf_all_accept_source_route	Disable Kernel Parameter for Accepting Source-Routed Packets on all IPv6 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only involves adding or commenting a sysctl entry to disable IPv6 source routing, which is a standard, low-impact configuration change. It does not affect authentication, SSH, or critical services and can be applied at runtime without reboot.	networking affected; IPv6 source routing can be abused for spoofing and man-in-the-middle attacks; Leaving the parameter enabled weakens network security
sysctl_net_ipv6_conf_all_forwarding	sysctl_net_ipv6_conf_all_forwarding	Disable Kernel Parameter for IPv6 Forwarding	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits sysctl configuration files to disable IPv6 forwarding, a standard STIG hardening step. It does not affect authentication, bootloader, or critical services, and the change takes effect at runtime without requiring a reboot.	networking affected; networking
sysctl_net_ipv6_conf_default_accept_ra	sysctl_net_ipv6_conf_default_accept_ra	Disable Accepting Router Advertisements on all IPv6 Interfaces by Default	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only modifies sysctl configuration files to disable a networking kernel parameter. This is a standard STIG hardening step, does not affect authentication, bootloader, or filesystem layout, and is unlikely to cause loss of access or service disruption.	networking affected; networking configuration change
sysctl_net_ipv6_conf_default_accept_redirects	sysctl_net_ipv6_conf_default_accept_redirects	Disable Kernel Parameter for Accepting ICMP Redirects by Default on IPv6 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only modifies a sysctl setting to disable IPv6 ICMP redirect acceptance. This is a standard STIG hardening step, does not affect authentication, bootloader, or filesystem layout, and can be applied without risking loss of remote access.	networking affected; network_security
sysctl_net_ipv6_conf_default_accept_source_route	sysctl_net_ipv6_conf_default_accept_source_route	Disable Kernel Parameter for Accepting Source-Routed Packets on IPv6 Interfaces by Default	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only involves commenting out existing sysctl entries and adding a persistent setting for a networking kernel parameter. This is a standard, low-impact configuration change that does not affect authentication, bootloader, or filesystem layout and is unlikely to cause loss of access or service disruption.	networking affected; network configuration change; potential impact on IPv6 routing behavior

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
sysctl_net_ipv4_conf_all_accept_redirects	sysctl_net_ipv4_conf_all_accept_redirects	Disable Accepting ICMP Redirects for All IPv4 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling net.ipv4.conf.all.accept_redirects via sysctl is a standard STIG hardening step that reduces exposure to ICMP redirect attacks. The change is limited to a kernel networking parameter, does not affect authentication, authorization, or critical services, and can be applied at runtime with persistence through a config file.	networking affected; Potential disruption if legitimate network devices rely on ICMP redirects for routing updates
sysctl_net_ipv4_conf_all_accept_source_route	sysctl_net_ipv4_conf_all_accept_source_route	Disable Kernel Parameter for Accepting Source-Routed Packets on all IPv4 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling source-routed packets via a sysctl setting is a standard STIG hardening step. The remediation only edits a sysctl configuration file and applies the change at runtime, which does not affect authentication, SSH access, or critical services. The risk of breaking legitimate functionality is minimal.	networking affected; Legacy applications that rely on source routing may stop functioning
sysctl_net_ipv4_conf_all_forwarding	sysctl_net_ipv4_conf_all_forwarding	Disable Kernel Parameter for IPv4 Forwarding on all IPv4 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits sysctl configuration files and applies a runtime sysctl change. This is a standard, low-impact STIG hardening action that does not affect authentication, bootloader, or filesystem layout, and it does not require a reboot.	networking affected; Potential disruption of routing if the system is used as a router or firewall
sysctl_net_ipv4_conf_all_rp_filter	sysctl_net_ipv4_conf_all_rp_filter	Enable Kernel Parameter to Use Reverse Path Filtering on all IPv4 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling net.ipv4.conf.all.rp_filter is a standard sysctl hardening step that does not require a reboot and is unlikely to lock out SSH or break critical services. The remediation only edits or creates a sysctl configuration file and applies the setting at runtime.	networking affected; Potential for legitimate traffic to be dropped if asymmetric routing is used
sysctl_net_ipv4_conf_default_accept_redirects	sysctl_net_ipv4_conf_default_accept_redirects	Disable Kernel Parameter for Accepting ICMP Redirects by Default on IPv4 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation consists of a straightforward sysctl configuration change that disables acceptance of ICMP redirects on default IPv4 interfaces. This is a common STIG hardening step, does not affect authentication, boot process, or critical services, and takes effect immediately without requiring a reboot. The risk of losing remote access is negligible because the change only influences how the kernel handles ICMP redirect packets, not SSH or console connectivity.	networking affected; Potential impact on network routing if legitimate ICMP redirects are used in the environment; Misconfiguration could leave the parameter enabled if duplicate entries exist

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
sysctl_net_ipv4_conf_default_r_p_filter	sysctl_net_ipv4_conf_default_rp_filter	Enable Kernel Parameter to Use Reverse Path Filtering on all IPv4 Interfaces by Default	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adds or updates a sysctl entry to enable reverse path filtering, which is a standard network hardening measure. It does not affect authentication, authorization, or critical services, and the change can be applied without reboot.	networking affected; Potential impact on asymmetric routing or VPN configurations; Misconfiguration could drop legitimate traffic
sysctl_net_ipv4_icmp_echo_ignore_broadcasts	sysctl_net_ipv4_icmp_echo_ignore_broadcasts	Enable Kernel Parameter to Ignore ICMP Broadcast Echo Requests on IPv4 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only involves adding or ensuring a sysctl entry and applying it at runtime. This change does not affect authentication, boot process, or critical services, and follows standard STIG sysctl hardening practices.	networking affected; Minimal impact on network diagnostics (ICMP echo requests will be ignored); Potential incompatibility with legacy monitoring tools that rely on broadcast pings
sysctl_net_ipv4_tcp_syncookies	sysctl_net_ipv4_tcp_syncookies	Enable Kernel Parameter to Use TCP Syncookies on Network Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits sysctl configuration files to enable net.ipv4.tcp_syncookies, a standard security hardening measure. It does not modify authentication, bootloader, or filesystem layouts, and can be applied at runtime without reboot. According to policy, sysctl persistence changes are classified as safe to remediate.	networking affected; network stack configuration change; potential impact on TCP behavior if misapplied
sysctl_net_ipv4_conf_all_send_redirects	sysctl_net_ipv4_conf_all_send_redirects	Disable Kernel Parameter for Sending ICMP Redirects on all IPv4 Interfaces	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only comments out existing sysctl entries and ensures the kernel parameter net.ipv4.conf.all.send_redirects is set to 0. This change does not affect authentication, sudo, or critical services and is a standard STIG sysctl hardening step, posing minimal risk of lockout or system breakage.	networking affected; Disabling ICMP redirects may impact certain network topologies that rely on them
sysctl_net_ipv4_conf_default_send_redirects	sysctl_net_ipv4_conf_default_send_redirects	Disable Kernel Parameter for Sending ICMP Redirects on all IPv4 Interfaces by Default	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling net.ipv4.conf.default.send_redirects is a standard STIG sysctl hardening step that does not affect authentication, console access, or critical services. The remediation only edits or adds a line in /etc/sysctl.d and applies the change at runtime, posing minimal risk.	networking affected; Minor impact on network behavior if ICMP redirects were previously relied upon

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
kernel_module_atm_disabled	kernel_module_atm_disabled	Disable ATM Support	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits /etc/modprobe.d/atm.conf to prevent the atm kernel module from loading. This is a standard, low-impact configuration change that does not affect authentication, critical services, or system boot. The change is idempotent and can be applied without risking SSH or console access.	networking affected; Disabling a rarely used network module may affect legacy applications that rely on ATM; Potential need to reboot for immediate effect if the module is already loaded
kernel_module_can_disabled	kernel_module_can_disabled	Disable CAN Support	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits a modprobe configuration file to prevent the CAN kernel module from loading. This is a standard STIG hardening step, does not affect authentication, SSH, or critical services, and can be applied without risking system lockout.	networking affected; Potential impact on applications that rely on CAN hardware; Kernel module loading behavior
kernel_module_sctp_disabled	kernel_module_sctp_disabled	Disable SCTP Support	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adds or updates a line in /etc/modprobe.d/sctp.conf to prevent the SCTP kernel module from loading. This is a standard STIG hardening step, does not affect authentication, bootloader, or critical services, and is unlikely to cause system lockout or breakage.	networking affected; Disabling SCTP may affect applications that rely on the SCTP protocol
kernel_module_bluetooth_disabled	kernel_module_bluetooth_disabled	Disable Bluetooth Kernel Module	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits a modprobe.d file to blacklist the Bluetooth kernel module. This is a standard STIG hardening step, does not affect authentication, bootloader, or critical services, and can be applied without risking SSH or console lockout.	networking affected; Loss of Bluetooth functionality on systems that rely on it; Potential need for a reboot to unload an already loaded module
networkmanager_dns_mode	networkmanager_dns_mode	NetworkManager DNS Mode Must Be Configured	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits NetworkManager configuration files to set the DNS mode. This is a straightforward text substitution that does not affect authentication, bootloader, or critical system services, and can be applied without risking loss of SSH or console access.	networking affected; Potential DNS resolution disruption if an incorrect mode is set; Misconfiguration could affect applications relying on DNS

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
rootfiles_configured	rootfiles_configured	Ensure rootfiles tmpfile.d is Configured Correctly	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits or creates a small text file under /etc/tmpfiles.d/ to enforce correct permissions on root's initialization files. This does not affect authentication mechanisms, networking, or critical services, and the change is reversible. The operation is straightforward and low risk.	filesystems affected; potential misconfiguration of root dotfile permissions; incorrect removal of existing tmpfiles entries
kernel_module_usb-storage_disabled	kernel_module_usb-storage_disabled	Disable Modprobe Loading of USB Storage Driver	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits a modprobe configuration file to prevent the usb-storage kernel module from loading. This is a standard STIG hardening step, does not affect authentication, networking, or core filesystem layout, and is unlikely to cause loss of SSH or console access. The change is reversible and does not require a reboot for the configuration to take effect on subsequent module loads.	Disables legitimate USB storage devices that may be required for certain workloads; Potential impact on applications that rely on hotplug USB storage
mount_option_dev_shm_nodev	mount_option_dev_shm_nodev	Add nodev Option to /dev/shm	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding the nodev mount option to /dev/shm is a simple fstab edit that does not affect authentication, networking, or bootloader configuration. The change is low risk, unlikely to cause lockout or service disruption, and follows standard STIG hardening practices.	filesystems affected; Potential impact on applications that rely on device files within /dev/shm
mount_option_dev_shm_nosuid	mount_option_dev_shm_nosuid	Add nosuid Option to /dev/shm	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding the nosuid mount option to /dev/shm is a standard STIG hardening step that prevents execution of setuid programs in a world-writable tmpfs. It does not modify authentication, networking, or bootloader settings and is unlikely to cause lockout or service disruption.	filesystems affected; Potential impact on applications that rely on setuid binaries placed in /dev/shm
sysctl_kernel_core_pattern	sysctl_kernel_core_pattern	Disable storing core dumps	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits sysctl configuration files to comment out kernel.core_pattern entries and optionally applies the setting at runtime. This is a standard sysctl persistence change, poses no risk of SSH or console lockout, and does not affect critical services or filesystem structures.	Potential loss of core dump information for debugging

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
sysctl_kernel_kexec_load_disabled	sysctl_kernel_kexec_load_disabled	Disable Kernel Image Loading	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits or adds a sysctl entry to disable kexec image loading. This is a standard STIG sysctl hardening action, does not affect authentication, networking, or filesystem layout, and does not require a reboot. The change is low risk and reversible.	Disables kexec fast reboot capability; May affect tools that rely on kexec (e.g., crash dump utilities)
sysctl_kernel_unprivileged_bpf_disabled	sysctl_kernel_unprivileged_bpf_disabled	Disable Access to Network bpf() Syscall From Unprivileged Processes	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only involves adding a sysctl entry and commenting out any existing conflicting entries, which is a standard, low impact configuration change. It does not affect authentication, authorization, bootloader, or filesystem layout, and does not require a reboot. The change is unlikely to cause lockout or critical service failure.	Potential breakage of applications that rely on unprivileged BPF (e.g., container runtimes, tracing tools)
sysctl_kernel_yama_ptrace_scope	sysctl_kernel_yama_ptrace_scope	Restrict usage of ptrace to descendant processes	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits or adds a sysctl configuration line to set kernel.yama_ptrace_scope=1. This change does not affect authentication, networking, or filesystem layout and does not require a reboot. It follows standard STIG sysctl persistence practices, so it is low risk and safe to apply automatically.	May limit debugging tools that rely on ptrace; Incorrect syntax could cause sysctl parsing errors
sysctl_net_core_bpf_jit_harden	sysctl_net_core_bpf_jit_harden	Harden the operation of the BPF just-in-time compiler	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only involves adding or updating a sysctl entry to set net.core.bpf_jit_harden=2 and commenting out any conflicting entries. This is a standard, low impact configuration change that does not affect authentication, SSH access, or critical services, and it can be applied without a reboot.	networking affected; Potential change in BPF JIT performance; May affect applications that rely on BPF JIT optimizations
sysctl_user_max_user_namespaces_no_remediation	sysctl_user_max_user_namespaces_no_remediation	Disable the use of user namespaces	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation consists of adding a simple sysctl configuration line and applying it at runtime. This does not affect authentication, networking, or filesystem layout, and it does not require a reboot. The only risk is that disabling user namespaces may impact container workloads, which can be evaluated after the change.	Potential disruption of container runtimes that rely on user namespaces; Possible incompatibility with applications expecting non-zero namespace limits

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
service_systemd-coredump_disabled	service_systemd-coredump_disabled	Disable acquiring, saving, and processing core dumps	Medium	FAIL	localhost	localhost.localdomain	LOW	Masking the systemd-coredump.socket simply disables core dump processing. It does not affect authentication, networking, or critical system services, and the remediation consists of a single systemctl command, making it low risk and reversible.	Loss of core dump data for postmortem debugging; Potential interruption of any currently running core dump processing
coredump_disable_backtraces	coredump_disable_backtraces	Disable core dump backtraces	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits or creates a systemd configuration file to set ProcessSizeMax=0, which disables backtrace generation for large core dumps. This is a straightforward file edit that does not affect authentication, networking, or critical services, and does not require a reboot. The change follows standard STIG hardening practices and poses minimal risk.	filesystems affected
coredump_disable_storage	coredump_disable_storage	Disable storing core dump	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits or creates a systemd drop-in file to set Storage=none, which disables core dump files. This change does not affect authentication, networking, or boot configuration, and it carries minimal risk of service disruption. The operation is straightforward and can be applied without reboot.	filesystems affected; Loss of core dump files for postmortem debugging; Potential mis-syntax in the edited configuration could prevent systemd-coredump from starting
disable_users_coredumps	disable_users_coredumps	Disable Core Dumps for All Users	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only modifies PAM limits configuration (limits.conf or a drop-in file) to set '* hard core 0'. This is a standard STIG hardening step, does not affect authentication mechanisms, networking, or filesystem layout, and does not require a reboot. The change is low risk and easily reversible.	authentication/authorization affected; Disables core dump generation, which may hinder postmortem debugging; Potential conflict with existing custom limits files
sysctl_kernel_randomize_va_space	sysctl_kernel_randomize_va_space	Enable Randomized Layout of Virtual Address Space	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits or adds a sysctl configuration line to set kernel.randomize_va_space=2, which is a standard STIG hardening action. It does not affect authentication, networking, or filesystem layout and does not require a reboot. The change is low risk and aligns with policy for safe sysctl persistence.	possible incompatibility with legacy applications that rely on disabled ASLR

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
package_policycoreutils-python-utils_installed	package_policycoreutils-python-utils_installed	Install policycoreutils-python-utils package	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only installs a standard SELinux utility package via dnf. This operation is low risk, does not modify authentication, networking, or filesystem layouts, and is unlikely to cause lockout or service disruption.	—
service_kdump_disabled	service_kdump_disabled	Disable KDump Kernel Crash Analyzer (kdump)	Medium	FAIL	localhost	localhost.localdomain	LOW	Disabling the kdump service is a straightforward service mask/disable operation that does not affect authentication, networking, or filesystem layout. The remediation script uses standard systemctl commands and poses no risk of locking out SSH or breaking critical system functionality. The change is reversible and does not require a reboot to apply.	Loss of kernel crash dump capability for post-mortem analysis; Potential impact on troubleshooting future kernel crashes
file_permissions_cron_d	file_permissions_cron_d	Verify Permissions on cron.d	Medium	FAIL	localhost	localhost.localdomain	LOW	Changing directory permissions to 0700 is a standard STIG hardening step that does not affect authentication, networking, or critical services. The remediation is a simple chmod operation, posing minimal risk of lockout or system breakage.	filesystems affected
file_permissions_cron_daily	file_permissions_cron_daily	Verify Permissions on cron.daily	Medium	FAIL	localhost	localhost.localdomain	LOW	Changing the directory permissions of /etc/cron.daily to 0700 is a standard STIG hardening step that does not affect authentication, networking, or critical services. The remediation is a single chmod command, low risk of lockout or system breakage.	filesystems affected; Improper permissions could allow non-privileged users to add or modify cron jobs; Potential for unauthorized script execution
file_permissions_cron_hourly	file_permissions_cron_hourly	Verify Permissions on cron.hourly	Medium	FAIL	localhost	localhost.localdomain	LOW	Changing the permissions of /etc/cron.hourly to 0700 is a straightforward file permission adjustment that does not affect authentication mechanisms, networking, or critical services. The impact is limited to the cron.hourly directory, and the fix is well-documented in the STIG guidance.	filesystems affected; If permissions are set too restrictively, legitimate cron.hourly jobs may fail to execute

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
file_permissions_cron_monthly	file_permissions_cron_monthly	Verify Permissions on cron.monthly	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only changes the mode of /etc/cron.monthly to 0700, a straightforward file permission adjustment that does not affect authentication, networking, or critical services. Such changes are standard STIG hardening actions and carry minimal risk of lockout or system breakage.	filesystems affected; Incorrect permissions may prevent legitimate cron scripts from executing if they rely on broader access
file_permissions_cron_weekly	file_permissions_cron_weekly	Verify Permissions on cron.weekly	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only changes directory permissions on /etc/cron.weekly, a standard STIG hardening step. It does not affect authentication, networking, or critical services, and the change is reversible. Therefore it is safe to apply automatically.	filesystems affected; Improper permissions could allow unauthorized users to add or modify scheduled tasks
package_fapolicyd_installed	package_fapolicyd_installed	Install fapolicyd Package	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation consists of installing the fapolicyd package, which is a standard, low-risk operation that does not affect authentication, networking, or critical services. Package installation is explicitly listed as safe_to_remediate in the policy.	—
service_fapolicyd_enabled	service_fapolicyd_enabled	Enable the File Access Policy Service	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling the fapolicyd service is a straightforward service enablement that does not modify authentication mechanisms, networking, or critical boot components. The remediation script uses standard systemctl commands and poses minimal risk of lockout or system breakage.	—
package_postfix_installed	package_postfix_installed	The Postfix package is installed	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the postfix package is a straightforward package installation that does not affect authentication, authorization, or critical system services. The remediation script simply installs the package if absent, posing minimal risk of lockout or system breakage.	networking affected; Enabling a mail service may expose the system to network traffic if not properly configured; Potential for misuse if the mail server is left open to the internet

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
package_s-nail_installed	package_s-nail_installed	The s-nail Package Is Installed	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only installs the s-nail package, which is a standard mail client. Installing a package does not modify authentication, authorization, networking, or critical filesystem configurations, and it does not require a reboot. Therefore the fix is low risk and can be applied automatically.	adds additional software to the system, slightly increasing the attack surface
postfix_client_config_mail_alias	postfix_client_config_mail_alias	Configure System to Forward All Mail For The Root Account	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits /etc/aliases and runs newaliases, which are standard, low-impact operations that do not affect authentication, SSH access, or critical system services. The change is straightforward and reversible.	filesystems affected; Incorrect or unreachable email address could cause loss of root mail notifications; Potential temporary mail delivery interruption until newaliases is run
chronyd_or_ntpd_set_maxpoll	chronyd_or_ntpd_set_maxpoll	Configure Time Service Maxpoll Interval	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits NTP/Chrony configuration files to set a maxpoll value, which is a straightforward, low-impact change. It does not affect authentication, bootloader, or filesystem layout, and the risk of losing access is minimal.	networking affected; filesystems affected; Potential temporary loss of time synchronization if syntax is incorrect; Service restart may briefly interrupt time service
chronyd_server_directive	chronyd_server_directive	Ensure Chrony is only configured with the server directive	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only requires editing /etc/chrony.conf to remove non-server time source directives and restarting the chronyd service. This does not affect authentication, bootloader, or critical filesystem layout, and the change is reversible if time sync issues arise.	networking affected; filesystems affected; Potential loss of accurate time synchronization if server directive is misconfigured; Service restart may temporarily interrupt time service
disable_host_auth	disable_host_auth	Disable Host-Based Authentication	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adds an explicit 'HostbasedAuthentication no' line to an SSH configuration drop-in. This follows standard STIG hardening, does not change authentication mechanisms, and the default is already disabled, so the risk of lockout is minimal.	authentication/authorization affected; Potential syntax error in sshd_config causing sshd to fail to start; If the drop-in file is not correctly placed, the setting may be ignored

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
sshd_disable_compression	sshd_disable_compression	Disable Compression Or Set Compression to delayed	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits SSH daemon configuration to disable or delay compression, a standard STIG hardening step. It does not modify authentication mechanisms, kernel parameters, or filesystem layouts, and the change can be applied without reboot. Risk of temporary SSH disconnect exists but can be mitigated with a backup and verification step.	authentication/authorization affected; Potential temporary loss of SSH connectivity during service restart; Misconfiguration could prevent SSH daemon from starting
sshd_disable_gssapi_auth	sshd_disable_gssapi_auth	Disable GSSAPI Authentication	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits SSH daemon configuration to explicitly set GSSAPIAuthentication to no, a common STIG hardening step. It does not affect core system services, partitions, or bootloader settings, and the change can be validated with a simple SSH connection test before and after a service restart.	authentication/authorization affected; Disabling GSSAPI may prevent legitimate GSSAPI/Kerberos logins if they are in use; Requires sshd restart, which could temporarily interrupt active SSH sessions
sshd_disable_rhosts	sshd_disable_rhosts	Disable SSH Support for .rhosts Files	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only ensures the SSH daemon configuration explicitly disables .rhosts support, which is already the default. This change does not affect service availability or authentication mechanisms beyond tightening security, and it follows standard STIG hardening patterns.	authentication/authorization affected
sshd_disable_user_known_hosts	sshd_disable_user_known_hosts	Disable SSH Support for User Known Hosts	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adds a standard SSH daemon configuration directive (IgnoreUserKnownHosts yes) and ensures the file exists with correct permissions. This change follows typical STIG hardening, does not affect boot or filesystem layout, and only requires an sshd reload, posing minimal risk of lockout.	authentication/authorization affected

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
sshd_do_not_permit_user_env	sshd_do_not_permit_user_env	Do Not Allow SSH Environment Options	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits SSH daemon configuration to disable PermitUserEnvironment, a standard STIG hardening step. It involves simple file edits and a service restart, with minimal risk of system breakage. While there is a remote lockout risk if the config syntax is invalid, this can be mitigated by testing the config before applying.	authentication/authorization affected; Potential SSH service disruption if configuration syntax is incorrect; Remote lockout if changes are applied without validation
sshd_enable_pubkey_auth	sshd_enable_pubkey_auth	Enable Public Key Authentication	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adds or ensures a line in an SSH daemon configuration fragment to explicitly enable PubkeyAuthentication, which is the default behavior. This is a standard, low-risk SSH hardening change and does not modify critical system services or filesystems.	authentication/authorization affected; Potential mis-typed configuration could affect SSH login; If the SSH service fails to restart, remote access could be temporarily unavailable
sshd_enable_strictmodes	sshd_enable_strictmodes	Enable Use of Strict Mode Checking	Medium	FAIL	localhost	localhost.localdomain	LOW	StrictModes is already enabled by default in the SSH daemon. Adding an explicit 'StrictModes yes' line follows standard STIG hardening practices and does not alter authentication mechanisms or service behavior, making remediation low risk.	authentication/authorization affected
sshd_print_last_log	sshd_print_last_log	Enable SSH Print Last Log	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling PrintLastLog only adds a harmless informational line to the SSH banner. The default behavior already prints the last login, and the remediation merely ensures the setting is explicitly present. No risk of SSH lockout or service disruption.	authentication/authorization affected
sshd_rekey_limit	sshd_rekey_limit	Force frequent session key renegotiation	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits or creates an SSH daemon configuration file to set RekeyLimit, a standard hardening parameter. This change does not affect boot, kernel, or filesystem layout and is unlikely to cause loss of access if applied carefully.	authentication/authorization affected; potential temporary loss of SSH connectivity if the new config contains syntax errors; requires a running SSH session to apply the change

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
sshd_set_loglevel_verbose	sshd_set_loglevel_verbose	Set SSH Daemon LogLevel to VERBOSE	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits or creates a small SSH configuration fragment to set LogLevel VERBOSE, a standard STIG recommendation. It does not modify authentication mechanisms, kernel parameters, or boot-critical files, and the change is unlikely to cause lockout. A service restart may be needed but poses minimal risk.	authentication/authorization affected; Service restart may briefly interrupt active SSH sessions; Incorrect syntax could prevent sshd from starting
package_usbguard_installed	package_usbguard_installed	Install usbguard Package	Medium	FAIL	localhost	localhost.localdomain	LOW	Installing the usbguard package is a standard, low-impact remediation that does not modify authentication, networking, or filesystem structures and does not require a reboot. The provided script safely checks platform applicability before installing.	—
service_usbguard_enabled	service_usbguard_enabled	Enable the USBGuard Service	Medium	FAIL	localhost	localhost.localdomain	LOW	Enabling the usbguard.service is a straightforward service enablement that does not affect SSH, console access, or critical system components. The remediation script only unmask, starts, and enables the service, which is low risk and aligns with STIG guidance.	—
package_audispd-plugins_installed	package_audispd-plugins_installed	Install audispd-plugins Package	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only installs the audispd-plugins package, which is a standard, non-disruptive operation that does not affect authentication, networking, or critical system services.	—
audit_rules_etc_cron_d	audit_rules_etc_cron_d	Ensure auditd Collects Changes to Cron Jobs - /etc/cron.d/	Medium	FAIL	localhost	localhost.localdomain	LOW	Adding an audit rule for /etc/cron.d/ is a standard STIG remediation that does not affect authentication, networking, or boot processes and carries minimal risk of system disruption.	—
audit_rules_immutable	audit_rules_immutable	Make the auditd Configuration Immutable	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adds the '-e 2' rule to the audit configuration, making the auditd rules immutable. This is a standard STIG audit rule change, does not affect authentication, networking, or filesystem layout, and is unlikely to cause lockout or service disruption. The change may require a service restart or later reboot to modify rules, but applying it is safe.	Requires auditd restart or future reboot to modify rules; Potential loss of ability to change audit rules without reboot

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
audit_rules_sudoers	audit_rules_sudoers	Ensure auditd Collects System Administrator Actions - /etc/sudoers	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adds a standard audit rule to monitor changes to /etc/sudoers. This is a typical STIG audit configuration change that does not affect authentication, networking, or filesystem layout and is unlikely to cause lockout or service disruption.	—
audit_rules_sudoers_d	audit_rules_sudoers_d	Ensure auditd Collects System Administrator Actions - /etc/sudoers.d/	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adds a watch rule for /etc/sudoers.d/ to the audit subsystem. This does not modify authentication mechanisms, services, or system boot configuration, and it will not cause loss of SSH or console access. Adding audit rules is explicitly listed as safe to remediate in the policy.	authentication/authorization affected
audit_rules_suid_privilege_function	audit_rules_suid_privilege_function	Record Events When Privileged Executables Are Run	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adds or corrects audit rules for execve syscalls on both 32- and 64-bit architectures. This is a standard STIG audit configuration change that does not affect authentication, networking, or critical services and does not require a reboot.	—
audit_rules_system_shutdown	audit_rules_system_shutdown	Shutdown System When Auditing Failures Occur	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adds or updates the '-f' audit failure mode line in audit rule files. This is a standard STIG audit rule change, does not affect authentication, networking, or critical services, and can be applied with a simple file edit and auditd restart.	system will halt on audit failure (intended behavior)
audit_rules_usergroup_modification_group	audit_rules_usergroup_modification_group	Record Events that Modify User/Group Information - /etc/group	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adds a standard audit rule for monitoring changes to /etc/group. This is a typical STIG requirement, does not affect authentication, networking, or critical services, and is unlikely to cause lockout or system breakage.	filesystems affected
audit_rules_usergroup_modification_gshadow	audit_rules_usergroup_modification_gshadow	Record Events that Modify User/Group Information - /etc/gshadow	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adds a standard audit rule to monitor writes and attribute changes on /etc/gshadow. This follows typical STIG audit rule patterns, does not modify authentication mechanisms, and is unlikely to cause lockout or service disruption.	authentication/authorization affected; Potential audit daemon failure if syntax is incorrect; Increased audit log volume

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
accounts_passwords_pam_faillock_deny	accounts_passwords_pam_faillock_deny	Lock Accounts After Failed Password Attempts	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation modifies PAM configuration using authselect or controlled edits to enable pam_faillock, a standard STIG hardening measure. While misconfiguration could lock out accounts, the process is well documented and low impact, fitting the safe_to_remediate policy.	authentication/authorization affected; Potential account lockout if deny count is set incorrectly; Possible loss of SSH access if PAM changes are applied incorrectly
accounts_passwords_pam_faillock_unlock_time	accounts_passwords_pam_faillock_unlock_time	Set Lockout Time for Failed Password Attempts	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only modifies PAM configuration (faillock settings) using the standard authselect workflow. This is a typical STIG hardening step and does not involve kernel, bootloader, or filesystem changes. While an incorrect unlock_time could temporarily lock accounts, the risk is manageable with proper testing and backup.	authentication/authorization affected; Potential account lockout if unlock_time is set to 0 or mistyped; Possible loss of SSH access if PAM stack becomes invalid
file_permissions_user_init_files_root	file_permission_user_init_files_root	Ensure All User Initialization Files Have Mode 0740 Or Less Permissive	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only adjusts file permissions on user initialization files (e.g., .bashrc, .profile). This is a standard STIG hardening step, does not modify authentication mechanisms, bootloader, or networking, and is unlikely to lock out users. The change can be applied without a reboot.	filesystems affected; Potential for user environment scripts to lose execute permission if they rely on group/other execution bits; Incorrect regex may miss some init files, leaving them noncompliant
rsyslog_encrypt_offload_action_sendstream_driver_authmode	rsyslog_encrypt_offload_action_sendstream_driver_authmode	Ensure Rsyslog Authenticates Off-Loaded Audit Records	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits rsyslog configuration files to set or remove the StreamDriverAuthMode option and then restarts the rsyslog service. This is a standard STIG hardening step, does not affect authentication mechanisms for local users, and is unlikely to cause lockout or critical service failure if performed correctly.	authentication/authorization affected; networking affected; Potential rsyslog service disruption if syntax error introduced; Loss of remote audit log forwarding until service is verified

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
rsyslog_encrypt_offload_actionstreamdrivermode	rsyslog_encrypt_offload_actionstreamdrivermode	Ensure Rsyslog Encrypts Off-Loaded Audit Records	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only edits rsyslog configuration files to enable encrypted offload of audit logs. This is a standard STIG hardening step, does not affect authentication, boot process, or critical system services, and can be rolled back easily. The risk is limited to potential loss of logging if the syntax is incorrect, which can be mitigated by testing the config before restart.	networking affected; Potential rsyslog service failure if configuration syntax is wrong; Loss of remote audit log collection until corrected
rsyslog_encrypt_offload_defaultnetstreamdriver	rsyslog_encrypt_offload_defaultnetstreamdriver	Ensure Rsyslog Encrypts Off-Loaded Audit Records	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation only modifies rsyslog configuration to enable TLS encryption for remote log forwarding. This change does not affect authentication, boot process, or critical system partitions, and can be applied and validated without risking loss of SSH or console access. The impact is limited to logging service behavior, which can be rolled back if needed.	networking affected; filesystems affected; Potential loss of logging if configuration syntax is incorrect; Remote log server connectivity issues may cause log delivery failures; Service restart may temporarily pause log collection
fapolicy_default_deny	fapolicy_default_deny	Configure Fapolicy Module to Employ a Deny-all, Permit-by-exception Policy to Allow the Execution of Authorized Software Programs.	Medium	FAIL	localhost	localhost.localdomain	MEDIUM	The remediation enforces a deny-all execution policy for fapolicyd, which can prevent essential binaries (including SSH, system services, and console utilities) from running unless explicit allow rules are added. This poses a clear risk of losing remote access or breaking critical services, necessitating human review to tailor exceptions before applying.	potential loss of SSH/console access; disruption of critical system services; need for custom allow rules; possible system instability if applied without testing
usbguard_generate_policy	usbguard_generate_policy	Generate USBGuard Policy	Medium	FAIL	localhost	localhost.localdomain	LOW	The remediation creates a policy file based on currently connected USB devices and restarts the usbguard service. This follows standard STIG patterns for service enablement and file permission changes, and the script includes safeguards for systems without USB devices. While there is a minor risk of locking out USB input devices on systems that rely on them, the overall impact is low and the fix is unlikely to cause system breakage.	filesystems affected; Potential loss of USB input devices if no devices are present during policy generation; Service restart may temporarily affect USBGuard functionality

Too Dangerous to Remediate (18)

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
enable_dracut_fips_module	enable_dracut_fips_module	Enable Dracut FIPS Module	High	FAIL	localhost	localhost.localdomain	CRITICAL	Enabling FIPS mode requires adding the dracut fips module and setting the kernel boot parameter fips=1, which involves bootloader/kernel changes. The policy states FIPS changes are classified as too dangerous to remediate on an existing system because they can cause system lockout or break critical services and are not supported on already installed systems.	reboot required; FIPS mode activation; bootloader modification; kernel parameter change; potential system lockout
enable_fips_mode	enable_fips_mode	Enable FIPS Mode	High	FAIL	localhost	localhost.localdomain	CRITICAL	Enabling FIPS mode requires adding a kernel boot parameter (fips=1) and changing the system cryptographic policy. The documentation states that enabling FIPS on an already installed system is not supported and can render the system unbootable. This poses a high risk of system breakage and loss of access, matching the policy rule that FIPS changes are classified as too dangerous to remediate automatically.	reboot required; potential boot failure; system may become unbootable; cryptographic policy changes could affect services; possible loss of SSH/console access
fips_crypto_subpolicy	fips_crypto_subpolicy	FIPS Must Use a Supported Subpolicy	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	The finding requires changing the system's FIPS crypto subpolicy, which is a FIPS-related configuration. According to policy, FIPS changes are classified as too_dangerous_to_remediate because they can impact system-wide cryptographic behavior and may break critical services or authentication mechanisms.	authentication/authorization affected; networking affected; Potential disruption of services that rely on specific cryptographic algorithms; Possible loss of SSH or other network connectivity if incompatible ciphers are enforced; Compliance impact if an unsupported subpolicy is applied

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
fips_custom_stig_sub_policy	fips_custom_stig_sub_policy	Implement STIG Sub Crypto Policy	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	The remediation changes the system-wide cryptographic policy to FIPS:STIG, which is a FIPS mode alteration. Such changes can break existing services, including SSH, and may cause system lockout or require extensive validation, matching the policy's criteria for 'too_dangerous_to_remediate' for FIPS changes.	authentication/authorization affected; Potential SSH cipher incompatibility leading to remote lockout; Breakage of services relying on non-FIPS algorithms; Compliance impact if FIPS mode is not fully supported
sysctl_crypto_fips_enabled	sysctl_crypto_fips_enabled	Set kernel parameter 'crypto.fips_enabled' to 1	High	FAIL	localhost	localhost.localdomain	CRITICAL	Enabling FIPS mode requires adding the fips=1 boot parameter, which modifies the bootloader configuration and forces the kernel to operate in FIPS mode. This change is not supported on an already installed system and can render the system unbootable or break cryptographic operations, making remediation high risk.	reboot required; authentication/authorization affected; Potential system boot failure; Loss of cryptographic functionality; Possible lockout of authentication mechanisms; Incompatibility with existing software
partition_for_var_tmp	partition_for_var_tmp	Ensure /var/tmp Located On Separate Partition	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	Filesystem/partition/mount-option changes can break boot or services and should not be auto-remediated.	reboot required; filesystems affected; filesystems/partitioning; service disruption risk
grub2_init_on_free	grub2_init_on_free	The system must booted with init_on_free=1	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	The remediation modifies the bootloader configuration to add a kernel parameter (init_on_free=1). Bootloader changes can prevent the system from booting if the parameter is unsupported or incorrectly applied, potentially causing loss of SSH/console access. Policy classifies bootloader/kernel parameter changes as too dangerous to remediate automatically.	reboot required; Potential boot failure; Kernel incompatibility with init_on_free; Loss of remote access if system fails to boot

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
grub2_vsycall_argument	grub2_vsycall_argument	Disable vsyscalls	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	The remediation modifies the GRUB2 kernel command line (or bootc kargs) to add vsyscall=none, which is a bootloader configuration change. Incorrect edits can render the system unbootable or break legacy applications that rely on vsyscall. Because of the high risk of loss of console/SSH access and potential system breakage, the fix is classified as too dangerous to apply automatically.	reboot required; bootloader configuration change; kernel compatibility issues; potential unbootable system; possible disruption of legacy binaries
grub2_admin_username	grub2_admin_username	Set the Boot Loader Admin Username to a Non-Default Value	High	FAIL	localhost	localhost.localdomain	CRITICAL	The remediation requires editing the GRUB2 boot loader configuration and regenerating the boot menu. An incorrect change can render the system unbootable or lock out console access, which matches the policy's definition of bootloader changes that are too risky to automate.	reboot required; authentication/authorization affected; bootloader misconfiguration; potential loss of console/SSH access; system may fail to boot
grub2_password	grub2_password	Set Boot Loader Password in grub2	High	FAIL	localhost	localhost.localdomain	CRITICAL	Setting a GRUB2 boot loader password modifies the bootloader configuration. An incorrect password or misconfiguration can prevent the system from booting, resulting in loss of console access and requiring physical intervention. The policy explicitly classifies bootloader changes as too dangerous to remediate automatically.	reboot required; authentication/authorization affected; Potential boot lockout if password is mistyped; Loss of remote console/SSH access until physical access is obtained; System may become unbootable after updates if GRUB configuration is corrupted
mount_option_boot_efi_nosuid	mount_option_boot_efi_nosuid	Add nosuid Option to /boot/efi	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	Modifying the mount options for the /boot/efi partition alters the system's boot filesystem. An error in /etc/fstab can prevent the EFI system partition from mounting, leading to an unbootable system. Because this change touches a critical boot component, it is considered too risky to automate without direct human oversight.	reboot required; filesystems affected; Potential boot failure if fstab syntax is incorrect; Inability to mount EFI system partition; Loss of console or remote access during reboot

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
mount_option_boot_nodev	mount_option_boot_nodev	Add nodev Option to /boot	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	Modifying the mount options for the /boot partition directly impacts the boot process. An incorrect fstab entry or missing /boot definition can render the system unbootable, requiring physical console access for recovery. Because this is a filesystem/bootloader related change, it is classified as too dangerous to remediate automatically.	reboot required; filesystems affected; potential boot failure; system may become unbootable; loss of remote access until physical console is used
mount_option_boot_nosuid	mount_option_boot_nosuid	Add nosuid Option to /boot	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	Modifying the mount options of the /boot partition directly impacts the boot filesystem. While adding nosuid is generally safe, any change to /boot can prevent the system from booting if the fstab entry becomes invalid or the kernel cannot mount the partition, posing a high risk of system unavailability.	reboot required; filesystems affected; boot partition modification; potential fstab syntax error; possible boot failure
mount_option_dev_shm_noexec	mount_option_dev_shm_noexec	Add noexec Option to /dev/shm	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	The remediation modifies /etc/fstab to add a mount option for /dev/shm, which is a filesystem configuration change. Such changes can affect system boot and may break applications that rely on executing binaries from /dev/shm. According to policy, filesystem/partitioning changes are classified as too dangerous to remediate automatically.	reboot required; filesystems affected; Potential service disruption if applications depend on exec from /dev/shm; Requires reboot to apply persistent change; Incorrect fstab entry could prevent system from booting
mount_option_home_noexec	mount_option_home_noexec	Add noexec Option to /home	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	Modifying the mount options for /home changes the filesystem behavior. Adding the noexec flag can break legitimate user executables and scripts, potentially impacting services that rely on executing binaries from /home. Such partitioning changes require careful validation and may need a reboot, so automated remediation is not advisable.	reboot required; filesystems affected; possible breakage of user applications; need for system reboot to apply change; potential loss of functionality for services using /home

ID	Rule	Title	Severity	Result	Host	OS	Risk	Reason	Impact
mount_option_home_nosuid	mount_option_home_nosuid	Add nosuid Option to /home	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	Modifying /etc/fstab to add the nosuid option changes filesystem mount behavior. An incorrect entry can prevent the system from booting or cause loss of setuid functionality for applications in /home, which may break user workflows. Because this is a filesystem/partitioning change, the policy classifies it as too dangerous to remediate automatically.	reboot required; filesystems affected; Potential boot failure if fstab syntax is incorrect; Loss of setuid/sgid binaries in /home may break applications; Requires reboot to apply the change
mount_option_nodev_nonroot_local_partitions	mount_option_nodev_nonroot_local_partitions	Add nodev Option to Non-Root Local Partitions	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	The remediation modifies mount options for non-root local partitions, which is a filesystem configuration change. Adjusting mount options can cause services that rely on device files on those partitions to fail, and may require a reboot to take effect. Per policy, such partitioning/filesystem changes are classified as too dangerous to remediate automatically.	reboot required; filesystems affected; Potential service disruption if device files are needed on affected partitions; Possible boot or mount failures if fstab syntax is incorrect; Requires system reboot to apply changes
grub2_page_poison_argument	grub2_page_poison_argument	Enable page allocator poisoning	Medium	FAIL	localhost	localhost.localdomain	CRITICAL	The remediation modifies the bootloader configuration and kernel command line, which can prevent the system from booting if the kernel does not support the page_poison parameter or if the GRUB configuration is corrupted. Such changes are classified as bootloader modifications and carry a high risk of boot failure, thus requiring human oversight.	reboot required; bootloader configuration change; kernel parameter incompatibility; potential loss of console/SSH access; requires system reboot