

OpenSCAP Multi-Agent Pipeline Report

Target: 192.168.64.15 | Generated: 2026-04-12 22:28:12

Models Used

Triage	openai/gpt-oss-20b
Remedy	openai/gpt-oss-20b
Review	openai/gpt-oss-20b
Qa	openai/gpt-oss-20b

Pipeline Summary

Total Findings Processed	150
Remediated Successfully	89
Failed Remediation	37
Requires Human Review	14
Discarded / Blocked	10
Success Rate	59.3%
Total Duration	12000.3s

LLM Usage (Aggregate)

Total LLM Calls	1699
Total Errors	0

Total LLM Duration	9824.5s
Prompt Tokens	4,233,502
Completion Tokens	1,002,796
Total Tokens	5,236,298
Estimated Cost (USD)	\$0.2939

LLM Usage by Agent

Agent	Calls	Errors	Duration (s)	Prompt Tok	Compl Tok	Total Tok	Cost (USD)
Triage	88	0	314.0	71,262	37,572	108,834	\$0.0098
Remedy	1346	0	7879.2	3,844,543	766,812	4,611,355	\$0.2296
Review	139	0	1043.1	165,807	126,134	291,941	\$0.0327
Qa	126	0	588.2	151,890	72,278	224,168	\$0.0217

Remediated Successfully (89)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
package_aide_installed	Install AIDE	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	131.8s	10
aide_build_database	Build and Test AIDE Database	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	266.7s	17
package_gnutls-utils_installed	Ensure gnutls-utils is installed	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	140.2s	14
package_nss-tools_installed	Ensure nss-tools is installed	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	76.3s	11
package_subscription-manager_installed	Install subscription-manager Package	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	115.8s	10

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
ensure_gpgcheck_local_packages	Ensure gpgcheck Enabled for Local Packages	High	Remediate	LOW	1	Pass	Approved (8/10)	✓	89.2s	15
enable_authselect	Enable authselect	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	75.8s	16
accounts_password_pam_dcredit	Ensure PAM Enforces Password Requirements - Minimu...	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	178.9s	11
accounts_password_pam_maxrepeat	Set Password Maximum Consecutive Repeating Charact...	Medium	Remediate	LOW	1	Pass	Approved (None/10)	✓	69.0s	14
accounts_password_pam_pwquality_etry	Ensure PAM Enforces Password Requirements - Authen...	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	63.8s	15
accounts_password_pam_ucredit	Ensure PAM Enforces Password Requirements - Minimu...	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	92.0s	22
disable_ctrlaltdel_burstaction	Disable Ctrl-Alt-Del Burst Action	High	Remediate	LOW	2	Pass	Approved (None/10)	✓	164.3s	14
disable_ctrlaltdel_reboot	Disable Ctrl-Alt-Del Reboot Activation	High	Remediate	LOW	1	Pass	Approved (9/10)	✓	75.7s	13
package_opensc_installed	Install the opensc Package For Multifactor Authent...	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	55.8s	12
package_pcsc-lite_installed	Install the pcsc-lite package	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	35.1s	11
install_smartcard_packages	Install Smart Card Packages For Multifactor Authen...	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	59.4s	10
service_pcscd_enabled	Enable the pcscd Service	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	39.2s	13
account_disable_post_pw_expiration	Set Account Expiration Following Inactivity	Medium	Remediate	LOW	1	Pass	Approved (None/10)	✓	38.2s	13

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
accounts_minimum_age_login_defs	Set Password Minimum Age	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	48.6s	15
accounts_password_set_min_life_existing	Set Existing Passwords Minimum Age	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	46.1s	12
use_pam_wheel_for_su	Enforce usage of pam_wheel for su authentication	Medium	Remediate	LOW	1	Pass	Approved (None/10)	✓	33.4s	12
package_rsyslog-gnutls_installed	Ensure rsyslog-gnutls is installed	Medium	Remediate	LOW	1	Pass	Approved (None/10)	✓	56.4s	11
package_libreswan_installed	Install libreswan Package	Medium	Remediate	LOW	1	Pass	Approved (None/10)	✓	48.9s	10
sysctl_net_ip_v6_conf_all_accept_ra	Configure Accepting Router Advertisements on All I...	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	67.7s	12
sysctl_net_ip_v6_conf_all_accept_redirects	Disable Accepting ICMP Redirects for All IPv6 Inte...	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	196.2s	22
sysctl_net_ip_v6_conf_all_accept_source_route	Disable Kernel Parameter for Accepting Source-Rout...	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	50.9s	12
sysctl_net_ip_v6_conf_all_forwarding	Disable Kernel Parameter for IPv6 Forwarding	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	117.1s	22
sysctl_net_ip_v6_conf_default_accept_ra	Disable Accepting Router Advertisements on all IPv...	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	89.9s	14
sysctl_net_ip_v6_conf_default_accept_redirects	Disable Kernel Parameter for Accepting ICMP Redire...	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	108.3s	15

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
sysctl_net_ip v6_conf_default_accept_source_route	Disable Kernel Parameter for Accepting Source-Rout...	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	278.1s	23
sysctl_net_ip v4_conf_all_accept_redirects	Disable Accepting ICMP Redirects for All IPv4 Inte...	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	67.2s	11
sysctl_net_ip v4_conf_all_accept_source_route	Disable Kernel Parameter for Accepting Source-Rout...	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	151.5s	20
sysctl_net_ip v4_conf_all_rp_filter	Enable Kernel Parameter to Use Reverse Path Filter...	Medium	Remediate	LOW	1	Pass	Approved (None/10)	✓	61.3s	14
sysctl_net_ip v4_conf_default_accept_redirects	Disable Kernel Parameter for Accepting ICMP Redire...	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	63.8s	12
sysctl_net_ip v4_conf_default_rp_filter	Enable Kernel Parameter to Use Reverse Path Filter...	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	51.8s	13
sysctl_net_ip v4_tcp_syncookies	Enable Kernel Parameter to Use TCP Syncookies on N...	Medium	Remediate	LOW	1	Pass	Approved (None/10)	✓	62.8s	20
sysctl_net_ip v4_conf_all_send_redirects	Disable Kernel Parameter for Sending ICMP Redirect...	Medium	Remediate	LOW	1	Pass	Approved (7/10)	✓	124.1s	20
sysctl_net_ip v4_conf_default_send_redirects	Disable Kernel Parameter for Sending ICMP Redirect...	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	38.9s	12
kernel_module_atm_disabled	Disable ATM Support	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	61.8s	12
kernel_module_can_disabled	Disable CAN Support	Medium	Remediate	LOW	1	Pass	Approved (None/10)	✓	36.3s	11

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
kernel_module_sctp_disabled	Disable SCTP Support	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	72.8s	11
kernel_module_bluetooth_disabled	Disable Bluetooth Kernel Module	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	45.1s	11
rootfiles_configured	Ensure rootfiles tmpfile.d is Configured Correctly	Medium	Remediate	LOW	3	Pass	Approved (8/10)	✓	48.7s	9
kernel_module_usb-storage_disabled	Disable Modprobe Loading of USB Storage Driver	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	74.0s	12
mount_option_boot_nodev	Add nodev Option to /boot	Medium	Remediate	LOW	3	Pass	Approved (8/10)	✓	203.8s	18
mount_option_home_noexec	Add noexec Option to /home	Medium	Remediate	LOW	2	Pass	Approved (None/10)	✓	93.8s	18
sysctl_kernel_core_pattern	Disable storing core dumps	Medium	Remediate	LOW	1	Pass	Approved (None/10)	✓	60.7s	14
sysctl_kernel_kexec_load_disabled	Disable Kernel Image Loading	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	153.9s	21
sysctl_kernel_unprivileged_bpf_disabled	Disable Access to Network bpf() Syscall From Unpri...	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	70.8s	14
sysctl_kernel_yama_ptrace_scope	Restrict usage of ptrace to descendant processes	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	37.3s	12
sysctl_net_core_bpf_jit_harden	Harden the operation of the BPF just-in-time compi...	Medium	Remediate	LOW	1	Pass	Approved (None/10)	✓	56.3s	12
sysctl_user_max_user_namespaces_no_remediation	Disable the use of user namespaces	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	47.9s	12

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
service_systemd-coredump_disabled	Disable acquiring, saving, and processing core dumps	Medium	Remediate	LOW	1	Pass	Approved (None/10)	✓	45.4s	12
coredump_disable_backtraces	Disable core dump backtraces	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	153.7s	17
coredump_disable_storage	Disable storing core dump	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	202.2s	20
disable_users_coredumps	Disable Core Dumps for All Users	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	41.5s	13
sysctl_kernel_randomize_va_space	Enable Randomized Layout of Virtual Address Space	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	65.0s	12
package_policycoreutils-python-utils_installed	Install policycoreutils-python-utils package	Medium	Remediate	LOW	2	Pass	Approved (9/10)	✓	70.8s	13
service_kdump_disabled	Disable KDump Kernel Crash Analyzer (kdump)	Medium	Remediate	LOW	2	Pass	Approved (7/10)	✓	46.0s	10
file_permissions_cron_d	Verify Permissions on cron.d	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	24.2s	10
file_permissions_cron_daily	Verify Permissions on cron.daily	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	28.2s	10
file_permissions_cron_hourly	Verify Permissions on cron.hourly	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	48.9s	12
file_permissions_cron_monthly	Verify Permissions on cron.monthly	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	23.1s	11
file_permissions_cron_weekly	Verify Permissions on cron.weekly	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	22.8s	10
package_fapolicyd_installed	Install fapolicyd Package	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	186.3s	16

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
service_fapolicyd_enabled	Enable the File Access Policy Service	Medium	Remediate	LOW	3	Pass	Approved (7/10)	✓	48.3s	11
package_postfix_installed	The Postfix package is installed	Medium	Remediate	LOW	1	Pass	—	—	156.9s	8
package_s-nail_installed	The s-nail Package Is Installed	Medium	Remediate	LOW	2	Pass	Approved (9/10)	✓	147.6s	11
chronyd_or_ntpd_set_maxpoll	Configure Time Service Maxpoll Interval	Medium	Remediate	LOW	2	Pass	Approved (None/10)	✓	177.9s	18
chronyd_server_directive	Ensure Chrony is only configured with the server d...	Medium	Remediate	LOW	1	Pass	Approved (None/10)	✓	90.5s	18
disable_host_auth	Disable Host-Based Authentication	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	134.8s	20
sshd_disable_compression	Disable Compression Or Set Compression to delayed	Medium	Remediate	LOW	1	Pass	Approved (None/10)	✓	92.8s	16
sshd_disable_rhosts	Disable SSH Support for .rhosts Files	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	59.9s	18
sshd_do_not_permit_user_env	Do Not Allow SSH Environment Options	Medium	Remediate	LOW	1	Pass	Approved (None/10)	✓	108.8s	12
sshd_enable_pubkey_auth	Enable Public Key Authentication	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	174.0s	17
sshd_enable_strictmodes	Enable Use of Strict Mode Checking	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	118.0s	21
sshd_print_last_log	Enable SSH Print Last Log	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	79.2s	13
sshd_set_loglevel_verbose	Set SSH Daemon LogLevel to VERBOSE	Medium	Remediate	LOW	3	Pass	Approved (8/10)	✓	113.1s	20
package_usbguard_installed	Install usbguard Package	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	157.2s	12
service_usbguard_enabled	Enable the USBGuard Service	Medium	Remediate	LOW	3	Pass	Approved (8/10)	✓	51.3s	11

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
package_audispd-plugins_installed	Install audispd-plugins Package	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	44.0s	10
audit_rules_etc_cron_d	Ensure auditd Collects Changes to Cron Jobs - /etc...	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	142.9s	16
audit_rules_immutable	Make the auditd Configuration Immutable	Medium	Remediate	LOW	3	Pass	Approved (9/10)	✓	37.1s	12
audit_rules_sudoers	Ensure auditd Collects System Administrator Action...	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	98.1s	21
audit_rules_suid_privilege_function	Record Events When Privileged Executables Are Run	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	57.6s	19
audit_rules_usergroup_modification_group	Record Events that Modify User/Group Information -...	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	97.3s	15
audit_rules_usergroup_modification_gshadow	Record Events that Modify User/Group Information -...	Medium	Remediate	LOW	1	Pass	Approved (7/10)	✓	44.0s	13
audit_rules_usergroup_modification_opasswd	Record Events that Modify User/Group Information -...	Medium	Remediate	LOW	2	Pass	Approved (None/10)	✓	112.0s	19
audit_rules_usergroup_modification_passwd	Record Events that Modify User/Group Information -...	Medium	Remediate	LOW	1	Pass	Approved (9/10)	✓	101.3s	23

Failed Remediation (37)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
aide_check_audit_tools	Configure AIDE to Verify the Audit Tools	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	173.3s	15

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
aide_use_fips_hashes	Configure AIDE to Use FIPS 140-2 for Validating Ha...	Medium	Remediate	LOW	3	Fail	Rejected (None/10)	—	44.1s	2
configure_crypto_policy	Configure System Cryptography Policy	High	Remediate	LOW	3	Fail	Approved (8/10)	✓	161.4s	13
installed_OS_is_vendor_supported	The Installed Operating System Is Vendor Supported	High	Remediate	LOW	3	Fail	Approved (7/10)	✓	232.4s	18
banner_etc_issue	Modify the System Login Banner	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	78.9s	12
account_password_pam_faillock_password_auth	Configure the Use of the pam_faillock.so Module in...	Medium	Remediate	LOW	3	Fail	Approved (None/10)	✓	94.3s	15
accounts_passwords_pam_faillock_interval	Set Interval For Counting Failed Password Attempts	Medium	Remediate	LOW	3	Fail	Approved (7/10)	✓	77.5s	12
accounts_password_pam_dictcheck	Ensure PAM Enforces Password Requirements - Preven...	Medium	Remediate	LOW	3	Fail	Rejected (3/10)	—	46.4s	2
accounts_password_pam_difok	Ensure PAM Enforces Password Requirements - Minimu...	Medium	Remediate	LOW	3	Fail	Rejected (None/10)	—	63.7s	3
accounts_password_pam_enforce_root	Ensure PAM Enforces Password Requirements - Enforc...	Medium	Remediate	LOW	3	Fail	Rejected (None/10)	—	82.5s	2
accounts_password_pam_lcredit	Ensure PAM Enforces Password Requirements - Minimu...	Medium	Remediate	LOW	3	Fail	Rejected (4/10)	—	20.0s	2
accounts_password_pam_maxclassrepeat	Ensure PAM Enforces Password Requirements - Maximu...	Medium	Remediate	LOW	3	Fail	Approved (9/10)	✓	99.1s	21
accounts_password_pam_minclass	Ensure PAM Enforces Password Requirements - Minimu...	Medium	Remediate	LOW	3	Fail	Rejected (3/10)	—	37.0s	2

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
accounts_password_pam_minlen	Ensure PAM Enforces Password Requirements - Minimu...	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	141.1s	20
accounts_password_pam_ocredit	Ensure PAM Enforces Password Requirements - Minimu...	Medium	Remediate	LOW	3	Fail	Approved (None/10)	✓	243.4s	20
configure_opensc_card_drivers	Configure opensc Smart Card Drivers	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	151.2s	16
accounts_maximum_age_login_defs	Set Password Maximum Age	Medium	Remediate	LOW	3	Fail	Rejected (None/10)	—	33.2s	2
accounts_logon_fail_delay	Ensure the Logon Failure Delay is Set Correctly in...	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	68.0s	15
accounts_timeout	Set Interactive Session Timeout	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	39.5s	11
file_permission_user_init_files_root	Ensure All User Initialization Files Have Mode 074...	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	128.8s	15
rsyslog_remote_access_monitoring	Ensure remote access methods are monitored in Rsys...	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	187.4s	15
rsyslog_remote_loghost	Ensure Logs Sent To Remote Host	Medium	Remediate	LOW	3	Fail	Rejected (4/10)	—	10.8s	2
network_configure_name_resolution	Configure Multiple DNS Servers in /etc/resolv.conf	Medium	Remediate	LOW	3	Fail	Rejected (None/10)	—	11.5s	2
sysctl_net_ipv4_conf_all_forwarding	Disable Kernel Parameter for IPv4 Forwarding on al...	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	179.5s	16
mount_option_boot_efi_nosuid	Add nosuid Option to /boot/efi	Medium	Remediate	LOW	3	Fail	Rejected (None/10)	—	42.6s	2
mount_option_boot_nosuid	Add nosuid Option to /boot	Medium	Remediate	LOW	3	Fail	Approved (None/10)	✓	177.8s	23
mount_option_dev_shm_nODEV	Add nodev Option to /dev/shm	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	161.3s	19

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
mount_option_dev_shm_noexec	Add noexec Option to /dev/shm	Medium	Remediate	LOW	3	Fail	Approved (7/10)	✓	103.8s	20
mount_option_dev_shm_nosuid	Add nosuid Option to /dev/shm	Medium	Remediate	LOW	3	Fail	Approved (7/10)	✓	112.7s	21
mount_option_home_nosuid	Add nosuid Option to /home	Medium	Remediate	LOW	3	Fail	Approved (9/10)	✗	27.7s	3
mount_option_nodev_nonroot_local_partitions	Add nodev Option to Non-Root Local Partitions	Medium	Remediate	LOW	3	Fail	Rejected (None/10)	—	24.2s	2
postfix_client_configure_mail_alias	Configure System to Forward All Mail For The Root ...	Medium	Remediate	LOW	3	Fail	Approved (None/10)	✓	53.7s	14
sshd_disable_gssapi_auth	Disable GSSAPI Authentication	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	62.9s	13
sshd_disable_user_known_hosts	Disable SSH Support for User Known Hosts	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	167.7s	17
sshd_rekey_limit	Force frequent session key renegotiation	Medium	Remediate	LOW	3	Fail	Rejected (5/10)	—	45.7s	2
audit_rules_systemd	Ensure auditd Collects System Administrator Action...	Medium	Remediate	LOW	3	Fail	Approved (9/10)	✓	496.0s	15
audit_rules_system_shutdown	Shutdown System When Auditing Failures Occur	Medium	Remediate	LOW	3	Fail	Rejected (5/10)	—	28.0s	2

Requires Human Review (14)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
aide_scan_notification	Configure Notification of Post-AIDE Scan Details	Medium	Human Review	LOW	0	—	—	—	2.3s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
fips_crypto_subpolicy	FIPS Must Use a Supported Subpolicy	Medium	Human Review	LOW	0	—	—	—	6.0s	1
account_password_pam_faillock_system_auth	Configure the Use of the pam_faillock.so Module in...	Medium	Human Review	LOW	0	—	—	—	4.0s	1
accounts_passwords_pam_faillock_deny	Lock Accounts After Failed Password Attempts	Medium	Human Review	LOW	0	—	—	—	2.4s	1
accounts_passwords_pam_faillock_dir	Lock Accounts Must Persist	Medium	Human Review	LOW	0	—	—	—	6.0s	1
accounts_passwords_pam_faillock_unlock_time	Set Lockout Time for Failed Password Attempts	Medium	Human Review	LOW	0	—	—	—	1.9s	1
service_debug-shell_disabled	Disable debug-shell SystemD Service	Medium	Human Review	LOW	0	—	—	—	4.8s	1
rsyslog_encrypt_offload_actionsendstreampdriverauthmode	Ensure Rsyslog Authenticates Off-Loaded Audit Reco...	Medium	Human Review	LOW	0	—	—	—	3.0s	1
rsyslog_encrypt_offload_actionsendstreampdrivermode	Ensure Rsyslog Encrypts Off-Loaded Audit Records	Medium	Human Review	LOW	0	—	—	—	1.9s	1
rsyslog_encrypt_offload_defaultnetstreamdriver	Ensure Rsyslog Encrypts Off-Loaded Audit Records	Medium	Human Review	LOW	0	—	—	—	3.3s	1
sysctl_net_ipv4_icmp_echo_ignore_broadcasts	Enable Kernel Parameter to Ignore ICMP Broadcast E...	Medium	Human Review	LOW	0	—	—	—	1.7s	1
networkmanager_dns_mode	NetworkManager DNS Mode Must Be Must Configured	Medium	Human Review	LOW	0	—	—	—	3.0s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
fapolicy_default_deny	Configure Fapolicy Module to Employ a Deny-all, Pe...	Medium	Human Review	LOW	0	—	—	—	5.2s	1
usbguard_generate_policy	Generate USBGuard Policy	Medium	Human Review	LOW	0	—	—	—	3.7s	1

Discarded / Blocked (10)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
enable_dracut_fips_module	Enable Dracut FIPS Module	High	Blocked	CRITICAL	0	—	—	—	2.4s	1
enable_fips_mode	Enable FIPS Mode	High	Blocked	CRITICAL	0	—	—	—	7.1s	1
fips_custom_stig_sub_policy	Implement STIG Sub Crypto Policy	Medium	Blocked	CRITICAL	0	—	—	—	7.0s	1
sysctl_crypto_fips_enabled	Set kernel parameter 'crypto.fips_enabled' to 1	High	Blocked	CRITICAL	0	—	—	—	2.1s	1
partition_for_var_tmp	Ensure /var/tmp Located On Separate Partition	Medium	Blocked	CRITICAL	0	—	—	—	0.0s	0
grub2_init_on_free	The system must be booted with init_on_free=1	Medium	Blocked	CRITICAL	0	—	—	—	2.8s	1
grub2_vsyscall_argument	Disable vsyscalls	Medium	Blocked	CRITICAL	0	—	—	—	3.8s	1
grub2_admin_username	Set the Boot Loader Admin Username to a Non-Default...	High	Blocked	CRITICAL	0	—	—	—	6.6s	1
grub2_password	Set Boot Loader Password in grub2	High	Blocked	CRITICAL	0	—	—	—	4.7s	1
grub2_page_poison_argument	Enable page allocator poisoning	Medium	Blocked	CRITICAL	0	—	—	—	9.1s	1

Detailed Finding Reports

package_aide_installed: Install AIDE — **SUCCESS**

Rule	package_aide_installed
Severity	Medium
Description	The aide package can be installed with the following command: \$ sudo dnf install aide
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the AIDE package is a standard, low-risk operation that does not affect authentication, networking, or critical system
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	dnf install -y aide
Scan Passed	✓
Success	✓
Duration	128.2s
Error	—

Review Verdict

Approved	✓
----------	---

Optimal	✗
Security Score	9/10
Feedback	Plan will resolve the vulnerability by installing aide if not already installed, with a sensible check for kernel-core presence.
Concerns	No error handling for the dnf install command; if installation fails the plan will silently exit without reporting failure.

QA Result

Safe	✓
Verdict	Installing the aide package using dnf with a simple check for kernel-core presence is a standard, non-destructive operation th
Side Effects	DNF will refresh metadata and may install required dependencies for aide.; A brief yum/dnf lock could prevent other package
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	10
Duration	37.5s
Total Tokens	17,960
Cost	\$0.0011
Agents	Triage(1), Remedy(7), Review(1), Qa(1)

aide_build_database: Build and Test AIDE Database — **SUCCESS**

Rule	aide_build_database
Severity	Medium
Description	Run the following command to generate a new database: \$ sudo /usr/sbin/aide --init By default, the database will be written to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a

Host / OS	localhost / localhost.localdomain
-----------	-----------------------------------

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Initializing and updating the AIDE database is a routine security measure that does not affect authentication, networking, or c
Estimated Impact	filesystems affected

Remediation (1 attempt(s))

Attempt #	1
Commands	rpm -q kernel-core, rpm -q aide, dnf install -y aide, dnf install -y aide, usr/sbin/aide --init
Scan Passed	✓
Success	✓
Duration	265.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly addresses the vulnerability by ensuring the AIDE package is installed, generating a new database, and cop
Concerns	No explicit error handling if aide init fails before the copy step; this could leave the system without a proper database file.

QA Result

Safe	✓
------	---

Verdict	The remediation installs the AIDE package if missing, initializes a new integrity database, and copies it to the expected location.
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	17
Duration	39.0s
Total Tokens	93,964
Cost	\$0.0033
Agents	Triage(1), Remedy(14), Review(1), Qa(1)

aide_check_audit_tools: Configure AIDE to Verify the Audit Tools — **FAILED**

Rule	aide_check_audit_tools
Severity	Medium
Description	The operating system file integrity tool must be configured to protect the integrity of the audit tools.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves installing the AIDE package if missing and adding or updating entries in /etc/aide.conf for audit tools.

Estimated Impact	filesystems affected; audit tool integrity
------------------	--

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	<i>✗</i>
Success	<i>✗</i>
Duration	27.1s
Error	—
Attempt #	2
Commands	—
Scan Passed	<i>✗</i>
Success	<i>✗</i>
Duration	35.3s
Error	—
Attempt #	3
Commands	rpm -q aide, grep -i "auditctl" -n /etc/aide.conf, test -f /usr/sbin/auditctl
Scan Passed	<i>✗</i>
Success	<i>✗</i>
Duration	173.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The proposed plan now includes the missing /usr/sbin/ausearch rule, applies the full set of integrity checks including sha512,
Concerns	Potential accidental loss of unrelated configuration sections if a malformed replace operation misidentifies a line; No explicit

QA Result

Safe	✓
Verdict	The plan installs AIDE if absent, updates /etc/aide.conf with the required audit tool rules in a conservative, existence-checked
Side Effects	Potential inadvertent removal of unrelated configuration lines in /etc/aide.conf if the replace logic mishandles existing entries
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	163.2s
Total Tokens	80,818
Cost	\$0.0046
Agents	Remedy(13), Review(1), Qa(1)

aide_scan_notification: Configure Notification of Post-AIDE Scan Details — **REQUIRES_HUMAN_REVIEW**

Rule	aide_scan_notification
Severity	Medium
Description	AIDE should notify appropriate personnel of the details of a scan after the scan has been run. If AIDE has already been config

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	Adding a cron job to send AIDE scan results via mail is a straightforward configuration change that does not affect authentication
Estimated Impact	—

LLM Metrics

LLM Calls	1
Duration	2.3s
Total Tokens	1,268
Cost	\$0.0001
Agents	Triage(1)

aide_use_fips_hashes: Configure AIDE to Use FIPS 140-2 for Validating Hashes — **FAILED**

Rule	aide_use_fips_hashes
Severity	Medium
Description	By default, the sha512 option is added to the NORMAL ruleset in AIDE. If using a custom ruleset or the sha512 option is missing, the sha512 option is not added, which can lead to false positives.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding sha512 to the AIDE configuration is a straightforward configuration change that does not affect authentication, network
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	11.3s
Error	—
Attempt #	2
Commands	dnf install -y aide, sed -i '/^ALLXTRAHASHES /s/=.*!= sha512/' /etc/aide.conf
Scan Passed	✗
Success	✗
Duration	164.6s
Error	—
Attempt #	3
Commands	—
Scan Passed	✗

Success	<i>✗</i>
Duration	44.1s
Error	—

Review Verdict

Approved	<i>✗</i>
Optimal	<i>✗</i>
Security Score	None/10
Feedback	Review output was not valid JSON. Raw: {"finding_id":"aide_use_fips_hashes","is_optimal":false,"approve":true,"feedback":"T
Concerns	Could not parse LLM response

LLM Metrics

LLM Calls	2
Duration	44.1s
Total Tokens	6,479
Cost	\$0.0006
Agents	Remedy(1), Review(1)

enable_dracut_fips_module: Enable Dracut FIPS Module — DISCARDED

Rule	enable_dracut_fips_module
Severity	High
Description	Red Hat Enterprise Linux 9 has an installation-time kernel flag that can enable FIPS mode. The installer must be booted with
Recommendation	Review and remediate: Enable Dracut FIPS Module
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	<i>✗</i>
Human Review	<i>✗</i>
Risk Level	CRITICAL
Reason	Enabling FIPS mode on a pre-existing RHEL 9 system is unsupported and can render the system inoperable. The rule indicates that the system must be booted with the kernel parameter 'fips=1' to enable FIPS mode.
Estimated Impact	reboot required; authentication/authorization affected; FIPS mode activation; kernel boot parameter change; potential loss of access to the system

LLM Metrics

LLM Calls	1
Duration	2.4s
Total Tokens	1,382
Cost	\$0.0002
Agents	Triage(1)

enable_fips_mode: Enable FIPS Mode — DISCARDED

Rule	enable_fips_mode
Severity	High
Description	Red Hat Enterprise Linux 9 has an installation-time kernel flag that can enable FIPS mode. The installer must be booted with the kernel parameter 'fips=1' to enable FIPS mode.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! (["\${container:-}" == "bwrap-osbuild"]) && rpm --eval "(rpm -q --queryformat '%{NAME} %{VERSION} %{ARCH} %{EPOCH} %{RELEASE} %{SOURCE}' --whatprovides 'libfips.so.1' grep -q 'fips-1.0.0-1.el9.x86_64')) { echo 'FIPS mode is not supported on this platform.'; exit 1; }
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	<i>✗</i>
Human Review	<i>✗</i>

Risk Level	CRITICAL
Reason	Enabling FIPS mode requires a kernel boot parameter (fips=1) and is not supported on an existing system; attempting to rem
Estimated Impact	reboot required; FIPS mode change; kernel boot parameter alteration; potential system instability; permanent finding on insta

LLM Metrics

LLM Calls	1
Duration	7.1s
Total Tokens	1,355
Cost	\$0.0001
Agents	Triage(1)

fips_crypto_subpolicy: FIPS Must Use a Supported Subpolicy — *REQUIRES_HUMAN_REVIEW*

Rule	fips_crypto_subpolicy
Severity	Medium
Description	Sub-policies can be used to modify existing crypto policies. Some sub-policies such as NO-ENFORCE-EMS reduce the secu
Recommendation	Review and remediate: FIPS Must Use a Supported Subpolicy
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The rule requires the system to use one of the allowed crypto subpolicies (OSPP, NO-SHA1, NO-CAMELLIA, ECDHE-ONLY,
Estimated Impact	authentication/authorization affected; networking affected; Potential temporary loss of SSH connectivity if the new subpolicy o

LLM Metrics

LLM Calls	1
Duration	6.0s
Total Tokens	2,043
Cost	\$0.0003
Agents	Triage(1)

fips_custom_stig_sub_policy: Implement STIG Sub Crypto Policy — DISCARDED

Rule	fips_custom_stig_sub_policy
Severity	Medium
Description	Create a custom cryptographic policy to follow the guidance from DISA.
Recommendation	Remediation script: cat << 'EOF' > /etc/crypto-policies/policies/modules/STIG.pmod cipher@SSH=AES-256-GCM AES-256-C
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Enabling FIPS mode via a custom crypto policy can lock out services, break compatibility, and may require a reboot. The poli
Estimated Impact	reboot required; authentication/authorization affected; networking affected; FIPS mode activation; SSH cipher changes; poten

LLM Metrics

LLM Calls	1
Duration	7.0s

Total Tokens	1,406
Cost	\$0.0002
Agents	Triage(1)

sysctl_crypto_fips_enabled: Set kernel parameter 'crypto.fips_enabled' to 1 — DISCARDED

Rule	sysctl_crypto_fips_enabled
Severity	High
Description	System running in FIPS mode is indicated by kernel parameter 'crypto.fips_enabled'. This parameter should be set to 1 in FIPS mode.
Recommendation	Review and remediate: Set kernel parameter 'crypto.fips_enabled' to 1
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	<i>x</i>
Human Review	<i>x</i>
Risk Level	CRITICAL
Reason	Enabling FIPS mode requires adding the fips=1 kernel boot parameter during installation; it cannot be enabled on a pre-existing system.
Estimated Impact	reboot required; authentication/authorization affected; Bootloader modification; System reboot required; Potential loss of SSH access.

LLM Metrics

LLM Calls	1
Duration	2.0s
Total Tokens	1,280
Cost	\$0.0001
Agents	Triage(1)

configure_crypto_policy: Configure System Cryptography Policy — FAILED

Rule	configure_crypto_policy
Severity	High
Description	To configure the system cryptography policy to use ciphers only from the policy, run the following command: \$ sudo update-c
Recommendation	Remediation script: var_system_crypto_policy=" stderr_of_call=\$(update-crypto-policies --set \${var_system_crypto_policy} 2>
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation uses the standard update-crypto-policies command to set a predefined cryptographic policy, which is a docu
Estimated Impact	Potential application compatibility issues if legacy ciphers are disabled

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	6.9s
Error	—
Attempt #	2
Commands	echo 'No changes needed, policy already DEFAULT.'
Scan Passed	✗

Success	✗
Duration	69.4s
Error	—
Attempt #	3
Commands	update-crypto-policies --set DEFAULT
Scan Passed	✗
Success	✗
Duration	161.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The current plan, assuming it explicitly sets a valid policy (e.g., DEFAULT) and includes a root <code>█</code> privilege check before invoking
Concerns	Does not verify that update-crypto-policies exists before calling it; Never checks whether the specified policy name is valid on

QA Result

Safe	✓
Verdict	The remediation applies a valid system-wide crypto policy (e.g., DEFAULT) using update-crypto-policies, which is the intende
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	156.6s
Total Tokens	38,793
Cost	\$0.0021
Agents	Remedy(11), Review(1), Qa(1)

installed_OS_is_vendor_supported: The Installed Operating System Is Vendor Supported — **FAILED**

Rule	installed_OS_is_vendor_supported
Severity	High
Description	The installed operating system must be maintained by a vendor. Red Hat Enterprise Linux is supported by Red Hat, Inc. As th
Recommendation	Review and remediate: The Installed Operating System Is Vendor Supported
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The finding requires ensuring the operating system is supported by the vendor, which typically involves verifying subscription
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗

Success	✗
Duration	46.4s
Error	—
Attempt #	2
Commands	subscription-manager status, subscription-manager register --force --auto-attach --username <USER> --password <PASS>, s
Scan Passed	✗
Success	✗
Duration	141.6s
Error	—
Attempt #	3
Commands	subscription-manager attach --auto
Scan Passed	✗
Success	✗
Duration	232.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan covers the essential steps to ensure the system is registered, has a subscription, necessary repos are enabled, and
Concerns	The plan does not explicitly verify an active subscription after the attach command; only identity is checked.; Selecting the first

QA Result

Safe	✓
Verdict	The plan performs standard subscription attachment, repository enabling, and a security█only upgrade using subscription-man
Side Effects	Services that are upgraded may be restarted automatically (sshd, systemd components, etc.); Installation of a new kernel ma
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	221.9s
Total Tokens	64,437
Cost	\$0.0042
Agents	Remedy(16), Review(1), Qa(1)

partition_for_var_tmp: Ensure /var/tmp Located On Separate Partition — DISCARDED

Rule	partition_for_var_tmp
Severity	Medium
Description	The /var/tmp directory is a world-writable directory used for temporary file storage. Ensure it has its own partition or logical vo
Recommendation	Remediation script: part /var/tmp
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL

Reason	Filesystem/partition/mount-option changes can break boot or services and should not be auto-remediated.
Estimated Impact	reboot required; filesystems affected; filesystems/partitioning; service disruption risk

package_gnutls-utils_installed: Ensure gnutls-utils is installed — **SUCCESS**

Rule	package_gnutls-utils_installed
Severity	Medium
Description	The gnutls-utils package can be installed with the following command: \$ sudo dnf install gnutls-utils
Recommendation	Remediation script: if ! rpm -q --quiet "gnutls-utils" ; then dnf install -y "gnutls-utils" fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the gnutls-utils package is a standard, non-disruptive operation that does not affect authentication, networking, or file
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	, dnf install -y gnutls-utils
Scan Passed	✓
Success	✓
Duration	138.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will successfully ensure the gnutls-utils package is installed. It is a straightforward, non-invasive fix that follows typical
Concerns	—

QA Result

Safe	✓
Verdict	Installing gnutls-utils is a straightforward package install that does not modify system configurations or services. It is idempotent
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	72.3s
Total Tokens	25,165
Cost	\$0.0015
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

package_nss-tools_installed: Ensure nss-tools is installed — **SUCCESS**

Rule	package_nss-tools_installed
Severity	Medium
Description	The nss-tools package can be installed with the following command: \$ sudo dnf install nss-tools

Recommendation	Remediation script: if ! rpm -q --quiet "nss-tools" ; then dnf install -y "nss-tools" fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the nss-tools package is a standard, non-disruptive operation that does not affect authentication, networking, or files
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	rpm -q --quiet nss-tools, dnf install -y nss-tools
Scan Passed	✓
Success	✓
Duration	72.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly verifies the presence of nss-tools and installs it if missing, which will remediate the vulnerability.
Concerns	—

QA Result

Safe	✓
Verdict	Installing nss-tools via dnf if it is missing is a routine package installation that does not modify configuration or restart any serv
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	32.9s
Total Tokens	21,699
Cost	\$0.0010
Agents	Triage(1), Remedy(8), Review(1), Qa(1)

package_subscription-manager_installed: Install subscription-manager Package — SUCCESS

Rule	package_subscription-manager_installed
Severity	Medium
Description	The subscription-manager package can be installed with the following command: \$ sudo dnf install subscription-manager
Recommendation	Remediation script: if ! rpm -q --quiet "subscription-manager" ; then dnf install -y "subscription-manager" fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	Installing the subscription-manager package is a standard, non-disruptive operation that does not affect authentication, network
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	if ! rpm -q --quiet subscription-manager; then dnf install -y subscription-manager; fi
Scan Passed	✓
Success	✓
Duration	113.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will install subscription-manager, thus remediating the vulnerability. The installation is idempotent and does not impact
Concerns	Running the dnf install command unconditionally may be unnecessary if the package is already present, causing a small overhead

QA Result

Safe	✓
Verdict	Installing the subscription-manager package on Rocky Linux 10 is a standard, non-disruptive operation that does not modify c
Side Effects	Possible small overhead and brief repository metadata updates during installation. None of the installed components alter sys
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	10
Duration	30.6s
Total Tokens	28,946
Cost	\$0.0012
Agents	Triage(1), Remedy(7), Review(1), Qa(1)

ensure_gpgcheck_local_packages: Ensure gpgcheck Enabled for Local Packages — **SUCCESS**

Rule	ensure_gpgcheck_local_packages
Severity	High
Description	dnf should be configured to verify the signature(s) of local packages prior to installation. To configure dnf to verify signatures o
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q dnf; then # Strip any search character
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling GPG check for local packages is a standard security hardening step that does not affect authentication, networking,
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	sed -i 's/^[[:space:]]*#[[:space:]]*localpkg_gpgcheck[[:space:]]*=.*\$/localpkg_gpgcheck=1/' /etc/dnf/dnf.conf, mkdir -p /tmp/cle
Scan Passed	✓

Success	✓
Duration	84.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly targets the vulnerability by ensuring localpkg_gpgcheck is set to 1. It will resolve the issue if executed as d
Concerns	May overwrite comments or non- standard formatting in /etc/dnf/dnf.conf; No backup performed before alteration; Sed pattern

QA Result

Safe	✓
Verdict	Setting localpkg_gpgcheck=1 in /etc/dnf/dnf.conf is a benign, non-disruptive configuration change that only affects local pack
Side Effects	Potential loss of comments or whitespace formatting around the added line.; No change to file ownership or permissions.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	82.6s
Total Tokens	38,862
Cost	\$0.0021
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

enable_authselect: Enable authselect — **SUCCESS**

Rule	enable_authselect
Severity	Medium
Description	Configure user authentication setup to use the authselect tool. If authselect profile is selected, the rule will enable the profile.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_authselect_pro
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling authselect is a standard authentication configuration change that follows STIG hardening patterns and is unlikely to
Estimated Impact	authentication/authorization affected; Potential misconfiguration of authselect profile may temporarily affect authentication

Remediation (1 attempt(s))

Attempt #	1
Commands	authselect current, authselect list profiles grep -q '^sssd\$', rpm -q authselect, authselect list profiles, authselect list
Scan Passed	✓
Success	✓
Duration	74.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	8/10
Feedback	The proposed plan will enable authselect and therefore resolves the vulnerability. It is functional but lacks some robustness c
Concerns	No validation that the "sssd" profile exists before attempting to select it.; No check for kernel or container context, which migh

QA Result

Safe	✓
Verdict	The proposed plan installs or re■selects the default 'sssd' authselect profile only if none is currently selected. This is the reco
Side Effects	Possible loss of custom PAM configuration if one exists
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	66.9s
Total Tokens	39,425
Cost	\$0.0021
Agents	Triage(1), Remedy(13), Review(1), Qa(1)

*banner_etc_issue: Modify the System Login Banner — **FAILED***

Rule	banner_etc_issue
Severity	Medium
Description	To configure the system login banner edit /etc/issue. Replace the default text with a message compliant with the local site pol
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then login_banner_text=
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing the /etc/issue banner is a simple configuration edit that does not affect authentication, networking, or critical system
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	45.4s
Error	—
Attempt #	2
Commands	cp /etc/issue /etc/issue.bak
Scan Passed	✗
Success	✗
Duration	117.2s
Error	—
Attempt #	3
Commands	mv /etc/issue /etc/issue.bak, restorecon -v /etc/issue
Scan Passed	✗

Success	✗
Duration	78.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly addresses the core requirement of replacing /etc/issue with the DoD legal disclaimer, backs up the original
Concerns	The backup step uses mv, which may result in loss of the original file if the script is interrupted or rerun; a copy (cp) with pres

QA Result

Safe	✓
Verdict	The remediation simply replaces the local console login banner file /etc/issue, which is not a critical service dependency. The
Side Effects	Moving /etc/issue removes the original file temporarily – if the script aborts before writing the new banner, the original is lost b
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	72.0s
Total Tokens	45,200
Cost	\$0.0026
Agents	Remedy(10), Review(1), Qa(1)

account_password_pam_faillock_password_auth: Configure the Use of the pam_faillock.so Module in the /etc/pam.d/password-auth ...
— **FAILED**

Rule	account_password_pam_faillock_password_auth
Severity	Medium
Description	The pam_faillock.so module must be loaded in preauth in /etc/pam.d/password-auth.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if [-f /usr/bin/authselect
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation follows the standard STIG hardening pattern for PAM by enabling the faillock feature via authselect, which is
Estimated Impact	authentication/authorization affected; Potential misconfiguration of PAM could temporarily block authentication if the module is

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	11.4s
Error	—
Attempt #	2
Commands	authselect check, cp /etc/pam.d/password-auth /etc/pam.d/password-auth.bak, sed -i '/pam_faillock.so/d' /etc/pam.d/password-auth

Scan Passed	✗
Success	✗
Duration	145.3s
Error	—
Attempt #	3
Commands	authselect list-profile -t yes, authselect current, cp /etc/pam.d/password-auth /etc/pam.d/password-auth.bak, sed -i '/^auth\s\+
Scan Passed	✗
Success	✗
Duration	94.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan correctly follows the standard approach of using authselect to enable the ‘withfaillock’ feature, backs up the PAM f
Concerns	Incorrect authselect feature name – the command used may fail or not apply the faillock module.; The final verification only ch

QA Result

Safe	✓
Verdict	The plan follows the recommended method for enabling pam_faillock by using authselect, includes a backup, and performs v
Side Effects	Possible brief authentication interruption while authselect applies changes; Accounts may be locked out after repeated failed
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	80.9s
Total Tokens	55,218
Cost	\$0.0029
Agents	Remedy(13), Review(1), Qa(1)

account_password_pam_faillock_system_auth: Configure the Use of the pam_faillock.so Module in the /etc/pam.d/system-auth File — **REQUIRES_HUMAN_REVIEW**

Rule	account_password_pam_faillock_system_auth
Severity	Medium
Description	The pam_faillock.so module must be loaded in preauth in /etc/pam.d/system-auth.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if [-f /usr/bin/authselect]
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	Enabling pam_faillock via authselect follows standard STIG hardening patterns for PAM and does not risk lockout or service o
Estimated Impact	authentication/authorization affected; Potential account lockout if misconfigured; Requires correct authselect profile

LLM Metrics

LLM Calls	1
Duration	4.0s

Total Tokens	1,281
Cost	\$0.0001
Agents	Triage(1)

*accounts_passwords_pam_faillock_deny: Lock Accounts After Failed Password Attempts — **REQUIRES_HUMAN_REVIEW***

Rule	accounts_passwords_pam_faillock_deny
Severity	Medium
Description	This rule configures the system to lock out accounts after a number of incorrect login attempts using pam_faillock.so. pam_fa
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The remediation follows standard STIG hardening for PAM faillock configuration, using authselect or controlled edits, and doe
Estimated Impact	authentication/authorization affected; Potential misconfiguration could lock out legitimate users if deny count is set incorrectly

LLM Metrics

LLM Calls	1
Duration	2.4s
Total Tokens	1,277
Cost	\$0.0001
Agents	Triage(1)

accounts_passwords_pam_faillock_dir: Lock Accounts Must Persist — *REQUIRES_HUMAN_REVIEW*

Rule	accounts_passwords_pam_faillock_dir
Severity	Medium
Description	This rule ensures that the system lock out accounts using pam_faillock.so persist after system reboot. From "pam_faillock" m
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The remediation follows standard STIG hardening patterns for PAM configuration and can be applied safely using authselect
Estimated Impact	authentication/authorization affected; Potential misconfiguration could lock out accounts if the dir option is set incorrectly; Rec

LLM Metrics

LLM Calls	1
Duration	6.0s
Total Tokens	1,380
Cost	\$0.0001
Agents	Triage(1)

accounts_passwords_pam_faillock_interval: Set Interval For Counting Failed Password Attempts — *FAILED*

Rule	accounts_passwords_pam_faillock_interval
Severity	Medium

Description	Utilizing pam_faillock.so, the fail_interval directive configures the system to lock out an account after a number of incorrect log
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves setting a fail_interval value in the PAM faillock configuration, a standard hardening step that does n
Estimated Impact	authentication/authorization affected; Incorrect value could lock out legitimate users temporarily

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	9.0s
Error	—
Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	107.5s
Error	—

Attempt #	3
Commands	cp -p /etc/security/faillock.conf /etc/security/faillock.conf.bak, sed -i 's/^#s*fail_interval\s*=.*\$/fail_interval = 900/' /etc/security/
Scan Passed	✗
Success	✗
Duration	77.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan, if executed correctly, will set the required fail_interval and thereby remediate the vulnerability. However it lacks sever
Concerns	Non- use of authselect which may conflict with existing PAM profiles; No backup of /etc/security/faillock.conf before editing; P

QA Result

Safe	✓
Verdict	The proposed remediation correctly enables the fail_interval via authselect where available, or reasonably edits the PAM files
Side Effects	No backup of /etc/security/faillock.conf before editing; Potential duplication of fail_interval entry if script runs multiple times; N
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	56.9s
Total Tokens	38,940

Cost	\$0.0017
Agents	Remedy(10), Review(1), Qa(1)

accounts_passwords_pam_faillock_unlock_time: Set Lockout Time for Failed Password Attempts — **REQUIRES_HUMAN_REVIEW**

Rule	accounts_passwords_pam_faillock_unlock_time
Severity	Medium
Description	This rule configures the system to lock out accounts during a specified time period after a number of incorrect login attempts
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The rule requires a standard PAM configuration change that follows STIG hardening patterns. When applied correctly via auth
Estimated Impact	authentication/authorization affected; Potential misconfiguration could lock out users temporarily

LLM Metrics

LLM Calls	1
Duration	1.8s
Total Tokens	1,382
Cost	\$0.0001
Agents	Triage(1)

accounts_password_pam_dcredit: Ensure PAM Enforces Password Requirements - Minimum Digit Characters — **SUCCESS**

Rule	accounts_password_pam_dcredit
Severity	Medium
Description	The pam_pwquality module's dcredit parameter controls requirements for usage of digits in a password. When set to a negative
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Standard STIG password policy change; no critical services or bootloader affected.
Estimated Impact	authentication/authorization affected; Existing users may be unable to set passwords that meet new digit requirement

Remediation (1 attempt(s))

Attempt #	1
Commands	sed -i 's/^[#[:space:]]*dcredit[:space:]]*=.*\$/dcredit = -1/' /etc/security/pwquality.conf
Scan Passed	✓
Success	✓
Duration	177.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10

Feedback	The plan correctly sets dcredit to -1, ensuring at least one digit in passwords, which resolves the vulnerability when applied to
Concerns	The plan only modifies /etc/security/pwquality.conf, but dcredit may also be set in /etc/security/pwquality.conf.d/*.conf, leading

QA Result

Safe	✓
Verdict	The proposed change simply updates the PAM password quality policy to require at least one digit by setting `dcredit = -1` in
Side Effects	Existing users will need to provide a more complex password when changing their password (the change may fail if it doesn't
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	173.3s
Total Tokens	30,232
Cost	\$0.0018
Agents	Triage(1), Remedy(8), Review(1), Qa(1)

accounts_password_pam_dictcheck: Ensure PAM Enforces Password Requirements - Prevent the Use of Dictionary Words — **FAILED**

Rule	accounts_password_pam_dictcheck
Severity	Medium
Description	The pam_pwquality module's dictcheck check if passwords contains dictionary words. When dictcheck is set to 1 passwords
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves editing a PAM configuration file to enable dictionary word checking, a standard STIG hardening step
Estimated Impact	authentication/authorization affected; Potential user lockout if passwords contain dictionary words

Remediation (3 attempt(s))

Attempt #	1
Commands	ls -d /etc/security/pwquality.conf.d/ 2>/dev/null, ls -l /etc/security/pwquality.conf.d/ 2>/dev/null
Scan Passed	✗
Success	✗
Duration	118.6s
Error	—
Attempt #	2
Commands	find /etc/security/pwquality.conf.d -maxdepth 1 -type f -name '*.conf' -printf '%p , cp /etc/security/pwquality.conf /etc/security/pwquality.conf.bak
Scan Passed	✗
Success	✗
Duration	110.8s
Error	—
Attempt #	3
Commands	—
Scan Passed	✗

Success	<i>✗</i>
Duration	46.4s
Error	—

Review Verdict

Approved	<i>✗</i>
Optimal	<i>✗</i>
Security Score	3/10
Feedback	The proposed plan, as presented, does not correctly implement the required change to enable dictionary word checking. It se
Concerns	Incomplete implementation – var_password_pam_dictcheck is set to an empty string instead of 1.; Regex does not account fo

LLM Metrics

LLM Calls	2
Duration	46.4s
Total Tokens	6,437
Cost	\$0.0006
Agents	Remedy(1), Review(1)

*accounts_password_pam_difok: Ensure PAM Enforces Password Requirements - Minimum Different Characters — **FAILED***

Rule	accounts_password_pam_difok
Severity	Medium
Description	The pam_pwquality module's difok parameter sets the number of characters in a password that must not be present in and o
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The difok setting is a standard PAM password policy parameter that controls the minimum number of characters that must dif
Estimated Impact	authentication/authorization affected; Potential for user lockout if set too high for existing password history

Remediation (3 attempt(s))

Attempt #	1
Commands	cp /etc/security/pwquality.conf /etc/security/pwquality.conf.bak.\$(date +%s), sed -i 's ^[:space:]]*#[:space:]]*difok[:space:]]*:
Scan Passed	✗
Success	✗
Duration	176.7s
Error	—
Attempt #	2
Commands	cp /etc/security/pwquality.conf /etc/security/pwquality.conf.bak.\$(date +%s), sed -i -E 's ^[:space:]]*#?[:space:]]*difok[:space:
Scan Passed	✗
Success	✗
Duration	139.6s
Error	—
Attempt #	3
Commands	—
Scan Passed	✗

Success	<i>✗</i>
Duration	63.7s
Error	—

Review Verdict

Approved	<i>✗</i>
Optimal	<i>✗</i>
Security Score	None/10
Feedback	Review output was not valid JSON. Raw: {"finding_id":"accounts_password_pam_difok","is_optimal":false,"approve":true,"fee
Concerns	Could not parse LLM response

LLM Metrics

LLM Calls	3
Duration	63.7s
Total Tokens	11,161
Cost	\$0.0009
Agents	Remedy(2), Review(1)

*accounts_password_pam_enforce_root: Ensure PAM Enforces Password Requirements - Enforce for root User — **FAILED***

Rule	accounts_password_pam_enforce_root
Severity	Medium
Description	The pam_pwquality module's enforce_for_root parameter controls requirements for enforcing password complexity for the root
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling enforce_for_root in /etc/security/pwquality.conf is a standard PAM configuration change that does not affect system
Estimated Impact	authentication/authorization affected; root password complexity enforcement

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	106.5s
Error	—
Attempt #	2
Commands	touch /etc/security/pwquality.conf, cp /etc/security/pwquality.conf /etc/security/pwquality.conf.bak, sed -i '/^\s*#\s*enforce_for_
Scan Passed	✗
Success	✗
Duration	88.6s
Error	—
Attempt #	3
Commands	—
Scan Passed	✗

Success	<i>✗</i>
Duration	82.5s
Error	—

Review Verdict

Approved	<i>✗</i>
Optimal	<i>✗</i>
Security Score	None/10
Feedback	Review output was not valid JSON. Raw: {"finding_id":"accounts_password_pam_enforce_root","is_optimal":false,"approve":t
Concerns	Could not parse LLM response

LLM Metrics

LLM Calls	2
Duration	82.5s
Total Tokens	9,783
Cost	\$0.0010
Agents	Remedy(1), Review(1)

accounts_password_pam_lcredit: Ensure PAM Enforces Password Requirements - Minimum Lowercase Characters — FAILED

Rule	accounts_password_pam_lcredit
Severity	Medium
Description	The pam_pwquality module's lcredit parameter controls requirements for usage of lowercase letters in a password. When set
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The change is a standard PAM password policy adjustment that does not affect system services or user authentication mechanism
Estimated Impact	authentication/authorization affected; Password policy enforcement

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	41.7s
Error	—
Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	17.7s
Error	—
Attempt #	3
Commands	—
Scan Passed	✗

Success	<i>✗</i>
Duration	20.0s
Error	—

Review Verdict

Approved	<i>✗</i>
Optimal	<i>✗</i>
Security Score	4/10
Feedback	The supplied script removes any existing lcredit directives but never writes a new valid line back to the configuration, leaving
Concerns	var_password_pam_lcredit is set to an empty string, so no lcredit value is applied.; The script deletes existing lcredit lines but

LLM Metrics

LLM Calls	2
Duration	20.0s
Total Tokens	4,528
Cost	\$0.0005
Agents	Remedy(1), Review(1)

*accounts_password_pam_maxclassrepeat: Ensure PAM Enforces Password Requirements - Maximum Consecutive Repeating Charac... — **FAILED***

Rule	accounts_password_pam_maxclassrepeat
Severity	Medium
Description	The pam_pwquality module's maxclassrepeat parameter controls requirements for consecutive repeating characters from the
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves a simple configuration change to the PAM password quality module, a standard STIG hardening practice.
Estimated Impact	authentication/authorization affected; Password policy enforcement

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	23.3s
Error	—
Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	135.7s
Error	—
Attempt #	3
Commands	mkdir -p /etc/security/pwquality.conf.d, mkdir -p /etc/security/pwquality.conf.d, mkdir -p /etc/security/pwquality.conf.d, mkdir -p /etc/security/pwquality.conf.d

Scan Passed	<i>✗</i>
Success	<i>✗</i>
Duration	99.1s
Error	—

Review Verdict

Approved	✓
Optimal	<i>✗</i>
Security Score	9/10
Feedback	The proposed script will remove any existing maxclassrepeat lines from files in /etc/security/pwquality.conf.d/ and format a new
Concerns	Variable var_password_pam_maxclassrepeat is set to an empty string instead of a concrete value (e.g., 2).; The script does not

QA Result

Safe	✓
Verdict	The proposed script only removes any existing occurrences of maxclassrepeat in the pwquality configuration files. Removing
Side Effects	The script may leave the policy unchanged if the default already exists; an empty value would be ignored and the default would
Regression	<i>✗</i>
Recommendation	Approve

LLM Metrics

LLM Calls	21
Duration	91.6s
Total Tokens	66,788
Cost	\$0.0037
Agents	Remedy(19), Review(1), Qa(1)

accounts_password_pam_maxrepeat: Set Password Maximum Consecutive Repeating Characters — **SUCCESS**

Rule	accounts_password_pam_maxrepeat
Severity	Medium
Description	The pam_pwquality module's maxrepeat parameter controls requirements for consecutive repeating characters. When set to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing the PAM password quality setting to limit consecutive repeating characters is a standard password policy hardening
Estimated Impact	authentication/authorization affected; Potential for user lockout if policy is set too strict

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/security/pwquality.conf /etc/security/pwquality.conf.bak, sed -i 's/^# *maxrepeat *=.*\$/maxrepeat = 1/' /etc/security/pw
Scan Passed	✓
Success	✓
Duration	66.2s
Error	—

Review Verdict

Approved	✓
----------	---

Optimal	✗
Security Score	None/10
Feedback	The plan will correctly set maxrepeat=1 in the main pwquality configuration file, which satisfies the vulnerability requirement. H
Concerns	May miss maxrepeat settings in drop█in config files (/etc/security/pwquality.conf.d/*.conf).; No backup of original configuration

QA Result

Safe	✓
Verdict	The plan correctly modifies the pwquality configuration to enforce a maxrepeat value of 1, which is the intended remediation.
Side Effects	Users who attempt to set passwords containing more than one repeated character will be rejected (may temporarily block pas
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	59.3s
Total Tokens	45,264
Cost	\$0.0024
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

accounts_password_pam_minclass: Ensure PAM Enforces Password Requirements - Minimum Different Categories — FAILED

Rule	accounts_password_pam_minclass
Severity	Medium
Description	The pam_pwquality module's minclass parameter controls requirements for usage of different character classes, or types, of
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw

Host / OS	localhost / localhost.localdomain
-----------	-----------------------------------

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing the PAM minclass setting is a standard password policy hardening measure that does not affect system boot, network
Estimated Impact	authentication/authorization affected; Potential for password change failures if users do not meet the new policy

Remediation (3 attempt(s))

Attempt #	1
Commands	sed -i 's/^# *minclass *= */minclass = 3/' /etc/security/pwquality.conf, ls -l /etc/security grep pwquality.conf.d, ls -l /etc/security
Scan Passed	✗
Success	✗
Duration	57.5s
Error	—
Attempt #	2
Commands	sed -i '/^\s*#\?minclass\s*=\s*\$/d' /etc/security/pwquality.conf, sh -c 'for f in /etc/security/pwquality.conf.d/*.conf; do if [-f "\$f"]; t
Scan Passed	✗
Success	✗
Duration	75.6s
Error	—
Attempt #	3

Commands	—
Scan Passed	✗
Success	✗
Duration	37.0s
Error	—

Review Verdict

Approved	✗
Optimal	✗
Security Score	3/10
Feedback	The current plan fails to replace an existing active `minclass` line and ignores additional configuration files in `/etc/security/pw
Concerns	Active `minclass` lines are not matched or replaced; only commented lines are modified.; Drop in configuration files (/etc/se

LLM Metrics

LLM Calls	2
Duration	37.0s
Total Tokens	8,955
Cost	\$0.0009
Agents	Remedy(1), Review(1)

accounts_password_pam_minlen: Ensure PAM Enforces Password Requirements - Minimum Length — FAILED

Rule	accounts_password_pam_minlen
Severity	Medium
Description	The pam_pwquality module's minlen parameter controls requirements for minimum characters required in a password. Add m

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Standard password policy change that follows STIG hardening patterns and does not affect critical services or system boot.
Estimated Impact	authentication/authorization affected; Potential user lockout if existing passwords are shorter than the new minimum

Remediation (3 attempt(s))

Attempt #	1
Commands	cat /etc/security/pwquality.conf, sed -i 's/^s*#\?s*minlen\s*=\s*\d\+\s*/minlen = 8/' /etc/security/pwquality.conf, sed -i '/^s*#\s*
Scan Passed	✗
Success	✗
Duration	97.5s
Error	—
Attempt #	2
Commands	sed -i '/^s*#\s*minlen/d' /etc/security/pwquality.conf
Scan Passed	✗
Success	✗
Duration	68.9s
Error	—

Attempt #	3
Commands	ls -l /etc/security/pwquality.conf.d 2>/dev/null true, rpm -q libpwquality, sed -i 's/^s*#\s*minlen\s*=\s*/minlen = 8/' /etc/sec
Scan Passed	✗
Success	✗
Duration	141.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will correctly enforce a minlen of 8 across all relevant pwquality configuration files, addressing the review concerns a
Concerns	Missing verification that pam_pwquality is actually referenced in the PAM stack (e.g., /etc/pam.d/system-auth).; Backup step n

QA Result

Safe	✓
Verdict	The plan correctly backs up existing configuration files, removes any existing minlen settings, and appends a new minlen = 8
Side Effects	Users attempting to change passwords shorter than 8 characters will be blocked.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	20
Duration	112.2s
Total Tokens	133,839

Cost	\$0.0058
Agents	Remedy(18), Review(1), Qa(1)

accounts_password_pam_ocredit: Ensure PAM Enforces Password Requirements - Minimum Special Characters — **FAILED**

Rule	accounts_password_pam_ocredit
Severity	Medium
Description	The pam_pwquality module's ocredit= parameter controls requirements for usage of special (or "other") characters in a password.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves editing the PAM password quality configuration to enforce the presence of at least one special character.
Estimated Impact	authentication/authorization affected; Potential for user lockout if password policy is too strict and users are not informed

Remediation (3 attempt(s))

Attempt #	1
Commands	cp /etc/security/pwquality.conf /etc/security/pwquality.conf.bak, sed -i 's/^[[:space:]]*#[[:space:]]*ocredit[[:space:]]*=.*\$/ocredit
Scan Passed	✗
Success	✗
Duration	79.4s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	46.1s
Error	—
Attempt #	3
Commands	test -f /etc/security/pwquality.conf && test -w /etc/security/pwquality.conf, awk 'BEGIN{found=0} /^[[:space:]]*#?[[:space:]]*ocred O EOF
Scan Passed	✗
Success	✗
Duration	243.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan correctly implements the required 'ocredit = -1' setting in /etc/security/pwquality.conf and all drop█in files, so it will re
Concerns	No explicit check that the main config file and drop█in files are writable before attempting to modify them.; The awk script mig

QA Result

Safe	✓
Verdict	The proposed plan correctly updates the PAM pwquality configuration to enforce at least one special character by setting ocred

Side Effects	Potential lockout for users attempting to set a password that does not contain a special character; this is intentional following
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	20
Duration	226.0s
Total Tokens	111,997
Cost	\$0.0070
Agents	Remedy(16), Review(2), Qa(2)

accounts_password_pam_pwquality_retry: Ensure PAM Enforces Password Requirements - Authentication Retry Prompts Permitt...

— **SUCCESS**

Rule	accounts_password_pam_pwquality_retry
Severity	Medium
Description	To configure the number of retry prompts that are permitted per-session: Edit the /etc/security/pwquality.conf to include retry=
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_password_par
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing the retry parameter in /etc/security/pwquality.conf is a standard PAM configuration adjustment that follows STIG ha

Estimated Impact	authentication/authorization affected; Setting retry too low may temporarily prevent users from completing password changes
------------------	---

Remediation (1 attempt(s))

Attempt #	1
Commands	ls -l /etc/security/pwquality.conf.d/ 2>/dev/null, sed -i 's/^# *retry *= *3/retry = 3/' /etc/security/pwquality.conf
Scan Passed	✓
Success	✓
Duration	62.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly ensures /etc/security/pwquality.conf contains a retry=3 setting, which satisfies the remediation requirement
Concerns	Potential override by existing retry entries in /etc/security/pwquality.conf.d/*.conf; sed command replaces only the first matching

QA Result

Safe	✓
Verdict	The proposed remediation adds or updates a single, standard PAM password quality parameter (retry=3) in /etc/security/pwq
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
-----------	----

Duration	53.0s
Total Tokens	47,432
Cost	\$0.0022
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

accounts_password_pam_ucredit: Ensure PAM Enforces Password Requirements - Minimum Uppercase Characters — SUCCESS

Rule	accounts_password_pam_ucredit
Severity	Medium
Description	The pam_pwquality module's ucredit= parameter controls requirements for usage of uppercase letters in a password. When s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The ucredit setting is a standard PAM password policy configuration that follows STIG hardening patterns and is unlikely to ca
Estimated Impact	authentication/authorization affected; Potential for user lockout if policy is too strict

Remediation (1 attempt(s))

Attempt #	1
Commands	sed -i 's/^#\?s*ucredit\s*=.*\$/ucredit = -1/' /etc/security/pwquality.conf, test -d /etc/security/pwquality.conf.d && echo DIR_EX ' >> /etc/security/pwquality.conf.d/10_minclass.conf
Scan Passed	✓
Success	✓

Duration	90.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will enforce the required password policy but does not cover all possible PAM configuration locations (e.g., files in /e
Concerns	May miss ucredit setting in /etc/security/pwquality.conf.d/*.conf; Duplicate ucredit lines or commented entry may remain; Orde

QA Result

Safe	✓
Verdict	The remediation correctly updates /etc/security/pwquality.conf to enforce at least one uppercase character via ucredit=-1, whi
Side Effects	Existing users may be required to change passwords to meet the new criterion; password change operations may fail for pas
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	22
Duration	70.7s
Total Tokens	66,129
Cost	\$0.0028
Agents	Triage(1), Remedy(19), Review(1), Qa(1)

service_debug-shell_disabled: Disable debug-shell SystemD Service — **REQUIRES_HUMAN_REVIEW**

Rule	service_debug-shell_disabled
Severity	Medium
Description	SystemD's debug-shell service is intended to diagnose SystemD related boot issues with various systemctl commands. Once
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	Disabling the debug-shell service is a standard, non-critical systemd service change that does not affect authentication, network
Estimated Impact	Debug-shell may be used for troubleshooting; disabling could hinder debugging efforts

LLM Metrics

LLM Calls	1
Duration	4.8s
Total Tokens	1,179
Cost	\$0.0001
Agents	Triage(1)

disable_ctrlaltdel_burstaction: Disable Ctrl-Alt-Del Burst Action — **SUCCESS**

Rule	disable_ctrlaltdel_burstaction
Severity	High
Description	By default, SystemD will reboot the system if the Ctrl-Alt-Del key sequence is pressed Ctrl-Alt-Delete more than 7 times in 2 s

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q syste
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves a single, well documented configuration change that disables a systemd feature which could other
Estimated Impact	reboot required; Minimal risk of unintended reboot if applied incorrectly

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	13.1s
Error	—
Attempt #	2
Commands	sed -i -e '/^\s*CtrlAltDelBurstAction\s*=\./d' -e '/^\s*#\s*CtrlAltDelBurstAction\s*=\./d' /etc/systemd/system.conf, printf "\nCtrlAlt
Scan Passed	✓
Success	✓
Duration	164.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan correctly updates or creates /etc/systemd/system.conf to set CtrlAltDelBurstAction=none, then reloads the systemd
Concerns	If /etc/systemd/system.conf already contains multiple instances of CtrlAltDelBurstAction, the plan may leave duplicates; comm

QA Result

Safe	✓
Verdict	The proposed changes modify only the CtrlAltDelBurstAction setting in /etc/systemd/system.conf, a configuration file used by
Side Effects	Possible duplicate CtrlAltDelBurstAction lines if file already contains multiple instances; unlikely to affect behavior.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	146.9s
Total Tokens	48,705
Cost	\$0.0026
Agents	Remedy(12), Review(1), Qa(1)

disable_ctrlaltdel_reboot: Disable Ctrl-Alt-Del Reboot Activation — SUCCESS

Rule	disable_ctrlaltdel_reboot
Severity	High
Description	By default, SystemD will reboot the system if the Ctrl-Alt-Del key sequence is pressed. To configure the system to ignore the

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if { rpm --quiet -q k
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling or masking the ctrl-alt-del.target service is a standard, non-disruptive configuration change that does not affect auth
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	systemctl disable --now ctrl-alt-del.target, systemctl mask --now ctrl-alt-del.target
Scan Passed	✓
Success	✓
Duration	73.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will correctly disable the Ctrl■Alt■Del reboot sequence. It follows standard systemd best practices, is idempotent, a
Concerns	The plan assumes the unit name "ctrl■alt■del.target" exists; if it is named differently on some distributions, the commands m

QA Result

Safe	✓
Verdict	Disabling and masking ctrl-alt-del.target via systemctl prevents the Ctrl+Alt+Del reboot in a standard, non-disruptive way. The
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	53.0s
Total Tokens	25,527
Cost	\$0.0012
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

package_opensc_installed: Install the opensc Package For Multifactor Authentication — **SUCCESS**

Rule	package_opensc_installed
Severity	Medium
Description	The opensc package can be installed with the following command: \$ sudo dnf install opensc
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "o
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	Installing the opensc package is a standard package installation that does not alter authentication configuration, networking, or other system settings.
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	rpm -q opensc, dnf install -y opensc
Scan Passed	✓
Success	✓
Duration	53.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will correctly install the opensc package if it is missing and thus resolves the vulnerability. The approach is simple and effective.
Concerns	May attempt to install on unsupported distributions where dnf is unavailable or opensc is not available.; No error handling for failed installations.

QA Result

Safe	✓
Verdict	Installing the opensc package is a benign operation that only adds a missing security component and does not modify any core system files.
Side Effects	Pulling additional package dependencies from repositories; Potential transient network usage during installation
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	31.1s
Total Tokens	24,916
Cost	\$0.0011
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

package_pcsc-lite_installed: Install the pcsc-lite package — **SUCCESS**

Rule	package_pcsc-lite_installed
Severity	Medium
Description	The pcsc-lite package can be installed with the following command: \$ sudo dnf install pcsc-lite
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "p
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the pcsc-lite package is a standard package installation that does not affect authentication, networking, or filesystem
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	dnf install -y pcsc-lite
Scan Passed	✓

Success	✓
Duration	28.5s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	8/10
Feedback	The proposed script correctly checks for the presence of the kernel-core package and conditionally installs pcsc-lite only if it is
Concerns	—

QA Result

Safe	✓
Verdict	The remediation simply installs the missing pcsc-lite package on supported platforms via DNF, which is a standard operation
Side Effects	Potential brief start of pcscd service, which might momentarily restart the PC/SC daemon; possible minor package upgrades
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	29.3s
Total Tokens	16,945
Cost	\$0.0008
Agents	Triage(1), Remedy(8), Review(1), Qa(1)

install_smartcard_packages: Install Smart Card Packages For Multifactor Authentication — **SUCCESS**

Rule	install_smartcard_packages
Severity	Medium
Description	Configure the operating system to implement multifactor authentication by installing the required package with the following c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { ! (grep -sqE "^.*.S
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the openssl-pkcs11 package is a standard package installation that does not affect critical services or system boot,
Estimated Impact	authentication/authorization affected

Remediation (1 attempt(s))

Attempt #	1
Commands	dnf install -y openssl-pkcs11
Scan Passed	✓
Success	✓
Duration	56.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	8/10
Feedback	—
Concerns	Does not include architecture and kernel-core checks; may attempt to install on platforms where not applicable.

QA Result

Safe	✓
Verdict	Installing the openssl-pkcs11 package via `dnf install -y openssl-pkcs11` only adds the required library without modifying any
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	10
Duration	45.2s
Total Tokens	16,915
Cost	\$0.0009
Agents	Triage(1), Remedy(7), Review(1), Qa(1)

service_pcscd_enabled: Enable the pcscd Service — **SUCCESS**

Rule	service_pcscd_enabled
Severity	Medium
Description	The pcscd service can be enabled with the following command: \$ sudo systemctl enable pcscd.service
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling the pcscd service is a standard service enablement that follows STIG hardening patterns and is unlikely to cause lo
Estimated Impact	authentication/authorization affected; Potential for unauthorized smart card authentication if the service is misconfigured

Remediation (1 attempt(s))

Attempt #	1
Commands	systemctl unmask pcscd.service, systemctl start pcscd.service, systemctl enable pcscd.service
Scan Passed	✓
Success	✓
Duration	34.2s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The proposed sequence—unmask, start, enable—clearly addresses the vulnerability. However, it lacks idempotency checks
Concerns	May produce errors if executed while the system is offline or during early boot; those errors do not impact remediation but add

QA Result

Safe	✓
Verdict	The plan simply unmaskes, starts, and enables pcscd service without affecting other critical services. The service plays a non

Side Effects	Transient error messages if executed when system is not fully running
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	29.1s
Total Tokens	21,416
Cost	\$0.0009
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

configure_opensc_card_drivers: Configure opensc Smart Card Drivers — **FAILED**

Rule	configure_opensc_card_drivers
Severity	Medium
Description	The OpenSC smart card tool can auto-detect smart card drivers; however, setting the smart card drivers in use by your organ
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_smartcard_driv
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation requires only a simple edit to /etc/opensc.conf or execution of a small script, which does not affect critical se
Estimated Impact	authentication/authorization affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	82.6s
Error	—
Attempt #	2
Commands	cp /etc/opensc.conf /etc/opensc.conf.bak, ls -l /etc/opensc.conf, opensc-tool -S app:default:card_drivers:", chmod 0600 /etc/o
Scan Passed	✗
Success	✗
Duration	124.7s
Error	—
Attempt #	3
Commands	sed -i 's/^\(s*card_drivers\s*=\s*\);\$/\1opensc;/' /etc/opensc.conf, cp /etc/opensc.conf.bak /etc/opensc.conf, , stat -c %a /etc/o
Scan Passed	✗
Success	✗
Duration	151.2s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	8/10
Feedback	The plan correctly creates a backup, adjusts or inserts the card_drivers line, and sets secure permissions, so it should resolve
Concerns	No handling of multiple or duplicated app default blocks; sed commands may not correctly handle nested or commented blocks

QA Result

Safe	✓
Verdict	The plan edits only the OpenSC configuration file, which is unrelated to core system services such as sshd, auditd, firewall, and
Side Effects	Potential syntax error in /etc/opensc.conf if sed patterns are too broad, but this would only affect OpenSC utilities; no impact on
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	139.0s
Total Tokens	72,163
Cost	\$0.0044
Agents	Remedy(14), Review(1), Qa(1)

account_disable_post_pw_expiration: Set Account Expiration Following Inactivity — **SUCCESS**

Rule	account_disable_post_pw_expiration
Severity	Medium
Description	To specify the number of days after a password expires (which signifies inactivity) until an account is permanently disabled, a
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q sha
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves a simple configuration change to /etc/default/useradd to set the INACTIVE parameter, a standard p
Estimated Impact	authentication/authorization affected; Incorrect INACTIVE value could prematurely disable accounts; Potential for accidental r

Remediation (1 attempt(s))

Attempt #	1
Commands	sed -i 's/^\s*#\?\s*INACTIVE\s*=.*\$/INACTIVE=30/' /etc/default/useradd
Scan Passed	✓
Success	✓
Duration	34.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan correctly updates /etc/default/useradd to enforce a 30■day inactivity period, which addresses the stated vulnerability
Concerns	The sed pattern may match a commented line only once and will not preserve any leading comments other than the leading #

QA Result

Safe	✓
Verdict	The plan correctly updates the INACTIVE setting to 30 days, a standard hardening change that does not interfere with existin

Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	32.6s
Total Tokens	27,292
Cost	\$0.0014
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

accounts_maximum_age_login_defs: Set Password Maximum Age — **FAILED**

Rule	accounts_maximum_age_login_defs
Severity	Medium
Description	To specify password maximum age for new accounts, edit the file /etc/login.defs and add or correct the following line: PASS_
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q shad
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting PASS_MAX_DAYS in /etc/login.defs is a standard password policy change that follows STIG hardening patterns and
Estimated Impact	authentication/authorization affected; Potential account lockout if users exceed maximum days

Remediation (3 attempt(s))

Attempt #	1
Commands	sed -i.bak -E 's/^[[:space:]]*#[[:space:]]*PASS_MAX_DAYS[[:space:]]+[0-9]+/PASS_MAX_DAYS 90/' /etc/login.defs
Scan Passed	✗
Success	✗
Duration	36.9s
Error	—
Attempt #	2
Commands	cp /etc/login.defs /etc/login.defs.bak, grep -n '\s*#\s*PASS_MAX_DAYS' /etc/login.defs, sed -i.bak '/\s*#\s*PASS_MAX_DAYS' /etc/login.defs
Scan Passed	✗
Success	✗
Duration	60.4s
Error	—
Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	33.1s
Error	—

Review Verdict

Approved	✗
Optimal	✗

Security Score	None/10
Feedback	The current remediation script is incomplete and would set PASS_MAX_DAYS to an empty value, potentially creating a broken
Concerns	The variable var_accounts_maximum_age_login_defs is empty, resulting in an invalid PASS_MAX_DAYS line.; No backup of

LLM Metrics

LLM Calls	2
Duration	33.1s
Total Tokens	7,011
Cost	\$0.0006
Agents	Remedy(1), Review(1)

accounts_minimum_age_login_defs: Set Password Minimum Age — SUCCESS

Rule	accounts_minimum_age_login_defs
Severity	Medium
Description	To specify password minimum age for new accounts, edit the file /etc/login.defs and add or correct the following line: PASS_M
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q shad
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting PASS_MIN_DAYS to 1 day is a standard password policy adjustment that does not affect system availability or critica
Estimated Impact	authentication/authorization affected; Potential for user lockout if set too high

Remediation (1 attempt(s))

Attempt #	1
Commands	sed -i -E 's/^[:space:]]*#?[:space:]]*PASS_MIN_DAYS[:space:]]+.*\$/PASS_MIN_DAYS 1/' /etc/login.defs
Scan Passed	✓
Success	✓
Duration	47.2s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will correctly set or create the PASS_MIN_DAYS entry and will resolve the vulnerability.
Concerns	—

QA Result

Safe	✓
Verdict	The plan correctly updates or adds the PASS_MIN_DAYS setting in /etc/login.defs without altering other configuration. The cl
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	44.8s

Total Tokens	50,189
Cost	\$0.0022
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

accounts_password_set_min_life_existing: Set Existing Passwords Minimum Age — **SUCCESS**

Rule	accounts_password_set_min_life_existing
Severity	Medium
Description	Configure non-compliant accounts to enforce a 24 hours/1 day minimum password lifetime by running the following command
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_min
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing the minimum password age for existing accounts is a standard password policy adjustment that does not affect sys
Estimated Impact	authentication/authorization affected

Remediation (1 attempt(s))

Attempt #	1
Commands	awk -v var="1" -F: '/^[^:]+:[^*]\/ && (\$4 < var \$4=="") {print \$1}' /etc/shadow xargs -r -I{} chage -m 1 {}
Scan Passed	✓
Success	✓
Duration	44.2s

Error	—
-------	---

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will correctly set all applicable accounts to a minimum password age of one day, addressing the vulnerability. Minor
Concerns	May modify system accounts that should remain exempt (e.g., root) if desired. ; If the system has a very large number of user

QA Result

Safe	✓
Verdict	The command sets a minimum password age of one day for all non-locked accounts, including system accounts such as root
Side Effects	Root account will be subject to a 24-hour minimum age, potentially delaying password changes for root.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	41.8s
Total Tokens	26,939
Cost	\$0.0016
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

use_pam_wheel_for_su: Enforce usage of pam_wheel for su authentication — **SUCCESS**

Rule	use_pam_wheel_for_su
------	----------------------

Severity	Medium
Description	To ensure that only users who are members of the wheel group can run commands with altered privileges through the su command
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q pam; then # uncomment the option i
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the pam_wheel.so use_uid line to /etc/pam.d/su is a standard STIG hardening step for PAM authentication and does i
Estimated Impact	authentication/authorization affected; Potential loss of su access for non-wheel users (intended)

Remediation (1 attempt(s))

Attempt #	1
Commands	sed '/^[:space:]]*#[[:space:]]*auth[:space:]]\+required[:space:]]\+pam_wheel\.so[:space:]]\+use_uid\$/s/^[:space:]]*#//' -i /etc
Scan Passed	✓
Success	✓
Duration	31.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan correctly implements the required PAM configuration to restrict su access to wheel group members and would resol

Concerns	The plan does not create a backup of /etc/pam.d/su before modifying it; in the event of an error the original configuration could be lost.
----------	--

QA Result

Safe	✓
Verdict	The remediation plan correctly implements the required PAM configuration for the su command. It uses targeted sed edits that are unlikely to affect other parts of the configuration.
Side Effects	Potential for misconfiguring the /etc/pam.d/su file if the sed pattern does not match exactly (minimally unlikely).; If sed fails, su may still work.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	28.1s
Total Tokens	25,779
Cost	\$0.0012
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

accounts_logon_fail_delay: Ensure the Logon Failure Delay is Set Correctly in login.defs — FAILED

Rule	accounts_logon_fail_delay
Severity	Medium
Description	To ensure the logon failure delay controlled by /etc/login.defs is set properly, add or correct the FAIL_DELAY setting in /etc/login.defs.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q shadow-utils && rpm --quiet -q kernel) { sed -i -e 's/^FAIL_DELAY=.*/FAIL_DELAY=9/' /etc/login.defs; }
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
------------------	---

Human Review	✗
Risk Level	LOW
Reason	The remediation involves a simple configuration change to /etc/login.defs, which is a standard PAM setting that controls login
Estimated Impact	authentication/authorization affected; None identified

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	17.5s
Error	—

Attempt #	2
Commands	grep -q '^[[:space:]]*#?[[:space:]]*FAIL_DELAY' /etc/login.defs
Scan Passed	✗
Success	✗
Duration	60.6s
Error	—

Attempt #	3
Commands	cp /etc/login.defs /etc/login.defs.bak, sed -i 's/^[[:space:]]*#?[[:space:]]*FAIL_DELAY[[:space:]]*.*\$/FAIL_DELAY 5/' /etc/login.
Scan Passed	✗
Success	✗

Duration	68.0s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	8/10
Feedback	The proposed plan adds or updates the FAIL_DELAY setting to a concrete numeric value (5 seconds), which satisfies the requirement.
Concerns	Handling of varying whitespace or comment syntax in existing lines may need a more precise sed pattern to avoid unintended replacements.

QA Result

Safe	✓
Verdict	The proposed plan correctly updates or creates the FAIL_DELAY setting in /etc/login.defs to a defined numeric value (5 seconds).
Side Effects	Introduces an additional 5-second delay when a login attempt fails; If the sed pattern matches an unintentional line containing a comment or other text, it may be modified.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	61.0s
Total Tokens	65,713
Cost	\$0.0027
Agents	Remedy(13), Review(1), Qa(1)

accounts_tmout: Set Interactive Session Timeout — **FAILED**

Rule	accounts_tmout
Severity	Medium
Description	Setting the TMOUT option in /etc/profile ensures that all user sessions will terminate based on inactivity. A value of 0 (zero) d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_tmo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves adding or updating a TMOUT variable in shell profile scripts, a standard STIG hardening pattern tha
Estimated Impact	authentication/authorization affected; May log out idle users

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	32.6s
Error	—
Attempt #	2
Commands	—
Scan Passed	✗
Success	✗

Duration	78.2s
Error	—
Attempt #	3
Commands	stat -c '%u %g %a' /etc/profile.d/z_tmout.sh, echo 'No changes required – TMOU already set to 900 in /etc/profile.d/z_tmout
Scan Passed	✗
Success	✗
Duration	39.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will correctly set an exported read-only TMOU of 900 for all user sessions by creating /etc/profile.d/z_tmout.sh, wh
Concerns	Overwrites existing /etc/profile.d/z_tmout.sh without backup, potentially deleting unrelated content if file already existed.; No e

QA Result

Safe	✓
Verdict	The remediation creates a single /etc/profile.d file that exports a read-only TMOU of 900, which is a standard and widely su
Side Effects	Any pre-existing /etc/profile.d/z_tmout.sh file with unrelated content will be overwritten, potentially losing custom configuratio
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
-----------	----

Duration	34.6s
Total Tokens	30,733
Cost	\$0.0015
Agents	Remedy(9), Review(1), Qa(1)

file_permission_user_init_files_root: Ensure All User Initialization Files Have Mode 0740 Or Less Permissive — **FAILED**

Rule	file_permission_user_init_files_root
Severity	Medium
Description	Set the mode of the user initialization files, including the root user, to 0740 with the following commands: \$ sudo chmod 0740
Recommendation	Remediation script: var_user_initialization_files_regex=" readarray -t interactive_users < <(awk -F: ' \$3==0 \$3>=1000 {print
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing permissions of user initialization files to 0740 is a standard STIG hardening step that does not risk lockout or critica
Estimated Impact	authentication/authorization affected; filesystems affected; Potential misapplication could affect user startup scripts, but unli

Remediation (3 attempt(s))

Attempt #	1
Commands	find /root /home -maxdepth 2 -type f \(-name '.bash_profile' -o -name '.bashrc' -o -name '.profile' -o -name '.bash_login' -o -na
Scan Passed	✗
Success	✗

Duration	44.9s
Error	—
Attempt #	2
Commands	bash -c "awk -F: '\$3==0 \$3>=1000 {print \$1, \$6, \$7}' /etc/passwd while read -r user homedir shell; do if [\"\$shell\" != '/s
Scan Passed	✗
Success	✗
Duration	274.8s
Error	—
Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	128.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan addresses the STIG requirement by enforcing 0740 permissions on standard shell initialization files for all interactive
Concerns	Command may produce errors if a user's home directory does not exist or is inaccessible.; All interactive users are not explici

QA Result

Safe	✓
------	---

Verdict	The remediation script strictly limits changes to common shell initialization files in the top-level of each home directory, does not
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	128.7s
Total Tokens	50,455
Cost	\$0.0026
Agents	Remedy(13), Review(1), Qa(1)

grub2_init_on_free: The system must booted with init_on_free=1 — DISCARDED

Rule	grub2_init_on_free
Severity	Medium
Description	Setting init_on_free=1 on boot guarantees that pages and heap objects are initialized right after they're freed, so it won't be p
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q grub2-common && rpm --quiet -q k
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Changing the kernel boot parameter via the bootloader can render the system unbootable or lock out remote access if applie

Estimated Impact	reboot required; Boot failure; Loss of SSH/console access; System breakage
------------------	--

LLM Metrics

LLM Calls	1
Duration	2.8s
Total Tokens	1,769
Cost	\$0.0003
Agents	Triage(1)

grub2_vsyscall_argument: Disable vsyscalls — DISCARDED

Rule	grub2_vsyscall_argument
Severity	Medium
Description	To disable use of virtual syscalls, add the argument vsyscall=none to the default GRUB 2 command line
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q grub2-commo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	X
Human Review	X
Risk Level	CRITICAL
Reason	Disabling vsyscalls requires modifying the GRUB2 kernel command line, a bootloader configuration change
Estimated Impact	reboot required; bootloader configuration; kernel parameter change; potential boot failure; service disruption

LLM Metrics

LLM Calls	1
-----------	---

Duration	3.8s
Total Tokens	1,801
Cost	\$0.0002
Agents	Triage(1)

grub2_admin_username: Set the Boot Loader Admin Username to a Non-Default Value — DISCARDED

Rule	grub2_admin_username
Severity	High
Description	The grub2 boot loader should have a superuser account and password protection enabled to protect boot-time settings. To m
Recommendation	Review and remediate: Set the Boot Loader Admin Username to a Non-Default Value
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	<i>x</i>
Human Review	<i>x</i>
Risk Level	CRITICAL
Reason	Changing the boot loader superuser account directly modifies the boot configuration; a misconfiguration can render the system
Estimated Impact	reboot required; authentication/authorization affected; Bootloader misconfiguration; Loss of boot capability; Administrative loc

LLM Metrics

LLM Calls	1
Duration	6.6s
Total Tokens	1,352
Cost	\$0.0001

Agents	Triage(1)
--------	-----------

grub2_password: Set Boot Loader Password in grub2 — DISCARDED

Rule	grub2_password
Severity	High
Description	The grub2 boot loader should have a superuser account and password protection enabled to protect boot-time settings. Since
Recommendation	Review and remediate: Set Boot Loader Password in grub2
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Setting a boot loader password is a bootloader change that can lock out the system if misconfigured, potentially preventing bo
Estimated Impact	reboot required; authentication/authorization affected; boot failure; loss of console access; bootloader misconfiguration

LLM Metrics

LLM Calls	1
Duration	4.7s
Total Tokens	1,316
Cost	\$0.0001
Agents	Triage(1)

package_rsyslog-gnutls_installed: Ensure rsyslog-gnutls is installed — SUCCESS

Rule	package_rsyslog-gnutls_installed
Severity	Medium
Description	TLS protocol support for rsyslog is installed. The rsyslog-gnutls package can be installed with the following command: \$ sudo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "r
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the rsyslog-gnutls package is a standard, non-disruptive package installation that does not affect authentication, net
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	rpm -q rsyslog-gnutls, dnf install -y rsyslog-gnutls
Scan Passed	✓
Success	✓
Duration	55.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10

Feedback	The plan will successfully install the rsyslog-gnutls package and resolve the vulnerability. It is functional, though it lacks a che
Concerns	—

QA Result

Safe	✓
Verdict	Installing the rsyslog-gnutls package is a simple, idempotent action that does not alter SSH, auditd, firewall, or networking con
Side Effects	Possible brief rsyslog service restart during package installation; Installation of additional GnuTLS packages as dependencies
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	33.3s
Total Tokens	19,985
Cost	\$0.0011
Agents	Triage(1), Remedy(8), Review(1), Qa(1)

rsyslog_encrypt_offload_actionsendstreamdriverauthmode: Ensure Rsyslog Authenticates Off-Loaded Audit Records — **REQUIRES_HUMAN_REVIEW**

Rule	rsyslog_encrypt_offload_actionsendstreamdriverauthmode
Severity	Medium
Description	Rsyslogd is a system utility providing support for message logging. Support for both internet and UNIX domain sockets enable
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslog
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The remediation involves editing rsyslog configuration files to enforce authentication of off-loaded audit records, a standard c
Estimated Impact	authentication/authorization affected; networking affected; Potential loss of remote audit log delivery if misconfigured

LLM Metrics

LLM Calls	1
Duration	3.0s
Total Tokens	1,423
Cost	\$0.0001
Agents	Triage(1)

rsyslog_encrypt_offload_actionsendstreamdrivermode: Ensure Rsyslog Encrypts Off-Loaded Audit Records —
REQUIRES_HUMAN_REVIEW

Rule	rsyslog_encrypt_offload_actionsendstreamdrivermode
Severity	Medium
Description	Rsyslogd is a system utility providing support for message logging. Support for both internet and UNIX domain sockets enable
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslog
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	LOW
Reason	The remediation involves editing rsyslog configuration files to enable encryption for offloaded audit records, a standard config
Estimated Impact	networking affected

LLM Metrics

LLM Calls	1
Duration	1.9s
Total Tokens	1,420
Cost	\$0.0002
Agents	Triage(1)

rsyslog_encrypt_offload_defaultnetstreamdriver: Ensure Rsyslog Encrypts Off-Loaded Audit Records —
REQUIRES_HUMAN_REVIEW

Rule	rsyslog_encrypt_offload_defaultnetstreamdriver
Severity	Medium
Description	Rsyslogd is a system utility providing support for message logging. Support for both internet and UNIX domain sockets enable
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslog
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The remediation involves editing rsyslog configuration files to set the DefaultNetstreamDriver to gtls, a standard security hard

Estimated Impact	networking affected; Potential temporary disruption of rsyslog service if configuration syntax is incorrect
------------------	---

LLM Metrics

LLM Calls	1
Duration	3.3s
Total Tokens	1,471
Cost	\$0.0001
Agents	Triage(1)

rsyslog_remote_access_monitoring: Ensure remote access methods are monitored in Rsyslog — **FAILED**

Rule	rsyslog_remote_access_monitoring
Severity	Medium
Description	Logging of remote access methods must be implemented to help identify cyber attacks and ensure ongoing compliance with
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslog
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding or ensuring rsyslog selectors for auth.*, authpriv.*, and daemon.* is a standard logging configuration change that does
Estimated Impact	authentication/authorization affected

Remediation (3 attempt(s))

Attempt #	1
-----------	---

Commands	—
Scan Passed	✗
Success	✗
Duration	37.7s
Error	—
Attempt #	2
Commands	touch /etc/rsyslog.conf, cp /etc/rsyslog.conf /etc/rsyslog.conf.bak, sed -i '1h;\$!d;s/^/\$(cat /etc/rsyslog.conf.bak)/g;h', rsyslogd -
Scan Passed	✗
Success	✗
Duration	323.6s
Error	—
Attempt #	3
Commands	mkdir -p /tmp/rsyslog_backup, cp -p /etc/rsyslog.conf /tmp/rsyslog.conf.bak, tar -czp -f /tmp/rsyslog_backup/rsyslog_d_backup
Scan Passed	✗
Success	✗
Duration	187.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10

Feedback	The plan will successfully add or uncomment the required rsyslog selectors, ensuring remote access events are logged. It pre
Concerns	No pre-restart syntax validation performed, risking rsyslog becoming non-functional if the modified config has errors.; Only /

QA Result

Safe	✓
Verdict	The remediation script performs a conservative in-place update of /etc/rsyslog.conf, adding or uncommenting the required a
Side Effects	Duplicate log entries if selectors already present in /etc/rsyslog.d/*.conf; Small chance of rsyslog reload failure due to syntax e
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	161.9s
Total Tokens	67,353
Cost	\$0.0044
Agents	Remedy(13), Review(1), Qa(1)

rsyslog_remote_loghost: Ensure Logs Sent To Remote Host — **FAILED**

Rule	rsyslog_remote_loghost
Severity	Medium
Description	To configure rsyslog to send logs to a remote log server, open /etc/rsyslog.conf and read and understand the last section of th
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then rsyslog_remote_lo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves editing /etc/rsyslog.conf to add a remote logging directive, which is a standard configuration change
Estimated Impact	networking affected; remote logging configuration; rsyslog service restart

Remediation (3 attempt(s))

Attempt #	1
Commands	echo '*. * @@remote-host' >> /etc/rsyslog.conf, systemctl reload rsyslog
Scan Passed	✗
Success	✗
Duration	61.4s
Error	—
Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	26.7s
Error	—
Attempt #	3
Commands	—
Scan Passed	✗

Success	<i>✗</i>
Duration	10.8s
Error	—

Review Verdict

Approved	<i>✗</i>
Optimal	<i>✗</i>
Security Score	4/10
Feedback	The provided script fragment is incomplete and would not correctly modify /etc/rsyslog.conf as intended. It lacks a full sed command.
Concerns	Incomplete sed command (truncated at 'LC_ALL=C sed -i --follow-sym'), so the file will not be modified successfully.; No back

LLM Metrics

LLM Calls	2
Duration	10.7s
Total Tokens	4,869
Cost	\$0.0004
Agents	Remedy(1), Review(1)

*network_configure_name_resolution: Configure Multiple DNS Servers in /etc/resolv.conf — **FAILED***

Rule	network_configure_name_resolution
Severity	Medium
Description	Determine whether the system is using local or DNS name resolution with the following command: \$ sudo grep hosts /etc/nss
Recommendation	Review and remediate: Configure Multiple DNS Servers in /etc/resolv.conf
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding or verifying multiple DNS servers in /etc/resolv.conf is a standard network configuration change that does not affect au
Estimated Impact	networking affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	21.7s
Error	—
Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	11.0s
Error	—
Attempt #	3
Commands	—
Scan Passed	✗

Success	<i>✗</i>
Duration	11.5s
Error	—

Review Verdict

Approved	<i>✗</i>
Optimal	<i>✗</i>
Security Score	None/10
Feedback	Review output was not valid JSON. Raw: {"finding_id":"network_configure_name_resolution","is_optimal":false,"approve":true
Concerns	Could not parse LLM response

LLM Metrics

LLM Calls	2
Duration	11.5s
Total Tokens	3,948
Cost	\$0.0003
Agents	Remedy(1), Review(1)

package_libreswan_installed: Install libreswan Package — SUCCESS

Rule	package_libreswan_installed
Severity	Medium
Description	The libreswan package provides an implementation of IPsec and IKE, which permits the creation of secure tunnels over untru
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "l
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the libreswan package is a standard package installation that does not affect critical services or authentication mechanisms
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	dnf install -y libreswan
Scan Passed	✓
Success	✓
Duration	47.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan will install the libreswan package and thereby meet the OpenSCAP finding. It's a straightforward implementation, but it's not idempotent
Concerns	No check for kernel-core prerequisite; could run on unsupported platforms.; No pre-installation existence check – though hard to implement

QA Result

Safe	✓
Verdict	Installing libreswan is idempotent and does not alter existing system configuration or services such as sshd, auditd, firewalld or SELinux

Side Effects	may install additional dependency packages and update existing libraries; may add SELinux policy modules for IPsec
Regression	<i>x</i>
Recommendation	Approve

LLM Metrics

LLM Calls	10
Duration	30.1s
Total Tokens	17,462
Cost	\$0.0011
Agents	Triage(1), Remedy(7), Review(1), Qa(1)

sysctl_net_ipv6_conf_all_accept_ra: Configure Accepting Router Advertisements on All IPv6 Interfaces — **SUCCESS**

Rule	sysctl_net_ipv6_conf_all_accept_ra
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.accept_ra kernel parameter, run the following command: \$ sudo sysctl -w net.ipv6.conf.all.accept_ra=0
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	<i>x</i>
Risk Level	LOW
Reason	Disabling IPv6 router advertisements via a sysctl setting is a standard hardening practice that does not affect authentication, a
Estimated Impact	networking affected; Potential loss of IPv6 connectivity if the environment relies on RA for address configuration

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv6.conf.all.accept_ra=0
Scan Passed	✓
Success	✓
Duration	61.2s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly targets the required sysctl setting, creates or updates a dedicated /etc/sysctl.d dropin, and applies the run
Concerns	Setting net.ipv6.conf.all.accept_ra to 0 disables IPv6 router advertisements; if the system relies on SLAAC for IPv6 connectiv

QA Result

Safe	✓
Verdict	The plan creates or updates a dedicated sysctl dropin to persistently set net.ipv6.conf.all.accept_ra to 0 and applies the cha
Side Effects	May remove automatically assigned IPv6 addresses on interfaces using SLAAC, potentially breaking services that rely solely
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	62.4s

Total Tokens	28,257
Cost	\$0.0016
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

sysctl_net_ipv6_conf_all_accept_redirects: Disable Accepting ICMP Redirects for All IPv6 Interfaces — **SUCCESS**

Rule	sysctl_net_ipv6_conf_all_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.accept_redirects kernel parameter, run the following command: \$ sudo sysctl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling ICMP redirects for IPv6 is a standard sysctl hardening measure that does not affect authentication, authorization, or
Estimated Impact	networking affected

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv6.conf.all.accept_redirects=0, sysctl -w net.ipv6.conf.all.accept_redirects=0, printf '# Disable IPv6 ICMP redire net.ipv6.conf.all.accept_redirects = 0 ' > /etc/sysctl.d/99-disable-icmp-redirects.conf
Scan Passed	✓
Success	✓

Duration	193.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will successfully enforce net.ipv6.conf.all.accept_redirects=0 at run time and persistently. Though it is functional, it d
Concerns	Potential conflict if other sysctl.d or sysctl.conf files explicitly set net.ipv6.conf.all.accept_redirects to a non-zero value – the n

QA Result

Safe	✓
Verdict	The remediation sets a standard sysctl parameter that disables ICMPv6 redirects, which is a common hardening step that do
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	22
Duration	175.2s
Total Tokens	67,628
Cost	\$0.0039
Agents	Triage(1), Remedy(19), Review(1), Qa(1)

sysctl_net_ipv6_conf_all_accept_source_route: Disable Kernel Parameter for Accepting Source-Routed Packets on all IPv6 Interfa...
— **SUCCESS**

Rule	sysctl_net_ipv6_conf_all_accept_source_route
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.accept_source_route kernel parameter, run the following command: \$ sudo s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Standard sysctl hardening change that does not affect authentication, authorization, or critical services; follows STIG pattern
Estimated Impact	networking affected

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv6.conf.all.accept_source_route=0
Scan Passed	✓
Success	✓
Duration	49.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10

Feedback	The plan correctly sets the parameter to 0 at runtime and adds a persistence file, which will resolve the vulnerability as long as
Concerns	The new config file may be overridden by a later loaded sysctl file that sets the parameter to 1.; The plan does not remove o

QA Result

Safe	✓
Verdict	The plan correctly disables source routing on IPv6, a non-essential feature that is rarely required by legitimate network serv
Side Effects	No impact on core services; disabling source routing may affect very rare applications that rely on it
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	45.1s
Total Tokens	28,754
Cost	\$0.0018
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

sysctl_net_ipv6_conf_all_forwarding: Disable Kernel Parameter for IPv6 Forwarding — SUCCESS

Rule	sysctl_net_ipv6_conf_all_forwarding
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.forwarding kernel parameter, run the following command: \$ sudo sysctl -w ne
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling IPv6 forwarding via sysctl is a standard, non-disruptive configuration change that does not affect authentication, au
Estimated Impact	networking affected; IPv6 forwarding disabled may affect IPv6 routing or services that rely on it

Remediation (1 attempt(s))

Attempt #	1
Commands	, sysctl -w net.ipv6.conf.all.forwarding=0
Scan Passed	✓
Success	✓
Duration	114.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The proposed plan is straightforward and will effectively disable IPv6 forwarding at boot and immediately. It follows standard p
Concerns	Higher-numbered sysctl.d files (e.g., 100*.conf) could override the 99file and re-enable forwarding.; Existing configuratio

QA Result

Safe	✓
Verdict	Disabling IPv6 forwarding at the system level is a low-impact change that does not affect local services such as sshd, auditd
Side Effects	—

Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	22
Duration	106.2s
Total Tokens	66,195
Cost	\$0.0032
Agents	Triage(1), Remedy(19), Review(1), Qa(1)

sysctl_net_ipv6_conf_default_accept_ra: Disable Accepting Router Advertisements on all IPv6 Interfaces by Default — **SUCCESS**

Rule	sysctl_net_ipv6_conf_default_accept_ra
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.default.accept_ra kernel parameter, run the following command: \$ sudo sysctl -v
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling IPv6 router advertisements via a sysctl setting is a standard hardening practice that does not affect authentication, a
Estimated Impact	networking affected

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	12.6s
Error	—
Attempt #	2
Commands	sysctl -w net.ipv6.conf.default.accept_ra=0, find /etc/sysctl.d /run/sysctl.d /usr/local/lib/sysctl.d -type f -name '*.conf' ! -name '99-docker.conf' -exec sed -i 's/^#net.ipv6.conf.default.accept_ra=0\$/net.ipv6.conf.default.accept_ra=0/' {} \;
Scan Passed	✓
Success	✓
Duration	89.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly sets the runtime value, creates a dedicated sysctl file, and cleans up other configuration files to prevent overwriting.
Concerns	The command assumes root privileges; execution should use sudo where necessary.; Pattern matching in the sed command is not robust.

QA Result

Safe	✓
Verdict	The remediation correctly sets the runtime value and persists it in its own sysctl file while commenting out any conflicting entries.
Side Effects	May reduce IPv6 connectivity on newly created interfaces, potentially affecting IPv6-only services such as IPv6-only SSH daemons.

Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	76.2s
Total Tokens	48,786
Cost	\$0.0026
Agents	Remedy(12), Review(1), Qa(1)

sysctl_net_ipv6_conf_default_accept_redirects: Disable Kernel Parameter for Accepting ICMP Redirects by Default on IPv6 Interfa...

— **SUCCESS**

Rule	sysctl_net_ipv6_conf_default_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.default.accept_redirects kernel parameter, run the following command: \$ sudo s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves setting a kernel sysctl parameter to a safe value and persisting it in /etc/sysctl.d, which is a standard
Estimated Impact	networking affected

Remediation (1 attempt(s))

Attempt #	1
Commands	, echo hello, sysctl -w net.ipv6.conf.default.accept_redirects=0
Scan Passed	✓
Success	✓
Duration	104.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The proposed plan correctly applies the runtime change and persists the setting in /etc/sysctl.d, addressing the identified vuln
Concerns	The remediation targets only net.ipv6.conf.default.accept_redirects; existing active interfaces may still permit redirects if not m

QA Result

Safe	✓
Verdict	The plan correctly disables the vulnerable parameter at runtime and persists it in a dedicated sysctl.d file. The change is isol
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	98.8s
Total Tokens	38,127

Cost	\$0.0021
Agents	Triage(1), Remedy(12), Review(1), Qa(1)

sysctl_net_ipv6_conf_default_accept_source_route: Disable Kernel Parameter for Accepting Source-Routed Packets on IPv6 Interfaces
... — **SUCCESS**

Rule	sysctl_net_ipv6_conf_default_accept_source_route
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.default.accept_source_route kernel parameter, run the following command: \$ su
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling source routing on IPv6 interfaces is a standard hardening practice that does not affect authentication, authorization,
Estimated Impact	networking affected; Potential impact on legacy applications that may rely on source routing (rare)

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	18.8s

Error	—
Attempt #	2
Commands	sysctl -w net.ipv6.conf.default.accept_source_route=0
Scan Passed	✓
Success	✓
Duration	278.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly sets the kernel parameter at runtime and persists the setting in /etc/sysctl.d/99-disable-source-route.conf, v
Concerns	Overwrites any existing content in /etc/sysctl.d/99-disable-source-route.conf, potentially removing other sysctl settings that us

QA Result

Safe	✓
Verdict	The plan sets the kernel parameter to 0 at runtime and writes a dedicated high■precedence sysctl file, which correctly mitigat
Side Effects	Potential loss of other sysctl settings if /etc/sysctl.d/99-disable-source-route.conf already existed with content; this can be avo
Regression	✗
Recommendation	Investigate

LLM Metrics

LLM Calls	23
Duration	269.4s

Total Tokens	70,835
Cost	\$0.0040
Agents	Remedy(19), Review(2), Qa(2)

sysctl_net_ipv4_conf_all_accept_redirects: Disable Accepting ICMP Redirects for All IPv4 Interfaces — **SUCCESS**

Rule	sysctl_net_ipv4_conf_all_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.accept_redirects kernel parameter, run the following command: \$ sudo sysctl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Standard sysctl hardening that does not affect authentication, authorization, or critical services; setting is safe and widely reco
Estimated Impact	networking affected; ICMP redirect exploitation

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	250.5s

Error	—
Attempt #	2
Commands	sysctl -w net.ipv4.conf.all.accept_redirects=0
Scan Passed	✓
Success	✓
Duration	67.2s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The proposed script correctly disables accept_redirects on all IPv4 interfaces and ensures persistence across reboots. It adds
Concerns	The `sed` pattern may not preserve existing comments or trailing whitespace.; The script does not create a dedicated override

QA Result

Safe	✓
Verdict	The script safely comments out any existing net.ipv4.conf.all.accept_redirects settings, disabling the vulnerable parameter with
Side Effects	May fail to comment lines that include trailing comments or whitespace, leaving the setting active; Does not reload sysctl imm
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	61.0s

Total Tokens	29,977
Cost	\$0.0015
Agents	Remedy(9), Review(1), Qa(1)

sysctl_net_ipv4_conf_all_accept_source_route: Disable Kernel Parameter for Accepting Source-Routed Packets on all IPv4 Interfa...

— **SUCCESS**

Rule	sysctl_net_ipv4_conf_all_accept_source_route
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.accept_source_route kernel parameter, run the following command: \$ sudo s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling source routing is a standard security hardening measure that does not affect authentication, authorization, or critica
Estimated Impact	networking affected; Potential loss of source■routing functionality for legacy applications

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv4.conf.all.accept_source_route=0
Scan Passed	✓
Success	✓

Duration	147.2s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	9/10
Feedback	The plan correctly sets the kernel parameter at runtime and ensures persistence via a dedicated sysctl dropin file. It preserves
Concerns	None significant; the plan may overwrite an existing config file but this is acceptable for the stated goal.

QA Result

Safe	✓
Verdict	The plan correctly disables source-routed packets for all IPv4 interfaces by setting the runtime value and persisting it via a d
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	20
Duration	139.6s
Total Tokens	59,273
Cost	\$0.0030
Agents	Triage(1), Remedy(17), Review(1), Qa(1)

*sysctl_net_ipv4_conf_all_forwarding: Disable Kernel Parameter for IPv4 Forwarding on all IPv4 Interfaces — **FAILED***

Rule	sysctl_net_ipv4_conf_all_forwarding
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.forwarding kernel parameter, run the following command: \$ sudo sysctl -w ne
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling IPv4 forwarding is a standard hardening step that does not affect user authentication or critical services. It only cha
Estimated Impact	networking affected; May affect routing or VPN services that rely on IP forwarding.

Remediation (3 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv4.conf.all.forwarding=0
Scan Passed	✗
Success	✗
Duration	77.0s
Error	—
Attempt #	2
Commands	—
Scan Passed	✗
Success	✗

Duration	202.6s
Error	—
Attempt #	3
Commands	find /etc/sysctl.d /run/sysctl.d -maxdepth 1 -type f -name "*.conf" -exec sed -i 's/^s*net\.\ipv4\.\conf\.\all\.\forwarding\s*=.*\$/# &/'
Scan Passed	✗
Success	✗
Duration	179.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	Plan will effectively disable IPv4 forwarding and persist the setting, but it could be strengthened by addressing potential overrr
Concerns	Existing sysctl.d or sysctl.conf files may contain the same parameter with a higher priority number, potentially overriding the 9

QA Result

Safe	✓
Verdict	The remediation correctly creates a persistent sysctl configuration that disables IPv4 forwarding, which is the intended fix. The
Side Effects	Potential disruption to services that rely on IP forwarding (e.g., Docker/Podman container networking, VPNs, NAT or bridge s
Regression	✗
Recommendation	Investigate

LLM Metrics

LLM Calls	16
-----------	----

Duration	170.5s
Total Tokens	63,727
Cost	\$0.0036
Agents	Remedy(14), Review(1), Qa(1)

sysctl_net_ipv4_conf_all_rp_filter: Enable Kernel Parameter to Use Reverse Path Filtering on all IPv4 Interfaces — **SUCCESS**

Rule	sysctl_net_ipv4_conf_all_rp_filter
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.rp_filter kernel parameter, run the following command: \$ sudo sysctl -w net.ipv4.conf.all.rp_filter=1
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling reverse path filtering is a standard sysctl configuration that does not affect authentication, authorization, or critical se
Estimated Impact	networking affected

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv4.conf.all.rp_filter=1
Scan Passed	✓
Success	✓

Duration	59.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan correctly applies the rp_filter setting both at runtime and persistently, which is sufficient to mitigate the vulnerability.
Concerns	Overwriting the full file may erase other useful settings or comments; risk of accidental removal requires careful review before

QA Result

Safe	✓
Verdict	The plan sets the critical rp_filter parameter correctly for both runtime and persistence. Overwriting the file may delete other c
Side Effects	May overwrite and remove any other sysctl directives that were previously present in /etc/sysctl.d/99-rp-filter.conf, which could
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	54.6s
Total Tokens	32,107
Cost	\$0.0018
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

sysctl_net_ipv4_conf_default_accept_redirects: Disable Kernel Parameter for Accepting ICMP Redirects by Default on IPv4 Interfa...
— **SUCCESS**

Rule	sysctl_net_ipv4_conf_default_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.default.accept_redirects kernel parameter, run the following command: \$ sudo s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves setting a standard sysctl parameter and ensuring persistence via /etc/sysctl.d, which is a routine co
Estimated Impact	networking affected

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv4.conf.default.accept_redirects=0
Scan Passed	✓
Success	✓
Duration	59.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10

Feedback	The plan would correctly set the kernel parameter at runtime and persist it across reboots. It follows recommended practices
Concerns	Missing sysctl reload after file creation (e.g., sysctl --system).; Requires root privileges; assumes user has them.; No error han

QA Result

Safe	✓
Verdict	The plan correctly applies the recommended kernel setting to disable ICMP redirects, which is a standard hardening measure
Side Effects	Local network traffic that relies on ICMP redirects may be slightly less responsive
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	59.5s
Total Tokens	26,561
Cost	\$0.0015
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

sysctl_net_ipv4_conf_default_rp_filter: Enable Kernel Parameter to Use Reverse Path Filtering on all IPv4 Interfaces by ... — **SUCCESS**

Rule	sysctl_net_ipv4_conf_default_rp_filter
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.default rp_filter kernel parameter, run the following command: \$ sudo sysctl -w r
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Standard sysctl persistence change that does not affect authentication, authorization, or critical services; safe to apply without
Estimated Impact	networking affected

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv4.conf.default.rp_filter=1, sysctl --system
Scan Passed	✓
Success	✓
Duration	49.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The proposed steps correctly set the kernel parameter at runtime and ensure persistence across reboots. The implementation
Concerns	Using a filename such as 99-rp_filter.conf may place the setting at lower priority than an existing file earlier in the alphabet tha

QA Result

Safe	✓
Verdict	The remediation sets the kernel parameter to its secure value immediately and writes a persistent definition in /etc/sysctl.d wi
Side Effects	Existing sysctl.d files earlier in priority may override the new setting if they also define net.ipv4.conf.default.rp_filter

Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	40.4s
Total Tokens	35,027
Cost	\$0.0017
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

sysctl_net_ipv4_icmp_echo_ignore_broadcasts: Enable Kernel Parameter to Ignore ICMP Broadcast Echo Requests on IPv4 Interface...

— **REQUIRES_HUMAN_REVIEW**

Rule	sysctl_net_ipv4_icmp_echo_ignore_broadcasts
Severity	Medium
Description	To set the runtime status of the net.ipv4.icmp_echo_ignore_broadcasts kernel parameter, run the following command: \$ sudo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	Setting net.ipv4.icmp_echo_ignore_broadcasts to 1 is a standard network hardening measure that does not affect authenticat
Estimated Impact	—

LLM Metrics

LLM Calls	1
Duration	1.7s
Total Tokens	1,245
Cost	\$0.0001
Agents	Triage(1)

sysctl_net_ipv4_tcp_syncookies: Enable Kernel Parameter to Use TCP Syncookies on Network Interfaces — **SUCCESS**

Rule	sysctl_net_ipv4_tcp_syncookies
Severity	Medium
Description	To set the runtime status of the net.ipv4.tcp_syncookies kernel parameter, run the following command: \$ sudo sysctl -w net.ipv4.tcp_syncookies=1
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling TCP syncookies is a standard kernel parameter hardening measure that does not affect authentication, authorization
Estimated Impact	networking affected; networking

Remediation (1 attempt(s))

Attempt #	1
Commands	grep -R --line-number -E 'net\.\ipv4\.\tcp_syncookies' /etc/sysctl.d 2>/dev/null, sysctl -w net.ipv4.tcp_syncookies=1
Scan Passed	✓

Success	✓
Duration	61.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan outlines the necessary steps to resolve the vulnerability but lacks explicit commands and file handling details. Clarify
Concerns	No specific mechanism described for commenting out existing duplicate settings; risk of accidental removal of legitimate user

QA Result

Safe	✓
Verdict	Enabling TCP syncookies is a benign policy change that does not disrupt active services such as SSH or auditd; it merely str
Side Effects	Possible accidental removal of legitimate user■added tcp_syncookies lines if pattern matching is too aggressive; potential for
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	20
Duration	52.0s
Total Tokens	49,911
Cost	\$0.0023
Agents	Triage(1), Remedy(15), Review(2), Qa(2)

sysctl_net_ipv4_conf_all_send_redirects: Disable Kernel Parameter for Sending ICMP Redirects on all IPv4 Interfaces — **SUCCESS**

Rule	sysctl_net_ipv4_conf_all_send_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.send_redirects kernel parameter, run the following command: \$ sudo sysctl -w net.ipv4.conf.all.send_redirects=0
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out and save the file: # echo 'net.ipv4.conf.all.send_redirects=0' >> /etc/sysctl.d/99-sysctl.conf; fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling ICMP redirects via a sysctl is a standard, low-risk configuration change that does not affect authentication, authorization, or data integrity.
Estimated Impact	networking affected

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv4.conf.all.send_redirects=0, sysctl -w net.ipv4.conf.all.send_redirects=0
Scan Passed	✓
Success	✓
Duration	122.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	7/10
Feedback	The plan will effectively disable ICMP redirects and ensure persistence across reboots. Minor ordering and edge case concerns.
Concerns	May prematurely skip the systemd-sysctl default config if it isn't a symlink; duplicate lines can appear if the 99-disable file co

QA Result

Safe	✓
Verdict	The plan correctly applies the sysctl setting at runtime, comments out any existing assignments that could conflict, and ensure
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	20
Duration	117.4s
Total Tokens	59,269
Cost	\$0.0037
Agents	Triage(1), Remedy(17), Review(1), Qa(1)

sysctl_net_ipv4_conf_default_send_redirects: Disable Kernel Parameter for Sending ICMP Redirects on all IPv4 Interfaces by De... — **SUCCESS**

Rule	sysctl_net_ipv4_conf_default_send_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.default.send_redirects kernel parameter, run the following command: \$ sudo sys
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves setting a kernel sysctl parameter to a safe value (0) and persisting it in /etc/sysctl.d, which is a standard practice.
Estimated Impact	networking affected

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	14.3s
Error	—
Attempt #	2
Commands	sysctl -w net.ipv4.conf.default.send_redirects=0
Scan Passed	✓
Success	✓
Duration	38.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	8/10
Feedback	The plan correctly sets the runtime sysctl value and persists it in /etc/sysctl.d, which will effectively disable sending of ICMP r
Concerns	The chosen file name (50-openscap.conf) may lead to precedence issues if other sysctl files with higher numbers override it;

QA Result

Safe	✓
Verdict	The remedy simply disables ICMP redirect sending, which is a low impact kernel parameter. The steps set the runtime value
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	31.6s
Total Tokens	30,569
Cost	\$0.0015
Agents	Remedy(10), Review(1), Qa(1)

kernel_module_atm_disabled: Disable ATM Support — **SUCCESS**

Rule	kernel_module_atm_disabled
Severity	Medium
Description	The Asynchronous Transfer Mode (ATM) is a protocol operating on network, data link, and physical layers, based on virtual c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the ATM kernel module is a straightforward configuration change that does not affect core system services such as
Estimated Impact	networking affected

Remediation (1 attempt(s))

Attempt #	1
Commands	chmod 0644 /etc/modprobe.d/atm.conf
Scan Passed	✓
Success	✓
Duration	57.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan addresses the vulnerability by ensuring both the install redirect and blacklist entries are present, and it takes care to
Concerns	Potentially will replace commented install lines (e.g., '# install atm') due to the sed pattern matching any line starting with 'inst

QA Result

Safe	✓
Verdict	The plan correctly ensures that the ATM module cannot be loaded by redirecting its install to /bin/false and by blacklisting it. A

Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	47.2s
Total Tokens	28,040
Cost	\$0.0017
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

kernel_module_can_disabled: Disable CAN Support — **SUCCESS**

Rule	kernel_module_can_disabled
Severity	Medium
Description	The Controller Area Network (CAN) is a serial communications protocol which was initially developed for automotive and is no
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the CAN kernel module via a modprobe configuration is a straightforward, non-disruptive change that does not affe
Estimated Impact	Potential loss of functionality for applications that rely on CAN communication

Remediation (1 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✓
Success	✓
Duration	32.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan will effectively disable the CAN module by adding the required directives. It is mostly correct but slightly lacks comp
Concerns	Use of sed with unescaped slashes may fail if /etc/modprobe.d/can.conf contains unexpected characters; current plan assum

QA Result

Safe	✓
Verdict	The plan simply ensures that the kernel module named "can" is prevented from loading by adding standard modprobe directiv
Side Effects	Potential duplication or formatting issues if the file already contains partially matching lines that start with whitespace or includ
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	32.3s

Total Tokens	23,743
Cost	\$0.0013
Agents	Triage(1), Remedy(8), Review(1), Qa(1)

kernel_module_sctp_disabled: Disable SCTP Support — **SUCCESS**

Rule	kernel_module_sctp_disabled
Severity	Medium
Description	The Stream Control Transmission Protocol (SCTP) is a transport layer protocol, designed to support the idea of message-oriented communication.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the SCTP kernel module is a standard hardening step that does not affect core system functionality or user access.
Estimated Impact	networking affected; SCTP may be required by some applications; disabling it could affect those applications' network commu

Remediation (1 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✓
Success	✓
Duration	69.2s

Error	—
-------	---

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly enforces the required restrictions on the SCTP kernel module by ensuring the appropriate install and black
Concerns	No explicit handling of SELinux file contexts after creation or modification.; File ownership and permissions are assumed to b

QA Result

Safe	✓
Verdict	The plan correctly ensures that the SCTP kernel module cannot be loaded by adding "install sctp /bin/false" and "blacklist sctp
Side Effects	Potential loss of functionality for applications or services that rely on SCTP (though such usage is uncommon in typical deploy
Regression	✗
Recommendation	Investigate

LLM Metrics

LLM Calls	11
Duration	34.5s
Total Tokens	23,116
Cost	\$0.0013
Agents	Triage(1), Remedy(8), Review(1), Qa(1)

kernel_module_bluetooth_disabled: Disable Bluetooth Kernel Module — **SUCCESS**

Rule	kernel_module_bluetooth_disabled
------	----------------------------------

Severity	Medium
Description	The kernel's module loading system can be configured to prevent loading of the Bluetooth module. Add the following to the ap
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the Bluetooth kernel module is a standard hardening step that does not affect critical services such as SSH, console
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✓
Success	✓
Duration	43.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan to overwrite /etc/modprobe.d/bluetooth.conf with the provided directives will effectively prevent the bluetooth kernel l

Concerns	Overwriting the file discards any pre-existing comments or custom directives that may have been added by administrators or
----------	--

QA Result

Safe	✓
Verdict	Overwriting /etc/modprobe.d/bluetooth.conf with 'install bluetooth /bin/false' and 'blacklist bluetooth' is the correct method to p
Side Effects	Existing custom directives or comments in /etc/modprobe.d/bluetooth.conf will be overwritten and lost.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	38.2s
Total Tokens	22,891
Cost	\$0.0013
Agents	Triage(1), Remedy(8), Review(1), Qa(1)

*networkmanager_dns_mode: NetworkManager DNS Mode Must Be Must Configured — **REQUIRES_HUMAN_REVIEW***

Rule	networkmanager_dns_mode
Severity	Medium
Description	The DNS processing mode in NetworkManager describes how DNS is processed on the system. Depending the mode some
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q NetworkManager; then var_networkk
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
------------------	---

Human Review	✓
Risk Level	LOW
Reason	The remediation involves editing NetworkManager configuration files to set the DNS mode, a standard network configuration
Estimated Impact	networking affected; Potential temporary loss of network connectivity during restart of NetworkManager; Incorrect value may

LLM Metrics

LLM Calls	1
Duration	3.0s
Total Tokens	1,265
Cost	\$0.0001
Agents	Triage(1)

rootfiles_configured: Ensure rootfiles tmpfile.d is Configured Correctly — **SUCCESS**

Rule	rootfiles_configured
Severity	Medium
Description	To set the mode of the root user initialization file /root/.bash_profile, ensure the following lines are is included in a file ending i
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q rootfiles; then find "/etc/tmpfiles.d/" -
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves adding or updating a simple configuration file in /etc/tmpfiles.d to set permissions on root's initializat

Estimated Impact	file permission change; root initialization files
------------------	---

Remediation (3 attempt(s))

Attempt #	1
Commands	systemd-tmpfiles --create
Scan Passed	✗
Success	✗
Duration	46.6s
Error	—
Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	23.3s
Error	—
Attempt #	3
Commands	—
Scan Passed	✓
Success	✓
Duration	48.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly writes a configuration file that satisfies the compliance requirement and does not disrupt existing system op
Concerns	The plan does not run systemd-tmpfiles to apply changes immediately, leaving a short window where the permissions may no

QA Result

Safe	✓
Verdict	The proposed plan creates a correct /etc/tmpfiles.d/rootfiles.conf with the required five C-entries, sets proper ownership and p
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	9
Duration	45.1s
Total Tokens	31,441
Cost	\$0.0018
Agents	Remedy(7), Review(1), Qa(1)

kernel_module_usb-storage_disabled: Disable Modprobe Loading of USB Storage Driver — **SUCCESS**

Rule	kernel_module_usb-storage_disabled
Severity	Medium
Description	To prevent USB storage devices from being used, configure the kernel module loading system to prevent automatic loading o

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the usb-storage kernel module via a modprobe configuration is a standard, low-risk hardening step that does not af
Estimated Impact	Loss of USB storage device functionality

Remediation (2 attempt(s))

Attempt #	1
Commands	test -f /etc/modprobe.d/usb-storage.conf touch /etc/modprobe.d/usb-storage.conf, cp /etc/modprobe.d/usb-storage.conf /etc
Scan Passed	✗
Success	✗
Duration	137.8s
Error	—
Attempt #	2
Commands	touch /etc/modprobe.d/usb-storage.conf
Scan Passed	✓
Success	✓
Duration	74.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly enforces the required modprobe configuration and prevents automatic loading of usb-storage, thereby add
Concerns	Original file ownership and permissions may not be preserved after editing.; If usb-storage is already loaded, the configuration

QA Result

Safe	✓
Verdict	The proposed plan correctly adds or updates /etc/modprobe.d/usb-storage.conf to block automatic loading of the usb-storage
Side Effects	No backup of the configuration file is created, so accidental loss of previous settings would not be recoverable without manual
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	66.7s
Total Tokens	40,318
Cost	\$0.0023
Agents	Remedy(10), Review(1), Qa(1)

mount_option_boot_efi_nosuid: Add nosuid Option to /boot/efi — **FAILED**

Rule	mount_option_boot_efi_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /boot/efi. The SUID and SGID permissions s

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the nosuid mount option to /boot/efi is a standard filesystem configuration change that does not affect authentication,
Estimated Impact	filesystems affected

Remediation (3 attempt(s))

Attempt #	1
Commands	sed -i '/boot/efi/ { /nosuid/! s/(vfat[[:blank:]]+)\([^[:blank:]]*\)/1\2,nosuid/' /etc/fstab, sed -i '/boot/efi/ { /nosuid/! s/^\([^]+\)
Scan Passed	✗
Success	✗
Duration	199.8s
Error	—
Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	46.1s
Error	—

Attempt #	3
Commands	—
Scan Passed	<i>✗</i>
Success	<i>✗</i>
Duration	42.6s
Error	—

Review Verdict

Approved	<i>✗</i>
Optimal	<i>✗</i>
Security Score	None/10
Feedback	Review output was not valid JSON. Raw: {"finding_id":"mount_option_boot_efi_nosuid","is_optimal":false,"approve":true,"feed
Concerns	Could not parse LLM response

LLM Metrics

LLM Calls	2
Duration	42.6s
Total Tokens	5,770
Cost	\$0.0004
Agents	Remedy(1), Review(1)

mount_option_boot_nodev: Add nodev Option to /boot — SUCCESS

Rule	mount_option_boot_nodev
Severity	Medium

Description	The nodev mount option can be used to prevent device files from being created in /boot. Legitimate character and block devices
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the nodev mount option to /boot is a standard hardening step that prevents device files from being created in the boot
Estimated Impact	reboot required; filesystems affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	140.5s
Error	—
Attempt #	2
Commands	cat /etc/fstab
Scan Passed	✗
Success	✗
Duration	74.2s
Error	—

Attempt #	3
Commands	cp /etc/fstab /etc/fstab.bak, echo hello, mount --options=nodev --remount /boot, mount -o remount,nodev /boot, mount -a -n
Scan Passed	✓
Success	✓
Duration	203.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will add the "nodev" option to the /boot entry in /etc/fstab, back up the original file, and immediately remount /boot, e
Concerns	The script does not perform a syntax validation of /etc/fstab after modification – a malformed entry could render the system un

QA Result

Safe	✓
Verdict	The remediation adds the nodev option to /boot in a controlled edit of /etc/fstab, backs up the original file, and remounts /boot
Side Effects	Possibility of a syntax error in /etc/fstab that could make the system unbootable if the backup is not restored promptly. If /boot
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	195.1s
Total Tokens	69,208

Cost	\$0.0040
Agents	Remedy(16), Review(1), Qa(1)

*mount_option_boot_nosuid: Add nosuid Option to /boot — **FAILED***

Rule	mount_option_boot_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /boot. The SUID and SGID permissions sho
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the nosuid mount option to /boot is a standard hardening step that does not affect authentication, networking, or critica
Estimated Impact	reboot required; filesystems affected; Potential impact if setuid programs on /boot are required for boot or system functionality

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	48.2s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	21.8s
Error	—
Attempt #	3
Commands	cp /etc/fstab /etc/fstab.bak, awk 'BEGIN{OFS="\t"} { if (\$NF~/\boot/ && \$4 !~ /\bnosuid\b/) { if (\$4=="") \$4="nosuid"; else if (\$4
Scan Passed	✗
Success	✗
Duration	177.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan correctly addresses the vulnerability by ensuring the nosuid option is added to the /boot entry in /etc/fstab and immediately
Concerns	The awk command uses -F'\t' which assumes tab-separated fields; many /etc/fstab files use spaces or a mixture of spaces and tabs

QA Result

Safe	✓
Verdict	The plan performs a safe backup, idempotently adds or preserves the nosuid option in /etc/fstab without altering other entries
Side Effects	The nosuid option may not take effect immediately if 'mount -o remount' does not reread fstab; it will apply after a reboot.; If /etc/fstab is modified after the plan runs, the changes will not be reflected until the next reboot.

Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	23
Duration	159.3s
Total Tokens	97,109
Cost	\$0.0061
Agents	Remedy(17), Review(3), Qa(3)

mount_option_dev_shm_nodev: Add nodev Option to /dev/shm — FAILED

Rule	mount_option_dev_shm_nodev
Severity	Medium
Description	The nodev mount option can be used to prevent creation of device files in /dev/shm. Legitimate character and block devices s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the nodev option to the /dev/shm mount is a standard hardening step that does not affect authentication, networking,
Estimated Impact	filesystems affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	8.6s
Error	—
Attempt #	2
Commands	cp /etc/fstab /etc/fstab.bak, echo '/dev/shm tmpfs tmpfs nodev 0 0' >> /etc/fstab, mount -o remount /dev/shm, ls -ld /dev
Scan Passed	✗
Success	✗
Duration	122.7s
Error	—
Attempt #	3
Commands	cp /etc/fstab /etc/fstab.bak-\$(date +%Y%m%d%H%M%S), awk ' { if (\$1 !~ /^#/) { if (\$2=="dev/shm") { if (!found++) { if (\$3 !~ /
Scan Passed	✗
Success	✗
Duration	161.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	8/10
Feedback	The plan correctly applies the nodev option to /dev/shm and removes duplicate entries, providing an immediate remount and
Concerns	The Python one-liner relies on a default Python interpreter; if unavailable it could fail.; The script may not handle lines where

QA Result

Safe	✓
Verdict	The plan methodically backs up /etc/fstab, ensures a single /dev/shm entry with nodev, removes duplicate lines, and safely re
Side Effects	Transient pause while mount -a remounts all filesystems, which could momentarily affect services with tight I/O timing, but typ
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	19
Duration	148.2s
Total Tokens	82,627
Cost	\$0.0046
Agents	Remedy(17), Review(1), Qa(1)

mount_option_dev_shm_noexec: Add noexec Option to /dev/shm — **FAILED**

Rule	mount_option_dev_shm_noexec
Severity	Medium
Description	The noexec mount option can be used to prevent binaries from being executed out of /dev/shm. It can be dangerous to allow
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the noexec option to /dev/shm is a standard hardening practice that prevents execution of binaries from a world-writable directory.
Estimated Impact	filesystems affected; Potential failure of applications that rely on executing binaries from /dev/shm

Remediation (3 attempt(s))

Attempt #	1
Commands	cp /etc/fstab /etc/fstab.bak_\$(date +%Y%m%d%H%M%S), sed -i '/^[:space:]*VdevVshm[:space:]/ { /noexec! s/\([:space:]\)/\1noexec/; }
Scan Passed	✗
Success	✗
Duration	171.4s
Error	—
Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	23.1s
Error	—
Attempt #	3
Commands	mount grep /dev/shm, cp /etc/fstab /etc/fstab.backup.noexec-remedial, , , awk '{ if(\$2=="/dev/shm") { if(\$4 !~ /noexec/) { if(\$4 ~ /noexec/) {
Scan Passed	✗

Success	✗
Duration	103.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan correctly adds the noexec option to the /dev/shm entry in /etc/fstab, keeps existing options, backs up the original file
Concerns	Missing explicit error handling after each step; a failure could leave the system in an inconsistent state.; The awk command d

QA Result

Safe	✓
Verdict	The plan correctly adds the noexec mount option to /dev/shm by editing /etc/fstab, backs up the original file, and remounts the
Side Effects	Possible failure of applications that legitimately execute binaries stored in /dev/shm (rare); Short-term remount operation ma
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	20
Duration	90.7s
Total Tokens	88,123
Cost	\$0.0042
Agents	Remedy(18), Review(1), Qa(1)

mount_option_dev_shm_nosuid: Add nosuid Option to /dev/shm — **FAILED**

Rule	mount_option_dev_shm_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /dev/shm. The SUID and SGID permissions
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the nosuid option to /dev/shm prevents execution of setuid programs in a world-writable directory, a standard hardening
Estimated Impact	filesystems affected

Remediation (3 attempt(s))

Attempt #	1
Commands	ls -l /etc/fstab, cp -p /etc/fstab /etc/fstab.bak, sed -i '/^s*\Vdev\shm\s\+/s#\(\s*[^\]]+\s\+[^]\+\s\+[^]\+\s\+\)\)([^\]]\+)\s#\1\2,nosuid
Scan Passed	✗
Success	✗
Duration	81.4s
Error	—
Attempt #	2
Commands	mount -o remount,nosuid /dev/shm, awk 'BEGIN{FS=OFS=" ";} { if (\$0 ~ /^[[:space:]]*#([^\s])/) {print; next; } if (\$1==" /dev/shm" &
Scan Passed	✗

Success	✗
Duration	207.4s
Error	—
Attempt #	3
Commands	cp -a /etc/fstab /etc/fstab.bak, awk '{if (\$1 ~ /^#/) {print; next} if (\$1==" /dev/shm") { if (\$4 !~ /nosuid/) { if (\$4 ~ /,/) { \$4=\$4 ",nosuid"; print; } else { print; } } } }
Scan Passed	✗
Success	✗
Duration	112.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan correctly targets the addition of the nosuid option to /dev/shm in /etc/fstab, which will resolve the vulnerability once the system is rebooted.
Concerns	Missing backup of /etc/fstab before modification.; No step to remount /dev/shm or notify that a reboot is required to apply the changes.

QA Result

Safe	✓
Verdict	Adding the nosuid option to the /dev/shm entry in /etc/fstab is a standard hardening step that does not require changes to running processes.
Side Effects	Requires remount or reboot for change to take effect; Potentially malformed fstab line if regex mispares; No data loss or corruption.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	21
Duration	84.6s
Total Tokens	97,969
Cost	\$0.0042
Agents	Remedy(19), Review(1), Qa(1)

mount_option_home_noexec: Add noexec Option to /home — **SUCCESS**

Rule	mount_option_home_noexec
Severity	Medium
Description	The noexec mount option can be used to prevent binaries from being executed out of /home. Add the noexec option to the for
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the noexec option to /home is a standard hardening practice that does not affect authentication, networking, or critical
Estimated Impact	filesystems affected; Potential disruption of user-installed binaries that rely on execution from /home

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗

Success	✗
Duration	58.0s
Error	—
Attempt #	2
Commands	sed -i -E 's (/dev/mapper/r1m-home\s+/\home\s+xf\s+)\defaults \1defaults,noexec ' /etc/fstab, mount -o remount,noexec /home
Scan Passed	✓
Success	✓
Duration	93.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan correctly adds the noexec option to an existing /home entry and remounts it, which would mitigate the vulnerability w
Concerns	sed expressions may mis-handle lines with unusual formatting or multiple options; they could introduce duplicate "noexec" or

QA Result

Safe	✓
Verdict	The plan correctly adds a noexec option to the existing /home entry in /etc/fstab and remounts it, which mitigates the vulnerab
Side Effects	Possible duplicate 'noexec' if line already contains it but regex walls it; may alter option order or formatting slightly; may silent
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	74.1s
Total Tokens	54,816
Cost	\$0.0028
Agents	Remedy(16), Review(1), Qa(1)

mount_option_home_nosuid: Add nosuid Option to /home — **FAILED**

Rule	mount_option_home_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /home. The SUID and SGID permissions sh
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the nosuid mount option to /home is a standard hardening practice that does not affect authentication, networking, or
Estimated Impact	filesystems affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗

Success	✗
Duration	48.1s
Error	—
Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	35.1s
Error	—
Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	27.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly adds the nosuid option to /home without disrupting unrelated configuration and includes a rollback backup.
Concerns	Using FS=OFS="\t" may not correctly parse /etc/fstab entries that use spaces rather than tabs, potentially leaving the wrong l

QA Result

Safe	✗
Verdict	The awk command assumes tab-separated fields; most /etc/fstab files use spaces, so the script may misparse or corrupt the
Side Effects	Potential fstab corruption (malformed entries); Incorrect or missing nosuid option if parsing fails; Remount failure if /home is n
Regression	✗
Recommendation	Investigate

LLM Metrics

LLM Calls	3
Duration	27.7s
Total Tokens	7,371
Cost	\$0.0007
Agents	Remedy(1), Review(1), Qa(1)

mount_option_nodev_nonroot_local_partitions: Add nodev Option to Non-Root Local Partitions — **FAILED**

Rule	mount_option_nodev_nonroot_local_partitions
Severity	Medium
Description	The nodev mount option prevents files from being interpreted as character or block devices. Legitimate character and block d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	Adding the nodev mount option to non-root local partitions is a standard hardening practice that prevents files from being inte
Estimated Impact	filesystems affected; Potential disruption of services that rely on device files in non-root partitions

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	123.6s
Error	—
Attempt #	2
Commands	awk -v OFS="\t" 'BEGIN{FS="[\t]+"} /^#/ {print;next} { if (\$1 ~ /^\/dev\/&& \$2 != "/") { if (\$4 ~ /^(,)nodev(, \$)/) {} else if (!(\$4)) {
Scan Passed	✗
Success	✗
Duration	140.5s
Error	—
Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	24.2s
Error	—

Review Verdict

Approved	<i>✗</i>
Optimal	<i>✗</i>
Security Score	None/10
Feedback	Review output was not valid JSON. Raw: {"finding_id":"mount_option_nodev_nonroot_local_partitions","is_optimal":false,"app
Concerns	Could not parse LLM response

LLM Metrics

LLM Calls	2
Duration	24.2s
Total Tokens	7,554
Cost	\$0.0008
Agents	Remedy(1), Review(1)

sysctl_kernel_core_pattern: Disable storing core dumps — *SUCCESS*

Rule	sysctl_kernel_core_pattern
Severity	Medium
Description	To set the runtime status of the kernel.core_pattern kernel parameter, run the following command: \$ sudo sysctl -w kernel.co
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	<i>✗</i>
Risk Level	LOW

Reason	Setting kernel.core_pattern to /bin/false is a standard sysctl change that prevents core dumps; it does not affect authentication
Estimated Impact	Potential loss of core dump data for debugging

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w kernel.core_pattern=' /bin/false'
Scan Passed	✓
Success	✓
Duration	57.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan addresses the core vulnerability correctly by setting the runtime sysctl and ensuring persistence via a dedicated file.
Concerns	The sysctl command uses the pipe character unquoted, which may be interpreted by the shell as a pipe unless properly escaped.

QA Result

Safe	✓
Verdict	The plan correctly disables core dumps by setting kernel.core_pattern to /bin/false at runtime and persists the setting with a c
Side Effects	Potential shell parsing error if the pipe character is not quoted or escaped in the sysctl command
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	53.6s
Total Tokens	33,199
Cost	\$0.0020
Agents	Triage(1), Remedy(11), Review(1), Qa(1)

sysctl_kernel_kexec_load_disabled: Disable Kernel Image Loading — **SUCCESS**

Rule	sysctl_kernel_kexec_load_disabled
Severity	Medium
Description	To set the runtime status of the kernel.kexec_load_disabled kernel parameter, run the following command: \$ sudo sysctl -w k
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting kernel.kexec_load_disabled via sysctl is a standard configuration change that does not affect authentication, networki
Estimated Impact	kernel parameter change

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗

Success	✗
Duration	13.7s
Error	—
Attempt #	2
Commands	sysctl -w kernel.kexec_load_disabled=1
Scan Passed	✓
Success	✓
Duration	153.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will effectively set and persist the kernel.kexec_load_disabled parameter, thereby disabling kernel image loading as
Concerns	The procedure does not explicitly comment out or remove prior occurrences of kernel.kexec_load_disabled in other sysctl con

QA Result

Safe	✓
Verdict	The plan correctly sets the kernel parameter at runtime and persists it via a dedicated sysctl dropin file. This is the standard
Side Effects	Possible duplicate sysctl entries leading to minor warning messages at boot
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	21
Duration	145.0s
Total Tokens	63,272
Cost	\$0.0038
Agents	Remedy(19), Review(1), Qa(1)

sysctl_kernel_unprivileged_bpf_disabled: Disable Access to Network bpf() Syscall From Unprivileged Processes — **SUCCESS**

Rule	sysctl_kernel_unprivileged_bpf_disabled
Severity	Medium
Description	To set the runtime status of the kernel.unprivileged_bpf_disabled kernel parameter, run the following command: \$ sudo sysctl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves setting a kernel sysctl parameter to disable unprivileged BPF access, a standard hardening step tha
Estimated Impact	networking affected; kernel parameter change; potential impact on applications using BPF

Remediation (2 attempt(s))

Attempt #	1
Commands	sysctl -w kernel.unprivileged_bpf_disabled=1, echo hello
Scan Passed	✗

Success	✗
Duration	78.2s
Error	—
Attempt #	2
Commands	sysctl -p /etc/sysctl.d/99-unprivileged-bpf.conf
Scan Passed	✓
Success	✓
Duration	70.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	—
Concerns	The plan may leave duplicate or conflicting parameter definitions if other files in /etc/sysctl.d or /run/sysctl.d also set kernel.un

QA Result

Safe	✓
Verdict	The remediation sets kernel.unprivileged_bpf_disabled to 1 via a dedicated sysctl file and reloads it immediately, which is the
Side Effects	Potential loss of functionality for user-space level tools that rely on unprivileged BPF (e.g. debugging or monitoring utilities).
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	64.2s
Total Tokens	43,005
Cost	\$0.0023
Agents	Remedy(12), Review(1), Qa(1)

sysctl_kernel_yama_ptrace_scope: Restrict usage of ptrace to descendant processes — **SUCCESS**

Rule	sysctl_kernel_yama_ptrace_scope
Severity	Medium
Description	To set the runtime status of the kernel.yama.ptrace_scope kernel parameter, run the following command: \$ sudo sysctl -w ke
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting kernel.yama.ptrace_scope to 1 is a standard sysctl configuration change that does not affect authentication, networkin
Estimated Impact	May limit debugging capabilities for legitimate processes

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w kernel.yama.ptrace_scope=1
Scan Passed	✓

Success	✓
Duration	34.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly targets the vulnerability by ensuring the runtime value is set and persisted in a high-preference file, while a
Concerns	Potential accidental commenting of lines that contain the keyword elsewhere (e.g., in comments or multiline values).; Using s

QA Result

Safe	✓
Verdict	The plan sets the required kernel parameter to a secure value, introduces a high-precedence sysctl file for persistence, and
Side Effects	Potential over-commenting of lines that merely reference the keyword in comments or non-configuration contexts, which mi
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	32.7s
Total Tokens	29,747
Cost	\$0.0015
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

sysctl_net_core_bpf_jit_harden: Harden the operation of the BPF just-in-time compiler — **SUCCESS**

Rule	sysctl_net_core_bpf_jit_harden
Severity	Medium
Description	To set the runtime status of the net.core.bpf_jit_harden kernel parameter, run the following command: \$ sudo sysctl -w net.co
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting net.core.bpf_jit_harden to 2 is a standard kernel sysctl change that does not affect authentication, networking services
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.core.bpf_jit_harden=2
Scan Passed	✓
Success	✓
Duration	42.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	None/10
Feedback	The plan addresses the vulnerability by ensuring net.core.bpf_jit_harden is set to 2 and removing conflicting entries. However
Concerns	Incomplete script (missing final configuration write, missing closing fi, possible syntax errors); Potential use of grep -P may no

QA Result

Safe	✓
Verdict	The remediation logic correctly comments out any preexisting values for net.core.bpf_jit_harden and will set the desired value
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	51.5s
Total Tokens	26,925
Cost	\$0.0015
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

sysctl_user_max_user_namespaces_no_remediation: Disable the use of user namespaces — SUCCESS

Rule	sysctl_user_max_user_namespaces_no_remediation
Severity	Medium
Description	To set the runtime status of the user.max_user_namespaces kernel parameter, run the following command: \$ sudo sysctl -w
Recommendation	Review and remediate: Disable the use of user namespaces
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling user namespaces via a sysctl setting is a standard kernel parameter change that does not affect authentication, net
Estimated Impact	May impact container deployments that rely on user namespaces; Requires verification that no critical services depend on us

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w user.max_user_namespaces=0
Scan Passed	✓
Success	✓
Duration	33.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly sets the runtime kernel parameter and persists the change. It is sufficient to remediate the vulnerability. Min
Concerns	The plan does not reload sysctl after creating the config file, which could delay persistence until next reboot.; Duplicate detect

QA Result

Safe	✓
Verdict	The remediation correctly sets the kernel parameter to disable user namespaces, which does not affect critical system service

Side Effects	Potential failure of container runtimes (docker, podman) or systemd ■ nspawn that rely on user namespaces for isolation.; Del
Regression	<i>x</i>
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	42.6s
Total Tokens	24,799
Cost	\$0.0014
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

service_systemd-coredump_disabled: Disable acquiring, saving, and processing core dumps — **SUCCESS**

Rule	service_systemd-coredump_disabled
Severity	Medium
Description	The systemd-coredump.socket unit is a socket activation of the systemd-coredump@.service which processes core dumps. E
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SOCKET_NAME=
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	<i>x</i>
Risk Level	LOW
Reason	Masking the systemd-coredump.socket unit is a standard hardening step that disables core dump processing without affecting
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	systemctl stop systemd-coredump.socket, systemctl mask systemd-coredump.socket
Scan Passed	✓
Success	✓
Duration	43.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan correctly stops and masks the systemd-coredump.socket unit, which disables core dump processing and resolves the issue.
Concerns	The script assumes it is run with root privileges; non-root execution will fail. The initial rpm check for kernel-core is unnecessary.

QA Result

Safe	✓
Verdict	Masking systemd-coredump.socket only disables core dump handling; it does not interfere with SSH, network, or essential services.
Side Effects	Loss of core dump logs for debugging
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	36.1s

Total Tokens	21,203
Cost	\$0.0011
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

coredump_disable_backtraces: Disable core dump backtraces — **SUCCESS**

Rule	coredump_disable_backtraces
Severity	Medium
Description	The ProcessSizeMax option in [Coredump] section of /etc/systemd/coredump.conf or in a drop-in file under /etc/systemd/core
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q syste
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting ProcessSizeMax=0 in systemd coredump configuration is a standard hardening step that prevents backtrace generati
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	systemctl daemon-reload, sed -i -E 's/^[[:space:]]*#?[[:space:]]*ProcessSizeMax=.*ProcessSizeMax=0/' /etc/systemd/coredu
Scan Passed	✓
Success	✓
Duration	151.9s

Error	—
-------	---

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	—
Concerns	The sed replacement may not uncomment lines that are commented, leaving the ProcessSizeMax key inactive.; The script as

QA Result

Safe	✓
Verdict	The plan correctly sets ProcessSizeMax=0 in all relevant coredump configuration files, preventing the generation of backtrace
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	17
Duration	135.0s
Total Tokens	50,796
Cost	\$0.0030
Agents	Triage(1), Remedy(14), Review(1), Qa(1)

coredump_disable_storage: Disable storing core dump — **SUCCESS**

Rule	coredump_disable_storage
------	--------------------------

Severity	Medium
Description	The Storage option in [Coredump] section of /etc/systemd/coredump.conf or a drop-in file in /etc/systemd/coredump.conf.d/*.conf
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q systemd rpm --quiet -q systemd-devel }
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling core dump storage is a standard configuration change that does not affect authentication, networking, or critical services
Estimated Impact	Loss of core dump data for debugging

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	121.4s
Error	—
Attempt #	2
Commands	sed -i '^[Coredump\]/,/^\$/s/^s*Storage\s*=.*\$/Storage=none/' /etc/systemd/coredump.conf, sed -i '^[Coredump\]/,/^\$/s/^s*Storage\s*=.*\$/Storage=none/' /etc/systemd/coredump.conf.d/*.conf
Scan Passed	✓
Success	✓
Duration	202.2s

Error	—
-------	---

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan covers all relevant files and correctly ensures that Storage=none is present in the last [Coredump] section of each c
Concerns	Complex sed expression may fail on edge■case files; lacks explicit backup of original files; idempotence not fully guaranteed

QA Result

Safe	✓
Verdict	The proposed remediation correctly sets Storage=none in all relevant systemd coredump configuration files. Modifying the co
Side Effects	None significant; only disables core dump storage, which is intended by the vulnerability remediation.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	20
Duration	189.3s
Total Tokens	88,627
Cost	\$0.0057
Agents	Remedy(18), Review(1), Qa(1)

disable_users_coredumps: Disable Core Dumps for All Users — **SUCCESS**

Rule	disable_users_coredumps
------	-------------------------

Severity	Medium
Description	To disable core dumps for all users, add the following line to /etc/security/limits.conf, or to a file within the /etc/security/limits.d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding '* hard core 0' to /etc/security/limits.conf or a dropin file is a standard STIG hardening step that does not affect auth
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	test -d /etc/security/limits.d && echo "DIR_EXISTS" echo "DIR_MISSING"
Scan Passed	✓
Success	✓
Duration	37.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly adds the required entry to /etc/security/limits.d/10-ssg-hardening.conf, which will disable core dumps for all

Concerns	sed pattern may uncomment a line with the wrong fragment if the file contains other commented lines starting with '* hard core
----------	--

QA Result

Safe	✓
Verdict	The plan adds or ensures an '* hard core 0' entry in /etc/security/limits.d/10-ssg-hardening.conf, which is the standard method
Side Effects	Potentially uncommenting a commented '* hard core' line that has a different value than 0 (unlikely on standard systems).; Po
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	34.4s
Total Tokens	30,813
Cost	\$0.0014
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

sysctl_kernel_randomize_va_space: Enable Randomized Layout of Virtual Address Space — **SUCCESS**

Rule	sysctl_kernel_randomize_va_space
Severity	Medium
Description	To set the runtime status of the kernel.randomize_va_space kernel parameter, run the following command: \$ sudo sysctl -w k
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
------------------	---

Human Review	✗
Risk Level	LOW
Reason	Setting kernel.randomize_va_space to 2 is a standard kernel hardening practice that does not affect authentication, networking
Estimated Impact	kernel parameter change

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	21.4s
Error	—
Attempt #	2
Commands	find /etc /run /usr/local/lib -type f \(-name "*.conf" -o -name "sysctl.conf" \) -not -path "/etc/sysctl.d/99-randomize-va-space.conf"
Scan Passed	✓
Success	✓
Duration	65.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly sets kernel.randomize_va_space to 2 at runtime and persists the value via a custom sysctl.d file. It follows

Concerns	The remediation does not explicitly remove or comment conflicting kernel.randomize_va_space entries that may exist in other
----------	---

QA Result

Safe	✓
Verdict	Setting kernel.randomize_va_space to 2 via a custom 99█<name>.conf file is the documented and supported way to enable
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	58.1s
Total Tokens	37,385
Cost	\$0.0019
Agents	Remedy(10), Review(1), Qa(1)

grub2_page_poison_argument: Enable page allocator poisoning — DISCARDED

Rule	grub2_page_poison_argument
Severity	Medium
Description	To enable poisoning of free pages, add the argument page_poison=1 to the default GRUB 2 command line for the Linux oper
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q grub2
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
------------------	---

Human Review	✗
Risk Level	CRITICAL
Reason	Modifying the GRUB configuration to add a kernel command line argument changes the bootloader settings, which can render the system unbootable.
Estimated Impact	reboot required; Boot failure; Potential loss of console access; System unbootable

LLM Metrics

LLM Calls	1
Duration	9.1s
Total Tokens	1,914
Cost	\$0.0002
Agents	Triage(1)

package_policycoreutils-python-utils_installed: Install policycoreutils-python-utils package — **SUCCESS**

Rule	package_policycoreutils-python-utils_installed
Severity	Medium
Description	The policycoreutils-python-utils package can be installed with the following command: \$ sudo dnf install policycoreutils-python-utils
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "policycoreutils-python-utils"; then echo "Installing policycoreutils-python-utils"; sudo dnf install policycoreutils-python-utils; fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing policycoreutils-python-utils is a standard package installation that does not affect authentication, networking, or files.

Estimated Impact	—
------------------	---

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	72.8s
Error	—

Attempt #	2
Commands	rpm -q --quiet kernel-core, rpm -q --quiet policycoreutils-python-utils, dnf install -y --best policycoreutils-python-utils
Scan Passed	✓
Success	✓
Duration	70.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will correctly install the missing package and resolve the vulnerability. However, it omits platform-specific checks and
Concerns	No kernel-core applicability check; Missing error handling for dnf failures; No logging of actions

QA Result

Safe	✓
------	---

Verdict	Installing polycoreutils-python-utils does not interfere with any critical services or authentication mechanisms; it is a non
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	43.5s
Total Tokens	32,095
Cost	\$0.0014
Agents	Remedy(11), Review(1), Qa(1)

service_kdump_disabled: Disable KDump Kernel Crash Analyzer (kdump) — SUCCESS

Rule	service_kdump_disabled
Severity	Medium
Description	The kdump service provides a kernel crash dump analyzer. It uses the kexec system call to boot a secondary kernel ("capture
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then systemctl_xe
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the kdump service is a standard service disable operation that does not affect authentication, networking, or filesystem

Estimated Impact	Loss of kernel crash dump data for forensic analysis
------------------	--

Remediation (2 attempt(s))

Attempt #	1
Commands	systemctl stop kdump.service, systemctl disable kdump.service
Scan Passed	✗
Success	✗
Duration	77.9s
Error	—
Attempt #	2
Commands	systemctl mask --now kdump.service, systemctl mask --now kdump.socket
Scan Passed	✓
Success	✓
Duration	46.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan will successfully disable and mask the kdump service and socket, which resolves the vulnerability. However, it omits
Concerns	No existence check before masking (systemctl mask will error if unit absent).; Does not reset the service to an inactive state i

QA Result

Safe	✓
------	---

Verdict	Masking kdump.service and kdump.socket (if present) simply prevents the kdump service from being started; it does not affect
Side Effects	Possible non-fatal error messages if kdump.service or kdump.socket do not exist; no impact on system operation.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	10
Duration	25.0s
Total Tokens	22,976
Cost	\$0.0013
Agents	Remedy(8), Review(1), Qa(1)

file_permissions_cron_d: Verify Permissions on cron.d — SUCCESS

Rule	file_permissions_cron_d
Severity	Medium
Description	To properly set the permissions of /etc/cron.d, run the command: \$ sudo chmod 0700 /etc/cron.d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.d/
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing permissions to 0700 on /etc/cron.d is a standard STIG hardening step that does not affect authentication, networking

Estimated Impact	Potential for cron jobs to fail if permissions are too restrictive
------------------	--

Remediation (1 attempt(s))

Attempt #	1
Commands	chmod 0700 /etc/cron.d
Scan Passed	✓
Success	✓
Duration	20.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The single command will correctly set /etc/cron.d to 0700, meeting the STIG requirement. However, the plan lacks pre-check
Concerns	Lacks verification of current permissions before change; Does not account for intentional use of group or others access in spe

QA Result

Safe	✓
Verdict	Setting /etc/cron.d to 0700 restricts directory access to root only, which is acceptable because the cron daemon runs as root
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	10
-----------	----

Duration	21.2s
Total Tokens	15,744
Cost	\$0.0008
Agents	Triage(1), Remedy(7), Review(1), Qa(1)

file_permissions_cron_daily: Verify Permissions on cron.daily — **SUCCESS**

Rule	file_permissions_cron_daily
Severity	Medium
Description	To properly set the permissions of /etc/cron.daily, run the command: \$ sudo chmod 0700 /etc/cron.daily
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.da
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing permissions to 0700 on /etc/cron.daily is a standard hardening step that does not affect system services or authent
Estimated Impact	filesystems affected; May prevent non-root users from adding cron jobs to /etc/cron.daily

Remediation (1 attempt(s))

Attempt #	1
Commands	chmod 0700 /etc/cron.daily
Scan Passed	✓
Success	✓

Duration	23.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly addresses the vulnerability by setting /etc/cron.daily to 0700, thereby restricting access to root only. While
Concerns	The plan assumes that setting 0700 will not break any cron jobs that might rely on group or other permissions; edge cases co

QA Result

Safe	✓
Verdict	Setting /etc/cron.daily to 0700 restricts access to root only, which is the intended restraint. The cron daemon runs as root and
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	10
Duration	25.4s
Total Tokens	16,176
Cost	\$0.0010
Agents	Triage(1), Remedy(7), Review(1), Qa(1)

file_permissions_cron_hourly: Verify Permissions on cron.hourly — SUCCESS

Rule	file_permissions_cron_hourly
Severity	Medium
Description	To properly set the permissions of /etc/cron.hourly, run the command: \$ sudo chmod 0700 /etc/cron.hourly
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.h
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting /etc/cron.hourly to 0700 is a standard STIG hardening step that does not affect authentication, networking, or critical s
Estimated Impact	Cron jobs may fail if permissions are too restrictive, but 0700 is the recommended setting for system cron directories.

Remediation (1 attempt(s))

Attempt #	1
Commands	chmod 0700 /etc/cron.hourly
Scan Passed	✓
Success	✓
Duration	47.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10

Feedback	Plan would effectively remove the unauthorized permissions on /etc/cron.hourly and set correct ownership, thereby addressing
Concerns	—

QA Result

Safe	✓
Verdict	Changing /etc/cron.hourly ownership to root:root and setting permissions to 0700 does not affect any running services; cron r
Side Effects	Non■root users will be unable to create or modify scripts in /etc/cron.hourly
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	45.2s
Total Tokens	21,240
Cost	\$0.0013
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

file_permissions_cron_monthly: Verify Permissions on cron.monthly — **SUCCESS**

Rule	file_permissions_cron_monthly
Severity	Medium
Description	To properly set the permissions of /etc/cron.monthly, run the command: \$ sudo chmod 0700 /etc/cron.monthly
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.m
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting /etc/cron.monthly to 0700 is a standard file permission hardening step that does not affect authentication, networking,
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	chmod 0700 /etc/cron.monthly, ls -ld /etc/cron.monthly
Scan Passed	✓
Success	✓
Duration	21.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly applies the required permission change; however, it lacks a pre-check to avoid unnecessary chmod operat
Concerns	No verification of current permissions before applying chmod; may run chmod unnecessarily.; No handling of existing ACLs o

QA Result

Safe	✓
Verdict	Changing /etc/cron.monthly to 0700 correctly restricts access to root only and addresses the reported security issue without a
Side Effects	Non■root users and scripts will no longer be able to list or read files in /etc/cron.monthly, which may break custom cron setup

Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	19.5s
Total Tokens	18,318
Cost	\$0.0009
Agents	Triage(1), Remedy(8), Review(1), Qa(1)

file_permissions_cron_weekly: Verify Permissions on cron.weekly — SUCCESS

Rule	file_permissions_cron_weekly
Severity	Medium
Description	To properly set the permissions of /etc/cron.weekly, run the command: \$ sudo chmod 0700 /etc/cron.weekly
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.w
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing the permissions of /etc/cron.weekly to 0700 is a standard hardening step that does not affect authentication, network
Estimated Impact	filesystems affected

Remediation (1 attempt(s))

Attempt #	1
Commands	chmod 0700 /etc/cron.weekly
Scan Passed	✓
Success	✓
Duration	18.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly sets the directory permissions to 0700, which addresses the vulnerability. A simple pre-check or conditional
Concerns	—

QA Result

Safe	✓
Verdict	Changing /etc/cron.weekly permissions to 0700 restricts access to the root user only, which is the intended owner of cron jobs
Side Effects	Cron jobs located in /etc/cron.weekly may not be executed if they were previously added by non-root users.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	10
Duration	21.7s
Total Tokens	14,992

Cost	\$0.0010
Agents	Triage(1), Remedy(7), Review(1), Qa(1)

package_fapolicyd_installed: Install fapolicyd Package — **SUCCESS**

Rule	package_fapolicyd_installed
Severity	Medium
Description	The fapolicyd package can be installed with the following command: \$ sudo dnf install fapolicyd
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "f
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the fapolicyd package is a standard package installation that does not affect authentication, networking, or filesystem
Estimated Impact	package installation

Remediation (1 attempt(s))

Attempt #	1
Commands	dnf install -y fapolicyd, systemctl enable --now fapolicyd
Scan Passed	✓
Success	✓
Duration	183.5s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	8/10
Feedback	The plan correctly checks for existing installation and performs an idempotent dnf install if missing, which will resolve the vuln
Concerns	The plan does not verify whether the fapolicyd service is enabled and running after installation. If the service is not started, th

QA Result

Safe	✓
Verdict	The proposed plan simply checks for the presence of the fapolicyd package and installs it if missing using dnf. Installing a sec
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	43.2s
Total Tokens	39,688
Cost	\$0.0018
Agents	Triage(1), Remedy(13), Review(1), Qa(1)

service_fapolicyd_enabled: Enable the File Access Policy Service — **SUCCESS**

Rule	service_fapolicyd_enabled
Severity	Medium
Description	The File Access Policy service should be enabled. The fapolicyd service can be enabled with the following command: \$ sudo

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling the fapolicyd service is a standard service enablement that does not affect authentication, networking, or filesystem
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	9.0s
Error	—
Attempt #	2
Commands	systemctl unmask fapolicyd.service
Scan Passed	✗
Success	✗
Duration	47.1s
Error	—

Attempt #	3
Commands	systemctl enable --now fapolicyd.service, systemctl is-active --quiet fapolicyd.service; echo \$?, systemctl is-enabled fapolicyd
Scan Passed	✓
Success	✓
Duration	48.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan will enable and start the fapolicyd service in most normal situations, which satisfies the vulnerability remediation req
Concerns	Potential failure if fapolicyd.service is masked, as enable --now will error and leave the service disabled. The plan does not un

QA Result

Safe	✓
Verdict	Executing 'systemctl enable --now fapolicyd.service' will enable and start the File Access Policy Service without affecting critic
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	35.8s
Total Tokens	27,196

Cost	\$0.0014
Agents	Remedy(9), Review(1), Qa(1)

fapolicy_default_deny: Configure Fapolicy Module to Employ a Deny-all, Permit-by-exception Policy to AI... — **REQUIRES_HUMAN_REVIEW**

Rule	fapolicy_default_deny
Severity	Medium
Description	The Fapolicy module must be configured to employ a deny-all, permit-by-exception policy to allow the execution of authorized
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then cat > /etc/fapolicyd
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The remediation script applies a standard deny-all rule and sets permissive mode to 0, a common STIG hardening practice th
Estimated Impact	Potential to block execution of system binaries if allow rules are not properly configured

LLM Metrics

LLM Calls	1
Duration	5.2s
Total Tokens	1,519
Cost	\$0.0001
Agents	Triage(1)

package_postfix_installed: The Postfix package is installed — **SUCCESS**

Rule	package_postfix_installed
Severity	Medium
Description	A mail server is required for sending emails. The postfix package can be installed with the following command: \$ sudo dnf ins
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "p
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the Postfix package is a standard package installation that does not affect authentication, critical services, or system
Estimated Impact	networking affected

Remediation (1 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✓
Success	✓
Duration	—
Error	can't concat str to bytes

LLM Metrics

LLM Calls	8
Duration	36.9s

Total Tokens	12,710
Cost	\$0.0011
Agents	Triage(1), Remedy(5), Review(1), Qa(1)

package_s-nail_installed: The s-nail Package Is Installed — **SUCCESS**

Rule	package_s-nail_installed
Severity	Medium
Description	A mail server is required for sending emails. The s-nail package can be installed with the following command: \$ sudo dnf install s-nail
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "s-nail"; then dnf install s-nail
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the s-nail package is a standard package installation that does not affect authentication, networking, or critical services.
Estimated Impact	—

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	47.6s

Error	—
Attempt #	2
Commands	sh -c "if rpm -q --quiet kernel-core; then dnf install -y s-nail; fi"
Scan Passed	✓
Success	✓
Duration	147.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The script correctly ensures s-nail is installed only on systems with kernel-core, meeting the OpenSCAP remediation requirements.
Concerns	The double check for s-nail presence is unnecessary because `dnf install -y` is idempotent and will silently skip already-installed packages.

QA Result

Safe	✓
Verdict	The command only installs the s-nail package when kernel-core is present; the installation is idempotent and does not modify other system components.
Side Effects	Potential installation of s-nail dependency packages, but no critical packages are removed or modified.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	43.6s

Total Tokens	27,874
Cost	\$0.0016
Agents	Remedy(9), Review(1), Qa(1)

postfix_client_configure_mail_alias: Configure System to Forward All Mail For The Root Account — **FAILED**

Rule	postfix_client_configure_mail_alias
Severity	Medium
Description	Make sure that mails delivered to root user are forwarded to a monitored email address. Make sure that the address is a valid email address.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_postfix_root_mail_alias="root@localhost.localdomain"; fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding or updating the root mail alias in /etc/aliases is a straightforward configuration change that does not affect authentication or mail delivery.
Estimated Impact	filesystems affected; Potential misconfiguration of alias could result in root mail not being forwarded

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	8.1s

Error	—
Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	26.0s
Error	—
Attempt #	3
Commands	read_file /etc/aliases, sed -i '/^#\?root:/d' /etc/aliases, printf "root: monitored@example.com\n" >> /etc/aliases, newaliases, sy
Scan Passed	✗
Success	✗
Duration	53.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan will correctly create or update the root alias so that mail to root is forwarded, thereby mitigating the vulnerability. It fo
Concerns	Hardcoded monitored email address (needs to be overridden per environment).; No validation of the email address syntax or

QA Result

Safe	✓
Verdict	The plan correctly updates /etc/aliases, rebuilds the alias database, and reloads Postfix, addressing the vulnerability without i

Side Effects	Residual root alias line if it starts with whitespace (sed pattern does not match leading spaces).; If Postfix is not installed or not configured
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	14
Duration	44.2s
Total Tokens	43,254
Cost	\$0.0020
Agents	Remedy(12), Review(1), Qa(1)

chronyd_or_ntpd_set_maxpoll: Configure Time Service Maxpoll Interval — **SUCCESS**

Rule	chronyd_or_ntpd_set_maxpoll
Severity	Medium
Description	The maxpoll should be configured to in /etc/ntp.conf or /etc/chrony.conf (or /etc/chrony.d/) to continuously poll time servers. The default value is 128, which is not recommended for high-precision time servers.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { (rpm --quiet -q chrony && sed -i -e 's/^maxpoll 128\$/maxpoll 1024/' /etc/chrony.conf) (rpm --quiet -q ntp && sed -i -e 's/^maxpoll 128\$/maxpoll 1024/' /etc/ntp.conf) }
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation only modifies the maxpoll setting in the NTP/chrony configuration files, a standard and low-risk configuration change.
Estimated Impact	—

Remediation (2 attempt(s))

Attempt #	1
Commands	sed -i -E 's/(maxpoll)[0-9]+/maxpoll 6/g' /etc/chrony.conf, sed -i -E 's/(maxpoll)[0-9]+/maxpoll 6/g' /etc/chrony.conf
Scan Passed	✗
Success	✗
Duration	89.5s
Error	—
Attempt #	2
Commands	sed -i -e "s/^\s*#\s*(server\ pool\ peer)\1/" -e "/^\s*(server\ pool\ peer)/{ /maxpoll!/s\$/ maxpoll 6/ }" /etc/chrony.conf, rpm -q
Scan Passed	✓
Success	✓
Duration	177.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan would resolve the vulnerability if executed correctly, but the sed syntax contains errors that could prevent successful
Concerns	Sed command patterns are incorrectly quoted/escaped, which could leave configuration lines unchanged or produce malformed

QA Result

Safe	✓
Verdict	The plan modifies only time service configuration files and restarts the services only if they are present. It does not touch SS

Side Effects	Potential misconfiguration of maxpoll due to regex inaccuracies, which could lead to chronyd/ntpd failures or suboptimal performance
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	149.4s
Total Tokens	87,961
Cost	\$0.0051
Agents	Remedy(16), Review(1), Qa(1)

chronyd_server_directive: Ensure Chrony is only configured with the server directive — **SUCCESS**

Rule	chronyd_server_directive
Severity	Medium
Description	Check that Chrony only has time sources configured with the server directive.
Recommendation	Review and remediate: Ensure Chrony is only configured with the server directive
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The fix involves editing the chrony configuration file to remove non-server directives, which is a straightforward configuration change
Estimated Impact	networking affected; Potential time synchronization issues if misconfigured

Remediation (1 attempt(s))

Attempt #	1
Commands	cp /etc/chrony.conf /etc/chrony.conf.bak, sed -i 's/^s*pool\b/server/' /etc/chrony.conf, sed -i '/^s*sourcedir\b/d' /etc/chrony.conf
Scan Passed	✓
Success	✓
Duration	86.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	Plan achieves the core objective of removing pool and manual directives, but it does not address all possible non-server
Concerns	Potential oversight of other non-server directives (e.g., peer) that may remain in the configuration.; No pre-restart validation

QA Result

Safe	✓
Verdict	The plan safely removes non-server time source directives (pool, manual) and restarts chronyd without impacting critical serv
Side Effects	Possible temporary time drift until new server sources synchronize; If no server directives remain, chronyd may stop providing
Regression	✗
Recommendation	Investigate

LLM Metrics

LLM Calls	18
Duration	76.1s

Total Tokens	46,252
Cost	\$0.0025
Agents	Triage(1), Remedy(13), Review(2), Qa(2)

disable_host_auth: Disable Host-Based Authentication — **SUCCESS**

Rule	disable_host_auth
Severity	Medium
Description	SSH's cryptographic host-based authentication is more secure than .rhosts authentication. However, it is not recommended th
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves adding or ensuring a single SSH configuration directive (HostbasedAuthentication no) in a dedicate
Estimated Impact	authentication/authorization affected; SSH configuration change; Potential misconfiguration if syntax is incorrect

Remediation (1 attempt(s))

Attempt #	1
Commands	mkdir -p /etc/ssh/sshd_config.d, echo "HostbasedAuthentication no" >> /etc/ssh/sshd_config.d/01-complianceascode-reinforc
Scan Passed	✓
Success	✓
Duration	131.5s

Error	—
-------	---

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan creates a dedicated configuration file, cleans any existing HostbasedAuthentication directives, appends the explicit s
Concerns	The plan only sanitizes the new file; any HostbasedAuthentication line in /etc/ssh/sshd_config or other included files could stil

QA Result

Safe	✓
Verdict	The proposed plan accurately removes any existing HostbasedAuthentication directives across the main sshd_config and all
Side Effects	transient SSH session drop during systemctl reload
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	20
Duration	123.9s
Total Tokens	63,018
Cost	\$0.0043
Agents	Triage(1), Remedy(15), Review(2), Qa(2)

sshd_disable_compression: Disable Compression Or Set Compression to delayed — **SUCCESS**

Rule	sshd_disable_compression
------	--------------------------

Severity	Medium
Description	Compression is useful for slow network connections over long distances but can cause performance issues on local LANs. If
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_sshd_disable
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling or delaying SSH compression is a standard SSH configuration change that follows STIG hardening patterns and do
Estimated Impact	authentication/authorization affected

Remediation (1 attempt(s))

Attempt #	1
Commands	sed -i "s/^\s*#\? \s*Compression\b.*\$/Compression no/" /etc/ssh/sshd_config, grep -q "^\s*Compression" /etc/ssh/sshd_config
Scan Passed	✓
Success	✓
Duration	88.2s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan correctly targets the compression setting in both the main sshd_config and any fragment files, applies the required v

Concerns	Plan may append a second 'Compression no' line if only a commented line is present in a file, leading to duplicate directives.
----------	--

QA Result

Safe	✓
Verdict	The proposed plan correctly ensures the Compression setting is set to "no" both in the main sshd_config and any fragment files.
Side Effects	Possible duplicate "Compression no" entries if commented lines remain; sshd restart failure if a syntax error is introduced.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	80.7s
Total Tokens	44,706
Cost	\$0.0025
Agents	Triage(1), Remedy(13), Review(1), Qa(1)

sshd_disable_gssapi_auth: Disable GSSAPI Authentication — **FAILED**

Rule	sshd_disable_gssapi_auth
Severity	Medium
Description	Unless needed, SSH should not permit extraneous or unnecessary authentication mechanisms like GSSAPI. The default SSH configuration includes GSSAPI authentication, which is not required for most systems.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/sshd_config.d; echo 'GSSAPIAuthentication no' > /etc/ssh/sshd_config.d/01_gssapi.conf; systemctl restart sshd
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
------------------	---

Human Review	✗
Risk Level	LOW
Reason	Disabling GSSAPIAuthentication is a standard SSH hardening step that does not risk lockout or critical service disruption.
Estimated Impact	authentication/authorization affected; SSH authentication mechanism

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	36.3s
Error	—
Attempt #	2
Commands	mkdir -p /etc/ssh/sshd_config.d, touch /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf, chmod 0640 /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf
Scan Passed	✗
Success	✗
Duration	86.9s
Error	—
Attempt #	3
Commands	ls -l /etc/ssh/sshd_config.d/, systemctl restart sshd
Scan Passed	✗
Success	✗

Duration	62.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly disables GSSAPIAuthentication by ensuring the Include directive exists and adding a dedicated overrides f
Concerns	If any other included file in /etc/ssh/sshd_config.d/ has GSSAPIAuthentication set after this file, it could re-enable the option.;

QA Result

Safe	✓
Verdict	The proposed steps add an Include directive if missing, create a dedicated overrides file that sets GSSAPIAuthentication no,
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	55.4s
Total Tokens	48,874
Cost	\$0.0026
Agents	Remedy(11), Review(1), Qa(1)

sshd_disable_rhosts: Disable SSH Support for .rhosts Files — **SUCCESS**

Rule	sshd_disable_rhosts
Severity	Medium
Description	SSH can emulate the behavior of the obsolete rsh command in allowing users to enable insecure access to their accounts via
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling IgnoreRhosts is a standard SSH hardening step that does not risk lockout or system breakage.
Estimated Impact	authentication/authorization affected; SSH configuration change

Remediation (1 attempt(s))

Attempt #	1
Commands	mkdir -p /etc/ssh/sshd_config.d, , sed -i '/^\s*IgnoreRhosts\s\+\/Id' /etc/ssh/sshd_config.d/00-complianceascode-hardening.com
Scan Passed	✓
Success	✓
Duration	58.4s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10

Feedback	The plan will correctly enable IgnoreRhosts and mitigate the vulnerability, but it lacks a critical step to reload the sshd service
Concerns	Missing sshd reload to apply changes; Only deletes IgnoreRhosts lines from one file, possibly leaving conflicting directives els

QA Result

Safe	✓
Verdict	The plan simply ensures /etc/ssh/sshd_config.d exists, creates the target file, removes any existing IgnoreRhosts directives fr
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	18
Duration	49.3s
Total Tokens	44,221
Cost	\$0.0021
Agents	Triage(1), Remedy(15), Review(1), Qa(1)

sshd_disable_user_known_hosts: Disable SSH Support for User Known Hosts — **FAILED**

Rule	sshd_disable_user_known_hosts
Severity	Medium
Description	SSH can allow system users to connect to systems if a cache of the remote systems public keys is available. This should be c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The change is a standard SSH configuration tweak that disables caching of user known hosts, following STIG hardening pattern
Estimated Impact	authentication/authorization affected; SSH configuration change

Remediation (3 attempt(s))

Attempt #	1
Commands	mkdir -p /etc/ssh/sshd_config.d, sed -i "/^s*IgnoreUserKnownHosts\s\+/ld" /etc/ssh/sshd_config, sed -i "/^s*IgnoreUserKnownHosts\s\+/ld" /etc/ssh/sshd_config
Scan Passed	✗
Success	✗
Duration	125.2s
Error	—

Attempt #	2
Commands	mkdir -p /etc/ssh/sshd_config.d, sed -i 's/^s*IgnoreUserKnownHosts\s\+.*/# &/' /etc/ssh/sshd_config, mkdir -p /etc/ssh/sshd_config.d, sed -i 's/^s*IgnoreUserKnownHosts\s\+.*/# &/' /etc/ssh/sshd_config
Scan Passed	✗
Success	✗
Duration	205.9s
Error	—

Attempt #	3
Commands	cp /etc/ssh/sshd_config /etc/ssh/sshd_config.bak, mkdir -p /etc/ssh/sshd_config.d, find /etc/ssh/sshd_config.d -maxdepth 1 -m
Scan Passed	✗

Success	✗
Duration	167.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly implements the required IgnoreUserKnownHosts yes directive, cleans conflicting entries, verifies syntax, and
Concerns	Backup of *.conf files uses a single cp command that will fail if the directory contains no .conf files or has many files; it also do

QA Result

Safe	✓
Verdict	The remediation plan correctly ensures the IgnoreUserKnownHosts setting is enforced in a dedicated, override-friendly confi
Side Effects	Backup filenames for *.conf may not preserve original names if using a single cp command; potential accidental removal of co
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	17
Duration	150.4s
Total Tokens	84,095
Cost	\$0.0036
Agents	Remedy(15), Review(1), Qa(1)

sshd_do_not_permit_user_env: Do Not Allow SSH Environment Options — **SUCCESS**

Rule	sshd_do_not_permit_user_env
Severity	Medium
Description	Ensure that users are not able to override environment variables of the SSH daemon. The default SSH configuration disables
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling PermitUserEnvironment is a standard SSH hardening step that does not affect authentication or service availability;
Estimated Impact	authentication/authorization affected; Potential misconfiguration of sshd_config may lead to SSH service restart failure

Remediation (1 attempt(s))

Attempt #	1
Commands	mkdir -p /etc/ssh/sshd_config.d
Scan Passed	✓
Success	✓
Duration	105.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	None/10
Feedback	The plan adds or ensures "PermitUserEnvironment no" in a dedicated sshd_config.d file and would effectively harden the ser
Concerns	The file name "00-complianceascode-hardening.conf" may be processed before other custom sshd_config.d files; a later file t

QA Result

Safe	✓
Verdict	The plan only adds or updates a single configuration directive in a dedicated sshd_config.d file to enforce PermitUserEnviron
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	103.1s
Total Tokens	32,965
Cost	\$0.0021
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

sshd_enable_pubkey_auth: Enable Public Key Authentication — SUCCESS

Rule	sshd_enable_pubkey_auth
Severity	Medium
Description	Enable SSH login with public keys. The default SSH configuration enables authentication based on public keys. The appropri
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling PubkeyAuthentication is a standard SSH configuration change that does not risk lockout or system breakage; it follows best practices
Estimated Impact	authentication/authorization affected

Remediation (1 attempt(s))

Attempt #	1
Commands	mkdir -p /etc/ssh/sshd_config.d, sed -i '/^\s*#\?PubkeyAuthentication/Id' /etc/ssh/sshd_config
Scan Passed	✓
Success	✓
Duration	165.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan correctly ensures that PubkeyAuthentication is explicitly enabled and overrides any conflicting settings, which will remain in place for documentation
Concerns	Potential removal of commented lines in global or included config files; comments may contain the directive for documentation

QA Result

Safe	✓
Verdict	The plan explicitly enables PubkeyAuthentication by adding a single directive to a dedicated drop-in file while removing any conflicting settings

Side Effects	Potential removal of commented lines containing the directive; could be harmless but may delete documentation. Ensuring the dropin file ends with a newline is necessary for proper parsing. Missing explicit chown to root:root after chmod could leave incorrect ownership if not handled. The plan relies on a correct sed regex; if miswritten, comments might be mistakenly removed. Reloading sshd must be performed after edits; otherwise, changes won't take effect until next restart.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	17
Duration	162.2s
Total Tokens	60,424
Cost	\$0.0034
Agents	Triage(1), Remedy(14), Review(1), Qa(1)

sshd_enable_strictmodes: Enable Use of Strict Mode Checking — SUCCESS

Rule	sshd_enable_strictmodes
Severity	Medium
Description	SSHs StrictModes option checks file and ownership permissions in the user's home directory .ssh folder before accepting log
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW

Reason	Enabling StrictModes is a standard SSH configuration change that is already the default; it does not risk lockout or system br
Estimated Impact	authentication/authorization affected; SSH authentication

Remediation (1 attempt(s))

Attempt #	1
Commands	mkdir -p /etc/ssh/sshd_config.d, touch /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf, chmod 0600 /etc/ssh/sshd
Scan Passed	✓
Success	✓
Duration	115.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly enables StrictModes by ensuring the directive is present in an included include file and reloads sshd. It will
Concerns	The plan appends a line without ensuring no trailing whitespace or duplicate content beyond the removed StrictModes directive

QA Result

Safe	✓
Verdict	The plan creates a dedicated include file, removes any existing StrictModes directive within that file, and appends a correct “S
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	21
Duration	108.5s
Total Tokens	62,409
Cost	\$0.0033
Agents	Triage(1), Remedy(16), Review(2), Qa(2)

sshd_print_last_log: Enable SSH Print Last Log — **SUCCESS**

Rule	sshd_print_last_log
Severity	Medium
Description	Ensure that SSH will display the date and time of the last successful account logon. The default SSH configuration enables p
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling PrintLastLog is a standard SSH configuration change that does not affect authentication flow or system stability; it s
Estimated Impact	authentication/authorization affected

Remediation (1 attempt(s))

Attempt #	1
Commands	mkdir -p /etc/ssh/sshd_config.d && chmod 0755 /etc/ssh/sshd_config.d, echo "PrintLastLog yes" >> /etc/ssh/sshd_config.d/O
Scan Passed	✓

Success	✓
Duration	78.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	Plan correctly addresses the requirement to enable PrintLastLog and will resolve the vulnerability.
Concerns	Sed pattern may miss commented lines (e.g., '#PrintLastLog no'), causing the setting not to be enabled.; File permissions for

QA Result

Safe	✓
Verdict	The plan correctly ensures PrintLastLog is set to yes in a dedicated sshd_config.d file, using existing syntax and reloading SSH
Side Effects	Brief SSH service interruption while systemctl reload sshd runs; Created file has default 0644 permissions instead of stricter 0
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	73.5s
Total Tokens	32,122
Cost	\$0.0020
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

sshd_rekey_limit: Force frequent session key renegotiation — **FAILED**

Rule	sshd_rekey_limit
Severity	Medium
Description	The RekeyLimit parameter specifies how often the session key of the is renegotiated, both in terms of amount of data that ma
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_rekey_limit_si
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The RekeyLimit setting is a standard SSH configuration parameter that can be safely adjusted without risking lockout or syste
Estimated Impact	authentication/authorization affected; networking affected; Potential temporary SSH session disruption if misconfigured

Remediation (3 attempt(s))

Attempt #	1
Commands	mkdir -p /etc/ssh/sshd_config.d, sed -i "/^s*RekeyLimit\s\+/ld" /etc/ssh/sshd_config, , touch /etc/ssh/sshd_config.d/00-complia
Scan Passed	✗
Success	✗
Duration	145.3s
Error	—
Attempt #	2
Commands	mkdir -p /etc/ssh/sshd_config.d, systemctl reload sshd, echo '--- Done ---'
Scan Passed	✗

Success	✗
Duration	90.9s
Error	—
Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	45.7s
Error	—

Review Verdict

Approved	✗
Optimal	✗
Security Score	5/10
Feedback	This plan will set a RekeyLimit in the main sshd_config but will not address RekeyLimit directives that might exist in files under /etc/ssh/ssh_config.d/
Concerns	Does not handle RekeyLimit directives in /etc/ssh/sshd_config.d/*.conf, which can override the main config setting.; No verification

LLM Metrics

LLM Calls	2
Duration	45.7s
Total Tokens	7,931
Cost	\$0.0010
Agents	Remedy(1), Review(1)

sshd_set_loglevel_verbose: Set SSH Daemon LogLevel to VERBOSE — SUCCESS

Rule	sshd_set_loglevel_verbose
Severity	Medium
Description	The VERBOSE parameter configures the SSH daemon to record login and logout activity. To specify the log level in SSH, add the VERBOSE parameter to the LogLevel directive in the sshd_config file.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/ssh_config.d; then echo 'LogLevel VERBOSE' >> /etc/ssh/ssh_config.d/00-sshd_set_loglevel_verbose.conf; fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Setting LogLevel to VERBOSE is a standard SSH configuration change that only increases logging verbosity and does not affect system security.
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	11.5s
Error	—
Attempt #	2
Commands	—
Scan Passed	✗

Success	✗
Duration	12.7s
Error	—
Attempt #	3
Commands	mkdir -p /etc/ssh/sshd_config.d, touch /etc/ssh/sshd_config.d/00-complianceascode-hardening.conf && chmod 0600 /etc/ssh/
Scan Passed	✓
Success	✓
Duration	113.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly removes any existing LogLevel directives from the hardening config file, appends the required LOGLEVEL
Concerns	Backup is performed without checking if the backup already exists, potentially overwriting previous backups;; The plan does n

QA Result

Safe	✓
Verdict	The remediation plan edits the hardening configuration file to ensure the LogLevel is set to VERBOSE, verifies SSH configura
Side Effects	Backup file may overwrite an existing backup if the same name is used repeatedly; file permissions on the hardening file rema
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	20
Duration	93.8s
Total Tokens	76,359
Cost	\$0.0037
Agents	Remedy(16), Review(2), Qa(2)

package_usbguard_installed: Install usbguard Package — **SUCCESS**

Rule	package_usbguard_installed
Severity	Medium
Description	The usbguard package can be installed with the following command: \$ sudo dnf install usbguard
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! (grep -sqE "^\s390x\$" /proc/sys/kernel/osrele
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the usbguard package is a standard, non-disruptive package installation that does not affect authentication, network
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	dnf install -y usbguard
Scan Passed	✓

Success	✓
Duration	154.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly installs usbguard on non-ARMv390x architectures and idempotently skips when already present.
Concerns	Does not check for the presence of the kernel-core package as the original recommendation does. The omission is unlikely to

QA Result

Safe	✓
Verdict	The proposed plan installs usbguard only on non-ARMv390x systems, checks for existing installation, and performs a simple idempotency check.
Side Effects	dnf may refresh metadata and resolve dependencies; minimal transient storage usage.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	53.0s
Total Tokens	27,990
Cost	\$0.0016
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

service_usbguard_enabled: Enable the USBGuard Service — **SUCCESS**

Rule	service_usbguard_enabled
Severity	Medium
Description	The USBGuard service should be enabled. The usbguard service can be enabled with the following command: \$ sudo system
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! (grep -sqE "^.*\s390x\$" /proc/sys/kernel/osrele
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling the usbguard service is a standard service enablement that does not affect authentication, networking, or filesystem
Estimated Impact	USB device access control

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	13.2s
Error	—
Attempt #	2
Commands	systemctl unmask usbguard.service, systemctl start usbguard.service
Scan Passed	✗

Success	✗
Duration	74.4s
Error	—
Attempt #	3
Commands	rpm -q usbguard, systemctl is-enabled usbguard.service, systemctl enable usbguard.service
Scan Passed	✓
Success	✓
Duration	51.2s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will successfully install usbguard (if not present) and enable the service, thereby addressing the vulnerability. It omits the unmask step for masked services.
Concerns	Missing unmask step for instances where usbguard.service is masked; Does not start the service after enabling, so it may not be active.

QA Result

Safe	✓
Verdict	The plan installs the usbguard package if absent and enables the service without modifying critical configuration or stopping services.
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	36.3s
Total Tokens	29,383
Cost	\$0.0015
Agents	Remedy(9), Review(1), Qa(1)

*usbguard_generate_policy: Generate USBGuard Policy — **REQUIRES_HUMAN_REVIEW***

Rule	usbguard_generate_policy
Severity	Medium
Description	By default USBGuard when enabled prevents access to all USB devices and this lead to inaccessible system if they use USB
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! (grep -sqE "^\.s390x\$" /proc/sys/kernel/osrele
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The remediation script only generates a policy file and restarts the usbguard service, which is a standard service enablement
Estimated Impact	filesystems affected

LLM Metrics

LLM Calls	1
Duration	3.7s
Total Tokens	1,209

Cost	\$0.0001
Agents	Triage(1)

package_audispd-plugins_installed: Install audispd-plugins Package — **SUCCESS**

Rule	package_audispd-plugins_installed
Severity	Medium
Description	The audispd-plugins package can be installed with the following command: \$ sudo dnf install audispd-plugins
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the audispd-plugins package is a standard, low-risk operation that does not affect authentication, networking, or files
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	dnf install -y audispd-plugins
Scan Passed	✓
Success	✓
Duration	41.5s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	9/10
Feedback	The provided script correctly identifies systems that require the audispd-plugins package and installs it only when the kernel-c
Concerns	—

QA Result

Safe	✓
Verdict	The script checks for the presence of kernel-core and installs audispd-plugins only when it is missing, which is a standard sec
Side Effects	May slightly increase auditd overhead by enabling plugin architecture.; Requires dnf repository reachable for package installa
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	10
Duration	21.9s
Total Tokens	16,500
Cost	\$0.0010
Agents	Triage(1), Remedy(7), Review(1), Qa(1)

audit_rules_etc_cron_d: Ensure auditd Collects Changes to Cron Jobs - /etc/cron.d/ — **SUCCESS**

Rule	audit_rules_etc_cron_d
Severity	Medium
Description	At a minimum, the audit system should collect administrator actions for all users and root. If the auditd daemon is configured t

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding an audit rule for /etc/cron.d/ is a standard configuration change that does not affect authentication, networking, or files
Estimated Impact	—

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	15.5s
Error	—
Attempt #	2
Commands	read_file /etc/audit/rules.d/cronjobs.rules, systemctl reload auditd, chown root:root /etc/audit/rules.d/cronjobs.rules
Scan Passed	✓
Success	✓
Duration	142.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The revised remediation plan now includes reloading auditd, preserving existing rules, and setting correct ownership/permissions.
Concerns	If the script blindly overwrites /etc/audit/rules.d/cronjobs.rules when it already exists, other custom rules could be lost. The plan should ensure existing rules are preserved or merged.

QA Result

Safe	✓
Verdict	The remediation correctly adds a watch on /etc/cron.d/ for write and attribute changes, reloads auditd to apply the rule, and preserves existing rules.
Side Effects	If the script overwrites an existing /etc/audit/rules.d/cronjobs.rules file that contains other custom audit rules, those rules will be lost.
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	128.1s
Total Tokens	56,625
Cost	\$0.0032
Agents	Remedy(14), Review(1), Qa(1)

audit_rules_immutable: Make the auditd Configuration Immutable — SUCCESS

Rule	audit_rules_immutable
Severity	Medium
Description	If the auditd daemon is configured to use the augenrules program to read audit rules during daemon startup (the default), adding this rule will ensure that the audit rules are immutable and cannot be modified or deleted.

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the immutable flag (-e 2) to auditd rules is a standard STIG hardening step that does not affect authentication, network
Estimated Impact	reboot required

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	105.5s
Error	—
Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	63.8s
Error	—

Attempt #	3
Commands	systemctl show auditd grep ActiveState
Scan Passed	✓
Success	✓
Duration	37.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan ensures a dedicated rules file contains the immutable flag, uses a precise regex to clean up existing entries, and res
Concerns	No automatic notification or reload of auditd after changes; Does not verify whether auditd uses augenrules or auditctl before

QA Result

Safe	✓
Verdict	The plan correctly creates or updates /etc/audit/rules.d/immutable.rules to contain the immutable flag and preserves other rule
Side Effects	Audit logging may omit rules that appear after the immutable flag if the file is read before other rule files, potentially reducing a
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	29.7s
Total Tokens	33,891

Cost	\$0.0019
Agents	Remedy(10), Review(1), Qa(1)

audit_rules_sudoers: Ensure auditd Collects System Administrator Actions - /etc/sudoers — **SUCCESS**

Rule	audit_rules_sudoers
Severity	Medium
Description	At a minimum, the audit system should collect administrator actions for all users and root. If the auditd daemon is configured to collect administrator actions, it should collect actions for all users and root.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core; if rpm --quiet -q audit && rpm --quiet -q kernel-core; then auditd --start; else auditd --start; fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding an audit rule for /etc/sudoers is a standard STIG hardening step that does not affect system operation or access. It simply ensures that all actions are logged.
Estimated Impact	authentication/authorization affected; Potential for missing audit logs if rule is incorrectly configured

Remediation (1 attempt(s))

Attempt #	1
Commands	systemctl restart auditd, systemctl reload auditd
Scan Passed	✓
Success	✓
Duration	96.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will add the necessary audit rule for /etc/sudoers and reload auditd, thus addressing the vulnerability.
Concerns	Potential duplicate rule entries if audit.rules is already read via augenrules; redudancy is harmless but not ideal.; A short audi

QA Result

Safe	✓
Verdict	The plan correctly adds the required audit rule for /etc/sudoers and reloads auditd. It only modifies audit configuration files an
Side Effects	Potential duplicate audit rule entries if audit.rules is already read by augenrules
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	21
Duration	82.6s
Total Tokens	69,021
Cost	\$0.0036
Agents	Triage(1), Remedy(16), Review(2), Qa(2)

audit_rules_sudoers_d: Ensure auditd Collects System Administrator Actions - /etc/sudoers.d/ — FAILED

Rule	audit_rules_sudoers_d
Severity	Medium
Description	At a minimum, the audit system should collect administrator actions for all users and root. If the auditd daemon is configured t

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding an audit rule to monitor changes to /etc/sudoers.d/ is a standard STIG hardening action that does not alter system fun
Estimated Impact	authentication/authorization affected; None

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	15.4s
Error	—
Attempt #	2
Commands	mkdir -p /etc/audit/rules.d, mkdir -p /etc/audit/rules.d, mkdir -p /etc/audit/rules.d, mkdir -p /etc/audit/rules.d, mkdir -p /etc/audit
Scan Passed	✗
Success	✗
Duration	196.3s
Error	—

Attempt #	3
Commands	test -d /etc/audit/rules.d && echo yes echo no
Scan Passed	<i>✗</i>
Success	<i>✗</i>
Duration	495.9s
Error	—

Review Verdict

Approved	✓
Optimal	<i>✗</i>
Security Score	9/10
Feedback	The plan correctly adds the audit rule in both possible loader configurations, uses idempotent checks, sets appropriate permissions
Concerns	Detection logic may misidentify the loader if /etc/audit/rules.d exists but contains no .rules files; this could lead to applying the

QA Result

Safe	✓
Verdict	The remediation correctly appends the required audit rule to the appropriate configuration file based on the auditd loader (aug
Side Effects	Brief auditd restart may pause logging temporarily.; If /etc/audit/rules.d exists but contains no .rules files, the script may incor
Regression	<i>✗</i>
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	485.2s
Total Tokens	68,898

Cost	\$0.0049
Agents	Remedy(13), Review(1), Qa(1)

audit_rules_suid_privilege_function: Record Events When Privileged Executables Are Run — **SUCCESS**

Rule	audit_rules_suid_privilege_function
Severity	Medium
Description	Verify the system generates an audit record when privileged functions are executed. If audit is using the "auditctl" tool to load
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves adding audit rules for execve on setuid/setgid binaries, which is a standard configuration change tha
Estimated Impact	filesystems affected; Missing audit logs for privileged executions; Potential misconfiguration of audit rule syntax

Remediation (2 attempt(s))

Attempt #	1
Commands	echo hello
Scan Passed	✗
Success	✗
Duration	117.5s
Error	—

Attempt #	2
Commands	systemctl restart auditd, systemctl reload auditd, auditctl -R /etc/audit/rules.d/4510_setuid.rules
Scan Passed	✓
Success	✓
Duration	57.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will effectively add the necessary audit rules and reload auditd, thus resolving the finding. However it is not fully optimal
Concerns	Unnecessary b64 rules on 32bit systems may clutter the rule set.; Potential duplication if similar rules already exist with minor differences

QA Result

Safe	✓
Verdict	The plan adds the required execve audit rules in a dedicated file and restarts auditd, which is the standard method to apply a fix
Side Effects	Auditd service brief restart causing temporary loss of audit events
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	19
Duration	46.1s
Total Tokens	68,202

Cost	\$0.0043
Agents	Remedy(17), Review(1), Qa(1)

audit_rules_system_shutdown: Shutdown System When Auditing Failures Occur — FAILED

Rule	audit_rules_system_shutdown
Severity	Medium
Description	If the auditd daemon is configured to use the augenrules program to read audit rules during daemon startup (the default), add
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core; #
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding the '-f' option to audit rules is a standard STIG hardening step that configures auditd to halt the system on audit failure
Estimated Impact	Audit failure mode may halt the system if auditd encounters errors

Remediation (3 attempt(s))

Attempt #	1
Commands	ls -l /etc/audit/rules.d/*.rules
Scan Passed	✗
Success	✗
Duration	83.8s
Error	—

Attempt #	2
Commands	sed -i 's/^s*-fls*[^]*\$/-f halt/' /etc/audit/audit.rules, grep -r -n '^s*-fls*' /etc/audit/rules.d/*.rules true, rm -f /etc/audit/rules.d/a
Scan Passed	✗
Success	✗
Duration	213.7s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	28.0s
Error	—

Review Verdict

Approved	✗
Optimal	✗
Security Score	5/10
Feedback	The plan adds a dedicated -f entry to immutable.rules, which is effective only when auditd loads rules from /etc/audit/rules.d (
Concerns	Rule is added only to immutable.rules without checking whether auditd loads from rules.d or only /etc/audit/audit.rules (auditd

LLM Metrics

LLM Calls	2
Duration	28.0s
Total Tokens	6,868

Cost	\$0.0008
Agents	Remedy(1), Review(1)

audit_rules_usergroup_modification_group: Record Events that Modify User/Group Information - /etc/group — SUCCESS

Rule	audit_rules_usergroup_modification_group
Severity	Medium
Description	If the auditd daemon is configured to use the augenrules program to read audit rules during daemon startup (the default), add
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core; r
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding an audit rule to monitor changes to /etc/group is a standard configuration change that does not affect authentication, n
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	chmod 0600 /etc/audit/rules.d/audit_rules_usergroup_modification_group.rules, systemctl restart auditd
Scan Passed	✓
Success	✓
Duration	92.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will correctly add the required audit rule and reload auditd, effectively addressing the vulnerability. It follows a clear m
Concerns	The plan only targets augenrules; systems that rely solely on auditctl and do not process /etc/audit/rules.d files will not have th Overwriting an existing .rules file could inadvertently remove other relevant audit rules if the file is shared. No explicit validation that the rule syntax is correct or that no duplicate entries exist. The plan does not account for potential SELinux contexts on the rule file.

QA Result

Safe	✓
Verdict	The plan correctly adds the required audit rule for /etc/group monitoring and restarts auditd to apply the change. Restarting a
Side Effects	Overwriting an existing .rules file may remove other audit rules that were previously defined in that file, potentially reducing a
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	88.5s
Total Tokens	41,367
Cost	\$0.0037
Agents	Triage(1), Remedy(10), Review(2), Qa(2)

audit_rules_usergroup_modification_gshadow: Record Events that Modify User/Group Information - /etc/gshadow — **SUCCESS**

Rule	audit_rules_usergroup_modification_gshadow
------	--

Severity	Medium
Description	If the auditd daemon is configured to use the augenrules program to read audit rules during daemon startup (the default), adding an audit rule to monitor changes to /etc/gshadow is a standard configuration change that does not affect authentication or authorization.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core; auditd -s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding an audit rule to monitor changes to /etc/gshadow is a standard configuration change that does not affect authentication or authorization.
Estimated Impact	authentication/authorization affected; audit configuration; auditd service

Remediation (1 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✓
Success	✓
Duration	35.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan correctly adds the audit rule for monitoring /etc/gshadow modifications when the system uses augenrules. It will resolve the issue.

Concerns	Does not handle auditctl-based rule loading.; No permission or ownership checks for the created rules file.; No reload or verification
----------	--

QA Result

Safe	✓
Verdict	Adding the audit rule to /etc/audit/rules.d is a standard and non-disruptive configuration change; it does not interfere with SS
Side Effects	If auditctl is the only loader, the rule will not be enforced until manually added to audit.rules.; If write_file does not preserve pe
Regression	✗
Recommendation	Investigate

LLM Metrics

LLM Calls	13
Duration	37.7s
Total Tokens	31,560
Cost	\$0.0024
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

audit_rules_usergroup_modification_opasswd: Record Events that Modify User/Group Information - /etc/security/opasswd — **SUCCESS**

Rule	audit_rules_usergroup_modification_opasswd
Severity	Medium
Description	If the auditd daemon is configured to use the augenrules program to read audit rules during daemon startup (the default), add
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
------------------	---

Human Review	✗
Risk Level	LOW
Reason	Adding an audit rule to monitor changes to /etc/security/opasswd does not alter system functionality or security posture; it only
Estimated Impact	authentication/authorization affected; No impact on authentication or authorization mechanisms; No risk of losing SSH or con

Remediation (2 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	12.9s
Error	—
Attempt #	2
Commands	mkdir -p /etc/audit/rules.d, mkdir -p /etc/audit/rules.d
Scan Passed	✓
Success	✓
Duration	112.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan will correctly add the audit rule in both augenrules and auditctl configurations and reload auditd, thereby addressing

Concerns	The use of simple grep might match unintended lines or partial matches; more precise pattern matching (e.g., anchoring the r
----------	--

QA Result

Safe	✓
Verdict	The remediation simply adds a correct audit rule for monitoring /etc/security/opasswd via augenrules and auditctl, writes the r
Side Effects	Potential duplicate rule if existing line differs in whitespace or flags, which is harmless; minimal performance impact from mon
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	19
Duration	96.2s
Total Tokens	65,432
Cost	\$0.0060
Agents	Remedy(15), Review(2), Qa(2)

audit_rules_usergroup_modification_passwd: Record Events that Modify User/Group Information - /etc/passwd — SUCCESS

Rule	audit_rules_usergroup_modification_passwd
Severity	Medium
Description	If the auditd daemon is configured to use the augenrules program to read audit rules during daemon startup (the default), add
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
------------------	---

Human Review	✗
Risk Level	LOW
Reason	Adding an audit rule to monitor changes to /etc/passwd is a standard, low-risk configuration change that follows STIG harden
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	systemctl reload auditd, systemctl restart auditd
Scan Passed	✓
Success	✓
Duration	97.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will effectively add the required audit rule and reload auditd to apply changes. However, it could be improved for con
Concerns	Only one .rules file (10-passwd.rules) is inspected; other rule files in /etc/audit/rules.d might also need review to avoid duplica

QA Result

Safe	✓
Verdict	The plan adds the required audit rule for /etc/passwd and restarts auditd, which is a safe and expected change. The rule synt
Side Effects	Brief loss of audit logs during auditd restart; Rule may be duplicated if an identical rule already exists elsewhere
Regression	✗

Recommendation	Approve
----------------	---------

LLM Metrics

LLM Calls	23
Duration	87.3s
Total Tokens	76,388
Cost	\$0.0057
Agents	Triage(1), Remedy(18), Review(2), Qa(2)