OpenSCAP Multi-Agent Pipeline Report

Target: 192.168.1.87 | Generated: 2026-04-07 03:10:27

Models Used

Triage	openai/gpt-oss-20b
Remedy	openai/gpt-oss-20b
Review	openai/gpt-oss-20b
Qa	openai/gpt-oss-20b

Pipeline Summary

Total Findings Processed	237
Remediated Successfully	6
Failed Remediation	29
Requires Human Review	198
Discarded / Blocked	4
Success Rate	2.5%
Total Duration	5931.1s

LLM Usage (Aggregate)

Total LLM Calls	557
Total Errors	209

Total LLM Duration	5076.2s
Prompt Tokens	908,104
Completion Tokens	249,204
Total Tokens	1,157,308
Estimated Cost (USD)	$0.0744

LLM Usage by Agent

Agent	Calls	Errors	Duration (s)	Prompt Tok	Compl Tok	Total Tok	Cost (USD)
Triage	206	194	220.6	9,401	5,852	15,253	$0.0015
Remedy	282	14	4064.2	810,012	190,074	1,000,086	$0.0593
Review	38	0	527.0	52,251	36,998	89,249	$0.0091
Qa	31	1	264.4	36,440	16,280	52,720	$0.0045

Remediated Successfully (6)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
package_aide_installed	Install AIDE	Medium	Remediate	LOW	2	Pass	Approved (None/10)	✓	210.1s	12
aide_build_database	Build and Test AIDE Database	Medium	Remediate	LOW	2	Pass	Approved (8/10)	✓	465.7s	22
package_nss-tools_installed	Ensure nss-tools is installed	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	283.9s	12
package_subscription-manager_installed	Install subscription-manager Package	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	91.2s	10
sysctl_net_ipv6_conf_all_accept_ra	Configure Accepting Router Advertisements on All I…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	520.7s	19

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
sysctl_net_ipv6_conf_all_accept_source_route	Disable Kernel Parameter for Accepting Source-Rout…	Medium	Remediate	LOW	1	Pass	Approved (8/10)	✓	118.0s	13

Failed Remediation (29)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
aide_check_audit_tools	Configure AIDE to Verify the Audit Tools	Medium	Remediate	LOW	3	Fail	Rejected (5/10)	—	72.6s	2
aide_scan_notification	Configure Notification of Post-AIDE Scan Details	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	179.1s	12
aide_use_fips_hashes	Configure AIDE to Use FIPS 140-2 for Validating Ha…	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	333.9s	13
fips_crypto_subpolicy	FIPS Must Use a Supported Subpolicy	Medium	Remediate	LOW	3	Fail	Rejected (4/10)	—	192.3s	2
fips_custom_stig_sub_policy	Implement STIG Sub Crypto Policy	Medium	Remediate	LOW	3	Fail	Rejected (None/10)	—	22.1s	3
configure_crypto_policy	Configure System Cryptography Policy	High	Remediate	LOW	3	Fail	Rejected (4/10)	—	10.2s	3
package_gnutls-utils_installed	Ensure gnutls-utils is installed	Medium	Remediate	LOW	3	Fail	Approved (9/10)	—	133.5s	3
ensure_gpgcheck_local_packages	Ensure gpgcheck Enabled for Local Packages	High	Remediate	LOW	3	Fail	Approved (8/10)	✓	31.7s	11
enable_authselect	Enable authselect	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✗	15.8s	3
banner_etc_issue	Modify the System Login Banner	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	214.5s	13
account_password_pam_faillock_password_auth	Configure the Use of the pam_faillock.so Module in…	Medium	Remediate	LOW	3	Fail	Approved (7/10)	✓	135.8s	12

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
account_password_pam_faillock_system_auth	Configure the Use of the pam_faillock.so Module in…	Medium	Remediate	LOW	3	Fail	Rejected (None/10)	—	124.0s	5
accounts_passwords_pam_faillock_interval	Set Interval For Counting Failed Password Attempts	Medium	Remediate	LOW	3	Fail	Approved (7/10)	✓	59.5s	16
accounts_password_pam_dcredit	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	3	Fail	Approved (None/10)	✓	52.0s	12
accounts_password_pam_dictcheck	Ensure PAM Enforces Password Requirements - Preven…	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	377.8s	16
accounts_password_pam_difok	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Remediate	LOW	3	Fail	Rejected (None/10)	—	38.9s	5
accounts_password_pam_enforce_root	Ensure PAM Enforces Password Requirements - Enforc…	Medium	Remediate	LOW	3	Fail	—	—	0.3s	1
service_debug-shell_disabled	Disable debug-shell SystemD Service	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	165.7s	11
disable_ctrlaltdel_burstaction	Disable Ctrl-Alt-Del Burst Action	High	Remediate	LOW	3	Fail	—	—	51.3s	9
package_opensc_installed	Install the opensc Package For Multifactor Authent…	Medium	Remediate	LOW	3	Fail	Approved (7/10)	✓	502.2s	22
package_pcsc-lite_installed	Install the pcsc-lite package	Medium	Remediate	LOW	3	Fail	Approved (9/10)	✓	39.4s	12
service_pcscd_enabled	Enable the pcscd Service	Medium	Remediate	LOW	3	Fail	—	—	0.3s	1
sysctl_net_ipv6_conf_all_accept_redirects	Disable Accepting ICMP Redirects for All IPv6 Inte…	Medium	Remediate	LOW	3	Fail	Approved (9/10)	✓	324.1s	15

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
sysctl_net_ipv6_conf_all_forwarding	Disable Kernel Parameter for IPv6 Forwarding	Medium	Remediate	LOW	3	Fail	Approved (7/10)	✓	219.7s	16
sysctl_net_ipv6_conf_default_accept_ra	Disable Accepting Router Advertisements on all IPv…	Medium	Remediate	LOW	3	Fail	Rejected (None/10)	—	70.2s	2
sysctl_net_ipv6_conf_default_accept_redirects	Disable Kernel Parameter for Accepting ICMP Redire…	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	542.0s	21
sysctl_net_ipv6_conf_default_accept_source_route	Disable Kernel Parameter for Accepting Source-Rout…	Medium	Remediate	LOW	3	Fail	Approved (8/10)	✓	54.0s	13
sysctl_net_ipv4_conf_all_accept_redirects	Disable Accepting ICMP Redirects for All IPv4 Inte…	Medium	Remediate	LOW	3	Fail	—	—	65.2s	12
sysctl_net_ipv4_conf_all_accept_source_route	Disable Kernel Parameter for Accepting Source-Rout…	Medium	Remediate	LOW	3	Fail	—	—	0.3s	1

Requires Human Review (198)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
installed_OS_is_vendor_supported	The Installed Operating System Is Vendor Supported	High	Human Review	LOW	0	—	—	—	11.5s	1
accounts_passwords_pam_faillock_deny	Lock Accounts After Failed Password Attempts	Medium	Human Review	LOW	0	—	—	—	8.0s	1
accounts_passwords_pam_faillock_deny_root	Configure the root Account for Failed Password Att…	Medium	Human Review	LOW	0	—	—	—	2.3s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
accounts_passwords_pam_faillock_dir	Lock Accounts Must Persist	Medium	Human Review	LOW	0	—	—	—	1.8s	1
accounts_passwords_pam_faillock_unlock_time	Set Lockout Time for Failed Password Attempts	Medium	Human Review	LOW	0	—	—	—	15.9s	1
accounts_password_pam_lcredit	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
accounts_password_pam_maxclassrepeat	Ensure PAM Enforces Password Requirements - Maximu…	Medium	Human Review	MEDIUM	0	—	—	—	1.4s	1
accounts_password_pam_maxrepeat	Set Password Maximum Consecutive Repeating Charact…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
accounts_password_pam_minclass	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
accounts_password_pam_minlen	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Human Review	MEDIUM	0	—	—	—	0.6s	1
accounts_password_pam_ocredit	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
accounts_password_pam_pwquality_retry	Ensure PAM Enforces Password Requirements - Authen…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
accounts_password_pam_ucredit	Ensure PAM Enforces Password Requirements - Minimu…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
disable_ctrlaltdel_reboot	Disable Ctrl-Alt-Del Reboot Activation	High	Human Review	MEDIUM	0	—	—	—	0.4s	1
install_smartcard_packages	Install Smart Card Packages For Multifactor Authen…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
configure_opensc_card_drivers	Configure opensc Smart Card Drivers	Medium	Human Review	MEDIUM	0	—	—	—	0.8s	1
account_disable_post_pw_expiration	Set Account Expiration Following Inactivity	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
accounts_maximum_age_login_defs	Set Password Maximum Age	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
accounts_minimum_age_login_defs	Set Password Minimum Age	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
accounts_password_set_max_life_existing	Set Existing Passwords Maximum Age	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
accounts_password_set_min_life_existing	Set Existing Passwords Minimum Age	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
accounts_password_pam_unix_rounds_password_auth	Set number of Password Hashing Rounds - password-a…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
accounts_password_pam_unix_rounds_system_auth	Set number of Password Hashing Rounds - system-aut…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
no_empty_passwords	Prevent Login to Accounts With Empty Password	High	Human Review	MEDIUM	0	—	—	—	0.4s	1
use_pam_wheel_for_su	Enforce usage of pam_wheel for su authentication	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
accounts_logon_fail_delay	Ensure the Logon Failure Delay is Set Correctly in…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
accounts_tmout	Set Interactive Session Timeout	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
file_permission_user_init_files_root	Ensure All User Initialization Files Have Mode 074…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
accounts_umask_etc_bashrc	Ensure the Default Bash Umask is Set Correctly	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
accounts_umask_etc_csh_cshrc	Ensure the Default C Shell Umask is Set Correctly	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
accounts_umask_etc_login_defs	Ensure the Default Umask is Set Correctly in login…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
accounts_umask_etc_profile	Ensure the Default Umask is Set Correctly in /etc/…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
grub2_init_on_free	The system must booted with init_on_free=1	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
grub2_vsyscall_argument	Disable vsyscalls	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
grub2_admin_username	Set the Boot Loader Admin Username to a Non-Defaul…	High	Human Review	MEDIUM	0	—	—	—	0.4s	1
grub2_password	Set Boot Loader Password in grub2	High	Human Review	MEDIUM	0	—	—	—	0.4s	1
package_rsyslog-gnutls_installed	Ensure rsyslog-gnutls is installed	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
rsyslog_encrypt_offload_actionsendstreamdriverauthmode	Ensure Rsyslog Authenticates Off-Loaded Audit Reco…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
rsyslog_encrypt_offload_actionsendstreamdrivermode	Ensure Rsyslog Encrypts Off-Loaded Audit Records	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
rsyslog_encrypt_offload_defaultnetstreamdriver	Ensure Rsyslog Encrypts Off-Loaded Audit Records	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
rsyslog_remote_access_monitoring	Ensure remote access methods are monitored in Rsys…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
rsyslog_remote_loghost	Ensure Logs Sent To Remote Host	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
network_configure_name_resolution	Configure Multiple DNS Servers in /etc/resolv.conf	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
package_libreswan_installed	Install libreswan Package	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
sysctl_net_ipv4_conf_all_forwarding	Disable Kernel Parameter for IPv4 Forwarding on al…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
sysctl_net_ipv4_conf_all_rp_filter	Enable Kernel Parameter to Use Reverse Path Filter…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
sysctl_net_ipv4_conf_default_accept_redirects	Disable Kernel Parameter for Accepting ICMP Redire…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
sysctl_net_ipv4_conf_default_rp_filter	Enable Kernel Parameter to Use Reverse Path Filter…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
sysctl_net_ipv4_icmp_echo_ignore_broadcasts	Enable Kernel Parameter to Ignore ICMP Broadcast E…	Medium	Human Review	MEDIUM	0	—	—	—	0.8s	1
sysctl_net_ipv4_tcp_syncookies	Enable Kernel Parameter to Use TCP Syncookies on N…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
sysctl_net_ipv4_conf_all_send_redirects	Disable Kernel Parameter for Sending ICMP Redirect…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
sysctl_net_ipv4_conf_default_send_redirects	Disable Kernel Parameter for Sending ICMP Redirect…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
kernel_module_atm_disabled	Disable ATM Support	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
kernel_module_can_disabled	Disable CAN Support	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
kernel_module_sctp_disabled	Disable SCTP Support	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
kernel_module_bluetooth_disabled	Disable Bluetooth Kernel Module	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
networkmanager_dns_mode	NetworkManager DNS Mode Must Be Must Configured	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
rootfiles_configured	Ensure rootfiles tmpfile.d is Configured Correctly	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
kernel_module_usb-storage_disabled	Disable Modprobe Loading of USB Storage Driver	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
mount_option_boot_efi_nosuid	Add nosuid Option to /boot/efi	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
mount_option_boot_nodev	Add nodev Option to /boot	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
mount_option_boot_nosuid	Add nosuid Option to /boot	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
mount_option_dev_shm_nodev	Add nodev Option to /dev/shm	Medium	Human Review	MEDIUM	0	—	—	—	0.6s	1
mount_option_dev_shm_noexec	Add noexec Option to /dev/shm	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
mount_option_dev_shm_nosuid	Add nosuid Option to /dev/shm	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
mount_option_home_noexec	Add noexec Option to /home	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
mount_option_home_nosuid	Add nosuid Option to /home	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
mount_option_nodev_nonroot_local_partitions	Add nodev Option to Non-Root Local Partitions	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
sysctl_kernel_core_pattern	Disable storing core dumps	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
sysctl_kernel_kexec_load_disabled	Disable Kernel Image Loading	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
sysctl_kernel_unprivileged_bpf_disabled	Disable Access to Network bpf() Syscall From Unpri…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
sysctl_kernel_yama_ptrace_scope	Restrict usage of ptrace to descendant processes	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
sysctl_net_core_bpf_jit_harden	Harden the operation of the BPF just-in-time compi…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
sysctl_user_max_user_namespaces_no_remediation	Disable the use of user namespaces	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
service_systemd-coredump_disabled	Disable acquiring, saving, and processing core dum…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
coredump_disable_backtraces	Disable core dump backtraces	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
coredump_disable_storage	Disable storing core dump	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
disable_users_coredumps	Disable Core Dumps for All Users	Medium	Human Review	MEDIUM	0	—	—	—	0.8s	1
sysctl_kernel_randomize_va_space	Enable Randomized Layout of Virtual Address Space	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
grub2_page_poison_argument	Enable page allocator poisoning	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
package_policycoreutils-python-utils_installed	Install policycoreutils-python-utils package	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
service_kdump_disabled	Disable KDump Kernel Crash Analyzer (kdump)	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
file_permissions_cron_d	Verify Permissions on cron.d	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
file_permissions_cron_daily	Verify Permissions on cron.daily	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
file_permissions_cron_hourly	Verify Permissions on cron.hourly	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
file_permissions_cron_monthly	Verify Permissions on cron.monthly	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
file_permissions_cron_weekly	Verify Permissions on cron.weekly	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
package_fapolicyd_installed	Install fapolicyd Package	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
service_fapolicyd_enabled	Enable the File Access Policy Service	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
fapolicy_default_deny	Configure Fapolicy Module to Employ a Deny-all, Pe…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
package_postfix_installed	The Postfix package is installed	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
package_s-nail_installed	The s-nail Package Is Installed	Medium	Human Review	MEDIUM	0	—	—	—	0.7s	1
postfix_client_configure_mail_alias	Configure System to Forward All Mail For The Root …	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
chronyd_or_ntpd_set_maxpoll	Configure Time Service Maxpoll Interval	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
chronyd_server_directive	Ensure Chrony is only configured with the server d…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
disable_host_auth	Disable Host-Based Authentication	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
sshd_disable_compression	Disable Compression Or Set Compression to delayed	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
sshd_disable_gssapi_auth	Disable GSSAPI Authentication	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
sshd_disable_kerb_auth	Disable Kerberos Authentication	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
sshd_disable_rhosts	Disable SSH Support for .rhosts Files	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
sshd_disable_user_known_hosts	Disable SSH Support for User Known Hosts	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
sshd_do_not_permit_user_env	Do Not Allow SSH Environment Options	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
sshd_enable_pubkey_auth	Enable Public Key Authentication	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
sshd_enable_strictmodes	Enable Use of Strict Mode Checking	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
sshd_print_last_log	Enable SSH Print Last Log	Medium	Human Review	MEDIUM	0	—	—	—	0.6s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
sshd_rekey_limit	Force frequent session key renegotiation	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
sshd_set_loglevel_verbose	Set SSH Daemon LogLevel to VERBOSE	Medium	Human Review	MEDIUM	0	—	—	—	0.6s	1
sshd_x11_use_localhost	Prevent remote hosts from connecting to the proxy …	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
sssd_certificate_verification	Certificate status checking in SSSD	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
sssd_enable_certmap	Enable Certmap in SSSD	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
sssd_enable_smartcards	Enable Smartcards in SSSD	Medium	Human Review	MEDIUM	0	—	—	—	0.9s	1
package_usbguard_installed	Install usbguard Package	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
service_usbguard_enabled	Enable the USBGuard Service	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
usbguard_generate_policy	Generate USBGuard Policy	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
package_audispd-plugins_installed	Install audispd-plugins Package	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_etc_cron_d	Ensure auditd Collects Changes to Cron Jobs - /etc…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_immutable	Make the auditd Configuration Immutable	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_sudoers	Ensure auditd Collects System Administrator Action…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_sudoers_d	Ensure auditd Collects System Administrator Action…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_suid_privilege_function	Record Events When Privileged Executables Are Run	Medium	Human Review	MEDIUM	0	—	—	—	61.0s	2

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
audit_rules_system_shutdown	Shutdown System When Auditing Failures Occur	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_usergroup_modification_group	Record Events that Modify User/Group Information -…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_usergroup_modification_gshadow	Record Events that Modify User/Group Information -…	Medium	Human Review	MEDIUM	0	—	—	—	0.7s	1
audit_rules_usergroup_modification_opasswd	Record Events that Modify User/Group Information -…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_rules_usergroup_modification_passwd	Record Events that Modify User/Group Information -…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_usergroup_modification_shadow	Record Events that Modify User/Group Information -…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_var_spool_cron	Ensure auditd Collects Changes to Cron Jobs - /var…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_rules_dac_modification_chmod	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_dac_modification_chown	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_dac_modification_fchmod	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_rules_dac_modification_fchmodat	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
audit_rules_dac_modification_fchown	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_dac_modification_fchownat	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_dac_modification_fremovexattr	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_dac_modification_fsetxattr	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.8s	1
audit_rules_dac_modification_lchown	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_rules_dac_modification_lremovexattr	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_dac_modification_lsetxattr	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_dac_modification_removexattr	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_dac_modification_setxattr	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_rules_dac_modification_umount	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_dac_modification_umount2	Record Events that Modify the System's Discretiona…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_execution_chacl	Record Any Attempts to Run chacl	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
audit_rules_execution_setfacl	Record Any Attempts to Run setfacl	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_execution_chcon	Record Any Attempts to Run chcon	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_rules_execution_semanage	Record Any Attempts to Run semanage	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_execution_setfiles	Record Any Attempts to Run setfiles	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_execution_setsebool	Record Any Attempts to Run setsebool	Medium	Human Review	MEDIUM	0	—	—	—	0.6s	1
audit_rules_file_deletion_events_rename	Ensure auditd Collects File Deletion Events by Use…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_rules_file_deletion_events_renameat	Ensure auditd Collects File Deletion Events by Use…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_file_deletion_events_rmdir	Ensure auditd Collects File Deletion Events by Use…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_file_deletion_events_unlink	Ensure auditd Collects File Deletion Events by Use…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_file_deletion_events_unlinkat	Ensure auditd Collects File Deletion Events by Use…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_rules_unsuccessful_file_modification_creat	Record Unsuccessful Access Attempts to Files - cre…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
audit_rules_unsuccessful_file_modification_ftruncate	Record Unsuccessful Access Attempts to Files - ftr…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_unsuccessful_file_modification_open	Record Unsuccessful Access Attempts to Files - ope…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_unsuccessful_file_modification_open_by_handle_at	Record Unsuccessful Access Attempts to Files - ope…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_unsuccessful_file_modification_openat	Record Unsuccessful Access Attempts to Files - ope…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_unsuccessful_file_modification_truncate	Record Unsuccessful Access Attempts to Files - tru…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_kernel_module_loading_delete	Ensure auditd Collects Information on Kernel Modul…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_rules_kernel_module_loading_finit	Ensure auditd Collects Information on Kernel Modul…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_kernel_module_loading_init	Ensure auditd Collects Information on Kernel Modul…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_login_events_faillock	Record Attempts to Alter Logon and Logout Events -…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_login_events_lastlog	Record Attempts to Alter Logon and Logout Events -…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_login_events_tallylog	Record Attempts to Alter Logon and Logout Events -…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
audit_privileged_commands_init	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_privileged_commands_poweroff	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_privileged_commands_reboot	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_privileged_commands_shutdown	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_privileged_commands_chage	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_privileged_commands_chsh	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_rules_privileged_commands_crontab	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_rules_privileged_commands_gpasswd	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_privileged_commands_kmod	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_privileged_commands_mount	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_privileged_commands_newgrp	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.6s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
audit_rules_privileged_commands_pam_timestamp_check	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_privileged_commands_passwd	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_privileged_commands_postdrop	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_privileged_commands_postqueue	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_rules_privileged_commands_ssh_agent	Record Any Attempts to Run ssh-agent	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_privileged_commands_ssh_keysign	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_privileged_commands_su	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_rules_privileged_commands_sudo	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1
audit_rules_privileged_commands_sudoedit	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_privileged_commands_umount	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
audit_rules_privileged_commands_unix_chkpwd	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
audit_rules_privileged_commands_unix_update	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_privileged_commands_usehelper	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
audit_rules_privileged_commands_usermod	Ensure auditd Collects Information on the Use of P…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
auditd_data_disk_error_action_stig	Configure auditd Disk Error Action on Disk Error	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
auditd_data_disk_full_action_stig	Configure auditd Disk Full Action when Disk Space …	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
auditd_data_retention_admin_space_left_action	Configure auditd admin_space_left Action on Low Di…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
auditd_data_retention_admin_space_left_percentage	Configure auditd admin_space_left on Low Disk Spac…	Medium	Human Review	MEDIUM	0	—	—	—	0.3s	1
auditd_data_retention_space_left_action	Configure auditd space_left Action on Low Disk Spa…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
auditd_data_retention_space_left_percentage	Configure auditd space_left on Low Disk Space	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1
auditd_freq	Set number of records to cause an explicit flush t…	Medium	Human Review	MEDIUM	0	—	—	—	0.4s	1

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
auditd_name_format	Set type of computer node name logging in audit lo…	Medium	Human Review	MEDIUM	0	—	—	—	0.5s	1

Discarded / Blocked (4)

ID	Title	Severity	Triage	Risk	Attempts	Remedy	Review	QA Safe	Duration	LLM Calls
enable_dracut_fips_module	Enable Dracut FIPS Module	High	Blocked	CRITICAL	0	—	—	—	19.0s	1
enable_fips_mode	Enable FIPS Mode	High	Blocked	CRITICAL	0	—	—	—	10.9s	1
sysctl_crypto_fips_enabled	Set kernel parameter 'crypto.fips_enabled' to 1	High	Blocked	CRITICAL	0	—	—	—	3.2s	1
partition_for_var_tmp	Ensure /var/tmp Located On Separate Partition	Medium	Blocked	CRITICAL	0	—	—	—	0.0s	0

Detailed Finding Reports

package_aide_installed: Install AIDE — SUCCESS

Rule	package_aide_installed
Severity	Medium
Description	The aide package can be installed with the following command: $ sudo dnf install aide
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the AIDE package is a standard, low-risk operation that does not affect authentication, networking, or filesystem cor
Estimated Impact	Potential dependency conflicts if the system is heavily customized

Remediation (2 attempt(s))

Attempt #	1
Commands	dnf install -y aide, dnf repolist, rpm -q aide
Scan Passed	✗
Success	✗
Duration	438.4s
Error	—

Attempt #	2
Commands	dnf list installed aide, printf 'Y\n' | dnf install aide, dnf list installed aide

Scan Passed	✓
Success	✓
Duration	210.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	None/10
Feedback	The plan will successfully install AIDE when executed with appropriate privileges. It correctly verifies the installation before an
Concerns	Requires root privileges but the plan does not explicitly use sudo or check EUID. If executed by a non■root user, the install w

QA Result

Safe	✓
Verdict	The plan installs the aide package, addressing the vulnerability with minimal system impact. The installation process is straigl
Side Effects	Requires root privileges; running as non■root will fail.; Depends on network connectivity and available repositories.; Potential
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	204.6s
Total Tokens	27,142
Cost	$0.0015
Agents	Remedy(10), Review(1), Qa(1)

aide_build_database: Build and Test AIDE Database — SUCCESS

Rule	aide_build_database
Severity	Medium
Description	Run the following command to generate a new database: $ sudo /usr/sbin/aide --init By default, the database will be written to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Building and initializing the AIDE database is a standard security hardening step that does not affect authentication, networkin
Estimated Impact	filesystems affected

Remediation (2 attempt(s))

Attempt #	1
Commands	rpm -q aide, dnf install -y aide, dnf install -y aide
Scan Passed	✗
Success	✗
Duration	437.4s
Error	—

Attempt #	2
Commands	/usr/sbin/aide --init, cp -p /var/lib/aide/aide.db.gz /var/lib/aide/aide.db.gz.bak 2>/dev/null || true, cp -p /var/lib/aide/aide.db.new

Scan Passed	✓
Success	✓
Duration	465.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly rebuilds and validates the AIDE database, includes permission setting, and performs a check, but it lacks e
Concerns	No explicit exit status checks after each command; No backup of existing /var/lib/aide/aide.db.gz before overwrite; Assumes '

QA Result

Safe	✓
Verdict	The remediation rebuilds the AIDE database, preserves file ownership/permissions, and runs a validity check without altering
Side Effects	Previous AIDE database snapshot is overwritten (not backed up); Installation may trigger package resolution overhead
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	22
Duration	275.7s
Total Tokens	72,569
Cost	$0.0033
Agents	Remedy(20), Review(1), Qa(1)

aide_check_audit_tools: Configure AIDE to Verify the Audit Tools — FAILED

Rule	aide_check_audit_tools
Severity	Medium
Description	The operating system file integrity tool must be configured to protect the integrity of the audit tools.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves installing the AIDE package if missing and adding simple entries to /etc/aide.conf to monitor audit to
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	20.8s
Error	—

Attempt #	2
Commands	—

Scan Passed	✗
Success	✗
Duration	27.0s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	72.6s
Error	—

Review Verdict

Approved	✗
Optimal	✗
Security Score	5/10
Feedback	The plan installs AIDE, validates the config, and adds rules for auditctl and auditd, but it does not explicitly create a monitorin
Concerns	Missing monitoring rule for /usr/sbin/ausearch; Potential syntax errors or accidental line replacements due to incomplete sed

LLM Metrics

LLM Calls	2
Duration	72.6s
Total Tokens	6,616
Cost	$0.0005
Agents	Remedy(1), Review(1)

aide_scan_notification: Configure Notification of Post-AIDE Scan Details — FAILED

Rule	aide_scan_notification
Severity	Medium
Description	AIDE should notify appropriate personnel of the details of a scan after the scan has been run. If AIDE has already been config
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Adding a cron job to send AIDE scan results via mail is a straightforward configuration change that does not affect authentica
Estimated Impact	Incorrect cron syntax could cause duplicate entries or mail failures; Mail service must be configured and reachable

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	20.8s
Error	—

Attempt #	2
Commands	—

Scan Passed	✗
Success	✗
Duration	42.0s
Error	—

Attempt #	3
Commands	dnf install -y aide, dnf install -y aide, echo remediation aborted. Unable to continue due to SSH session closure.
Scan Passed	✗
Success	✗
Duration	179.1s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will add or update a cron line that triggers AIDE and emails the output, thereby achieving the desired notification fun
Concerns	Only /etc/crontab is modified – systems using /etc/cron.d, /etc/cron.daily/aide, or other cron directories will remain unchanged

QA Result

Safe	✓
Verdict	The planned actions install the aide package (idempotent), verify /etc/crontab exists, and safely add or update a cron entry th
Side Effects	Potential for duplicate cron lines if the duplicate■check regex logic fails; minor formatting changes to /etc/crontab may occur,
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	178.3s
Total Tokens	37,661
Cost	$0.0022
Agents	Remedy(10), Review(1), Qa(1)

aide_use_fips_hashes: Configure AIDE to Use FIPS 140-2 for Validating Hashes — FAILED

Rule	aide_use_fips_hashes
Severity	Medium
Description	By default, the sha512 option is added to the NORMAL ruleset in AIDE. If using a custom ruleset or the sha512 option is miss
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves editing the /etc/aide.conf file to add the sha512 hash algorithm and remove disallowed hashes. This
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	test -f /etc/aide.conf && echo exists || echo missing, echo test, mkdir -p /var/backups

Scan Passed	✗
Success	✗
Duration	169.9s
Error	—

Attempt #	2
Commands	rpm -q aide, true
Scan Passed	✗
Success	✗
Duration	188.9s
Error	—

Attempt #	3
Commands	ls -l /etc/aide.conf, rpm -q aide, dnf install -y aide
Scan Passed	✗
Success	✗
Duration	333.9s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The script, when run as root, will install AIDE if missing, then edit /etc/aide.conf to add the sha512 algorithm to all rule set def

Concerns	No backup of /etc/aide.conf is created – accidental corruption requires manual recovery.; The approach updates every upperc

QA Result

Safe	✓
Verdict	The script installs AIDE if absent and updates all rule■sets in /etc/aide.conf to ensure the sha512 hash algorithm is included w
Side Effects	No backup of /etc/aide.conf – accidental corruption requires manual recovery; Potential modification of custom rule■sets that
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	332.9s
Total Tokens	54,839
Cost	$0.0036
Agents	Remedy(11), Review(1), Qa(1)

enable_dracut_fips_module: Enable Dracut FIPS Module — DISCARDED

Rule	enable_dracut_fips_module
Severity	High
Description	Red Hat Enterprise Linux 9 has an installation-time kernel flag that can enable FIPS mode. The installer must be booted with
Recommendation	Review and remediate: Enable Dracut FIPS Module
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗

Human Review	✗
Risk Level	CRITICAL
Reason	Enabling FIPS mode on a preexisting RHEL 9 system requires boot-time kernel flag and dracut module changes that are not
Estimated Impact	reboot required; FIPS mode activation; bootloader/kernel parameter changes; potential system lockout

LLM Metrics

LLM Calls	1
Duration	19.0s
Total Tokens	1,441
Cost	$0.0001
Agents	Triage(1)

enable_fips_mode: Enable FIPS Mode — DISCARDED

Rule	enable_fips_mode
Severity	High
Description	Red Hat Enterprise Linux 9 has an installation-time kernel flag that can enable FIPS mode. The installer must be booted with
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! (["${container:-}" == "bwrap-osbuild"]) && rpm
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Enabling FIPS mode requires a kernel boot parameter (fips=1) and is not supported on an existing system; attempting to rem

Estimated Impact	reboot required; FIPS mode change; kernel boot parameter alteration; potential system instability; permanent finding on instal

LLM Metrics

LLM Calls	1
Duration	10.9s
Total Tokens	1,353
Cost	$0.0001
Agents	Triage(1)

fips_crypto_subpolicy: FIPS Must Use a Supported Subpolicy — FAILED

Rule	fips_crypto_subpolicy
Severity	Medium
Description	Sub-policies can be used to modify existing crypto policies. Some sub-policies such as NO-ENFORCE-EMS reduce the secu
Recommendation	Review and remediate: FIPS Must Use a Supported Subpolicy
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The subpolicy configuration is a straightforward system setting that can be reviewed and corrected without risking lockout or c
Estimated Impact	Potential reduction in cryptographic security if unsupported subpolicy is used; Possible service disruption if incompatible ciphe

Remediation (3 attempt(s))

Attempt #	1

Commands	update-crypto-policies --set OSPP, cat /etc/crypto-policies/back-ends/openssl.config, echo test
Scan Passed	✗
Success	✗
Duration	102.9s
Error	—

Attempt #	2
Commands	sed -i 's/^CRYPTO_POLICY=.*/CRYPTO_POLICY=OSPP/' /etc/sysconfig/crypto-policies
Scan Passed	✗
Success	✗
Duration	277.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	192.3s
Error	—

Review Verdict

Approved	✗
Optimal	✗
Security Score	4/10

Feedback	The proposed sed command may fail to add the CRYPTO_POLICY line when it is absent, and the plan does not use the offic
Concerns	Potential sed failure to append CRYPTO_POLICY if missing; Manual file editing instead of using update-crypto-policies may l

LLM Metrics

LLM Calls	2
Duration	192.3s
Total Tokens	9,234
Cost	$0.0010
Agents	Remedy(1), Review(1)

fips_custom_stig_sub_policy: Implement STIG Sub Crypto Policy — FAILED

Rule	fips_custom_stig_sub_policy
Severity	Medium
Description	Create a custom cryptographic policy to follow the guidance from DISA.
Recommendation	Remediation script: cat << 'EOF' > /etc/crypto-policies/policies/modules/STIG.pmod cipher@SSH=AES-256-GCM AES-256-C
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation follows a standard DISA STIG cryptographic policy change that is widely used and documented. It does not i
Estimated Impact	authentication/authorization affected; networking affected; Potential temporary SSH connectivity issues if clients do not suppo

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	228.1s
Error	—

Attempt #	2
Commands	ls -l /etc/crypto-policies/policies/modules, echo hello
Scan Passed	✗
Success	✗
Duration	84.9s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	22.1s
Error	—

Review Verdict

Approved	✗
Optimal	✗

Security Score	None/10
Feedback	Review output was not valid JSON. Raw: {"finding_id":"fips_custom_stig_sub_policy","is_optimal":false,"approve":true,"feedba
Concerns	Could not parse LLM response

LLM Metrics

LLM Calls	3
Duration	22.0s
Total Tokens	7,136
Cost	$0.0006
Agents	Remedy(2), Review(1)

sysctl_crypto_fips_enabled: Set kernel parameter 'crypto.fips_enabled' to 1 — DISCARDED

Rule	sysctl_crypto_fips_enabled
Severity	High
Description	System running in FIPS mode is indicated by kernel parameter 'crypto.fips_enabled'. This parameter should be set to 1 in FIP
Recommendation	Review and remediate: Set kernel parameter 'crypto.fips_enabled' to 1
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Enabling FIPS mode requires adding the fips=1 kernel boot parameter at installation time; it cannot be enabled on a running s
Estimated Impact	authentication/authorization affected; FIPS mode activation; bootloader modification; potential loss of cryptographic functiona

LLM Metrics

LLM Calls	1
Duration	3.2s
Total Tokens	1,311
Cost	$0.0002
Agents	Triage(1)

configure_crypto_policy: Configure System Cryptography Policy — FAILED

Rule	configure_crypto_policy
Severity	High
Description	To configure the system cryptography policy to use ciphers only from the policy, run the following command: $ sudo update-c
Recommendation	Remediation script: var_system_crypto_policy='' stderr_of_call=$(update-crypto-policies --set ${var_system_crypto_policy} 2>
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Updating the system cryptography policy via update-crypto-policies is a standard STIG hardening action that does not risk loc
Estimated Impact	authentication/authorization affected; networking affected; Potential temporary disruption of SSH/TLS connections if the new

Remediation (3 attempt(s))

Attempt #	1
Commands	update-crypto-policies --set FUTURE, update-crypto-policies --set DEFAULT, echo test

Scan Passed	✗
Success	✗
Duration	149.4s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	60.2s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	10.2s
Error	—

Review Verdict

Approved	✗
Optimal	✗
Security Score	4/10
Feedback	The current plan does not specify a concrete cryptographic policy to set (var_system_crypto_policy is empty) and lacks critica

Concerns	var_system_crypto_policy is set to an empty string, so the command likely fails or results in an undefined policy.; No check fo

LLM Metrics

LLM Calls	3
Duration	10.2s
Total Tokens	7,413
Cost	$0.0007
Agents	Remedy(2), Review(1)

installed_OS_is_vendor_supported: The Installed Operating System Is Vendor Supported — REQUIRES_HUMAN_REVIEW

Rule	installed_OS_is_vendor_supported
Severity	High
Description	The installed operating system must be maintained by a vendor. Red Hat Enterprise Linux is supported by Red Hat, Inc. As th
Recommendation	Review and remediate: The Installed Operating System Is Vendor Supported
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The remediation involves ensuring the system runs a Red Hat Enterprise Linux release that is still supported by Red Hat. This
Estimated Impact	reboot required; OS end■of■life; potential unpatched vulnerabilities

LLM Metrics

LLM Calls	1

Duration	11.5s
Total Tokens	1,356
Cost	$0.0002
Agents	Triage(1)

partition_for_var_tmp: Ensure /var/tmp Located On Separate Partition — DISCARDED

Rule	partition_for_var_tmp
Severity	Medium
Description	The /var/tmp directory is a world-writable directory used for temporary file storage. Ensure it has its own partition or logical vo
Recommendation	Remediation script: part /var/tmp
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✗
Risk Level	CRITICAL
Reason	Filesystem/partition/mount-option changes can break boot or services and should not be auto-remediated.
Estimated Impact	reboot required; filesystems affected; filesystems/partitioning; service disruption risk

package_gnutls-utils_installed: Ensure gnutls-utils is installed — FAILED

Rule	package_gnutls-utils_installed
Severity	Medium
Description	The gnutls-utils package can be installed with the following command: $ sudo dnf install gnutls-utils

Recommendation	Remediation script: if ! rpm -q --quiet "gnutls-utils" ; then dnf install -y "gnutls-utils" fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the gnutls-utils package is a standard, non-disruptive operation that does not affect authentication, networking, or fil
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	110.4s
Error	—

Attempt #	2
Commands	dnf install -y gnutls-utils, rpm -q gnutls-utils, dnf install -y gnutls-utils, dnf install -y gnutls-utils, dnf install -y gnutls-utils
Scan Passed	✗
Success	✗
Duration	701.6s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	133.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	Plan is sufficient to resolve the vulnerability, though adding exit status handling and basic logging would strengthen reliability.
Concerns	No explicit exit status or error handling for the install command.; No logging or audit trail to confirm operation.

LLM Metrics

LLM Calls	3
Duration	133.5s
Total Tokens	5,624
Cost	$0.0005
Agents	Remedy(1), Review(1), Qa(1)

package_nss-tools_installed: Ensure nss-tools is installed — SUCCESS

Rule	package_nss-tools_installed
Severity	Medium

Description	The nss-tools package can be installed with the following command: $ sudo dnf install nss-tools
Recommendation	Remediation script: if ! rpm -q --quiet "nss-tools" ; then dnf install -y "nss-tools" fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the nss-tools package is a standard, non-disruptive operation that does not affect authentication, networking, or files
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	rpm -q nss-tools, dnf install -y nss-tools
Scan Passed	✓
Success	✓
Duration	279.9s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	8/10
Feedback	The plan correctly checks for and installs the nss-tools package, which resolves the vulnerability. It uses idempotent logic and
Concerns	—

QA Result

Safe	✓
Verdict	Installing nss-tools is a harmless package addition that does not impact existing services or authentication mechanisms. The
Side Effects	Possible brief package download and installation time, minimal temporary repository access
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	161.3s
Total Tokens	23,016
Cost	$0.0010
Agents	Triage(1), Remedy(9), Review(1), Qa(1)

package_subscription-manager_installed: Install subscription-manager Package — SUCCESS

Rule	package_subscription-manager_installed
Severity	Medium
Description	The subscription-manager package can be installed with the following command: $ sudo dnf install subscription-manager
Recommendation	Remediation script: if ! rpm -q --quiet "subscription-manager" ; then dnf install -y "subscription-manager" fi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗

Risk Level	LOW
Reason	Installing the subscription-manager package is a standard, non-disruptive operation that does not affect authentication, netwo
Estimated Impact	—

Remediation (1 attempt(s))

Attempt #	1
Commands	if ! rpm -q --quiet subscription-manager; then dnf install -y subscription-manager; fi
Scan Passed	✓
Success	✓
Duration	88.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will successfully install the subscription-manager package, thereby resolving the vulnerability.
Concerns	Plan does not explicitly check for root/sudo privileges; running dnf as a non■root user will fail.; Uses unconditional installation

QA Result

Safe	✓
Verdict	Running 'dnf install -y subscription-manager' is idempotent and only installs a missing package with no configuration changes
Side Effects	may install additional dependency packages during the transaction
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	10
Duration	43.7s
Total Tokens	28,333
Cost	$0.0012
Agents	Triage(1), Remedy(7), Review(1), Qa(1)

ensure_gpgcheck_local_packages: Ensure gpgcheck Enabled for Local Packages — FAILED

Rule	ensure_gpgcheck_local_packages
Severity	High
Description	dnf should be configured to verify the signature(s) of local packages prior to installation. To configure dnf to verify signatures
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q dnf; then # Strip any search characte
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling local package GPG check is a straightforward configuration change that does not affect authentication, networking,
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	cp /etc/dnf/dnf.conf /etc/dnf/dnf.conf.bak, cp /etc/dnf/dnf.conf /etc/dnf/dnf.conf.bak

Scan Passed	✗
Success	✗
Duration	54.1s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	20.9s
Error	—

Attempt #	3
Commands	cp /etc/dnf/dnf.conf /etc/dnf/dnf.conf.bak-$(date +%s), echo test
Scan Passed	✗
Success	✗
Duration	31.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will enable local GPG checking and resolves the vulnerability. It creates a timestamped backup, replaces or append

Concerns	Sed regex is case■sensitive and may miss lines like 'LocalPkg_GpgCheck', omitting leading comments on the same line afte

QA Result

Safe	✓
Verdict	The plan only modifies /etc/dnf/dnf.conf to enable local GPG checking; it does not touch SSH, networking, auditd or firewall c
Side Effects	May block installation of unsigned local packages via dnf
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	31.1s
Total Tokens	35,964
Cost	$0.0028
Agents	Remedy(9), Review(1), Qa(1)

enable_authselect: Enable authselect — FAILED

Rule	enable_authselect
Severity	Medium
Description	Configure user authentication setup to use the authselect tool. If authselect profile is selected, the rule will enable the profile.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_authselect_pro
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓

Human Review	✗
Risk Level	LOW
Reason	Enabling authselect is a standard STIG hardening step for authentication that follows established patterns and does not pose
Estimated Impact	authentication/authorization affected; Potential misconfiguration of PAM if wrong profile selected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	17.2s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	65.7s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗

Duration	15.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will correctly install and activate the authselect sssd profile, thereby addressing the vulnerability. However, it lacks s
Concerns	No verification of authselect command exit status after selection; if selection fails, the system may remain unmanaged.; Step

QA Result

Safe	✗
Verdict	The plan forcefully applies the 'sssd' authselect profile without first confirming that a functional sssd service is configured on t
Side Effects	Potential loss of local user authentication, resulting in SSH login failure; Possible interruption of services that rely on PAM, e.g
Regression	✗
Recommendation	Rollback

LLM Metrics

LLM Calls	3
Duration	15.8s
Total Tokens	6,967
Cost	$0.0007
Agents	Remedy(1), Review(1), Qa(1)

banner_etc_issue: Modify the System Login Banner — FAILED

Rule	banner_etc_issue
Severity	Medium
Description	To configure the system login banner edit /etc/issue. Replace the default text with a message compliant with the local site pol
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then login_banner_text=
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing the /etc/issue banner is a simple configuration edit that does not affect authentication, networking, or critical system
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	20.6s
Error	—

Attempt #	2
Commands	cp /etc/issue /etc/issue.bak, printf '%s\n%s\n' "You are accessing a U.S. Government (USG) Information System (IS) that is p
Scan Passed	✗
Success	✗

Duration	439.2s
Error	—

Attempt #	3
Commands	pwd, echo 'checking connectivity'
Scan Passed	✗
Success	✗
Duration	214.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan outlines a straightforward replacement of /etc/issue with a DoD■approved banner and restores SELinux context, wh
Concerns	Missing backup of the current /etc/issue file before overwriting it.; Uncertain whether the full DoD disclaimer text is included as

QA Result

Safe	✓
Verdict	Replacing /etc/issue with a properly formatted DoD banner and running restorecon will not impact critical services such as ssl
Side Effects	Potential missing backup of original /etc/issue; Possibility of missing trailing newline or slight text formatting issues
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13

Duration	212.6s
Total Tokens	35,708
Cost	$0.0018
Agents	Remedy(11), Review(1), Qa(1)

account_password_pam_faillock_password_auth: Configure the Use of the pam_faillock.so Module in the /etc/pam.d/password-auth … — *FAILED*

Rule	account_password_pam_faillock_password_auth
Severity	Medium
Description	The pam_faillock.so module must be loaded in preauth in /etc/pam.d/password-auth.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if [-f /usr/bin/auths
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation follows standard STIG hardening patterns for PAM authentication, using authselect to enable the faillock fea
Estimated Impact	authentication/authorization affected; Potential misconfiguration could temporarily block authentication if parameters are incor

Remediation (3 attempt(s))

Attempt #	1
Commands	authselect enable-feature faillock, authselect check, sed -i "5 i\n auth required pam_faillock.so preauth silent audit d
Scan Passed	✗

Success	✗
Duration	212.2s
Error	—

Attempt #	2
Commands	authselect enable-feature faillock --force, authselect enable-feature faillock --force, echo hello, cat /etc/pam.d/password-auth
Scan Passed	✗
Success	✗
Duration	341.5s
Error	—

Attempt #	3
Commands	cat /etc/pam.d/password-auth
Scan Passed	✗
Success	✗
Duration	135.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan will address the vulnerability by inserting the required preauth faillock entry, though it diverges from the recommende
Concerns	Manual editing may clash with systems that use authselect, potentially leaving the profile inconsistent or overwritten on future

QA Result

Safe	✓
Verdict	The plan adds the required pam_faillock preauth line in a controlled manner using sed, ensuring the line is present and not du
Side Effects	Minor risk of duplicate line if the unique marker logic fails; may cause login lockouts after five failed attempts (intentional).
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	135.0s
Total Tokens	39,975
Cost	$0.0020
Agents	Remedy(10), Review(1), Qa(1)

account_password_pam_faillock_system_auth: Configure the Use of the pam_faillock.so Module in the /etc/pam.d/system-auth Fi… — FAILED

Rule	account_password_pam_faillock_system_auth
Severity	Medium
Description	The pam_faillock.so module must be loaded in preauth in /etc/pam.d/system-auth.
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if [-f /usr/bin/auths
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗

Risk Level	LOW
Reason	The remediation follows a standard STIG hardening pattern for PAM configuration using authselect, which is designed to safe
Estimated Impact	authentication/authorization affected; Misconfiguration could temporarily block authentication if syntax errors occur

Remediation (3 attempt(s))

Attempt #	1
Commands	cat /etc/pam.d/system-auth, authselect --force enable-feature with-faillock, test -f /etc/pam.d/system-auth && echo found || ec
Scan Passed	✗
Success	✗
Duration	280.9s
Error	—

Attempt #	2
Commands	authselect enable-feature with-faillock
Scan Passed	✗
Success	✗
Duration	335.2s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	124.0s

Error	—

Review Verdict

Approved	✗
Optimal	✗
Security Score	None/10
Feedback	Review output was not valid JSON. Raw: {"finding_id":"account_password_pam_faillock_system_auth","is_optimal":false,"app
Concerns	Could not parse LLM response

LLM Metrics

LLM Calls	5
Duration	123.4s
Total Tokens	14,399
Cost	$0.0011
Agents	Remedy(4), Review(1)

accounts_passwords_pam_faillock_deny: Lock Accounts After Failed Password Attempts — REQUIRES_HUMAN_REVIEW

Rule	accounts_passwords_pam_faillock_deny
Severity	Medium
Description	This rule configures the system to lock out accounts after a number of incorrect login attempts using pam_faillock.so. pam_fa
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗

Human Review	✓
Risk Level	LOW
Reason	The remediation follows standard STIG hardening patterns for PAM authentication, using authselect or controlled edits to PAI
Estimated Impact	authentication/authorization affected; Potential account lockout if deny value misconfigured; Requires careful editing of PAM f

LLM Metrics

LLM Calls	1
Duration	8.0s
Total Tokens	1,487
Cost	$0.0002
Agents	Triage(1)

accounts_passwords_pam_faillock_deny_root: Configure the root Account for Failed Password Attempts — REQUIRES_HUMAN_REVIEW

Rule	accounts_passwords_pam_faillock_deny_root
Severity	Medium
Description	This rule configures the system to lock out the root account after a number of incorrect login attempts using pam_faillock.so. p
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW

Reason	The remediation follows standard STIG hardening for PAM, using authselect to enable faillock, which is a documented and sa
Estimated Impact	authentication/authorization affected; Potential root lockout if PAM configuration is incorrect; Requires correct pam_faillock se

LLM Metrics

LLM Calls	1
Duration	2.3s
Total Tokens	1,283
Cost	$0.0001
Agents	Triage(1)

accounts_passwords_pam_faillock_dir: Lock Accounts Must Persist — REQUIRES_HUMAN_REVIEW

Rule	accounts_passwords_pam_faillock_dir
Severity	Medium
Description	This rule ensures that the system lock out accounts using pam_faillock.so persist after system reboot. From "pam_faillock" m
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW
Reason	The remediation involves a standard PAM configuration change to set a persistent faillock tally directory, following STIG hard
Estimated Impact	authentication/authorization affected; Potential misconfiguration could lock out users if the directory path is incorrect or permis

LLM Metrics

LLM Calls	1
Duration	1.8s
Total Tokens	1,364
Cost	$0.0001
Agents	Triage(1)

accounts_passwords_pam_faillock_interval: Set Interval For Counting Failed Password Attempts — FAILED

Rule	accounts_passwords_pam_faillock_interval
Severity	Medium
Description	Utilizing pam_faillock.so, the fail_interval directive configures the system to lock out an account after a number of incorrect log
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves configuring a PAM faillock interval, a standard authentication hardening step that does not affect co
Estimated Impact	authentication/authorization affected; Incorrect interval value could temporarily lock accounts if set too low

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗

Success	✗
Duration	66.8s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	290.8s
Error	—

Attempt #	3
Commands	cat /etc/security/faillock.conf, test -f /etc/security/faillock.conf && echo 'exists', echo ok
Scan Passed	✗
Success	✗
Duration	59.5s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	—
Concerns	Potential conflict with authselect■managed PAM configuration; the plan directly edits /etc/security/faillock.conf even when au

QA Result

Safe	✓
Verdict	The plan safely backs up /etc/security/faillock.conf, checks for an intact authselect profile, and then edits the file in-place to se
Side Effects	Minor risk: if sed expression mis■matches a comment, the comment could be inadvertently removed; however the pattern re
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	58.1s
Total Tokens	51,217
Cost	$0.0040
Agents	Remedy(14), Review(1), Qa(1)

accounts_passwords_pam_faillock_unlock_time: Set Lockout Time for Failed Password Attempts — REQUIRES_HUMAN_REVIEW

Rule	accounts_passwords_pam_faillock_unlock_time
Severity	Medium
Description	This rule configures the system to lock out accounts during a specified time period after a number of incorrect login attempts
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	LOW

Reason	The remediation involves configuring a standard PAM module (pam_faillock) to set an unlock time, which is a common STIG
Estimated Impact	authentication/authorization affected; Incorrect unlock_time value could temporarily lock users out

LLM Metrics

LLM Calls	1
Duration	15.9s
Total Tokens	1,309
Cost	$0.0001
Agents	Triage(1)

accounts_password_pam_dcredit: Ensure PAM Enforces Password Requirements - Minimum Digit Characters — FAILED

Rule	accounts_password_pam_dcredit
Severity	Medium
Description	The pam_pwquality module's dcredit parameter controls requirements for usage of digits in a password. When set to a negati
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The change involves a standard PAM password policy adjustment that is widely accepted in STIG hardening and does not aff
Estimated Impact	authentication/authorization affected; Potential user lockout if existing passwords lack digits; Requires users to change passw

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	7.9s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	17.5s
Error	—

Attempt #	3
Commands	cp /etc/security/pwquality.conf /etc/security/pwquality.conf.bak, echo hello, ls -l /etc/security
Scan Passed	✗
Success	✗
Duration	52.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	None/10
Feedback	The plan would functionally enforce a minimum of one digit in passwords if executed correctly. It addresses the key concerns
Concerns	Sed command may not delete commented dcredit lines; risk of leaving duplicate or commented entries.; No backup or handlin

QA Result

Safe	✓
Verdict	The proposed changes correctly set dcredit to -1, ensuring at least one digit is required while removing potential overrides. No
Side Effects	Password changes that do not include a digit will be rejected until the user creates a compliant password
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	51.1s
Total Tokens	32,531
Cost	$0.0024
Agents	Remedy(10), Review(1), Qa(1)

accounts_password_pam_dictcheck: Ensure PAM Enforces Password Requirements - Prevent the Use of Dictionary Words — FAILED

Rule	accounts_password_pam_dictcheck
Severity	Medium
Description	The pam_pwquality module's dictcheck check if passwords contains dictionary words. When dictcheck is set to 1 passwords w
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves a straightforward PAM configuration change to enable dictionary word checking, a standard STIG h
Estimated Impact	authentication/authorization affected

Remediation (3 attempt(s))

Attempt #	1
Commands	sed -i '/^\s*dictcheck\s*=.*$/d' /etc/security/pwquality.conf.d/*.conf, echo hi, mkdir -p /etc/security/pwquality.conf.d, echo hello
Scan Passed	✗
Success	✗
Duration	79.5s
Error	—

Attempt #	2
Commands	install -d -m 755 /etc/security/pwquality.conf.d, install -d -m 755 /etc/security/pwquality.conf.d, echo ok, ls -l /tmp
Scan Passed	✗
Success	✗
Duration	51.7s
Error	—

Attempt #	3
Commands	sed -i '/^ *dictcheck[[:space:]]*=/d' /etc/security/pwquality.conf, ls -l /etc/security/pwquality.conf, touch /tmp/testfile
Scan Passed	✗

Success	✗
Duration	377.8s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan will enable dictionary word checks by setting dictcheck=1 in the primary pam_pwquality configuration. However it do
Concerns	Does not remove or check for dictcheck entries in /etc/security/pwquality.conf.d/*.conf, which could override the main setting.

QA Result

Safe	✓
Verdict	The proposed plan updates the primary pam_pwquality configuration file to enforce dictionary word checks, which is the corre
Side Effects	If any dictionary check settings exist in /etc/security/pwquality.conf.d/*.conf, those files could override the main setting, potent
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	374.5s
Total Tokens	66,921
Cost	$0.0049
Agents	Remedy(14), Review(1), Qa(1)

accounts_password_pam_difok: Ensure PAM Enforces Password Requirements - Minimum Different Characters — *FAILED*

Rule	accounts_password_pam_difok
Severity	Medium
Description	The pam_pwquality module's difok parameter sets the number of characters in a password that must not be present in and ol
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Changing the difok setting is a standard PAM password policy adjustment that follows STIG hardening patterns and does not
Estimated Impact	authentication/authorization affected; Potential password change failures if the new difok value is too restrictive for existing us

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	25.9s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗

Success	✗
Duration	11.9s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	38.9s
Error	—

Review Verdict

Approved	✗
Optimal	✗
Security Score	None/10
Feedback	Review output was not valid JSON. Raw: {"finding_id":"accounts_password_pam_difok","is_optimal":false,"approve":true,"fee
Concerns	Could not parse LLM response

LLM Metrics

LLM Calls	5
Duration	38.8s
Total Tokens	14,852
Cost	$0.0012
Agents	Remedy(2), Review(2), Qa(1)

accounts_password_pam_enforce_root: Ensure PAM Enforces Password Requirements - Enforce for root User — *FAILED*

Rule	accounts_password_pam_enforce_root
Severity	Medium
Description	The pam_pwquality module's enforce_for_root parameter controls requirements for enforcing password complexity for the roo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling enforce_for_root in /etc/security/pwquality.conf is a standard PAM configuration change that does not affect system
Estimated Impact	authentication/authorization affected; root password complexity requirement

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	LLM API error 402: {"error":{"message":"This request requires more credits, or fewer max_tokens. You requested up to 65536

Attempt #	2
Commands	—
Scan Passed	✗

Success	✗
Duration	—
Error	LLM API error 402: {"error":{"message":"This request requires more credits, or fewer max_tokens. You requested up to 65536

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	LLM API error 402: {"error":{"message":"This request requires more credits, or fewer max_tokens. You requested up to 65536

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Remedy(1)

accounts_password_pam_lcredit: Ensure PAM Enforces Password Requirements - Minimum Lowercase Characters — REQUIRES_HUMAN_REVIEW

Rule	accounts_password_pam_lcredit
Severity	Medium
Description	The pam_pwquality module's lcredit parameter controls requirements for usage of lowercase letters in a password. When set
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw

Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_password_pam_maxclassrepeat: Ensure PAM Enforces Password Requirements - Maximum Consecutive Repeating Charac… — REQUIRES_HUMAN_REVIEW

Rule	accounts_password_pam_maxclassrepeat
Severity	Medium
Description	The pam_pwquality module's maxclassrepeat parameter controls requirements for consecutive repeating characters from the
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗

Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	1.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_password_pam_maxrepeat: Set Password Maximum Consecutive Repeating Characters — REQUIRES_HUMAN_REVIEW

Rule	accounts_password_pam_maxrepeat
Severity	Medium
Description	The pam_pwquality module's maxrepeat parameter controls requirements for consecutive repeating characters. When set to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A

Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_password_pam_minclass: Ensure PAM Enforces Password Requirements - Minimum Different Categories — REQUIRES_HUMAN_REVIEW

Rule	accounts_password_pam_minclass
Severity	Medium
Description	The pam_pwquality module's minclass parameter controls requirements for usage of different character classes, or types, of c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1

Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_password_pam_minlen: Ensure PAM Enforces Password Requirements - Minimum Length — REQUIRES_HUMAN_REVIEW

Rule	accounts_password_pam_minlen
Severity	Medium
Description	The pam_pwquality module's minlen parameter controls requirements for minimum characters required in a password. Add m
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000

Agents	Triage(1)

accounts_password_pam_ocredit: Ensure PAM Enforces Password Requirements - Minimum Special Characters — REQUIRES_HUMAN_REVIEW

Rule	accounts_password_pam_ocredit
Severity	Medium
Description	The pam_pwquality module's ocredit= parameter controls requirements for usage of special (or "other") characters in a passw
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_password_pam_pwquality_retry: Ensure PAM Enforces Password Requirements - Authentication Retry Prompts Permitt… — *REQUIRES_HUMAN_REVIEW*

Rule	accounts_password_pam_pwquality_retry
Severity	Medium
Description	To configure the number of retry prompts that are permitted per-session: Edit the /etc/security/pwquality.conf to include retry=
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_password_par
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_password_pam_ucredit: Ensure PAM Enforces Password Requirements - Minimum Uppercase Characters — *REQUIRES_HUMAN_REVIEW*

Rule	accounts_password_pam_ucredit

Severity	Medium
Description	The pam_pwquality module's ucredit= parameter controls requirements for usage of uppercase letters in a password. When s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q libpw
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

service_debug-shell_disabled: Disable debug-shell SystemD Service — FAILED

Rule	service_debug-shell_disabled
Severity	Medium
Description	SystemD's debug-shell service is intended to diagnose SystemD related boot issues with various systemctl commands. Once
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE

Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling the debug-shell service is a standard hardening step that does not affect authentication, networking, or filesystem in
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	systemctl stop debug-shell.service, systemctl stop debug-shell.service, systemctl mask --now debug-shell.service, echo 'test',
Scan Passed	✗
Success	✗
Duration	210.2s
Error	—

Attempt #	2
Commands	systemctl disable --now debug-shell.service, ln -sf /dev/null /etc/systemd/system/debug-shell.service, systemctl mask --now d
Scan Passed	✗
Success	✗
Duration	145.8s
Error	—

Attempt #	3

Commands	systemctl stop debug-shell.service, ln -s /dev/null /etc/systemd/system/debug-shell.service, echo 'test'
Scan Passed	✗
Success	✗
Duration	165.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan effectively masks the debug-shell service and socket by creating symlinks to /dev/null and reloading systemd, ensur
Concerns	Commands assume root privileges but do not explicitly enforce them or use sudo; non■root execution will fail silently.; The pl

QA Result

Safe	✓
Verdict	Masking the debug-shell.service and debug-shell.socket by creating symlinks to /dev/null is a valid, non■intrusive way to prev
Side Effects	Possible lingering running instance of debug-shell.service until it is manually stopped or system rebooted
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	11
Duration	165.1s
Total Tokens	37,497
Cost	$0.0020

Agents	Remedy(9), Review(1), Qa(1)

disable_ctrlaltdel_burstaction: Disable Ctrl-Alt-Del Burst Action — FAILED

Rule	disable_ctrlaltdel_burstaction
Severity	High
Description	By default, SystemD will reboot the system if the Ctrl-Alt-Del key sequence is pressed Ctrl-Alt-Delete more than 7 times in 2 s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q syste
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation requires a simple configuration change in /etc/systemd/system.conf, which is unlikely to cause lockout or sys
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	cat /etc/systemd/system.conf, test -f /etc/systemd/system.conf; echo $?
Scan Passed	✗
Success	✗
Duration	37.0s
Error	—

Attempt #	2

Commands	—
Scan Passed	✗
Success	✗
Duration	94.0s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	LLM API error 402: {"error":{"message":"This request requires more credits, or fewer max_tokens. You requested up to 65536

LLM Metrics

LLM Calls	9
Duration	50.5s
Total Tokens	27,464
Cost	$0.0021
Agents	Remedy(7), Review(1), Qa(1)

disable_ctrlaltdel_reboot: Disable Ctrl-Alt-Del Reboot Activation — REQUIRES_HUMAN_REVIEW

Rule	disable_ctrlaltdel_reboot
Severity	High
Description	By default, SystemD will reboot the system if the Ctrl-Alt-Del key sequence is pressed. To configure the system to ignore the

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if { rpm --quiet -q k
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

package_opensc_installed: Install the opensc Package For Multifactor Authentication — FAILED

Rule	package_opensc_installed
Severity	Medium
Description	The opensc package can be installed with the following command: $ sudo dnf install opensc
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "c
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the opensc package is a standard package installation that does not alter authentication configuration, networking, c
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	dnf install -y opensc, rpm -q opensc
Scan Passed	✗
Success	✗
Duration	102.6s
Error	—

Attempt #	2
Commands	rpm -q kernel-core, cat /etc/os-release
Scan Passed	✗
Success	✗
Duration	177.0s
Error	—

Attempt #	3
Commands	yum install -y opensc, yum install opensc, rpm -q opensc, which dnf, dnf install -y opensc
Scan Passed	✗

Success	✗
Duration	502.2s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The plan will install the opensc package and thus resolve the vulnerability. It lacks several optional checks and robust error ha
Concerns	No kernel-core pre■check – may run on unsupported platforms; No silent rpm check to confirm opensc is already installed; N

QA Result

Safe	✓
Verdict	Installing the opensc package with dnf does not affect critical system services such as sshd, auditd, firewalld, or networking. I
Side Effects	Optional few minutes of package download and installation time; may install additional dependencies, but these are harmless
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	22
Duration	500.8s
Total Tokens	79,501
Cost	$0.0056
Agents	Remedy(16), Review(3), Qa(3)

package_pcsc-lite_installed: Install the pcsc-lite package — FAILED

Rule	package_pcsc-lite_installed
Severity	Medium
Description	The pcsc-lite package can be installed with the following command: $ sudo dnf install pcsc-lite
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "p
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Installing the pcsc-lite package is a standard package installation that does not affect authentication, networking, or filesystem
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	bash -c 'if rpm -q kernel-core >/dev/null 2>&1; then dnf install -y pcsc-lite; else echo "kernel-core not present; skipping installa
Scan Passed	✗
Success	✗
Duration	307.1s
Error	—

Attempt #	2
Commands	dnf install -y pcsc-lite --nodocs, dnf install -y pcsc-lite, dnf list installed pcsc-lite, rpm -q pcsc-lite, uname -a
Scan Passed	✗

Success	✗
Duration	194.5s
Error	—

Attempt #	3
Commands	yum install -y pcsc-lite, dnf install -y pcsc-lite
Scan Passed	✗
Success	✗
Duration	39.3s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	9/10
Feedback	The plan will install the pcsc-lite package and thus mitigate the vulnerability, but it lacks the optional applicability check and p
Concerns	Missing applicability check for kernel-core; No post■installation verification of pcsc-lite; Use of yum alias instead of dnf (thoug

QA Result

Safe	✓
Verdict	Installing pcsc-lite via yum is a straightforward package management operation that will not alter existing system services suc
Side Effects	May load the pcscd service and its kernel modules; minimal additional runtime overhead
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	12
Duration	38.9s
Total Tokens	34,885
Cost	$0.0030
Agents	Remedy(10), Review(1), Qa(1)

install_smartcard_packages: Install Smart Card Packages For Multifactor Authentication — REQUIRES_HUMAN_REVIEW

Rule	install_smartcard_packages
Severity	Medium
Description	Configure the operating system to implement multifactor authentication by installing the required package with the following c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { ! (grep -sqE "^.*\.s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0

Cost	$0.0000
Agents	Triage(1)

service_pcscd_enabled: Enable the pcscd Service — FAILED

Rule	service_pcscd_enabled
Severity	Medium
Description	The pcscd service can be enabled with the following command: $ sudo systemctl enable pcscd.service
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Enabling the pcscd service is a standard service enablement that does not affect authentication, networking, or filesystem inte
Estimated Impact	—

Remediation (3 attempt(s))

Attempt #	1
Commands	systemctl unmask pcscd.service, systemctl unmask pcscd.service, echo test, whoami, systemctl enable pcscd.service
Scan Passed	✗
Success	✗
Duration	30.6s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	LLM API error 402: {"error":{"message":"This request requires more credits, or fewer max_tokens. You requested up to 65536

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	LLM API error 402: {"error":{"message":"This request requires more credits, or fewer max_tokens. You requested up to 65536

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Remedy(1)

configure_opensc_card_drivers: Configure opensc Smart Card Drivers — REQUIRES_HUMAN_REVIEW

Rule	configure_opensc_card_drivers
Severity	Medium

Description	The OpenSC smart card tool can auto-detect smart card drivers; however, setting the smart card drivers in use by your organ
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_smartcard_dri
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.7s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

account_disable_post_pw_expiration: Set Account Expiration Following Inactivity — REQUIRES_HUMAN_REVIEW

Rule	account_disable_post_pw_expiration
Severity	Medium
Description	To specify the number of days after a password expires (which signifies inactivity) until an account is permanently disabled, a
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q shad
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_maximum_age_login_defs: Set Password Maximum Age — REQUIRES_HUMAN_REVIEW

Rule	accounts_maximum_age_login_defs
Severity	Medium
Description	To specify password maximum age for new accounts, edit the file /etc/login.defs and add or correct the following line: PASS_
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q shad
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_minimum_age_login_defs: Set Password Minimum Age — REQUIRES_HUMAN_REVIEW

Rule	accounts_minimum_age_login_defs
Severity	Medium
Description	To specify password minimum age for new accounts, edit the file /etc/login.defs and add or correct the following line: PASS_M
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q shad
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_password_set_max_life_existing: Set Existing Passwords Maximum Age — REQUIRES_HUMAN_REVIEW

Rule	accounts_password_set_max_life_existing
Severity	Medium
Description	Configure non-compliant accounts to enforce a -day maximum password lifetime restriction by running the following comman
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_max
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s

Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_password_set_min_life_existing: Set Existing Passwords Minimum Age — REQUIRES_HUMAN_REVIEW

Rule	accounts_password_set_min_life_existing
Severity	Medium
Description	Configure non-compliant accounts to enforce a 24 hours/1 day minimum password lifetime by running the following command
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_mini
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_password_pam_unix_rounds_password_auth: Set number of Password Hashing Rounds - password-auth — REQUIRES_HUMAN_REVIEW

Rule	accounts_password_pam_unix_rounds_password_auth
Severity	Medium
Description	Configure the number or rounds for the password hashing algorithm. This can be accomplished by using the rounds option fo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q pam && rpm --quiet -q kernel-core
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_password_pam_unix_rounds_system_auth: Set number of Password Hashing Rounds - system-auth — REQUIRES_HUMAN_REVIEW

Rule	accounts_password_pam_unix_rounds_system_auth

Severity	Medium
Description	Configure the number or rounds for the password hashing algorithm. This can be accomplished by using the rounds option fo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q pam && rpm --quiet -q kernel-core
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

no_empty_passwords: Prevent Login to Accounts With Empty Password — REQUIRES_HUMAN_REVIEW

Rule	no_empty_passwords
Severity	High
Description	If an account is configured for password authentication but does not have an assigned password, it may be possible to log int
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if [-f /usr/bin/auths

Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

use_pam_wheel_for_su: Enforce usage of pam_wheel for su authentication — REQUIRES_HUMAN_REVIEW

Rule	use_pam_wheel_for_su
Severity	Medium
Description	To ensure that only users who are members of the wheel group can run commands with altered privileges through the su com
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q pam; then # uncomment the option i
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗

Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_logon_fail_delay: Ensure the Logon Failure Delay is Set Correctly in login.defs — REQUIRES_HUMAN_REVIEW

Rule	accounts_logon_fail_delay
Severity	Medium
Description	To ensure the logon failure delay controlled by /etc/login.defs is set properly, add or correct the FAIL_DELAY setting in /etc/lo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q shadow-utils && rpm --quiet -q kerr
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A

Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_tmout: Set Interactive Session Timeout — REQUIRES_HUMAN_REVIEW

Rule	accounts_tmout
Severity	Medium
Description	Setting the TMOUT option in /etc/profile ensures that all user sessions will terminate based on inactivity. A value of 0 (zero) d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_tmo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1

Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

file_permission_user_init_files_root: Ensure All User Initialization Files Have Mode 0740 Or Less Permissive — REQUIRES_HUMAN_REVIEW

Rule	file_permission_user_init_files_root
Severity	Medium
Description	Set the mode of the user initialization files, including the root user, to 0740 with the following commands: $ sudo chmod 0740
Recommendation	Remediation script: var_user_initialization_files_regex='' readarray -t interactive_users < <(awk -F: '$3==0 || $3>=1000 {print
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0

Cost	$0.0000
Agents	Triage(1)

accounts_umask_etc_bashrc: Ensure the Default Bash Umask is Set Correctly — REQUIRES_HUMAN_REVIEW

Rule	accounts_umask_etc_bashrc
Severity	Medium
Description	To ensure the default umask for users of the Bash shell is set properly, add or correct the umask setting in /etc/bashrc to reac
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q bash
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_umask_etc_csh_cshrc: Ensure the Default C Shell Umask is Set Correctly — REQUIRES_HUMAN_REVIEW

Rule	accounts_umask_etc_csh_cshrc
Severity	Medium
Description	To ensure the default umask for users of the C shell is set properly, add or correct the umask setting in /etc/csh.cshrc to read
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_use
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_umask_etc_login_defs: Ensure the Default Umask is Set Correctly in login.defs — REQUIRES_HUMAN_REVIEW

Rule	accounts_umask_etc_login_defs
Severity	Medium
Description	To ensure the default umask controlled by /etc/login.defs is set properly, add or correct the UMASK setting in /etc/login.defs t

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q shad
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

accounts_umask_etc_profile: Ensure the Default Umask is Set Correctly in /etc/profile — REQUIRES_HUMAN_REVIEW

Rule	accounts_umask_etc_profile
Severity	Medium
Description	To ensure the default umask controlled by /etc/profile is set properly, add or correct the umask setting in /etc/profile to read as
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_accounts_use
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

grub2_init_on_free: The system must booted with init_on_free=1 — REQUIRES_HUMAN_REVIEW

Rule	grub2_init_on_free
Severity	Medium
Description	Setting init_on_free=1 on boot guarantees that pages and heap objects are initialized right after they're freed, so it won't be p
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q grub2-common && rpm --quiet -q k
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM

Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

grub2_vsyscall_argument: Disable vsyscalls — REQUIRES_HUMAN_REVIEW

Rule	grub2_vsyscall_argument
Severity	Medium
Description	To disable use of virtual syscalls, add the argument vsyscall=none to the default GRUB 2 command line for the Linux operatin
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (rpm --quiet -q grub2-common && rpm --quiet -q k
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

grub2_admin_username: Set the Boot Loader Admin Username to a Non-Default Value — REQUIRES_HUMAN_REVIEW

Rule	grub2_admin_username
Severity	High
Description	The grub2 boot loader should have a superuser account and password protection enabled to protect boot-time settings. To m
Recommendation	Review and remediate: Set the Boot Loader Admin Username to a Non-Default Value
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0

Cost	$0.0000
Agents	Triage(1)

grub2_password: Set Boot Loader Password in grub2 — REQUIRES_HUMAN_REVIEW

Rule	grub2_password
Severity	High
Description	The grub2 boot loader should have a superuser account and password protection enabled to protect boot-time settings. Since
Recommendation	Review and remediate: Set Boot Loader Password in grub2
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

package_rsyslog-gnutls_installed: Ensure rsyslog-gnutls is installed — REQUIRES_HUMAN_REVIEW

Rule	package_rsyslog-gnutls_installed
Severity	Medium
Description	TLS protocol support for rsyslog is installed. The rsyslog-gnutls package can be installed with the following command: $ sudo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "r
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

rsyslog_encrypt_offload_actionsendstreamdriverauthmode: Ensure Rsyslog Authenticates Off-Loaded Audit Records — REQUIRES_HUMAN_REVIEW

Rule	rsyslog_encrypt_offload_actionsendstreamdriverauthmode
Severity	Medium

Description	Rsyslogd is a system utility providing support for message logging. Support for both internet and UNIX domain sockets enabl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslog
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

rsyslog_encrypt_offload_actionsendstreamdrivermode: Ensure Rsyslog Encrypts Off-Loaded Audit Records — REQUIRES_HUMAN_REVIEW

Rule	rsyslog_encrypt_offload_actionsendstreamdrivermode
Severity	Medium
Description	Rsyslogd is a system utility providing support for message logging. Support for both internet and UNIX domain sockets enabl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslog

Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

rsyslog_encrypt_offload_defaultnetstreamdriver: Ensure Rsyslog Encrypts Off-Loaded Audit Records — REQUIRES_HUMAN_REVIEW

Rule	rsyslog_encrypt_offload_defaultnetstreamdriver
Severity	Medium
Description	Rsyslogd is a system utility providing support for message logging. Support for both internet and UNIX domain sockets enabl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗

Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

rsyslog_remote_access_monitoring: Ensure remote access methods are monitored in Rsyslog — REQUIRES_HUMAN_REVIEW

Rule	rsyslog_remote_access_monitoring
Severity	Medium
Description	Logging of remote access methods must be implemented to help identify cyber attacks and ensure ongoing compliance with r
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && rpm --quiet -q rsyslog
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A

Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

rsyslog_remote_loghost: Ensure Logs Sent To Remote Host — REQUIRES_HUMAN_REVIEW

Rule	rsyslog_remote_loghost
Severity	Medium
Description	To configure rsyslog to send logs to a remote log server, open /etc/rsyslog.conf and read and understand the last section of tl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then rsyslog_remote_lo
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1

Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

network_configure_name_resolution: Configure Multiple DNS Servers in /etc/resolv.conf — REQUIRES_HUMAN_REVIEW

Rule	network_configure_name_resolution
Severity	Medium
Description	Determine whether the system is using local or DNS name resolution with the following command: $ sudo grep hosts /etc/nss
Recommendation	Review and remediate: Configure Multiple DNS Servers in /etc/resolv.conf
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000

Agents	Triage(1)

package_libreswan_installed: Install libreswan Package — REQUIRES_HUMAN_REVIEW

Rule	package_libreswan_installed
Severity	Medium
Description	The libreswan package provides an implementation of IPsec and IKE, which permits the creation of secure tunnels over untru
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "l
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sysctl_net_ipv6_conf_all_accept_ra: Configure Accepting Router Advertisements on All IPv6 Interfaces — SUCCESS

Rule	sysctl_net_ipv6_conf_all_accept_ra
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.accept_ra kernel parameter, run the following command: $ sudo sysctl -w net
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling IPv6 router advertisements via sysctl is a standard hardening practice that does not affect authentication, authoriza
Estimated Impact	networking affected

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv6.conf.all.accept_ra=0
Scan Passed	✓
Success	✓
Duration	518.6s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10

Feedback	The proposed plan will set the kernel parameter and create a persistent override, satisfying the remediation requirement. It do
Concerns	Duplicate configuration lines may remain in earlier files, potentially confusing admins.; The plan does not verify execution priv

QA Result

Safe	✓
Verdict	The plan safely sets the kernel parameter to disable router advertisements and writes a high■priority persistence file, which w
Side Effects	Disables IPv6 router advertisements, potentially breaking IPv6 connectivity for services that rely on it.; Existing IPv6■specific
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	19
Duration	171.7s
Total Tokens	55,875
Cost	$0.0033
Agents	Triage(1), Remedy(12), Review(3), Qa(3)

sysctl_net_ipv6_conf_all_accept_redirects: Disable Accepting ICMP Redirects for All IPv6 Interfaces — FAILED

Rule	sysctl_net_ipv6_conf_all_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.accept_redirects kernel parameter, run the following command: $ sudo sysctl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling ICMP redirects for IPv6 is a standard sysctl hardening measure that does not affect authentication, authorization, or
Estimated Impact	networking affected; ICMP redirect exploitation

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	120.4s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	30.5s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗

Success	✗
Duration	324.1s
Error	—

Review Verdict

Approved	✓
Optimal	✓
Security Score	9/10
Feedback	The plan will set net.ipv6.conf.all.accept_redirects to 0 both at runtime and persistently, correctly addressing the vulnerability.
Concerns	If a sysctl.d file with a higher numeric name sets the parameter after the 90-* override, it could override the value unless all su

QA Result

Safe	✓
Verdict	The remediation correctly comments any conflicting existing settings, installs a single override file that sets the parameter to 0
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	15
Duration	210.3s
Total Tokens	54,463
Cost	$0.0034
Agents	Remedy(13), Review(1), Qa(1)

sysctl_net_ipv6_conf_all_accept_source_route: Disable Kernel Parameter for Accepting Source-Routed Packets on all IPv6 Interfa… — *SUCCESS*

Rule	sysctl_net_ipv6_conf_all_accept_source_route
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.accept_source_route kernel parameter, run the following command: $ sudo s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling source routing is a standard kernel parameter hardening step that does not affect authentication, authorization, or c
Estimated Impact	networking affected; Potential exploitation of source routing vulnerabilities

Remediation (1 attempt(s))

Attempt #	1
Commands	sysctl -w net.ipv6.conf.all.accept_source_route=0
Scan Passed	✓
Success	✓
Duration	115.9s
Error	—

Review Verdict

Approved	✓

Optimal	✗
Security Score	8/10
Feedback	—
Concerns	Requires root privileges which may not be present for the executed context; Potential conflict if another sysctl.d file also sets t

QA Result

Safe	✓
Verdict	The plan simply disables IPv6 source routing by setting the correct sysctl value in a dedicated .conf file and applies it at runtir
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	115.8s
Total Tokens	31,776
Cost	$0.0017
Agents	Triage(1), Remedy(10), Review(1), Qa(1)

sysctl_net_ipv6_conf_all_forwarding: Disable Kernel Parameter for IPv6 Forwarding — FAILED

Rule	sysctl_net_ipv6_conf_all_forwarding
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.all.forwarding kernel parameter, run the following command: $ sudo sysctl -w ne
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an

Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling IPv6 forwarding is a standard hardening practice that does not affect local authentication or critical services; it only
Estimated Impact	networking affected; May affect IPv6 routing if the host is intended to forward traffic

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	46.1s
Error	—

Attempt #	2
Commands	sysctl -w net.ipv6.conf.all.forwarding=0
Scan Passed	✗
Success	✗
Duration	167.8s
Error	—

Attempt #	3

Commands	mkdir -p /etc/sysctl.d
Scan Passed	✗
Success	✗
Duration	219.7s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	7/10
Feedback	The proposed plan would effectively set net.ipv6.conf.all.forwarding to 0 at runtime and persist the change across reboots via
Concerns	No backup of existing sysctl.d files before modification; risk of data loss if an error occurs.; Potential to overwrite entire file or

QA Result

Safe	✓
Verdict	The remediation correctly disables IPv6 forwarding and persists the change. It will not interfere with core services like sshd, a
Side Effects	Disabling IPv6 forwarding may affect IPv6 routing or container networking if the host is used as a gateway or bridge.; The cor
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	16
Duration	218.7s
Total Tokens	55,493
Cost	$0.0032

Agents	Remedy(12), Review(2), Qa(2)

sysctl_net_ipv6_conf_default_accept_ra: Disable Accepting Router Advertisements on all IPv6 Interfaces by Default — *FAILED*

Rule	sysctl_net_ipv6_conf_default_accept_ra
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.default.accept_ra kernel parameter, run the following command: $ sudo sysctl -v
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling IPv6 router advertisements via a sysctl is a standard hardening step that does not affect authentication, authorizatio
Estimated Impact	networking affected; IPv6 routing; network configuration

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	32.4s
Error	—

Attempt #	2

Commands	—
Scan Passed	✗
Success	✗
Duration	108.0s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	70.2s
Error	—

Review Verdict

Approved	✗
Optimal	✗
Security Score	None/10
Feedback	Review output was not valid JSON. Raw: {"finding_id":"sysctl_net_ipv6_conf_default_accept_ra","is_optimal":false,"approve":
Concerns	Could not parse LLM response

LLM Metrics

LLM Calls	2
Duration	70.2s
Total Tokens	5,914
Cost	$0.0005

Agents	Remedy(1), Review(1)

sysctl_net_ipv6_conf_default_accept_redirects: Disable Kernel Parameter for Accepting ICMP Redirects by Default on IPv6 Interfa… — *FAILED*

Rule	sysctl_net_ipv6_conf_default_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.default.accept_redirects kernel parameter, run the following command: $ sudo s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The remediation involves setting a sysctl parameter and adding a line to a sysctl.d file, which is a standard, low-risk configura
Estimated Impact	networking affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	124.8s
Error	—

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	64.9s
Error	—

Attempt #	3
Commands	sed -i '/^[[:space:]]*net\.ipv6\.conf\.default\.accept_redirects[[:space:]]*=/{ s/^/# / }' /etc/sysctl.conf, find /etc/sysctl.conf /etc/sys
Scan Passed	✗
Success	✗
Duration	542.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗
Security Score	8/10
Feedback	The plan correctly addresses the vulnerability by ensuring all active settings for the parameter are disabled and a single autho
Concerns	Sed pattern may comment out unintended lines if not anchored correctly; use a regex such as '^\s*net\.ipv6\.conf\.default\.acc

QA Result

Safe	✓
Verdict	The remediation addresses the vulnerability by commenting any existing active settings for net.ipv6.conf.default.accept_redire
Side Effects	Potential accidental commenting of unrelated lines if regex is not anchored; risk of modifying or trailing symlinks if --follow-sym

Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	21
Duration	539.2s
Total Tokens	105,560
Cost	$0.0058
Agents	Remedy(19), Review(1), Qa(1)

sysctl_net_ipv6_conf_default_accept_source_route: Disable Kernel Parameter for Accepting Source-Routed Packets on IPv6 Interfaces … — *FAILED*

Rule	sysctl_net_ipv6_conf_default_accept_source_route
Severity	Medium
Description	To set the runtime status of the net.ipv6.conf.default.accept_source_route kernel parameter, run the following command: $ su
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	The kernel parameter controls source routing on IPv6 interfaces, a non-critical setting that can be safely disabled without affe
Estimated Impact	networking affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	41.4s
Error	—

Attempt #	2
Commands	sysctl -w net.ipv6.conf.default.accept_source_route=0, ls /, echo hello
Scan Passed	✗
Success	✗
Duration	394.2s
Error	—

Attempt #	3
Commands	echo "net.ipv6.conf.default.accept_source_route = 0" > /etc/sysctl.d/99-disable-ipv6-source-route.conf
Scan Passed	✗
Success	✗
Duration	54.0s
Error	—

Review Verdict

Approved	✓
Optimal	✗

Security Score	8/10
Feedback	The proposed plan will correctly set the kernel parameter to 0 at runtime and persist across reboots. It follows STIG hardenin
Concerns	Overwrites any existing /etc/sysctl.d/99■disable■ipv6■source■route.conf, potentially discarding valid customizations; Does

QA Result

Safe	✓
Verdict	The plan correctly sets the kernel parameter to 0 in a high■priority sysctl file, reloads the sysctl daemon to apply it immediate
Side Effects	—
Regression	✗
Recommendation	Approve

LLM Metrics

LLM Calls	13
Duration	52.2s
Total Tokens	39,411
Cost	$0.0028
Agents	Remedy(11), Review(1), Qa(1)

sysctl_net_ipv4_conf_all_accept_redirects: Disable Accepting ICMP Redirects for All IPv4 Interfaces — FAILED

Rule	sysctl_net_ipv4_conf_all_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.accept_redirects kernel parameter, run the following command: $ sudo sysctl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling ICMP redirects via a sysctl setting is a standard, low-risk configuration change that does not affect authentication, a
Estimated Impact	networking affected

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	310.4s
Error	—

Attempt #	2
Commands	find /etc/sysctl.d /run/sysctl.d /usr/local/lib/sysctl.d -type f -name '*.conf' -not -lname '/etc/sysctl.conf' -exec sed -i.bak '/^[[:spac
Scan Passed	✗
Success	✗
Duration	199.3s
Error	—

Attempt #	3
Commands	—
Scan Passed	✗

Success	✗
Duration	—
Error	LLM API error 402: {"error":{"message":"This request requires more credits, or fewer max_tokens. You requested up to 65536

LLM Metrics

LLM Calls	12
Duration	64.5s
Total Tokens	40,448
Cost	$0.0029
Agents	Remedy(10), Review(1), Qa(1)

sysctl_net_ipv4_conf_all_accept_source_route: Disable Kernel Parameter for Accepting Source-Routed Packets on all IPv4 Interfa… — *FAILED*

Rule	sysctl_net_ipv4_conf_all_accept_source_route
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.accept_source_route kernel parameter, run the following command: $ sudo s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✓
Human Review	✗
Risk Level	LOW
Reason	Disabling source routing is a standard security hardening step that does not affect authentication, authorization, or critical ser

Estimated Impact	networking affected; Potential impact on legacy applications that rely on source routing

Remediation (3 attempt(s))

Attempt #	1
Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	LLM API error 402: {"error":{"message":"This request requires more credits, or fewer max_tokens. You requested up to 65536

Attempt #	2
Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	LLM API error 402: {"error":{"message":"This request requires more credits, or fewer max_tokens. You requested up to 65536

Attempt #	3
Commands	—
Scan Passed	✗
Success	✗
Duration	—
Error	LLM API error 402: {"error":{"message":"This request requires more credits, or fewer max_tokens. You requested up to 65536

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Remedy(1)

sysctl_net_ipv4_conf_all_forwarding: Disable Kernel Parameter for IPv4 Forwarding on all IPv4 Interfaces — REQUIRES_HUMAN_REVIEW

Rule	sysctl_net_ipv4_conf_all_forwarding
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.forwarding kernel parameter, run the following command: $ sudo sysctl -w ne
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s

Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sysctl_net_ipv4_conf_all_rp_filter: Enable Kernel Parameter to Use Reverse Path Filtering on all IPv4 Interfaces — REQUIRES_HUMAN_REVIEW

Rule	sysctl_net_ipv4_conf_all_rp_filter
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.rp_filter kernel parameter, run the following command: $ sudo sysctl -w net.ip
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000

Agents	Triage(1)

sysctl_net_ipv4_conf_default_accept_redirects: Disable Kernel Parameter for Accepting ICMP Redirects by Default on IPv4 Interfa… — *REQUIRES_HUMAN_REVIEW*

Rule	sysctl_net_ipv4_conf_default_accept_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.default.accept_redirects kernel parameter, run the following command: $ sudo s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sysctl_net_ipv4_conf_default_rp_filter: Enable Kernel Parameter to Use Reverse Path Filtering on all IPv4 Interfaces by … — *REQUIRES_HUMAN_REVIEW*

Rule	sysctl_net_ipv4_conf_default_rp_filter
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.default.rp_filter kernel parameter, run the following command: $ sudo sysctl -w r
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.2s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sysctl_net_ipv4_icmp_echo_ignore_broadcasts: Enable Kernel Parameter to Ignore ICMP Broadcast Echo Requests on IPv4 Interface… — *REQUIRES_HUMAN_REVIEW*

Rule	sysctl_net_ipv4_icmp_echo_ignore_broadcasts

Severity	Medium
Description	To set the runtime status of the net.ipv4.icmp_echo_ignore_broadcasts kernel parameter, run the following command: $ sudo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.8s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sysctl_net_ipv4_tcp_syncookies: Enable Kernel Parameter to Use TCP Syncookies on Network Interfaces — REQUIRES_HUMAN_REVIEW

Rule	sysctl_net_ipv4_tcp_syncookies
Severity	Medium
Description	To set the runtime status of the net.ipv4.tcp_syncookies kernel parameter, run the following command: $ sudo sysctl -w net.ip

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sysctl_net_ipv4_conf_all_send_redirects: Disable Kernel Parameter for Sending ICMP Redirects on all IPv4 Interfaces — REQUIRES_HUMAN_REVIEW

Rule	sysctl_net_ipv4_conf_all_send_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.all.send_redirects kernel parameter, run the following command: $ sudo sysctl -
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sysctl_net_ipv4_conf_default_send_redirects: Disable Kernel Parameter for Sending ICMP Redirects on all IPv4 Interfaces by De… — REQUIRES_HUMAN_REVIEW

Rule	sysctl_net_ipv4_conf_default_send_redirects
Severity	Medium
Description	To set the runtime status of the net.ipv4.conf.default.send_redirects kernel parameter, run the following command: $ sudo sys
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

kernel_module_atm_disabled: Disable ATM Support — REQUIRES_HUMAN_REVIEW

Rule	kernel_module_atm_disabled
Severity	Medium
Description	The Asynchronous Transfer Mode (ATM) is a protocol operating on network, data link, and physical layers, based on virtual c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

kernel_module_can_disabled: Disable CAN Support — REQUIRES_HUMAN_REVIEW

Rule	kernel_module_can_disabled
Severity	Medium
Description	The Controller Area Network (CAN) is a serial communications protocol which was initially developed for automotive and is no
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s

Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

kernel_module_sctp_disabled: Disable SCTP Support — REQUIRES_HUMAN_REVIEW

Rule	kernel_module_sctp_disabled
Severity	Medium
Description	The Stream Control Transmission Protocol (SCTP) is a transport layer protocol, designed to support the idea of message-orie
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

kernel_module_bluetooth_disabled: Disable Bluetooth Kernel Module — REQUIRES_HUMAN_REVIEW

Rule	kernel_module_bluetooth_disabled
Severity	Medium
Description	The kernel's module loading system can be configured to prevent loading of the Bluetooth module. Add the following to the ap
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

networkmanager_dns_mode: NetworkManager DNS Mode Must Be Must Configured — REQUIRES_HUMAN_REVIEW

Rule	networkmanager_dns_mode
Severity	Medium

Description	The DNS processing mode in NetworkManager describes how DNS is processed on the system. Depending the mode some
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q NetworkManager; then var_network
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

rootfiles_configured: Ensure rootfiles tmpfile.d is Configured Correctly — REQUIRES_HUMAN_REVIEW

Rule	rootfiles_configured
Severity	Medium
Description	To set the mode of the root user initialization file /root/.bash_profile, ensure the following lines are is included in a file ending i
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q rootfiles; then find "/etc/tmpfiles.d/" -
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

kernel_module_usb-storage_disabled: Disable Modprobe Loading of USB Storage Driver — REQUIRES_HUMAN_REVIEW

Rule	kernel_module_usb-storage_disabled
Severity	Medium
Description	To prevent USB storage devices from being used, configure the kernel module loading system to prevent automatic loading c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if LC_ALL=C grep
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

mount_option_boot_efi_nosuid: Add nosuid Option to /boot/efi — REQUIRES_HUMAN_REVIEW

Rule	mount_option_boot_efi_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /boot/efi. The SUID and SGID permissions s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

mount_option_boot_nodev: Add nodev Option to /boot — REQUIRES_HUMAN_REVIEW

Rule	mount_option_boot_nodev
Severity	Medium
Description	The nodev mount option can be used to prevent device files from being created in /boot. Legitimate character and block devic
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s

Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

mount_option_boot_nosuid: Add nosuid Option to /boot — REQUIRES_HUMAN_REVIEW

Rule	mount_option_boot_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /boot. The SUID and SGID permissions sho
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

mount_option_dev_shm_nodev: Add nodev Option to /dev/shm — REQUIRES_HUMAN_REVIEW

Rule	mount_option_dev_shm_nodev
Severity	Medium
Description	The nodev mount option can be used to prevent creation of device files in /dev/shm. Legitimate character and block devices s
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet -
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.6s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

mount_option_dev_shm_noexec: Add noexec Option to /dev/shm — REQUIRES_HUMAN_REVIEW

Rule	mount_option_dev_shm_noexec
Severity	Medium

Description	The noexec mount option can be used to prevent binaries from being executed out of /dev/shm. It can be dangerous to allow
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

mount_option_dev_shm_nosuid: Add nosuid Option to /dev/shm — REQUIRES_HUMAN_REVIEW

Rule	mount_option_dev_shm_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /dev/shm. The SUID and SGID permissions
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

mount_option_home_noexec: Add noexec Option to /home — REQUIRES_HUMAN_REVIEW

Rule	mount_option_home_noexec
Severity	Medium
Description	The noexec mount option can be used to prevent binaries from being executed out of /home. Add the noexec option to the fo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

mount_option_home_nosuid: Add nosuid Option to /home — REQUIRES_HUMAN_REVIEW

Rule	mount_option_home_nosuid
Severity	Medium
Description	The nosuid mount option can be used to prevent execution of setuid programs in /home. The SUID and SGID permissions sh
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

mount_option_nodev_nonroot_local_partitions: Add nodev Option to Non-Root Local Partitions — REQUIRES_HUMAN_REVIEW

Rule	mount_option_nodev_nonroot_local_partitions
Severity	Medium
Description	The nodev mount option prevents files from being interpreted as character or block devices. Legitimate character and block d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! ({ rpm --quiet -q kernel-core ;} && { rpm --quiet
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s

Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sysctl_kernel_core_pattern: Disable storing core dumps — REQUIRES_HUMAN_REVIEW

Rule	sysctl_kernel_core_pattern
Severity	Medium
Description	To set the runtime status of the kernel.core_pattern kernel parameter, run the following command: $ sudo sysctl -w kernel.co
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sysctl_kernel_kexec_load_disabled: Disable Kernel Image Loading — REQUIRES_HUMAN_REVIEW

Rule	sysctl_kernel_kexec_load_disabled
Severity	Medium
Description	To set the runtime status of the kernel.kexec_load_disabled kernel parameter, run the following command: $ sudo sysctl -w k
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sysctl_kernel_unprivileged_bpf_disabled: Disable Access to Network bpf() Syscall From Unprivileged Processes — REQUIRES_HUMAN_REVIEW

Rule	sysctl_kernel_unprivileged_bpf_disabled
Severity	Medium

Description	To set the runtime status of the kernel.unprivileged_bpf_disabled kernel parameter, run the following command: $ sudo sysct
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sysctl_kernel_yama_ptrace_scope: Restrict usage of ptrace to descendant processes — REQUIRES_HUMAN_REVIEW

Rule	sysctl_kernel_yama_ptrace_scope
Severity	Medium
Description	To set the runtime status of the kernel.yama.ptrace_scope kernel parameter, run the following command: $ sudo sysctl -w ke
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sysctl_net_core_bpf_jit_harden: Harden the operation of the BPF just-in-time compiler — REQUIRES_HUMAN_REVIEW

Rule	sysctl_net_core_bpf_jit_harden
Severity	Medium
Description	To set the runtime status of the net.core.bpf_jit_harden kernel parameter, run the following command: $ sudo sysctl -w net.co
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sysctl_user_max_user_namespaces_no_remediation: Disable the use of user namespaces — REQUIRES_HUMAN_REVIEW

Rule	sysctl_user_max_user_namespaces_no_remediation
Severity	Medium
Description	To set the runtime status of the user.max_user_namespaces kernel parameter, run the following command: $ sudo sysctl -w
Recommendation	Review and remediate: Disable the use of user namespaces
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

service_systemd-coredump_disabled: Disable acquiring, saving, and processing core dumps — REQUIRES_HUMAN_REVIEW

Rule	service_systemd-coredump_disabled
Severity	Medium
Description	The systemd-coredump.socket unit is a socket activation of the systemd-coredump@.service which processes core dumps. E
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SOCKET_NAME=
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s

Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

coredump_disable_backtraces: Disable core dump backtraces — REQUIRES_HUMAN_REVIEW

Rule	coredump_disable_backtraces
Severity	Medium
Description	The ProcessSizeMax option in [Coredump] section of /etc/systemd/coredump.conf or in a drop-in file under /etc/systemd/core
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q syste
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

coredump_disable_storage: Disable storing core dump — REQUIRES_HUMAN_REVIEW

Rule	coredump_disable_storage
Severity	Medium
Description	The Storage option in [Coredump] section of /etc/systemd/coredump.conf or a drop-in file in /etc/systemd/coredump.conf.d/*.c
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q syste
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

disable_users_coredumps: Disable Core Dumps for All Users — REQUIRES_HUMAN_REVIEW

Rule	disable_users_coredumps
Severity	Medium

Description	To disable core dumps for all users, add the following line to /etc/security/limits.conf, or to a file within the /etc/security/limits.d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q pam;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.8s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sysctl_kernel_randomize_va_space: Enable Randomized Layout of Virtual Address Space — REQUIRES_HUMAN_REVIEW

Rule	sysctl_kernel_randomize_va_space
Severity	Medium
Description	To set the runtime status of the kernel.randomize_va_space kernel parameter, run the following command: $ sudo sysctl -w k
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then # Comment out an
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

grub2_page_poison_argument: Enable page allocator poisoning — REQUIRES_HUMAN_REVIEW

Rule	grub2_page_poison_argument
Severity	Medium
Description	To enable poisoning of free pages, add the argument page_poison=1 to the default GRUB 2 command line for the Linux oper
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { rpm --quiet -q grub2
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

package_policycoreutils-python-utils_installed: Install policycoreutils-python-utils package — REQUIRES_HUMAN_REVIEW

Rule	package_policycoreutils-python-utils_installed
Severity	Medium
Description	The policycoreutils-python-utils package can be installed with the following command: $ sudo dnf install policycoreutils-pythor
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "p
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

service_kdump_disabled: Disable KDump Kernel Crash Analyzer (kdump) — REQUIRES_HUMAN_REVIEW

Rule	service_kdump_disabled
Severity	Medium
Description	The kdump service provides a kernel crash dump analyzer. It uses the kexec system call to boot a secondary kernel ("capture
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s

Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

file_permissions_cron_d: Verify Permissions on cron.d — REQUIRES_HUMAN_REVIEW

Rule	file_permissions_cron_d
Severity	Medium
Description	To properly set the permissions of /etc/cron.d, run the command: $ sudo chmod 0700 /etc/cron.d
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.d/
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

file_permissions_cron_daily: Verify Permissions on cron.daily — REQUIRES_HUMAN_REVIEW

Rule	file_permissions_cron_daily
Severity	Medium
Description	To properly set the permissions of /etc/cron.daily, run the command: $ sudo chmod 0700 /etc/cron.daily
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.da
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

file_permissions_cron_hourly: Verify Permissions on cron.hourly — REQUIRES_HUMAN_REVIEW

Rule	file_permissions_cron_hourly
Severity	Medium

Description	To properly set the permissions of /etc/cron.hourly, run the command: $ sudo chmod 0700 /etc/cron.hourly
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.ho
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

file_permissions_cron_monthly: Verify Permissions on cron.monthly — REQUIRES_HUMAN_REVIEW

Rule	file_permissions_cron_monthly
Severity	Medium
Description	To properly set the permissions of /etc/cron.monthly, run the command: $ sudo chmod 0700 /etc/cron.monthly
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.m
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

file_permissions_cron_weekly: Verify Permissions on cron.weekly — REQUIRES_HUMAN_REVIEW

Rule	file_permissions_cron_weekly
Severity	Medium
Description	To properly set the permissions of /etc/cron.weekly, run the command: $ sudo chmod 0700 /etc/cron.weekly
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then find -H /etc/cron.we
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

package_fapolicyd_installed: Install fapolicyd Package — REQUIRES_HUMAN_REVIEW

Rule	package_fapolicyd_installed
Severity	Medium
Description	The fapolicyd package can be installed with the following command: $ sudo dnf install fapolicyd
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "f
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

service_fapolicyd_enabled: Enable the File Access Policy Service — REQUIRES_HUMAN_REVIEW

Rule	service_fapolicyd_enabled
Severity	Medium
Description	The File Access Policy service should be enabled. The fapolicyd service can be enabled with the following command: $ sudo
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then SYSTEMCTL_EXE
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s

Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

fapolicy_default_deny: Configure Fapolicy Module to Employ a Deny-all, Permit-by-exception Policy to Al… — REQUIRES_HUMAN_REVIEW

Rule	fapolicy_default_deny
Severity	Medium
Description	The Fapolicy module must be configured to employ a deny-all, permit-by-exception policy to allow the execution of authorized
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then cat > /etc/fapolicyd
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000

Agents	Triage(1)

package_postfix_installed: The Postfix package is installed — REQUIRES_HUMAN_REVIEW

Rule	package_postfix_installed
Severity	Medium
Description	A mail server is required for sending emails. The postfix package can be installed with the following command: $ sudo dnf ins
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "p
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

package_s-nail_installed: The s-nail Package Is Installed — REQUIRES_HUMAN_REVIEW

Rule	package_s-nail_installed
Severity	Medium
Description	A mail server is required for sending emails. The s-nail package can be installed with the following command: $ sudo dnf insta
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.7s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

postfix_client_configure_mail_alias: Configure System to Forward All Mail For The Root Account — REQUIRES_HUMAN_REVIEW

Rule	postfix_client_configure_mail_alias
Severity	Medium
Description	Make sure that mails delivered to root user are forwarded to a monitored email address. Make sure that the address is a valid

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_postfix_root_m
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

chronyd_or_ntpd_set_maxpoll: Configure Time Service Maxpoll Interval — REQUIRES_HUMAN_REVIEW

Rule	chronyd_or_ntpd_set_maxpoll
Severity	Medium
Description	The maxpoll should be configured to in /etc/ntp.conf or /etc/chrony.conf (or /etc/chrony.d/) to continuously poll time servers. T
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core && { (rpm --quiet -q chro
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

chronyd_server_directive: Ensure Chrony is only configured with the server directive — REQUIRES_HUMAN_REVIEW

Rule	chronyd_server_directive
Severity	Medium
Description	Check that Chrony only has time sources configured with the server directive.
Recommendation	Review and remediate: Ensure Chrony is only configured with the server directive
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM

Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

disable_host_auth: Disable Host-Based Authentication — REQUIRES_HUMAN_REVIEW

Rule	disable_host_auth
Severity	Medium
Description	SSH's cryptographic host-based authentication is more secure than .rhosts authentication. However, it is not recommended tl
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sshd_disable_compression: Disable Compression Or Set Compression to delayed — REQUIRES_HUMAN_REVIEW

Rule	sshd_disable_compression
Severity	Medium
Description	Compression is useful for slow network connections over long distances but can cause performance issues on local LANs. If
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_sshd_disable_
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0

Cost	$0.0000
Agents	Triage(1)

sshd_disable_gssapi_auth: Disable GSSAPI Authentication — REQUIRES_HUMAN_REVIEW

Rule	sshd_disable_gssapi_auth
Severity	Medium
Description	Unless needed, SSH should not permit extraneous or unnecessary authentication mechanisms like GSSAPI. The default SSH
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sshd_disable_kerb_auth: Disable Kerberos Authentication — REQUIRES_HUMAN_REVIEW

Rule	sshd_disable_kerb_auth
Severity	Medium
Description	Unless needed, SSH should not permit extraneous or unnecessary authentication mechanisms like Kerberos. The default SS
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sshd_disable_rhosts: Disable SSH Support for .rhosts Files — REQUIRES_HUMAN_REVIEW

Rule	sshd_disable_rhosts
Severity	Medium
Description	SSH can emulate the behavior of the obsolete rsh command in allowing users to enable insecure access to their accounts via

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sshd_disable_user_known_hosts: Disable SSH Support for User Known Hosts — REQUIRES_HUMAN_REVIEW

Rule	sshd_disable_user_known_hosts
Severity	Medium
Description	SSH can allow system users to connect to systems if a cache of the remote systems public keys is available. This should be
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sshd_do_not_permit_user_env: Do Not Allow SSH Environment Options — REQUIRES_HUMAN_REVIEW

Rule	sshd_do_not_permit_user_env
Severity	Medium
Description	Ensure that users are not able to override environment variables of the SSH daemon. The default SSH configuration disables
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM

Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sshd_enable_pubkey_auth: Enable Public Key Authentication — REQUIRES_HUMAN_REVIEW

Rule	sshd_enable_pubkey_auth
Severity	Medium
Description	Enable SSH login with public keys. The default SSH configuration enables authentication based on public keys. The appropri
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sshd_enable_strictmodes: Enable Use of Strict Mode Checking — REQUIRES_HUMAN_REVIEW

Rule	sshd_enable_strictmodes
Severity	Medium
Description	SSHs StrictModes option checks file and ownership permissions in the user's home directory .ssh folder before accepting log
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0

Cost	$0.0000
Agents	Triage(1)

sshd_print_last_log: Enable SSH Print Last Log — REQUIRES_HUMAN_REVIEW

Rule	sshd_print_last_log
Severity	Medium
Description	Ensure that SSH will display the date and time of the last successful account logon. The default SSH configuration enables pr
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/ss
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.6s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sshd_rekey_limit: Force frequent session key renegotiation — REQUIRES_HUMAN_REVIEW

Rule	sshd_rekey_limit
Severity	Medium
Description	The RekeyLimit parameter specifies how often the session key of the is renegotiated, both in terms of amount of data that ma
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then var_rekey_limit_siz
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sshd_set_loglevel_verbose: Set SSH Daemon LogLevel to VERBOSE — REQUIRES_HUMAN_REVIEW

Rule	sshd_set_loglevel_verbose
Severity	Medium
Description	The VERBOSE parameter configures the SSH daemon to record login and logout activity. To specify the log level in SSH, ad

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.6s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sshd_x11_use_localhost: Prevent remote hosts from connecting to the proxy display — REQUIRES_HUMAN_REVIEW

Rule	sshd_x11_use_localhost
Severity	Medium
Description	The SSH daemon should prevent remote hosts from connecting to the proxy display. The default SSH configuration for X11U
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then mkdir -p /etc/ssh/s
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sssd_certificate_verification: Certificate status checking in SSSD — REQUIRES_HUMAN_REVIEW

Rule	sssd_certificate_verification
Severity	Medium
Description	Multifactor solutions that require devices separate from information systems gaining access include, for example, hardware to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q sssd-common; then var_sssd_certifi
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM

Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sssd_enable_certmap: Enable Certmap in SSSD — REQUIRES_HUMAN_REVIEW

Rule	sssd_enable_certmap
Severity	Medium
Description	SSSD should be configured to verify the certificate of the user or group. To set this up ensure that section like certmap/testing
Recommendation	Review and remediate: Enable Certmap in SSSD
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

sssd_enable_smartcards: Enable Smartcards in SSSD — REQUIRES_HUMAN_REVIEW

Rule	sssd_enable_smartcards
Severity	Medium
Description	SSSD should be configured to authenticate access to the system using smart cards. To enable smart cards in SSSD, set pam
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q sssd-common; then # sssd configura
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.9s
Total Tokens	0

Cost	$0.0000
Agents	Triage(1)

package_usbguard_installed: Install usbguard Package — REQUIRES_HUMAN_REVIEW

Rule	package_usbguard_installed
Severity	Medium
Description	The usbguard package can be installed with the following command: $ sudo dnf install usbguard
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! (grep -sqE "^.*\.s390x$" /proc/sys/kernel/osrele
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

service_usbguard_enabled: Enable the USBGuard Service — REQUIRES_HUMAN_REVIEW

Rule	service_usbguard_enabled
Severity	Medium
Description	The USBGuard service should be enabled. The usbguard service can be enabled with the following command: $ sudo system
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! (grep -sqE "^.*\.s390x$" /proc/sys/kernel/osrele
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

usbguard_generate_policy: Generate USBGuard Policy — REQUIRES_HUMAN_REVIEW

Rule	usbguard_generate_policy
Severity	Medium
Description	By default USBGuard when enabled prevents access to all USB devices and this lead to inaccessible system if they use USB

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if (! (grep -sqE "^.*\.s390x$" /proc/sys/kernel/osrele
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

package_audispd-plugins_installed: Install audispd-plugins Package — REQUIRES_HUMAN_REVIEW

Rule	package_audispd-plugins_installed
Severity	Medium
Description	The audispd-plugins package can be installed with the following command: $ sudo dnf install audispd-plugins
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q kernel-core; then if ! rpm -q --quiet "a
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_etc_cron_d: Ensure auditd Collects Changes to Cron Jobs - /etc/cron.d/ — *REQUIRES_HUMAN_REVIEW*

Rule	audit_rules_etc_cron_d
Severity	Medium
Description	At a minimum, the audit system should collect administrator actions for all users and root. If the auditd daemon is configured t
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core; t
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM

Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_immutable: Make the auditd Configuration Immutable — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_immutable
Severity	Medium
Description	If the auditd daemon is configured to use the augenrules program to read audit rules during daemon startup (the default), add
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_sudoers: Ensure auditd Collects System Administrator Actions - /etc/sudoers — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_sudoers
Severity	Medium
Description	At a minimum, the audit system should collect administrator actions for all users and root. If the auditd daemon is configured t
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0

Cost	$0.0000
Agents	Triage(1)

audit_rules_sudoers_d: Ensure auditd Collects System Administrator Actions - /etc/sudoers.d/ — *REQUIRES_HUMAN_REVIEW*

Rule	audit_rules_sudoers_d
Severity	Medium
Description	At a minimum, the audit system should collect administrator actions for all users and root. If the auditd daemon is configured t
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core; t
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_suid_privilege_function: Record Events When Privileged Executables Are Run — *REQUIRES_HUMAN_REVIEW*

Rule	audit_rules_suid_privilege_function
Severity	Medium
Description	Verify the system generates an audit record when privileged functions are executed. If audit is using the "auditctl" tool to load
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	2
Duration	60.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(2)

audit_rules_system_shutdown: Shutdown System When Auditing Failures Occur — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_system_shutdown
Severity	Medium
Description	If the auditd daemon is configured to use the augenrules program to read audit rules during daemon startup (the default), add

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_usergroup_modification_group: Record Events that Modify User/Group Information - /etc/group — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_usergroup_modification_group
Severity	Medium
Description	If the auditd daemon is configured to use the augenrules program to read audit rules during daemon startup (the default), add
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_usergroup_modification_gshadow: Record Events that Modify User/Group Information - /etc/gshadow — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_usergroup_modification_gshadow
Severity	Medium
Description	If the auditd daemon is configured to use the augenrules program to read audit rules during daemon startup (the default), add
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.7s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_usergroup_modification_opasswd: Record Events that Modify User/Group Information - /etc/security/opasswd — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_usergroup_modification_opasswd
Severity	Medium
Description	If the auditd daemon is configured to use the augenrules program to read audit rules during daemon startup (the default), add
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A

Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_usergroup_modification_passwd: Record Events that Modify User/Group Information - /etc/passwd — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_usergroup_modification_passwd
Severity	Medium
Description	If the auditd daemon is configured to use the augenrules program to read audit rules during daemon startup (the default), add
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1

Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_usergroup_modification_shadow: Record Events that Modify User/Group Information - /etc/shadow — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_usergroup_modification_shadow
Severity	Medium
Description	If the auditd daemon is configured to use the augenrules program to read audit rules during daemon startup (the default), add
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0

Cost	$0.0000
Agents	Triage(1)

audit_rules_var_spool_cron: Ensure auditd Collects Changes to Cron Jobs - /var/spool/cron — *REQUIRES_HUMAN_REVIEW*

Rule	audit_rules_var_spool_cron
Severity	Medium
Description	If the auditd daemon is configured to use the augenrules program to read audit rules during daemon startup (the default), add
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_chmod: Record Events that Modify the System's Discretionary Access Controls - chmod — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_dac_modification_chmod
Severity	Medium
Description	At a minimum, the audit system should collect file permission changes for all users and root. If the auditd daemon is configure
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core &
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_chown: Record Events that Modify the System's Discretionary Access Controls - chown — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_dac_modification_chown

Severity	Medium
Description	At a minimum, the audit system should collect file permission changes for all users and root. If the auditd daemon is configure
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core &
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_fchmod: Record Events that Modify the System's Discretionary Access Controls - fchmod — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_dac_modification_fchmod
Severity	Medium
Description	At a minimum, the audit system should collect file permission changes for all users and root. If the auditd daemon is configure

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_fchmodat: Record Events that Modify the System's Discretionary Access Controls - fchmodat — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_dac_modification_fchmodat
Severity	Medium
Description	At a minimum, the audit system should collect file permission changes for all users and root. If the auditd daemon is configure
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_fchown: Record Events that Modify the System's Discretionary Access Controls - fchown — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_dac_modification_fchown
Severity	Medium
Description	At a minimum, the audit system should collect file permission changes for all users and root. If the auditd daemon is configure
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_fchownat: Record Events that Modify the System's Discretionary Access Controls - fchownat — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_dac_modification_fchownat
Severity	Medium
Description	At a minimum, the audit system should collect file permission changes for all users and root. If the auditd daemon is configure
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A

Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_fremovexattr: Record Events that Modify the System's Discretionary Access Controls - fremovexa… — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_dac_modification_fremovexattr
Severity	Medium
Description	At a minimum, the audit system should collect file permission changes for all users and root. If the auditd daemon is configure
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1

Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_fsetxattr: Record Events that Modify the System's Discretionary Access Controls - fsetxattr — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_dac_modification_fsetxattr
Severity	Medium
Description	At a minimum, the audit system should collect file permission changes for all users and root. If the auditd daemon is configure
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.8s
Total Tokens	0

Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_lchown: Record Events that Modify the System's Discretionary Access Controls - lchown — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_dac_modification_lchown
Severity	Medium
Description	At a minimum, the audit system should collect file permission changes for all users and root. If the auditd daemon is configure
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core &
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_lremovexattr: Record Events that Modify the System's Discretionary Access Controls - lremovexa… — *REQUIRES_HUMAN_REVIEW*

Rule	audit_rules_dac_modification_lremovexattr
Severity	Medium
Description	At a minimum, the audit system should collect file permission changes for all users and root. If the auditd daemon is configure
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_lsetxattr: Record Events that Modify the System's Discretionary Access Controls - lsetxattr — *REQUIRES_HUMAN_REVIEW*

Rule	audit_rules_dac_modification_lsetxattr

Severity	Medium
Description	At a minimum, the audit system should collect file permission changes for all users and root. If the auditd daemon is configure
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_removexattr: Record Events that Modify the System's Discretionary Access Controls - removexat… — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_dac_modification_removexattr
Severity	Medium
Description	At a minimum, the audit system should collect file permission changes for all users and root. If the auditd daemon is configure

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_setxattr: Record Events that Modify the System's Discretionary Access Controls - setxattr — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_dac_modification_setxattr
Severity	Medium
Description	At a minimum, the audit system should collect file permission changes for all users and root. If the auditd daemon is configure
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_umount: Record Events that Modify the System's Discretionary Access Controls - umount — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_dac_modification_umount
Severity	Medium
Description	At a minimum, the audit system should collect file system umount changes. If the auditd daemon is configured to use the aug
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core &
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_dac_modification_umount2: Record Events that Modify the System's Discretionary Access Controls - umount2 — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_dac_modification_umount2
Severity	Medium
Description	At a minimum, the audit system should collect file system umount2 changes. If the auditd daemon is configured to use the au
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A

Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_execution_chacl: Record Any Attempts to Run chacl — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_execution_chacl
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1

Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_execution_setfacl: Record Any Attempts to Run setfacl — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_execution_setfacl
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000

Agents	Triage(1)

audit_rules_execution_chcon: Record Any Attempts to Run chcon — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_execution_chcon
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_execution_semanage: Record Any Attempts to Run semanage — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_execution_semanage
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_execution_setfiles: Record Any Attempts to Run setfiles — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_execution_setfiles
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_execution_setsebool: Record Any Attempts to Run setsebool — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_execution_setsebool
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.6s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_file_deletion_events_rename: Ensure auditd Collects File Deletion Events by User - rename — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_file_deletion_events_rename
Severity	Medium
Description	At a minimum, the audit system should collect file deletion events for all users and root. If the auditd daemon is configured to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core &
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_file_deletion_events_renameat: Ensure auditd Collects File Deletion Events by User - renameat — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_file_deletion_events_renameat
Severity	Medium
Description	At a minimum, the audit system should collect file deletion events for all users and root. If the auditd daemon is configured to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A

Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_file_deletion_events_rmdir: Ensure auditd Collects File Deletion Events by User - rmdir — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_file_deletion_events_rmdir
Severity	Medium
Description	At a minimum, the audit system should collect file deletion events for all users and root. If the auditd daemon is configured to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core &
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1

Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_file_deletion_events_unlink: Ensure auditd Collects File Deletion Events by User - unlink — *REQUIRES_HUMAN_REVIEW*

Rule	audit_rules_file_deletion_events_unlink
Severity	Medium
Description	At a minimum, the audit system should collect file deletion events for all users and root. If the auditd daemon is configured to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core &
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000

Agents	Triage(1)

audit_rules_file_deletion_events_unlinkat: Ensure auditd Collects File Deletion Events by User - unlinkat — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_file_deletion_events_unlinkat
Severity	Medium
Description	At a minimum, the audit system should collect file deletion events for all users and root. If the auditd daemon is configured to
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_unsuccessful_file_modification_creat: Record Unsuccessful Access Attempts to Files - creat — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_unsuccessful_file_modification_creat
Severity	Medium
Description	At a minimum, the audit system should collect unauthorized file accesses for all users and root. If the auditd daemon is config
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core &
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_unsuccessful_file_modification_ftruncate: Record Unsuccessful Access Attempts to Files - ftruncate — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_unsuccessful_file_modification_ftruncate

Severity	Medium
Description	At a minimum, the audit system should collect unauthorized file accesses for all users and root. If the auditd daemon is config
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_unsuccessful_file_modification_open: Record Unsuccessful Access Attempts to Files - open — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_unsuccessful_file_modification_open
Severity	Medium
Description	At a minimum, the audit system should collect unauthorized file accesses for all users and root. If the auditd daemon is config

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core &
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_unsuccessful_file_modification_open_by_handle_at: Record Unsuccessful Access Attempts to Files - open_by_handle_at — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_unsuccessful_file_modification_open_by_handle_at
Severity	Medium
Description	At a minimum, the audit system should collect unauthorized file accesses for all users and root. If the auditd daemon is config
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_unsuccessful_file_modification_openat: Record Unsuccessful Access Attempts to Files - openat — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_unsuccessful_file_modification_openat
Severity	Medium
Description	At a minimum, the audit system should collect unauthorized file accesses for all users and root. If the auditd daemon is config
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_unsuccessful_file_modification_truncate: Record Unsuccessful Access Attempts to Files - truncate — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_unsuccessful_file_modification_truncate
Severity	Medium
Description	At a minimum, the audit system should collect unauthorized file accesses for all users and root. If the auditd daemon is config
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A

Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_kernel_module_loading_delete: Ensure auditd Collects Information on Kernel Module Unloading - delete_module — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_kernel_module_loading_delete
Severity	Medium
Description	To capture kernel module loading and unloading events, use the following line, setting ARCH to either b32 for 32-bit system,
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1

Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_kernel_module_loading_finit: Ensure auditd Collects Information on Kernel Module Loading and Unloading - fini… — *REQUIRES_HUMAN_REVIEW*

Rule	audit_rules_kernel_module_loading_finit
Severity	Medium
Description	To capture kernel module loading and unloading events, use the following line, setting ARCH to either b32 for 32-bit system,
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0

Cost	$0.0000
Agents	Triage(1)

audit_rules_kernel_module_loading_init: Ensure auditd Collects Information on Kernel Module Loading - init_module — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_kernel_module_loading_init
Severity	Medium
Description	To capture kernel module loading and unloading events, use the following line, setting ARCH to either b32 for 32-bit system,
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_login_events_faillock: Record Attempts to Alter Logon and Logout Events - faillock — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_login_events_faillock
Severity	Medium
Description	The audit system already collects login information for all users and root. If the auditd daemon is configured to use the augen
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_login_events_lastlog: Record Attempts to Alter Logon and Logout Events - lastlog — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_login_events_lastlog
Severity	Medium

Description	The audit system already collects login information for all users and root. If the auditd daemon is configured to use the augen
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_login_events_tallylog: Record Attempts to Alter Logon and Logout Events - tallylog — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_login_events_tallylog
Severity	Medium
Description	The audit system already collects login information for all users and root. If the auditd daemon is configured to use the augen
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_privileged_commands_init: Ensure auditd Collects Information on the Use of Privileged Commands - init — REQUIRES_HUMAN_REVIEW

Rule	audit_privileged_commands_init
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_privileged_commands_poweroff: Ensure auditd Collects Information on the Use of Privileged Commands - poweroff — REQUIRES_HUMAN_REVIEW

Rule	audit_privileged_commands_poweroff
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A

Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_privileged_commands_reboot: Ensure auditd Collects Information on the Use of Privileged Commands - reboot — REQUIRES_HUMAN_REVIEW

Rule	audit_privileged_commands_reboot
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1

Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_privileged_commands_shutdown: Ensure auditd Collects Information on the Use of Privileged Commands - shutdown — REQUIRES_HUMAN_REVIEW

Rule	audit_privileged_commands_shutdown
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0

Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_chage: Ensure auditd Collects Information on the Use of Privileged Commands - chage — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_chage
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_chsh: Ensure auditd Collects Information on the Use of Privileged Commands - chsh — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_chsh
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_crontab: Ensure auditd Collects Information on the Use of Privileged Commands - crontab — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_crontab

Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_gpasswd: Ensure auditd Collects Information on the Use of Privileged Commands - gpasswd — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_gpasswd
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_kmod: Ensure auditd Collects Information on the Use of Privileged Commands - kmod — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_kmod
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_mount: Ensure auditd Collects Information on the Use of Privileged Commands - mount — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_mount
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓

Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_newgrp: Ensure auditd Collects Information on the Use of Privileged Commands - newgrp — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_newgrp
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A

Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.6s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_pam_timestamp_check: Ensure auditd Collects Information on the Use of Privileged Commands - pam_times… — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_pam_timestamp_check
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1

Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_passwd: Ensure auditd Collects Information on the Use of Privileged Commands - passwd — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_passwd
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0

Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_postdrop: Ensure auditd Collects Information on the Use of Privileged Commands - postdrop — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_postdrop
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_postqueue: Ensure auditd Collects Information on the Use of Privileged Commands - postqueue — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_postqueue
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_ssh_agent: Record Any Attempts to Run ssh-agent — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_ssh_agent
Severity	Medium

Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_ssh_keysign: Ensure auditd Collects Information on the Use of Privileged Commands - ssh-keysi… — *REQUIRES_HUMAN_REVIEW*

Rule	audit_rules_privileged_commands_ssh_keysign
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;

Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_su: Ensure auditd Collects Information on the Use of Privileged Commands - su — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_su
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗

Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_sudo: Ensure auditd Collects Information on the Use of Privileged Commands - sudo — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_sudo
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM

Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_sudoedit: Ensure auditd Collects Information on the Use of Privileged Commands - sudoedit — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_sudoedit
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_umount: Ensure auditd Collects Information on the Use of Privileged Commands - umount — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_umount
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s

Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_unix_chkpwd: Ensure auditd Collects Information on the Use of Privileged Commands - unix_chkp… — REQUIRES_HUMAN_REVIEW

Rule	audit_rules_privileged_commands_unix_chkpwd
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000

Agents	Triage(1)

audit_rules_privileged_commands_unix_update: Ensure auditd Collects Information on the Use of Privileged Commands - unix_upda… — *REQUIRES_HUMAN_REVIEW*

Rule	audit_rules_privileged_commands_unix_update
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_userhelper: Ensure auditd Collects Information on the Use of Privileged Commands - userhelpe… — *REQUIRES_HUMAN_REVIEW*

Rule	audit_rules_privileged_commands_userhelper
Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

audit_rules_privileged_commands_usermod: Ensure auditd Collects Information on the Use of Privileged Commands - usermod — *REQUIRES_HUMAN_REVIEW*

Rule	audit_rules_privileged_commands_usermod

Severity	Medium
Description	At a minimum, the audit system should collect the execution of privileged commands for all users and root. If the auditd daem
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

auditd_data_disk_error_action_stig: Configure auditd Disk Error Action on Disk Error — REQUIRES_HUMAN_REVIEW

Rule	auditd_data_disk_error_action_stig
Severity	Medium
Description	The auditd service can be configured to take an action when there is a disk error. Edit the file /etc/audit/auditd.conf. Add or m
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;

Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

auditd_data_disk_full_action_stig: Configure auditd Disk Full Action when Disk Space Is Full — REQUIRES_HUMAN_REVIEW

Rule	auditd_data_disk_full_action_stig
Severity	Medium
Description	The auditd service can be configured to take an action when disk space is running low but prior to running out of space comp
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗

Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

auditd_data_retention_admin_space_left_action: Configure auditd admin_space_left Action on Low Disk Space — REQUIRES_HUMAN_REVIEW

Rule	auditd_data_retention_admin_space_left_action
Severity	Medium
Description	The auditd service can be configured to take an action when disk space is running low but prior to running out of space comp
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM

Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

auditd_data_retention_admin_space_left_percentage: Configure auditd admin_space_left on Low Disk Space — REQUIRES_HUMAN_REVIEW

Rule	auditd_data_retention_admin_space_left_percentage
Severity	Medium
Description	The auditd service can be configured to take an action when disk space is running low but prior to running out of space comp
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

auditd_data_retention_space_left_action: Configure auditd space_left Action on Low Disk Space — REQUIRES_HUMAN_REVIEW

Rule	auditd_data_retention_space_left_action
Severity	Medium
Description	The auditd service can be configured to take an action when disk space starts to run low. Edit the file /etc/audit/auditd.conf. M
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.3s
Total Tokens	0

Cost	$0.0000
Agents	Triage(1)

auditd_data_retention_space_left_percentage: Configure auditd space_left on Low Disk Space — REQUIRES_HUMAN_REVIEW

Rule	auditd_data_retention_space_left_percentage
Severity	Medium
Description	The auditd service can be configured to take an action when disk space is running low but prior to running out of space comp
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

auditd_freq: Set number of records to cause an explicit flush to audit logs — REQUIRES_HUMAN_REVIEW

Rule	auditd_freq
Severity	Medium
Description	To configure Audit daemon to issue an explicit flush to disk command after writing records, set freq to in /etc/audit/auditd.conf
Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.4s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)

auditd_name_format: Set type of computer node name logging in audit logs — REQUIRES_HUMAN_REVIEW

Rule	auditd_name_format
Severity	Medium
Description	To configure Audit daemon to use a unique identifier as computer node name in the audit events, set name_format to in /etc/a

Recommendation	Remediation script: # Remediation is applicable only in certain platforms if rpm --quiet -q audit && rpm --quiet -q kernel-core;
Host / OS	localhost / localhost.localdomain

Triage Decision

Should Remediate	✗
Human Review	✓
Risk Level	MEDIUM
Reason	LLM triage failed; defaulting to requires_human_review. Last error: API/runtime error with openai/gpt-oss-20b: OpenRouter A
Estimated Impact	triage automation failure

LLM Metrics

LLM Calls	1
Duration	0.5s
Total Tokens	0
Cost	$0.0000
Agents	Triage(1)