

# Access Methods I: Tree-based indexes

"If you don't find it in the index, look very carefully through the entire catalogue."

-- Sears, Roebuck, and Co.,  
Consumer's Guide, 1897


# Example

Relation R

name	age	weight
Moe	10	55
Curly	10	65
Larry	12	70
Bob	15	60
Alice	17	48
Lucy	17	45
John	17	59
Charlie	20	69
Marcie	22	50
Linus	23	60
Sally	23	48
Tom	25	56

SELECT \* FROM R WHERE weight BETWEEN 50 AND 55

# Example




**SELECT \* FROM R WHERE weight BETWEEN 50 AND 55**

# Example

Relation R

name	age	weight
Moe	10	55
Curly	10	65
Larry	12	70
Bob	15	60
Alice	17	48
Lucy	17	45
John	17	59
Charlie	20	69
Marcie	22	50
Linus	23	60
Sally	23	48
Tom	25	56



Scan  
the  
entire  
relation

SELECT \* FROM R WHERE weight BETWEEN 50 AND 55


# *Single Record and Range Searches*

- Single record retrievals
  - *“Find student name whose matric# = 921000Y13”*
- Range queries
  - *“Find all students with  $2.0 < cap < 2.5$ ”*
- Sequentially scanning the file is costly
- If data is sorted in the search condition
  - Can stop once you find the desired record(s)
  - Can you do a binary search?

# Indexes


- An **index** is a data structure on a file to speed up retrieval/selections based on some **search key**
  - Any **subset** of the fields of a relation can be the search key for an index on the relation
  - **Search key** is **NOT** the same as **key** (minimal set of fields that uniquely identify a record in a relation)
    - e.g., consider Student(matric#, name, addr, cap), the key is matric#, but the search key can be matric#, name, addr, cap or any combination of them (e.g., (name, address))
  - For each search key, you can build an index, i.e., there can be multiple indexes on a single relation that provides different **access paths**
- An index is a **unique index** if its search key is a candidate key; otherwise, it is a non-unique index
- An index is stored as a file
  - Records in an index file are referred to as **data entries**

# Simple Index File: **Unsorted** Data File



(50, ●) is the data entry for the data record (Marcie, 22, 50)


# Simple Index File



SELECT \* FROM R WHERE weight BETWEEN 50 AND 55




# Simple Index File




SELECT \* FROM R WHERE weight BETWEEN 65 AND 69

# Simple Index File




(48, ■) is the index entry for the first page of data entries

# Simple Index File




SELECT \* FROM R WHERE weight BETWEEN 65 AND 69

# Simple Index File



# Simple Index File



SELECT \* FROM R WHERE weight BETWEEN 65 AND 69

What if data file is sorted  
(on search key)?

What if you want to insert a new record, say (Judy, 24, 47) for (un)sorted data file?


# Index Types

- Two main types of indexes
  - Tree-based index
    - Based on **sorting of search key** values
    - Examples: ISAM, **B<sup>+</sup>-tree**
  - Hash-based index
    - Data entries are accessed using **hashing function**
    - Examples: static hashing, extensible hashing, linear hashing
- Things to consider when choosing an index
  - Search performance
    - Equality search:  $k = v$
    - Range search:  $v_1 \leq k \leq v_2$
  - Storage overhead
  - Update performance



# Tree-Structured Indexing


- Tree-structured indexing techniques support both *range searches* and *equality searches*



# B+ Tree: The Most Widely Used Index

Employee

name	dept#	...
Alice	5	...
Bob	16	...
Charlie	19	...
Curly	39	...
Dave	38	...
Eve	14	...
Fred	33	...
Harry	2	...
John	34	...
Kate	8	...
Larry	27	...
Linus	24	...
Lucy	3	...
Marcie	22	...
Moe	29	...
Sally	20	...
Tom	7	...




Employee

name	dept#	...
Alice	5	...
Bob	16	...
Charlie	19	...
Curly	39	...
Dave	38	...
Eve	14	...
Fred	33	...
Harry	2	...
John	34	...
Kate	8	...
Larry	27	...
Linus	24	...
Lucy	3	...
Marcie	22	...
Moe	29	...
Sally	20	...
Tom	7	...

# B+ Tree: The Most Widely Used Index

- Leaf nodes stored **sorted** data entries
  - $k^*$  denote a **data entry** of the form  $(k, \text{RID})$ 
    - $k$  = search key value of corresponding data record
    - RID = RID of corresponding record
  - Leaf nodes are either **singly** or doubly linked
  - Each data record has an entry in the leaf node (**dense index**)
  - Efficient for range search**




B+-tree index on Employee.dept#

(each node can hold 4 entries (**order = 2**))

## Employee

name	dept#	...
Alice	5	...
Bob	16	...
Charlie	19	...
Curly	39	...
Dave	38	...
Eve	14	...
Fred	33	...
Harry	2	...
John	34	...
Kate	8	...
Larry	27	...
Linus	24	...
Lucy	3	...
Marcie	22	...
Moe	29	...
Sally	20	...
Tom	7	...


- Internal nodes store index entries of the form  $(p_0, k_1, p_1, k_2, p_2, \dots, p_n)$ 
  - $k_1 < k_2 < \dots < k_n$
  - $p_i$  = disk page address (root node of an index subtree  $T_i$ )
  - For each data entry  $k^*$  in  $T_0$ ,  $k < k_1$
  - For each data entry  $k^*$  in  $T_i$  ( $i \in [1, n)$ ),  $k \in [k_i, k_{i+1})$
  - For each data entry  $k^*$  in  $T_n$ ,  $k \geq k_n$
- Key values for index entries (internal nodes) are **separators** (not necessarily correspond to any key values)
  - e.g., 13, 30. How did this happen???




B+-tree index on Employee.dept#

# Node structure

- A node essentially corresponds to a page (each node access costs an I/O)
- Non-leaf node



- Leaf node



# *How to determine the Order?*


- A node essentially corresponds to a page
- Assume 8 KB page, 8-byte key, 4-byte pointer, we have
  - $m = 2*d$
  - $(2d+1)*4 + 2d*8 \leq 8096$
  - $d \sim 336$
- $m = 672$  (though we can actually store 673 entries ~ 8080 bytes!)

# Properties of $B^+$ Tree

- *Height-balanced* (*search and update efficient*)
  - Insert/delete at  $\log_F N$  cost ( $F$  = fanout,  $N$  = # leaf pages)
- *Grow and shrink dynamically* (*update efficient*)
- Minimum 50% occupancy (except for root) (*storage efficient*)
  - Each non-leaf node contains  $d \leq m \leq 2d$  entries. The parameter  $d$  is called the *order* of the tree
  - *Order* ( $d$ ) concept replaced by physical space criterion in practice (*'at least half-full'*)
- next-leaf-pointer to chain up the leaf nodes (*efficient range search*)
- Data entries at leaf are sorted

# Searching in B+ Tree

- Search begins at root, and key comparisons direct it to a leaf
  - At each internal node  $N$ , find the largest key  $k_j$  in  $N$  s.t.  $k \geq k_j$ 
    - If  $k_j$  exists, then search subtree at  $p_j$
    - Otherwise, search subtree at  $p_0$
- Search for 5






# Searching in B+ Tree

- Search begins at root, and key comparisons direct it to a leaf
  - At each internal node  $N$ , find the largest key  $k_j$  in  $N$  s.t.  $k \geq k_j$ 
    - If  $k_j$  exists, then search subtree at  $p_j$
    - Otherwise, search subtree at  $p_0$
- Search for 15


*Based on the search for 15\*, we know no such records in the database!*

*How can we be certain?*



# Searching in B+ Tree

- Search begins at root, and key comparisons direct it to a leaf
  - At each internal node  $N$ , find the largest key  $k_j$  in  $N$  s.t.  $k \geq k_j$ 
    - If  $k_j$  exists, then search subtree at  $p_j$
    - Otherwise, search subtree at  $p_0$
- Search for all data entries between 22 and 27




# *B+ Trees in Practice*

- Typical order: 100. Typical fill-factor: 67%
  - average fanout = 133
- Typical capacities (**root at Level 1 with 1 entry**):
  - Level 4:  $2 \times 133^3 = 2 \times 2,352,637$  pointers
  - Level 5:  $2 \times 133^4 = 2 \times 312,900,700$  pointers
- Can often hold top levels in buffer pool:
  - Level 1 = 1 page = 8 Kbytes
  - Level 2 = 133 pages = 1 Mbyte
  - Level 3 = 17,689 pages = 133 MBytes

# Formats of Data Entries


- So far, our examples assume  $k^*$  is of the form  $(k, \text{rid})$ , where  $\text{rid}$  is the record identifier of a data record with search key value  $k$ 
  - This is referred to as **Format 2 (Default unless otherwise stated)**
- Two other different formats for data entries:
  - **Format 1**:  $k^*$  is an actual data record (with search key value  $k$ )
  - **Format 3**:  $k^*$  is of the form  $(k, \text{rid-list})$ , where  $\text{rid-list}$  is a list of record identifiers of data records with search key value  $k$

# Formats of Data Entries: Example




$B^+$ -tree index on R.age (Format 1)

name	age	weight	height
Moe	10	55	180
Curly	10	65	171
Larry	12	70	175
Bob	15	60	178
Alice	17	48	175
Lucy	17	45	170
John	18	59	182
Charlie	20	69	173
Marcie	22	50	165
Linus	23	60	166
Sally	24	48	169
Tom	25	56	176




$B^+$ -tree index on R.age (Format 2)

# Formats of Data Entries: Example




Index on R.age (format 3)

Relation R			
name	age	weight	height
Moe	10	55	180
Curly	10	65	171
Larry	12	70	175
Bob	15	60	178
Alice	17	48	175
Lucy	17	45	170
John	18	59	182
Charlie	20	69	173
Marcie	22	50	165
Linus	23	60	166
Sally	24	48	169
Tom	25	56	176




Index on R.age (format 2)

# *Inserting 7 into Example B+ Tree*



Find the leaf node to insert


# *Inserting 7 into Example B+ Tree*




What if we insert 8 now?



# Inserting 8 into Example B+ Tree




# *Inserting 8 into Example B+ Tree*




# Insertion Algorithm

- Find correct leaf  $L$
- Put data entry into  $L$ 
  - If  $L$  has enough space, *done!*
  - Else, must split  $L$  (into  $L$  and a new node  $L2$ )
    - Redistribute entries evenly, copy up middle key
    - Insert index entry pointing to  $L2$  into parent of  $L$
- This can happen recursively (**index node can be full!**)
  - To split index node, redistribute entries evenly, but push up middle key (Contrast with leaf splits)
- Splits “grow” tree; root split increases height
  - Tree growth: gets wider or one level taller at top

# *Inserting 8 into Example B+ Tree (Internal node is full)*





# Inserting 8 into Example B+ Tree





# Insertion (Cont)

- Note difference between *copy-up* (for leaf nodes) and *push-up* (for internal nodes); be sure you understand the reasons for this
- Observe how minimum occupancy is guaranteed in both leaf and index page splits




# Example B+ Tree After Inserting 8




- Notice that root was split, leading to increase in height
- Tree gets wider and one level taller

# Delete 19 from the example tree






# *Delete 19 from the example tree*



- Deleting 19 is easy
- Delete 20 next?

# *Example Tree After Deleting 20 ...*




- Deleting 20 is done with **re-distribution**
- Notice how middle key is *copied up*


# *Deleting a Data Entry from a B+ Tree*

- Start at root, find leaf  $L$  where entry belongs
- Remove the entry
  - If  $L$  is at least half-full, *done!*
  - If  $L$  has only  $d-1$  entries,
    - Try to **re-distribute**, borrowing from sibling (*adjacent node with same parent as  $L$* )
    - If re-distribution fails, merge  $L$  and sibling
- If merge occurs, must delete entry (pointing to  $L$  or sibling) from parent of  $L$
- Merge could propagate to root, decreasing height

# *Example Tree*




# Example Tree After Deleting 24 ...




Node underflows

- Must merge




# ... And Then Deleting 24


- Observe *toss* of index entry, and *pull down* of index entry




# Example of Non-leaf Re-distribution (Delete 24)



# Example of Non-leaf Re-distribution (Delete 24)




- In contrast to previous example, can **re-distribute entry from left child of root to right child**.






# Re-distribution




# After Re-distribution

- Intuitively, entries are **re-distributed by 'pushing through'** the splitting entry in the parent node
- It suffices to re-distribute index entry with key 20; we've re-distributed 17 as well for illustration



# Clustered vs Unclustered Index


- An index is a **clustered index** if the order of its data entries is the same as or “close to” the order of the data records; otherwise, it is an **unclustered index**



# ***Clustered vs. Unclustered Index***


- An index using Format 1 for its data entries is a clustered index
- There is at most one clustered index for each relation.  
Why?
- Suppose the data file is unsorted
  - To build clustered index, first sort the data file (with some free space on each page for future inserts)
  - Overflow pages may be needed for inserts
    - Thus, order of data records is *close to*, but not identical to, the sort order

# Clustered vs Unclustered Index: Example



Relation R


name	age	weight	height
Moe	10	55	180
Curly	10	65	171
Larry	12	70	175
Bob	15	60	178
Alice	17	48	175
Lucy	17	45	170
John	18	59	182
Charlie	20	69	173
Marcie	22	50	165
Linus	23	60	166
Sally	24	48	169
Tom	25	56	176



(RIDij = slot j on data page i)

# Dense vs. Sparse


- Dense index
  - There is at least one data entry per search key value (in some data record)
  - B+-tree is a dense index
- Sparse index
  - Every sparse index is **clustered**
  - Sparse indexes are smaller
  - Sparse index cannot support “exists” search



# Multi-attribute Indexes

- **Composite Search Keys:** Search on a combination of fields
  - Equality query: Every field value is equal to a constant value. E.g. wrt  $\langle \text{age}, \text{sal} \rangle$  index:
    - $\text{age}=22 \ \& \ \text{sal} =75$
  - Range query: Some field value is not a constant. E.g.:
    - $\text{age}=22 \ \& \ \text{sal} > 10$  (use  $\langle \text{age}, \text{sal} \rangle$ )
    - $\text{age} < 22 \ \& \ \text{sal} = 10$  (use  $\langle \text{age}, \text{sal} \rangle$  may fetch more records than desired)
- Data entries in index sorted by search key to support range queries
  - Lexicographic order, or
  - Spatial order
- There are also multi-attribute indexing structures (e.g., R-trees)

Examples of composite key indexes using lexicographic order.



# Summary

- B+-tree index can facilitate fast search for both single record and range search
  - Storage-friendly (works well on any kind of storage)
  - good performance
  - universal applicability
- Is it always beneficial to use an index for data retrieval?
- Is it beneficial to build indexes on ALL (combinations of) attributes of a table?