


# Network Programming:

## *Basic client/server application:*

### *1. getaddrinfo*

# Sockets Interface



# Host and Service Conversion: `getaddrinfo`

- **`getaddrinfo(3)` is the modern way to convert string representations of hostnames, host addresses, ports, and service names to socket address structures.**
  - Replaces obsolete `gethostbyname` and `getservbyname` funcs.
  - Resolving implemented by `libc`, *not* kernel (which implements TCP/IP).
- **Advantages:**
  - Reentrant (can be safely used by threaded programs).
  - Allows us to write portable protocol-independent code
    - Works with both IPv4 and IPv6
- **Disadvantages:**
  - Somewhat complex
  - Fortunately, a small number of usage patterns suffice in most cases.

# Host and Service Conversion: getaddrinfo


```
int getaddrinfo(const char *host,          /* Hostname or address */
               const char *service,       /* Port / service name */
               const struct addrinfo *hints, /* Input parameters */
               struct addrinfo **result);  /* Output linked list */

void freeaddrinfo(struct addrinfo *result); /* Free linked list */

const char *gai_strerror(int errcode);     /* Return error msg */
```

- Given host and service, `getaddrinfo` sets `result` to point to a linked list of **addrinfo** structs, each of which points to a corresponding **SA**, and which contains arguments for the sockets interface functions.
- **Helper functions:**
  - `freeaddrinfo` frees the entire linked list.
  - `gai_strerror` converts error code to an error message.

# Linked List Returned by getaddrinfo



- **Clients:** walk this list, trying each socket address in turn, until the calls to `socket` and `connect` succeed.
- **Servers:** walk the list until calls to `socket` and `bind` succeed.

# addrinfo Struct

```
struct addrinfo {  
    int          ai_flags;      /* Hints argument flags */  
    int          ai_family;     /* First arg to socket function */  
    int          ai_socktype;   /* Second arg to socket function */  
    int          ai_protocol;   /* Third arg to socket function */  
    char         *ai_canonname; /* Canonical host name */  
    size_t       ai_addrlen;    /* Size of ai_addr struct */  
    SA           *ai_addr;      /* Ptr to socket address structure */  
    struct addrinfo *ai_next;    /* Ptr to next item in linked list */  
};
```

- Each `addrinfo` struct returned by `getaddrinfo` contains arguments that can be passed directly to `socket` function.
- Also points to a `SA` struct that can be passed directly to `connect` and `bind` functions.

# Host and Service Conversion: `getnameinfo`

- `getnameinfo` is the inverse of `getaddrinfo`, converting a socket address to the corresponding host and service.
  - Replaces obsolete `gethostbyaddr` and `getservbyport` funcs.
  - Reentrant and protocol independent.

```
int getnameinfo(const SA *sa, socklen_t salen, /* In: socket addr */
               char *host, size_t hostlen, /* Out: host */
               char *serv, size_t servlen, /* Out: service */
               int flags); /* optional flags */
```

# Conversion Example

```
#include "csapp.h"

int main(int argc, char **argv)
{
    struct addrinfo *p, *listp, hints;
    char buf[MAXLINE];
    int rc, flags;

    /* Get a list of addrinfo records */
    memset(&hints, 0, sizeof(struct addrinfo));
    hints.ai_family = AF_INET; /* IPv4 only, remove for any */
    hints.ai_socktype = SOCK_STREAM; /* TCP Connections only */
    if ((rc = getaddrinfo(argv[1], NULL, &hints, &listp)) != 0) {
        fprintf(stderr, "getaddrinfo error: %s\n", gai_strerror(rc));
        exit(1);
    }
}
```

hostinfo.c



# Conversion Example (cont)

```
/* Walk the list and display each IP address */
flags = NI_NUMERICHOST; /* Display address instead of name */
for (p = listp; p; p = p->ai_next) {
    Getnameinfo(p->ai_addr, p->ai_addrlen,
                buf, MAXLINE, NULL, 0, flags);
    printf("%s\n", buf);
}

/* Clean up */
Freeaddrinfo(listp);

exit(0);
}
```

hostinfo.c

# Running hostinfo



# Running hostinfo

```
$ ./hostinfo localhost  
127.0.0.1
```

# Running hostinfo

```
$ ./hostinfo localhost  
127.0.0.1
```

```
$ ./hostinfo mc.cdm.depaul.edu  
216.220.181.74
```

# Running hostinfo

```
$ ./hostinfo localhost
```

```
127.0.0.1
```

```
$ ./hostinfo mc.cdm.depaul.edu
```

```
216.220.181.74
```

```
$ ./hostinfo twitter.com
```

```
199.16.156.230
```

```
199.16.156.38
```

```
199.16.156.102
```

```
199.16.156.198
```