1. Inspect the pilot's access and usage

Use an authorized demonstration tenant with existing entitlements. This walkthrough doesn't require purchasing licenses, enabling paid consumption, changing a password, or weakening an identity policy.

1. Sign in to the Microsoft 365 admin center with the administration account. Identify the tenant and account before proceeding.

2. Open Billing > Licenses. Select the Copilot product shown in your tenant and inspect its assignments. Record the intended pilot user's existing assignment; don't assign a new product merely to make a screenshot.

3. Open Users > Active users and inspect the same user's Licenses and apps details where available. Keep entitlement separate from source access.

4. In the inspected tenant, open Copilot > Cost management, then classic Billing & usage. In tenants using the documented classic navigation, open Copilot > Billing & usage.

5. Inspect the existing billing policy and the service to which it is attached. Record the audience and response owner. Don't create a new Azure billing relationship or activate paid usage as part of this walkthrough.

6. Select Show all if Reports is hidden. Open Reports > Usage > Microsoft Copilot > Copilot, then the Usage tab.

7. Choose a reporting period and read the update date. Compare enabled users, active users, and application usage. Explain that report latency prevents it from being an immediate activation test.

8. Test the approved source document separately as the intended pilot user. Record the application and source. An administrator opening the document isn't equivalent evidence.

Interpretation: entitlement, service consumption, source authorization, adoption, and answer quality are separate observations. The budget notification in the classic billing-policy workflow isn't an enforced spending cap.

Current first-party references (checked October 19, 2026)

Set up Microsoft Copilot

Pay-as-you-go setup

Copilot usage report

Microsoft 365 Copilot architecture

2. Create the label-based DLP example

Prepared fixture: a harmless test file labelled Pearson Demo - Restricted. The label must already be configured and available in the demonstration tenant. The literal label name is a proposed fixture, not a claim that it already exists. Keep this example isolated from production labels.

1. Open the Microsoft Purview portal. Go to Solutions > Data Loss Prevention > Policies, then Create policy.

2. Choose the Custom template and Custom policy. Name it Pearson-AB900-Copilot-Label-Demo. Describe it as a synthetic training configuration.

3. On Locations, select Microsoft 365 Copilot and Copilot Chat. The documented location is supported by the Custom template and disables other locations in that policy. It doesn't support administrative units.

4. Add a rule named Exclude synthetic restricted guide. Select Content contains > Sensitivity labels. Choose only the prepared Pearson Demo - Restricted label.

5. For the action, select Prevent Copilot from processing content. Review the exact displayed action, since prompt-processing and web-search actions are different controls.

6. Keep the initial policy in simulation mode. Review the summary and create only the isolated training policy when the environment and label are prepared.

7. Record the policy name, rule, label, location, mode, creation time, and actual result in the private rehearsal record. Configuration success isn't evidence of blocking.

8. For a later controlled enforcement rehearsal, first establish that the test user can read the file and retrieve a harmless marker without the protection in effect. After an authorized policy-mode change and propagation, repeat the same test and record the result.

Boundary: a labelled file can remain in citations while its content is excluded from processing. In Word, Excel, and PowerPoint, reopen a file if its label changed during the session. Don't infer failure solely from citation presence, or success solely from a missing answer.

Current first-party references (checked October 19, 2026)

DLP for Microsoft 365 Copilot and Copilot Chat

Create and deploy a DLP policy

3. Inspect SharePoint oversharing

1. From Microsoft 365 admin center, open the tenant's SharePoint admin center. Go to Reports > Data access governance.

2. Identify the available report families and collection state. A site-permissions snapshot describes current access; sharing-link activity describes a time window. They answer different questions.

3. For the prepared demonstration site, use the available report's creation or run action, with its displayed scope. If data collection isn't enabled, record that prerequisite instead of treating the empty page as evidence.

4. Read the report's generation status. Report collection and generation can take time. Keep a dated captured report available for the live session and label it accurately.

5. Inspect a broad-permission or sharing-link finding. Identify the site, access pattern, intended audience, and accountable content owner.

6. Ask the owner whether the broad access is required. In a lab, make only the approved correction to the isolated fixture. Don't remove broad access from an unrelated production site.

7. Retest source access as the intended pilot user and an excluded test user. Record the exact results; a report row alone doesn't establish effective access.

8. Review the report again after its documented refresh interval. Keep the before and after observations, collection periods, and timestamps together.

Licensing and population affect report availability. SharePoint Advanced Management provides the full reporting and remediation experience; some E5 access is more limited. Consult the current report prerequisites before planning a particular report. If the required report is unavailable, use the included synthetic-sharing-report.csv as a labelled discussion exercise, not as tenant evidence.

Exercise

The synthetic site has broad read permission but no new broad links in its recent activity window. Explain why both can be true, then name the evidence needed to verify a repair.

Current first-party references (checked October 19, 2026)

SharePoint data access governance

4. Close the loop with posture and ownership

Purview's current documentation distinguishes DSPM from DSPM for AI (classic). Use the experience present in your tenant. The sample configurations handout explains how to handle that difference without inventing a common menu.

1. Select a finding relevant to the pilot's information sources. Read its scope, timestamp, evidence, and recommendation before deciding whether it applies.

2. Assign the investigation to the source owner. Record whether the finding is an actual exposure, a justified access pattern, or a condition requiring more evidence.

3. Apply the narrow correction through the organization's normal process. Keep identity, source permissions, DLP, and lifecycle controls separate in the change record.

4. Repeat the relevant source-access and content-use tests. Don't substitute a configured policy, simulation event, or empty query for the intended live behavior.

5. Review adoption and task quality alongside the protection evidence. Decide whether to continue, repair, or expand the pilot.

6. Retain the synthetic fixtures for the scheduled demonstration. Afterward, retire only the isolated course-owned policy and files according to the lab owner's decision.

Evidence record

Field	Record
Who and where	Account, tenant, application, source, report scope
What changed	Policy or permission, before and after state
What happened	Exact operation and observed result
When	Timestamp, propagation wait, report period
Decision	Owner, next action, completion criterion

No live enforcement, report completion, or agent publishing result is implied by this walkthrough. Those results belong in a dated rehearsal record.

Current first-party references (checked October 19, 2026)

Protect data used by Copilot

DLP for Microsoft 365 Copilot and Copilot Chat

SharePoint data access governance

Copilot usage report