RESOLUTE BiSS readhead part numbers

Linear and partial arc readheads

R L 32B B T 001 E 30 A

Series

R = RESOLUTE

Scale form

L = Linear/partial arc

Serial interface

26B = BiSS 26 bit

32B = BiSS 32 bit

36B = BiSS 36 bit

Mechanical option

B = Standard cable outlet

R = Side cable outlet

Gain option

T = RTLA30 / RTLA30-S / RKLA30-S

S = RSLA30

E = RELA30

Resolution

001 = 1 nm

005 = 5 nm

050 = 50 nm

Scale code option [1]

B = RTLA30 / RTLA30-S / RKLA30-S (20 mm to 10 m scale length)

C = RSLA30 (20 mm to 5 m scale length) / RELA30 (> 1.13 m to 1.5 m scale length)

D = RELA30 (20 mm to 1.13 m scale length)

E = RTLA30 / RTLA30-S / RKLA30-S (> 10 m to 21 m scale length)

Cable length

02 = 0.2 metres
05 = 0.5 metres
10 = 1.0 metres
15 = 1.5 metres
30 = 3.0 metres
50 = 5.0 metres
90 = 9.0 metres
99 = 10.0 metres

Cable termination

A = 9-way D-type connector

F = Flying lead (unterminated cable)

L = LEMO in-line connector

S = M12 (sealed) connector

For RESOLUTE BiSS UHV and Functional Safety linear readhead part numbers see the relevant data sheet at **www.renishaw.com/resolutedownloads**.

Valid system configurations (readheads and scale) can be checked at **www.renishaw.com/epc**.

[1] The maximum scale length may be limited for some serial interfaces and resolutions; refer to 'Resolution and scale lengths' on page 7 for details.