


# JMS 302: Hacking the Media

## Problem Set for Week 10

### 1. iTunes mimicry

- Download cover art for 12 or more of your favorite albums. Put them in an “images” folder in your week\_10 homework folder.
- Create an HTML file titled “my\_favorite\_albums.html” and put the album cover with artist and title in an unordered list.
  - See class discussion about the formatting for this.
- Create an external style sheet that makes the list look iTunes-ish. Minimum:
  - No bullets.
  - The list should flow from left to right and then down.
  - Bold the artist name.
  - Put the artist and album title on separate lines.
  - Try to include extras like: rounded corners and drop-shadow.



---

### In Class

For your own reference (nothing to turn in). You should review the finished code on GitHub.

1. **Word Frequency.** Write code that reads a text file and prints out a count of each word in the file.

## **2. Simple Debugging.**

- a. Using puts
- b. end (quotes, brackets, parenthesis, etc.) error messages
- c. formatting (indenting)
- d. Also, sorty\_by and reading lines of code, and f.puts

## **3. Restaurants by User.**

## **4. Rock, Paper, Scissors.**

---

### **On hold – don't do**

## **2. Random movie generator, v1 (command line, hashes)**

Generate a random movie generator. It should:

1. Look for a file named "movies.txt."
  - 1.1.If it does not exist, ask the user: "Enter the name of a viewer:"
    - 1.1.1. Then ask: "Enter the names of movies or TV shows [viewer] likes (press enter when done and we'll select a movie):"
  - 1.2.Determine the viewers in "movies.txt" and ask the user: "Select one of these viewers or type "Other" to add a viewer."
    - 1.2.1. If the user does not type "Other," ask the user: "Enter the names of movies or TV shows [viewer] likes (press enter when done and we'll select a movie):"
    - 1.2.2. If the user types "Other," ask: Enter the name of a viewer:"
      - 1.2.2.1. Then ask the user: "Enter the names of movies or TV shows [viewer] likes (press enter when done and we'll select a movie):"
  - 1.3. When the user is done entering movies, save movies to "movies.txt" with the viewer, then randomly generate a movie for the selected viewer. Print out "Watch [movie] from [viewer]'s list."

Hints: Use methods to eliminate redundancies. User hashes.  
Format “movies.txt” like so (using tabs or similar character to  
separate the two pieces of data on a line):

```
viewer_1  movie_1  
viewer_2  movie_2  
viewer_2  movie_3
```

Using YAML would be a better idea (and I may make that an iteration of  
this later), but I want you to get use to creating hashes.