

# Databases

## Part 2/2 SQL

**Kai Brännler**  
**CAS Applied Data Science**  
**University of Bern**

Material adapted from: Silberschatz, Korth, Sudarshan: Database System Concepts. 6th Edition.

# Comparison Procedural vs Declarative

- Example: Find the name of the instructor with ID 22222

```
import csv

with open('instructor.csv') as file:
    reader = csv.DictReader(file)
    for row in reader:
        if row['ID'] == '2222':
            print(row['name'])
```

```
select name
from    instructor
where ID = '22222'
```

# Comparison Procedural vs Declarative

- Example: Find the building of the instructor “Einstein”

```
import csv

with open('instructor.csv') as file:
    reader = csv.DictReader(file)
    for row in reader:
        if row['name'] == 'Einstein':
            dept_name = row['dept_name']

with open('department.csv') as file:
    reader = csv.DictReader(file)
    for row in reader:
        if row['dept_name'] == dept_name:
            print(row['building'])
```

```
select building
from    instructor, department
where   instructor.dept_name =
         department.dept_name
         and
         name = 'Einstein'
```

# Create Table

- Example:

```
create table instructor (  
    ID          char(5),  
    name       varchar(20),  
    dept_name varchar(20),  
    salary    numeric(8,2))
```

- Example with Integrity Constraints:

```
create table instructor (  
    ID          char(5),  
    name       varchar(20) not null,  
    dept_name varchar(20),  
    salary    numeric(8,2),  
    primary key (ID),  
    foreign key (dept_name) references department)
```

# The select Clause

- By default SQL lists duplicate tuples:

```
select dept_name  
from instructor
```

- To force the elimination of duplicates:

```
select distinct dept_name  
from instructor
```

- To retain duplicates (default):

```
select all dept_name  
from instructor
```

- An asterisk denotes “all attributes”

```
select *  
from instructor
```

- Can contain arithmetic expressions:

```
select ID, name, salary / 12  
from instructor
```

# Natural Join

- Natural join joins two tables in the natural way:
  - By combining all rows that have the same values on the common attributes.
- List the names of instructors along with the course ID of the courses that they taught:
  - **select** *name, course\_id*  
**from** *instructor, teaches*  
**where** *instructor.ID = teaches.ID;*
  - **select** *name, course\_id*  
**from** *instructor* **natural join** *teaches;*

# Natural Join Example

- **select \* from *instructor* natural join *teaches*;**

ID	name	dept_name	salary
10101	Srinivasan	Comp. Sci.	65000
12121	Wu	Finance	90000
15151	Mozart	Music	40000
22222	Einstein	Physics	95000
32343	El Said	History	60000
33456	Gold	Physics	87000
45565	Katz	Comp. Sci.	75000
58583	Califieri	History	62000
76543	Singh	Finance	80000
76766	Crick	Biology	72000
83821	Brandt	Comp. Sci.	92000
98345	Kim	Elec. Eng.	80000

ID	course_id	sec_id	semester	year
10101	CS-101	1	Fall	2009
10101	CS-315	1	Spring	2010
10101	CS-347	1	Fall	2009
12121	FIN-201	1	Spring	2010
15151	MU-199	1	Spring	2010
22222	PHY-101	1	Fall	2009
32343	HIS-351	1	Spring	2010
45565	CS-101	1	Spring	2010
45565	CS-319	1	Spring	2010
76766	BIO-101	1	Summer	2009
76766	BIO-301	1	Summer	2010
83821	CS-190	1	Spring	2009
83821	CS-190	2	Spring	2009
83821	CS-319	2	Spring	2010
98345	EE-181	1	Spring	2009

ID	name	dept_name	salary	course_id	sec_id	semester	year
10101	Srinivasan	Comp. Sci.	65000	CS-101	1	Fall	2009
10101	Srinivasan	Comp. Sci.	65000	CS-315	1	Spring	2010
10101	Srinivasan	Comp. Sci.	65000	CS-347	1	Fall	2009
12121	Wu	Finance	90000	FIN-201	1	Spring	2010
15151	Mozart	Music	40000	MU-199	1	Spring	2010
22222	Einstein	Physics	95000	PHY-101	1	Fall	2009
32343	El Said	History	60000	HIS-351	1	Spring	2010
45565	Katz	Comp. Sci.	75000	CS-101	1	Spring	2010
45565	Katz	Comp. Sci.	75000	CS-319	1	Spring	2010
76766	Crick	Biology	72000	BIO-101	1	Summer	2009
76766	Crick	Biology	72000	BIO-301	1	Summer	2010
83821	Brandt	Comp. Sci.	92000	CS-190	1	Spring	2009
83821	Brandt	Comp. Sci.	92000	CS-190	2	Spring	2009
83821	Brandt	Comp. Sci.	92000	CS-319	2	Spring	2010
98345	Kim	Elec. Eng.	80000	EE-181	1	Spring	2009

# Renaming, String Matching, Ordering

- Often we rename attributes or relations:

```
select ID, name, salary/12 as monthly_salary  
from instructor
```

- We can match strings using patterns containing:
  - percent (%). Matches any substring.
  - underscore (\_). Matches any character.

```
select name  
from instructor  
where name like ' _ _ _ %stein %'
```

- List names in alphabetic order:


```
select distinct name  
from instructor  
order by name
```





# Set Operations: union, intersect, except

Keyword in SQL	Set Operation
<b>union</b>	union
<b>intersect</b>	intersection
<b>except</b>	difference


Union of A and B



Intersection of A and B



Difference A minus B



Difference B minus A

- Find courses that ran in 2009 or in 2010 or both:

```
select course_id from section where year = 2009  
union  
select course_id from section where year = 2010
```

- Set operations eliminate duplicates
- To retain duplicates use **union all**, **intersect all** and **except all**

# Null Values

- How would you add an instructor if you don't know his/her salary?
  - Use a special value? Like 0 or -1?
- There is the special value **null**, which signifies an unknown or non-existent value
- Every attribute can be **null** unless its explicitly forbidden

# Null Values

- Rules for Null values:
  - The result of any arithmetic expression involving *null* is *null*
  - A comparison with *null* returns the special boolean value *unknown*
  - The **where** clause treats *unknown* as *false*

- What's the result of this?

```
select name  
from instructor  
where salary = null
```

name	salary
Einstein	80000
Katz	null
Mozart	0

- Null values are often problematic.
  - Check for null with **is null**
  - Always consider the possibility that a value is null.

# Aggregate Functions

- Find the average salary of instructors in the Computer Science department
  - **select avg** (*salary*)  
**from** *instructor*  
**where** *dept\_name*= 'Comp. Sci.';
- Find the number of tuples in the *course* relation
  - **select count** (\*)  
**from** *course*;
- Find the number of instructors who taught a course in 2010
  - **select count** (**distinct** *ID*)  
**from** *teaches*  
**where** *year* = 2010;

# Aggregate Functions – Group By

- Find the average salary of instructors in each department
  - select** *dept\_name*, **avg** (*salary*) as *avg\_salary*  
**from** *instructor*  
**group by** *dept\_name*;

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
76766	Crick	Biology	72000
45565	Katz	Comp. Sci.	75000
10101	Srinivasan	Comp. Sci.	65000
83821	Brandt	Comp. Sci.	92000
98345	Kim	Elec. Eng.	80000
12121	Wu	Finance	90000
76543	Singh	Finance	80000
32343	El Said	History	60000
58583	Califieri	History	62000
15151	Mozart	Music	40000
33456	Gold	Physics	87000
22222	Einstein	Physics	95000

<i>dept_name</i>	<i>avg_salary</i>
Biology	72000
Comp. Sci.	77333
Elec. Eng.	80000
Finance	85000
History	61000
Music	40000
Physics	91000

# Nested Queries

- A **subquery** is a query inside another query.
- There are three kinds of subqueries:
  - in the **from**-clause,
  - in the **where**-clause, using **in** or **exists**
  - scalar subqueries (that can occur anywhere).

# Subquery in the Where-Clause – in

- Find courses offered in 2009 and in 2010

```
select distinct course_id  
from section  
where year = 2009 and  
course_id in ( select course_id  
                  from section  
                  where year = 2010 );
```

# Subquery in the Where-Clause – exists

- **exists** *r* returns **true** iff *r* is nonempty.
- Find all courses taught in both 2009 and 2010  

```
select course_id
from section as S
where year = 2009 and
      exists (select *
              from section as T
              where year = 2010 and S.course_id = T.course_id);
```

  - S is a **correlation variable**
  - the inner query is a **correlated subquery**



# Scalar Subqueries

- A **scalar subquery** is a subquery which is used where a single value is expected
  - If it returns more than one tuple it causes a runtime error
- Find the instructors that cost more than 10% of their departments budget:

```
select name
from instructor
where salary * 10 >
      (select budget from department
       where department.dept_name = instructor.dept_name)
```

# Deletion

- Delete all instructors

**delete from** *instructor* ;

- Delete all instructors from the Finance department

**delete from** *instructor*  
**where** *dept\_name* = 'Finance';

- Delete all tuples in the *instructor* relation for those instructors associated with a department located in the Watson building.

**delete from** *instructor*  
**where** *dept\_name* in (**select** *dept\_name*  
                          **from** *department*  
                          **where** *building* = 'Watson');

# Deletion

- Delete all instructors whose salary is less than the average salary of instructors

**delete from** *instructor*

**where** *salary* < (**select avg** (*salary*) **from** *instructor*);

- Problem: as we delete tuples, the average salary changes
- Solution used in SQL:
  - First, compute avg salary and find all tuples to delete
  - Only then delete all those tuples

# Insertion

- Add a new tuple to *course*:

```
insert into course  
values ('CS-437', 'Database Systems', 'Comp. Sci.', 4);
```

- Equivalent and better:

```
insert into course (course_id, title, dept_name, credits)  
values ('CS-437', 'Database Systems', 'Comp. Sci.', 4);
```

- Add all instructors to the *student* relation with *tot\_creds* set to 0

```
insert into student  
select ID, name, dept_name, 0  
from instructor
```

# Updates

- Increase salaries of instructors by 5%:

```
update instructor  
set salary = salary * 1.05;
```

- Problem: How to increase salaries of instructors whose salary is over \$100,000 by 3%, and all others by 5%?
  - Write two **update** statements?

```
update instructor  
  set salary = salary * 1.03  
  where salary > 100000;  
update instructor  
  set salary = salary * 1.05  
  where salary <= 100000;
```

# Updates – case statement

- Problem as before, solution with case statement:

```
update instructor  
  set salary =  
    case  
      when salary <= 100000 then salary * 1.05  
      else salary * 1.03  
    end
```