RoutinesRGB v1.9.8

Generated by Doxygen 1.8.8

Sun Jul 3 2016 16:02:53

Contents

1	Mod	ule Ind	ex									1
	1.1	Module	es			 	 	 	 	 	 	1
2	Clas	s Index	T									3
	2.1	Class	List			 	 	 	 	 	 	3
3	File	Index										5
	3.1	File Lis	st			 	 	 	 	 	 	5
4	Mod	ule Dod	cumentatio	on								7
	4.1	Getter	s and Sette	rs		 	 	 	 	 	 	7
		4.1.1	Detailed	Description .		 	 	 	 	 	 	7
		4.1.2	Function	Documentation	١	 	 	 	 	 	 	7
			4.1.2.1	barSize		 	 	 	 	 	 	7
			4.1.2.2	blinkSpeed .		 	 	 	 	 	 	7
			4.1.2.3	blue		 	 	 	 	 	 	8
			4.1.2.4	brightness .		 	 	 	 	 	 	8
			4.1.2.5	color		 	 	 	 	 	 	8
			4.1.2.6	customColorC	Count	 	 	 	 	 	 	8
			4.1.2.7	fadeSpeed .		 	 	 	 	 	 	8
			4.1.2.8	green		 	 	 	 	 	 	8
			4.1.2.9	mainColor .		 	 	 	 	 	 	8
			4.1.2.10	red		 	 	 	 	 	 	8
			4.1.2.11	setColor		 	 	 	 	 	 	8
			4.1.2.12	setCustomCo	lorCount	 	 	 	 	 	 	8
			4.1.2.13	setMainColor		 	 	 	 	 	 	9
	4.2	Single	Color Rou	ines		 	 	 	 	 	 	10
		4.2.1	Detailed	Description .		 	 	 	 	 	 	10
		4.2.2		Documentation								10
			4.2.2.1	singleBlink .								10
			4.2.2.2	singleFade .								10
			4000	oinglo Climmo								10

iv CONTENTS

			4.2.2.4	singleSawtoothFade		11
			4.2.2.5	singleSolid		11
			4.2.2.6	singleWave		11
	4.3	Multi C	olors Rout	tines		12
		4.3.1	Detailed	Description		12
		4.3.2	Function	Documentation		12
			4.3.2.1	multiBarsMoving		12
			4.3.2.2	multiBarsSolid		12
			4.3.2.3	multiFade		12
			4.3.2.4	multiGlimmer		13
			4.3.2.5	multiRandomIndividual		13
			4.3.2.6	multiRandomSolid		13
	4.4	These	methods o	can be called after a routine is chosen		14
5	Clas	s Docui	mentation			15
•	5.1			* ass Reference		15
	0.1	5.1.1		Description		16
		5.1.2		etor & Destructor Documentation		16
		0.1.2	5.1.2.1	RoutinesRGB		16
		5.1.3		Function Documentation		17
		0.1.0	5.1.3.1	applyBrightness		'
			5.1.3.2	drawColor		., 17
			5.1.3.3	resetToDefaults		'
			0.1.0.0	Toostropolation	•	.,
6	File I	Docume	entation		•	19
	6.1	ColorP	resets.h Fi	ile Reference		19
		6.1.1	Detailed	Description		19
	6.2	Lightin	gProtocols	s.h File Reference		19
		6.2.1	Detailed	Description	. 2	20
		6.2.2	Enumera	ation Type Documentation	. 2	20
			6.2.2.1	EColorGroup	. 2	20
			6.2.2.2	ELightingRoutine	. 2	21
			6.2.2.3	EPacketHeader	. 2	22

Index

23

Module Index

1.1 Modules

Here is a l	ist of all	modules:

Getters and Setters	7
Single Color Routines	10
Multi Colors Routines	12
These methods can be called after a routine is chosen	14

2 **Module Index**

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

RoutinesRGB

An Arduino library that provides a set of RGB lighting routines for compatible LED array hardware 15

Class Index

File Index

\mathbf{a}	-4	 	
-4	т.	 ПΩ	ICT

Here is a list of all documented files with brief descriptions:	
ColorPresets.h	19
LightingProtocols.h	19
RoutinesRGB.h	??

6 File Index

Module Documentation

4.1 Getters and Setters

Functions

- bool RoutinesRGB::setMainColor (byte r, byte g, byte b)
- void RoutinesRGB::setColor (uint16_t colorIndex, byte r, byte g, byte b)
- void RoutinesRGB::setCustomColorCount (uint8 t count)
- uint8_t RoutinesRGB::customColorCount ()
- void RoutinesRGB::brightness (uint8_t brightness)
- void RoutinesRGB::fadeSpeed (uint8 t fadeSpeed)
- void RoutinesRGB::blinkSpeed (uint8_t blinkSpeed)
- void RoutinesRGB::barSize (uint8_t barSize)
- Color RoutinesRGB::mainColor ()
- Color RoutinesRGB::color (uint16_t i)
- uint8_t RoutinesRGB::red (uint16_t i)
- uint8_t RoutinesRGB::green (uint16_t i)
- uint8_t RoutinesRGB::blue (uint16_t i)

4.1.1 Detailed Description

These are the getters and setters for RoutinesRGB that are used to control the settings and the colors.

4.1.2 Function Documentation

4.1.2.1 void RoutinesRGB::barSize (uint8_t barSize)

Sets the size of bars in routines that use them. Bars are groups of LEDs that all display the same color. The routines SingleWave, MultiBarsSolid, and MultiBarsMoving use them.

a number greater than 0 and less than the number of LEDs being used.

4.1.2.2 void RoutinesRGB::blinkSpeed (uint8_t blinkSpeed)

Sets how many updates to wait before changing the light state in the blink routine and in routines that switch between solid colors.

8 Module Documentation

Parameters

blinkSpeed	a value between 1 and 255 representing how fast to blink. A value of 1 will make it blink on
	every frame, which may be too fast when used with other routines.

4.1.2.3 uint8_t RoutinesRGB::blue (uint16_t i)

Retrieve the b value at a given index in the buffer.

4.1.2.4 void RoutinesRGB::brightness (uint8_t brightness)

Set the brightness between 0 and 100. 0 is off, 100 is full power.

4.1.2.5 RoutinesRGB::Color RoutinesRGB::color (uint16_t i)

Retrieve the color at the given index.

4.1.2.6 uint8_t RoutinesRGB::customColorCount()

Retrieve the amount of colors that are used from the custom array.

4.1.2.7 void RoutinesRGB::fadeSpeed (uint8_t fadeSpeed)

Sets the speed of routines that fade between colors between 1 and 100. A fade speed of 1 is the slowest possible fade.

4.1.2.8 uint8_t RoutinesRGB::green (uint16_t i)

Retrieve the g value at a given index in the buffer.

4.1.2.9 RoutinesRGB::Color RoutinesRGB::mainColor ()

Retrieve the main color, which is used for single color routines.

4.1.2.10 uint8_t RoutinesRGB::red (uint16_t i)

Retrieve the r value at a given index in the buffer.

4.1.2.11 void RoutinesRGB::setColor (uint16_t colorIndex, byte r, byte g, byte b)

Set the color in the custom color array at the provided index. colorIndex must be less than the size of the custom color array or else it won't have any effect.

4.1.2.12 void RoutinesRGB::setCustomColorCount (uint8_t count)

Sets the amount of colors used in custom multi color routines. The value given must be less than the size of the custom array or else it will be set to use the entire array.

4.1 Getters and Setters 9

4.1.2.13 bool RoutinesRGB::setMainColor (byte r, byte g, byte b)

Sets the color used for single color routines. This is automatically called by each routine. Returns false if the new main color matches the previous main color.

Returns

true if a new color is set, false if the input matches the current color.

10 Module Documentation

4.2 Single Color Routines

Functions

- void RoutinesRGB::singleSolid (uint8_t red, uint8_t green, uint8_t blue)
- void RoutinesRGB::singleBlink (uint8_t red, uint8_t green, uint8_t blue)
- void RoutinesRGB::singleWave (uint8 t red, uint8 t green, uint8 t blue)
- void RoutinesRGB::singleGlimmer (uint8_t red, uint8_t green, uint8_t blue, uint8_t percent=20)
- void RoutinesRGB::singleFade (uint8 t red, uint8 t green, uint8 t blue, bool isSine)
- void RoutinesRGB::singleSawtoothFade (uint8 t red, uint8 t green, uint8 t blue, bool fadeln)

4.2.1 Detailed Description

These routines each take a R, G, and B value as parameters to generate a color. This color is the only color used by the routine.

All routines except singleSolid should be called repeatedly on a loop for their full effect. The speed of the loop determines how fast the LEDs update.

4.2.2 Function Documentation

4.2.2.1 void RoutinesRGB::singleBlink (uint8_t red, uint8_t green, uint8_t blue)

Switches between ON and OFF states using the provided color.

Parameters

red	strength of red LED, between 0 and 255
green	strength of green LED, between 0 and 255
blue	strength of blue LED, between 0 and 255

4.2.2.2 void RoutinesRGB::singleFade (uint8_t red, uint8_t green, uint8_t blue, bool isSine)

Fades the LEDs in and out based on the provided color. Can fade in two ways: linear and sine. If isSine is set to false, the interval between each update is constant. If isSine is true, a sine wave is used to generate the intervals, resulting in lights that stay on near their full brightness for longer.

Parameters

red	strength of red LED, between 0 and 255
green	strength of green LED, between 0 and 255
blue	strength of blue LED, between 0 and 255
isSine	if true, a sine wave is used, if false, constant intervals are used.

4.2.2.3 void RoutinesRGB::singleGlimmer (uint8_t red, uint8_t green, uint8_t blue, uint8_t percent = 20)

Set every LED to the provided color. A subset of the LEDs based on the percent parameter will be less bright than the rest of the LEDs.

red	strength of red LED, between 0 and 255
green	strength of green LED, between 0 and 255
blue	strength of blue LED, between 0 and 255
percent	determines how many LEDs will be slightly dimmer than the rest, between 0 and 100

4.2.2.4 void RoutinesRGB::singleSawtoothFade (uint8_t red, uint8_t green, uint8_t blue, bool fadeIn)

If fadeIn is true, the LEDs start with a brightness value of 0 and each update rasies the brightness by a constant value. When it reaches maximum brightness, it resets the brightness back to 0 and repeats the fade in. If fadeIn is set to false, it does the opposite; it starts at full brightness and then fades to darkness.

Parameters

red	strength of red LED, between 0 and 255
green	strength of green LED, between 0 and 255
blue	strength of blue LED, between 0 and 255
fadeIn	if true, it fades from darkness to maximum brightness, if false, it fades from maximum bright-
	ness to darkness.

4.2.2.5 void RoutinesRGB::singleSolid (uint8_t red, uint8_t green, uint8_t blue)

Set every LED to the provided color.

Parameters

red	strength of red LED, between 0 and 255
green	strength of green LED, between 0 and 255
blue	strength of blue LED, between 0 and 255

4.2.2.6 void RoutinesRGB::singleWave (uint8_t red, uint8_t green, uint8_t blue)

Uses the provided color and generates groups of the color in increasing levels of brightness. On each update, the LEDs move one index to the right. This creates a wave/scrolling effect.

	red	strength of red LED, between 0 and 255
Ī	green	strength of green LED, between 0 and 255
Ī	blue	strength of blue LED, between 0 and 255

12 Module Documentation

4.3 Multi Colors Routines

Functions

- void RoutinesRGB::multiGlimmer (EColorGroup colorGroup, uint8_t percent=20)
- void RoutinesRGB::multiFade (EColorGroup colorGroup)
- void RoutinesRGB::multiRandomIndividual (EColorGroup colorGroup)
- void RoutinesRGB::multiRandomSolid (EColorGroup colorGroup)
- void RoutinesRGB::multiBarsSolid (EColorGroup colorGroup, uint8 t barSizeSetting)
- void RoutinesRGB::multiBarsMoving (EColorGroup colorGroup, uint8_t barSizeSetting)

4.3.1 Detailed Description

These routines use multiple colors. They all take the parameter of colorGroup which is used to determine which set of colors to use. The custom color array is eCustom, all other values for colorGroup come from groups of preset colors. Go to the project's github for a full list of the colorGroups and their corresponding values.

All routines except multiBarsSolid should be called repeatedly on a loop for their full effect. The speed of the loop determines how fast the LEDs update.

4.3.2 Function Documentation

4.3.2.1 void RoutinesRGB::multiBarsMoving (EColorGroup colorGroup, uint8_t barSizeSetting)

Provides a similar effect as multiBarSolid, but the alternating patches move up one LED index on each frame update to create a "scrolling" effect.

Parameters

colorGroup	the color group to use for the routine. eCustom is the custom array, all other values are preset	
	groups.	
barSize	how many LEDs before switching to the other bar.	

4.3.2.2 void RoutinesRGB::multiBarsSolid (EColorGroup colorGroup, uint8_t barSizeSetting)

Uses the chosen color group to set the LEDs in alternating patches with a size of barSize.

Parameters

colorGroup	the color group to use for the routine. eCustom is the custom array, all other values are preset	
	groups.	
barSize	how many LEDs before switching to the other bar.	

4.3.2.3 void RoutinesRGB::multiFade (EColorGroup colorGroup)

Fades between all the colors used by the color group.

colorGroup	the color group to use for the routine. eCustom is the custom array, all other values are presented	
	groups.	

4.3 Multi Colors Routines 13

4.3.2.4 void RoutinesRGB::multiGlimmer (EColorGroup colorGroup, uint8_t percent = 20)

This method uses its percent parameter to dim LEDs randomly, similar to the standard glimmer mode. It also uses the percent to randomly change the color of select LEDs to a color in the chosen color group. The base color is the first from the chosen color group.

Parameters

colorGroup	3 - 1 - 3 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	
	groups.	
percent	percent of LEDs that will get the glimmer applied, between 0 and 100	

4.3.2.5 void RoutinesRGB::multiRandomIndividual (EColorGroup colorGroup)

sets each individual LED as a random color from the chosen color group.

Parameters

colorGroup	the color array to use for the routine. eCustom is the custom array, all other values are
	colorGroup arrays.

4.3.2.6 void RoutinesRGB::multiRandomSolid (EColorGroup colorGroup)

A random color is chosen from the chosen color group and applied to each LED.

colorGroup	the color group to use for the routine. eCustom is the custom array, all other values are present	
	groups.	

14 Module Documentation

4.4 These methods can be called after a routine is chosen

but before the routines get displayed to the LEDs. They add special effects to the routines.

Class Documentation

5.1 RoutinesRGB Class Reference

An Arduino library that provides a set of RGB lighting routines for compatible LED array hardware.

```
#include <RoutinesRGB.h>
```

Public Member Functions

- RoutinesRGB (uint16_t ledCount)
- void resetToDefaults ()
- bool setMainColor (byte r, byte g, byte b)
- void setColor (uint16_t colorIndex, byte r, byte g, byte b)
- void setCustomColorCount (uint8_t count)
- uint8_t customColorCount ()
- void brightness (uint8_t brightness)
- void fadeSpeed (uint8 t fadeSpeed)
- void blinkSpeed (uint8_t blinkSpeed)
- · void barSize (uint8_t barSize)
- Color mainColor ()
- Color color (uint16_t i)
- uint8_t red (uint16_t i)
- uint8_t green (uint16_t i)
- uint8 t blue (uint16 t i)
- void singleSolid (uint8_t red, uint8_t green, uint8_t blue)
- void singleBlink (uint8_t red, uint8_t green, uint8_t blue)
- void singleWave (uint8_t red, uint8_t green, uint8_t blue)
- void singleGlimmer (uint8_t red, uint8_t green, uint8_t blue, uint8_t percent=20)
- void singleFade (uint8_t red, uint8_t green, uint8_t blue, bool isSine)
- void singleSawtoothFade (uint8_t red, uint8_t green, uint8_t blue, bool fadeIn)
- void multiGlimmer (EColorGroup colorGroup, uint8_t percent=20)
- void multiFade (EColorGroup colorGroup)
- void multiRandomIndividual (EColorGroup colorGroup)
- void multiRandomSolid (EColorGroup colorGroup)
- void multiBarsSolid (EColorGroup colorGroup, uint8_t barSizeSetting)
- void multiBarsMoving (EColorGroup colorGroup, uint8_t barSizeSetting)
- void applyBrightness ()
- bool drawColor (uint16_t i, uint8_t red, uint8_t green, uint8_t blue)

16 Class Documentation

5.1.1 Detailed Description

An Arduino library that provides a set of RGB lighting routines for compatible LED array hardware.

Version

v1.9.8

Date

July 3, 2016

Author

Tim Seemann

Copyright

```
MIT License
```

This library has been tested with SeeedStudio Rainbowduinos, quite a few of the Adafruit Neopixels products, and a standard RGB LED. Sample code is provided in the git repo for all tested hardware in the samples folder of the git repository.

If you are starting a project from scratch, first you'll need to make a global object in the arduino sketch:

```
RoutinesRGB routines = RoutinesRGB(LED_COUNT);
```

where LED_COUNT is the number of LEDs in your array.

The library produces lighting routines based on the functions used and stores the routine in its internal buffers. These buffers can then be accessed by getters and displayed on the LED hardware. For routines that change over time, this process should be repeated on a loop. For example, here is how you would make a red blinking light with the library and a Neopixels board:

First, call this function to store the routine in the library's internal buffers:

```
routines.singleBlink(255, 0, 0);
```

Then, update the LED array with the values from the library's RGB buffer. The way to do this will vary from hardware to hardware, but for a NeoPixels sample, it would look something like this:

By this point, the LEDs should be showing red. To achieve the blink effect, put both of these in your loop () function and then put a delay between updates. This delay will be used to determine how fast the LED's blink.

5.1.2 Constructor & Destructor Documentation

5.1.2.1 RoutinesRGB::RoutinesRGB (uint16_t ledCount)

Required constructor. The library should be stored in global memory and allocated only once at startup.

It will allocate 4 * ledCount bytes.

Parameters

ledCount	number of individual RGB LEDs.

5.1.3 Member Function Documentation

5.1.3.1 void RoutinesRGB::applyBrightness ()

This function takes the **brightness()** value given to the routines object and applies it to every LED. Relatively speaking, this is a pretty expensive operation so it is left optional.

5.1.3.2 bool RoutinesRGB::drawColor (uint16_t i, uint8_t red, uint8_t green, uint8_t blue)

Attempts to draw the color provided on the index provided.

Parameters

i	the index of the LED that you want to change. Must be less than the total amount of LEDs or	
	else it will return false.	
red	the new red value of the LED, between 0 and 255.	
green	the new green value of the LED, between 0 and 255.	
blue	the new blue value of the LED, between 0 and 255.	

Returns

true if index exists and the color was drawn, false otherwise.

5.1.3.3 void RoutinesRGB::resetToDefaults ()

Resets all internal values to the original values.

18 **Class Documentation**

File Documentation

6.1 ColorPresets.h File Reference

```
#include <avr/pgmspace.h>
```

6.1.1 Detailed Description

Version

v1.9.8

Date

July 3, 2016

Author

Tim Seemann

Copyright

MIT License

These color presets are stored in program memory and loaded into a buffer when accessed. This makes the presets read-only, but in return, it allows them to take a much smaller hit on SRAM usage.

6.2 LightingProtocols.h File Reference

Enumerations

```
    enum ELightingRoutine {
        eOff, eSingleSolid, eSingleBlink, eSingleWave,
        eSingleGlimmer, eSingleLinearFade, eSingleSineFade, eSingleSawtoothFadeIn,
        eSingleSawtoothFadeOut, eMultiGlimmer, eMultiFade, eMultiRandomSolid,
        eMultiRandomIndividual, eMultiBarsSolid, eMultiBarsMoving }
    enum EColorGroup {
        eCustom, eWater, eFrozen, eSnow,
        eCool, eWarm, eFire, eEvil,
        eCorrorsive, ePoison, eRose, ePinkGreen,
        eRedWhiteBlue, eRGB, eCMY, eSixColor,
        eSevenColor, eAll }
```

20 File Documentation

enum EPacketHeader {
 eModeChange, eMainColorChange, eCustomArrayColorChange, eBrightnessChange,
 eSpeedChange, eCustomColorCountChange, eldleTimeoutChange, eResetSettingsToDefaults }

6.2.1 Detailed Description

Version

v1.9.8

Date

July 3, 2016

Author

Tim Seemann

Copyright

MIT License

This file defines the protocols used for the Arduino libraries and the GUI.

A slightly modified version of this file exists in the Qt GUI project. None of the modifications change the naming, documentation, or order of the protocols. Instead, the changes allow the GUI version to use the strongly typed enums that were made available in C++11.

6.2.2 Enumeration Type Documentation

6.2.2.1 enum EColorGroup

used during multi color routines to determine which colors to use in the routine. eCustom uses the custom color array, eAll generates its colors randomly. All other values use presets based around overall themes.

Enumerator

eCustom 0

Use the custom color array instead of a preset group.

eWater 1

Shades of blue with some teal.

eFrozen 2

Shades of teal with some blue, white, and light purple.

eSnow 3

Shades of white with some blue and teal.

eCool 4

Based on the cool colors: blue, green, and purple.

eWarm 5

Based on the warm colors: red, orange, and yellow.

eFire 6

Similar to the warm set, but with an emphasis on oranges to give it a fire-like glow.

eEvil 7

Mostly red, with some other, evil highlights.

eCorrorsive 8

Greens and whites, similar to radioactive goo from a 90s kids cartoon.

ePoison 9

A purple-based theme. Similar to poison vials from a 90s kids cartoon.

eRose 10

Shades of pink, red, and white.

ePinkGreen 11

The colors of watermelon candy. bright pinks and bright green.

eRedWhiteBlue 12

Bruce Springsteen's favorite color scheme, good ol' red, white, and blue.

eRGB 13

red, green, and blue.

eCMY 14

Cyan, magenta, yellow.

eSixColor 15

Red, yellow, green, cyan, blue, magenta.

eSevenColor 16

Red, yellow, green, cyan, blue, magenta, white.

eAll 17

Rather than using using preset colors, it uses all possible colors.

6.2.2.2 enum ELightingRoutine

Each routine makes the LEDs shine in different ways. There are two main types of routines: Single Color Routines use a single color while Multi Color Routines rely on an EColorGroup.

Enumerator

eOff 0

Turns off the LEDs.

eSingleSolid 1

Shows a single color at a fixed brightness.

eSingleBlink 2

Alternates between showing a single color at a fixed brightness and turning the LEDs completely off.

eSingleWave 3

Linear fade of the brightness of the LEDs.

eSingleGlimmer 4

Randomly dims some of the LEDs to give a glimmer effect.

eSingleLinearFade 5

Linear fade of the brightness of the LEDs.

eSingleSineFade 6

Uses a sine function to fade in and out. This makes it spend more time near the extremes of full brightness and very dim light, and less time in the mid range. of the LEDs.

eSingleSawtoothFadeIn 7

fades in starting at 0 brightness and increases a constant rate. Once it reaches full brightness, it resets back to zero and repeats.

eSingleSawtoothFadeOut 8

fades out starting at 0 brightness and decreases at a constant rate. Once it reaches 0, it resets back to full brightness and repeats.

eMultiGlimmer 9

Uses the first color of the array as the base color and uses the other colors for a glimmer effect.

eMultiFade 10

Fades slowly between each color in the array.

22 File Documentation

eMultiRandomSolid 11

Chooses a random color from the array and lights all all LEDs to match that color.

eMultiRandomIndividual 12

Chooses a random color from the array for each individual LED.

eMultiBarsSolid 13

Draws the colors of the array in alternating groups of equal size.

eMultiBarsMoving 14

Draws the colors of the array in alternating groups of equal size. On each update, it moves those groups one index to the right, creating a scrolling effect.

6.2.2.3 enum EPacketHeader

Message headers for packets coming over serial.

Enumerator

eModeChange 0

Takes one int parameter that gets cast to ELightingMode.

eMainColorChange 1

Takes 3 parameters, a 0-255 representation of Red, Green, and Blue.

eCustomArrayColorChange 2

Takes four parameters, three parameters, the LED, a 0-255 representation of Red, Green, and Blue.

eBrightnessChange 3

Takes one parameter, sets the brightness between 0 and 100.

eSpeedChange 4

Takes one parameter, sets the delay value 1 - 23767.

eCustomColorCountChange 5

Change the number of colors used in a custom array routine.

eldleTimeoutChange 6

Set to 0 to turn off, set to any other number minutes until idle timeout happens.

eResetSettingsToDefaults 7

Resets all values inside of RoutinesRGB back to their default values. Useful for soft reseting the LED hardware.

Index

blue	ePinkGreen
Getters and Setters, 8	LightingProtocols.h, 21
brightness	ePoison
Getters and Setters, 8	LightingProtocols.h, 20
	eRGB
color	LightingProtocols.h, 21
Getters and Setters, 8	eRedWhiteBlue
	LightingProtocols.h, 21
eAll	eResetSettingsToDefaults
LightingProtocols.h, 21	LightingProtocols.h, 22
eBrightnessChange	eRose
LightingProtocols.h, 22	LightingProtocols.h, 21
eCMY	eSevenColor
LightingProtocols.h, 21	LightingProtocols.h, 21
eCool	eSingleBlink
LightingProtocols.h, 20	LightingProtocols.h, 21
eCorrorsive	eSingleGlimmer
LightingProtocols.h, 20 eCustom	LightingProtocols.h, 21
LightingProtocols.h, 20	eSingleLinearFade
eCustomArrayColorChange	LightingProtocols.h, 21
LightingProtocols.h, 22	eSingleSawtoothFadeIn
eCustomColorCountChange	LightingProtocols.h, 21
LightingProtocols.h, 22	eSingleSawtoothFadeOut
eEvil	LightingProtocols.h, 21
LightingProtocols.h, 20	eSingleSineFade
eFire	LightingProtocols.h, 21
LightingProtocols.h, 20	eSingleSolid
eFrozen	LightingProtocols.h, 21
LightingProtocols.h, 20	eSingleWave
eldleTimeoutChange	LightingProtocols.h, 21
LightingProtocols.h, 22	eSixColor
eMainColorChange	LightingProtocols.h, 21
LightingProtocols.h, 22	eSnow
eModeChange	LightingProtocols.h, 20
LightingProtocols.h, 22	eSpeedChange
eMultiBarsMoving	LightingProtocols.h, 22
LightingProtocols.h, 22	eWarm
eMultiBarsSolid	LightingProtocols.h, 20
LightingProtocols.h, 22	eWater
eMultiFade	LightingProtocols.h, 20
LightingProtocols.h, 21	
eMultiGlimmer	Getters and Setters, 7
LightingProtocols.h, 21	blue, 8
eMultiRandomIndividual	brightness, 8
LightingProtocols.h, 22	color, 8
eMultiRandomSolid	green, 8
LightingProtocols.h, 21	red, 8
eOff	green
LightingProtocols.h. 21	Getters and Setters, 8

24 INDEX

```
LightingProtocols.h
    eAll, 21
    eBrightnessChange, 22
    eCMY, 21
    eCool, 20
    eCorrorsive, 20
    eCustom, 20
    eCustomArrayColorChange, 22
    eCustomColorCountChange, 22
    eEvil, 20
    eFire, 20
    eFrozen, 20
    eldleTimeoutChange, 22
    eMainColorChange, 22
    eModeChange, 22
    eMultiBarsMoving, 22
    eMultiBarsSolid, 22
    eMultiFade, 21
    eMultiGlimmer, 21
    eMultiRandomIndividual, 22
    eMultiRandomSolid, 21
    eOff, 21
    ePinkGreen, 21
    ePoison, 20
    eRGB, 21
    eRedWhiteBlue, 21
    eResetSettingsToDefaults, 22
    eRose, 21
    eSevenColor, 21
    eSingleBlink, 21
    eSingleGlimmer, 21
    eSingleLinearFade, 21
    eSingleSawtoothFadeIn, 21
    eSingleSawtoothFadeOut, 21
    eSingleSineFade, 21
    eSingleSolid, 21
    eSingleWave, 21
    eSixColor, 21
    eSnow, 20
    eSpeedChange, 22
    eWarm, 20
    eWater, 20
Multi Colors Routines, 12
red
    Getters and Setters, 8
Single Color Routines, 10
These methods can be called after a routine is chosen,
```