

Organizing Your Environment

> ****Series:**** ONBRD | ****Notebook:**** 6 of 10 | ****Created:**** December 2025

Tags, Segments, and Naming Conventions

As your Dynatrace environment grows, organization becomes critical. This notebook covers how to structure your environment with tags, segments, and naming conventions for maintainability and access control.

Table of Contents

1. Why Organization Matters
2. Modern Organization Building Blocks
3. Tagging with Host Properties and Cloud Tags
4. Segments for Data Filtering
5. Naming Conventions
6. Querying by Tags and Properties
7. Next Steps

Prerequisites

- Admin or Configurator access to Dynatrace
- Entities discovered (hosts, services)
- Understanding of your organizational structure

1. Why Organization Matters

Without organization, Dynatrace environments become difficult to manage:

Problem	Impact
-----	-----
No structure	Can't find entities quickly
No ownership	Don't know who to contact
No access control	Everyone sees everything
No filtering	Dashboards show irrelevant data
No grouping	Can't compare similar systems

Modern Organization Building Blocks

![Organization Hierarchy]

(

IG9mZnNldD0iMCuiIHN0eWxlPSJzdG9wLWNvbG9y0iM4YjVjZjY7c3RvcC1vcGFjaXR50jEiIC8+C
iAgICAgIDxdG9wIG9mZnNldD0iMTAwJSIgc3R5bGU9InN0b3AtY29sb3I6IzZjM2F1ZDtdZD9wLW
9wYWNpdHk6MSIgZ4KICAgIDwvbgLuZWFyR3JhZGllbnQ+CiaAgICA8bGluZWfYR3JhZGllbnQgaWQ
9InNLZ0dyYWQiIHGxPSIwJSIgeTE9IjAlIiB4Mj0iMTAwJSIgeTI9IjEwMCUiPgogICAgICA8c3Rv
cCBvZmZzZXQ9IjAlIiBzdHlsZT0ic3RvcC1jb2xvcjojM2I4MmY203N0b3Atb3BhY2l0eToxIiAvP
gogICAgICA8c3RvcCBvZmZzZXQ9IjEwMCUiIHN0eWxlPSJzdG9wLWNvbG9y0iMyNTYzZWl7c3RvcC
1vcGFjaXR50jEiIC8+CiaAgICA8L2xpbmVhckdyYWRpZW50PgogICAgPGxpbmVhckdyYWRpZW50IGl
kPSJ0YwdHcmFkIiB4MT0iMCUiIHkxPSIwJSIgeDI9IjEwMCUiIHkyPSIxMDAlIj4KICAgICAgPHN0
b3Agb2Zmc2V0PSIwJSIgc3R5bGU9InN0b3AtY29sb3I6IzEwYjJk4MTtZD9wLW9wYWNpdHk6MSIgZ
4KICAgICAgPHN0b3Agb2Zmc2V0PSIxMDAlIiBzdHlsZT0ic3RvcC1jb2xvcjojMDU5NjY503N0b3
Atb3BhY2l0eToxIiAvPgogICAgPC9saW5lYXJHcmFkaWVudD4KICAgIDxsaW5lYXJHcmFkaWVudCB
pZD0ibmFtZUdyYWQiIHGxPSIwJSIgeTE9IjAlIiB4Mj0iMTAwJSIgeTI9IjEwMCUiPgogICAgICA8
c3RvcCBvZmZzZXQ9IjAlIiBzdHlsZT0ic3RvcC1jb2xvcjojZjU5ZTBi03N0b3Atb3BhY2l0eToxI
iAvPgogICAgICA8c3RvcCBvZmZzZXQ9IjEwMCUiIHN0eWxlPSJzdG9wLWNvbG9y0iNk0Tc3MDY7c3
RvcC1vcGFjaXR50jEiIC8+CiaAgICA8L2xpbmVhckdyYWRpZW50PgogICAgPGxpbmVhckdyYWRpZW5
0IGlkPSJlbnRHcmFkIiB4MT0iMCUiIHkxPSIwJSIgeDI9IjEwMCUiIHkyPSIxMDAlIj4KICAgICAgPHN
0b3Agb2Zmc2V0PSIwJSIgc3R5bGU9InN0b3AtY29sb3I6IzY0NzQ4YjtzdG9wLW9wYWNpdHk6MS
SIgZ4KICAgICAgPHN0b3Agb2Zmc2V0PSIxMDAlIiBzdHlsZT0ic3RvcC1jb2xvcjojNDc1NTY503
N0b3Atb3BhY2l0eToxIiAvPgogICAgPC9saW5lYXJHcmFkaWVudD4KICAgIDxmaWx0ZXIgaWQ9Im9
yZ1NoYWRvdyI+CiaAgICAgIDxmZURyb3BTaGfkb3cgZHg9IjEiIGR5PSIxIiBzdGREZXZpYXRpb249
IjIiIGZsb29kLW9wYWNpdHk9IjAuMTUuLz4KICAgIDwvZmZzZGVyPgogIDwvZGVmcz4KICAgPCEtL
SBCYWNrZ3JvdW5kIC0tPgogIDxyZWNOIHdpZHRoPSI1MDAiIGhlaWdodD0iMzQwIiBmaWxsPSIjZj
hm0WZhIiByeD0iMTAiLz4KICAgPCEtLSBUaXR5ZSAAtLT4KICA8dGV4dCB4PSIyNTAiIHk9IjI4IiB
mb250LWZhbWlseT0iQXJpYWwsIHNhbnMtc2VyaWYiIGZvbnQtc2l6ZT0iMTYiIGZvbnQtd2VpZ2h0
PSJib2xkIiBmaWxsPSIjMzMzIiB0ZXh0LWFuY2hvcj0ibWlkZGxliIj5Pcmdhbmbl6YXRpb24gSGllc
mFyY2h5IChNb2Rlcm4gUGxhdGZvcmpPC90ZXh0PgoKICA8IS0tIExheWVyIDE6IFBvbGJlYWVzIC
YgUGVyblZlc2lvbnMgLS0+CiaAgPHJlY3QgeD0iNDAlIHk9IjUwIiB3aWR0aD0iNDIwIiBoZWlnaHQ
9IjQ4IiByeD0iOCIGZmlsbD0idXJsKCNwb2xHcmFkKSIGZmlsdGVyPSJ1cmwoI29yZ1NoYWRvdyki
Lz4KICA8dGV4dCB4PSIyNTAiIHk9IjcyIiBmb250LWZhbWlseT0iQXJpYWwsIHNhbnMtc2VyaWYiIG
ZvbnQtc2l6ZT0iMTYiIGZvbnQtd2VpZ2h0PSJib2xkIiBmaWxsPSJ3aG0ZSIgdGV4dC1hbmNob3
I9Im1pZGRsZSI+UG9saWNPZXMgJmFtcDsgUGVyblZlc2lvbnM8L3RleHQ+CiaAgPHRleHQgeD0iMjU
wIiB5PSI40CIGZm9udC1mYW1pbHk9IkFyaWFsLCBzYW5zLXNlcmIiBmb250LXNpemU9IjEwIiBm
aWxsPSJyZ2JhKDI1NSwNTUsMjU1LDAu0SkiIHRleHQTYW5jaG9yPSJtaWRkbGUiPiBY2Nlc3MgY
29udHJvbCB2aWEGSUFNKTwvdGV4dD4KICAgPCEtLSBMXl1lcAya0iBTZwdtZW50cyAtLT4KICA8cm
VjdCB4PSI0MCIGeT0iMTA1IiB3aWR0aD0iNDIwIiBoZWlnaHQ9IjQ4IiByeD0iOCIGZmlsbD0idXJ
sKCNzZWdHcmFkKSIGZmlsdGVyPSJ1cmwoI29yZ1NoYWRvdykiLz4KICA8dGV4dCB4PSIyNTAiIHk9
IjEyNyIgZm9udC1mYW1pbHk9IkFyaWFsLCBzYW5zLXNlcmIiBmb250LXNpemU9IjEyIiBmb250L
XdlawdodD0iYm9sZCIgZmlsbD0id2hpdGUiIHRleHQTYW5jaG9yPSJtaWRkbGUiPiNLZ21lbnRzPC
90ZXh0PgogIDx0ZXh0IHg9IjI1MCIGeT0iMTQzIiBmb250LWZhbWlseT0iQXJpYWwsIHNhbnMtc2V
yaWYiIGZvbnQtc2l6ZT0iMTA1IGZpbGw9InJnYmEoMjU1LDAu0SNTUsMC45KSIGdGV4dC1hbmNo
b3I9Im1pZGRsZSI+KERRTC1iYXNlZCBkYXRhIGZpbHRlcmLuZyk8L3RleHQ+CgogIDwhLS0gTGF5Z
XIGMzogVGfncyAtLT4KICA8cmVjdCB4PSI0MCIGeT0iMTYwIiB3aWR0aD0iNDIwIiBoZWlnaHQ9Ij
Q4IiByeD0iOCIGZmlsbD0idXJsKCN0YwdHcmFkKSIGZmlsdGVyPSJ1cmwoI29yZ1NoYWRvdykiLz4
KICA8dGV4dCB4PSIyNTAiIHk9IjE4MiIgZm9udC1mYW1pbHk9IkFyaWFsLCBzYW5zLXNlcmIiBm
b250LXNpemU9IjEyIiBmb250LXdlawdodD0iYm9sZCIgZmlsbD0id2hpdGUiIHRleHQTYW5jaG9yP
SJtaWRkbGUiPiRhZ3MgKEhvc3QgUHVjcvGVydgllcyArIENSb3VkiFRhZ3MpPC90ZXh0PgogIDx0ZX
h0IHg9IjI1MCIGeT0iMTk4IiBmb250LWZhbWlseT0iQXJpYWwsIHNhbnMtc2VyaWYiIGZvbnQtc2l6

! [Modern Tagging Flow]

[illegible]

```

**During Installation:**
```bash
Linux
sudo /bin/sh Dynatrace-OneAgent.sh \
 --set-host-property=env=production \
 --set-host-property=team=platform \
 --set-host-property=tier=backend

```

```
Windows
.\Dynatrace-OneAgent.exe --set-host-property=env=production --set-host-
property=team=checkout
```



```
```

**Via Configuration File:**
```

/var/lib/dynatrace/oneagent/agent/config/hostcustomproperties.conf
env=production
team=platform
cost-center=engineering
```

### Recommended Property Categories

Category	Example Properties	Purpose
<b>**Environment**</b>	`env=prod`, `env=staging`, `env=dev`	Distinguish environments
<b>**Owner**</b>	`team=platform`, `team=checkout`	Identify responsible team
<b>**Application**</b>	`app=ecommerce`, `app=mobile-api`	Group by application
<b>**Cost Center**</b>	`cost-center=marketing`	Financial allocation
<b>**Tier**</b>	`tier=frontend`, `tier=backend`	Architecture layer

### Cloud Provider Tags

Cloud tags are automatically imported when using cloud integrations:



Cloud	Tag Format	DQL Field
<b>**AWS**</b>	AWS resource tags	`aws.tag.*`
<b>**Azure**</b>	Azure resource tags	`azure.tag.*`
<b>**GCP**</b>	GCP labels	`gcp.label.*`

**AWS Tag Example:**

If your EC2 instance has tag `Environment=Production`, it appears as `aws.tag.Environment` in Dynatrace.

### Kubernetes Labels

K8s labels are automatically available for container workloads:



K8s Metadata	DQL Field
Namespace	`k8s.namespace.name`
Deployment	`k8s.deployment.name`


```


```



```
| Pod labels | `k8s.pod.labels.*` |
| Node labels | `k8s.node.labels.*` |
```

## ## 4. Segments for Data Filtering

Segments provide DQL-based filtering to create focused views of your data.

**\*\*Location:\*\*** Observe and explore → Segments

### ### What are Segments?

Segments are reusable DQL filters that:

- Filter data in Notebooks, Dashboards, and Apps
- Can be applied as default context
- Are shareable across the organization

### ### Creating a Segment

1. Go to Observe and explore → Segments
2. Click "Create segment"
3. Define your DQL filter:

```
```dql
dt.entity.host.properties.env == "production"
```
```
4. Name your segment (e.g., "Production Environment")
5. Save

### ### Segment Use Cases

| Use Case               | Segment Filter                                 | Purpose              |
|------------------------|------------------------------------------------|----------------------|
| <b>**Environment**</b> | <code>`properties.env == "prod"`</code>        | Focus on production  |
| <b>**Team**</b>        | <code>`properties.team == "checkout"`</code>   | Team-specific view   |
| <b>**Application**</b> | <code>`service.name contains "payment"`</code> | Application focus    |
| <b>**Region**</b>      | <code>`aws.tag.Region == "us-east-1"`</code>   | Geographic filtering |

### ### Segments vs Legacy Management Zones

| Feature                    | Segments             | Management Zones (Legacy) |
|----------------------------|----------------------|---------------------------|
| <b>**Filter basis**</b>    | DQL expressions      | Rule-based matching       |
| <b>**Data types**</b>      | All Grail data       | Entities only             |
| <b>**Flexibility**</b>     | Highly flexible      | Limited rule types        |
| <b>**Access control**</b>  | Use Policies instead | Built-in                  |
| <b>**Modern platform**</b> | ✅ Recommended        | ⚠️ Being deprecated       |

### ### Segment Best Practices

| Practice            | Why                             |
|---------------------|---------------------------------|
| Use host properties | Consistent filtering            |
| Name clearly        | Prod-Checkout-Team not Segment1 |
| Document purpose    | Add description                 |
| Test filters        | Verify expected data            |

## 5. Naming Conventions

Consistent naming makes entities discoverable and filtering effective.

### Host Naming

Set meaningful host names that encode key information:

| Pattern               | Example            | Components                  |
|-----------------------|--------------------|-----------------------------|
| {env}-{tier}-{seq}    | prod-web-01        | Environment, tier, sequence |
| {region}-{app}-{role} | us-east-ecom-api   | Region, app, role           |
| {team}-{service}-{id} | checkout-cart-a1b2 | Team, service, unique ID    |

### Host Naming via OneAgent

You can set a custom display name during installation:

```
bash
sudo /bin/sh Dynatrace-OneAgent.sh --set-host-name="prod-web-01"
```

### Naming Principles

| Principle   | Good                       | Bad                       |
|-------------|----------------------------|---------------------------|
| Descriptive | payment-service            | svc-001                   |
| Consistent  | prod-web-01, prod-web-02   | prod-web-01, Web Server 2 |
| Parseable   | us-east-prod-checkout      | USEastProdCheckout        |
| Unique      | Include environment/region | Generic names             |

### Property Naming Standards

For host properties, use consistent naming:

| Standard         | Example         | Why                              |
|------------------|-----------------|----------------------------------|
| Lowercase        | env=prod        | not ENV=PROD Consistency         |
| Hyphen separated | cost-center=eng | Readability                      |
| Short keys       | env             | not environment Query simplicity |



```
| **Consistent values** | Always `prod` not sometimes `production` |
Filtering works |
```

## ## 6. Querying by Tags and Properties

Use host properties and cloud tags in DQL queries to filter and group data.

```
```dql  
// Find hosts by name pattern  
fetch dt.entity.host  
| filter contains(entity.name, "prod")  
| fields entity.name  
| limit 20  
```  

```dql  
// Count hosts by operating system type  
fetch dt.entity.host  
| summarize host_count = count(), by: {osType}  
| sort host_count desc  
```  

```dql  
// Find services by name pattern  
fetch dt.entity.service  
| filter contains(entity.name, "checkout")  
| fields entity.name, serviceType  
| limit 20  
```  

```dql  
// Query logs filtered by host group (Kubernetes)  
fetch logs, from: now() - 1h  
| filter isNotNull(k8s.namespace.name)  
| summarize log_count = count(), by: {k8s.namespace.name}  
| sort log_count desc  
| limit 20  
```  

```dql  
// Query spans by service name pattern  
fetch spans, from: now() - 1h  
| filter span.kind == "server"  
| filter contains(service.name, "payment")  
| summarize request_count = count(), by: {service.name}  
| sort request_count desc  
| limit 20  
```
```

```
```sql
// Find hosts by name pattern for environment identification
fetch dt.entity.host
| filter not(contains(entity.name, "prod"))
      and not(contains(entity.name, "staging"))
      and not(contains(entity.name, "dev"))
| fields entity.name
| limit 20
```
```

## ## 7. Next Steps

With organization in place:

1. **\*\*ONBRD-07: Understanding Your Data\*\*** – Explore what Dynatrace discovered
2. Define host properties for your environment
3. Create segments for team-specific views
4. Document your naming conventions

### ### Organization Checklist

- [ ] Host property strategy documented
- [ ] Properties set on OneAgent installations
- [ ] Cloud tags verified (if using cloud providers)
- [ ] Segments created for common filters
- [ ] Naming conventions established
- [ ] Access control configured via Policies (see ONBRD-02)

---

## ## Summary

In this notebook, you learned:

- Why organization matters for scalability
- The modern "tag at source" approach
- How to use host properties and cloud tags
- How to create and use Segments for filtering
- Naming convention best practices
- How to query by properties and attributes

---

## ## References

- [Host Properties]([https://docs.dynatrace.com/docs/setup-and-configuration/dynatrace-oneagent/installation-and-](https://docs.dynatrace.com/docs/setup-and-configuration/dynatrace-oneagent/installation-and-configuration)

[operation/linux/installation/customize-oneagent-installation-on-linux](#))

- [Segments] (<https://docs.dynatrace.com/docs/observe-and-explore/segments>)
- [Cloud Tags] (<https://docs.dynatrace.com/docs/setup-and-configuration/setup-on-cloud-platforms>)
- [Kubernetes Labels] (<https://docs.dynatrace.com/docs/ingest-from/setup-on-k8s>)
- [DQL Reference] (<https://docs.dynatrace.com/docs/platform/grail/dynatrace-query-language>)