ORGNZ-01: Introduction to Organizing Data in Grail

> **Series:** ORGNZ — Organize Data: Buckets, Segments, Security | **Notebook:** 1 of 10 | **Created:** January 2026 | **Last Updated:** 10/13/2026

Overview

Dynatrace Grail organizes data in **buckets**, **tables**, and **views** to ensure efficient storage, flexible access, and scalable querying. Understanding how to organize your data is fundamental to achieving optimal query performance, compliance requirements, and access control.

Prerequisites

Requirement	Details
Dynatrace Environment	SaaS environment with Grail enabled
Permissions	`storage:buckets:read`, `storage:logs:read`
Knowledge	Basic Dynatrace navigation
Data	At least 1 hour of log data

Table of Contents

1. Why Organize Data?
2. The Grail Data Model
3. Three Pillars of Data Organization

4. When to Use Each Mechanism
5. Permission Levels in Grail
6. Exploring Your Data Organization
7. Organization Decision Framework

Learning Objectives

By the end of this notebook, you will:
- Understand why data organization matters in Grail
- Know the three pillars of data organization: buckets, segments, and security
- Recognize when to use each organization mechanism
- Understand the Grail data model structure


Why Organize Data?

Effective data organization in Grail enables:

Benefit	Description
Query Performance	Reduce query execution time by limiting data scope
Cost Control	Transparent GiB/day pricing with bucket-level attribution
Access Control	Fine-grained permissions from bucket to field level
Compliance	Meet retention and data residency requirements
Operational Clarity	Teams see only relevant data for faster troubleshooting


The Grail Data Model

Grail organizes data hierarchically with tables (data types), buckets (storage containers), and segments (logical views):



Three Pillars of Data Organization

All three pillars read metadata that was set once, upstream of them. This is the layered view — where tagging happens, and what consumes it:



Dynatrace states the ordering plainly: *"At-source enrichment is always preferred over OpenPipeline-based enrichment for the security context."* The value then travels, because

"Dynatrace enriches all derived signals (service metrics, Davis events, and problems) with the same tags." Buckets, segments and security context are three consumers of that one value; ownership routing and cost allocation are two more. **FAQ-02** covers the tagging side in full.

> **Spaces — upcoming; not yet documented as an available feature (status 10/13/2026).** `dt.space` is listed in the published semantic dictionary as an `experimental` permission field: *"The space associated with the record. Spaces enable granular scoping and delegation of monitoring responsibilities."* An earlier pre-release version of the SaaS 1.348 release notes announced space-based data access control in Grail (read 09/24/2026); the current version of those notes no longer lists it, and the IAM policy reference has no `dt.space` policy condition. Treat Spaces as **announced and subject to change** — the direction is a data-access control beside `dt.security_context`, deciding which *records* a team may read — and do not design access control around it until Dynatrace documents it as available on your tenant.
>
> The gap this column was first drawn for is still open in what Dynatrace documents. Nothing yet delegates which *configuration objects* a team may own — changing an alert, an SLO or a maintenance window still goes through whoever holds the settings permissions, which is how a central team becomes a queue. Whether spaces will also delegate ownership of configuration objects is **not documented**: as of 10/13/2026 there is no docs page for spaces, and `dt.space` was not in this validation tenant's `dt.semantic_dictionary.fields` — check yours. The field description's "delegation of monitoring responsibilities" is not a documented mechanism for owning configuration objects. Until Spaces is documented — and for configuration ownership in any case — design against what the other columns give you today.
>
> **Sources:** Permission fields — semantic dictionary (DT docs) — *"The space associated with the record. Spaces enable granular scoping and delegation of monitoring responsibilities."* (listed `experimental`). What's new in Dynatrace SaaS 1.348 (DT docs) — pre-release; read 09/24/2026 with a Spaces entry and 10/13/2026 without one. IAM policy reference (DT docs) — no `dt.space` condition, checked 10/13/2026. **Dictionary:** no row for `dt.space` in the validation tenant under `filter contains(name, "space")`, read 10/13/2026 (control: the same filter returned 23 other fields, including `dt.security_context`).

Sources: Configure security context (DT docs), Primary Grail fields and tags (DT docs).

1. Buckets (Physical Organization)

Buckets are logical storage containers where records are stored:

Aspect	Description
Purpose	Physical data partitioning and retention control
Scope	One data type per bucket (logs, metrics, etc.)
Retention	1 day to 10 years per bucket
Access	IAM policies can grant bucket-level access
Cost	Enable precise cost attribution by team/LOB

2. Segments (Logical Organization)

Segments provide dynamic, cross-signal data views:

Aspect	Description
Purpose	Real-time filtering without physical separation
Scope	Spans multiple data types and buckets
Flexibility	Rule-based, can use variables and relationships
Access	Governed by existing access controls
Cost	No direct storage cost impact

3. Security Context (Access Control)

Security context enables fine-grained permissions:

Aspect	Description
Purpose	Record-level access control
Mechanism	`dt.security_context` attribute on records
Flexibility	Custom values, hierarchical encoding
Enforcement	IAM policies filter at query time

When to Use Each Mechanism

Need	Solution	Rationale
Different retention periods	**Buckets**	Retention is set per bucket
Cost attribution by team	**Buckets**	Direct GiB/day billing visibility
Broad team isolation	**Buckets**	Simple bucket-level IAM policies
Dynamic data views	**Segments**	Filter across data types at query time
Application-centric views	**Segments**	Group related entities and signals
Record-level access control	**Security Context**	Fine-grained ABAC
Multi-team shared buckets	**Security Context**	Filter records within same bucket

Permission Levels in Grail

Grail supports permissions at multiple levels:

Level	Granularity	Example Use Case
Bucket	All records in a bucket	Team owns entire bucket
Table	All records of a data type	Access to all logs
Record	Individual records by attribute	By host group, namespace, security context
Field	Specific fields on records	Hide sensitive fields (fieldsets)

> **Important**: Without permissions, users cannot query data from Grail. Permissions must be explicitly granted.

Exploring Your Data Organization

DQL: Bucket Discovery

Use the following query to explore your Grail bucket configuration:

```
// List all buckets — foundational discovery query for your Grail environment
fetch dt.system.buckets
| fields name, display_name, dt.system.table, retention_days,
estimated_uncompressed_bytes
| sort dt.system.table asc, name asc
```

Organization Decision Framework

Use this framework to decide how to organize your data:



Series Overview

This series covers data organization in depth:

Notebook	Topic	Focus
ORGNZ-01	Introduction	Why and how to organize data
ORGNZ-02	Grail Buckets	Bucket fundamentals and limits
ORGNZ-03	Bucket Strategy	Naming, retention, design patterns
ORGNZ-04	Permissions Overview	Permission levels and policy management
ORGNZ-05	Bucket-Level Access	IAM policies for bucket access
ORGNZ-06	Security Context	Fine-grained access with dt.security_context
ORGNZ-07	Advanced Permissions	Record-level and field-based access
ORGNZ-08	Grail Segments	Dynamic data organization
ORGNZ-09	Enterprise Patterns	Combined approaches and best practices
ORGNZ-10	Advanced Segment Definitions	Filter syntax, enrichment, variables, troubleshooting

Next Steps

Continue with the ORGNZ series:
- **ORGNZ-02**: Understanding Grail Buckets

References

- Organize data
- Permissions in Grail
- Grail data model

This notebook was AI-generated from Dynatrace documentation and enterprise best practices. It is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.