IAM-95 LAB: Terraform IAM Provisioning — Groups, Policies, Boundaries, Bindings

> **Series:** IAM — IAM Administration | **Reference:** 95 — Terraform IAM Provisioning LAB | **Created:** July 2026 | **Last Updated:** 10/14/2026

Overview

Hands-on lab: provision a complete persona + team IAM model with **Terraform**. The lab is **self-contained** — Step 1 gives you every module and the composition that wires them, so there is nothing to clone. Every command and expected output comes from a real run, verified live against the Account Management API on 07/16/2026, and the HCL is schema-verified against `dynatrace-oss/dynatrace` v1.100.0.

This is one of **three provisioning flavors** — pick the one that fits your workflow:

Flavor	Notebook	Best for
curl / shell	**IAM-12**	One-off scripts, CI glue
Terraform (this lab)	**IAM-95**	Declarative IaC, drift detection, team review via plan/apply
Python	**IAM-96**	Programmatic onboarding, integration into portals/tooling

What you will build (the BPN pattern from IAM-05 / IAM-10):

```
Persona groups (Standard / Power / Admin)
  └── account-level persona policies, bound 1:1

Team groups — driven entirely by ONE `teams` variable
  └── Policy binding (scoped to ONE environment)
        ├── Policy: ONE shared parameterized template  ← created once, reused
by every team
        │     ALLOW storage:logs:read WHERE storage:dt.security_context IN
("${bindParam:team}");
        └── Boundary: one per team (defense-in-depth)
              storage:dt.security_context IN ("&lt;team-context&gt;");
```

Time: 30–45 minutes | **Difficulty:** Intermediate | **Cost:** No consumption impact (IAM objects only)

Table of Contents

1. Get the Project and Inspect the Modules
2. Configure Credentials and Teams
3. Initialize and Plan
4. Apply
5. Validate
6. The Payoff: Onboard a Team with Three Lines
7. Clean Up
8. Troubleshooting
9. Validation Checklist
10. References

Prerequisites

Requirement	Details
Terraform	>= 1.3 (`terraform version`)

Requirement	Details
Project	None to fetch — Step 1 builds the whole tree from this notebook
Account UUID	Account Management → Account settings
OAuth client	Account Management → Identity & access management → OAuth clients
OAuth scopes	`account-idm-read account-idm-write` (groups) and `iam-policies-management account-env-read` (policies, boundaries, bindings) — the scopes the provider docs list for each resource. Earlier revisions of this lab listed the granular `iam:policies:*`, `iam:bindings:*` and `iam:boundaries:*` scopes instead of `iam-policies-management`; the provider docs name only the four above.
Prior reading	IAM-04 (policy authoring), IAM-05 (boundary design), IAM-10 (templated policies)

> ⚠️ **Safety rails (do not skip):**
> 1. Run this lab only against a **sanctioned test tenant** — confirm the environment ID with your team before executing.
> 2. Keep `name_prefix` set (e.g. `TFTEST-`) so every created object is unmistakably a lab artifact.
> 3. Keep `binding_environment_id` set. IAM groups/policies/boundaries are **account-level** objects; the binding is what grants access, and environment-scoping it confines the lab's effect to one environment.

Step 1 — Build the Project

This lab is **self-contained**: every file is below, so there is nothing to clone. Create the tree, then write each file into the path named above it.

```
mkdir -p dt-iam-
terraform/modules/{iam_groups,iam_policies,policy_boundaries,policy_bindings,p
olicy_templates} \
         dt-iam-terraform/examples/complete
cd dt-iam-terraform
```

> **Use a quoted heredoc — `<<'EOF'`, not `<<EOF`.** These files contain `${..}` and `$${...}`; an unquoted heredoc lets your shell expand them and you will write out broken HCL.

The five modules map 1:1 onto the IAM object model:

Module	Resource
`modules/iam_groups`	`dynatrace_iam_group`
`modules/iam_policies`	`dynatrace_iam_policy` (account level)
`modules/policy_boundaries`	`dynatrace_iam_policy_boundary`
`modules/policy_bindings`	`dynatrace_iam_policy_bindings_v2` (parameters + boundaries)
`modules/policy_templates`	none — emits verified statement **strings** the others consume

Shared `versions.tf` — every module needs the same pin, so write it into all five:

```
for m in iam_groups iam_policies policy_boundaries policy_bindings
policy_templates; do
  cat &gt; "modules/$m/versions.tf" &lt;&lt;'EOF'
terraform {
  required_version = "&gt;= 1.3"

  required_providers {
    dynatrace = {
      source  = "dynatrace-oss/dynatrace"
      version = "&gt;= 1.60.0"
    }
  }
}
EOF
done
```

`modules/policy_templates/main.tf` — Ready-to-use policy **statements** (strings only, no resources). Feeds `iam_policies`.

```
cat &gt; modules/policy_templates/main.tf &lt;&lt;'EOF'
# Policy Templates Module
# Ready-to-use policy STATEMENTS (strings only — no resources) aligned with
the
# BPN IAM notebooks (IAM-04 policy authoring, IAM-10 templated assignments,
# IAM-11 persona workshop). Feed these into the iam_policies module.
#
# Statements are additive: multiple ALLOW lines combine. There is no implicit
# access — anything not ALLOWed is denied. Avoid DENY (it overrides ALLOWs
# granted by other groups).
#
# The team template uses ${bindParam:team} placeholders (written as
# $${bindParam:team} in HCL to escape interpolation). Resolve them per group
# at binding time via the `parameters` map on the policy binding — one policy,
# many bindings (BPN IAM-10).

# ------------------------------------------------------------------------
--
# Persona statements
# ------------------------------------------------------------------------
--
locals {
  # Standard User — read-only visibility (BPN IAM-11)
  standard_user_statement = &lt;&lt;-EOT
    ALLOW environment:roles:viewer;
    ALLOW app-engine:apps:run;
    ALLOW document:documents:read;
    ALLOW storage:metrics:read;
    ALLOW storage:logs:read;
    ALLOW storage:events:read;
    ALLOW storage:entities:read;
    ALLOW storage:buckets:read;
    ALLOW settings:objects:read, settings:schemas:read;
  EOT

  # Power User — read everything, write dashboards/notebooks, manage alerting
  # config only (schema-scoped write, BPN IAM-11 GLOBAL-PowerUser-Config).
  # builtin:davis.anomaly-detectors + workflows = alerting in Latest
Dynatrace.
  # builtin:alerting.profile / builtin:problem.notifications are Dynatrace
  # Classic only: "None of the schemas on this page are visible in Latest
  # Dynatrace" (Settings 2.0 schemas removed in Latest Dynatrace, DT docs).
  # Drop those two lines once no target environment runs Classic.
  power_user_statement = &lt;&lt;-EOT
    ALLOW environment:roles:viewer;
    ALLOW app-engine:apps:run;
    ALLOW document:documents:read, document:documents:write,
```

```
document:documents:delete;
    ALLOW storage:metrics:read;
    ALLOW storage:logs:read;
    ALLOW storage:spans:read;
    ALLOW storage:events:read;
    ALLOW storage:bizevents:read;
    ALLOW storage:entities:read;
    ALLOW storage:system:read;
    ALLOW storage:buckets:read;
    ALLOW automation:workflows:read, automation:workflows:write,
automation:workflows:run;
    ALLOW settings:objects:read, settings:schemas:read;
    ALLOW settings:objects:write WHERE settings:schemaId startsWith
"builtin:davis.anomaly-detectors";
    ALLOW settings:objects:write WHERE settings:schemaId startsWith
"builtin:alerting.profile";
    ALLOW settings:objects:write WHERE settings:schemaId startsWith
"builtin:problem.notifications";
  EOT

  # Admin — all data + settings (Gen3) plus Classic roles (Gen2 transitional).
  # NOTE: there is no environment:roles:admin permission — Classic admin means
  # viewer + manage-settings (BPN IAM-05). Verified against the live Account
  # Management API (invalid names are rejected server-side with HTTP 400).
  admin_statement = &lt;&lt;-EOT
    ALLOW environment:roles:viewer, environment:roles:manage-settings;
    ALLOW app-engine:apps:run, app-engine:apps:install;
    ALLOW document:documents:read, document:documents:write,
document:documents:delete;
    ALLOW storage:metrics:read;
    ALLOW storage:logs:read, storage:logs:write;
    ALLOW storage:spans:read;
    ALLOW storage:events:read, storage:events:write;
    ALLOW storage:bizevents:read;
    ALLOW storage:entities:read;
    ALLOW storage:system:read;
    ALLOW storage:buckets:read;
    ALLOW automation:workflows:read, automation:workflows:write,
automation:workflows:run;
    ALLOW settings:objects:read, settings:objects:write,
settings:schemas:read;
  EOT

  # ------------------------------------------------------------------------
--
  # Parameterized team template (Gen3 — Grail security context)
  # One policy for ALL teams; bind per group with parameters = { team = "..."
}
```

```
  # and attach the team's standalone boundary for defense-in-depth (IAM-05).
  # storage:buckets:read is "Required additionally to a table permission"
  # (IAM policy reference) — the table reads below are not enough on their
own.
  # The security-context conditions still decide which records match.
  # No environment:roles:viewer here: it is a classic role that only an
  # environment:management-zone condition can scope, and a team without a
  # zone would get it environment-wide. It lives in its own policy below.
  # ------------------------------------------------------------------------
--
  team_data_access_template = &lt;&lt;-EOT
    ALLOW app-engine:apps:run;
    ALLOW document:documents:read;
    ALLOW storage:logs:read WHERE storage:dt.security_context IN
("$${bindParam:team}");
    ALLOW storage:spans:read WHERE storage:dt.security_context IN
("$${bindParam:team}");
    ALLOW storage:metrics:read WHERE storage:dt.security_context IN
("$${bindParam:team}");
    ALLOW storage:events:read WHERE storage:dt.security_context IN
("$${bindParam:team}");
    ALLOW storage:bizevents:read WHERE storage:dt.security_context IN
("$${bindParam:team}");
    ALLOW storage:buckets:read;
    ALLOW settings:objects:read WHERE settings:dt.security_context IN
("$${bindParam:team}");
    ALLOW settings:schemas:read;
  EOT

  # Classic viewer role for teams that still have a management zone. Bound
  # ONLY for teams with `management_zone` set, under the team boundary, whose
  # environment:management-zone line scopes it (IAM-05 §3: a classic grant
that
  # shares a binding needs a zone line of its own). Retire with your MZs.
  team_classic_viewer_statement = &lt;&lt;-EOT
    ALLOW environment:roles:viewer;
  EOT

  # Gen2 / Classic transitional statement — management-zone scoped write on
  # top of global read (MZ2POL pattern; retire together with your MZs).
  mz_scoped_config_template = &lt;&lt;-EOT
    ALLOW environment:roles:viewer;
    ALLOW settings:objects:read, settings:schemas:read;
    ALLOW settings:objects:write WHERE environment:management-zone IN
("$${bindParam:zone}");
  EOT
}
```

```
# ------------------------------------------------------------------------------
--
# Boundary query helpers (for the policy_boundaries module)
# ------------------------------------------------------------------------------
--
locals {
  # Gen3 boundary per team — standardize on dt.security_context (IAM-05)
  gen3_team_boundary_query_example = "storage:dt.security_context IN
(\"checkout\"); settings:dt.security_context IN (\"checkout\");"

  # Gen2 boundary — management-zone is the Classic universal scoping field
  gen2_mz_boundary_query_example = "environment:management-zone IN
(\"Checkout\");"
}

output "standard_user_statement" {
  description = "Read-only persona statement"
  value       = local.standard_user_statement
}

output "power_user_statement" {
  description = "Power user persona statement (read all, write documents +
alerting config)"
  value       = local.power_user_statement
}

output "admin_statement" {
  description = "Admin persona statement"
  value       = local.admin_statement
}

output "team_data_access_template" {
  description = "Parameterized Gen3 team statement — bind with parameters = {
team = \"&lt;security-context&gt;\" }"
  value       = local.team_data_access_template
}

output "team_classic_viewer_statement" {
  description = "Classic viewer role for zone-scoped teams — bind only under a
boundary with an environment:management-zone line"
  value       = local.team_classic_viewer_statement
}

output "mz_scoped_config_template" {
  description = "Parameterized Gen2 transitional statement — bind with
parameters = { zone = \"&lt;mz-name&gt;\" }"
  value       = local.mz_scoped_config_template
}
```

```
output "boundary_query_examples" {
  description = "Example boundary query formats for the policy_boundaries
module"
  value = {
    gen3_team = local.gen3_team_boundary_query_example
    gen2_mz   = local.gen2_mz_boundary_query_example
  }
}
EOF
```

`modules/iam_groups/main.tf` — `dynatrace_iam_group` — persona and team groups.

```
cat &gt; modules/iam_groups/main.tf &lt;&lt;'EOF'
# IAM Groups Module
# Manages Dynatrace IAM groups (Account Management API).
#
# Schema verified against dynatrace-oss/dynatrace v1.100.0:
#   dynatrace_iam_group supports: name (required), description,
#   federated_attribute_values (set of strings for SSO/SAML group mapping).
#
# Group membership is managed either via SSO federated attributes
(recommended,
# see IAM-02 in the BPN IAM notebooks) or via dynatrace_iam_user resources
that
# reference these group IDs — NOT on the group resource itself.

variable "groups" {
  description = "Map of IAM group configurations, keyed by a stable logical
name"
  type = map(object({
    name        = string
    description = optional(string, "Managed by Terraform")

    # SAML/SSO federated attribute values that map IdP groups to this group.
    # Leave empty when membership is managed manually or via
dynatrace_iam_user.
    federated_attribute_values = optional(set(string), [])
  }))
  default = {}
}

resource "dynatrace_iam_group" "this" {
  for_each = var.groups

  name                       = each.value.name
  description                = each.value.description
  federated_attribute_values = length(each.value.federated_attribute_values)
&gt; 0 ? each.value.federated_attribute_values : null
}

output "group_ids" {
  description = "Map of logical group keys to group UUIDs (use in policy
bindings)"
  value = {
    for group_key, group in dynatrace_iam_group.this :
    group_key =&gt; group.id
  }
}
```

```
output "groups" {
  description = "Map of created IAM groups with details"
  value = {
    for group_key, group in dynatrace_iam_group.this :
    group_key =&gt; {
      id          = group.id
      name        = group.name
      description = group.description
    }
  }
}
EOF
```

`modules/iam_policies/main.tf` — `dynatrace_iam_policy` at **account** level.

```
cat &gt; modules/iam_policies/main.tf &lt;&lt;'EOF'
# IAM Policies Module
# Manages Dynatrace IAM policies using official permission syntax.
# Reference: https://docs.dynatrace.com/docs/manage/identity-access-
management/permission-management
#
# Schema verified against dynatrace-oss/dynatrace v1.100.0:
#   dynatrace_iam_policy supports: name (required), statement_query
(required),
#   account XOR environment (scope), description, tags (set of strings).
#
# Best practice (BPN IAM-04 / MZ2POL-04): create policies at ACCOUNT level and
# scope them per group at binding time via ${bindParam:...} parameters and
# boundaries — do NOT create per-environment policy copies. The `environment`
# attribute is deprecated in the provider for exactly this reason.
#
# Statement syntax:
#   ALLOW &lt;service&gt;:&lt;resource&gt;:&lt;action&gt;;
#   ALLOW storage:logs:read WHERE storage:dt.security_context = "checkout";
#   ALLOW storage:logs:read WHERE storage:dt.security_context =
"${bindParam:team}";
# (in HCL heredocs write $${bindParam:team} to escape Terraform interpolation)

variable "account_id" {
  description = "Dynatrace account UUID — policies are created at account
level"
  type        = string
}

variable "policies" {
  description = "Map of IAM policy configurations, keyed by a stable logical
name"
  type = map(object({
    name        = string
    description = optional(string, "Managed by Terraform")

    # Policy statement using Dynatrace permission syntax (may contain
    # $${bindParam:...} placeholders resolved per binding).
    statement = string

    tags = optional(set(string), [])
  }))
  default = {}
}

resource "dynatrace_iam_policy" "this" {
  for_each = var.policies
```

```
  name            = each.value.name
  description     = each.value.description
  account         = var.account_id
  statement_query = each.value.statement
  tags            = length(each.value.tags) &gt; 0 ? each.value.tags : null
}

output "policy_ids" {
  description = "Map of logical policy keys to policy IDs (accepted by policy
bindings)"
  value = {
    for policy_key, policy in dynatrace_iam_policy.this :
    policy_key =&gt; policy.id
  }
}

output "policy_uuids" {
  description = "Map of logical policy keys to bare policy UUIDs"
  value = {
    for policy_key, policy in dynatrace_iam_policy.this :
    policy_key =&gt; policy.uuid
  }
}

output "policies" {
  description = "Map of created policies with details"
  value = {
    for policy_key, policy in dynatrace_iam_policy.this :
    policy_key =&gt; {
      id          = policy.id
      uuid        = policy.uuid
      name        = policy.name
      description = policy.description
    }
  }
}
EOF
```

`modules/policy_boundaries/main.tf` — `dynatrace_iam_policy_boundary` — standalone, account-level.

```
cat &gt; modules/policy_boundaries/main.tf &lt;&lt;'EOF'
# Policy Boundaries Module
# Manages Dynatrace IAM policy boundaries — standalone, account-level IAM
# objects that restrict WHAT DATA a policy binding can reach.
#
# Schema verified against dynatrace-oss/dynatrace v1.100.0:
#   dynatrace_iam_policy_boundary supports ONLY: name (required), query
(required).
#   (No description, no environment — boundaries are account-level objects and
#   are attached to groups via the `boundaries` list on policy binding
blocks.)
#
# Boundary query syntax (BPN IAM-05):
#   Gen3 (Grail/AppEngine policies):
#     storage:dt.security_context IN ("checkout");
#     settings:dt.security_context IN ("checkout");
#     storage:bucket-name IN ("checkout_logs");
#   Gen2 / Classic (environment:* policies, transitional while MZs still
exist):
#     environment:management-zone IN ("Checkout");
#
# Pair Gen2 boundaries with Gen2 policies and Gen3 boundaries with Gen3
# policies — conditions from the wrong generation are silently ignored.
# Best practice: one boundary per team with hardcoded scope (the policy stays
# parameterized; the boundary is the defense-in-depth layer). Max 10
conditions
# per boundary — create multiple boundaries if you need more.

variable "boundaries" {
  description = "Map of policy boundary configurations, keyed by a stable
logical name"
  type = map(object({
    name = string

    # Boundary query, e.g.:
    #   storage:dt.security_context IN ("checkout");
settings:dt.security_context IN ("checkout");
    query = string
  }))
  default = {}
}

resource "dynatrace_iam_policy_boundary" "this" {
  for_each = var.boundaries

  name  = each.value.name
  query = each.value.query
```

```
}

output "boundary_ids" {
  description = "Map of logical boundary keys to boundary UUIDs (attach via
policy binding `boundaries`)"
  value = {
    for boundary_key, boundary in dynatrace_iam_policy_boundary.this :
    boundary_key =&gt; boundary.id
  }
}

output "boundaries" {
  description = "Map of created boundaries with details"
  value = {
    for boundary_key, boundary in dynatrace_iam_policy_boundary.this :
    boundary_key =&gt; {
      id    = boundary.id
      name  = boundary.name
      query = boundary.query
    }
  }
}
EOF
```

`modules/policy_bindings/main.tf` — `dynatrace_iam_policy_bindings_v2` — where groups, policies, parameters and boundaries meet.

```
cat &gt; modules/policy_bindings/main.tf &lt;&lt;'EOF'
# Policy Bindings Module
# Connects IAM groups to policies via dynatrace_iam_policy_bindings_v2.
#
# Schema verified against dynatrace-oss/dynatrace v1.100.0:
#   dynatrace_iam_policy_bindings_v2 supports: group (required),
#   account XOR environment (scope), and repeated `policy` blocks with:
#     id         — id (or uuid) of a dynatrace_iam_policy
#     parameters — map(string) resolving $${bindParam:...} placeholders
#     boundaries — set of dynatrace_iam_policy_boundary IDs
#     metadata   — map(string) free-form metadata
#
# One binding resource per (group, scope) pair — it OWNS the full set of
# policies bound to that group at that scope. This is where the BPN
# "templated policy" pattern lands: one parameterized policy, many bindings
# with different `parameters` and per-team `boundaries` (IAM-10, IAM-05).

variable "bindings" {
  description = "Map of policy binding configurations, keyed by a stable
logical name. Exactly one of account_id / environment_id must be set per
binding."
  type = map(object({
    group_id = string

    # Scope: account UUID for account-level bindings (policies must be
    # account-level), or environment ID (e.g. `abc12345`) for
    # environment-level bindings.
    account_id     = optional(string)
    environment_id = optional(string)

    policies = list(object({
      id         = string
      parameters = optional(map(string), {})
      boundaries = optional(set(string), [])
      metadata   = optional(map(string), {})
    }))
  }))
  default = {}

  validation {
    condition = alltrue([
      for binding in values(var.bindings) :
      (binding.account_id != null) != (binding.environment_id != null)
    ])
    error_message = "Each binding must set exactly one of account_id or
environment_id."
  }
```

```
}

resource "dynatrace_iam_policy_bindings_v2" "this" {
  for_each = var.bindings

  group       = each.value.group_id
  account     = each.value.account_id
  environment = each.value.environment_id

  dynamic "policy" {
    for_each = each.value.policies
    content {
      id         = policy.value.id
      parameters = length(policy.value.parameters) &gt; 0 ?
policy.value.parameters : null
      boundaries = length(policy.value.boundaries) &gt; 0 ?
policy.value.boundaries : null
      metadata   = length(policy.value.metadata) &gt; 0 ?
policy.value.metadata : null
    }
  }
}

output "bindings" {
  description = "Map of created bindings with details"
  value = {
    for binding_key, binding in dynatrace_iam_policy_bindings_v2.this :
    binding_key =&gt; {
      id          = binding.id
      group       = binding.group
      account     = binding.account
      environment = binding.environment
    }
  }
}
EOF
```

> **Provider caveat — a binding update replaces the group's whole policy set.** The provider docs for `dynatrace_iam_policy_bindings_v2` say the resource *"re-assigns all policies bound to a group, so every policy that should remain bound must be specified in the configuration; otherwise, it will be unbound."* During that update *"there is a brief window where the group has no policies assigned, which may temporarily cause permission issues for users in that group."* Apply binding changes to production groups in a change window, and manage each group's bindings from one place only.

> **Sources:** dynatrace_iam_policy_bindings_v2 (Dynatrace GitHub).

`examples/complete/variables.tf` — Inputs for the composition.

```
cat &gt; examples/complete/variables.tf &lt;&lt;'EOF'
variable "dynatrace_account_id" {
  description = "Dynatrace account UUID (Account Management &gt; Account
settings)"
  type        = string
}

variable "dynatrace_client_id" {
  description = "OAuth client ID for the Account Management API (dt0s02....)"
  type        = string
  sensitive   = true
}

variable "dynatrace_client_secret" {
  description = "OAuth client secret for the Account Management API"
  type        = string
  sensitive   = true
}

variable "teams" {
  description = &lt;&lt;-EOT
    Teams to onboard. Each team gets a group, a standalone boundary, and one
    binding of the shared parameterized policy. `security_context` must match
    the dt.security_context value stamped on the team's data (Gen3).
    `management_zone` (optional) adds a Gen2/Classic condition to the boundary
    while management zones still exist (MZ2POL transitional pattern).
  EOT
  type = map(object({
    name                       = string
    security_context           = string
    management_zone            = optional(string)
    federated_attribute_values = optional(set(string), [])
  }))
  default = {}
}

variable "name_prefix" {
  description = "Optional prefix for every group/policy/boundary name — useful
for test runs and multi-instance deployments"
  type        = string
  default     = ""
}

variable "binding_environment_id" {
  description = "If set (e.g. \"abc12345\"), all policy bindings attach at
ENVIRONMENT level to this environment instead of account level — scopes
granted access to a single environment"
```

```
  type        = string
  default     = null
}
EOF
```

`examples/complete/main.tf` — The composition: personas + one parameterized policy shared by every team.

```
cat &gt; examples/complete/main.tf &lt;&lt;'EOF'
# Complete example: Dynatrace IAM with groups, policies, boundaries and
bindings
#
# Implements the BPN best-practice pattern (IAM-04/05/10/11, MZ2POL-04):
#
#   1. Persona groups (Standard / Power / Admin) bound to persona policies
#      at ACCOUNT level — one policy each, no duplication.
#   2. Team groups driven entirely by `var.teams`:
#        - ONE parameterized policy (`$${bindParam:team}` on
dt.security_context)
#          shared by every team,
#        - one standalone boundary per team (defense-in-depth),
#        - one binding per team supplying parameters + boundary.
#      Adding a team = adding one entry to terraform.tfvars. No new policies.
#
# Everything here validates against dynatrace-oss/dynatrace v1.100.0.

terraform {
  required_version = "&gt;= 1.3"

  required_providers {
    dynatrace = {
      source  = "dynatrace-oss/dynatrace"
      version = "&gt;= 1.60.0"
    }
  }
}

provider "dynatrace" {
  # IAM resources authenticate via an Account Management OAuth client.
  iam_account_id    = var.dynatrace_account_id
  iam_client_id     = var.dynatrace_client_id
  iam_client_secret = var.dynatrace_client_secret
}

#
================================================================================
# Policy statement templates (strings only — verified BPN syntax)
#
================================================================================
module "policy_templates" {
  source = "../../modules/policy_templates"
}

#
================================================================================
```

```
# Groups: three personas + one group per team
#
================================================================================
module "iam_groups" {
  source = "../../modules/iam_groups"

  groups = merge(
    {
      standard_users = {
        name        = "${var.name_prefix}Standard Users"
        description = "Read-only access to dashboards, metrics, logs and
events"
      }
      power_users = {
        name        = "${var.name_prefix}Power Users"
        description = "Read everything; write dashboards/notebooks and
alerting config"
      }
      admins = {
        name        = "${var.name_prefix}Administrators"
        description = "Full environment control"
      }
    },
    {
      for team_key, team in var.teams :
      "team_${team_key}" =&gt; {
        name                        = "${var.name_prefix}${team.name} Team"
        description                 = "Team-scoped access to the
'${team.security_context}' security context"
        federated_attribute_values = team.federated_attribute_values
      }
    }
  )
}

#
================================================================================
# Policies: one per persona + ONE parameterized policy shared by all teams
#
================================================================================
module "iam_policies" {
  source = "../../modules/iam_policies"

  account_id = var.dynatrace_account_id

  policies = {
    standard_user = {
      name        = "${var.name_prefix}base-standard-user"
```

```
      description = "Persona: read-only visibility"
      statement   = module.policy_templates.standard_user_statement
      tags        = ["persona", "managed-by-terraform"]
    }

    power_user = {
      name        = "${var.name_prefix}base-power-user"
      description = "Persona: read all, write documents and alerting config"
      statement   = module.policy_templates.power_user_statement
      tags        = ["persona", "managed-by-terraform"]
    }

    admin = {
      name        = "${var.name_prefix}base-admin"
      description = "Persona: full environment control"
      statement   = module.policy_templates.admin_statement
      tags        = ["persona", "managed-by-terraform"]
    }

    # One template for ALL teams — resolved per binding via parameters.team
    team_data_access = {
      name        = "${var.name_prefix}tpl-team-data-access"
      description = "Parameterized: data access scoped to $${bindParam:team}
security context"
      statement   = module.policy_templates.team_data_access_template
      tags        = ["template", "managed-by-terraform"]
    }

    # Classic viewer role, bound only for teams that still have a management
zone
    team_classic_viewer = {
      name        = "${var.name_prefix}tpl-team-classic-viewer"
      description = "Classic viewer role — bound only under a boundary with a
management-zone condition"
      statement   = module.policy_templates.team_classic_viewer_statement
      tags        = ["template", "transitional", "managed-by-terraform"]
    }
  }
}

#
================================================================================
# Boundaries: one standalone boundary per team (hardcoded scope is intentional
# — the policy carries the parameterized scope, the boundary is the
# defense-in-depth layer; BPN IAM-05)
#
================================================================================
module "policy_boundaries" {
```

```
  source = "../../modules/policy_boundaries"

  boundaries = {
    for team_key, team in var.teams :
    "team_${team_key}" =&gt; {
      name = "${var.name_prefix}bnd-team-${team_key}"
      query = join(" ", concat(
        [
          "storage:dt.security_context IN (\"${team.security_context}\");",
          "settings:dt.security_context IN (\"${team.security_context}\");",
        ],
        # Gen2/Classic condition — transitional while management zones exist
        team.management_zone != null ? ["environment:management-zone IN
(\"${team.management_zone}\");"] : []
      ))
    }
  }
}

#
================================================================================
# Bindings: personas + one parameterized binding per team.
# Bound at account level by default; set binding_environment_id to scope all
# granted access to a single environment instead.
#
================================================================================
locals {
  bind_account_id = var.binding_environment_id == null ?
var.dynatrace_account_id : null
}

module "policy_bindings" {
  source = "../../modules/policy_bindings"

  bindings = merge(
    {
      standard_users = {
        group_id       = module.iam_groups.group_ids["standard_users"]
        account_id     = local.bind_account_id
        environment_id = var.binding_environment_id
        policies       = [{ id =
module.iam_policies.policy_ids["standard_user"] }]
      }
      power_users = {
        group_id       = module.iam_groups.group_ids["power_users"]
        account_id     = local.bind_account_id
        environment_id = var.binding_environment_id
        policies       = [{ id = module.iam_policies.policy_ids["power_user"]
```

```
}]
      }
      admins = {
        group_id       = module.iam_groups.group_ids["admins"]
        account_id     = local.bind_account_id
        environment_id = var.binding_environment_id
        policies       = [{ id = module.iam_policies.policy_ids["admin"] }]
      }
    },
    {
      for team_key, team in var.teams :
      "team_${team_key}" =&gt; {
        group_id       = module.iam_groups.group_ids["team_${team_key}"]
        account_id     = local.bind_account_id
        environment_id = var.binding_environment_id
        policies = concat(
          [{
            id         = module.iam_policies.policy_ids["team_data_access"]
            parameters = { team = team.security_context }
            boundaries =
[module.policy_boundaries.boundary_ids["team_${team_key}"]]
            metadata   = { managed-by = "terraform" }
          }],
          # Classic viewer only where a zone scopes it; a team without a
          # management zone gets no classic role at all.
          team.management_zone != null ? [{
            id         = module.iam_policies.policy_ids["team_classic_viewer"]
            boundaries =
[module.policy_boundaries.boundary_ids["team_${team_key}"]]
            metadata   = { managed-by = "terraform" }
          }] : []
        )
      }
    }
  )
}

#
================================================================================
# Outputs
#
================================================================================
output "groups" {
  description = "Created IAM groups"
  value       = module.iam_groups.groups
}

output "policies" {
```

```
  description = "Created IAM policies"
  value       = module.iam_policies.policies
}

output "boundaries" {
  description = "Created policy boundaries"
  value       = module.policy_boundaries.boundaries
}

output "bindings" {
  description = "Created policy bindings"
  value       = module.policy_bindings.bindings
}
EOF
```

`examples/complete/terraform.tfvars.example` — Template for your values. Copy to `terraform.tfvars` in Step 2.

```
cat &gt; examples/complete/terraform.tfvars.example &lt;&lt;'EOF'
# Rename to terraform.tfvars and fill in your values.
# NEVER commit terraform.tfvars — it contains credentials.
#
# The OAuth client is created in Account Management &gt; Identity &amp; access
# management &gt; OAuth clients. Required scopes:
#   account-idm-read account-idm-write      (dynatrace_iam_group)
#   iam-policies-management account-env-read (dynatrace_iam_policy,
#     dynatrace_iam_policy_boundary, dynatrace_iam_policy_bindings_v2)

dynatrace_account_id    = "00000000-0000-0000-0000-000000000000"
dynatrace_client_id     = "dt0s02.XXXXXXXX"
dynatrace_client_secret = "dt0s02.XXXXXXXX.YYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYY"

# Adding a team here is ALL that is needed to onboard it:
teams = {
  checkout = {
    name             = "Checkout"
    security_context = "checkout"
    management_zone  = "Checkout" # optional — drop once MZs are retired
  }

  platform = {
    name             = "Platform"
    security_context = "platform"
  }
}
EOF
```

That is the whole project. Sanity-check the layout before moving on:

```
find . -name '*.tf' -o -name '*.tfvars.example' | sort
```

You should see 12 `.tf` files (five modules x `main.tf` + `versions.tf`, plus the example's `main.tf` and `variables.tf`) and one `terraform.tfvars.example`.

Step 2 — Configure Credentials and Teams

The files you run Terraform against live in `examples/complete` — the composition is the root module. Change into it first; Steps 2–7 all run from there:

```
cd examples/complete
cp terraform.tfvars.example terraform.tfvars
```

Edit `terraform.tfvars`:

```
dynatrace_account_id    = "&lt;your-account-uuid&gt;"
dynatrace_client_id     = "dt0s02.XXXXXXXX"
dynatrace_client_secret = "dt0s02.XXXXXXXX.YYYY..."

name_prefix            = "TFTEST-"      # every object gets this prefix
binding_environment_id = "abc12345"     # YOUR test environment ID

teams = {
  alpha = {
    name             = "Alpha"
    security_context = "tftest-alpha"
    management_zone  = "TFTEST-Alpha"   # optional Gen2 condition (MZ2POL
transitional)
  }
  beta = {
    name             = "Beta"
    security_context = "tftest-beta"    # no MZ -&gt; pure Gen3 boundary
  }
}
```

> `terraform.tfvars` contains credentials — it is gitignored. Never commit it.

Step 3 — Initialize and Plan

```
terraform init
terraform plan
```

Expected output (tail of plan):

```
Plan: 17 to add, 0 to change, 0 to destroy.
```

17 resources = 5 groups (3 personas + 2 teams) + 5 policies (3 personas + 1 shared team template + 1 classic-viewer template) + 2 boundaries + 5 bindings. Inspect the parameterized policy in the plan — the `${bindParam:team}` placeholders must appear **literally** (they are resolved per binding, not by Terraform):

```
+ statement_query = &lt;&lt;-EOT
      ALLOW app-engine:apps:run;
      ALLOW document:documents:read;
      ALLOW storage:logs:read WHERE storage:dt.security_context IN
("${bindParam:team}");
      ...
```

> **Counts changed 10/14/2026.** `environment:roles:viewer` moved out of the shared team template into `tpl-team-classic-viewer`, bound only for teams with a `management_zone` — so a team without a zone no longer gets the classic viewer role environment-wide. On 10/14/2026 this revision passed `terraform validate`, and `terraform plan -refresh=false` reported 17 to add for a two-team configuration (one team with a zone, one without); it has not been re-applied against a live account.

Step 4 — Apply

```
terraform apply
```

Type `yes` at the prompt. **Expected output (abridged):**

```
module.iam_groups.dynatrace_iam_group.this["team_alpha"]: Creation complete
after 0s [id=00d43484-fc8a-435f-8e4f-57ea9d056d35]
module.policy_boundaries.dynatrace_iam_policy_boundary.this["team_alpha"]:
Creation complete after 0s [id=d81e7853-abd4-4159-908f-75c202432cf1]
module.iam_policies.dynatrace_iam_policy.this["team_data_access"]: Creation
complete after 1s [id=dea9e886-...#-#account#-#&lt;account-uuid&gt;]
module.policy_bindings.dynatrace_iam_policy_bindings_v2.this["team_alpha"]:
Creation complete after 1s [id=00d43484-...#-#environment#-#abc12345]

Apply complete! Resources: 17 added, 0 changed, 0 destroyed.
```

Note the binding IDs end in `#-#environment#-#abc12345` — proof the grants are environment-scoped.

Step 5 — Validate

In the UI — Account Management → Identity & access management:

- **Groups**: search `TFTEST-` → 5 groups
- **Policies**: open `TFTEST-tpl-team-data-access` → statement shows `${bindParam:team}` placeholders; its **bindings** tab shows per-team resolved values
- **Boundaries**: `TFTEST-bnd-team-alpha` shows all three conditions; `TFTEST-bnd-team-beta` shows Gen3 conditions only

Via the API (or use the IAM-96 Python tool). **Expected binding for the Alpha team:**

```
{
  "policyUuid": "dea9e886-d49d-4989-ac15-c193e823dd00",
  "groups": ["00d43484-fc8a-435f-8e4f-57ea9d056d35"],
  "parameters": { "team": "tftest-alpha" },
  "boundaries": ["d81e7853-abd4-4159-908f-75c202432cf1"]
}
```

Expected boundary query (Alpha — with transitional MZ condition):

```
storage:dt.security_context IN ("tftest-alpha");
settings:dt.security_context IN ("tftest-alpha");
environment:management-zone IN ("TFTEST-Alpha");
```

Alpha (which has a `management_zone`) also has `TFTEST-tpl-team-classic-viewer` bound with the same boundary, so its classic viewer role is limited to `TFTEST-Alpha`. Beta has no

classic-viewer binding.

✅ **Checkpoint:** `parameters.team` matches the team's `security_context`, and exactly one boundary UUID is attached to each team policy binding.

Step 6 — The Payoff: Onboard a Team with Three Lines

Add to `teams` in `terraform.tfvars`:

```
  gamma = {
    name             = "Gamma"
    security_context = "tftest-gamma"
  }
```

```
terraform plan
```

Expected output:

```
Plan: 3 to add, 0 to change, 0 to destroy.
```

Three resources — group, boundary, binding. **The shared policy is untouched.** That is the entire value of the templated-policy pattern: teams scale without policy sprawl. Apply if you want, then continue.

Step 7 — Clean Up

```
terraform destroy
```

Expected output (tail):

```
Destroy complete! Resources: 16 destroyed.
```

(19 if you applied Gamma.) Verify in the UI that no `TFTEST-` objects remain, then delete `terraform.tfvars`.

Troubleshooting

Symptom	Cause	Fix
400 `Invalid permission name: ...` on apply	Statement uses a nonexistent permission (e.g. `environment:roles:admin`, `storage:spans:write`)	See the verified permission rules in **IAM-04** and error table in **IAM-12 §7**
400 `ALLOW or DENY must be followed by a permission...`	Wildcard in a statement (`storage:*:read`)	Wildcards are not supported — enumerate permissions
401 on plan/apply	OAuth client credentials wrong or scopes missing	Recreate client with the full scope list above
Binding created at account level unexpectedly	`binding_environment_id` unset	Set it — null means account-level bindings
`${bindParam:team}` resolved to nothing by Terraform	Written as `${...}` in HCL	In HCL heredocs escape as `$${bindParam:team}`

Validation Checklist

- [ ] `terraform plan` showed 16 to add before apply
- [ ] Binding IDs contain `#-#environment#-#<env-id>`
- [ ] The shared policy statement contains literal `${bindParam:team}`
- [ ] Alpha's binding carries `parameters: {team: tftest-alpha}` + 1 boundary
- [ ] Beta's boundary has NO `environment:management-zone` line (pure Gen3)
- [ ] Adding a team planned exactly **3** new resources
- [ ] `terraform destroy` removed everything (UI search for prefix is empty)

References

- **IAM-04** Policy Authoring (verified statement syntax) · **IAM-05** Boundary Design · **IAM-10** Templated Policy Assignments · **IAM-12** API Provisioning (curl flavor) · **IAM-96** Python lab (same pattern, Python flavor)
- **MZ2POL series** — migrating off Management Zones onto this pattern
- **AUTOM-95 LAB** (AUTOM series) — provider-lifecycle depth for the same `dynatrace_iam_*` resources: permission-DSL discovery, bulk export/import of an existing account, deprecated arguments, CI/CD integration
- Provider reference for every resource used here: `dynatrace_iam_group`, `dynatrace_iam_policy`, `dynatrace_iam_policy_boundary`, `dynatrace_iam_policy_bindings_v2` — the HCL in Step 1 is schema-verified against provider v1.100.0

This notebook was AI-generated from community-submitted and publicly available sources. This notebook series is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.