IAM-05: Boundary Design Patterns

> **Series:** IAM — IAM Administration | **Notebook:** 5 of 12 | **Created:** January 2026 | **Last Updated:** 10/14/2026

Controlling Data Visibility with Boundaries

Boundaries determine **what data** users can see. While policies control actions, boundaries filter visibility. This notebook covers boundary syntax, patterns, and implementation strategies, including how to scope access to lookup files in Grail.

Table of Contents

1. Boundary Fundamentals
2. The Three-Domain Model
3. Boundary Syntax Reference
4. Security Context and Data Partitioning Strategy
5. Common Boundary Patterns
6. Multi-Tenant Isolation
7. Boundary Testing

Prerequisites

Requirement	Details
Dynatrace Environment	SaaS with Gen3 IAM enabled

Requirement	Details
Permissions	`account-user-management` (boundaries are account-level objects)
Prior Knowledge	**IAM-01** through **IAM-04**

1. Boundary Fundamentals

Boundaries filter what entities and data a user can see within an environment.

Policies vs Boundaries

Concept	Controls	Example
Policy	What actions	"Can read logs"
Boundary	What data	"Logs from checkout service only"

A **policy** is required; a **boundary** is optional and only narrows it:
- A **policy** grants the action (e.g., `storage:logs:read`)
- A **boundary**, attached to a policy binding, restricts it to certain data (e.g., the `checkout` security context)

A policy bound without a boundary applies to all data its permissions cover.

How Boundaries Work

1. User attempts to access data (query, view, etc.)
2. Dynatrace checks if user's policy allows the action
3. Dynatrace filters results to match user's boundary
4. User sees only data within their boundary

Boundary Scope


Boundaries are **account-level** objects, attached per policy binding — and the binding itself can be account- or environment-scoped:

```
Group: dt-checkout-editors
├── Policy: Pro User
└── Boundary: checkout-services-only
```

> **Sources:** Policy boundaries (DT docs) — *"Boundaries alone don't restrict anything, they are always used together with policies in the process of assigning policies to your user groups."*

2. The Three-Domain Model

Boundary conditions fall into three domains, and each line scopes only the permissions of its own service. One boundary should carry a line for **every domain the policies bound with it grant** — a domain with no line is not blocked, it is unscoped.



Domain 1: Environment

The `environment:management-zone` condition scopes the classic `environment:roles:*` permissions — the classic pages for hosts, services, applications, databases and cloud resources. It is transitional: Grail does not read it.

Domain 2: Storage

The `storage:` conditions (`storage:dt.security_context` , `storage:bucket-name` , primary Grail fields) scope Grail reads — including Smartscape (`storage:smartscape:read`) and classic entities (`storage:entities:read`):
- Logs
- Spans (traces)
- Metrics
- Events
- Business events

Domain 3: Settings

Controls visibility of configuration:
- Alerting rules
- SLOs
- Custom settings

Why All Three Matter

A boundary never adds access, and a missing line never removes it. If the bound policies grant a domain the boundary has no line for, that domain is **unscoped**:

Missing line	Effect when the bound policy grants that domain
`environment:management-zone`	Classic pages (`environment:roles:*`) for every zone
`storage:dt.security_context`	Every record the policy's `storage:*:read` permissions cover
`settings:dt.security_context`	Every settings object the policy's `settings:objects:*` permissions cover

> **Sources:** Policy boundaries (DT docs) — *"Only conditions added to service configuration will be applied to relative permissions."*; the page's own example ends in *"would effectively grant unconditional read access to storage entities"* because boundary one's host-name condition does not apply to `storage:entities:read` .

3. Boundary Syntax Reference

Basic Boundary Structure

```
&lt;domain&gt;:&lt;field&gt; &lt;operator&gt; (&lt;values&gt;)
```

One boundary, one line per domain the bound policies grant. A boundary line scopes only the permissions of its own service: Dynatrace's rule is *"Only conditions added to service configuration will be applied to relative permissions."* An `environment:management-zone` line scopes `environment:roles:*` statements and nothing in Grail; a `storage:dt.security_context` line scopes `storage:` reads and nothing classic. Whatever the boundary has no line for stays **unscoped**. So when the bound policies span Grail, settings and — during the transition — classic roles, the boundary carries a line for each, together. Dynatrace's own boundary page shows this mixed shape: its `Kubernetes` boundary holds `environment:management-zone startsWith "[Kubernetes]";` next to `storage:k8s.namespace.name IN ("DEV","PREPROD");`.

```
# Policy
ALLOW storage:buckets:read;
ALLOW storage:logs:read, storage:spans:read, storage:metrics:read;
ALLOW settings:objects:read, settings:objects:write;
ALLOW environment:roles:viewer;
```

```
# Boundary — one boundary covering every domain the policy grants
storage:dt.security_context  IN ("checkout");
settings:dt.security_context IN ("checkout");
environment:management-zone  IN ("checkout");
```

The `environment:management-zone` line (and the `environment:roles:viewer` statement it scopes) is transitional: delete both when classic pages are retired, without rebinding anything. `storage:buckets:read` is *"Required additionally to a table permission"*; it takes `storage:bucket-name` / `storage:table-name` conditions rather than `dt.security_context`, so the table permissions carry the record scoping.

Two bindings instead of one boundary also work — a Grail/settings policy bound under a Grail-only boundary, plus a custom classic policy (`ALLOW environment:roles:viewer;`) bound under a zone-only boundary. Bindings combine as a union, so this is safe **only if each binding's policies stay inside its boundary's domain**. Bind a default policy such as *Standard User* (which includes

`settings:objects:read` and `environment:roles:viewer`) under a single-domain boundary and its other domains come out unscoped.

Never attach two single-domain boundaries to one binding. *"When more than one boundary applies to a policy, then effective statements are calculated for each boundary separately"* — the zone-only boundary leaves the storage statements unconditional, the Grail-only boundary leaves the classic statements unconditional, and the union is unrestricted access in both domains.

> **Sources:** Policy boundaries (DT docs) — *"Only conditions added to service configuration will be applied to relative permissions."*; *"When more than one boundary applies to a policy, then effective statements are calculated for each boundary separately"*; *"In certain configurations this may cause unintended unconditional access."* IAM policy reference (DT docs) — `storage:buckets:read`: *"Required additionally to a table permission."*
>
> **`=` and `IN` only work while `dt.security_context` holds a single value.** Dynatrace's Grail permissions reference: *"Using `=`, `STARTSWITH` or `IN` when the field holds an array will always return `false`."* The failure is silent — the policy is valid, it evaluates, and it matches nothing. If any enrichment path can write an array into `dt.security_context`, use `MATCH` instead: *"you must use the `MATCH` operator to get 'for any value' set semantic."*
>
> Find out which case you are in before choosing an operator: `fetch logs, from:-1h | filter isNotNull(dt.security_context) | fieldsAdd sc_type = type(dt.security_context) | summarize records = count(), by:{sc_type}`. Any `array` row means an `=` or `IN` condition misses those records. **ORGNZ-04** covers the operator semantics in full.
>
> **Sources:** Permissions in Grail (DT docs) — the array semantics quoted above.

`MATCH` is not available everywhere. `environment:management-zone` does accept it (the policy reference lists `IN`, `startsWith`, `NOT startsWith`, `=`, `!=` and `MATCH` on `environment:roles:viewer`), but `storage:entities:read` (classic entities) supports only `=`, `IN` and `startsWith` for `storage:dt.security_context`, and `settings:dt.security_context` supports only `IN`, `=` and `startsWith`.

Operators

Operator	Description	Example
`IN`	Match any in list	`IN ("a", "b", "c")`
`=`	Exact match	`= "checkout"`
`!=`	Not equal — only where the policy reference lists it (e.g. `storage:bucket-name`, `environment:management-zone`); **not** on `storage:dt.security_context` or `settings:dt.security_context`	`storage:bucket-name != "pci_logs"`
`startsWith`	Prefix match	`startsWith "team-"`
`MATCH`	Wildcard pattern match	`storage:dt.security_context MATCH('*/app:easytrade')`

> **`MATCH()` is available on the Grail record tables (`storage:logs:read` etc.), `storage:smartscape:read` and `environment:management-zone`.** It supports `*` as a wildcard at any position — anchor with a trailing `*` to mimic prefix matching. It is **not** available for `settings:dt.security_context` (`IN`, `=`, `startsWith`) or on `storage:entities:read` (below).
>
> **`storage:entities:read` (classic entities) supports `=`, `IN` and `startsWith` only** — Dynatrace documents `startsWith` as evaluating for any matching value of the multi-value entity context. `storage:smartscape:read` and the record tables also accept `MATCH`.
>
> **Sources:** Grant access to entities with security context (DT docs) — *"the security context of this entity. Can be a multi-value field and startsWith will evaluate for any matching value."* IAM policy reference (DT docs) — operator lists per condition, read 10/13/2026.
>
> **Place wildcards next to a word separator.** Dynatrace's guidance is to put the `*` immediately before or after a separator character — `-`, `_`, `.`, or `/`. `MATCH("db-tech-*")` evaluates more efficiently than `MATCH("db-tech*")`. This is why the structured `dt.security_context` format below uses `/` between dimensions and `:`

> within them: every boundary a transversal team needs then lands on a separator rather than mid-token.

Common Fields

Domain	Field	Description
environment	`management-zone`	Management zone filter
storage	`dt.security_context`	Data security context
storage	`bucket-name`	Storage bucket name
settings	`dt.security_context`	Settings security context
settings	`schemaId`	Settings schema

Multiple Values

Grant access to multiple security contexts — one boundary, a line per domain:

```
# Policy
ALLOW storage:buckets:read;
ALLOW storage:logs:read, storage:spans:read;
ALLOW settings:objects:read;
ALLOW environment:roles:viewer;
```

```
# Boundary
storage:dt.security_context  IN ("checkout", "payments", "shared");
settings:dt.security_context IN ("checkout", "payments", "shared");
environment:management-zone  IN ("checkout", "payments", "shared");
```

Wildcard Access

For admin groups needing full access, bind without a boundary:

```
# Admin: all data + settings + classic roles, no boundary
ALLOW storage:buckets:read;
ALLOW storage:logs:read, storage:spans:read, storage:metrics:read;
ALLOW settings:objects:read, settings:objects:write;
ALLOW environment:roles:manage-settings, environment:roles:viewer;
```

> **Don't write a wildcard `MATCH('*')` to mean "everything".** A policy bound without a boundary already applies to all data its permissions cover, and `storage:entities:read` and `settings:dt.security_context` have no `MATCH` at all.

Boundary Limitations

Limitation	Description	Workaround
Max 10 conditions	Only 10 lines per boundary	Fold values into `IN` lists first. Dynatrace allows assigning multiple boundaries to a policy, but each is evaluated separately — so every extra boundary must itself carry a line for every domain the policy grants
No AND inside a boundary	One condition per line; repeated condition names multiply the statement	Need AND? Put it in the policy's WHERE clause (IAM-04). Multiple boundaries on one policy are evaluated separately — they widen, not narrow
No `MATCH` on some conditions	`storage:entities:read` and `settings:dt.security_context` accept only `=`, `IN`, `startsWith`	Use `IN`, or `startsWith` for a prefix

> **Sources:** Policy boundaries (DT docs) — *"Boundaries don't support the AND operator, every line of a boundary can only consist of one condition."*; *"When more than one boundary applies to a policy, then effective statements are calculated for each boundary separately"*.

4. Security Context and Data Partitioning Strategy

Security contexts and Grail buckets form the foundation of boundary filtering and data partitioning. Plan your strategy carefully.

> **Boundary design vs policy parameterization (read first).** This notebook covers **standalone Boundary resources** — separate IAM objects applied to groups for defense-in-depth scoping. Standalone boundaries are typically per-team with hardcoded scope (one boundary per team), distinct from the **policy WHERE clauses** in IAM-04 which ARE parameterizable via `${bindParam:NAME}` and bound per group. The two layer together: a parameterized policy (the "what" — bound per team) plus a per-team standalone boundary (the "where" — hardcoded per team) gives both scaling and defense-in-depth. See **IAM REFERENCE.md § Policy Parameterization and Boundary Standardization** for the canonical pattern; standardize the boundary FIELD on `dt.security_context` (Gen3) or management zone (Classic) regardless of which layer you're scoping.

What is a Security Context?

A **security context** is a label applied to:
- Entities (hosts, services)
- Data (logs, spans)
- Settings (configurations)

Boundaries filter based on these labels.

Primary Grail Fields

Primary Grail fields are first-class attributes that Dynatrace uses for data organization. These should drive your permission, segmentation and routing strategy:

Field	Source	Use Case
`k8s.cluster.name`	Kubernetes	Cluster-level isolation
`k8s.namespace.name`	Kubernetes	Namespace-level access
`aws.account.id`	AWS metadata	AWS account separation
`azure.subscription.id`	Azure metadata	Azure subscription separation
`gcp.project.id`	GCP metadata	GCP project separation
`dt.host_group.id`	OneAgent config	Host group-based isolation

These fields are automatically enriched from infrastructure metadata and provide consistent, reliable partitioning dimensions.

Grail Bucket Strategy

Buckets partition data in Grail for retention, cost allocation and query performance. They are **not** the access-control layer: Dynatrace states buckets are *"not intended as the primary mechanism for securing or segmenting data access."* Scope access with `dt.security_context` (and primary Grail fields); add a bucket when a retention period, cost allocation or a compliance requirement calls for one.

Key Principle: Create a bucket for a retention, cost or compliance reason, and route data into it based on primary Grail fields.

Bucket Design	Example	Benefit
By Retention	`logs_30d`, `logs_365d`	Different retention per data class
By Cost Owner	`checkout_data`, `payments_data`	Cost allocation per team / LOB
By Compliance	`pci_logs`, `general_logs`	Regulatory separation (an explicit bucket-scoped grant on top of the security context)
By Environment	`prod_logs`, `dev_logs`	Different retention for prod and non-prod

> **Sources:** Partition data with Grail buckets (DT docs) — *"Buckets are best used for organizing data by retention time, cost allocation, or query optimization. They are not intended as the primary mechanism for securing or segmenting data access."*

Bucket Limitations

> ⚠️ **Critical:** Plan buckets carefully - these constraints cannot be changed later.

Limitation	Details
One data type per bucket	Logs, metrics, events, OR spans - not mixed
Names are immutable	Bucket names CANNOT be changed after creation
No data migration	Data CANNOT be moved between buckets
Naming rules	3-100 chars, lowercase alphanumeric, underscores, hyphens only
Maximum buckets	80 per environment (default limit)
Optimal ingest	~1 TB/day per bucket for best query performance
Acceptable ingest	1-3 TB/day per bucket (limited query window)
Maximum ingest	No per-bucket ingest cap is documented. The 500 GB scan limit shrinks the queryable window as a bucket grows, and Dynatrace's split guidance differs between pages — see the note below

> **Sizing guidance varies.** Dynatrace pages describe single buckets well above 3 TB/day as possible but slow to query, and they give different points at which to split. Size against your own query windows rather than a fixed ceiling.
>
> **Sources:** Partition data with Grail buckets (DT docs) — *"We recommend splitting up buckets that receive more than 2 TB of daily ingest."*; Logs bucket strategy best practices (DT docs) — *"At 100 TB/day in a single bucket, the same 500 GB scan covers only a few minutes of logs, making historical queries impractical without increasing scan limits."*

Query Constraints

Limit	Value	Impact
Maximum data scanned	500 GB	Limits queryable time window
Maximum records returned	1,000	Use aggregations for larger datasets
Maximum response payload	1 MB	Large result sets may be truncated

Default Bucket Retentions

Bucket	Retention
`default_logs`	35 days
`default_metrics`	15 months
`default_spans`	10 days
`default_events`	35 days

Naming Convention: Include organization, data type, and retention in bucket names:

- `team_a_logs_90d`
- `prod_spans_30d`
- `pci_metrics_365d`

Bucket + Boundary Integration

> **When this combo fits:** the policy + standalone boundary pattern below is well-suited to scenarios where bucket-based scoping is already the right tool — compliance separation (PCI/HIPAA), retention isolation, or hard cost attribution. For general team-scoped data access without one of those reasons, a parameterized policy on `dt.security_context` alone (no bucket-name condition, no standalone boundary) is usually simpler. See **IAM REFERENCE.md § Bucket-Match Overlay** for scenario gating.

When the scenario does fit, the policy carries the **parameterized scope** and the boundary carries the **per-team hardcoded scope** for defense-in-depth. Pair them on the same group.

Policy (parameterized — one template, bound per team):

```
// Recommended: parameterized policy template
// storage:buckets:read is required in addition to each table permission
ALLOW storage:buckets:read WHERE storage:bucket-name = "${bindParam:log-
bucket}";
ALLOW storage:buckets:read WHERE storage:bucket-name = "${bindParam:span-
bucket}";
ALLOW storage:logs:read  WHERE storage:bucket-name = "${bindParam:log-
bucket}";
ALLOW storage:spans:read WHERE storage:bucket-name = "${bindParam:span-
bucket}";
```

Resolved when bound to the checkout group with `{"parameters": {"log-bucket": "checkout_logs", "span-bucket": "checkout_spans"}}`:

```
ALLOW storage:buckets:read WHERE storage:bucket-name = "checkout_logs";
ALLOW storage:buckets:read WHERE storage:bucket-name = "checkout_spans";
ALLOW storage:logs:read  WHERE storage:bucket-name = "checkout_logs";
ALLOW storage:spans:read WHERE storage:bucket-name = "checkout_spans";
```

Standalone Gen3 boundary (per-team — hardcoded scope is intentional here):

```
# Gen3 boundary — pair with a Gen3 policy (storage:*, settings:*)
# One boundary per team; standardize on dt.security_context as the universal
field.
storage:bucket-name IN ("checkout_logs", "checkout_spans");
storage:dt.security_context IN ("checkout");
settings:dt.security_context IN ("checkout");
```

Classic access during the transition: if the bound policies also grant `environment:roles:*`, either bind those classic statements separately under a zone-only boundary, or — if they share this binding — they need a zone line of their own (§3). The upgrade guidance below keeps zones out of the target boundary, so the separate binding is the cleaner choice here.

> **Why the policy is parameterized but the standalone boundary isn't:** policy WHERE clauses support `${bindParam:NAME}` and are bound per group at policy-binding time. Standalone Boundary resources are independent IAM objects — typically one boundary per team with hardcoded scope, attached to the group separately. See **IAM-10** for policy-binding mechanics; see **IAM REFERENCE.md § Anti-patterns** for why parameterizing on entity-type-specific fields (e.g., `host.name`) is the "dead in water" failure mode.

Using Buckets for Team Isolation

> **When this approach fits:** bucket-based team isolation is well-suited to scenarios where the bucket already exists for a specific reason — compliance separation (PCI/HIPAA), retention isolation, hard cost attribution, or hostile multi-tenancy. For general team-scoped access without one of those reasons, a parameterized policy on `dt.security_context` (no buckets, no standalone boundary) is usually simpler. The pattern below applies once you've decided buckets are the right tool. See **IAM REFERENCE.md § Bucket-Match Overlay** for scenario gating.

For team-level data access control (when the bucket scenario fits):

1. **Create team-specific buckets** - `team_a_logs`, `team_a_spans`, etc.
2. **Configure pipeline routing** - Route data to buckets based on primary Grail fields
3. **Create one parameterized policy** — bound to each team's group with different bucket parameters
4. **Create one standalone boundary per team** — hardcoded scope, applied per group

Recommended (parameterized policy + per-team standalone boundary):

```
// One parameterized policy template — bound per team
Policy: tpl-team-data-access (parameterized)
├── ALLOW storage:buckets:read WHERE storage:bucket-name = "${bindParam:log-
bucket}";
├── ALLOW storage:buckets:read WHERE storage:bucket-name = "${bindParam:span-
bucket}";
├── ALLOW storage:buckets:read WHERE storage:bucket-name =
"${bindParam:metric-bucket}";
├── ALLOW storage:logs:read    WHERE storage:bucket-name = "${bindParam:log-
bucket}";
├── ALLOW storage:spans:read   WHERE storage:bucket-name = "${bindParam:span-
bucket}";
└── ALLOW storage:metrics:read WHERE storage:bucket-name =
"${bindParam:metric-bucket}";

// One standalone boundary per team — hardcoded scope (defense-in-depth)
Boundary: bnd-team-checkout
    storage:bucket-name IN ("checkout_logs", "checkout_spans",
"checkout_metrics");
    storage:dt.security_context IN ("checkout");

// Group: bind both — policy with team-specific parameters, boundary as-is
Group: Checkout-Team
├── Policy binding: tpl-team-data-access
│     parameters: {log-bucket: "checkout_logs", span-bucket: "checkout_spans",
│                  metric-bucket: "checkout_metrics"}
└── Boundary attachment: bnd-team-checkout
```

Resolved view (what the policy evaluates to for the Checkout-Team group):

```
Group: Checkout-Team
├── Policy: tpl-team-data-access (resolved for this group)
│   ├── ALLOW storage:buckets:read WHERE storage:bucket-name IN
("checkout_logs", "checkout_spans", "checkout_metrics");
│   ├── ALLOW storage:logs:read    WHERE storage:bucket-name =
"checkout_logs";
│   ├── ALLOW storage:spans:read   WHERE storage:bucket-name =
"checkout_spans";
│   └── ALLOW storage:metrics:read WHERE storage:bucket-name =
"checkout_metrics";
└── Boundary: bnd-team-checkout (unchanged — per-team hardcoded scope)
    storage:bucket-name IN ("checkout_logs", "checkout_spans",
"checkout_metrics");
    storage:dt.security_context IN ("checkout");
```

> **No management zone in `bnd-team-checkout`.** Dynatrace's upgrade guidance is explicit: *"Boundary definitions must not reference classic management zones."* That is the **target** model. If the group still needs classic pages during the transition, bind the classic statements (`ALLOW environment:roles:viewer;`) in a **separate** binding under a zone-only boundary — and keep that binding free of `storage:` and `settings:` permissions, or they come out unscoped (§3).
>
> **Sources:** Upgrade management zones to IAM and segments (DT docs).

Adding a new team is one boundary YAML + one binding YAML — the policy stays unchanged. See **IAM-10: Templated Policy-Group Assignments** for binding mechanics and **IAM REFERENCE.md § Change-Management Caveat** for why parameter-shape decisions matter at design time.

> **For comprehensive bucket guidance**, see **ORGNZ-03: Bucket Strategy and Design** which covers naming conventions, retention planning, and cost attribution patterns.

Primary Grail Tags

Beyond fields, **Primary Grail Tags** can be configured from:
- Kubernetes labels (first 3 selected during setup)
- AWS resource tags
- Azure resource tags

These tags become first-class Grail attributes available for:
- Bucket assignment rules
- Policy/boundary conditions
- Pipeline routing
- Segment filters

Assigning Security Context

Security context is set via (modern approaches):

1. **Entity Enrichment rules** - Automatic based on entity properties
2. **Host properties** - Set on hosts and inherited by services
3. **Primary Grail fields/tags** - First-class tags for Grail data

4. **OneAgent group** - Inherited from deployment
5. **Log attributes** - Set during OpenPipeline ingestion

> **Note:** Auto-tagging is a legacy approach. Prefer Entity Enrichment and Primary Grail Fields for new implementations.

Security Context Design Patterns

Pattern	Example Values	Use Case
Team-based	`checkout-team`, `payments-team`	Team ownership
Application-based	`ecommerce-app`, `mobile-app`	App isolation
Environment-based	`prod`, `staging`, `dev`	Env separation
Business unit	`retail`, `wholesale`, `corporate`	Business isolation
Geography	`us-east`, `eu-west`, `apac`	Regional separation

Naming Conventions

Rule	Good	Bad
Lowercase	`checkout`	`Checkout`
Hyphens	`team-checkout`	`team_checkout`
Descriptive	`payments-api`	`pa`
No spaces	`mobile-app`	`mobile app`

Shared Context

Some data should be visible to multiple teams:

```
Security Contexts:
├── checkout      (checkout team data)
├── payments      (payments team data)
└── shared        (cross-team data - infrastructure, common services)
```

Teams get their context + `shared` — one boundary, a line per domain (the zone line only while classic pages are in use):

```
storage:dt.security_context  IN ("checkout", "shared");
settings:dt.security_context IN ("checkout", "shared");
environment:management-zone  IN ("checkout", "shared");
```

Recommended Partitioning Strategy

1. **Identify primary dimensions** - What drives access control? (team, environment, region, compliance)
2. **Map to Primary Grail Fields** - Use `k8s.cluster.name`, `aws.account.id`, `dt.host_group.id`
3. **Set `dt.security_context`** - Enrich every signal (logs, spans, events, metrics) with the access dimension, and measure coverage on records, not just entities
4. **Define policies and boundaries** - Scope reads with `storage:dt.security_context` and settings with `settings:dt.security_context`, one boundary per team covering every domain
5. **Design buckets** - Only where retention, cost allocation or a compliance requirement calls for one; add `storage:bucket-name` conditions for those
6. **Configure pipelines** - Route data to those buckets based on primary fields
7. **Create segments** - For query filtering (segments are not access control)

> **See Also:** For migration from Management Zones, refer to **MZ2POL-04: Policies and Boundaries** which covers mapping MZ patterns to the new model.

5. Common Boundary Patterns

Pattern 1: Single Team Boundary

Restrict to one team's data with **one** boundary that holds a line for every domain. Do not split it into a Grail boundary and a zone boundary on the same binding — each boundary is evaluated separately, so each leaves the other domain unconditional (§3).

```
# One boundary — a line per domain the bound policies grant
storage:dt.security_context  IN ("checkout");
settings:dt.security_context IN ("checkout");
environment:management-zone  IN ("checkout");   # transitional — delete at MZ
retirement
```

> **Sources:** Policy boundaries (DT docs) — *"When more than one boundary applies to a policy, then effective statements are calculated for each boundary separately"*.

Pattern 2: Team + Shared

Team data plus shared infrastructure:

```
# One boundary — a line per domain the bound policies grant
storage:dt.security_context  IN ("checkout", "shared", "infrastructure");
settings:dt.security_context IN ("checkout", "shared");
environment:management-zone  IN ("checkout", "shared", "infrastructure");   #
transitional — delete at MZ retirement
```

Pattern 3: Multiple Teams (Cross-Functional)

For SRE or platform teams:

```
# One boundary — a line per domain the bound policies grant
storage:dt.security_context  IN ("checkout", "payments", "catalog", "shared");
settings:dt.security_context IN ("checkout", "payments", "catalog", "shared");
environment:management-zone  IN ("checkout", "payments", "catalog", "shared");
# transitional — delete at MZ retirement
```

Pattern 4: Environment Tier

Production vs non-production:

Production:

```
# One boundary — a line per domain the bound policies grant
storage:dt.security_context  IN ("prod-checkout", "prod-payments");
settings:dt.security_context IN ("prod-checkout", "prod-payments");
environment:management-zone  IN ("prod-checkout", "prod-payments");   #
transitional — delete at MZ retirement
```

Non-Production:

```
# One boundary — a line per domain the bound policies grant
storage:dt.security_context  IN ("dev-checkout", "staging-checkout");
settings:dt.security_context IN ("dev-checkout", "staging-checkout");
environment:management-zone  IN ("dev-checkout", "staging-checkout");   #
transitional — delete at MZ retirement
```

Pattern 5: Read-All, Write-Scoped

Using two groups for the same user:

Group 1: All-Viewers (broad read)

```
Policies: Standard User + All Grail data read access (default policies)
Boundary: none — a policy bound without a boundary is already environment-wide
```

Standard User alone is not a read-everything policy: it grants app, document, workflow and settings-read access, but no Grail table reads (`storage:logs:read` and the like). Pair it with *All Grail data read access* — or the per-table *Read Logs*, *Read Spans* … policies — for data visibility.

Group 2: Checkout-Editors (scoped write)

```
Policy: checkout-write-policy
  ALLOW settings:objects:read, settings:objects:write;
  ALLOW environment:roles:manage-settings;          # transitional
Boundary:
  settings:dt.security_context IN ("checkout");
  environment:management-zone  IN ("checkout");      # transitional
```

A zone line alone would scope only the classic `environment:roles:manage-settings` statement; `settings:objects:write` needs the `settings:dt.security_context` line, or the group could write settings across the environment. That condition applies only to settings objects on the scope of an entity that can carry a security context — verify how

the environment-scoped schemas you grant behave before relying on it, and narrow them with `settings:schemaId` in the policy where needed.

> **Sources:** Default policies (DT docs) — *Standard User* and *All Grail data read access* policy statements; *All Grail data read access*: *"Grants unconditional access to ALL Grail tables and to ALL Grail buckets."* IAM policy reference (DT docs) — `settings:dt.security_context` : *"This condition is applicable to any settings object that is allowed on the scope of an entity that can have a security context assigned."*

Pattern 6: Application Team — Structured Security Context

When `dt.security_context` follows the `comp:<component>/bu:<bu>/app:<app>` format (see **Structured Security Context Design** in **IAM-04**), app teams can access all component types for their application using a single wildcard boundary:

```
// Every line below applies to EVERY storage permission in the bound policy —
// repeated condition names multiply the statement, one copy per line (an OR).

// MATCH — Grail record tables and storage:smartscape:read
storage:dt.security_context MATCH('*/app:easytrade');

// startsWith — the operator storage:entities:read accepts (it has no MATCH);
// on records these lines also match single-value contexts with this prefix
storage:dt.security_context startsWith "comp:app/bu:digital/app:easytrade";
storage:dt.security_context startsWith "comp:db/bu:digital/app:easytrade";
storage:dt.security_context startsWith "comp:lb/bu:digital/app:easytrade";
```

> **The comments are a reading aid, not a routing rule.** A boundary cannot target a line at one permission: Dynatrace applies each condition to every statement whose service accepts it. Dynatrace lists no `MATCH` for `storage:entities:read`, so do not rely on a `MATCH` line to scope classic entities — the `startsWith` lines are what scope them. Check the effective statements per permission before binding.
>
> **Sources:** Policy boundaries (DT docs) — *"When a boundary contains repeated condition names, then each policy statement is multiplied by such conditions. Each of the repeated conditions appears separately in each applicable statement."*

This grants access to all data tagged with any component prefix for that application:

- `comp:app/bu:digital/app:easytrade`
- `comp:db/bu:digital/app:easytrade`
- `comp:lb/bu:digital/app:easytrade`

Pattern 7: Transversal Team — Component-Based Access

Infrastructure teams (database, network, OS) that need cross-application access to their component type use a leading `comp:` prefix to enable a single rule:

```
// Both lines apply to every storage permission in the bound policy (an OR).
// MATCH — Grail record tables and storage:smartscape:read
storage:dt.security_context MATCH('comp:db*');

// startsWith — what scopes storage:entities:read (no MATCH there)
storage:dt.security_context startsWith "comp:db";
```

This grants access to all data matching:

- `comp:db/bu:digital/app:easytrade`
- `comp:db/bu:digital/app:easytravel`
- `comp:db/bu:corp/app:hipstershop`

> **Dimension order is the key design decision.** Placing `comp` first in the string means component-based transversal access is always a simple anchored match. Access by `bu` or other mid-string dimensions requires `MATCH('*/bu:digital/*')`.

Multi-Value Security Context

`dt.security_context` can already hold an array, and on classic entities it commonly does — on the validation tenant (10/13/2026) 55 of 56 hosts held an array, and 52 of them carried two or more values. Grail record permissions evaluate arrays only with `MATCH` (`=`, `IN` and `startsWith` return false); for `storage:entities:read`, use `startsWith`, which evaluates any matching value.

The single-string model above requires choosing one leading dimension. Storing each dimension as its own array value removes that choice:

```
dt.security_context = ["bu:digital", "app:easytrade", "comp:db"]
```

This removes the dimension-ordering trade-off and simplifies all three team types to a single boundary condition per signal type:

Team	Boundary
App team (easytrade)	`storage:dt.security_context MATCH('app:easytrade')`
Database team (transversal)	`storage:dt.security_context MATCH('comp:db')`
Business unit (digital)	`storage:dt.security_context MATCH('bu:digital')`

Whichever model you choose, check what your data actually holds before writing conditions (the array check in Section 3).

> **Sources:** Permissions in Grail (DT docs) — *"// will match both "crn-70400-alpha" and ["crn-70131", "crn-70400-beta", "crn-70500"]".*

Pattern 8: Path-Scoped Lookup Files

Lookup files in Grail (uploaded tables that DQL reads with `load` and joins with `lookup`) are not records with a security context. The file permissions accept exactly one condition, the file path, so a **folder per team** is the only handle for scoping them:

Permission	Grants	Condition	Operators
`storage:files:read`	Read a lookup file	`storage:file-path`	`=`, `startsWith`, `IN`
`storage:files:write`	Upload a file (REST API)	`storage:file-path`	`=`, `startsWith`, `IN`
`storage:files:delete`	Delete a file (REST API)	`storage:file-path`	`=`, `startsWith`, `IN`

Goal: everyone reads `/lookups/global/*`; each team reads and writes only its own folder `/lookups/<team>/*`; only curators write to `global`.

Policy 1: **`lookups-global-read`.** Bind it to every group that queries lookups, with **no boundary**.

```
ALLOW storage:files:read WHERE storage:file-path startsWith
"/lookups/global/";
```

Unlike `storage:logs:write`, which accepts no condition (IAM-10), the file permissions accept `storage:file-path`, so writes can be scoped as well as reads.

Policy 2: `lookups-team-rw`. Write one central policy. Bind it once per team group, and give each binding that team's boundary.

```
ALLOW storage:files:read, storage:files:write WHERE storage:file-path
startsWith "/lookups/";
ALLOW storage:files:delete WHERE storage:file-path startsWith "/lookups/";
// only if teams must delete files
```

The boundary for one team, for example `team_payments`:

```
storage:file-path startsWith "/lookups/team_payments/";
```

A boundary is applied *"no matter if the statement already contains the same condition"*, so each effective statement carries both prefixes: `/lookups/` from the policy and `/lookups/team_payments/` from the boundary. The binding therefore reaches only that team's folder.

Policy 3: `lookups-global-write`. Bind it only to the curator or admin group, with **no boundary**.

```
ALLOW storage:files:read, storage:files:write WHERE storage:file-path
startsWith "/lookups/global/";
```

Alternative: one templated policy, no boundaries

This series defaults to parameterized policies (IAM-10), and they fit this case too. Write Policy 2 once with a parameter, then bind it per team with that team's folder as the value:

```
ALLOW storage:files:read, storage:files:write WHERE storage:file-path
startsWith "${bindParam:folder}";
```

Binding: `{"parameters": {"folder": "/lookups/team_payments/"}}`

This uses no boundary, so the *Boundary assignments per policy* question below does not arise. The templating page says parameters *"can be used in a policy similarly to how regular condition values are used"*, but it shows them only with `=` and `IN`. Confirm that a

`startsWith` parameter is enforced before you rely on it. Parameterized policies are bound only through the Account Management API, not in the group management UI.

> **Sources:** Templated policies (DT docs) — *"Parameters can be used in a policy similarly to how regular condition values are used."*

Why global read is a separate policy

A boundary *can* say "global **or** own folder". Two `storage:file-path` lines in one boundary multiply the statement, one copy per line, which works as an OR. But the boundary applies to every statement in the policy it is bound with, so in Policy 2 that OR would also grant **write** on `global` to every team. Keeping global read in an unbounded policy of its own keeps `global` read-only for everyone except the curators.

Rules for path-scoped boundaries

Rule	Why
Keep the leading slash on every path: `"/lookups/..."`	Every file path *"Must start with* `/` *"*. A condition without the slash matches no file.
End every prefix with a slash: `"/lookups/team_a/"`	`startsWith "/lookups/team_a"` also matches `/lookups/team_a2/...` and `/lookups/team_archive`.
Use `startsWith` for folders	`=` and `IN` compare whole paths. `IN ("/lookups/team_a/")` matches no file inside the folder.
Name each folder after the team's security context value	That way one naming scheme governs both data and files. Check the value is a legal path segment, though: a path may contain only `a-zA-Z0-9`, `-`, `_`, `.` and `/`, so a structured context such as `comp:db/bu:digital/app:easytrade` (Pattern 6) needs a mapped folder name.
Keep Policy 2 to `storage:files:*` permissions only	A boundary line restricts only the permissions that accept its condition. Add `storage:logs:read` to Policy 2 and the file-path boundary leaves it **unrestricted**.

Rule	Why
One boundary per binding	Several boundaries on one binding are evaluated separately, so they widen access. A team boundary that already holds `storage:dt.security_context` lines can take the `storage:file-path` line too. Each line applies only to the permissions that accept it.
Restrict with conditional `ALLOW`, never conditional `DENY`	Boundaries do not apply to `DENY` statements, and conditional `DENY` on storage is supported only for `buckets:read`.
Give automation tokens the same permissions	The lookup page says a token used for uploads needs these permissions too, and so does the user that owns it.

Limits to plan for

Limit	Value
Policies per account	200
Policy boundaries per account	2,000
Restrictions per boundary	10
Boundary assignments per policy	10

> **Open question: how many teams can share Policy 2?** The IAM limits page lists *Boundary assignments per policy* as **10**, not adjustable, and gives its level as *Boundary*. If it means one policy can carry at most 10 boundary assignments across all its bindings, a single `lookups-team-rw` policy serves at most 10 teams. Dynatrace does not say which reading applies, and this guide has not tested it. Until you have confirmed it on your account (bind one policy to 11 team groups, each with its own boundary), plan for the strict reading: one copy of Policy 2 per 10 teams. That stays well inside the 200-policy limit.

Test with a user that holds only these bindings

Action	Expected
Read `/lookups/global/<file>`	Allowed

Action	Expected
Write `/lookups/global/<file>` (non-curator)	Denied
Read and write `/lookups/<own team>/<file>`	Allowed
Read and write `/lookups/<other team>/<file>`	Denied
Read a file directly under `/lookups/` (no team folder)	Denied

The policy text above follows the Dynatrace docs. This guide has not bound it on a test account, so run the table before rolling it out.

> **Sources:**
> - Lookup data in Grail (DT docs) — *"All permissions can be restricted to specific paths or prefixes, giving users access to only a limited set of files."*; folder example *"/lookups/my_team/allow_list"*
> - IAM policy reference (DT docs) — `storage:files:read` / `write` / `delete`, condition `storage:file-path`, operators `=`, `startsWith`, `IN`; *"Conditional DENY statements are supported only for the buckets:read permission."*
> - Policy boundaries (DT docs) — *"Boundary will be applied no matter if the statement already contains the same condition"*; *"Boundaries don't apply to DENY statements"*; *"When a boundary contains repeated condition names, then each policy statement is multiplied by such conditions."*
> - IAM limits (DT docs) — Policies 200, Policy boundaries 2,000, Boundary assignments per policy 10, none adjustable
> - **Derived:** the trailing-slash, whole-path `IN` and folder-naming rules follow from the `startsWith` / `=` / `IN` operators and the path character rules; "Policy 2 leaks write on global" follows from the repeated-condition and applied-to-every-statement rules

Audit who changes lookup files


A successful upload writes an `AUDIT_EVENT` with `event.provider == "GRAIL"`, `event.category == "FILE_MANAGEMENT"`, and the file path in `resource`. The first query below counts changes per team folder. A **denied** call, as the test table above produces, is recorded only by the API gateway, as a `403` on the files API path. That record carries no file path, so a denied attempt can be tied to a user but not to a folder (second query).

```
// Lookup file changes per team folder (validated 10/14/2026)
// Successful uploads are GRAIL / FILE_MANAGEMENT audit events whose resource
is the file path.
// A file directly under /lookups/ (no team folder) reports as "(top level)":
on the validation
// tenant every one of 390 changes in 30 days was top level, which is the gap
Pattern 8 closes.
fetch dt.system.events, from:-30d
| filter event.kind == "AUDIT_EVENT" and event.category == "FILE_MANAGEMENT"
| filter startsWith(resource, "/lookups/")
| fieldsAdd parts = splitString(resource, "/")
| fieldsAdd zone = if(arraySize(parts) &gt; 3, parts[2], else: "(top level)")
| summarize {changes = count(), files = countDistinctExact(resource),
last_change = max(timestamp)}, by:{zone, user.id, event.type}
| sort changes desc
```

```
// Denied calls to the files API (validated 10/14/2026)
// Denials are recorded only by the API gateway, against the API path: the
file path is not in the
// record. On the validation tenant: 50 uploads denied with 403 in 30 days,
against 390 that succeeded.
// Not included: a 404 on lookup:delete, which reports a missing file, not a
denial.
fetch dt.system.events, from:-30d
| filter event.kind == "AUDIT_EVENT" and event.provider == "API_GATEWAY"
| filter contains(resource, "/platform/storage/resource-store/v1/files/")
| filter in(event.outcome, {"401", "403"})
| summarize {denied = count(), last_seen = max(timestamp)}, by:{user.id,
resource, event.outcome}
| sort denied desc
```

6. Multi-Tenant Isolation

For organizations serving multiple customers or business units that require strict isolation.



Isolation Requirements

Requirement	Implementation
Data isolation	Unique security context per tenant
No cross-tenant access	Strict boundary matching
Audit capability	Centralized logging
Shared infrastructure	Separate "platform" context

Multi-Tenant Boundary Example

Tenant A Group:

```
# One boundary — a line per domain the bound policies grant
storage:dt.security_context  IN ("tenant-a");
settings:dt.security_context IN ("tenant-a");
environment:management-zone  IN ("tenant-a");   # transitional — delete at MZ retirement
```

Tenant B Group:

```
# One boundary — a line per domain the bound policies grant
storage:dt.security_context  IN ("tenant-b");
settings:dt.security_context IN ("tenant-b");
environment:management-zone  IN ("tenant-b");   # transitional — delete at MZ
retirement
```

Platform Team (cross-tenant):

```
# One boundary — a line per domain the bound policies grant
storage:dt.security_context  IN ("platform", "shared");
settings:dt.security_context IN ("platform", "shared");
environment:management-zone  IN ("platform", "shared");   # transitional —
delete at MZ retirement
```

Entity Enrichment for Multi-Tenancy

Use Entity Enrichment rules (Settings > Entity Enrichment) to assign tenant context:

```
# Entity Enrichment rule based on host group
Rule: Assign security context from host group
Entity Type: Host
Condition: Host group name contains "tenant-"
Action: Set dt.security_context = {hostGroup.name}
```

Alternatively, set the context on the OneAgent at deployment. The June-2026 tags hub documents the host-tag form for `dt.*` primary fields (the older `--set-host-property` form remains documented in the oneagentctl reference):

```
# Set via OneAgent installer / oneagentctl (tags-hub form)
--set-host-tag="dt.security_context=tenant-a"
```

7. Boundary Testing

Verify boundaries work as expected before production use.

```
// Check security context distribution on services
fetch dt.entity.service
| summarize count = count(), by:{dt.security_context}
| sort count desc
| limit 20

// Smartscape note (dt.entity.* is deprecated but still functional):
dt.security_context exists
// on Smartscape nodes but as an ARRAY (empty [] when unset, not null), so
isNull / isNotNull
// and by:{dt.security_context} do not carry over — a Smartscape rewrite would
miscount coverage.
// Keep the classic query above.
```

```
// An empty result here is the HEALTHY answer, not a broken query (verified
08/12/2026: 0 of 37
// services lacked a security context on the validation tenant). Rows
appearing means governance
// gaps exist. Do not "fix" this cell because it returns nothing — confirm
with:
//   fetch dt.entity.service, from:-7d | summarize {total = count(),
no_context = countIf(isNull(dt.security_context))}
// Find entities without security context (boundary gaps)
fetch dt.entity.service, from:-7d
| filter isNull(dt.security_context)
| fields entity.name, tags
| sort entity.name
| limit 50

// Smartscape note (dt.entity.* is deprecated but still functional):
dt.security_context exists
// on Smartscape nodes but as an ARRAY (empty [] when unset, not null), so
isNull / isNotNull
// and by:{dt.security_context} do not carry over — a Smartscape rewrite would
miscount coverage.
// Keep the classic query above.
// (entity tags are also not a flat "tags" field on Smartscape — resolve via
getNodeField.)
```

```
// Check host security context coverage
fetch dt.entity.host
| summarize
    total = count(),
    withContext = countIf(isNotNull(dt.security_context)),
    missing = countIf(isNull(dt.security_context))
| fieldsAdd coveragePercent = round(100.0 * withContext / total, decimals: 2)

// Smartscape note (dt.entity.* is deprecated but still functional):
dt.security_context exists
// on Smartscape nodes but as an ARRAY (empty [] when unset, not null), so
isNull / isNotNull
// and by:{dt.security_context} do not carry over — a Smartscape rewrite would
miscount coverage.
// Keep the classic query above.
```

```
// Verify logs have security context
fetch logs, from: now() - 1h
| summarize
    total = count(),
    withContext = countIf(isNotNull(dt.security_context))
| fieldsAdd coveragePercent = round(100.0 * withContext / total, decimals: 2)
```

Testing Methodology

1. **Create test group** with the boundary
2. **Add test user** to the group
3. **Log in as test user** (or impersonate)
4. **Verify visible entities** match expected
5. **Verify hidden entities** are not visible
6. **Query data** to confirm filtering works

Validation Checklist

Test	Expected
List services	Only boundary-included services
Query logs	Only logs with matching context
View settings	Only settings with matching context

Test	Expected
Access denied entity	Empty result or error
Lookup file in another team's folder	Read and upload denied (Pattern 8)

Next Steps

With boundaries configured, complete your IAM implementation:

Recommended Path

1. **IAM-06: User Lifecycle and Provisioning** - Automate user management
2. **IAM-07: Audit Logging and Compliance** - Monitor access patterns
3. **IAM-08: Multi-Environment IAM** - Scale across environments

Boundary Checklist

Before moving on, ensure you have:

- [ ] Understood the three-domain model
- [ ] Designed your security context strategy
- [ ] Created boundaries for each team/group
- [ ] Configured entity enrichment for context assignment
- [ ] Tested boundaries with real users
- [ ] Verified no entities are missing context
- [ ] Scoped lookup files by folder, if teams upload them (Pattern 8)

Summary

In this notebook, you learned:

- Boundary fundamentals and how they differ from policies
- The three-domain model (environment, storage, settings)
- Boundary syntax and operators

- Security context strategy and naming
- Common boundary patterns, including path-scoped lookup files
- Multi-tenant isolation design
- Boundary testing and validation

References

- Permission Boundaries
- Security Context
- Primary Tags
- Lookup data in Grail (DT docs)
- IAM limits (DT docs)
- Host properties and tags via OneAgent (DT docs)

This notebook was AI-generated from community-submitted and publicly available sources. This notebook series is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.