MZ2POL-07: Validation and Troubleshooting

> **Series:** MZ2POL — Management Zone Migration: Segments, Policies, Workflows | **Notebook:** 8 of 17 | **Created:** December 2025 | **Last Updated:** 10/13/2026

Overview

This notebook provides comprehensive validation procedures and troubleshooting guidance for your migration from Management Zones to Policies, Boundaries, and Segments. Use this guide to verify your migration success and resolve common issues.

Table of Contents

1. Migration Validation Checklist
2. Security Context Validation
3. Access Control Validation
4. Segment Validation
5. Common Issues and Troubleshooting
6. Diagnostic Queries
7. Ongoing Maintenance
8. Health Monitoring Queries
9. Best Practices Summary
10. Migration Complete!
11. Additional Resources

Prerequisites

- Completed migration (MZ2POL-06), including the tag readiness gate (MZ2POL-10 §9–§10) and, if zones scoped alerting, the workflow cutover (MZ2POL-09)
- Admin access to Dynatrace — to confirm data exists, never to judge access
- Pilot user accounts for validation, one per persona (MZ2POL-12 §7)

Learning Objectives

By the end of this notebook, you will:
1. Be able to validate migration completeness
2. Know how to troubleshoot common access issues
3. Understand ongoing maintenance requirements
4. Have queries for monitoring access health

---

1. Migration Validation Checklist

Component Validation

Component	Validation	Status
User Groups	All groups created and populated	☐
Policies	Policies bound to all groups	☐
Boundaries	Boundaries applied where needed	☐
Tag readiness	MZ2POL-10 readiness gate passed	☐
Security Context	Records (logs, spans, events) carry it at the agreed coverage — measured per table, not on entities (§2)	☐
Segments	Segments created for all filtering needs	☐
Dashboards	Updated to use segments	☐

Component	Validation	Status
Alerts	Zone-scoped alerting profiles rebuilt as problem-triggered workflows; alert parity confirmed by the receiving teams (MZ2POL-09) — segments do not scope alerting	☐

Access Validation Matrix

For each user type, verify:

User Type	Can Access	Cannot Access	Verified
Frontend Dev	Frontend services	Backend services	☐
SRE	All production	Development	☐
Viewer	View dashboards	Edit settings	☐

---

2. Security Context Validation

Check Coverage on Records, Not Entities

Measure security context on the **data** — logs, spans, events — the same way as MZ2POL-06 §3 and MZ2POL-12 §10. Entity coverage proves nothing: the classic *Grail Security Context* mapping can copy zone names onto entities, and the records those entities send *"do not inherit the management zones of that entity."* On the validation tenant on 10/13/2026, all 35 services and all 24 hosts carried a security context, while 41.1% of logs and 75.3% of events in the same hour carried none.

`dt.security_context` is an **array** on classic entities, Smartscape nodes, events and problem records alike, and a string on logs and spans on the validation tenant. Count events with `arraySize()`, not `isNull()`; check the type per table with MZ2POL-12 §10 Check 1.

> **Sources:** Grant access to entities with security context (DT docs) — *"Logs, spans, metrics, and events powered by Grail that are sent from an entity do not inherit the management zones of that entity."* Counts executed against the validation tenant, 10/13/2026.

```
// Validate: security-context coverage on the DATA, per table (same pattern as
MZ2POL-06 §3).
// Records without it are invisible to users scoped only by
dt.security_context.
// Executed 10/13/2026: logs 58.9% / spans 100% / events 24.7% covered (last
hour).
fetch logs, from:-1h
| summarize {records = count(), without_sc =
countIf(isNull(dt.security_context))}
| fieldsAdd table = "logs"
| append [fetch spans, from:-1h | summarize {records = count(), without_sc =
countIf(isNull(dt.security_context))} | fieldsAdd table = "spans"]
| append [fetch events, from:-1h | summarize {records = count(), without_sc =
countIf(isNull(dt.security_context) or arraySize(dt.security_context) == 0)} |
fieldsAdd table = "events"]
| fieldsAdd coverage_pct = round(100.0 * (records - without_sc) / records,
decimals: 1)
| fields table, records, without_sc, coverage_pct
```

```
// Find the PRODUCERS whose records lack a security context.
// Fix these at the source (MZ2POL-10 §5) — not on the entity.
// Executed 10/13/2026: the top rows were Kubernetes namespaces (log
collectors, platform namespaces).
fetch logs, from:-1h
| filter isNull(dt.security_context)
| summarize {records = count()}, by:{dt.entity.host, k8s.namespace.name}
| sort records desc
| limit 20
```

```
// Validate: event coverage per event kind. dt.security_context is an ARRAY on
events.
// Executed 10/13/2026 over 24 h: DAVIS_EVENT 79.1%, DAVIS_PROBLEM 77.7%,
FLEET_EVENT 77.5%,
// SYNTHETIC_EVENT 14.6% without a security context.
fetch events, from:-24h
| summarize {records = count(),
             without_sc = countIf(isNull(dt.security_context) or
arraySize(dt.security_context) == 0)},
  by:{event.kind}
| fieldsAdd without_pct = round(100.0 * without_sc / records, decimals: 1)
| sort without_sc desc
```

Verify Security Context Distribution

```
// Distribution of security-context values on the DATA.
// Verify expected teams/environments are represented — and nothing
unexpected.
// On logs the field is a string on the validation tenant; for events, expand
the array first.
fetch logs, from:-1h
| filter isNotNull(dt.security_context)
| summarize {records = count()}, by:{dt.security_context}
| sort records desc
| limit 20
```

---

3. Access Control Validation

Test User Access Scenarios

Test **permissions**, not views. A segment narrows what a query returns whether or not the user is allowed to see more, so a scenario that selects a segment and then sees "only frontend services" proves nothing about access. Run every scenario **with no segment selected**, signed in as a **pilot user** who holds only the persona's groups — never an admin, whose grants hide boundary problems (§5, step 5).

For each test scenario:
1. Resolve the pilot user's effective permissions first (MZ2POL-12 §10) — look for any `storage:*:read` without a condition
2. Sign in as the pilot user, with no segment selected
3. Run the same DQL query the persona will use, and an equivalent query for data outside its scope
4. Document results, including record counts

Scenario 1: Team-Based Access

Test User: Pilot user holding only the `frontend-team` group
Expected: Records carrying the frontend security context only

Validation Steps:
1. With no segment selected, run `fetch logs, from:-1h | summarize {records =`

`count()}, by:{dt.security_context}` → only the frontend value(s) should appear
2. Open the Services app with no segment selected → only frontend services visible
3. Open a backend service directly by link → should fail or show no data
4. Compare the record count with an admin run of the same query filtered to the frontend value — they should match; a lower count means records without the field (§2)

Scenario 2: Environment Restriction

Test User: Pilot user holding only the `prod-viewers` group
Expected: Production data only, no edit

Validation Steps:
1. With no segment selected, query logs → only production security-context values appear
2. Query for a non-production value explicitly (`filter dt.security_context == "<non-prod value>"`) → zero records; confirm with an admin that such records exist, so the zero is the boundary and not an empty table
3. Try editing settings → should fail
4. Only then select the "Production" segment and confirm it changes the **view**, not the access — the results should be a subset of step 1

Scenario 3: Full Access (SRE)

Test User: Pilot user holding only the `sre-team` group
Expected: Full access to production environment

Validation Steps:
1. Open any app with no segment selected
2. Verify data visible across all services, including records **without** a security context (an unscoped grant is the only way to see those)
3. Verify edit capabilities work
4. Verify settings access

---

4. Segment Validation

Verify Segment Data Match

Compare segment results with expected MZ results:

```
// Compare: MZ entity count vs Segment entity count
// Replace with your MZ name and segment filter
fetch dt.entity.service
| summarize
    viaMZ = countIf(in(managementZones, {"Frontend-Team"})),
    viaSegment = countIf(matchesValue(tags, "team:frontend"))
| fields viaMZ, viaSegment,
         match = if(viaMZ == viaSegment, then: "MATCH", else: "MISMATCH")

// Note: dt.entity.* is deprecated, but this is a migration-ASSESSMENT query — it inspects
// the classic constructs this migration replaces, so keep the classic query above:
//   - management zones have NO Smartscape node equivalent; they are what this migration
//     replaces with segments and policies.
//   - on Smartscape nodes `tags` is a record read as tags[&lt;key&gt;], and it carries no classic
//     auto-tags (MZ2POL-10 §2) — this check reads the classic tag array on purpose.
```

```
// Find entities in MZ but not matching segment filter
// These are migration gaps
fetch dt.entity.service
| filter in(managementZones, {"Frontend-Team"})
| filter NOT matchesValue(tags, "team:frontend")
| fields entity.name, tags, managementZones


// Note: dt.entity.* is deprecated, but this is a migration-ASSESSMENT query — it inspects
// the classic constructs this migration replaces, so keep the classic query above:
//   - management zones have NO Smartscape node equivalent; they are what this migration
//     replaces with segments and policies.
//   - on Smartscape nodes `tags` is a record read as tags[&lt;key&gt;], and it carries no classic
//     auto-tags (MZ2POL-10 §2) — this check reads the classic tag array on purpose.
```

```
// Find entities matching segment but not in MZ
// May indicate over-inclusion in new model
fetch dt.entity.service
| filter matchesValue(tags, "team:frontend")
| filter NOT in(managementZones, {"Frontend-Team"})
| fields entity.name, tags, managementZones

// Note: dt.entity.* is deprecated, but this is a migration-ASSESSMENT query — it inspects
// the classic constructs this migration replaces, so keep the classic query above:
//   - management zones have NO Smartscape node equivalent; they are what this migration
//     replaces with segments and policies.
//   - on Smartscape nodes `tags` is a record read as tags[&lt;key&gt;], and it carries no classic
//     auto-tags (MZ2POL-10 §2) — this check reads the classic tag array on purpose.
```

---

5. Common Issues and Troubleshooting



Issue 1: User Can't See Any Data

Symptoms:
- Apps show empty results
- DQL queries return no records

Troubleshooting:

Check	Action
Group membership	Verify user is in correct group
Policy binding	Verify group has policy bound
Boundary scope	Verify boundary isn't too restrictive
Data policy	Verify a data-read policy (`Read Logs` / `All Grail data read access`) is included
Segment selection	Check if restrictive segment is active

Resolution Steps:
1. Check user's group membership in Account Management
2. Verify group has appropriate policy binding
3. Review boundary conditions
4. Test with admin account to verify data exists

Issue 2: User Sees Too Much Data

Symptoms:
- User sees data outside their scope
- Cross-team data visible

Troubleshooting:

Check	Action
Boundary conditions	Verify boundary is correctly restrictive
Multiple group membership	User may be in multiple groups

Check	Action
Security context	Verify the **records** carry the correct value (§2) — entity contexts may be copied from zone names
Policy conditions	Check for overly broad conditions

Resolution Steps:
1. Review all groups user belongs to
2. Check all policy bindings for those groups
3. Verify boundary conditions are correct
4. Check the security-context values on the visible records (§2, distribution query)

Issue 3: Segment Filter Not Working

Symptoms:
- Segment selected but data not filtered
- Same data visible with/without segment

Troubleshooting:

Check	Action
Segment syntax	Verify DQL filter is correct
Tag existence	Verify entities have expected tags
App support	Verify app supports segments
Segment sharing	Verify segment is shared with user

Resolution Steps:
1. Test segment filter as standalone DQL query
2. Verify tags exist on target entities
3. Check segment is shared/public
4. Try segment in different app

Issue 4: Classic Apps Work, New Apps Don't

Symptoms:
- Legacy UI shows expected data
- New apps (Services, Logs) show no/wrong data

Causes (the diagram's *Classic OK, Grail wrong* row; MZ2POL-12 §4):
- **The boundary has only the zone line.** It scopes classic pages; the Grail permissions bound with it get no condition from it. On a default policy they come out **unscoped** (MZ2POL-12 §4.2), so the Grail app shows the team more than the classic page did
- **The data lacks the field.** Records the team needs carry no `dt.security_context` value it is granted — typically because the value lived in an auto-tag or a zone, neither of which reaches Grail records (§2, MZ2POL-10 §2)
- **Entities are scoped only by `dt.security_context`.** `storage:entities:read` accepts `dt.security_context` and `entity.type`; zone membership does not scope entity reads in Grail apps, so an entity whose context is missing or zone-derived behaves differently from the classic page

Resolution:
1. Resolve the user's effective permissions (MZ2POL-12 §10) and confirm the boundary has a `storage:` line as well as the zone line
2. Run the §2 record-coverage queries for the team's producers; set the value at the source (MZ2POL-10 §5)
3. Retest as the pilot user with **no segment selected** — a segment changes the view, never the access, so it cannot fix this

---

6. Diagnostic Queries

Check Entity Tag Distribution

```
// Analyze tag patterns for segment creation
fetch dt.entity.service
| expand tag = tags
| parse tag, "LD:key ':' LD:value"
| summarize count = count(), by:{key}
| sort count desc
| limit 20

// Note: dt.entity.* is deprecated, but this is a migration-ASSESSMENT query — it inspects
// the classic constructs this migration replaces, so keep the classic query above:
//   - on Smartscape nodes `tags` is a record read as tags[&lt;key&gt;], and it carries no classic
//     auto-tags (MZ2POL-10 §2) — this check reads the classic tag array on purpose.
```

```
// Find entities without standard tags
// These may need tagging for segment filters
fetch dt.entity.service
| filter NOT matchesValue(tags, "team:*")
| filter NOT matchesValue(tags, "env:*")
| fields entity.name, tags
| limit 50

// Note: dt.entity.* is deprecated, but this is a migration-ASSESSMENT query — it inspects
// the classic constructs this migration replaces, so keep the classic query above:
//   - on Smartscape nodes `tags` is a record read as tags[&lt;key&gt;], and it carries no classic
//     auto-tags (MZ2POL-10 §2) — this check reads the classic tag array on purpose.
```

Check MZ Assignment Health

```
// Entities with MZ but no security context.
// dt.security_context is an ARRAY on classic entities (and on Smartscape
nodes): test arraySize(), not isNull().
// A pass here proves little — an MZ-derived context counts as present
(MZ2POL-12 §10, Check 3).
// Executed 10/13/2026: 0 rows; control: all 35 services carry a one-element
array.
fetch dt.entity.service
| filter arraySize(managementZones) &gt; 0
| filter isNull(dt.security_context) or arraySize(dt.security_context) == 0
| fields entity.name, managementZones, tags
| limit 50

// Note: dt.entity.* is deprecated, but this is a migration-ASSESSMENT query —
it inspects
// the classic constructs this migration replaces, so keep the classic query
above:
//   - management zones have NO Smartscape node equivalent; they are what this
migration
//     replaces with segments and policies.
```

```
// MZ to tag alignment check
// Verify MZ membership aligns with tags used in segments
fetch dt.entity.service
| expand mz = managementZones
| summarize {
    entityCount = count(),
    withTeamTag = countIf(matchesValue(tags, "team:*")),
    withEnvTag = countIf(matchesValue(tags, "env:*"))
  }, by:{mz}
| sort entityCount desc

// Note: dt.entity.* is deprecated, but this is a migration-ASSESSMENT query —
it inspects
// the classic constructs this migration replaces, so keep the classic query
above:
//   - management zones have NO Smartscape node equivalent; they are what this
migration
//     replaces with segments and policies.
//   - on Smartscape nodes `tags` is a record read as tags[&lt;key&gt;], and
it carries no classic
//     auto-tags (MZ2POL-10 §2) — this check reads the classic tag array on
purpose.
```

7. Ongoing Maintenance

Regular Validation Tasks

Task	Frequency	Purpose
Security context audit	Weekly	Ensure new producers' records carry it (§2)
Segment effectiveness	Monthly	Verify segments return expected data
Access review	Quarterly	Verify user access is appropriate
Policy review	Quarterly	Ensure policies match requirements

New Entity Onboarding

When new services/hosts are deployed:

1. **Enrichment at source**: Ensure the deployment sets the team and environment values — `--set-host-tag`, `DT_TAGS`, Kubernetes annotations, OTel resource attributes or the central ingest enrichment configuration (MZ2POL-10 §5). Auto-tagging rules do not reach Grail data
2. **Security context**: Verify the new producer's **records** carry it (§2)
3. **Segment inclusion**: Verify entity appears in appropriate segments
4. **Access verification**: Test user access to new entity

New User Onboarding

When new users join:

1. Add user to appropriate group(s)
2. Communicate available segments
3. Provide access documentation
4. Verify access works as expected

8. Health Monitoring Queries

Create Monitoring Dashboard

Use these queries for an access health dashboard:

```
// KPI: security-context coverage on the DATA, per table (one bar per table).
// Same pattern as §2 and MZ2POL-06 §3.
fetch logs, from:-1h
| summarize {records = count(), without_sc =
countIf(isNull(dt.security_context))}
| fieldsAdd table = "logs"
| append [fetch spans, from:-1h | summarize {records = count(), without_sc =
countIf(isNull(dt.security_context))} | fieldsAdd table = "spans"]
| append [fetch events, from:-1h | summarize {records = count(), without_sc =
countIf(isNull(dt.security_context) or arraySize(dt.security_context) == 0)} |
fieldsAdd table = "events"]
| fieldsAdd coverage_pct = round(100.0 * (records - without_sc) / records,
decimals: 1)
| fields table, coverage_pct
```

```
// KPI: log records per security-context value.
// Monitor for unexpected growth/decline, and for values no boundary grants.
fetch logs, from:-1h
| filter isNotNull(dt.security_context)
| summarize {records = count()}, by:{dt.security_context}
| sort records desc
| limit 10
```

```
// KPI: log records no scope can reach — no security context, no team tag,
// and no built-in field a boundary or segment could use (migration gaps).
// Executed 10/13/2026: 15,432 of 796,892 log records (1.9%) in the last hour.
fetch logs, from:-1h
| summarize {records = count(),
             no_scope = countIf(isNull(dt.security_context) and
isNull(primary_tags.team)
                                and isNull(k8s.namespace.name) and
isNull(dt.host_group.id))}
| fieldsAdd no_scope_pct = round(100.0 * no_scope / records, decimals: 1)
```

9. Best Practices Summary

Access Control

- ✅ Use groups, not individual user permissions
- ✅ Apply least privilege principle
- ✅ Document all policy bindings
- ✅ Regular access reviews

Segments

- ✅ Align with organizational structure
- ✅ Use consistent naming conventions
- ✅ Test filters before deployment
- ✅ Share segments appropriately

Boundaries

- ✅ Create reusable boundaries
- ✅ Use security context for entity-level control
- ✅ Document boundary purpose
- ✅ Keep conditions simple

Maintenance

- ✅ Automate security context assignment
- ✅ Monitor access health metrics
- ✅ Review and update documentation
- ✅ Train new team members

Summary

In this notebook, you learned:

1. **Validation procedures**: How to verify migration success
2. **Troubleshooting**: Common issues and resolutions
3. **Diagnostic queries**: DQL for investigating access problems
4. **Ongoing maintenance**: Regular tasks for access health
5. **Health monitoring**: Queries for access dashboards

Migration Complete!

Congratulations on completing the MZ2POL migration series. You have:

- ✅ Understood why migration is necessary (MZ2POL-01)
- ✅ Learned the new access control model (MZ2POL-02)
- ✅ Assessed and planned your migration (MZ2POL-03)
- ✅ Configured policies and boundaries (MZ2POL-04)
- ✅ Implemented segments (MZ2POL-05)
- ✅ Executed the migration (MZ2POL-06)
- ✅ Validated and can troubleshoot (MZ2POL-07)
- ✅ Templated policies for scale (MZ2POL-08)
- ✅ Rebuilt zone-scoped alerting as problem-triggered workflows (MZ2POL-09)
- ✅ Put the context on the data and passed the readiness gate (MZ2POL-10)
- ✅ Translated zone rules to values at the source (MZ2POL-11)
- ✅ Checked the access design against the IAM reference architecture (MZ2POL-12)
- ✅ Know what is and is not documented about Spaces (MZ2POL-13)
- ✅ Ran the zone-disposition workshop (MZ2POL-14)

Additional Resources

- Access Management Concepts
- Dynatrace Community - Boundaries + Policies Best Practices
- Segments Documentation
- IAM Policy Reference
- Policy Templating

This notebook was AI-generated from community-submitted and publicly available sources. This notebook series is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.