K8S-08: DQL Queries for Kubernetes

> **Series:** K8S — Kubernetes Monitoring | **Notebook:** 8 of 14 | **Created:** January 2026 | **Last Updated:** 11/11/2026

Advanced Query Patterns for Kubernetes Data

This notebook provides a comprehensive reference of DQL queries for Kubernetes monitoring. From basic entity queries to complex performance analysis, these patterns help you extract insights from your Kubernetes data.

Table of Contents

1. Entity Queries
2. Metric Queries
3. Log and Event Queries
4. Trace Queries
5. Correlation Queries
6. Dashboard Queries
7. Alerting Queries
8. Query Templates

Prerequisites

Requirement	Details
Dynatrace Environment	SaaS with Kubernetes monitoring

Requirement	Details
Permissions	`storage:metrics:read`, `storage:logs:read`, `storage:events:read`, `storage:spans:read`, `storage:smartscape:read`
Knowledge	K8S-01 through K8S-07
Data	Active Kubernetes cluster monitored

1. Entity Queries

Kubernetes Entity Types

Object	Smartscape node (`smartscapeNodes`)	Classic entity (`fetch`)
Cluster	`K8S_CLUSTER`	`dt.entity.kubernetes_cluster`
Node	`K8S_NODE`	`dt.entity.kubernetes_node`
Namespace	`K8S_NAMESPACE`	`dt.entity.cloud_application_namespace`
Workload	`K8S_DEPLOYMENT`, `K8S_STATEFULSET`, `K8S_DAEMONSET`, `K8S_REPLICASET`, `K8S_JOB`, `K8S_CRONJOB`	`dt.entity.cloud_application` (all kinds)
Pod	`K8S_POD`	`dt.entity.cloud_application_instance`
Container	`CONTAINER`	`dt.entity.container_group_instance`
Service	`SERVICE`	`dt.entity.service`

> **Dictionary:** classic-to-Smartscape mappings from `dt.semantic_dictionary.models` (`classic_models` → `smartscape_node_type`), read 10/02/2026.

```
// List all Kubernetes clusters (smartscape topology)
smartscapeNodes "K8S_CLUSTER"
| fields entity.name = name, tags
| sort entity.name asc

// Legacy alternative (deprecated for new content):
// fetch dt.entity.kubernetes_cluster
// | fields entity.name, tags
// | sort entity.name asc
```

```
// List all Kubernetes nodes (smartscape topology)
smartscapeNodes "K8S_NODE"
| fields entity.name = name, tags
| sort entity.name asc

// Legacy alternative (deprecated for new content):
// fetch dt.entity.kubernetes_node
// | fields entity.name, tags
// | sort entity.name asc
```

```
// List all namespaces (smartscape topology)
smartscapeNodes "K8S_NAMESPACE"
| fields entity.name = name, tags
| sort entity.name asc

// Legacy alternative (deprecated for new content):
// fetch dt.entity.cloud_application_namespace
// | fields entity.name, tags
// | sort entity.name asc
```

```
// List all workloads — Deployments (smartscape topology)
smartscapeNodes "K8S_DEPLOYMENT"
| fields entity.name = name, tags
| sort entity.name asc
| limit 50

// For other workload types, substitute:
// smartscapeNodes "K8S_STATEFULSET"
// smartscapeNodes "K8S_DAEMONSET"

// Legacy alternative (deprecated for new content):
// fetch dt.entity.cloud_application
// | fields entity.name, tags
// | sort entity.name asc
// | limit 50
```

```
// Count Kubernetes nodes (smartscape topology)
smartscapeNodes "K8S_NODE"
| summarize nodeCount = count()
```

2. Metric Queries

Common Kubernetes Metrics

The table below lists keys verified present on a live tenant (`yhu28601`, 08/11/2026). Enumerate your own before writing a query — this is what exists there, not a guarantee for every estate:

```
metrics
| filter startsWith(metric.key, "dt.kubernetes")
| summarize n = count(), by:{metric.key}
| sort metric.key asc
```

> Two mechanics that bite here. **`metrics` takes `from:` with no leading comma** — `metrics from:-2h | …`. Writing `metrics, from:-2h` is a `PARSE_ERROR`, and a parse error read only for its record count is indistinguishable from "this tenant carries no such metrics." And **`metrics` returns one row per dimension tuple**, not one per key, so `summarize by:{metric.key}` is what collapses the result into a key list.

Metric	Description	Unit	Grain
`dt.kubernetes.container.cpu_usage`	Container CPU usage	Millicores	container
`dt.kubernetes.container.memory_working_set`	Container memory (active)	Bytes	container
`dt.kubernetes.container.requests_cpu`	CPU requests	Millicores	container
`dt.kubernetes.container.requests_memory`	Memory requests	Bytes	container
`dt.kubernetes.container.limits_cpu`	CPU limits	Millicores	container
`dt.kubernetes.container.limits_memory`	Memory limits	Bytes	container
`dt.kubernetes.container.cpu_throttled`	CPU throttling	—	container
`dt.kubernetes.container.restarts`	Restart count (delta)	Count	container
`dt.kubernetes.container.oom_kills`	OOMKilled count	Count	container
`dt.containers.cpu.throttled_time`	CPU throttle time	Nanoseconds	container
`dt.kubernetes.node.cpu_allocatable`	Node allocatable CPU	Millicores	node
`dt.kubernetes.node.memory_allocatable`	Node allocatable memory	Bytes	node
`dt.kubernetes.node.pods_allocatable`	Node allocatable pod slots	Count	node
`dt.kubernetes.node.conditions`	Node condition status	—	node

Metric	Description	Unit	Grain
`dt.kubernetes.pod.containers_desired`	Desired containers per pod	Count	pod
`dt.kubernetes.pod.network_received_data` / `.network_transmitted_data`	Pod network throughput	Bytes	pod
`dt.kubernetes.workload.pods_desired`	Desired pods per workload	Count	workload
`dt.kubernetes.workload.conditions`	Workload condition status	—	workload
`dt.kubernetes.nodes` / `.pods` / `.containers` / `.workloads` / `.events`	Object counts	Count	cluster

> **There is no node- or workload-grain *usage* or *requests* metric.** `dt.kubernetes.node.cpu_usage`, `dt.kubernetes.node.memory_usage`, `dt.kubernetes.workload.requests_cpu` and `dt.kubernetes.workload.requests_memory` **do not exist** — each returns zero rows from `metrics | filter metric.key == "…"` (checked 08/11/2026). Node and workload views are **derived**: sum the `dt.kubernetes.container.*` series across `k8s.node.name` or `k8s.workload.name`. Only the `*_allocatable` family is genuinely node-grain.
>
> This is worth stating plainly because a `timeseries` against a key that does not exist is syntactically valid, executes without error, and returns nothing — the same shape as a correct query against an idle cluster. §5 below shows the derivation for nodes.
>
> **Reading request and limit metrics across ActiveGate upgrades.** The CPU and memory *request* and *limit* metrics carry an **effective pod value**. Where a simple sum of container values would not match what Kubernetes enforces, Dynatrace adds a **compensating delta data point** to the same metric at ingest — in the docs' words, *"Dynatrace calculates the correct effective value at ingest time and adjusts the metric so that aggregated views across pods, workloads, namespaces, and clusters always reflect what Kubernetes actually enforces."* What that effective value covers grew in ActiveGate steps:

ActiveGate	What the request/limit metrics account for
1.339+	App containers and native sidecars (`restartPolicy: Always`)
1.343+	Init containers — a delta where the init phase peaks above the running-phase sum
1.345+ (rollout from 08/25/2026)	Pod-level `spec.resources` (Kubernetes 1.34+) and RuntimeClass `overhead` — including a **negative** delta where a pod-level *limit* caps the total below the container sum
1.347 (rollout from 09/30/2026)	Fix for a miscalculated effective value when a native sidecar precedes one or more non-restartable init containers

Metric family	Affected by the effective-resource changes?
`dt.kubernetes.container.requests_cpu` , `.requests_memory` , `.limits_cpu` , `.limits_memory`	**Yes** — the effective value changes at each boundary above
`dt.kubernetes.container.cpu_usage` , `.memory_working_set`	**No** — usage metrics are unchanged

Three practical consequences:

1. **A trend that spans any of these ActiveGate versions may carry a discontinuity** — up for init containers, up **or down** for pod-level limits, with no workload change at all. It appears only where the pod shape triggers it (an init container larger than the running-phase sum, a pod-level `spec.resources` , or an `overhead`), so it is not a uniform shift. Do not read a request/limit chart across a boundary as a single trend, and do not let a threshold alert on reserved CPU or memory fire on the discontinuity. Bound your comparison windows on one side of the upgrade or the other.
2. **Earlier baselines misstate reservations** relative to what Kubernetes enforces. The post-upgrade figures are the more faithful number — re-baseline rather than trying to reconcile the two.
3. **The delta belongs to no container.** The compensating data point has no `dt.smartscape.container` dimension (its `dt.smartscape_source.type` is `K8S_POD`), so a breakdown *by container* shows it as an unnamed row. Summing across it gives the enforced pod value; filtering out rows without a container quietly brings back the old arithmetic.

> Because node and namespace roll-ups are *derived* from these container-grain series (see the note above), a change propagates to every level you aggregate to — there is no unaffected roll-up to fall back on. One edge case the docs call out explicitly: *"Upgrading Istio to version 1.27+ (where native sidecars are the default) without also upgrading to ActiveGate version 1.339+ will cause sidecar resources to be missing from the metric."*
>
> Each version rolls out per ActiveGate, not per tenant, and ActiveGate fleets lag tenant version — so **verify the version of the ActiveGate carrying the `kubernetes-monitoring` capability for the cluster in question** before deciding which side of a boundary a data point sits on. Until a given version reaches that ActiveGate, the earlier reading is what your data shows, and everything above about baselines and alert thresholds still describes it correctly.
>
> Sources: Effective pod resources (DT docs), ActiveGate 1.345 release notes (DT docs), ActiveGate 1.347 release notes (DT docs) — *"Fixed incorrect calculation of effective pod resource requests and limits when a restartable init container (native sidecar) preceded one or more non-restartable init containers."* Read 10/02/2026.

```
// Container CPU usage — top consumers
// Sort on a scalar. `sort` on the timeseries array itself compares arrays
element by element,
// so the order has nothing to do with the average — reduce with arrayAvg()
first.
timeseries cpu = avg(dt.kubernetes.container.cpu_usage), from:-1h,
  by:{k8s.cluster.name, k8s.namespace.name, k8s.pod.name, k8s.container.name}
| fieldsAdd avgCpuMillicores = round(arrayAvg(cpu), decimals: 0)
| fields k8s.cluster.name, k8s.namespace.name, k8s.pod.name, k8s.container.name,
avgCpuMillicores
| sort avgCpuMillicores desc
| limit 15
```

```
// Container memory usage approaching limits
// "Approaching the limit" needs the limit: compare working set with
limits_memory per container.
// Containers with no memory limit drop out (limitMiB is null) — they cannot be
OOM-killed for
// exceeding a limit, only by node pressure.
timeseries {
    used = avg(dt.kubernetes.container.memory_working_set),
    lim = avg(dt.kubernetes.container.limits_memory)
  }, from:-1h, by:{k8s.cluster.name, k8s.namespace.name, k8s.pod.name,
k8s.container.name}
| fieldsAdd usedMiB = round(arrayAvg(used) / 1048576, decimals: 0),
            limitMiB = round(arrayAvg(lim) / 1048576, decimals: 0)
| filter limitMiB &gt; 0
| fieldsAdd pctOfLimit = round(100 * usedMiB / limitMiB, decimals: 1)
| fields k8s.cluster.name, k8s.namespace.name, k8s.pod.name, k8s.container.name,
usedMiB, limitMiB, pctOfLimit
| sort pctOfLimit desc
| limit 15
```

```
// CPU throttling detection
// One series per container instance, so avg() is its own value. A bare sum()
would also add the
// raw points inside each time bucket and read high at wide timeframes.
timeseries totalThrottle = avg(dt.containers.cpu.throttled_time), from:-1h, by:
{dt.entity.container_group_instance}
| fieldsAdd totalThrottleValue = arrayAvg(totalThrottle)
| filter totalThrottleValue &gt; 0
| sort totalThrottleValue desc
| limit 15
```

```
// Namespace-level resource usage — sum() of every container in the namespace
// rollup: avg averages each container within a time bucket before the cross-
container sum;
// without it, sum() also adds the 1-min points in each bucket and wide
timeframes read ~10x high.
timeseries cpuMillicores = sum(dt.kubernetes.container.cpu_usage, rollup: avg),
from:-1h, by:{k8s.namespace.name}
| fieldsAdd avgCpuMillicores = arrayAvg(cpuMillicores)
| sort avgCpuMillicores desc
| limit 15
```

```
// Resource requests by namespace (capacity planning)
// Requests are container-grain; sum them to reach the namespace figure.
// rollup: avg averages each container within a time bucket before the cross-container sum;
// without it, sum() also adds the 1-min points in each bucket and wide timeframes read ~10x high.
timeseries cpuReq = sum(dt.kubernetes.container.requests_cpu, rollup: avg), from:-1h, by:{k8s.namespace.name}
| fieldsAdd avgReqMillicores = round(arrayAvg(cpuReq), decimals: 0)
| fields k8s.namespace.name, avgReqMillicores
| sort avgReqMillicores desc
| limit 15
```

3. Log and Event Queries

Logs and Kubernetes events are two different objects, and the split is not optional. Application output written to stdout/stderr lands in `logs`. Kubernetes events — `FailedScheduling`, `BackOff`, `Unhealthy`, `Killing` — land in `events`, and are **not** searchable through `logs`.

Getting this wrong is expensive in both directions:

Anti-pattern	Result on a live tenant (08/11/2026)
`fetch logs | filter matchesPhrase(log.source, "kubernetes")`	**0 rows after scanning 46.5 GB.** Empty *and* billed.
`fetch events | filter event.kind == "K8S_EVENT"`	**0 rows.** `event.kind` never takes that value — over 24 h the only values present were `DAVIS_EVENT`, `SYNTHETIC_EVENT`, `FLEET_EVENT`, `DAVIS_PROBLEM`. Kubernetes events carry `DAVIS_EVENT`, so *kind* cannot discriminate them.

Anti-pattern	Result on a live tenant (08/11/2026)
`k8s.event.reason`	Field resolves, **null on every record**. Semantic Dictionary 1.350 (09/21/2026) adds `k8s.event.reason`, `k8s.event.type` and `k8s.event.involved_object.kind` to the global field reference, but on the validation tenant (11/11/2026) all three were still null on 6,351 of 6,351 Kubernetes event records over 24 h, while `dt.kubernetes.event.reason` was set on all of them. Keep querying `dt.kubernetes.event.*`, and compare the two families (K8S-04 § 5 has the query) before moving a query to the new names.

The working pair is `event.provider == "KUBERNETES_EVENT"` plus `dt.kubernetes.event.reason`. Companion fields: `dt.kubernetes.event.message`, `.count`, `.first_seen`, `.last_seen`, `.involved_object.kind`, `.involved_object.name`, alongside `k8s.cluster.name` / `k8s.namespace.name` / `k8s.pod.name` / `k8s.workload.name` / `k8s.node.name`.

> **Sources:** Semantic Dictionary changelog 1.350 (DT docs) — *Global field reference*, change type *Added*: `k8s.event.involved_object.kind`, `k8s.event.reason`, `k8s.event.type`. Null-rate comparison executed on the validation tenant 11/11/2026.

Log Query Patterns

```
// Error logs by namespace
fetch logs, from:-1h
// status == "ERROR" also counts SEVERE, CRITICAL and FATAL logs; loglevel ==
"ERROR" misses them
| filter status == "ERROR"
| filter isNotNull(k8s.namespace.name)
| summarize errorCount = count(), by:{k8s.namespace.name}
| sort errorCount desc
| limit 15
```

```
// Kubernetes events — what your estate actually emits, by reason
fetch events, from:-1h
| filter event.provider == "KUBERNETES_EVENT"
| summarize eventCount = countDistinctExact(event.id), by:
{dt.kubernetes.event.reason}
| sort eventCount desc
| limit 30
```

```
// Pod crash / restart loops — the BackOff event carries the pod and the reason
// One open event is re-written about every 5 min under the same event.id, so it
can repeat here.
fetch events, from:-1h
| filter event.provider == "KUBERNETES_EVENT"
| filter dt.kubernetes.event.reason == "BackOff"
| fields timestamp, k8s.cluster.name, k8s.namespace.name,
         dt.kubernetes.event.involved_object.name,
         dt.kubernetes.event.message
| sort timestamp desc
| limit 20
```

```
// OOM kills — a metric, not an event
// Dynatrace derives this counter from the container status and writes it only
// when at least one kill occurred, so any non-null value is a real OOM.
timeseries oom = sum(dt.kubernetes.container.oom_kills), from:-24h,
  by:{k8s.cluster.name, k8s.namespace.name, k8s.workload.name}
| fieldsAdd oomTotal = arraySum(oom)
| filter oomTotal &gt; 0
| fields k8s.cluster.name, k8s.namespace.name, k8s.workload.name, oomTotal
| sort oomTotal desc
| limit 20
```

```
// Log volume trend by namespace
// makeTimeseries returns one series per namespace with every hourly bucket. The
earlier
// `sort time_bucket asc | limit 200` cut the newest hours first once namespaces
x hours passed 200.
fetch logs, from: now() - 24h
| filter isNotNull(k8s.namespace.name)
| makeTimeseries log_count = count(), by:{k8s.namespace.name}, interval:1h
```

4. Trace Queries

Span Queries for Kubernetes Services

> **`duration` is a duration type — compare it against a duration literal (`1s` , `500ms`), never a nanosecond integer.** `duration > 1000000000` is a type mismatch: it raises only a `DATATYPE_MISMATCH` warning, evaluates to null, and the filter silently drops every span. Spans also have no `timestamp` field — their time fields are `start_time` and `end_time` .

```
// Service response times in K8s (server spans)
fetch spans, from:-1h
| filter span.kind == "server"
| filter isNotNull(k8s.namespace.name)
| summarize {
    p50_ms = percentile(duration, 50) / 1ms,
    p95_ms = percentile(duration, 95) / 1ms,
    p99_ms = percentile(duration, 99) / 1ms
  }, by:{k8s.namespace.name, dt.service.name}
| sort p99_ms desc
| limit 15
```

```
// Error rate by service
// Three things to get right here, each of which fails silently:
//   1. The field is span.status_code (stable). otel.status_code does not exist.
//   2. Values are LOWERCASE — "error", not "ERROR".
//   3. span.status_code is NULL on almost every successful span, so derive
//      successes as total - errors rather than counting a non-error value.
fetch spans, from:-1h
| filter span.kind == "server"
| filter isNotNull(k8s.namespace.name)
| summarize {
    total = count(),
    errors = countIf(span.status_code == "error")
  }, by:{k8s.namespace.name, dt.service.name}
| fieldsAdd successes = total - errors
| fieldsAdd errorRate = round(100.0 * errors / total, decimals: 2)
| filter errors &gt; 0
| sort errorRate desc
| limit 15
```

```
// Slow traces (&gt;1 second)
fetch spans, from:-1h
| filter span.kind == "server" and duration &gt; 1s
| filter isNotNull(k8s.namespace.name)
| fields start_time, trace.id, k8s.namespace.name, span.name, duration
| sort duration desc
| limit 20
```

```
// Server-span throughput by namespace (each service hop a request passes
through adds one server span)
fetch spans, from:-1h
| filter span.kind == "server"
| filter isNotNull(k8s.namespace.name)
| summarize requestCount = count(), by:{k8s.namespace.name}
| sort requestCount desc
| limit 10
```

5. Correlation Queries

Joining Multiple Data Sources

```
// High-CPU workloads, by name
// k8s.workload.name is a dimension on the container metrics, so no entity
lookup is needed.
// A workload's CPU is the sum of its containers (and replicas): sum(...,
rollup: avg), not avg().
timeseries cpu = sum(dt.kubernetes.container.cpu_usage, rollup: avg), from:-1h,
  by:{k8s.cluster.name, k8s.namespace.name, k8s.workload.name}
| fieldsAdd avgCpuMillicores = round(arrayAvg(cpu), decimals: 0)
| fields k8s.cluster.name, k8s.namespace.name, k8s.workload.name,
avgCpuMillicores
| sort avgCpuMillicores desc
| limit 20
```

```
// Nodes with high utilization — derived, because no node-grain usage metric
exists
// used  = container CPU summed across every container on the node
// alloc = the one genuinely node-grain family
// rollup: avg averages each container within a time bucket before the cross-
container sum;
// without it, sum() also adds the 1-min points in each bucket and wide
timeframes read ~10x high.
timeseries {
    used = sum(dt.kubernetes.container.cpu_usage, rollup: avg),
    allocatable = avg(dt.kubernetes.node.cpu_allocatable)
  }, from:-1h, by:{k8s.cluster.name, k8s.node.name}
| fieldsAdd cpuPercent = round(100 * arrayAvg(used) / arrayAvg(allocatable),
decimals: 1)
| filter cpuPercent &gt; 70
| fields k8s.cluster.name, k8s.node.name, cpuPercent
| sort cpuPercent desc
```

6. Dashboard Queries

Queries Optimized for Dashboards

```
// Cluster summary tile (smartscape topology)
smartscapeNodes "K8S_CLUSTER"
| summarize clusterCount = count()
```

```
// Node count tile (smartscape topology)
smartscapeNodes "K8S_NODE"
| summarize nodeCount = count()
```

```
// Error rate trend (chart)
fetch logs, from: now() - 24h
// status == "ERROR" also counts SEVERE, CRITICAL and FATAL logs; loglevel ==
"ERROR" misses them
| filter status == "ERROR" and isNotNull(k8s.namespace.name)
| summarize errors = count(), by:{time_bucket = bin(timestamp, 1h)}
| sort time_bucket asc
```

```
// Top namespaces by CPU (bar chart) — sum() of every container in the namespace
// rollup: avg averages each container within a time bucket before the cross-container sum;
// without it, sum() also adds the 1-min points in each bucket and wide timeframes read ~10x high.
timeseries cpuMillicores = sum(dt.kubernetes.container.cpu_usage, rollup: avg), from:-1h, by:{k8s.namespace.name}
| fieldsAdd avgCpuMillicores = arrayAvg(cpuMillicores)
| sort avgCpuMillicores desc
| limit 10
```

7. Alerting Queries

Threshold-Based Alerting Patterns

```
// High memory usage alert query — containers above 90% of their memory limit
// "Approaching the limit" needs the limit: compare working set with limits_memory per container.
// Containers with no memory limit drop out (limitMiB is null) — they cannot be OOM-killed for
// exceeding a limit, only by node pressure.
timeseries {
    used = avg(dt.kubernetes.container.memory_working_set),
    lim = avg(dt.kubernetes.container.limits_memory)
  }, from:-1h, by:{k8s.cluster.name, k8s.namespace.name, k8s.pod.name, k8s.container.name}
| fieldsAdd usedMiB = round(arrayAvg(used) / 1048576, decimals: 0),
            limitMiB = round(arrayAvg(lim) / 1048576, decimals: 0)
| filter limitMiB &gt; 0
| fieldsAdd pctOfLimit = round(100 * usedMiB / limitMiB, decimals: 1)
| filter pctOfLimit &gt; 90
| fields k8s.cluster.name, k8s.namespace.name, k8s.pod.name, k8s.container.name, usedMiB, limitMiB, pctOfLimit
| sort pctOfLimit desc
| limit 50
```

```
// CrashLoop detection (last hour) — alerting condition
// The event reason is "BackOff"; "CrashLoopBackOff" appears in the message
text,
// so filter on the reason and read the message for detail.
fetch events, from:-1h
| filter event.provider == "KUBERNETES_EVENT"
| filter dt.kubernetes.event.reason == "BackOff"
| summarize {crashLoopEvents = countDistinctExact(event.id),
    affectedPods = countDistinctExact(dt.kubernetes.event.involved_object.name)}
```

```
// Error rate spike detection
fetch logs, from: now() - 1h
// status == "ERROR" also counts SEVERE, CRITICAL and FATAL logs; loglevel ==
"ERROR" misses them
| filter status == "ERROR" and isNotNull(k8s.namespace.name)
| summarize errors = count(), by:{k8s.namespace.name}
| filter errors &gt; 100
| sort errors desc
```

8. Query Templates

Reusable Query Patterns

Filter by Namespace:

```
| filter k8s.namespace.name == "NAMESPACE_NAME"
```

Filter by Cluster:

```
| filter k8s.cluster.name == "CLUSTER_NAME"
```

Time-based Analysis:

```
fetch logs, from:-DURATION
| summarize log_count = count(), by:{time_bucket = bin(timestamp, INTERVAL)}
| sort time_bucket asc
```

Top N Pattern:

```
| sort METRIC desc
| limit N
```

Summary

This notebook provided DQL query patterns for:

- Entity discovery and relationships
- Container and node metrics
- Log and event analysis
- Distributed tracing
- Multi-source correlation
- Dashboard visualizations
- Alerting conditions

References

- Dynatrace Query Language (DQL) reference (DT docs)
- smartscapeNodes command (DT docs)
- Set up Dynatrace on Kubernetes (DT docs)
- Kubernetes app — workloads + namespaces views (DT docs)
- Davis Problems app (DT docs)
- Effective pod resources (DT docs)
- ActiveGate 1.345 release notes (DT docs)
- ActiveGate 1.347 release notes (DT docs)

This notebook was AI-generated from community-submitted and publicly available sources. This notebook series is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.