

M2S-99: Best Practice Summary

Series: M2S — Managed to SaaS Migration | **Notebook:** 99 | **Created:** March 2026 | **Last Updated:** 10/01/2026

A definitive, actionable reference of every best practice extracted from the M2S Managed-to-SaaS Migration series (notebooks 01–09). Each practice specifies the exact setting or action, its priority, and its step. No hedging—follow these and your migration succeeds.

The 9-Step Migration Framework

The M2S series follows a structured, step-based approach to Managed-to-SaaS migration:

Step	Name	Focus
1	Discover	Understand SaaS Differences
2	Strategize	Define Your Migration Approach
3	Design	Create Target Architecture
4	Prepare	Readiness and Pre-Migration
5	Execute	Migrate Configuration and Agents
6	Integrate	Reconnect Integrations
7	Enable	User Enablement and Communication
8	Expand	Adopt New SaaS Capabilities
9	Optimize	Validate, Optimize, and Decommission

OneAgent Attribute Enrichment (1.333+): OneAgent can enrich all telemetry (metrics, spans, logs, events) with primary fields (`dt.security_context` , `dt.cost.costcenter`) and primary tags (`primary_tags.environment` , `primary_tags.team`) at the source. More efficient than auto-tags — feeds directly into OpenPipeline routing, bucket assignment, and Grail permissions. Configure via `oneagentctl --set-host-tag` or `--set-host-tag` at install time. See [docs](#).

The 11-Step Order of Operations (Upgrade Phase)

Within the upgrade phase, follow this precise execution order:

#	Operation	Description
1	Assess	Inventory current environment
2	Provision	SaaS tenant and access (SSO)
3	Install	New ActiveGates in parallel with old ActiveGates
4	Migrate	Configuration and integrations
5	Rebuild	Dashboards, zones, alerts
6	Redirect	OneAgents to SaaS
7	Reconnect	Integrations and extensions
8	Migrate	Any remaining configuration and integrations
9	Validate	Data flow and performance
10	Cutover	Full switch to SaaS
11	Decommission	Managed environment

Table of Contents

- [1. Step 1: Discover — Understand SaaS Differences](#)
- [2. Step 2: Strategize — Define Your Migration Approach](#)
- [3. Step 3: Design — Create Target Architecture](#)
- [4. Step 4: Prepare — Readiness and Pre-Migration](#)
- [5. Step 5: Execute — Migrate Configuration and Agents](#)
- [6. Step 6: Integrate — Reconnect Integrations](#)
- [7. Step 7: Enable — User Enablement and Communication](#)
- [8. Step 8: Expand — Adopt New SaaS Capabilities](#)
- [9. Step 9: Optimize — Validate, Optimize, and Decommission](#)

1. Step 1: Discover — Understand SaaS Differences

Practice	Recommended Setting/Value	Priority
Complete entity discovery before strategy	Run Entities API v2 inventory: <code>type(HOST)</code> , <code>type(SERVICE)</code> , <code>type(APPLICATION)</code> , <code>type(SYNTHETIC_TEST)</code> . Document counts in a spreadsheet before any other planning work.	Critical

Practice	Recommended Setting/Value	Priority
Plan for historic data loss	Historic metrics, logs, traces, problems, and session data cannot be migrated . Export critical reports before shutdown. Run dual environments to build SaaS baselines.	Critical
Plan tenant sizing against the host guideline	Dynatrace recommends roughly 25,000 hosts per environment (about 50,000 per cluster) as a sizing guideline — verify current thresholds with Dynatrace. The enforced ceiling is your licensed host-unit quota , a separate metric. Split into multiple environments when consolidating Managed clusters would exceed the recommendation.	Recommended
Align Managed and SaaS versions	There is no fixed minimum Managed version for the SaaS Upgrade Assistant — align the Managed cluster to the same major version as the target SaaS tenant rather than targeting a specific floor.	Critical
Use SaaS Upgrade Assistant for most migrations	Install the app on the target SaaS tenant. Assign <code>upgrade-assistant:environments:write</code> IAM policy to migration users. The SaaS Upgrade Assistant is the recommended tool for the majority of migrations.	Recommended
Use Monaco for tenant consolidation	When consolidating multiple Managed tenants with identical configuration names , use Monaco—the SaaS Upgrade Assistant cannot resolve name conflicts.	Recommended

2. Step 2: Strategize — Define Your Migration Approach

Practice	Recommended Setting/Value	Priority
Choose migration approach by environment size	<500 hosts: Big Bang. 500–2,000 hosts: Phased by environment. >2,000 hosts or complex integrations: Phased by region/application.	Critical
Define measurable success criteria	Set targets: 100% host coverage, 100% service discovery, <15 min data gaps, 100% alert delivery, 100% dashboard availability, 100% integration success.	Critical
Budget time for the manual remainder	Most configuration moves through the Upgrade Assistant; the small remainder (credentials, webhooks, custom scripts) takes most of the manual effort. "90/10" is community shorthand, not a documented ratio — the app's review screen gives your real split.	Recommended
Engage Dynatrace Professional Services early	Involve account team and PS during the Strategize phase, not during execution. Early engagement prevents avoidable rework.	Recommended

Practice	Recommended Setting/Value	Priority
Choose one migration tool	Pick one primary tool: SaaS Upgrade Assistant (recommended), Monaco, Terraform, or Settings API. Never mix approaches—Monaco YAML conflicts with the SaaS Upgrade Assistant. The rule is one writer per configuration schema per migration window; sequencing tools with an explicit ownership handoff is safe. For the Terraform path and the handoff pattern, see M2S-95.	Critical

3. Step 3: Design — Create Target Architecture

Practice	Recommended Setting/Value	Priority
Open outbound 443 to SaaS endpoints	Allow HTTPS (port 443) from all monitored hosts and ActiveGates to <code>{tenant-id}.live.dynatrace.com</code> and <code>{tenant-id}.apps.dynatrace.com</code> .	Critical
Use ActiveGate routing for restricted networks	If hosts cannot reach the internet directly, deploy Environment ActiveGates. OneAgents connect to AG on port 9999 ; AG connects outbound on 443 .	Critical
Have every network zone in SaaS before migrating	The Upgrade Assistant can import network zones (its Hub listing names them); confirm they arrived, create missing ones via Settings or the Settings API (<code>builtin:networkzones.zones</code>), then assign the new ActiveGates.	Critical
Deploy minimum 2 ActiveGates per network zone	Provides high availability within each zone. OneAgent auto-discovers available AGs.	Recommended
Configure SAML SSO with full message signing	IdP must sign the entire SAML message , not just the assertion. Azure AD meets this requirement by default. Failure causes authentication errors.	Critical
Confirm data residency region at provisioning	Select the correct region (US, EU, APAC) during tenant provisioning. Cannot be changed after provisioning.	Critical
Enforce TLS 1.2+ for all traffic	Dynatrace SaaS enforces TLS 1.2 minimum. Verify no legacy TLS 1.0/1.1 configurations on proxies or load balancers.	Critical
Ensure DNS resolves SaaS domains	Verify DNS resolution for <code>{tenant-id}.live.dynatrace.com</code> , <code>{tenant-id}.apps.dynatrace.com</code> , and <code>*.dynatrace.com</code> .	Critical
Match network zones to physical topology	Name zones by datacenter or region (e.g., <code>datacenter-east</code> , <code>aws-us-east-1</code>). Define alternative zones for failover.	Recommended
Size ActiveGates by host count	Up to 500 hosts: 2 CPU / 4 GB RAM / 20 GB disk . 500–1,500: 4 CPU / 8 GB / 40 GB . 1,500–5,000: 8 CPU / 16 GB / 80 GB . >5,000: scale horizontally with multiple AGs.	Recommended

4. Step 4: Prepare — Readiness and Pre-Migration

Practice	Recommended Setting/Value	Priority
Align the Managed version before upgrading	The SaaS Upgrade Assistant has no fixed minimum Managed version — align the Managed cluster to the same major version as the target SaaS tenant rather than a specific floor. Upgrade the Managed cluster first if the versions differ.	Critical
Coordinate dual licensing	Work with Dynatrace account team to arrange temporary overlap licensing for the period both Managed and SaaS run simultaneously.	Critical
Deploy new SaaS ActiveGates in parallel	Install new SaaS-connected AGs alongside existing Managed AGs before migrating OneAgents. Validates connectivity without impacting monitored hosts.	Critical
Install SaaS Upgrade Assistant	Install the app on the target SaaS tenant and verify connectivity to the Managed cluster. Confirm all required permissions are in place.	Critical
Announce configuration freeze	Notify all teams that no configuration changes should be made to the Managed environment during the migration window. Document the freeze start and end dates.	Recommended
Test rollback procedure	Document the Managed server URL, environment ID and tenant token. Rollback: <code>oneagentctl --set-server=<managed-url> --set-tenant=<managed-env-id> --set-tenant-token=<token> --restart-service</code> . Test on one host before bulk migration.	Critical
Test connectivity before migration	Run <code>curl -v https://{tenant-id}.live.dynatrace.com/api/v1/time</code> from monitored hosts and ActiveGate servers before scheduling the migration window.	Critical
Verify OneAgent versions are within support window	OneAgent support window is 9 months (Standard) / 12 months (Enterprise) . Check oldest deployed versions before migration. Upgrade outdated agents first. SaaS 1.347 (staged tenant rollout) rejects OneAgent 1.241 and earlier — those hosts stop reporting, not just fall out of support (M2S-01).	Recommended

5. Step 5: Execute — Migrate Configuration and Agents

Practice	Recommended Setting/Value	Priority
Migrate configurations BEFORE redirecting OneAgents	Deploy foundational settings (management zones, tags, service detection rules) to SaaS before any agents start reporting.	Critical

Practice	Recommended Setting/Value	Priority
Follow the 4-wave deployment order	Wave 1: Management zones, auto-tagging rules, host groups. Wave 2: Service detection, request attributes, deep monitoring. Wave 3: Alerting profiles, anomaly detection, SLOs. Wave 4: Dashboards, remaining configs.	Critical
Use <code>oneagentctl</code> to reconfigure (not reinstall)	Run one call: <code>oneagentctl --set-server="https://{tenant}.live.dynatrace.com:443/communication" --set-tenant={tenant} --set-tenant-token={token} --restart-service</code> . Omitting <code>--set-tenant</code> leaves the agent on its Managed environment ID. Preserves the installation and host metadata; entity IDs are re-minted.	Critical
Restart application processes after migration	Full-stack monitoring requires process restarts—Java, .NET, Node.js, PHP all inject instrumentation at process startup. Without restart: host metrics flow but no distributed tracing, no service detection, no code-level visibility .	Critical
Migrate non-production first, then production	Validate data flow on non-prod hosts before touching production. Apply lessons learned to each subsequent wave.	Critical
Download deploy result CSVs for audit	After each wave, download the deployment result CSV from SaaS Upgrade Assistant. Archive these for compliance and troubleshooting.	Recommended
Use SaaS Upgrade Assistant selective import	Deploy configuration types incrementally using Smart Selective Import. Smart dependency management auto-adds required configs.	Recommended
Preview all changes before deploying	Use the SaaS Upgrade Assistant Preview Changes feature to verify edits. The app retains original values for rollback reference.	Recommended
Manually recreate Credentials Vault entries	Cannot be exported. Re-enter all credentials (cloud platform integrations, extension credentials) directly in SaaS.	Critical
Generate new API tokens in SaaS	Managed tokens do not work in SaaS. Create new tokens with minimal required scopes for each use case.	Critical
Use Ansible/automation for bulk reconfiguration	For large environments, use configuration management (Ansible, Puppet, Chef) to execute <code>oneagentctl</code> commands and rolling application restarts across all hosts.	Recommended

6. Step 6: Integrate — Reconnect Integrations

Practice	Recommended Setting/Value	Priority
Recreate webhooks with SaaS URLs	Endpoint URLs change for SaaS. Create new Slack, Teams, PagerDuty, ServiceNow, and custom webhook integrations with SaaS URLs.	Critical

Practice	Recommended Setting/Value	Priority
Update all API base URLs	Change from <code>{managed-url}/e/{env-id}</code> to <code>{tenant}.live.dynatrace.com</code> . Update tokens in all CI/CD pipelines and automation scripts.	Critical
Test alert delivery end-to-end	Trigger a test alert and confirm delivery through every notification channel (email, Slack, Teams, PagerDuty, ServiceNow).	Critical
Recreate synthetic private locations	Deploy new Synthetic ActiveGates in SaaS. Private locations are infrastructure-specific and do not transfer.	Recommended
Update CI/CD pipelines	Replace Managed API endpoints and tokens in all deployment pipelines, quality gates, and automated testing integrations.	Critical
Deploy dedicated AGs for Extensions 2.0	Plan host-based ActiveGates for remote extensions (SQL extensions can also run on Kubernetes through the Dynatrace Operator). Deploy a separate AG group for extension execution.	Recommended
Remove hardcoded entity IDs from dashboards	Before importing dashboards, replace hardcoded entity IDs with entity selectors. Update management zone IDs and dashboard owners.	Recommended

7. Step 7: Enable — User Enablement and Communication

Practice	Recommended Setting/Value	Priority
Communicate migration to all users	Send advance notice with migration timeline, expected impacts, new login URLs, and support channels. Communicate before, during, and after each migration wave.	Critical
Deliver persona-based training	Tailor training by role: SREs get DQL and alerting, developers get distributed tracing and code-level visibility, managers get dashboards and reporting.	Recommended
Update all documentation	Replace Managed URLs, procedures, and screenshots with SaaS equivalents in runbooks, architecture diagrams, onboarding guides, and disaster recovery plans.	Critical
Establish support channels	Create dedicated Slack/Teams channels for migration questions. Designate migration champions in each application team.	Recommended
Map Managed roles to SaaS IAM policies	Cluster admin > Account admin. Environment admin > Environment admin. Monitor user > Viewer + specific policies. Custom roles > Custom IAM policies.	Critical
Replace LDAP with SAML	Dynatrace documents SAML 2.0 federation for SaaS sign-in. Migrate LDAP users to SAML 2.0 SSO through your IdP.	Critical
Sign the entire SAML message	Dynatrace rejects assertion-only signatures with <code>400 Bad Request</code> . Microsoft Entra signs only the assertion by default — set <i>Sign SAML response and assertion</i> .	Critical

Practice	Recommended Setting/Value	Priority
Filter SAML group claims to Dynatrace groups only	Azure Entra limit: 150 groups per user in SAML claim. Filter to Dynatrace-related groups to stay under the limit.	Recommended

8. Step 8: Expand — Adopt New SaaS Capabilities

Practice	Recommended Setting/Value	Priority
Adopt Grail for unified querying	Replace ad-hoc USQL queries with Notebook-based DQL analysis. Grail provides a unified data lakehouse for logs, metrics, traces, events, and entities.	Recommended
Configure OpenPipeline for log masking	Configure log processing rules in OpenPipeline to redact PII (SSNs, credit card numbers, email addresses) before storage.	Recommended
Enable PII masking at capture	Enable masking on request attributes that capture user input, account numbers, or personal data, and configure session replay masking for RUM. OpenPipeline masking (DPL, not regex — FAQ-15) covers the other ingest channels.	Critical
Implement Workflows for automation	Replace Managed problem notifications with SaaS Workflow triggers + HTTP Request actions. Recreate custom webhook logic as workflow steps.	Recommended
Right-size data retention for cost optimization	Configure Grail bucket retention by data type. Logs: set retention based on compliance needs. Metrics: 15 months included in Grail, extensible to 10 years at extra cost (FAQ-11). Use <code>bucket :</code> targeting in queries to limit scan scope.	Recommended
Explore Dynatrace Assist for AI-assisted analysis	Enable Dynatrace Assist for natural language querying and root cause analysis.	Optional

9. Step 9: Optimize — Validate, Optimize, and Decommission

Practice	Recommended Setting/Value	Priority
Allow for the baseline relearn window	In community practice: availability ~2–3 days, response time and error rate ~1–2 weeks, resource usage and traffic ~2–4 weeks. Measure each host's history depth with the FAQ-25 § 5 query instead of guessing. Do not disable alerting.	Critical
Tune alert thresholds after the baseline period	Not during it — thresholds set against a half-learned baseline get baked in. Then: tune noisy detectors, set a Minimum duration on notifying workflows, and fix missing alerts.	Recommended

Practice	Recommended Setting/Value	Priority
Compare entity counts against inventory	Run <code>fetch dt.entity.host \ summarize count()</code> (and <code>service</code> , <code>application</code> , <code>process_group</code> , <code>synthetic_test</code>). Counts must match the planning-phase inventory.	Critical
Verify metrics flow with no gaps >15 minutes	Run <code>timeseries avg(dt.host.cpu.usage), from:-1h, by: {dt.entity.host}</code> and check for nulls. Any host returning null has a data gap.	Critical
Validate log ingestion is continuous	Run <code>fetch logs, from:-1h \ summarize count(), by: {bin(timestamp, 5m)}</code> and confirm no 5-minute buckets with zero count.	Critical
Confirm distributed traces are flowing	Run <code>fetch spans, from:-1h \ summarize count(), by: {bin(start_time, 5m)}</code> . Zero spans after agent migration means application processes need restart.	Critical
Get stakeholder sign-off	Obtain written approval from: Platform Team Lead, Security Team, Application Teams, Executive Sponsor.	Critical
Keep Managed running 2–4 weeks post-migration	Maintain access for historical reference and comparison. Decommission only after full validation period.	Recommended
Archive migration artifacts before decommission	Save SaaS Upgrade Assistant deploy result CSVs, entity inventory spreadsheets, and configuration mapping documents before decommissioning Managed.	Recommended
Validate all dashboard tiles show data	Open every migrated dashboard. Tiles with "No data" indicate missing entity mappings or incorrect management zone IDs.	Recommended
Set API token expiration dates	Set expiration on all tokens. Store in secrets management (HashiCorp Vault, AWS Secrets Manager). Rotate regularly.	Recommended

This notebook was AI-generated from community-submitted and publicly available sources. This notebook series is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.