SLO-05: SLOs as Code

> **Series:** SLO — Service Level Objectives | **Notebook:** 5 of 6 | **Created:** June 2026 | **Last Updated:** 11/09/2026

Overview

A validated SLO that lives only in the UI is one accidental click from gone, and impossible to reproduce across environments. This notebook covers promoting SLOs into version control: the `dynatrace_platform_slo` Terraform resource and SLO Service Public API for the modern app, the classic `dynatrace_slo_v2` / `builtin:monitoring.slo` path it replaces (blocked at upgrade), the Monaco alternative, and the API path — with a deliberate emphasis on verifying field names at the source rather than copying a payload that may be stale.

Table of Contents

1. Why Version SLOs
2. The Schema and Terraform Resource
3. Terraform Worked Example
4. Monaco Alternative
5. API and CI/CD

Prerequisites

Requirement	Details
Dynatrace Environment	SaaS Gen3 with the SLO app


Requirement	Details
Tooling	Terraform with the `dynatrace-oss/dynatrace` provider, or Monaco
Auth	**OAuth client** (`DT_CLIENT_ID` / `DT_CLIENT_SECRET` / `DT_ACCOUNT_ID`) with `slo:slos:read` + `slo:slos:write` for `dynatrace_platform_slo` ; a classic API token only if you still maintain `dynatrace_slo_v2` — see AUTOM-04 §3
Prior reading	SLO-02 (the SLI query you will codify), AUTOM-04 / AUTOM-07 (provider auth, CI/CD)

1. Why Version SLOs

SLOs are configuration, and configuration that matters belongs in source control:

- **Reproducible across environments** — the same SLO in dev, staging, and prod from one definition.
- **Reviewable** — a target change goes through a PR, not a quiet UI edit.
- **Recoverable** — an accidental deletion is a `terraform apply` away from restored.

The workflow mirrors AIOPS-02's stance on detectors: **prototype in the app, promote to code once it matters.**



2. The Schema and Terraform Resource

Surface	Modern SLO app	SLO Classic
API	**SLO Service Public API**	Service-level Objectives API classic (`/api/v2/slo`) — **blocked at upgrade**
Terraform resource	`dynatrace_platform_slo` (provider v1.78.0+; OAuth client with `slo:slos:read` / `slo:slos:write`)	`dynatrace_slo_v2` (classic `slo.*` + `settings.*` token scopes)
Monaco	`type: slo-v2` — supported since Monaco v2.22 (despite the name, this is the **modern** type, unrelated to the classic Terraform `dynatrace_slo_v2`)	`builtin:monitoring.slo` via `--settings-schema` — **blocked at upgrade**
Settings 2.0 schema	none — the SLO service is the store	`builtin:monitoring.slo`

> **What "blocked at upgrade" rests on (checked 08/28/2026; quote re-read 09/28/2026).** The phrase is the **tenant upgrade readiness scan's** classification, read 07/31/2026 — not documentation. No Dynatrace page restates it; the published upgrade guidance is softer: *"An automated upgrade flow is under consideration; however, given the highly customized nature of SLOs, manual review is expected to yield the best results."* A readiness scan reporting what a tenant will not carry across and a docs page describing a manual migration are answering different questions, so they can both be right — but they imply different urgency. **Run the scan against your own tenant** before planning the work.
>
> **Corrected 07/31/2026.** This section previously presented `builtin:monitoring.slo` / `dynatrace_slo_v2` as *the* config-as-code path. They are the **classic** generation. `dynatrace_slo_v2` authenticates with classic `slo.read` / `slo.write` plus `settings.read` / `settings.write` and writes through `builtin:monitoring.slo` ; the modern app has its own SLO Service Public API, reached by `dynatrace_platform_slo` with OAuth `slo:slos:*` scopes. The readiness scan flags both classic surfaces as blocked at upgrade, so codifying new SLOs as `dynatrace_slo_v2` puts them on a path that stops working. Verify argument names

> at the provider docs before writing HCL — the note below applies to `dynatrace_platform_slo` too.

The DQL-SLI gap was a property of the classic resource, and `dynatrace_platform_slo` closes it. `dynatrace_platform_slo` takes the SLI as a **DQL query** in `custom_sli.indicator` — the same query shape SLO-02 builds and the SLO app's Custom SLO uses, producing a timeseries field named `sli`. So the query you validated in a notebook goes into the HCL unchanged apart from the timeframe, which the SLO's `criteria` supplies. The classic `dynatrace_slo_v2` resource cannot do this: its SLI field (`metric_expression`) takes a **classic metric-selector expression** — e.g. `100*(builtin:service.requestCount.server:splitBy())/(...)` — so a span-ratio or log/bizevent-derived SLI (SLO-02's latency and custom examples) has no classic Terraform form at all. That is one more reason new SLOs belong on the modern resource.

> **Verify the exact argument names against the provider docs before you write HCL.** The provider schema evolves between releases, and copying a stale payload is precisely how the field-authored alerting document ended up with an SLO API body that would not apply. The modern example below follows the `platform_slo` resource docs (Dynatrace GitHub) as read on 09/28/2026 (provider v1.105.0); the classic example follows the `slo_v2` resource docs as fetched on 07/01/2026. Treat both pages as authoritative going forward.

Modern — `dynatrace_platform_slo` (use this for new SLOs)

Environment-wide request availability, using the SLO-02 availability SLI (live-validated there) with its `from:` / `interval:` removed — the SLO's `criteria` block owns the evaluation window:

```
# dynatrace_platform_slo — schema read from the provider's resource docs
09/28/2026 (v1.105.0)
# Auth: OAuth client only — DT_CLIENT_ID / DT_CLIENT_SECRET / DT_ACCOUNT_ID,
# scopes slo:slos:read + slo:slos:write. A Platform Token does not drive this
resource.
resource "dynatrace_platform_slo" "service_availability_30d" {
  name        = "Service Availability - 30d"
  description = "Request success ratio across services, rolling 30 days"
  tags        = ["team:platform", "tier:gold"]

  criteria {
    criteria_detail {
      target         = 99.5      # the goal (SLO-01 §4)
      warning        = 99.9      # early-warning line, above target
      timeframe_from = "now-30d" # rolling 30-day window
      timeframe_to   = "now"
    }
  }

  # The SLI is DQL. It must produce a timeseries field named `sli` (a
percentage).
  # No from:/interval: here — the criteria block supplies the timeframe.
  custom_sli {
    indicator = &lt;&lt;-EOT
      timeseries {
        total    = sum(dt.service.request.count),
        failures = sum(dt.service.request.failure_count)
      }
      | fieldsAdd sli = ((total[] - failures[]) / total[]) * 100
      | fieldsRemove total, failures
    EOT
  }
}
```

Classic — `dynatrace_slo_v2` (existing SLOs on unupgraded tenants only)

> **Dynatrace Classic.** Keep this form only to manage SLOs that already exist as `builtin:monitoring.slo` objects while your tenant is still on the classic surface — the readiness scan flags that schema as blocked at upgrade (see above). Do not author new SLOs this way; move existing ones to `dynatrace_platform_slo` as part of the upgrade.

```
# dynatrace_slo_v2 — schema verified at the provider registry 07/01/2026
# Metric-based SLI (classic metric-selector syntax) — see the gap callout in
Section 2
# regarding DQL-only SLIs, which this resource does not accept directly.
resource "dynatrace_slo_v2" "web_availability_30d" {
  name               = "Web Service Availability - 30d"
  custom_description = "Request success ratio for the critical web service,
rolling 30 days"
  enabled            = true
  evaluation_type    = "AGGREGATE"

  # rolling 30-day window
  evaluation_window = "-30d"

  # entitySelector syntax (not a DQL filter) — scopes the SLO to web services
  filter = "type(SERVICE),serviceType(WEB_SERVICE,WEB_REQUEST_SERVICE)"

  # classic metric-selector expression — good / total as a percentage
  # keys checked against the classic built-in metrics list 11/09/2026
  metric_expression = "100*
(builtin:service.errors.total.successCount:splitBy())/(builtin:service.request
Count.total:splitBy())"
  metric_name       = "web_availability_30d"

  target_success = 99.5
  target_warning = 99.9

  # required block — burn-rate visualization + optional fast-burn threshold
(SLO-04)
  error_budget_burn_rate {
    burn_rate_visualization_enabled = true
    fast_burn_threshold             = 14
  }
}
```

3. Terraform Worked Example — Notes

Modern resource (`dynatrace_platform_slo`):

- **`criteria`** → **`criteria_detail`** carries `target` and `warning` (the goal and the early-warning line from SLO-01 §4) and the evaluation window as `timeframe_from` / `timeframe_to` (`now-30d` → `now` for a rolling 30 days). `criteria` is required; `criteria_detail` can repeat when you need more than one window.

- **`custom_sli.indicator`** is DQL and must yield a timeseries field named **`sli`**. Build and validate it in a notebook first (SLO-02), then paste it in without `from:` / `interval:`. The alternative, `sli_reference`, points at an SLI template instead of inlining a query.
- **Scope** with `custom_sli.filter_segments` — the SLO equivalent of applying a segment (ORGNZ) — or with a `filter` inside the DQL. An unscoped SLO measures the whole environment, which is rarely what you want outside an example.
- **Auth is an OAuth client, not a Platform Token.** The resource docs require `DT_CLIENT_ID` / `DT_CLIENT_SECRET` / `DT_ACCOUNT_ID` with `slo:slos:read` / `slo:slos:write`; see AUTOM-04 §3 for running it alongside Platform-Token resources in one provider block.
- **Export is opt-in** — name `dynatrace_platform_slo` explicitly when exporting (Section 5).

Classic resource (`dynatrace_slo_v2`) — only while you still maintain classic SLOs:

- **`target_success`** and **`target_warning`** are the goal and warning line (not the shorter `target` / `warning` the modern resource uses).
- **`metric_expression`** is a classic metric-selector string, not DQL — see the Section 2 gap.
- **`filter`** uses entitySelector syntax (`type(SERVICE),serviceType(...)`), not a DQL filter clause.
- **`error_budget_burn_rate`** **is a required block** — `fast_burn_threshold` inside it pairs with the SLO-04 burn-rate recipe.
- **Auth** is a classic API token (`slo.*` + `settings.*` scopes).

State handling follows the same rules as every other Dynatrace Terraform resource — see AUTOM-09 for state-backend setup.

4. Monaco Alternative

If your shop standardises on Monaco rather than Terraform, use the **`slo-v2`** type for a modern, DQL-based SLO. Monaco has supported it since v2.22. It is a different type from the classic `slo` type, and the Monaco docs say the two cannot be swapped. The docs' example of an SLO with a custom DQL SLI:

```
configs:
  - id: custom-sli          # an SLO that uses a custom DQL query as its SLI
    type: slo-v2
    config:
      name: custom-sli
      template: custom-sli.json
```

The `slo-v2` type needs no extra type fields. Validate the SLI query in a notebook first. Then export the working SLO with `monaco download` to capture `custom-sli.json`, rather than hand-writing the JSON.

Classic — inventory only

Existing Monaco projects may still hold the classic settings object below, which targets the blocked `builtin:monitoring.slo` schema. It is kept here because running `monaco download` against it is how you inventory what needs moving:

```
configs:
  - id: web-availability-30d
    type:
      settings:
        schema: builtin:monitoring.slo
        scope: environment
    config:
      template: web-availability-30d.json
      skip: false
```

The classic schema takes a metric expression, not DQL, so a DQL SLI has no classic form. Move it to `slo-v2`, not into this object.

> **Sources:** Monaco YAML configuration: SaaS type fields (DT docs) — *"These two configuration types are incompatible, and deploying a slo configuration as a slo-v2 or vice versa results in the API rejecting the request."*; *"This type does not require additional fields."* dynatrace_slo_v2 (Dynatrace provider docs), the Terraform twin of `builtin:monitoring.slo`, takes a `metric_expression`.

5. API and CI/CD

For direct API automation, use the **SLO Service Public API** — the modern app's own endpoint. This is not `/api/v2/slo`, which is the Service-level Objectives API *classic* and is flagged blocked at upgrade by the readiness scan; nor the older v1 SLO API. Rather than reproduce a request body that may drift, generate it from a working SLO:

1. Create and validate one SLO in the app.
2. Read it back via the API (or `monaco download` / `terraform-provider-dynatrace -export`) to capture the exact current schema.
   - **`dynatrace_platform_slo` will not appear in a default export.** Its resource documentation states: *"This resource is excluded by default in the export utility, please explicitly specify the resource to retrieve existing configuration."* Name it explicitly — `terraform-provider-dynatrace -export dynatrace_platform_slo` — or the step above returns nothing for exactly the resource you are trying to capture, which reads as "no SLOs are codified" rather than "this resource is opt-in".
3. Template that shape for the rest.

This "export a known-good object" approach is the antidote to stale-payload errors, and it is also the path of least resistance for a DQL-only SLI, since the classic resource's `metric_expression` field cannot carry one (Section 2) — on the modern resource it goes straight into `custom_sli.indicator`. For the full CI/CD pattern — plan on PR, gated apply, three-way validation — see AUTOM-07 (pipelines) and AUTOM-96 (GitHub Actions LAB); the SLO resource slots into exactly the same pipeline as any other Dynatrace config.

A codified SLO and a codified deployment gate are two different resources answering two different questions — see **SLO-06** for the `dynatrace_site_reliability_guardian` counterpart to everything in this notebook, including how to reuse an SLO's SLI query as a guardian objective (`REFERENCE_SLO` points only at a Classic SLO, and the docs mark it deprecated).

> **Sources:** Service-Level Objectives (DT docs), dynatrace_slo_v2 resource (Dynatrace provider docs), dynatrace_platform_slo resource (Dynatrace provider docs) — the modern resource this section recommends: *"covers configuration for platform service-level objectives"*, Dynatrace SaaS only, OAuth **View SLOs** (`slo:slos:read`) / **Create and edit SLOs** (`slo:slos:write`), and *"This resource is excluded by default in the export utility, please explicitly specify the resource to retrieve existing configuration."*, platform_slo.md (Dynatrace GitHub) — the same resource doc at its source; the

> registry page renders client-side, so it is the repository copy that makes the two quotes above machine-verifiable. SLO Service Public API (DT docs) — endpoints are `/slos` and `/objective-templates`; the classic surface is documented separately as *Service-level Objectives API classic*, Upgrade from Service-Level Objectives Classic (DT docs) — the version gates in §2, verbatim: *"Configuration as Code via Terraform overview support the SLO Service Public API since v1.78.0"* and *"Configuration as Code via Monaco overview supports the SLO Service Public API since v2.22."*, Create service-level objectives (DT docs), Monaco configuration (DT docs). Terraform schema (`builtin:monitoring.slo`, `evaluation_window`, `target_success`/`target_warning`, required `error_budget_burn_rate` block) verified at the provider registry 07/01/2026; `dynatrace_platform_slo`'s schema (`criteria`/`criteria_detail`, `custom_sli.indicator`, `filter_segments`, `sli_reference`), OAuth scopes and export exclusion re-verified at source 09/28/2026 (provider v1.105.0). **Readiness scan:** the "blocked at upgrade" classification is from the tenant upgrade readiness scan, read 07/31/2026; re-checked 08/28/2026 against both upgrade pages and the API references, where it is not restated. **Derived:** the metric-expression-vs-DQL-sli gap in Section 2 combines the two resources' schemas (`metric_expression` vs `custom_sli.indicator`) with the Create-SLO docs' DQL `sli`-field description — no source states the gap explicitly.

This notebook was AI-generated from community-submitted and publicly available sources. This notebook series is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.