ADOPT-06: Maximizing Platform Value — Coverage Audit and Staged Enablement

> **Series:** ADOPT — Observability Adoption & Maturity | **Notebook:** 6 of 6 | **Created:** July 2026 | **Last Updated:** 10/12/2026

Overview

Most Dynatrace estates run below the coverage they pay for, and well below the coverage that would change outcomes: hosts in Infrastructure mode on the revenue path, Full-Stack hosts whose main process group has deep monitoring switched off, logs shipped to a tool nobody correlates, RUM "planned for next quarter" three quarters running. The impact of each gap — what specifically stops working — is cataloged in **FAQ-12** (*Coming from Another Tool — How Partial Enablement Handicaps Your Dynatrace Coverage*); this notebook is the **program** that closes the gaps: audit current coverage, segment the estate, enable in waves, and prove value at a gate before each next wave.

This is a maturity play, not a switch-flip: it deliberately builds on ADOPT-01 (where you are on the maturity model), ADOPT-02 (platform health), and ADOPT-03 (the success metrics that become your value gates).

Table of Contents

1. Why Coverage Gaps Erode Value
2. Wave 0 — Audit Current Coverage
3. Segment the Estate
4. Waves 1–4 — Staged Enablement
5. Value Gates — Proving the Uplift

6. Recommended Approach

Prerequisites

Requirement	Details
Dynatrace Environment	SaaS on DPS (Discovery mode and the mode-split billing series are DPS constructs).
Permissions	Settings access for monitoring modes and process-group monitoring rules; `storage:system:read`, `storage:logs:read` and `storage:metrics:read` for the audit DQL.
Companion reading	**FAQ-12** — the per-capability impact matrix this program operationalizes; ADOPT-01/02/03 for maturity level, health baseline, and metrics.
Audience	Platform / Observability Lead running an enablement program; account teams building the customer business case.


1. Why Coverage Gaps Erode Value

The short version of FAQ-12 §3: Dynatrace's capabilities stack — code modules produce traces, traces produce services, services complete Smartscape, topology powers Davis root-cause analysis, RUM attaches user impact, logs supply the evidence. Because the layers feed each other, **the marginal value of each layer is higher when the others are on** — and the marginal damage of each gap is bigger than the layer itself. An estate at 60% coverage does not get 60% of the value; it gets the intersection, and the intersection is where the expensive questions ("what broke, why, who is affected") go unanswered.

The program consequence: enabling in **connected segments** (one application's full path at Full-Stack + logs + RUM) beats enabling one layer estate-wide. A fully-covered revenue path demonstrates Davis RCA, user-impact statements, and trace-context logs on day one — the demo that funds the next wave.

For the per-capability breakdown (what exactly stops working without Full-Stack, deep monitoring, tracing, logs, RUM, synthetic, or AppSec), use the FAQ-12 impact matrix — this notebook does not repeat it.

2. Wave 0 — Audit Current Coverage



Run the audit before any enablement conversation — most estates find at least one surprise. Four measurements:

Hosts by monitoring mode — read from the billing usage events, which name the capability each host was charged under. Do not use the classic `monitoringMode` host property for this: it is empty for many hosts. On the validation tenant (10/01/2026), 29 of the 36 hosts billed as Full-Stack had no `monitoringMode` value, so a breakdown by that field hid most of the Full-Stack estate in a null bucket. `smartscapeNodes "HOST"` does not expose a mode field either.

> **SaaS 1.347 — staged tenant rollout from 09/16/2026:** billing usage events are moving their host ID from `dt.entity.host` to `dt.smartscape.host` . Verbatim: *"If you use custom DQL queries that reference entity ID attributes in billing usage events, review and update them to the new Smartscape attribute names."* The query below reads `coalesce(toString(dt.smartscape.host), dt.entity.host)` , so it returns the same hosts before and after the change reaches your tenant (on the validation tenant both fields were written, with identical values, on 10/05/2026). What's new in SaaS 1.347 (DT docs).

```
// Wave 0 — hosts by the capability they were billed under (DPS), last 24
hours.
// A host can appear in more than one row (e.g. Full-Stack and Code
Monitoring).
fetch dt.system.events, from:-24h
| filter event.kind == "BILLING_USAGE_EVENT"
// SaaS 1.347 moves the host ID to dt.smartscape.host; coalesce reads
whichever field your tenant writes.
| fieldsAdd host = coalesce(toString(dt.smartscape.host), dt.entity.host)
| filter isNotNull(host)
| summarize {hosts = countDistinctExact(host)}, by:{billed_as = event.type}
| sort hosts desc
```

Log coverage — hosts actually shipping logs vs. the inventory above:

```
// Wave 0 — log coverage in the last 24 h: hosts attributed to log records
fetch logs, from:-24h
| summarize {hosts_reporting_logs = countDistinctExact(dt.entity.host),
log_records = count()}

// Count dt.entity.host, not host.name: on the validation tenant (10/01/2026)
the same day of logs
// carried 22 distinct dt.entity.host values but only 9 distinct host.name
values.
```

Consumption by mode — the cost-side mirror of the mode audit, using the pre-aggregated billing series (worked patterns in FINOPS-01 §5):

```
// Wave 0 — consumption split across the three host-monitoring tiers, last 7
days.
// rate:1h turns each daily bucket into GiB-hours (Full-Stack) or host-hours
(Infrastructure,
// Discovery) per hour — that is, the average monitored footprint that day.
Multiply by 24 for the
// day's total.
timeseries {
  full_stack = sum(dt.billing.full_stack_monitoring.usage, rate:1h),
  infrastructure = sum(dt.billing.infrastructure_monitoring.usage, rate:1h),
  discovery = sum(dt.billing.foundation_and_discovery.usage, rate:1h)
}, from:-7d, interval:24h
```

Deep-monitoring exceptions are configuration, not telemetry: review **Settings → Processes and containers → Process group monitoring** for rules that switch off service/code-level monitoring — a Full-Stack host whose main workload is excluded

delivers Infrastructure value at Full-Stack cost (FAQ-12 gotcha #1). Record all four measurements as the Wave-0 baseline; every value gate re-runs them.

> **Query provenance:** all three queries were executed live on a SaaS tenant 10/01/2026 (36 hosts billed as Full-Stack and 22 as Code Monitoring over 24 h; 22 hosts shipping 24.7M log records in 24 h; the daily Full-Stack series averaged about 170 GiB-hours per hour, matching the billing events). RUM coverage (`fetch user.sessions, from:-24h | summarize sessions = count()`) passed the DQL verifier but the validation token lacked `storage:user.sessions:read` — verify in your tenant.

3. Segment the Estate

Match mode to segment before matching budget to mode (the documented guidance, expanded in FAQ-12 §6):

Segment	Target mode	Rationale
Revenue-path / business-critical applications	**Full-Stack** (+ logs, RUM, AppSec)	Where tracing, Davis RCA, user impact, and runtime security earn their keep — the docs' explicit Full-Stack recommendation
Backing services (databases, queues, messaging)	**Infrastructure**	Saturation/disk/network/process health; transaction context comes from the app tier calling them
Long-tail / undifferentiated fleet	**Discovery**	Cheap inventory + upgrade signals — designed exactly for "the remainder of your infrastructure"
Short-lived, frequently-restarting process groups	Per-PG deep-monitoring exclusion	The documented injection-overhead case — a rule, not a host-mode decision
Decommission-scheduled hosts	Discovery or none	No value accrues to a host with a shutdown date

Use ADOPT-01's maturity assessment to decide *which applications* count as revenue-path — the maturity interviews usually surface two or three that the infrastructure team would not have picked.

4. Waves 1–4 — Staged Enablement

Wave	Enable	Mechanics to plan	Why this order
1 — Core apps Full-Stack	Revenue-path apps → Full-Stack; their backing services → Infrastructure	Code modules attach at **process start** — schedule restarts into the change window, or coverage stays dark	Everything else multiplies off this layer
2 — Logs	Log ingestion on the Full-Stack segment; OpenPipeline routing + bucket strategy (ORGNZ); log-derived metrics for recurring queries (FAQ-09)	Auto-discovery covers OneAgent hosts (FAQ-08); plan API/forwarder paths for the rest	Logs land in trace context only where traces exist — enabling after Wave 1 maximizes their value
3 — RUM + Synthetic	RUM on the covered applications; synthetic on must-not-fail endpoints	Privacy review (masking levels, opt-in — WEBRUM/MOBL); baselines start accruing at enablement, not before	User-impact statements need the backend traces from Wave 1 to correlate against
4 — AppSec + optimize	RVA/RAP on the code modules already in place; long tail → Discovery; deep-monitoring exception cleanup	AppSec rides Wave 1's modules — no new injection decision required	Security lands last only mechanically; decide it *with* Wave 1 (FAQ-12's prerequisite trap)

Each wave is one connected segment end-to-end, not one layer estate-wide (§1). Deployment mechanics per layer live in ONBRD; this notebook owns the sequencing.

5. Value Gates — Proving the Uplift

A wave earns the next wave by moving a metric that existed at Wave 0. Use ADOPT-03's success-metric definitions; the canonical gate per wave:

Gate after	Metric	Evidence source
Wave 1	MTTR on covered services vs. the Wave-0 baseline; % of problems with a named root cause	`fetch dt.davis.problems` duration analysis (AIOPS-03 patterns)
Wave 2	% of investigations where log evidence appears in problem context; log-derived metrics replacing recurring log scans (FAQ-09 economics)	Problem review + FINOPS-01 query-cost trend
Wave 3	% of problems carrying a user-impact statement; experience SLO coverage of revenue paths	Problems app + SLO series
Wave 4	Reachable-vulnerability backlog trend; % of estate in a deliberate (not default) mode	APPSEC-10 governance views + re-run Wave-0 audit

Re-run the Wave-0 audit queries at every gate — coverage decays between waves (new hosts land in default modes; exclusion rules outlive their incidents). The quarterly re-audit is what makes this a program instead of a project.

6. Recommended Approach

1. **Run Wave 0 this week.** Four measurements, three of them DQL — the audit itself is a one-day exercise and it usually pays for the meeting that reviews it.
2. **Pick one revenue path** for Wave 1, not a host list — a connected segment demonstrates the compounding value (§1) that a scattered enablement never shows.
3. **Decide AppSec inside the Wave-1 decision** even though it activates in Wave 4 — it changes no mechanics (same code modules) but avoids re-opening the injection conversation later.
4. **Publish the gates before Wave 1 starts.** Value gates chosen after the fact convince nobody; the Wave-0 baseline is what makes the uplift measurable.
5. **Institutionalize the re-audit** — quarterly, owned, on a calendar. Coverage entropy is the steady state; the program is what fights it.

Summary

Coverage gaps are a value decision usually made by default rather than on purpose. This program makes it deliberate: measure what you have (Wave 0), match mode to segment, enable connected paths in waves, and prove each wave at a gate using metrics that existed before you started. The impact catalog lives in FAQ-12; the maturity frame in ADOPT-01; the metrics in ADOPT-03; the cost mirror in FINOPS.

Next Steps

- **FAQ-12** — the per-capability impact matrix behind every segmentation argument in this notebook.
- **ADOPT-03** — success-metric definitions for the value gates.
- **ONBRD** — deployment mechanics for each wave.
- **FINOPS-01 / FINOPS-03** — the consumption mirror of the coverage audit, and the Cut / Tune / Filter framework for what Wave 4 finds.

References

- OneAgent monitoring modes (DT docs) — mode capability matrix and segment recommendations
- Enable OneAgent monitoring modes (DT docs)
- Host Monitoring modes overview — DPS (DT docs)
- Process deep monitoring (DT docs) — injection-at-start mechanics, per-PG rules, short-lived-process guidance

---

This notebook was AI-generated from community-submitted and publicly available sources. This notebook series is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.