IAM-04: Policy Authoring and Management

> **Series:** IAM — IAM Administration | **Notebook:** 4 of 12 | **Created:** January 2026 | **Last Updated:** 11/08/2026

Mastering Dynatrace Policy Syntax

Policies are the heart of Dynatrace Gen3 IAM. They define what actions users can perform. This notebook provides a comprehensive guide to policy authoring, from basic syntax to advanced patterns.

Table of Contents

1. Policy Fundamentals
2. Policy Statement Syntax
3. Services and Actions Reference
4. Condition Expressions
5. Common Policy Patterns
6. Default vs Custom Policies
7. Policy Testing and Validation
8. GitOps for Policies
9. Policy Assessment Queries

Prerequisites

Requirement	Details
Dynatrace Environment	SaaS with Gen3 IAM enabled
Permissions	`account-user-management` to create/modify policies
Prior Knowledge	**IAM-01** through **IAM-03**

SaaS 1.337: `frontend.name` as a permission field

SaaS 1.337 added `frontend.name` as a condition for metrics, RUM and Smartscape data, so access can be scoped per frontend without splitting buckets. The condition is `storage:frontend.name` on each table permission, and the policy reference lists `=`, `IN`, `startsWith` and `MATCH` for it:

```
ALLOW storage:metrics:read WHERE storage:frontend.name IN ("checkout-web",
"account-web");
ALLOW storage:user.events:read WHERE storage:frontend.name IN ("checkout-web",
"account-web");
ALLOW storage:user.sessions:read WHERE storage:frontend.name MATCH ("checkout-
web", "account-web");
```

Use `MATCH` for `user.sessions`: a session can span several frontends. Check each value in Experience Vitals before binding the policy, because the `frontend.name` value is not always the display name.

> **Sources:**
>
> - SaaS 1.337 (DT docs) — *"Statements like ALLOW storage:metrics:read WHERE storage:frontend.name = "mobile_app" let you selectively control access to metrics and Smartscape data at the record- and field level."*
> - RUM data access controls best practices (DT docs) — *"Because user sessions may span multiple frontends, use the MATCH operator"*; *"The frontend.name value may differ from the display name shown in Experience Vitals."*
> - IAM policy reference (DT docs)

1. Policy Fundamentals

Policies define **what actions** users can perform. They're separate from boundaries (which control **what data** users can see).

> **One policy language for all authorization.** Dynatrace's security policies are the single configuration surface for *every* authorization requirement — environment access, Grail data access, and AppEngine capabilities alike. What used to be split between classic *roles* (RBAC — "viewer", "admin") and attribute-based permissions is now unified: classic roles are expressed as `environment:roles:*` permissions inside the same `ALLOW` grammar as `storage:*` and `app-engine:*`. There is no separate RBAC subsystem to manage — one policy, one language, optionally scoped by `WHERE` conditions or boundaries.

Policy Scope Levels

Scope	Applies To	Managed By
Account	All environments in account	Account Admin
Environment	Single environment	Environment Admin

Policy Assignment

Policies are assigned to **groups**, not individual users:


```
Group: dt-checkout-editors
├── Policy: Pro User (default)
├── Policy: log-management (custom)
└── Boundary: checkout-services-only
```

Policy Types

Type	Description	Examples
Default Policies	Pre-built by Dynatrace	Standard User, Pro User, Admin User
Custom Policies	Created by you	`log-read-only`, `dashboard-manager`

2. Policy Statement Syntax

Every policy contains one or more **statements** that define allowed actions.



Basic Statement Structure

```
ALLOW &lt;service&gt;:&lt;resource&gt;:&lt;action&gt;;
```

Examples:

Statement	Meaning
`ALLOW storage:logs:read;`	Read log records (plus `storage:buckets:read` — see below)
`ALLOW storage:spans:read;`	Read span records (plus `storage:buckets:read`)
`ALLOW settings:objects:write;`	Modify settings
`ALLOW document:documents:read;`	Read dashboards/notebooks

Wildcards Are NOT Supported

> **Live-verified (Account Management API, 07/2026):** wildcards in permissions are **rejected** with `Invalid policy statement. ALLOW or DENY must be followed by a permission in the form service-name:resource:action`. This applies to every position: `storage:*:read`, `storage:logs:*`, and `*:*:read` all fail.

Enumerate permissions explicitly — comma-separated lists keep statements compact:

Instead of (invalid)	Write (valid)
`ALLOW storage:*:read`	`ALLOW storage:logs:read, storage:spans:read, storage:metrics:read, storage:events:read, storage:bizevents:read, storage:entities:read, storage:system:read, storage:buckets:read;`
`ALLOW storage:logs:*`	`ALLOW storage:logs:read, storage:logs:write;`
`ALLOW settings:objects:*`	`ALLOW settings:objects:read, settings:objects:write;`

> **Also live-verified — storage WRITE permissions accept no WHERE conditions.** `ALLOW storage:logs:write WHERE storage:bucket-name = "x"` is rejected (`Invalid condition name for permission storage:logs:write`). Storage writes are all-or-nothing: only `storage:logs:write`, `storage:metrics:write`, `storage:events:write` exist (`storage:spans:write` and `storage:bizevents:write` do **not**), and none can be scoped by `WHERE`. Scope *reads* with conditions; grant *writes* unscoped and only to trusted ingest paths — or control ingest via OpenPipeline instead. (Settings writes are different: `settings:objects:write` **does** accept `settings:schemaId` and `settings:dt.security_context` conditions.)

Multiple Statements

Combine statements to build complete policies:

```
ALLOW storage:buckets:read;
ALLOW storage:logs:read;
ALLOW storage:spans:read;
ALLOW storage:metrics:read;
ALLOW document:documents:read;
```

> **Note:** Statements are additive. Multiple ALLOW statements combine to grant broader access.
>
> **Grail reads take two permissions.** A table permission (`storage:logs:read`, `storage:spans:read` …) is not enough on its own: `storage:buckets:read` is *"Required additionally to a table permission."* Grant it unconditionally when the table permissions carry the scoping (`dt.security_context`), or with `WHERE storage:bucket-name …` / `WHERE storage:table-name …` when the scope *is* the bucket. Every pattern below includes it.
>
> **DENY statements behave differently.** *"Boundaries don't apply to DENY statements"*, and in Grail *"Conditional DENY statements are supported only for the buckets:read permission. All other table-level storage permissions do not support conditional DENY."* — so express an exclusion on a table permission by narrowing the `ALLOW`, or as a `DENY storage:buckets:read WHERE storage:bucket-name …`.
>
> **Sources:** IAM policy reference (DT docs) — `storage:buckets:read` and the Grail DENY rule quoted above; Policy boundaries (DT docs) — *"Boundaries don't apply to DENY statements"*.

3. Services and Actions Reference

Core Services

Service	Purpose	Common Resources
`storage`	Grail data access	`logs`, `spans`, `metrics`, `events`, `bizevents`, `buckets`, `bucket-definitions`
`settings`	Configuration objects	`objects`, `schemas`
`document`	Notebooks, dashboards	`documents`, `direct-shares`, `environment-shares`

Service	Purpose	Common Resources
`environment`	Classic roles	`roles` (`environment:roles:*`)
`state`	App state storage	`app-states`, `user-app-states`
`automation`	Workflows, AutomationEngine	`workflows`, `calendars`, `rules`

> **What each permission actually does: IAM-97: IAM Permission Reference** covers every permission in the *Standard User* default policy and the usual reader-persona additions — what each really grants, its scope and risk, which built-in apps request it, and the basis for each claim. It also covers services this table leaves out, such as `state-management`, `app-settings`, `synthetic`, `credential-vault`, `platform-management` and `unified-analysis`.

Common Actions

Action	Description
`read`	View/query data
`write`	Create/modify data
`delete`	Remove data
`run`	Run (workflows: `automation:workflows:run`)
`admin`	Administer all objects of a type (e.g. `document:documents:admin`, `automation:workflows:admin`)

Storage Service Details

Resource	Description	Actions
`logs`	Log records	read, write
`spans`	Distributed traces	read
`metrics`	Metric data	read, write
`events`	Platform events	read, write

Resource	Description	Actions
`bizevents`	Business events	read
`entities`	Smartscape entities (Classic surface)	read
`system`	System/audit data (query events, internal)	read
`buckets`	Read records from Grail buckets (required in addition to a table permission)	read
`bucket-definitions`	Create and manage bucket definitions	read, write, delete, truncate

Specialized record tables follow the same `storage:<table>:read` shape — e.g. `storage:security.events:read`, `storage:user.sessions:read`, `storage:user.replays:read`, `storage:application.snapshots:read`, `storage:smartscape:read`.

Storage condition attributes: scope `storage:*` reads with `storage:bucket-name` (e.g. `startsWith "default_"`), `storage:table-name` (e.g. `= "logs"`), and `storage:dt.security_context` (the Gen3 record-level scoping spine — see IAM-05). Example — default-bucket monitoring read:

```
ALLOW storage:buckets:read WHERE storage:bucket-name startsWith "default_";
ALLOW storage:logs:read, storage:events:read, storage:metrics:read,
      storage:entities:read, storage:bizevents:read, storage:spans:read;
```

For system/audit data (the *Storage All System Data Read* managed policy), add `storage:system:read`:

```
ALLOW storage:buckets:read;
ALLOW storage:system:read;
ALLOW storage:logs:read, storage:events:read, storage:metrics:read,
      storage:entities:read, storage:bizevents:read, storage:spans:read;
```

Settings Service Details

Resource	Description	Actions
`objects`	Configuration objects	read, write, delete
`schemas`	Schema definitions	read

Document Service Details

Resource	Description	Actions
`documents`	Dashboards, notebooks	read, write, delete, admin
`direct-shares`	Direct shares with users and groups	read, write, delete
`environment-shares`	Shares with the whole environment	read, write, delete, claim

> **Sources:** IAM policy reference (DT docs) — permission list read 09/24/2026.

Environment Roles (`environment:roles:*`)

Classic environment roles are expressed as IAM permissions. This is how RBAC folds into the one policy language (see §1). All are scoped by the `environment:management-zone` attribute **except** `agent-install` and `configure-request-capture-data` (management-zone not applicable). Those two are broader than their names suggest: for each, Dynatrace states *"Users who have this permission assigned are also able to view monitoring data for all management zones."* Grant them only to groups that may see every zone.

Permission	Classic role meaning
`environment:roles:viewer`	Access environment (read)
`environment:roles:manage-settings`	Change monitoring settings
`environment:roles:agent-install`	Download / install OneAgent
`environment:roles:logviewer`	View logs
`environment:roles:view-sensitive-request-data`	View sensitive request data
`environment:roles:configure-request-capture-data`	Configure capture of sensitive data
`environment:roles:replay-sessions-with-masking`	Replay session data (masked)
`environment:roles:replay-sessions-without-masking`	Replay session data (unmasked)

Permission	Classic role meaning
`environment:roles:view-security-problems`	View security problems
`environment:roles:manage-security-problems`	Manage security problems

> **Sources:** IAM policy reference (DT docs) — `environment:roles:agent-install` and `environment:roles:configure-request-capture-data`.
>
> **Privacy / compliance note.** The session-replay pair and `view-sensitive-request-data` are the load-bearing least-privilege controls here — `replay-sessions-without-masking` and `view-sensitive-request-data` expose unmasked end-user data and should be granted narrowly (specific groups, specific management zones), never bundled into a broad editor policy.

Extensions Service Details

Extension authorization splits into *definitions* (the extension package) and *configurations* (a deployed instance):

Permission	Description	Condition attributes
`extensions:definitions:read` / `:write`	The extension package itself	`extensions:extension-name`
`extensions:configurations:read` / `:write`	A deployed configuration	`extensions:host`, `extensions:host-group`, `extensions:ag-group`, `extensions:management-zone`
`extensions:configuration.actions:write`	Run configuration actions	(as above)
`extensions:discovery.jmx:read` / `extensions:discovery.pmi:read`	Discovery surfaces	—

Extension-ownership delegation — let a team manage *their* extension on *their* hosts without granting tenant-wide extension rights:

```
ALLOW extensions:definitions:read, extensions:definitions:write
WHERE extensions:extension-name = "com.acme.payments";
ALLOW extensions:configurations:read, extensions:configurations:write
WHERE extensions:host-group startsWith "payments-";
```

AppEngine Service Details (`app-engine:*`)

Permission	Description
`app-engine:apps:run`	See / open an app (controls navigation visibility)
`app-engine:functions:run`	Execute AppEngine functions
`app-engine:apps:install`	Install apps
`app-engine:apps:delete`	Remove apps

App-level scoping uses the `shared:app-id` attribute (operators `=`, `!=`, `IN`, `NOT IN`, `startsWith`, `NOT startsWith`). Example — let developers install only their own apps, and grant Workflows access:

```
ALLOW app-engine:apps:install, app-engine:apps:delete WHERE shared:app-id
startsWith "my.";
ALLOW app-engine:apps:run WHERE shared:app-id = "dynatrace.automations";
```

4. Condition Expressions

Conditions add fine-grained control to policy statements.

> **Boundary standardization (canonical pattern).** The examples in this section illustrate condition operators with literal values for clarity. In production, the literal value should be a `${bindParam:NAME}` placeholder bound at policy-binding time, with the boundary field standardized on `dt.security_context` (Gen3) or management zone (Classic). See **IAM REFERENCE.md § Policy Parameterization and**

> **Boundary Standardization** for the canonical pattern, and **IAM-10: Templated Policy-Group Assignments** for binding mechanics.

Condition Syntax

```
ALLOW &lt;service&gt;:&lt;resource&gt;:&lt;action&gt; WHERE &lt;condition&gt;;
```

Condition Operators

Operator	Description	Example
`=`	Equals	`storage:dt.security_context = "team-a"`
`!=`	Not equals — only on conditions that list it (e.g. `storage:bucket-name`, `settings:schemaId`); `storage:dt.security_context` does **not** accept `!=` or `NOT IN`	`storage:bucket-name != "restricted_logs"`
`IN`	In list	`storage:dt.security_context IN ("team-a", "team-b")`
`startsWith`	Prefix match	`settings:schemaId startsWith "builtin:openpipeline.logs."`
`MATCH`	Wildcard pattern match	`storage:dt.security_context MATCH('*/app:easytrade')`

> **`MATCH()` vs `startsWith`:** Use `MATCH()` for flexible wildcard patterns anywhere in the value (e.g. middle segment). Use `startsWith` when matching a fixed leading prefix. **And use `MATCH()` whenever the field can hold an array** — on an array, `=`, `startsWith` and `IN` *"always return `false`"*, silently. The exception is `storage:entities:read` (classic entities), which offers no `MATCH`; there, `startsWith` is the documented operator for the multi-value field (see below). See **IAM-05** for where that bites in a boundary.
>
> **Corrected 09/10/2026 — `contains` is not an IAM condition operator.** An earlier revision of this table listed `contains` (`settings:schemaId contains "custom"`). The IAM policy statement syntax reference gives the operator set as `= != < > IN`

> `startsWith NOT IN NOT startsWith MATCH`, and the IAM policy reference lists `IN`, `=`, `!=`, `startsWith` and `NOT startsWith` for `settings:schemaId` — `contains` appears in neither. Use `startsWith` for a prefix, or `MATCH` for a pattern.
>
> **Sources:** IAM policy statement syntax and examples (DT docs), IAM policy reference (DT docs), Permissions in Grail (DT docs) — *"Using `=`, `STARTSWITH` or `IN` when the field holds an array will always return `false`."*

Common Condition Fields

Domain	Field	Description
Storage	`storage:dt.security_context`	Security context on data
Storage	`storage:bucket-name`	Bucket name (for team isolation)
Storage	`storage:file-path`	Lookup file path. The only condition `storage:files:read` / `write` / `delete` accept, so scope files by folder (IAM-05 Pattern 8)
Settings	`settings:schemaId`	Settings schema
Settings	`settings:dt.security_context`	Security context on settings

Security Context vs Bucket Conditions

> **Default to `dt.security_context` for general team-scoped access.** Bucket conditions work well when the bucket already exists for a specific reason — compliance separation, retention isolation, or hard cost attribution. For routine team-scoped access without one of those scenarios, the `dt.security_context` condition alone is usually simpler. See **IAM REFERENCE.md § Bucket-Match Overlay** for the scenario gating.

Condition Type	Use Case	Example
Security Context	Team- and app-scoped access — the primary mechanism	`storage:dt.security_context = "team-a"`

Condition Type	Use Case	Example
Bucket	Data already separated for retention, cost or compliance (e.g. a PCI bucket)	`storage:bucket-name = "team-a-logs"`
Both	Defense in depth where a compliance bucket exists	Both conditions in policy + boundary

> **Sources:** Partition data with Grail buckets (DT docs) — buckets are *"not intended as the primary mechanism for securing or segmenting data access."*

Condition Examples

Scope to security context (exact):

```
ALLOW storage:buckets:read;
ALLOW storage:logs:read WHERE storage:dt.security_context = "checkout";
```

Scope to specific bucket:

```
ALLOW storage:buckets:read WHERE storage:bucket-name = "checkout_logs";
ALLOW storage:logs:read WHERE storage:bucket-name = "checkout_logs";
```

Scope to a lookup-file folder (read and upload):

```
ALLOW storage:files:read, storage:files:write WHERE storage:file-path
startsWith "/lookups/team_payments/";
```

Keep the leading and trailing slashes. Without the trailing slash, the prefix also matches `/lookups/team_payments2/`.

Scope to settings schema:

```
ALLOW settings:objects:write WHERE settings:schemaId startsWith
"builtin:openpipeline.logs.";
```

Pick schema IDs that exist on your platform generation. Many classic schemas — `builtin:alerting.profile`, `builtin:problem.notifications`, most

`builtin:logmonitoring.*` processing rules — are not visible in Latest Dynatrace, so a statement scoped to them grants nothing there (Patterns 4 and 6 below).

Multiple conditions (AND):

```
ALLOW storage:logs:read WHERE storage:dt.security_context = "team-a" AND
storage:bucket-name = "team-a-logs";
```

Multiple values (IN):

```
ALLOW storage:logs:read WHERE storage:dt.security_context IN ("team-a", "team-
b", "shared");
```

Multiple buckets (team access):

```
ALLOW storage:buckets:read WHERE storage:bucket-name IN ("checkout_logs",
"shared_logs", "checkout_spans", "shared_spans");
ALLOW storage:logs:read WHERE storage:bucket-name IN ("checkout_logs",
"shared_logs");
ALLOW storage:spans:read WHERE storage:bucket-name IN ("checkout_spans",
"shared_spans");
```

Parameterizing the boundary (recommended for production):

The examples above use literal values to illustrate operators. In production, replace each literal with a `${bindParam:NAME}` placeholder and supply the value at binding time. One policy template, N bindings — instead of N near-identical policies.

Recommended (parameterized):

```
ALLOW storage:logs:read WHERE storage:dt.security_context =
"${bindParam:team}";
```

Resolved when bound with `{"parameters": {"team": "checkout"}}`:

```
ALLOW storage:logs:read WHERE storage:dt.security_context = "checkout";
```

The same approach applies to bucket-name overlays, MATCH() patterns, and IN lists. See **IAM-10: Templated Policy-Group Assignments** for binding mechanics and **IAM REFERENCE.md § Policy Parameterization and Boundary Standardization** for the full canonical pattern (including the Gen3 = `dt.security_context` standardization rule and the change-management caveat).

Structured Security Context Design

For organisations with multiple teams and cross-cutting access requirements, a flat single-value context (e.g. `"checkout"`) scales poorly. Instead, encode multiple dimensions into a structured key-value string:

```
comp:&lt;component&gt;/bu:&lt;business-unit&gt;/app:&lt;application&gt;
```

Examples:

Entity	Security Context
Easytrade application	`comp:app/bu:digital/app:easytrade`
Easytrade database	`comp:db/bu:digital/app:easytrade`
Easytrade load balancer	`comp:lb/bu:digital/app:easytrade`

> ⚠️ **Dimension order matters for Smartscape/Classic entities.** Place the dimension you need transversal access on **first** — typically `comp` for infrastructure teams. On `storage:smartscape:read` and the record tables, use `MATCH('comp:db*')` to anchor at the start. **`storage:entities:read` (classic entities) supports `=`, `IN` and `startsWith` only** — no `MATCH` — and Dynatrace documents `startsWith` as evaluating for any matching value of the multi-value entity context.

Using `MATCH()` for flexible policy conditions:

App team — access all components within their application:


```
// 3rd Gen signals
ALLOW storage:metrics:read WHERE storage:dt.security_context
MATCH('*/app:easytrade');
ALLOW storage:logs:read    WHERE storage:dt.security_context
MATCH('*/app:easytrade');
ALLOW storage:spans:read   WHERE storage:dt.security_context
MATCH('*/app:easytrade');
```

Transversal database team — access all database components across all applications:

```
// 3rd Gen signals
ALLOW storage:metrics:read WHERE storage:dt.security_context
MATCH('comp:db*');
ALLOW storage:logs:read    WHERE storage:dt.security_context
MATCH('comp:db*');
ALLOW storage:spans:read   WHERE storage:dt.security_context
MATCH('comp:db*');
// Classic entities — storage:entities:read has no MATCH; startsWith matches
any value of the array
ALLOW storage:entities:read  WHERE storage:dt.security_context startsWith
"comp:db";
ALLOW storage:smartscape:read WHERE storage:dt.security_context
MATCH('comp:db*');
```

> **Note:** `storage:entities:read` (classic entities) supports `=`, `IN` and `startsWith` only — Dynatrace documents `startsWith` as evaluating for any matching value of the multi-value entity context. `storage:smartscape:read` and the record tables (`storage:logs:read` etc.) also accept `MATCH`; anchor at the start with a trailing `*` to mimic a prefix match (e.g. `MATCH('comp:db*')`). See **IAM-05** for the corresponding boundary patterns.
>
> **Sources:** IAM policy reference (DT docs), Grant access to entities with security context (DT docs) — *"the security context of this entity. Can be a multi-value field and startsWith will evaluate for any matching value."*

5. Common Policy Patterns



Pattern 1: Read-Only Access

```
// Read all data, no write access (wildcards are not supported — enumerate)
ALLOW storage:logs:read, storage:spans:read, storage:metrics:read,
      storage:events:read, storage:bizevents:read, storage:entities:read,
      storage:system:read, storage:buckets:read;
ALLOW document:documents:read;
ALLOW state:app-states:read, state:user-app-states:read;
ALLOW settings:objects:read, settings:schemas:read;
```

Pattern 2: Team-Scoped Access (Security Context)

> **Recommended (parameterized):** One policy bound per team via binding parameters. Boundary field standardized on `dt.security_context` (Gen3 universal scoping field). See **IAM REFERENCE.md § Policy Parameterization and Boundary Standardization**.

```
// Parameterized — one policy template, bound per team via binding parameters.
// Reads are condition-scoped; storage writes cannot take WHERE conditions
// (live-verified) — grant them separately and unscoped only where justified.
ALLOW storage:buckets:read;
ALLOW storage:logs:read, storage:spans:read, storage:metrics:read,
      storage:events:read, storage:bizevents:read
  WHERE storage:dt.security_context = "${bindParam:team}";
ALLOW settings:objects:read, settings:objects:write
  WHERE settings:dt.security_context = "${bindParam:team}";
```

Resolved when bound with `{"parameters": {"team": "checkout-team"}}`:

```
ALLOW storage:buckets:read;
ALLOW storage:logs:read, storage:spans:read, storage:metrics:read,
      storage:events:read, storage:bizevents:read
  WHERE storage:dt.security_context = "checkout-team";
ALLOW settings:objects:read, settings:objects:write
  WHERE settings:dt.security_context = "checkout-team";
```

Bind the same template to each team with a different `team` value rather than duplicating the policy. See **IAM-10** for binding mechanics.

Pattern 3: Bucket-Scoped Team Access (When the Bucket Already Exists)

> **Not the primary isolation mechanism.** Dynatrace: buckets are *"not intended as the primary mechanism for securing or segmenting data access"*; they are *"best used for organizing data by retention time, cost allocation, or query optimization."* Isolate teams with `dt.security_context` (Pattern 2); add bucket conditions when a team's data already sits in its own bucket for one of those reasons.
>
> **Sources:** Partition data with Grail buckets (DT docs).
>
> **When this pattern fits:** bucket boundaries are well-suited to scenarios where the bucket already exists for a specific reason — compliance separation (PCI/HIPAA), retention isolation, or hard cost attribution. For general team-scoped access without one of those reasons, **Pattern 2 (`dt.security_context`) is usually the simpler choice**. When the bucket-based scenario does apply, parameterize per-team bucket names via binding parameters (shared bucket statements stay as literals — "shared" is a singleton, not a per-team scope). See **IAM REFERENCE.md § Bucket-Match**

> **Overlay** for scenario gating, and **§ Policy Parameterization and Boundary Standardization** for the full pattern.

```
// Parameterized — per-team data permissions (one policy template, bound per
team)
ALLOW storage:buckets:read WHERE storage:bucket-name = "${bindParam:log-
bucket}";
ALLOW storage:buckets:read WHERE storage:bucket-name = "${bindParam:span-
bucket}";
ALLOW storage:buckets:read WHERE storage:bucket-name = "${bindParam:metric-
bucket}";
ALLOW storage:logs:read    WHERE storage:bucket-name = "${bindParam:log-
bucket}";
ALLOW storage:spans:read   WHERE storage:bucket-name = "${bindParam:span-
bucket}";
ALLOW storage:metrics:read WHERE storage:bucket-name = "${bindParam:metric-
bucket}";

// Shared buckets — literal (Class C: shared is a singleton, not per-team)
ALLOW storage:buckets:read WHERE storage:bucket-name IN ("shared_logs",
"shared_spans");
ALLOW storage:logs:read  WHERE storage:bucket-name = "shared_logs";
ALLOW storage:spans:read WHERE storage:bucket-name = "shared_spans";
```

> **Writes cannot be bucket-scoped (live-verified).** `storage:logs:write WHERE storage:bucket-name = ...` is rejected by the API, and `storage:spans:write` does not exist at all — spans are ingest-only. If a team needs log/metric/event write access, grant it unscoped in a separate, deliberately-assigned policy, and control WHERE data lands via OpenPipeline routing — not via IAM conditions.

Resolved when bound with `{"parameters": {"log-bucket": "checkout_logs", "span-bucket": "checkout_spans", "metric-bucket": "checkout_metrics"}}`:

```
ALLOW storage:buckets:read WHERE storage:bucket-name IN ("checkout_logs",
"checkout_spans", "checkout_metrics");
ALLOW storage:buckets:read WHERE storage:bucket-name IN ("shared_logs",
"shared_spans");
ALLOW storage:logs:read    WHERE storage:bucket-name = "checkout_logs";
ALLOW storage:spans:read   WHERE storage:bucket-name = "checkout_spans";
ALLOW storage:metrics:read WHERE storage:bucket-name = "checkout_metrics";
ALLOW storage:logs:read  WHERE storage:bucket-name = "shared_logs";
ALLOW storage:spans:read WHERE storage:bucket-name = "shared_spans";
```

Bucket + Security Context (Defense in Depth):

> **Recommended (parameterized):** Both fields parameterized; the bucket-match clause is the Gen3 data overlay on the `dt.security_context` spine.

```
// Parameterized defense-in-depth
ALLOW storage:buckets:read WHERE storage:bucket-name = "${bindParam:log-
bucket}";
ALLOW storage:logs:read WHERE storage:bucket-name = "${bindParam:log-bucket}"
  AND storage:dt.security_context = "${bindParam:team}";
```

Resolved when bound with `{"parameters": {"log-bucket": "checkout_logs", "team": "checkout"}}`:

```
ALLOW storage:buckets:read WHERE storage:bucket-name = "checkout_logs";
ALLOW storage:logs:read WHERE storage:bucket-name = "checkout_logs"
  AND storage:dt.security_context = "checkout";
```

Pattern 4: Log Management

Latest Dynatrace — log processing lives in OpenPipeline, whose configuration is stored in Settings 2.0 schemas (`builtin:openpipeline.logs.pipelines` , `.routing` , `.ingest-sources`):

```
// Read all logs, manage log pipelines (OpenPipeline)
ALLOW storage:buckets:read WHERE storage:table-name = "logs";
ALLOW storage:logs:read;
ALLOW settings:objects:read, settings:objects:write
  WHERE settings:schemaId startsWith "builtin:openpipeline.logs.";
```

Pipelines and ingest sources also have owners, who can read and write the objects they create; routing has no owner-based control, so a write grant on the routing schema — as in the statement above — covers every route in that scope.

Dynatrace Classic only — the classic log-processing schemas are removed in Latest Dynatrace (processing, log metrics and log security context are *"Replaced by OpenPipeline"*; log buckets by *"Grail bucket assignment"*). Keep this form only on an environment that has not moved:

```
// Classic log monitoring settings
ALLOW settings:objects:read, settings:objects:write
  WHERE settings:schemaId startsWith "builtin:logmonitoring";
```

Pattern 5: Dashboard Creator

```
// Create and share dashboards (documents:share does not exist — sharing is
direct-shares)
ALLOW document:documents:read, document:documents:write,
document:documents:delete;
ALLOW document:direct-shares:read, document:direct-shares:write;
ALLOW storage:buckets:read;
ALLOW storage:logs:read, storage:spans:read, storage:metrics:read,
      storage:events:read, storage:bizevents:read;
```

Pattern 6: Alerting Manager

Latest Dynatrace — problem notifications and alerting profiles are *"Replaced by Workflows"*, and custom alerts are Davis anomaly detectors (`builtin:davis.anomaly-detectors`):

```
// Manage notifications (workflows) and custom alerts (anomaly detectors)
ALLOW automation:workflows:read, automation:workflows:write,
automation:workflows:run;
ALLOW settings:objects:read, settings:objects:write
  WHERE settings:schemaId = "builtin:davis.anomaly-detectors";
```

Dynatrace Classic only — `builtin:alerting.profile` , `builtin:alerting.maintenance-window` and `builtin:problem.notifications` are not visible in Latest Dynatrace, so on a Latest environment these two statements grant nothing:

```
// Classic alerting profiles, maintenance windows and problem notifications
ALLOW settings:objects:read, settings:objects:write
  WHERE settings:schemaId startsWith "builtin:alerting";
ALLOW settings:objects:read, settings:objects:write
  WHERE settings:schemaId startsWith "builtin:problem";
```

> **Sources:** Settings 2.0 schemas that are removed in Latest Dynatrace (DT docs) — *"None of the schemas on this page are visible in Latest Dynatrace."*; Owner-based access control in OpenPipeline

> (DT docs) — *"Owner-based control is available for pipelines and ingest sources, and not routing."*, *"This policy gives users write permissions to all routes for a configuration scope and should therefore be used with caution."*; Anomaly detectors schema table (DT docs).

Pattern 7: SRE On-Call Access

```
// Broad read access + problem/event visibility
// (state:problems does not exist — Davis problems are events in Grail)
ALLOW storage:buckets:read;
ALLOW storage:logs:read, storage:spans:read, storage:metrics:read,
      storage:events:read, storage:bizevents:read, storage:entities:read;
ALLOW document:documents:read;
ALLOW settings:objects:read;
```

Pattern 8: Security Auditor

```
// Read everything, write nothing (enumerated — wildcards are not supported)
ALLOW storage:logs:read, storage:spans:read, storage:metrics:read,
      storage:events:read, storage:bizevents:read, storage:entities:read,
      storage:system:read, storage:buckets:read;
ALLOW settings:objects:read, settings:schemas:read;
ALLOW document:documents:read, document:direct-shares:read,
document:environment-shares:read;
ALLOW state:app-states:read, state:user-app-states:read;
```

Pattern 9: Compliance-Scoped Access (Bucket-Based)

```
// Access only to PCI-compliant data bucket
ALLOW storage:buckets:read WHERE storage:bucket-name IN ("pci_logs",
"pci_spans");
ALLOW storage:logs:read WHERE storage:bucket-name = "pci_logs";
ALLOW storage:spans:read WHERE storage:bucket-name = "pci_spans";
// No access to non-PCI buckets
```

Pattern 10: Tiered Environment Access (Management Zones)

Grant full access in lower environments and read-only in production — using `environment:roles:*` permissions scoped by the `environment:management-zone` attribute (the classic-role surface, complementary to the Grail patterns above):

```
// Full access in dev and hardening
ALLOW environment:roles:viewer, environment:roles:manage-settings
WHERE environment:management-zone IN ("dev", "hardening");

// Read-only in production
ALLOW environment:roles:viewer
WHERE environment:management-zone IN ("prod");
```

This is the canonical app-developer shape: iterate freely in non-prod, observe-only in prod. Add `environment:roles:logviewer` to the prod statement if the team needs production log access without settings rights.

Choosing Between Patterns

Requirement	Recommended Pattern
Teams can share data flexibly	Pattern 2 (Security Context)
Teams must never see each other's data	**Pattern 2 (Security Context)**, enforced by enrichment coverage on every signal
Compliance/regulatory data separation	**Pattern 9 (Bucket-Based)**
Temporary project access	Pattern 2 (Security Context)
Data already split into per-team buckets for cost allocation	**Pattern 3 (Buckets)**
Full in non-prod, read-only in prod	**Pattern 10 (Management Zones)**

6. Default vs Custom Policies

Built-in Default Policies

Dynatrace provides default policies for common use cases:

Policy	Description	Use Case
Standard User	Access the environment and run Dynatrace apps	Most users

Policy	Description	Use Case
Pro User	Standard, plus build and run apps and workflows	Team members
Admin User	Administrative access across all platform services	Administrators
`account-viewer` (account permission)	View account	Cross-team visibility
`account-user-management` (account permission)	Manage users, groups, policies	IAM administrators

Reach for Managed Policies First

Default to the policies Dynatrace ships before authoring custom ones. Most standard scenarios — monitoring read access, app users, automation access — are already covered by managed policies; hand-rolling a custom policy for these is extra surface to maintain and audit. Author custom policies only when no managed policy fits (team-scoped data, specific single-capability grants, compliance constraints).

Commonly used managed policies for Grail and AppEngine onboarding:

Managed policy	Grants
All Grail data read access	Unrestricted Grail read
Read `<table>`	Per-table read (e.g. *Read Logs*, *Read Metrics*, *Read Spans*, *Read System Events*)
Standard User / Pro User / Admin User	App use, app and workflow building, administration (see the table above)

Legacy default policies. *AppEngine - User*, *AppEngine - Admin*, *AppEngine - Developer access*, *AppEngine - Manage EdgeConnect*, *AutomationEngine - User access*, *AutomationEngine - Admin access*, every *Environment role - …* policy (*Access environment*, *Change monitoring settings*, *View logs*, *Download/install OneAgent*, *Configure capture of sensitive data*, …), *Extensions - Admin access*, *Extensions - User access*, *Settings Reader*, *Settings Writer*, *Storage All System Data Read*, *Storage Default Monitoring Read* and others are now listed as legacy: Dynatrace states they *"are not accessible for new policy assignments, but existing assignments of these policies remain until removed."* Use the role policies and the *Read* `<table>` policies for new bindings;

where a legacy policy such as *Settings Writer* has no direct successor, write a custom policy (for example `settings:objects:read`, `settings:objects:write` and `settings:schemas:read`, scoped by `settings:schemaId` or `settings:dt.security_context`). Verify the current catalog in your tenant's Account Management — it evolves.

> **Sources:** Default policies (DT docs).

When to Use Default Policies

Scenario	Recommendation
Simple permission levels	Use defaults
Quick onboarding	Use defaults
Standard roles	Use defaults

When to Create Custom Policies

Scenario	Recommendation
Team-scoped data access	Custom policy
Specific capability (logs only)	Custom policy
Compliance requirements	Custom policy
Least privilege needs	Custom policy

Combining Default and Custom

Groups can have both:

```
Group: dt-checkout-editors
├── Default Policy: Standard User (environment and app access)
├── Default Policy: Read Logs / Read Spans … (data access — Standard User has no Grail table reads)
└── Custom Policy: checkout-write-access (team-specific writes)
```

This provides base access plus targeted write permissions. *Standard User* grants app, document, workflow and settings-read access but no `storage:logs:read`-style table reads, so pair it with a data-access policy.

> **Sources:** Default policies (DT docs) — *Standard User*, *All Grail data read access* and legacy-policy statements, read 10/13/2026.

7. Policy Testing and Validation

Testing Methodology

1. **Create policy in test environment** (or account)
2. **Assign to test group** with a test user
3. **Verify intended access** works
4. **Verify unintended access** is blocked
5. **Document results** and adjust

Common Validation Tests

Test	Expected Result
Query logs in scope	Success
Query logs out of scope	Empty or denied
Modify settings in scope	Success
Modify settings out of scope	Denied
Create dashboard	Success (if allowed)

Debugging Policy Issues

If access isn't working as expected:

1. **Check group membership** - Is user in the correct group?
2. **Check policy assignment** - Is policy assigned to group?

3. **Check boundary** - Does boundary allow access to the entity?
4. **Check conditions** - Do condition values match?
5. **Check security context** - Is data tagged correctly?

See **IAM-09: Troubleshooting Access Issues** for detailed debugging.

8. GitOps for Policies

Version control your policies for audit trail and peer review.

Policy as Code Structure

```
iam-config/
├── policies/
│   ├── team-checkout-access.yaml
│   ├── team-payments-access.yaml
│   ├── sre-oncall.yaml
│   └── security-auditor.yaml
├── groups/
│   └── group-assignments.yaml
└── README.md
```

Policy YAML Format (Monaco)

Monaco manages IAM as **account resources** — `policies:`, `groups:` and `boundaries:` are dedicated top-level types in YAML, not Settings schemas, and no JSON templates are needed. `monaco deploy` ignores account configuration — Monaco has dedicated commands for account resources, which authenticate with an OAuth client configured under `accounts:` in `manifest.yaml`.

Policy and group (documented account format):

```
# account/iam.yaml
policies:
  - name: team-data-reader
    id: team-data-reader
    level:
      type: account
    description: Read logs and spans — scoped per team by the boundary on each
binding
    policy: |-
      ALLOW storage:buckets:read;
      ALLOW storage:logs:read;
      ALLOW storage:spans:read;

boundaries:
  - id: bnd-team-checkout
    name: bnd-team-checkout
    query: storage:dt.security_context IN ("checkout");

groups:
  - name: dt-checkout-team
    id: dt-checkout-team
    description: Checkout team
    environments:
      - environment: abc12345
        policies:
          - policy:
              type: reference
              id: team-data-reader
            boundaries:
              - type: reference
                id: bnd-team-checkout
```

> **Binding parameters are not in Monaco's documented account format.** The page documents policies, groups, boundaries and the policy-to-group binding (with boundaries), but not binding `parameters`, so a `${bindParam:team}` template cannot be given its value here. Bind templated policies with parameters through the IAM API or Terraform (`dynatrace_iam_policy_bindings_v2`) — see **IAM-10** and **IAM-95**. The example above keeps the policy unparameterized and scopes it with a per-team boundary instead.
>
> **Sources:** Monaco account configuration (DT docs) — *"Using Monaco, you can define users, service users, groups, policies, and boundaries as dedicated types in YAML configuration files."*

GitOps Workflow

1. **Branch**: Create feature branch for policy change
2. **Edit**: Modify policy YAML
3. **Review**: Submit PR, get peer review
4. **Test**: Deploy to test environment
5. **Approve**: Merge after validation
6. **Deploy**: CI/CD applies to production

Benefits

Benefit	Description
Audit Trail	Git history shows who changed what, when
Peer Review	Changes reviewed before apply
Rollback	Easy revert to previous state
Documentation	Policies are self-documenting
Consistency	Same process for all changes

See **AUTOM-03: Monaco** for full implementation details.

9. Policy Assessment Queries

Use these queries to audit policy-related activity.

> **Group, policy, boundary and binding changes are account-level, and this environment's audit events are not their change log.** *"Dynatrace provides audit logs of changes to your account-level identity and access (IAM) management settings" — "Administrators can view these logs in Account Management > Settings > Audit log"*, where they are kept for up to ten years (also queryable through the Account Audits API). The same page says *"The Account Management audit log doesn't yet cover every account-level change. Some IAM configuration and login events aren't recorded."* The query below shows IAM API calls made **through this environment** — useful for spotting automation, not a change log. On the validation

> tenant, 30 days of these events held no group or policy change at all: only user lookups and scheduled `/lookups/iam_*` file uploads, which the query now excludes.
>
> **Sources:** Account Management audit logs (DT docs).

```
// IAM API activity in this environment (policy changes themselves: account
audit log)
// Data object corrected 08/12/2026. The Dynatrace audit trail is NOT in
`logs`: this cell used
// `fetch logs | filter matchesPhrase(log.source, "audit")`, and no log.source
on a Grail tenant
// contains "audit" — the filter matched nothing, silently, forever. Platform
audit records live in
// `dt.system.events` with `event.kind == "AUDIT_EVENT"` (265,000+ records
over 7 days here), and
// they are STRUCTURED, so the old `matchesPhrase(content, ...)` string-
scraping is replaced by real
// field predicates. Key fields: user.id, user.organization, event.type
(GET/POST/PUT/PATCH/DELETE/
// CREATE/LOGIN/app.opened), event.outcome (HTTP status or "success"),
authentication.type
// (OAUTH2/TOKEN/NONE), authentication.grant.type, resource (the API path),
origin.address,
// origin.type, request.source, dt.app.id, event.provider.
// Enumerate your own with:
//   fetch dt.system.events, from:-24h | filter event.kind == "AUDIT_EVENT" |
limit 1
fetch dt.system.events, from:-30d
| filter event.kind == "AUDIT_EVENT"
| filter in(event.type, {"POST", "PUT", "PATCH", "DELETE", "CREATE",
"UPDATE"}) and contains(resource, "iam")
| filter not startsWith(resource, "/lookups/")
| fields timestamp, user.id, event.type, resource, event.outcome
| sort timestamp desc
| limit 50
```

```
// Find access denied events
// Data object corrected 08/12/2026. The Dynatrace audit trail is NOT in
`logs`: this cell used
// `fetch logs | filter matchesPhrase(log.source, "audit")`, and no log.source
on a Grail tenant
// contains "audit" — the filter matched nothing, silently, forever. Platform
audit records live in
// `dt.system.events` with `event.kind == "AUDIT_EVENT"` (265,000+ records
over 7 days here), and
// they are STRUCTURED, so the old `matchesPhrase(content, ...)` string-
scraping is replaced by real
// field predicates. Key fields: user.id, user.organization, event.type
(GET/POST/PUT/PATCH/DELETE/
// CREATE/LOGIN/app.opened), event.outcome (HTTP status or "success"),
authentication.type
// (OAUTH2/TOKEN/NONE), authentication.grant.type, resource (the API path),
origin.address,
// origin.type, request.source, dt.app.id, event.provider.
// Enumerate your own with:
//   fetch dt.system.events, from:-24h | filter event.kind == "AUDIT_EVENT" |
limit 1
fetch dt.system.events, from:-7d
| filter event.kind == "AUDIT_EVENT"
| filter event.outcome == "403"
| fields timestamp, user.id, event.type, resource, origin.address
| sort timestamp desc
| limit 50
```

```
// Summarize permission-related audit events
// Data object corrected 08/12/2026. The Dynatrace audit trail is NOT in
`logs`: this cell used
// `fetch logs | filter matchesPhrase(log.source, "audit")`, and no log.source
on a Grail tenant
// contains "audit" — the filter matched nothing, silently, forever. Platform
audit records live in
// `dt.system.events` with `event.kind == "AUDIT_EVENT"` (265,000+ records
over 7 days here), and
// they are STRUCTURED, so the old `matchesPhrase(content, ...)` string-
scraping is replaced by real
// field predicates. Key fields: user.id, user.organization, event.type
(GET/POST/PUT/PATCH/DELETE/
// CREATE/LOGIN/app.opened), event.outcome (HTTP status or "success"),
authentication.type
// (OAUTH2/TOKEN/NONE), authentication.grant.type, resource (the API path),
origin.address,
// origin.type, request.source, dt.app.id, event.provider.
// Enumerate your own with:
//   fetch dt.system.events, from:-24h | filter event.kind == "AUDIT_EVENT" |
limit 1
fetch dt.system.events, from:-7d
| filter event.kind == "AUDIT_EVENT"
| summarize events = count(), by:{event.outcome, event.type}
| sort events desc
| limit 25
```

Next Steps

With policies defined, complete your access control setup:

Recommended Path

1. **IAM-05: Boundary Design Patterns** - Control what entities users can see
2. **IAM-06: User Lifecycle and Provisioning** - Automate user management
3. **IAM-07: Audit Logging and Compliance** - Monitor policy effectiveness
4. **IAM-10: Templated Policy-Group Assignments** - Reusable parameterized policies for team/environment scoping at scale
5. **IAM-11: Policy Persona Workshop** - Design persona-based policies from stakeholder requirements using a structured 6-goal methodology

Policy Checklist

Before moving on, ensure you have:

- [ ] Understood policy statement syntax
- [ ] Reviewed services and actions reference
- [ ] Designed policies for your team structure
- [ ] Decided on default vs custom policy usage
- [ ] Established testing methodology
- [ ] Considered GitOps for policy management

Summary

In this notebook, you learned:

- Policy fundamentals and scope levels
- Statement syntax: `ALLOW <service>:<resource>:<action>`
- Services and actions reference
- Condition expressions for fine-grained control
- Ten common policy patterns
- When to use default vs custom policies
- Policy testing and validation approaches
- GitOps for policy version control

References

- Policy Statements Reference
- Permission Management
- Account Policies

References

- IAM policy statements reference (DT docs) — authoritative permission + attribute catalog
- Tailored access management, Part 1 — one configuration for all authorization requirements (Dynatrace News)
- Tailored access management, Part 2 — onboard users to Grail and AppEngine (Dynatrace News)

This notebook was AI-generated from community-submitted and publicly available sources. This notebook series is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.