OPMIG-04: OpenPipeline Migration Guide: Part 4

> **Series:** OPMIG — OpenPipeline Migration | **Notebook:** 4 of 10 | **Created:** December 2025 | **Last Updated:** 10/30/2026

Pipeline Configuration Fundamentals

Table of Contents

1. Accessing OpenPipeline Settings - Detailed Guide
2. Step-by-Step: Creating Your First Pipeline
3. Complete Pipeline Examples
4. Understanding the Interface
5. Creating Your First Pipeline
6. Configuring Processors
7. Setting Up Dynamic Routing
8. Testing Your Configuration
9. Configuration Best Practices
10. Verifying Pipeline Processing
11. Complete Pipeline Example

Learning Objectives

By the end of this notebook, you will:

- ✅ Navigate the OpenPipeline UI confidently

- ✅ **Follow step-by-step UI walkthrough**
- ✅ Create custom pipelines from scratch
- ✅ Configure processors with best practices
- ✅ Test configurations with sample data
- ✅ **Build complete end-to-end pipeline examples**
- ✅ Verify pipeline processing with DQL

Prerequisites

Requirement	Details
Dynatrace Environment	Dynatrace SaaS with Grail and OpenPipeline access — Managed is not covered by this series
Permissions	`settings:read` and `settings:write` (custom pipelines; built-in and ready-made pipelines are view-only with `settings:read`)
API Access	`logs.read` and `logs.ingest` token scopes
Knowledge	OPMIG-01 through OPMIG-03; basic understanding of log ingestion

> **Sources:** Processing in OpenPipeline (DT docs) — pipeline *Types* table, *Permissions* row.

SaaS 1.337: Certain Configuration API endpoints are deprecated

SaaS 1.337 deprecated certain Configuration API endpoints: *"Many Configuration API endpoints are now covered by the Settings endpoints in the Environment API v2."* The affected endpoints *"remain fully active"* and have no sunset date, but *"these endpoints may be removed in a future release"* — so point new automation at the Settings endpoints rather than the deprecated paths.

> **Sources:** What's new in SaaS 1.337 (DT docs) — *"Affected endpoints remain fully active. While we haven't set a sunset date, these endpoints may be removed in a future release."*

Migration impact for OpenPipeline / log-monitoring config:

Legacy area	Settings v2 schema	Upgrade status
Log custom attributes	`builtin:logmonitoring.log-custom-attributes`	**Blocked at upgrade**
Log storage configuration	`builtin:logmonitoring.log-storage-settings`	Carries forward
Log dpp rules	`builtin:logmonitoring.log-dpp-rules`	**Blocked at upgrade**
Log timestamp configuration	`builtin:logmonitoring.timestamp-configuration`	Carries forward

> **Settings v2 is the right destination for the API move, but not the end of the journey for these four schemas.** The sprint-1.337 guidance above is about *which API surface* to call — and on that axis it stands. On the separate upgrade axis, two of these four schemas are flagged **Blocked at upgrade** (the other two carry forward) by the ready-made *Check your upgrade readiness* dashboard: they stop answering once the tenant moves to the latest Dynatrace. Their real successor is an OpenPipeline processor, which is what the rest of this series builds.
>
> So: if you are moving automation off the Configuration API *today*, Settings v2 is the correct target and this table is the mapping. If you are planning the Gen3 migration, do not stop here — retarget these four onto OpenPipeline rather than rebuilding them as Settings v2 objects you will migrate again. See AUTOM-02's catalog for status and OPMIG §5–§7 for the pipeline equivalents.

If your migration tooling reaches into the Configuration API for any of these, switch to the Settings v2 endpoints in Environment API v2 (see **AUTOM-02 § Sprint 1.337** for general patterns and **AUTOM-04 (Terraform)** for `dynatrace_settings` resource usage).

Accessing OpenPipeline Settings - Detailed Guide

Navigation Path


From Dynatrace Home:

```
1. Click ☰ (hamburger menu) in top-left
2. Scroll to "Manage" section
3. Click "Settings"
4. In left sidebar, expand "Process and contextualize"
5. Click "OpenPipeline"
```

Direct URL:

```
https://{your-environment}.apps.dynatrace.com/ui/settings/openpipeline
```

OpenPipeline UI Overview



Configuration Scopes

The dropdown at the top lets you switch between data types:

Scope	Icon	What It Handles
Logs	📋	Log records from all sources

Scope	Icon	What It Handles
Spans	🔗	Distributed trace spans
Metrics	📊	Metric data ingestion
Events	⚡	Platform events
Business Events	💼	Business analytics events
Security Events	🔐	Security data

> 💡 **Tip:** Each scope has its own separate set of pipelines. Start with **Logs** for your migration.

Three Main Tabs

1. Pipelines Tab

- View all pipelines for selected scope
- Create new pipelines
- Edit pipeline configuration
- Configure processing, extraction, storage

2. Dynamic Routing Tab

- Create routing rules
- Map data to pipelines
- Set matching conditions
- Control route order

3. Ingest Sources Tab

- View data sources
- See ingestion statistics
- Monitor source health
- Troubleshoot ingestion issues

Step-by-Step: Creating Your First Pipeline

Let's walk through creating a complete pipeline for nginx access logs.

Step 1: Create the Pipeline

Actions:
1. Go to OpenPipeline → Logs scope
2. Click **[+ Pipeline]** button (top-left)
3. Enter name: `nginx-access-logs`
4. Add description: `Process nginx access logs with parsing and metric extraction`
5. Click **Create**

Result: New empty pipeline appears in list

Step 2: Configure Processing Stage

2a. Add DQL Processor for Parsing

Actions:
1. Click on your `nginx-access-logs` pipeline
2. Go to **Processing** tab
3. Click **[+ Processor]** button
4. Select **DQL** from processor types

Configuration:

```
Name: Parse nginx access log

Matching condition:
log.source == "nginx" OR matchesPhrase(content, "GET") OR
matchesPhrase(content, "POST")

Processor definition:
parse content, "IPADDR:client_ip SPACE '-' SPACE LD:user SPACE '[' LD:log_time
']' SPACE '\"' LD:method SPACE LD:path SPACE LD:protocol '\"' SPACE
INT:status_code SPACE INT:bytes"
```

Test with Sample Data:

```
{
  "content": "192.168.1.100 - - [12/Dec/2024:10:30:45 +0000] \"GET /api/users
HTTP/1.1\" 200 1234",
  "log.source": "nginx"
}
```

5. Click **[Run sample data]**
6. Verify fields extracted: `client_ip`, `log_time`, `method`, `path`, `status_code`, `bytes` (the bracketed time goes into `log_time`, not `timestamp` — overwriting the record's `timestamp` with a string risks the record failing log schema validation)
7. Click **[Save]**

2b. Add Enrichment Processor

Actions:
1. Click **[+ Processor]** again
2. Select **DQL**

Configuration:

```
Name: Add environment tags

Matching condition:
(leave empty to apply to all)

Processor definition:
fieldsAdd environment = "production"
| fieldsAdd service_type = "web-server"
| fieldsAdd response_category = if(status_code &lt; 400, "success",
                                  else: if(status_code &lt; 500, "client_error",
                                  else: "server_error"))
```

3. Click **[Save]**

Step 3: Configure Metric Extraction

Actions:
1. Go to **Metric extraction** tab
2. Click **[+ Metric]**

Configuration for Request Count:

```
Metric type: Counter
Metric key: log.nginx.request_count

Dimensions:
  - method
  - status_code
  - environment

Matching condition:
isNotNull(status_code)
```

3. Click **[Save]**
4. Click **[+ Metric]** again for bytes metric

Configuration for Response Size:

```
Metric type: Value
Metric key: log.nginx.response_bytes
Value field: bytes

Dimensions:
  - method
  - path

Matching condition:
isNotNull(bytes)
```

5. Click **[Save]**

Step 4: Configure Storage

Actions:
1. Go to the **Bucket assignment** stage
2. Add a **Bucket assignment** processor, give it a name and a matching condition (for example `true`)
3. In the **Storage** list, choose the bucket — for example a custom `web_logs` bucket with 14-day retention
4. Click **[Save]**

> 💡 **Tip:** Bucket assignment is *first match only* — the first processor whose condition matches decides the bucket. In community practice, records that match no bucket-

> assignment processor land in the scope's default bucket (`default_logs`); confirm where yours land with the bucket query in Verifying Pipeline Processing. To keep a record out of storage entirely (for example after extracting a metric), use **No storage assignment** instead.

Step 5: Create Dynamic Routing

Actions:

1. Go to **Dynamic routing** tab (top of OpenPipeline page)
2. Click **[+ Dynamic route]**

Configuration:

```
Name: Route nginx logs

Matching condition:
log.source == "nginx" OR matchesValue(content, "*nginx*")

Pipeline: nginx-access-logs
```

3. Click **[Save]**

Step 6: Test End-to-End

Option 1: Send Test Log via API

```
curl -i -X POST \
  "https://{your-environment}.live.dynatrace.com/api/v2/logs/ingest" \
  -H "Content-Type: application/json" \
  -H "Authorization: Api-Token {your-token}" \
  -d '{
    "content": "192.168.1.100 - - [12/Dec/2024:10:30:45 +0000] \"GET
/api/users HTTP/1.1\" 200 1234",
    "log.source": "nginx"
  }'
```

Option 2: Check with Existing Logs

Wait 2-3 minutes for processing, then run verification query (see next section).

Step 7: Verify Processing

See the validation queries in the next section to confirm:
- Logs are routed to your pipeline ✓
- Fields are parsed correctly ✓
- Metrics are being generated ✓

Complete Pipeline Examples

Example 1: Application Logs with Error Tracking

Use Case: Java application logs with structured format

Pipeline: `java-app-logs`

Processing Stage:

Processor 1: Parse Log Structure

```
parse content, "'[' TIMESTAMP('yyyy-MM-dd HH:mm:ss'):log_time ']' SPACE '['
LD:level ']' SPACE '[' LD:thread ']' SPACE LD:class ' - ' DATA:message"
```

Processor 2: Extract Request ID

```
parse content, "LD? 'requestId=' NSPACE:request_id"
```

`parse` matches from the **start** of the field. A pattern that opens with `'requestId='` returns null on every line that does not *begin* with that text, and a trailing `LD` runs to the end of the line. `LD?` skips any prefix (or none); `NSPACE` stops at the next space.

Processor 3: Classify Errors

```
fieldsAdd error_type = if(contains(message, "NullPointerException"), "NPE",
                       else: if(contains(message, "SQLException"), "DB",
                       else: if(contains(message, "TimeoutException"),
"Timeout",
                       else: "Other")))
| fieldsAdd severity = if(level == "ERROR", "critical",
                       else: if(level == "WARN", "warning",
                       else: "info"))
```

Metric Extraction:
- **Counter:** `log.java.error_count` (dimensions: error_type, class)
- **Counter:** `log.java.request_count` (dimensions: level, thread)

Event Extraction:
Davis stage → **Davis event** processor:
- **Event name:** `Error in {class}: {error_type}`
- **Event properties:** `event.type = CUSTOM_ALERT` (`event.type` is required)
- **Matching:** `level == "ERROR"`

Storage: `default_logs` (35 days)

Example 2: Payment Service with PCI-DSS Compliance

Use Case: Financial logs requiring credit card masking

Pipeline: `payment-service-secure`

Processing Stage (in order):

Processor 1: Mask Credit Cards (FIRST!)

```
fieldsAdd content = replacePattern(content, "!&lt;&lt;[0-9A-Za-z-] CREDITCARD
!&gt;&gt;[0-9A-Za-z-]", replacement: "[CC_REDACTED]")
```

Processor 2: Mask CVV

```
fieldsAdd content = replacePattern(content, "('cvv='|'cvc='|'CVV='|'CVC=') [0-
9]{3,4}", replacement: "cvv=[REDACTED]")
```

Processor 3: Parse Payment Data

```
parse content, "LD? 'orderId=' INT:order_id"
| parse content, "LD? 'amount=' DOUBLE:amount"
| parse content, "LD? 'currency=' NSPACE:currency"
| parse content, "LD? 'status=' NSPACE:payment_status"
```

Processor 4: Add Tags

```
fieldsAdd service = "payment"
| fieldsAdd compliance = "pci-dss"
| fieldsAdd audit_required = true
```

Metric Extraction:
- **Value:** `log.payment.amount` (value: amount, dimensions: currency, payment_status)
- **Counter:** `log.payment.transaction_count` (dimensions: payment_status, currency)

Business Event Extraction:
- **Type:** `com.company.payment.processed`
- **Provider:** `payment-service`
- **Fields:** order_id, amount, currency, payment_status

Storage: `financial_logs` (90 days - compliance requirement)

Example 3: Kubernetes Logs with Pod Context

Use Case: Container logs with K8s metadata

Pipeline: `kubernetes-app-logs`

Processing Stage:

Processor 1: Drop System Logs

```
Processor type: Drop record
Matching condition: k8s.namespace.name == "kube-system" AND loglevel ==
"DEBUG"
```

Processor 2: Parse JSON Logs

```
parse content, "JSON:json_payload"
```

Processor 3: Enrich with K8s Context

```
fieldsAdd app = k8s.deployment.name
| fieldsAdd namespace = k8s.namespace.name
| fieldsAdd pod_name = k8s.pod.name
| fieldsAdd container = k8s.container.name
```

Metric Extraction:
- **Counter:** `log.k8s.pod_log_count` (dimensions: namespace, app, loglevel)

Storage: Route based on namespace:
- production namespace → `prod_logs` (35 days)
- staging namespace → `staging_logs` (14 days)
- dev namespace → `dev_logs` (7 days)

Understanding the Interface

Pipeline Configuration Tabs

Each pipeline has these configuration sections:

Stage	Purpose	Processors
Processing	Transform, mask, drop and enrich records	DQL, Add/Remove/Rename fields, Drop record, Technology bundle, Inline lookup
Smartscape node / edge	Create topology from records	Smartscape node, Smartscape edge
Permission	Set `dt.security_context`	Set security context (first match only)
Product / Cost allocation	DPS cost allocation	First match only
Bucket assignment	Choose the Grail bucket	Bucket assignment, No storage assignment (first match only)
Metric extraction	Create metrics from records	Counter, Value, Histogram metric
Davis	Raise Davis events	Davis event

Stage	Purpose	Processors
Data extraction	Create new records	Business event, SDLC event


The stage order is fixed; only the processor order *within* a stage is yours (see OPMIG-02 § Understanding Processing Order).

> **Sources:** Processing in OpenPipeline (DT docs) — stage and processor table.
>
> **Two additions in SaaS 1.345 (August 2026 — staged tenant rollout).** The **Inline lookup** processor maps an attribute to a new value from a lookup table defined inside the processor, with no external system — useful for error-code descriptions, app-ID-to-cost-centre mapping, and deriving `dt.security_context`. Separately, any field named with the `dt.temp` prefix is available throughout processing but is **not persisted to Grail**, so intermediate values feeding metric/event/bizevent extraction no longer have to be stored on the record. Both apply across every scope with a Processing stage. Verify each has reached your tenant before designing against it.

Processor Configuration Panel

When adding a processor, you configure:

1. **Name**: Descriptive name for the processor
2. **Matching condition**: When this processor runs
3. **Processor definition**: What the processor does
4. **Sample data**: Test data to validate



Creating Your First Pipeline

Step-by-Step: Create a Log Processing Pipeline

Example: Create a pipeline for nginx access logs

Step 1: Navigate to OpenPipeline

```
Settings → Process and contextualize → OpenPipeline → Logs
```

Step 2: Create Pipeline

1. Click **+ Pipeline**
2. Enter name: `nginx-access-logs`
3. Click **Create**

Step 3: Add Processing (Parsing)

1. Go to **Processing** tab

2. Click **+ Processor → DQL**
3. Configure:
   - **Name**: `Parse nginx access log`
   - **Matching condition**: `matchesValue(content, "*HTTP*")`
   - **Processor definition**:
   `parse content, "IPADDR:client_ip SPACE '-' SPACE LD:user SPACE '[' LD:log_time ']' SPACE '\"' LD:method SPACE LD:path SPACE LD:protocol '\"' SPACE INT:status_code SPACE INT:bytes"`

Step 4: Test with Sample Data

1. Enter sample log:
   `json {"content": "192.168.1.100 - - [12/Dec/2024:10:30:45 +0000] \"GET /api/users HTTP/1.1\" 200 1234"}`
2. Click **Run sample data**
3. Verify extracted fields

Step 5: Save Pipeline

Click **Save** to store the configuration.

Configuring Processors

DQL Processor Examples

The DQL processor is the most flexible. Here are common patterns:

Add Static Fields

```
fieldsAdd environment = "production"
| fieldsAdd application = "web-frontend"
```

Add Conditional Fields

```
fieldsAdd severity = if(loglevel == "ERROR", "critical",
                     else: if(loglevel == "WARN", "warning",
                     else: "normal"))
```

Parse with DPL Pattern

```
parse content, "LD? 'userId=' LD:user_id ','"
```

Start the pattern with `LD?` unless the field always begins with your literal — `parse` anchors at the start of the field and returns null otherwise.

Remove Sensitive Fields

```
fieldsRemove password, secret_key, api_token
```

Rename Fields for Standardization

```
fieldsRename standardized_name = old_field_name
```

Drop Processor Examples

Drop processors remove records matching conditions:

Matching Condition	Effect
`loglevel == "DEBUG"`	Drop all debug logs
`matchesValue(content, "*healthz*")`	Drop health check logs
`matchesValue(content, "*/metrics*")`	Drop Prometheus scrapes
`loglevel == "TRACE"`	Drop trace-level logs

> Matchers accept `matchesValue` (with `*` wildcards, any substring) and `matchesPhrase` (whole tokens); `contains()` is not enabled in a matching condition.

Technology Bundle Processor

For common formats, add a **Technology bundle** processor instead of writing the pattern yourself. It *"matches records for the selected technology and processes them according to predefined context-sensitive processing statements."* The fields each bundle adds are defined by the bundle — run its preview on a sample record before you depend on them downstream.

> **Sources:** Processing in OpenPipeline (DT docs) — processor table, *Technology bundle*.

Setting Up Dynamic Routing

Dynamic routing sends data to specific pipelines based on matching conditions.


Routing Configuration Steps

1. Go to **Dynamic routing** tab
2. Click **+ Dynamic route**
3. Configure:
   - **Name**: Descriptive route name
   - **Matching condition**: When to use this route
   - **Pipeline**: Target pipeline

Matching Condition Examples

Condition	Routes To
`log.source == "nginx"`	nginx-logs pipeline
`k8s.namespace.name == "production"`	prod-logs pipeline
`matchesPhrase(content, "payment")`	payment-logs pipeline
`dt.openpipeline.source == "/api/v2/logs/ingest"`	api-ingested pipeline
`host.name == "web-server-01"`	specific host pipeline

Route Evaluation Order



> 💡 **Tip:** Routes are evaluated in order. Place more specific routes first, general routes last.

Testing Your Configuration

Using Sample Data in UI

Every processor supports sample data testing:

1. Enter JSON sample in **Sample data** field
2. Click **Run sample data**
3. Review output in preview panel
4. Adjust processor definition as needed

Sample Data Format

```
{
  "content": "Your log message here",
  "log.source": "your-source",
  "timestamp": "2024-12-12T10:30:00Z",
  "k8s.namespace.name": "production"
}
```

Testing via API

Send test logs to validate end-to-end:

```
curl -i -X POST \
  "https://{your-environment}.live.dynatrace.com/api/v2/logs/ingest" \
  -H "Content-Type: application/json" \
  -H "Authorization: Api-Token {your-token}" \
  -d '{"content":"Test log message","log.source":"test-source"}'
```

Response `204` indicates successful ingestion.

Configuration Best Practices

Pipeline Design Principles

Principle	Recommendation
Single Purpose	One pipeline per use case (not one mega-pipeline)
Specific Routing	Use precise matching conditions
Security First	Add masking processors early in the chain
Drop Early	Remove unwanted data before processing
Test Thoroughly	Validate every processor with sample data

Processor Ordering

Within the **Processing stage**, order processors logically:

```
1. Masking      → Protect sensitive data first
2. Drop         → Remove unwanted records
3. Parse        → Extract structured fields
4. Enrich       → Add context fields
5. Transform    → Compute derived values
```

Everything else — Smartscape, permission, cost allocation, bucket assignment, and metric/event extraction — runs in later stages whose order is fixed by the platform (see

OPMIG-02 § Understanding Processing Order).

Naming Conventions

Type	Convention	Example
Pipeline	`{source}-{purpose}`	`nginx-access-logs`
Processor	`{action}-{target}`	`parse-request-line`
Route	`route-to-{pipeline}`	`route-to-nginx-logs`

Common Mistakes to Avoid

Mistake	Problem	Solution
Overly broad routing	Too many logs hit pipeline	Use specific conditions
No masking	Sensitive data stored	Add masking before processing
Complex conditions	Hard to maintain	Break into multiple pipelines
Untested patterns	Parsing fails on real data	Always test with samples
Assuming unmatched data is lost	It is not — the default route still stores it, unprocessed (classic pipeline for logs and business events)	Watch default-route volume with the query below and add routes for what lands there

---

Verifying Pipeline Processing

After configuring pipelines, verify they're working correctly with these queries.

```
// Verify logs are being processed by your new pipeline
// Replace 'your-pipeline-name' with your actual pipeline name
fetch logs, from: now() - 1h
| filter contains(toString(dt.openpipeline.pipelines), "your-pipeline-name")
| summarize {processed_count = count()}
| fieldsAdd status = if(processed_count &gt; 0, "✅ Pipeline is processing
logs", else: "⚠️ No logs processed yet")
```

```
// Check routing distribution across all pipelines
fetch logs, from: now() - 1h
| summarize {record_count = count()}, by: {dt.openpipeline.pipelines}
| sort record_count desc
```

```
// Verify parsing is extracting expected fields
// Check for a specific field that should be parsed
fetch logs, from: now() - 1h
| filter isNotNull(dt.openpipeline.pipelines)
| summarize {
    total = count(),
    with_loglevel = countIf(loglevel != "NONE")
  }, by: {dt.openpipeline.pipelines}
| fieldsAdd parsing_rate = round((toDouble(with_loglevel) / toDouble(total)) *
100, decimals: 1)
```

```
// Sample recent logs from your pipeline to inspect parsed fields
fetch logs, from: now() - 1h
| filter contains(toString(dt.openpipeline.pipelines), "your-pipeline-name")
| limit 10
```

```
// Check logs taking the default route (may need routing)
// For logs, the default route is the classic pipeline: pipeline id
"logs:default".
// dt.openpipeline.pipelines is an array, so use in(), never ==.
fetch logs, from: now() - 1h
| filter in(dt.openpipeline.pipelines, "logs:default")
| summarize {unrouted = count()}, by: {log.source}
| sort unrouted desc
| limit 20
```

```
// Monitor pipeline processing over time
fetch logs, from: now() - 24h
| filter isNotNull(dt.openpipeline.pipelines)
| makeTimeseries {record_count = count()}, by: {dt.openpipeline.pipelines},
interval: 1h
```

```
// Verify bucket routing is working
fetch logs, from: now() - 1h
| filter isNotNull(dt.openpipeline.pipelines)
| summarize {record_count = count()}, by: {dt.openpipeline.pipelines,
dt.system.bucket}
| sort record_count desc
```

Complete Pipeline Example

Here's a complete example of a production pipeline configuration:

Pipeline: `payment-service-logs`

Routing Condition:

```
k8s.namespace.name == "payments" OR log.source == "payment-service"
```

Processors (in order):

1. **Mask Credit Cards** (Masking)
   - Matching: `matchesPhrase(content, "card")`
   - Definition: `fieldsAdd content = replacePattern(content, "!<<[0-9A-Za-z-] CREDITCARD !>>[0-9A-Za-z-]", replacement: "****-****-****-****")` — `replacePattern` takes a DPL pattern, not a regular expression. The `!<<` / `!>>` bounds stop `CREDITCARD` matching digit runs inside UUIDs, which it otherwise rewrites (OPMIG-08)
2. **Drop Health Checks** (Drop)
   - Matching: `matchesValue(content, "*/health*") OR matchesValue(content, "*/ready*")`
3. **Parse Payment Logs** (DQL)
   - Matching: `matchesValue(content, "*transaction*")`

- Definition: `parse content, "LD? 'transaction_id=' LD:transaction_id ',' SPACE? 'amount=' DOUBLE:amount ',' SPACE? 'status=' NSPACE:payment_status"`

4. **Add Environment Tag** (DQL)
   - Matching: (none - applies to all)
   - Definition: `fieldsAdd service = "payment-service", criticality = "high"`

Metric Extraction:
- Name: `payment_amount_by_status`
- Field: `amount`
- Dimensions: `payment_status`

Storage:
- Bucket: `financial_logs` (90-day retention)

Next Steps

Now that you can create and configure pipelines, continue with:

Notebook	Focus Area
OPMIG-05	Routing & Bucket Management
OPMIG-06	Processing, Parsing & Transformation
OPMIG-07	Metric & Event Extraction
OPMIG-08	Security, Masking & Compliance

References

- Configure Processing Pipeline
- Processing Examples
- DQL Functions in OpenPipeline
- Dynatrace Pattern Language

This notebook was AI-generated from community-submitted and publicly available sources. This notebook series is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.