S2S-99: Best Practice Summary

> **Series:** S2S — SaaS to SaaS Migration | **Notebook:** 99 | **Created:** March 2026 | **Last Updated:** 10/14/2026

Overview

This notebook consolidates **112 actionable best practices** from the S2S series into a single reference organized around the 9-step migration framework. Each practice is definitive: it tells you exactly what to set, when, and why. Use this as a pre-flight checklist and ongoing reference throughout your SaaS-to-SaaS migration.

The S2S series follows a **9-step framework** (Discover through Optimize) supported by an **11-step Order of Operations** that governs execution sequence. When the migration retires a cloud provider — moving the environment to an Azure-hosted cluster *and* the workloads from AWS to Azure — the appendix LAB **S2S-94** sequences both.

The 9-Step Migration Framework

Step	Name	Focus
1	**Discover**	Migration scenarios and inventory
2	**Strategize**	Define your migration approach
3	**Design**	Target tenant architecture
4	**Prepare**	Export and pre-stage
5	**Execute**	Configuration import and agent cutover
6	**Integrate**	Cloud, dashboards, and workflows
7	**Expand**	OpenPipeline, SLOs, and alerting
8	**Enable**	Parallel operation and stakeholder handover

Step	Name	Focus
9	**Optimize**	Cutover validation and decommission

The 11-Step Order of Operations

#	Operation	Description
1	**Assess**	Inventory source tenant
2	**Provision**	Target SaaS tenant and access (SSO/IAM)
3	**Export**	Configuration from source tenant
4	**Migrate**	Configuration to target tenant
5	**Rebuild**	Dashboards, SLOs, alerts
6	**Redirect**	OneAgents and operators to target
7	**Reconnect**	Cloud integrations and extensions
8	**Migrate**	Any remaining configuration
9	**Validate**	Data flow and performance
10	**Cutover**	Full switch to target tenant
11	**Decommission**	Source tenant

> **OneAgent Attribute Enrichment (1.333+):** OneAgent can enrich telemetry at the source — metrics, spans, logs, events and entities — with primary fields (`dt.security_context`, `dt.cost.costcenter`, `dt.cost.product`) and primary tags (`primary_tags.environment`, `primary_tags.team`). The values travel with the data into OpenPipeline routing, bucket assignment and record-level permissions. Set them with `--set-host-tag` at install time or with `oneagentctl` afterwards, or per process with `DT_TAGS`. See docs.

Table of Contents

1. Step 1: Discover — Migration Scenarios and Inventory
2. Step 2: Strategize — Define Your Migration Approach
3. Step 3: Design — Target Tenant Architecture
4. Step 4: Prepare — Export and Pre-Stage
5. Step 5: Execute — Configuration Import and Agent Cutover
6. Step 6: Integrate — Cloud, Dashboards, and Workflows
7. Step 7: Expand — OpenPipeline, SLOs, and Alerting
8. Step 8: Enable — Parallel Operation and Stakeholder Handover
9. Step 9: Optimize — Cutover Validation and Decommission
10. The Five Principles of S2S Migration

Prerequisites

Requirement	Details
S2S Series	Read S2S-01 through S2S-09 for full context
Source Tenant	Active Dynatrace SaaS with admin access
Target Tenant	Provisioned Dynatrace SaaS with admin access
CLI Tools	Monaco CLI v2.x, Terraform v1.5+ with provider ~> 1.91

1. Step 1: Discover — Migration Scenarios and Inventory

Source: S2S-01

#	Best Practice	Recommended Setting/Value	Priority
1	Complete entity discovery before anything else	Run `smartscapeNodes "HOST", from:-7d | summarize count()` (and the `SERVICE` / `FRONTEND` equivalents; process groups stay on `fetch dt.entity.process_group`) to establish baseline numbers — and run the same queries in the target later	**Critical**
2	Identify your migration scenario	Classify as consolidation (many-to-one), split (one-to-many), regional relocation, hosting-cloud change (the environment moves to another cloud), or workload cloud change (the monitored workloads move) — retiring a cloud is both at once	**Critical**
3	Select Monaco for configuration, Terraform for IAM	Monaco v2 covers all 8 config types (settings, document, automation, bucket, segment, slo-v2, openpipeline, classic api), and account IAM through `monaco account` (OAuth client); Terraform is the common choice for IAM because it keeps state and shows drift	**Critical**
4	Plan for entity ID changes	Entity IDs (HOST-xxx, SERVICE-xxx) are tenant-specific and will change; identify every dashboard, SLO, and alert that hardcodes an entity ID	**Critical**
5	Document the manual remainder	Most configuration moves with tooling; budget most of your effort for the remainder — entity ID remapping, integration repointing, IAM redesign, credential recreation ("90/10" is community shorthand, not a measured ratio)	**Critical**
6	Build a comprehensive endpoint inventory	Document every agent URL, API call, webhook, and integration endpoint that references the source tenant URL	**Critical**
7	Triage detected problems before migration	Active, short-lived and duplicate problems carry noise to the target tenant; tune the detectors behind sources with >500 active problems (the frequent-issue flag is being phased out — do not measure noise with it)	**Critical**

#	Best Practice	Recommended Setting/Value	Priority
8	Identify configuration debt to leave behind	Catalog stale maintenance windows, disabled notification rules, inactive synthetic monitors, unused management zones — do not migrate these	**Critical**
9	Inventory Extensions 2.0 separately	Monaco does not export extension installations; Terraform can install/activate (`dynatrace_hub_extension_active_version`) and configure (`dynatrace_hub_extension_v2_config`) Hub extensions — otherwise reinstall from Hub; list all extensions and plan their path before migration	**Recommended**
10	Audit configuration changes from last 30 days	Query audit logs to identify recently changed settings that may not be in your last export	**Recommended**

2. Step 2: Strategize — Define Your Migration Approach

Source: S2S-02

#	Best Practice	Recommended Setting/Value	Priority
11	Choose phased approach for environments with >500 hosts	Migrate dev first (weeks 1-2), staging (weeks 3-4), production (weeks 5-6); gives Dynatrace Intelligence time to build baselines	**Critical**
12	Define success criteria before starting	Document measurable targets: host count parity, service count parity, log volume parity, SLO evaluation accuracy, alerting coverage	**Critical**
13	Engage your account team for licensing early	Contact Dynatrace to discuss temporary parallel licensing; negotiate before the migration window opens	**Critical**

#	Best Practice	Recommended Setting/Value	Priority
14	Plan a per-wave overlap, sized by measurement	Historical data does not migrate; keep the source readable while each wave builds history in the target, and measure per-host history depth (FAQ-25 §5) rather than fixing a number of weeks	**Critical**
15	Establish a configuration freeze window	No settings modifications in the source tenant during cutover; communicate freeze dates to all teams	**Critical**
16	Migrate multi-source consolidations sequentially	Complete Source 1 → validate → Source 2 → validate; never migrate two sources in parallel; migrate the simpler source first (non-K8s before K8s)	**Critical**
17	Align migration timing with stable traffic periods	Avoid holidays, sales events, or other atypical traffic patterns that would distort Dynatrace Intelligence baselines	**Recommended**
18	Expect the 90/10 shape	Most configuration moves with tooling; budget most of the effort for the remainder	**Critical**
19	Prepare a rollback plan	Document how to revert agents to the source tenant if issues arise during cutover	**Recommended**

3. Step 3: Design — Target Tenant Architecture

Source: S2S-03

#	Best Practice	Recommended Setting/Value	Priority
20	Redesign IAM during consolidation	Use the migration as the opportunity to fix group sprawl and overprivileged policies; redesign from scratch for the target tenant	**Critical**
21	Deploy data foundation before governance	Buckets and enrichment rules must exist before OpenPipeline routing, segments, SLOs, and IAM policies that reference them	**Critical**

#	Best Practice	Recommended Setting/Value	Priority
22	Replace entity IDs with tag-based filters	Convert `entityId("HOST-xxxx")` to `tag(app:checkout),tag(env:production)` in dashboards, SLOs, and notification rules before migration	**Critical**
23	Design bucket naming for consolidation	Use prefix naming (e.g., `us-east_app_logs`, `eu-west_app_logs`) to prevent collisions when consolidating multiple tenants	**Recommended**
24	Plan the 24-item deployment order	Buckets (1st) → Enrichment (2nd) → OpenPipeline (3rd) → Segments (4th) → Gen2 config (5th-13th) → Alerting/SLOs (14th-18th) → Dashboards/Workflows (19th-21st) → IAM last (22nd-24th)	**Critical**
25	Replace management zone ID references with names	Convert `mzId(123)` to `mzName("Production")` because zone IDs change between tenants	**Critical**
26	Prefix resources with source identifier during consolidation	Set `name = "${source_prefix} - ${resource_name}"` on all dashboards, rules, and SLOs to prevent naming collisions	**Recommended**
27	Tag everything by business unit before splitting a tenant	Apply auto-tags identifying ownership before splitting one tenant into many	**Recommended**
28	Map cloud provider identity constructs when changing providers	AWS IAM roles to Azure Service Principals, Azure AD Groups to GCP Google Groups, etc.	**Recommended**

4. Step 4: Prepare — Export and Pre-Stage

Source: S2S-04, S2S-10

#	Best Practice	Recommended Setting/Value	Priority
29	Export via `monaco download`	Run `monaco download --manifest manifest.yaml --environment source-tenant` to export all configuration in one operation	**Critical**
30	Use the S2S-10 migration scripts for export	Automates Monaco download with a short-lived, auto-revoked read-only token and stages a timestamped folder for `monaco deploy`, with an optional SaaS Upgrade Assistant package; Bash and PowerShell versions provided	**Recommended**
31	Plan on `monaco deploy`; treat the SaaS Upgrade Assistant as an optional, rehearsed path	The SUA is documented for a Managed source (*"imports your Dynatrace Managed environment configuration"*); importing a packaged Monaco export (S2S-10 §1) is a field practice — rehearse it on a non-production target and keep `monaco deploy` as the fallback	**Critical**
32	Store exported configuration in Git	Commit the Monaco export directory to a Git repository immediately after download	**Critical**
33	Validate export completeness	Compare `ls projects/full-export/settings/ | wc -l` against Settings API `totalCount` per schema	**Critical**
34	Validate export contains no secrets	Run `grep -r "dt0c01" projects/` after export and confirm 0 matches	**Critical**
35	Run `monaco deploy manifest.yaml --environment <target> --dry-run` before any deploy	Checks manifest structure, references and template rendering; it does not contact the tenant, so a deploy can still fail with HTTP 400. Monaco has no `validate` command	**Critical**

#	Best Practice	Recommended Setting/Value	Priority
36	Provision target tenant and verify admin access	Choose the hosting cloud and region deliberately (Azure-hosted regions are *"Available on request"*; Azure Native Dynatrace Service creates a new account and environment); confirm SSO, API token creation, and environment admin role before proceeding	**Critical**
37	Configure SSO with full SAML message signing	Create a new SAML application in your IdP for the target tenant — new Entity ID, new ACS URL; never reuse the source SAML app. Dynatrace returns `400` for assertion-only signatures, and Microsoft Entra signs only the assertion by default — set *Sign SAML response and assertion*	**Critical**
38	Test SSO with a pilot user before cutover	SAML configuration issues are the #1 day-of-cutover blocker	**Critical**
39	Deploy ActiveGates in the target tenant	ActiveGates cannot be reconfigured like OneAgents; install fresh from the target tenant UI	**Critical**
40	Prepare K8s operator manifests for the target tenant	Write a new DynaKube for the target in an API version your Operator release supports (check its release notes); the switch is delete-and-recreate — *"starting with Dynatrace Operator version 1.3.0, editing spec.apiUrl is not allowed"*	**Critical**
41	Recreate network zones in the target	Export with `monaco download … --settings-schema builtin:networkzones.zones` and deploy to the target before agent migration; zone names must match because agents keep their zone setting	**Critical**
42	Create new OAuth clients and API tokens in the target	Source credentials cannot be exported; create fresh clients with matching scopes	**Critical**

#	Best Practice	Recommended Setting/Value	Priority
43	Keep Microsoft Entra ID group claims under 150 per SAML assertion	Microsoft: *"The number of groups emitted in a token is limited to 150 for SAML assertions"* — above it the claim is omitted entirely; emit only groups assigned to the application, or filter (Group claims (Microsoft Learn))	**Recommended**

5. Step 5: Execute — Configuration Import and Agent Cutover

Source: S2S-05

#	Best Practice	Recommended Setting/Value	Priority
44	Follow the 24-item deployment order	Buckets → Enrichment → OpenPipeline → Segments → Gen2 config → Alerting/SLOs → Dashboards/Workflows → IAM last	**Critical**
45	Deploy IAM groups, policies, and bindings last	IAM `WHERE` clauses reference schemas, buckets, and security contexts that must already exist	**Critical**
46	Use `monaco deploy manifest.yaml --environment target` for import	Monaco resolves dependencies automatically within a single run (except IAM)	**Critical**
47	Read a clean dry-run as structure-only	Payload errors (HTTP 400) and missing permissions (HTTP 403) surface only at deploy time — deploy to a non-production target first	**Critical**

#	Best Practice	Recommended Setting/Value	Priority
48	Deploy IAM via Terraform with `account-idm-read`, `account-idm-write`, and `iam-policies-management` scopes	These three OAuth scopes are required to manage groups, policies, and bindings	**Critical**
49	Reconfigure OneAgent with `oneagentctl` — do not reinstall	Run `oneagentctl --set-server=<target-url>/communication --set-tenant=<target-id> --set-tenant-token=<target-token> --restart-service`, then restart applications monitored with deep code modules	**Critical**
50	Route firewall-restricted hosts through ActiveGates	Use `--set-server="https://<ag-host>:9999/communication"` for on-prem or DMZ hosts; semicolon-separate multiple AGs for failover	**Critical**
51	Restart application processes after agent reconfiguration	Application processes must restart for the agent to report to the new tenant	**Critical**
52	Migrate non-production first	Dev agents first (weeks 1-2), staging (weeks 3-4), production last (weeks 5-6)	**Critical**
53	Validate after each migration wave	Verify host count, service count, and data flow in the target after each environment wave	**Critical**
54	Automate fleet-wide `oneagentctl` with config management	Use Ansible, Chef, Puppet, AWS SSM, or Azure Automation for large fleets	**Recommended**
55	Budget 540m CPU and 872Mi memory per node for Dynatrace overhead	OneAgent (100m/512Mi) + CSI Driver (440m/360Mi) per node; control plane adds 650m/320Mi per cluster	**Recommended**

#	Best Practice	Recommended Setting/Value	Priority
56	Update IRSA (AWS), Managed Identity (Azure), or Workload Identity (GCP) to reference target	Cloud-specific K8s identity must point to the new tenant	**Critical**

6. Step 6: Integrate — Cloud, Dashboards, and Workflows

Source: S2S-06

#	Best Practice	Recommended Setting/Value	Priority
57	Recreate cloud provider connections in the target tenant	`monaco download` cannot export AWS, Azure, or K8s credentials; create new connections from the target (Latest Dynatrace Cloud Platform Monitoring first, classic integrations only as fallback)	**Critical**
58	Create the target's AWS connection	*"All AWS connection creation methods are powered by CloudFormation"* — deploy the stack the target generates in each account (classic fallback: IAM role trust policy with the target's external ID)	**Critical**
59	Create a new, dedicated service principal for the target's Azure connection	*"Do not share it across Dynatrace environments"*; and never leave a subscription on two connections — switch it per subscription	**Critical**

#	Best Practice	Recommended Setting/Value	Priority
60	Create new GCP Service Account with `Monitoring Viewer` and `Compute Viewer` roles	Generate new JSON key for the target tenant integration	**Critical**
61	Move cloud log ingest to the target	AWS: subscribe log groups to the Firehose streams of the target's connection (classic fallback: a new Lambda forwarder). Azure: Event Hubs ingest (classic forwarder: switch within 24 hours — older logs are rejected)	**Critical**
62	Update webhook URLs that reference source-tenant-specific endpoints	Verify custom webhooks accept traffic from the target tenant's IP range	**Critical**
63	Migrate dashboards via Monaco and audit for hardcoded entity IDs	Search dashboard JSON for `entityId(`, `HOST-`, `SERVICE-`, `PROCESS_GROUP-` patterns and replace with tag-based filters	**Critical**
64	Reassign dashboard ownership to a target tenant user or service account	Source user accounts may not exist in the target; set `owner` field to a valid target identity	**Critical**

#	Best Practice	Recommended Setting/Value	Priority
65	Create new workflow service user (actor) in the target tenant	Source service users cannot be migrated; create new service user and set as workflow actor	**Critical**
66	Recreate Synthetic private locations in the target tenant	Private Synthetic locations are tenant-specific; update location references in all monitor configs	**Critical**
67	Use a classic API token (not OAuth) for Synthetic monitor migration	Synthetic monitors require classic token as of provider v1.88.0+	**Critical**
68	Plan Extensions 2.0 separately	Monaco does not export extension installations; Terraform can install/activate (`dynatrace_hub_extension_active_version`) and configure (`dynatrace_hub_extension_v2_config`) Hub extensions — otherwise reinstall from Hub. Remote extensions run on an ActiveGate group; SQL extensions can alternatively run in Kubernetes via Dynatrace Operator — verify per extension	**Critical**
69	Standardize tag naming across cloud providers	Use consistent keys (`app` , `env` , `team`) regardless of AWS/Azure/GCP	**Recommended**

#	Best Practice	Recommended Setting/Value	Priority
70	Verify every webhook integration (Teams, Slack, PagerDuty, ServiceNow, Jira)	Check each integration's URL and credential; many are unchanged, but none is guaranteed (see #62)	**Recommended**

7. Step 7: Expand — OpenPipeline, SLOs, and Alerting

Source: S2S-07

#	Best Practice	Recommended Setting/Value	Priority
71	Deploy Grail buckets before OpenPipeline routing rules	Routing rules that target nonexistent buckets cause data loss	**Critical**
72	Deploy in order: buckets → enrichment rules → OpenPipeline rules	This three-step sequence ensures data flows correctly from the first byte	**Critical**
73	Wait for K8s enrichment propagation before deploying routing rules	Enrichment rules typically take ~45 min to propagate on EKS; routing rules that depend on enriched attributes fail silently until propagation completes — data lands in `default_logs`	**Critical**

#	Best Practice	Recommended Setting/Value	Priority
74	Add a CI/CD validation gate between enrichment and routing deploys	Query for the enriched field your routing matches on (e.g. `isNotNull(k8s.namespace.name)`) before applying routing rules; do not rely on `monaco deploy` alone (it does not wait for propagation)	**Recommended**
75	Use prefix naming for bucket consolidation	E.g., `us-east_app_logs`, `eu-west_app_logs` to prevent collisions when consolidating tenants	**Recommended**
76	Match retention policies exactly for regulated environments	Set to same days as source (e.g., 360 days for PCI); verify compliance requirements before cutover	**Critical**
77	Update bucket references in OpenPipeline routing rules	Routing rules from export contain source bucket names; replace with target bucket names	**Critical**
78	Rebuild SLOs without source-tenant entity IDs	Entity IDs change in the target tenant. Write each SLI as DQL (`dynatrace_platform_slo` or Monaco `slo-v2`) and scope it with a segment deployed to the target, not `dt.entity.service == "SERVICE-xxx"`; rewrite classic entity-selector SLOs rather than copying them (classic `dynatrace_slo_v2` targets: `tag(...)` filters, see S2S-07 §3 and SLO-05)	**Critical**
79	Shorten SLO timeframes while target history fills	The target tenant has no data from before cutover, so a 30-day SLO reads partial data for 30 days. Start with `timeframe_from = "now-7d"` on `dynatrace_platform_slo`, then move to the full window (S2S-07 §3)	**Critical**
80	Align SLO cutover with calendar boundaries	If using calendar-based SLOs, switch at the start of a month or quarter to avoid partial evaluation	**Recommended**

#	Best Practice	Recommended Setting/Value	Priority
81	Port alerting profile severity and tag filters as-is	Ensure the referenced tags exist in the target tenant before deploying alerting profiles	**Critical**
82	Verify maintenance window timezone settings	Cron expressions are timezone-sensitive; confirm schedules are correct after import	**Recommended**
83	Update maintenance window entity scopes	Source entity references in scope definitions must be remapped to target tenant entities	**Critical**

8. Step 8: Enable — Parallel Operation and Stakeholder Handover

Source: S2S-08

#	Best Practice	Recommended Setting/Value	Priority
84	Keep the source readable through every wave's overlap	Historical data does not migrate; size each wave's overlap from measured history depth in the target (FAQ-25 §5)	**Critical**
85	Treat baseline timescales as estimates and measure them	In community practice: availability 2-3 days; response time and error rate 1-2 weeks; resource utilization 2-4 weeks — confirm per host with the FAQ-25 §5 history-depth query	**Critical**
86	Use phased parallel model to control cost	Each host reports to one tenant (OneAgent cannot dual-report), so agent cost does not double; overlap cost comes from integrations, synthetics and forwarders you point at both tenants, plus the per-wave window	**Critical**

#	Best Practice	Recommended Setting/Value	Priority
87	Communicate to all personas	Engineering teams: 4 weeks before cutover; SRE/on-call: 2 weeks before; executives: weekly status	**Critical**
88	Communicate the SLO baseline gap to stakeholders	SLOs start at 0% in the target and accumulate data over 7-30 days depending on evaluation window	**Critical**
89	Warn about Dynatrace Intelligence false positives	Baselines relearn from the target's own data; expect noisier alerting for recently migrated hosts, and route it to a staging channel rather than disabling it	**Recommended**
90	Negotiate dual licensing with Dynatrace	Contact your account team to discuss temporary parallel licensing to reduce cost	**Recommended**
91	Configure SCIM provisioning for the target tenant	Set new SCIM URL and token; users sync automatically on first login	**Recommended**
92	Export problem history before decommission	Problem history cannot migrate; export critical incidents as documentation for post-mortem reference	**Recommended**
93	Keep a fallback local admin account	If SAML is misconfigured on day of cutover, local admin bypasses SSO	**Critical**

9. Step 9: Optimize — Cutover Validation and Decommission

Source: S2S-09

#	Best Practice	Recommended Setting/Value	Priority
94	Complete go/no-go checklist before cutover	Verify host count, service count, log volume, span volume, SLO evaluation, alerting coverage — all must match success criteria	**Critical**

#	Best Practice	Recommended Setting/Value	Priority
95	Validate all data flows via DQL	Run `fetch logs, from:-1h | summarize count()`, `fetch spans, from:-1h | summarize count()`, and entity count queries to confirm parity	**Critical**
96	Verify enrichment tags are populating	Run `fetch logs, from:-1h | filter isNotNull(dt.security_context) | summarize count()` and confirm count > 0	**Critical**
97	Run final `monaco download` → `monaco deploy` sync before cutover	Captures any configuration changes made since initial export	**Critical**
98	Get stakeholder sign-off	SRE, dev, security, management, and compliance each validate their domain: alerting, dashboards, IAM, SLO reporting, retention	**Critical**
99	Disable alerting in source tenant after cutover	Prevents duplicate alerts during the transition tail	**Critical**
100	Keep source tenant running 30 days minimum after cutover	Stop ingest (redirect agents and integrations, revoke ingest tokens); data stays queryable for its bucket retention. Do not deprovision until all stakeholders confirm	**Critical**
101	Rotate all credentials within 30 days of cutover	API tokens, OAuth clients, cloud provider keys — revoke any temporary migration credentials	**Critical**
102	Revoke all source tenant API tokens and deactivate OAuth clients	Prevents unauthorized access to the deprecated tenant	**Critical**
103	Remove SAML/SSO application from IdP for source tenant	Eliminates stale IdP configuration and prevents confusion	**Recommended**

#	Best Practice	Recommended Setting/Value	Priority
104	Export final audit logs from source before decommission	Compliance requires audit trail retention; export before access is lost	**Critical**
105	Update all documentation	Replace source tenant URLs, API endpoints, and dashboard links in runbooks, CI/CD pipelines, and architecture diagrams	**Critical**
106	Tune Dynatrace Intelligence anomaly detection after the relearn window	Not during it — thresholds set against a half-learned baseline get baked in (FAQ-25 § 5). Route noise to a staging channel first, then tune what actually fired	**Critical**
107	Expand SLO timeframes to full duration by week 4	Move `timeframe_from` from `now-7d` to the full window (e.g. `now-30d`) once 30 days of target data exist	**Recommended**
108	Consolidate redundant Synthetic monitors	If consolidating tenants, deduplicate monitors that tested the same endpoints from different tenants	**Optional**
109	Replace all remaining entity ID references	Post-migration cleanup ensures configuration is fully portable for future migrations	**Recommended**
110	Schedule credential rotation for cloud provider integrations	Rotate within 30 days of cutover for all AWS, Azure, and GCP integrations	**Recommended**
111	Conduct a lessons-learned review within 2 weeks of cutover	Capture planning gaps, tool issues, communication effectiveness, timeline accuracy	**Recommended**
112	Stop ingest into the source tenant after cutover	Redirect agents and integrations and revoke ingest tokens; historical data stays queryable for its bucket retention without active monitoring cost	**Critical**

The Five Principles of S2S Migration

1. **Export early, validate often** — do not wait for cutover to discover missing config
2. **Tags over entity IDs** — make all configuration portable before migration
3. **Parallel is not optional** — historical data does not migrate; 30 days minimum
4. **IAM last** — deploy the resources first, then lock them down with policies
5. **Communicate relentlessly** — migration is as much about people as technology

Summary

This notebook contains **112 best practices** across 9 migration steps. The breakdown by priority:

Priority	Count	Guidance
Critical	81	Must implement. Skipping any of these risks data loss, access failures, or migration rollback.
Recommended	27	Implement unless there is a documented reason not to. These reduce risk and cost.
Optional	4	Implement if resources allow. These improve efficiency but are not blockers.

Use the 9-step framework table and the 11-step Order of Operations table at the top of this notebook to track progress and govern execution sequence. Each step's best practices align to the corresponding S2S notebook (S2S-01 through S2S-10) for full context and worked examples.

This notebook was AI-generated from community-submitted and publicly available sources. This notebook series is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.