

What is the relationship between the mass of a damped spring-block oscillator ([masses TBD]) and the damping ratio?

Physics HL

Internal Assessment

Word count: TBD

Table of Contents

1	Introduction	1
1.1	The Research Question	1
1.2	Background Information	1
1.3	Hypothesis	2
2	Research Design	4
2.1	Variables	4
2.2	Apparatus and Materials	6
2.3	Methodology	7
2.4	Preliminary Trials	8
2.5	Risk Assessment	8
3	Results	9
3.1	Raw Data	9
3.1.1	Qualitative Data	9
3.1.2	Quantitative Data	9
3.2	Data Processing	9
3.2.1	Transformation	9
3.2.2	Uncertainty Analysis	9
3.3	Analysis and Interpretation	9
4	Conclusion	9
4.1	Evaluation	9
4.2	Extensibility	9

1 Introduction

This essay extends the investigation of simple harmonic motion by studying the damping force of a damped oscillator submerged in water, aiming to scrutinize the relationship between the mass of the block and the damping ratio. By scrutinizing this relationship, the study aims to offer valuable insights that can inform the design of systems seeking to optimize damping levels for safety-related objectives.

1.1 The Research Question

What is the relationship between the mass of a damped spring-block oscillator ([masses TBD]) and the damping ratio?

1.2 Background Information

An ideal and rather theoretical spring-mass system oscillates indefinitely, producing an ongoing sine or cosine curve. In reality, there will be a damping force that can be as minimally consequential as air resistance or as observable as viscous drag in a liquid. Anyway, energy is dissipated to the surroundings and hence the amplitude will gradually decrease until the oscillation stops.

The extent to which the viscous drag force, modeled by Stoke's law, diminishes the oscillatory motion submerged in water depends on the mass of the oscillator. This investigation delves into the relationship between the independent variable of mass m , and the dependent variable of the damping ratio ζ . The mass set used in the system consists of spheres of equal radii but different densities.

Stoke's law determines the drag force acting upon an object traveling through a fluid. It is proportional to the object's velocity and is given by the following per the Physics Data Booklet, in Newtons

$$F_d = 6\pi r\eta v$$

This law holds iff. the object speed is low such that the flow to be *laminar*, and the object

is *spherical*.

Assumption 1. *The damping force is the viscous drag force.*

Moreover, the motion of the oscillator is modeled by the following differential equation, with the damping force proportional to velocity (Miller, 2004):

$$m\ddot{x}(t) + b\dot{x}(t) + kx(t) = 0 \quad (1)$$

The damping ratio ζ is defined as the ratio of the damping coefficient to the critical damping coefficient — the damping coefficient when the system returns to equilibrium without completing an oscillation. That is

$$\zeta = \frac{b}{c_c} = \frac{b}{2mw_0}$$

where w_0 is the natural frequency of the system

$$w_0 = \sqrt{\frac{k}{m}} \\ \Rightarrow \zeta = \frac{b}{2\sqrt{mk}}$$

1.3 Hypothesis

Suppose that the constant of proportionality of the damping force with speed is given by $b = 6\pi r\eta$, per Stoke's law. Then

$$6\pi r\eta = 2\zeta\sqrt{mk} \\ 9\pi^2 r^2 \eta^2 = \zeta^2 mk \\ \frac{\zeta^2}{m^{-1}} = \frac{9\pi^2 r^2 \eta^2}{k}$$

Proposition 1. *For a fixed sphere radius r and viscosity η ,*

$$\zeta^2 \propto m^{-1} \quad (2)$$

Equivalently, the graph ζ^2/m^{-1} is ideally a straight line, although not necessarily passing through the origin, as some form of systematic errors are expected.

Proposition 1 has a few dependencies that may affect its accuracy. It relies on Assumption 1, which, in turn, requires that the flow is laminar. This is a reasonable assumption given that the spheres are relatively small, and the speed is low; the potential for turbulence is insignificant and even if present, the impact is minimal. Furthermore, the buoyancy force on the object

$$F_b = \rho g V$$

is always present but is not modeled in the differential equation at eq. (1). Notwithstanding, the absence of considerations of buoyancy has negligible impact on precision. The setup involves spheres of radius 2.5cm and water of density 997kg m^{-3} , then

$$F_b \approx 10 \times 1000 \times \frac{4}{3}\pi(2.5 \times 10^{-2})^3 < 1\text{N}$$

Null hypothesis (H_0): There is no relationship between the mass and the damping ratio.

Alternative hypothesis (H_1): There is a relationship between the mass and the damping ratio.

2 Research Design

2.1 Variables

Variables		Explanation	Measurement
Independent	Mass m	The masses of the spherical metal bobs	Measured using an electric balance, to two d.p. with uncertainty $\pm 0.005\text{g}$
Dependent	Peak Amplitude	At least 5 consecutive peaks, if the oscillation does not stop before the 5th peak, will have their heights measured. These datasets are used then to compute the damping ratio.	Ruler, with uncertainty $\pm 0.0005\text{m}$

Table 1: Variables of investigation

Control Variables		
Variable	Rationale	Means of Control
Liquid viscosity	To keep the drag coefficient per Stoke's Law constant	Using water from the same source throughout the experiment, and keep the room temperature constant by turning off the air conditioning. Unknown uncertainty
Radius of the sphere	This is so that the drag force, per Stoke's law, is constant	Using a set of spherical masses of the same diameter
Spring constant	This is so that the natural frequency of the system is constant	Using the same spring throughout the experiment. Read from the label of on the box.
Initial amplitude, A_0	So that the damping ratio is not affected by the initial conditions	Pulling the spring down by equal distances for every mass. Measured by a ruler and hence has uncertainty $\pm 0.0005\text{m}$
Damping coefficient	Linearizes relationship between damping ratio and mass	Previous means of control keep fluid viscosity and object dimensions constant, so the damping coefficient, which depend on these, will be constant.

Table 2: Control variables

2.2 Apparatus and Materials




Figure 1: The experimental setup

1. Ruler ($\pm 0.0005\text{m}$)
2. Electric balance ($\pm 0.005\text{g}$)
3. Spring with spring constant $k = ???\text{N m}^{-1}$
4. Mass set with five spherical masses of diameter $??? \text{cm}$, and masses
 - (a) $m_1 = ???\text{g}$
5. Beaker ([dimensions here])
6. Tap water ([volume here])
7. Camera — keeps a record for future reference
8. Thermometer — to ensure that the liquid stays at a constant temperature
9. Retort stand
10. Clamp

2.3 Methodology

1. Take a piece of metal wire, and cut into segments of 3cm in length. [may change to scotch tape]
2. Arrange the masses in increasing order, i.e. $m_1 < m_2 < \dots < m_n$, where n is the number of masses in the mass set.
3. Fill in the beaker with AmL of tap water
4. Measure the temperature of the water, and record as T_0
5. Attach the clamp to the retort stand.
6. Lean the ruler vertically against the retort stand.
7. Place the beaker directly under the clamp such that the clamp lies at the center of the beaker in bird's eye view.
8. For i from 1 to n inclusive, repeat the following
 - (a) Take the i th mass, m_i , and attach its hook to the spring.
 - (b) Take a piece of metal wire, wrap it as many times as possible across the diagonal (explanation to be improved), fix and reinforce the connection between the mass and the spring.
 - (c) Attach the spring-mass pair to the clamp and let the mass hang freely.
 - (d) Adjust the height of the clamp so that the mass is submerged in the water.
 - (e) Measure the height of the mass from the surface of the desk, and record as h_0
 - (f) Adjust the vertical camera position such that it levels with the reading $(h_0 - \frac{A_0}{2})$ cm to minimize parallax error of the camera.
 - (g) For j from 1 to 3 inclusive, repeat the following
 - i. Pull the mass down by A_0 cm by reading $h_0 - A_0$ from the ruler at eye level.

- ii. Start the camera recording.
 - iii. Release the mass.
 - iv. Record the clip until the 5th negative peak is reached.
 - v. Save the clip as `Mass_i_Trial_j.mp4`
 - vi. Open the clip in a video viewer.
 - vii. Identify the first 3 negative peaks, one in each cycle.
 - viii. Record the respective heights above the desk as $\{h_k\}_{k=1}^5$.
 - ix. Then the corresponding peak amplitudes are $A_k = h_0 - h_k$
- (h) Take the average values across the three trials for each peak amplitude.

2.4 Preliminary Trials

2.5 Risk Assessment

Consideration	Relevance and Mitigation
Safety	All valuable assets are kept away from the experimental setup to prevent accidental detachments of the spring-mass system leading to the mass being thrown out and causing damage. Moreover, the amplitude was kept low to prevent fierce movements that can break the beaker or computer camera.
Ethical	No use of animals or human bodies involved. However, the recording selects the location and angle that avoids the storage and exposure of any personal information or objects of the lab owner, ensuring maximum privacy protection.
Environmental	The entire experiment aims to reuse the same water throughout to minimize water wastage. Furthermore, the spring was carefully pulled to prevent it from passing its elastic limit and become unusable for future experiments.

Table 3: Risk Assessment

3 Results

3.1 Raw Data

3.1.1 Qualitative Data

During the entire experiment, there is no spillage of water, which means that the volume is kept constant. Moreover, the spring is always able to return to its original length without any permanent deformation, indicating that the spring is not stretched beyond its elastic limit and that Hooke's Law applies throughout.

3.1.2 Quantitative Data

Mass (g)	Peak 1 (cm)					Peak 2 (cm)					Peak 3 (cm)				

3.2 Data Processing

3.2.1 Transformation

3.2.2 Uncertainty Analysis

3.3 Analysis and Interpretation

4 Conclusion

4.1 Evaluation

4.2 Extensibility

References

Miller, H. (2004). 13. natural frequency and damping ratio. *DSpace@MIT*. Retrieved May 14, 2024, from https://dspace.mit.edu/bitstream/handle/1721.1/34888/18-03Spring2004/NR/rdonlyres/Mathematics/18-03Spring2004/B76E6F4F-7B05-4DA0-A5A5-03FA4ACCB6B2/0/sup_13.pdf