11/8/21 Test cases by Tina Martin

Depending on test case mgmt tool, you can write prerequisites to running test cases and then specify to review prereq.

Prereq:

- 1. PORT set to 8088 in system environment variables
- 2. Launch .exe app
- 3. Open command prompt

Test cases:

- 1. Verify after launch DOES not wait for https connection
 - a. Steps:
 - i. Launch .exe app
 - ii. From command prompt type: curl https://127.0.0.1:8088/stats
 - iii. Expected result: Should not return stats
- 2. Verify after launch waits for http connection
 - a. Steps:
 - i. Launch .exe app
 - ii. From command prompt type: curl http://127.0.0.1:8088/stats
 - iii. Expected result: Should return stats with 0 for TotalRequests and AverageTime
- 3. Verify incorrect port does not grant access
 - a. Steps:
 - i. Launch .exe app
 - ii. From command prompt type: curl http://127.0.0.1:8089/stats
 - iii. Expected result: Should return connection refused message
- 4. Verify valid port grants access
 - a. Steps:
 - i. Launch .exe app
 - ii. From command prompt type: curl http://127.0.0.1:8088/stats
 - iii. Expected result: Should return stats with 0 for TotalRequests and AverageTime
- 5. Verify post to /hash accepts password with special characters.
 - a. Steps:
 - i. Launch .exe app
 - ii. From command prompt type: curl -X POST -H "application/json" -d "{\"password\":\"angrymonkey@\"}" http://127.0.0.1:8088/hash
 - iii. Expected results: Should return job identifier NOTE: Write down job identifier as it will be used in next test case
- 6. Verify get DOES NOT return plain text password
 - a. Steps:

- i. Launch .exe app
- ii. From command prompt type: curl -H "application/json" http://127.0.0.1:8088/hash/x where x is the identifier
- iii. Expected results:
 - 1. Should not return plain text password
 - Should return base64 encoded password (NOTE: Go to https://www.base64decode.org/>select decode button>copy in the returned encrypted password. After converting it should match password.
- 7. Verify stats match requests sent in milliseconds
 - a. Steps:
 - i. Launch .exe app
 - ii. From command prompt type: curl http://127.0.0.18088/stats
 - iii. Expected result:
 - Should return TotalRequests that match how many POSTS you did
 - 2. Should return AverageTime in milliseconds
- 8. Verify app can handle multiple connections
 - a. Launch .exe app
 - b. Launch 2 command windows and in each one change the password in this line: curl -X POST -H "application/json" -d "{\"password\":\"angrymonkey\"}" http://127.0.0.1:8088/hash
 - c. Hit enter in both
 - d. Expected results: Each command should process and increment the identifier by number of requests
- 9. Verify number of requests is reset with server restart
 - a. Launch .exe app
 - b. From command prompt type: curl -X POST -H "application/json" -d "{\"password\":\"angrymonkey\"}" http://127.0.0.1:8088/hash
 - c. From command prompt type: curl http://127.0.0.1:8088/stats
 - d. Close .exe app
 - e. Retype your curl http://127.0.0.1:8088/stats
 - f. Expected results: Stats should return back to 0 for TotalRequests & AverageTime
- 10. Verify post is processed before ungraceful shutdown is completed.
 - a. Steps:
 - i. From command prompt type: curl -X POST -H "application/json" -d "{\"password\":\"angrymonkey\"}" http://127.0.0.1:8088/hash
 - ii. Close .exe app
 - iii. Expected results: Should process the request and not error out
- 11. Verify post is processed before shutdown is completed.
 - a. Open 2 command prompts
 - b. Command prompt 1: curl -X POST -H "application/json" -d "{\"password\":\"angrymonkey\"}" http://127.0.0.1:8088/hash

- c. Command prompt 2: curl -X POST -d "shutdown" http://127.0.0.1:8088/hash
- d. Expected result:
 - i. Command 1: Should return identifier code
 - ii. Should close .exe open app
- 12. Verify shutdown returns 200 code
 - a. Steps:
 - i. From command prompt type: curl -X POST -d "shutdown" http://127.0.0.1:8088/hash
 - ii. Expected results:
 - 1. Should return 200 code
 - 2. Should close .exe open app
- 13. Verify no password requests when app is shutdown
 - a. Open 2 command prompts
 - b. Command prompt 1: curl -X POST -d "shutdown" http://127.0.0.1:8088/hash
 - c. Command prompt 2: curl -X POST -H "application/json" -d "{\"password\":\"angrymonkey\"}" http://127.0.0.1:8088/hash
 - d. Expected result: On command prompt 2 should connection refused error msg
- 14. Verify GET is rejected when server is shutdown
 - a. Make sure .exe is closed
 - b. From command prompt type: curl -H "application/json" http://127.0.0.1:8088/hash/x where x is the identifier
 - c. Expected result: Should receive connection refused msg