tsmc Taiwan Semiconductor Manufacturing Co., LTD

| SECURITY B |
|-----------------------|
| SMC-RESTRICTED SECRET |

| Ver. | Eff_Date | ECN No. | Author | Change Description | |
|--|----------|---------------|------------|--|--|
| 1.0C | 10-29-10 | E070201041043 | P. Y. Wang | Migration to OA by Cadence AFM | |
| 1.00 | 10-23-10 | L070201041043 | (PDKD) | Wilgration to OA by Cadence Ar W | |
| | | | (I BIXB) | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | 1,0 | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | CI | | |
| | | | | | |
| | | | 715 | | |
| | | | | | |
| | | | | | |
| | | | 0 .2 | \(\frac{1}{2}\) | |
| | | | 0 | | |
| | | 7 | | | |
| | | | 10 | 0.0 | |
| | | | | 9 7 | |
| | | | 90.1 | 7- " " (0 | |
| | | | | | |
| | | | | $\sim 0.$ | |
| | | | | | |
| Appro | vals: | | | Title | |
| | | | | | |
| Please refer EDW workflow to see detail approval | | | | TSMC 65 NM CMOS RF MIXED SIGNAL | |
| record | records | | | GENERAL PURPOSE PLUS 1P9M | |
| | | | | SALICIDE CU_LOWK 1.0&2.5V PDK | |
| | | | | (CADENCE OA6.1 VERSION) (WITH | |
| | | | | UNDER-DRIVE 1.8V / 2.5V | |
| | | | | OVER-DRIVE 3.3V DEVICES) | |
| | | | | (INCLUDES: CRN65G+ 2.5V) | |
| | | | | | |
| | | | | Document No.: T-N65-CM-SP-018-K3 | |
| | | | | | |
| | | | | File: | |
| | | | | PDK_CRN65GP_v1.0c_official_IC61_20101010 | |
| | | | | _all.tar.gz | |
| | | | | Size: 584,943,544 (bytes) | |

tsmo

Taiwan Semiconductor Manufacturing Co., LTD

SECURITY **B**TSMC-RESTRICTED SECRET

| Ver. | Eff_Date | ECN No. | Author | Change Description |
|------|----------|---------------|------------|---|
| 1.0A | 08-07-08 | E070200830020 | P. Y. Wang | Original (This is the first OA6.1 version of CRN65GP PDK) |
| 1.0B | 01-21-09 | E070200904030 | P. Y. Wang | Change RTMOM layout from rectangle dummy OD to strip dummy OD. Enhance RTMOM layout connectivity from top metal layer to all RTMOM stack layers and the connection pin from top/bottom to "L-shape" increase route flexibility. Add 1p8m_5x2z0u RC Raphael Table in order to support parasitic devices. Fix mosfet layout pcell issue in "SDshrink" and "routePolydir" option. Solve Cadence tool issue of device hspiceD current probe problem Fix eldoD netlist out of two terminal resistors: rnod rnodwo rnpoly rnpolywo rpod rpodwo rppoly rppolywo (TSMC PDK fix the propMapping "nil I sumL w sumW"> "nil" this revise will avoid the sumL/sumW into I/w) Change the default value typo of mimcap_udc*(2T/3T)and the default value typo of mimcap* (2T/3T) Fix TSMC Utility -> "Add MOM key license" error when user installs "MM" (mixed-mode pdk). Fix AMS netlist out due to Cadence AMS netlist out tool issue. (Resistors AMS netlist problem in serial/parallel in resistor segment) |
| | | l | l | Title |
| | | | | TSMC 65 NM CMOS RF MIXED SIGNAL GENERAL PURPOSE PLUS 1P9M SALICIDE CU_LOWK 1.0&2.5V PDK (CADENCE OA6.1 VERSION) (WITH UNDER-DRIVE 1.8V / 2.5V OVER-DRIVE 3.3V DEVICES) (INCLUDES: CRN65G+2.5V) |
| | | | | Document No. : T-N65-CM-SP-018-K3 |
| | | | | |