CS:5980
Foundations of Embedded Systems

Asynchronous Model
Part III

Copyright 2014-26, Rajeev Alur and Cesare Tinelli.
Created by Cesare Tinelli at the University of Iowa from notes originally developed by Rajeev Alur at the University of Pennsylvania. These notes are copyrighted materials and may not be used in other course settings outside of the University of Iowa in their current form or modified form without the express written permission of one of the copyright holders. During this course, students are prohibited from selling notes to or being paid for taking notes by any person or commercial firm without the express written permission of one of the copyright holders.

Asynchronous Coordination Protocols


In the Asynchronous Model, coordination between processes is often necessary

Algorithms for solving coordination problems cannot assume processes proceed in lock-step rounds (as in the synchronous model)

This imposes unique design challenges for coordination protocols

We will see a few challenges next

Leader Election



Recall: Several network nodes elect a unique node as a leader

- Exchange messages to find out which nodes are in network
- Output the decision using the variable status

Requirements:

- Eventually, every node sets status to either leader or follower
- Only one node sets status to leader

Asynchronous Leader Election

Asynchronous network

- Channel models directed network link
- If there is a channel C between nodes M and N,
  then synchronization on C allows M to send a message to N


Key challenge: no notion of global execution round

- Synchronous solution strategy (executing protocol for k rounds implies that message has traveled k hops) does not work here!

Simplification assumption: processes are connected in a unidirectional ring

- Protocols for general topologies exist, but are more complex


Sample Asynchronous Ring Network



Setting:

- Each process has a unique identifier
- A process does not know the size of the ring (number of processes)
- Execution model is asynchronous
- Each process executes its protocol faithfully (no failures)

Asynchronous Execution in a Ring




One step in the execution of the system is either

- a local step in one of the processes, or
- a communication step that transfers message
  - from front of output queue y of P
    to back of input queue x of P's right neighbor

Adapting Synchronous Algorithm


Flooding Algorithm

- Set variable id to MyID, and initialize queue y to contain id
- Local step/task
  - Remove a value v from queue x
  - If v > id, then change id to v, and enqueue v in queue y
- When should a process stop and decide?
  - If v equals id !
  - This would imply that MyID has traversed the entire ring
- What is an upper bound on the number of messages exchanged?
  - Quadratic, $O(N^2)$, where N is number of processes




Improved Flooding Algorithm

1. Set id to MyID, and initialize queue y to contain id, which will be communicated to right neighbor
2. Store value from left neighbor also in state variable id1, and relay it to right neighbor (by adding it to queue y)
3. Store another value from left neighbor in state var id2
   - id = MyID, id1 = left neighbor, id2 = left-left neighbor




4. If id1 > max(id, id2), set id to id1, set id1 to 0, and go to step 2
   - Continue to next phase as active, but with different identifier
5. If id1 <= max(id, id2), decide to be a follower and continue as a passive participant
   - Just relay values in input queue to output queue


Example Execution



Example Execution



Example Execution




Since first message from left neighbor equals id, stop and become the leader!

Algorithm Properties

- Actual execution proceeds asynchronously
  - Messages are processed at arbitrary times
  - Different processes may be executing different phases
- The process that becomes leader need not be the one with the highest original identifier
- In each phase, each process sends only 2 messages
- Among processes active during a phase, if a process remains active in next phase, then its left neighbor can not remain active (why?)
- At least one and at most half of the processes continue to next phase
  - Construct scenarios for these two extremes
  - For a ring of N processes, at most $\log N$ phases, so a total of $O(N \log N)$ messages
  - Tight lower bound: cannot solve leader election in a ring while exchanging fewer messages


Unreliable FIFO



Models a link that may lose and/or duplicate messages

How to implement a reliable FIFO link using unreliable ones?

Reliable Transmission Problem



Requirement: Design asynchronous processes S and R so that

- sequence of messages received on channel in coincides with sequence of messages delivered on channel out


Alternating Bit Protocol

1. How can sender S ensure that receiver R gets a copy of S's message on a lossy link?
   - S must repeatedly send a message
   - R must repeatedly send back an acknowledgement
2. How can receiver R distinguish between a repeated message and a fresh message?
   - Each message must be tagged with extra bits

Alternating bit protocol

- **Key insight:** tagging each message and acknowledgement with a single bit suffices
- Both S and R keep a local tag bit
- if the incoming message tag matches with the local tag, message is considered fresh, and local tag is toggled

ABP Sender




Task A: Store incoming messages in queue q

Task B: Transmit message at front of queue q tagged with local tag

Do not remove the message: this ensures it can be retransmitted

Task C: If ack a2 matches tag, then message successfully delivered; remove it from q, and flip tag

ABP Receiver



Task A: Transmit outgoing messages from queue q to output channel out

Task B: Transmit local tag as acknowledgement on channel a1


Note: Same acknowledgement may be transmitted repeatedly

Task C: If tag of incoming message (Second(m2)) differs from local tag, then message is new; so, add message to q and flip tag

ABP Example Execution

1. Initially S.tag = 1 and R.tag = 0
2. S receives a message m to be delivered
3. S repeatedly sends (m,1) over unreliable link
4. Eventually, R gets at least one, maybe multiple, copies of (m,1)
5. Meanwhile, R is sending 0, possibly multiple times, but all these acknowledgements are ignored by S for a while
6. When R gets (m,1) the first time, it stores m in its queue q (and this message will then eventually be transmitted on out), and sets tag to 1
7. Duplicate versions of (m,1) are ignored by R
8. R repeatedly sends the acknowledgment 1 over unreliable link
9. Eventually, S gets at least one ack = 1. It then removes m from input queue, and sets its tag to 0
10. Later duplicate versions of ack = 1 are ignored by S
11. Input messages received by S are queued up in S.q
    S repeats the cycle by sending next message m' along with tag 0

Exercise: ABP Variations



1. Suppose unreliable link can lose messages but is guaranteed not to duplicate a message. Can we simplify the protocol?

2. Suppose unreliable link can also reorder messages, in addition to losing and duplicating them. How should we modify the protocol to ensure reliable transmission?
   Hint: a Boolean-valued tag is not enough. Messages need to be tagged with a counter variable of type **nat**

Consensus

Goal of coordination: Exchange information and arrive at a common decision value

Initial state: Each process starts with its own initial preference value, known only to itself

Classical example: Byzantine Generals Problem communicating by messengers to decide on whether or not to attack

Our focus: Two processes P1 and P2 with Boolean preferences, and communicating by shared memory

P1 and P2 start with initial Boolean preferences pref1 and pref2, and
arrive at Boolean decisions dec1 and dec2 so that we have

1. *Agreement*: dec1 must equal dec2
2. *Validity*: The decision value must be either pref1 or pref2
3. *Wait-freedom*: If from some point on only one process is executed repeatedly, it eventually reaches a decision
   (does not have to wait for the other, and thus, is fault-tolerant)

First Attempt at Solving Consensus

AtomicRegister boolOpt x1 := **null** ; x2 := **null**

boolOpt := { 0, 1, **null** }

Process P1

bool pref1, dec1

boolOpt y1 := **null**

x1 := pref1

y1 := x2

if y1 != **null**
then dec1 := pref1 ∨ y1
else dec1 := pref1

Process P2

bool pref2, dec2

boolOpt y2 := **null**

x2 := pref2

y2 := x1

if y2 != **null**
then dec2 := pref2 ∨ y2
else dec2 := pref2

- Write pref in a shared var
- If other's pref is absent, choose your own initial pref
- Otherwise, decide on OR of the two prefs

Agreement?


Validity?

Wait-freedom?

Second Attempt at Solving Consensus

AtomicRegister boolOpt x1 := **null** ; x2 := **null**

boolOpt := { 0, 1, **null** }



- Write pref in a shared var
- If other's pref is absent, read again
- Otherwise, decide on OR of the two prefs

Agreement?

Validity?

Wait-freedom?

Impossibility of Consensus

Theorem. There is no protocol for two-process consensus such that both of the following hold:

1. Processes communicate using only shared atomic registers.
2. Protocol satisfies agreement, validity, and wait-freedom.

Solving Consensus

Why solving consensus using only atomic registers is impossible:

- Primitives of read and write are too weak to achieve desired coordination while satisfying all 3 requirements

Intuitive difficulty:

- When a process writes a shared variable, it does not know whether the other process has read this value, so cannot decide right away
- When a process reads a shared variable, it needs to communicate to other process that it has seen this value, so needs to continue

Byzantine Generals Problem: Coordination with just atomic registers impossible


- Sending a message, and receiving a message are similar to write and read operations

Solution: Use stronger primitives such as Test&Set registers


Consensus using Test&Set Register

AtomicRegister bool x1, x2 ; **Test&SetReg** y := 0

Process P1



Process P2



- Write value in a shared var
- Execute test&set
- If you *win*, choose your own initial value
- Otherwise, read other's preference as decision value

Agreement?

Validity?

Wait-freedom?

Credits

Notes based on Chapter 4 of

Principles of Cyber-Physical Systems
by Rajeev Alur
MIT Press, 2015