

CS:5980

Foundations of Embedded Systems

Safety Requirements

Part II

Copyright 2014-26, Rajeev Alur and Cesare Tinelli.

Created by Cesare Tinelli at the University of Iowa from notes originally developed by Rajeev Alur at the University of Pennsylvania. These notes are copyrighted materials and may not be used in other course settings outside of the University of Iowa in their current form or modified form without the express written permission of one of the copyright holders. During this course, students are prohibited from selling notes to or being paid for taking notes by any person or commercial firm without the express written permission of one of the copyright holders.

A Brief Detour into Computational Complexity

Goal: Classify computational problems in terms of (roughly) how many basic operations it takes to solve the problem, as function of input size

Example 1: Finding maximum of a list of numbers

- Time complexity is linear: $O(n)$

Example 2: Sorting an array of numbers

- Algorithm (e.g., selection sort) with doubly-nested loop: $O(n^2)$
- More efficient algorithms (e.g., quicksort) possible: $O(n \log n)$

A Brief Detour into Computational Complexity

Goal: Classify computational problems in terms of (roughly) how many basic operations it takes to solve the problem, as function of input size

Example 3: Boolean expression evaluation. Given

1. an expression e (with not/or/and as operations) over Boolean vars, and
2. an assignment a of 0/1 values to vars,

determine whether e evaluates to 1 or 0. Time complexity: $O(n)$

Example 4: Boolean satisfiability. Given a Boolean expression e , determine if there is an assignment a to vars that makes the expression evaluate to 1

- Naïve algorithm: Evaluate e on every possible assignment a
- Exponentially many choices for a : algorithm is $O(2^k)$, k = no. of vars

The Class P

Polynomial-time algorithm means a deterministic algorithm with time complexity such as $O(n)$, $O(n \log n)$, $O(n^2)$, $O(n^3)$, or $O(n^c)$, for some constant c

A problem is in **P** if there is a polynomial-time algorithm to solve it

Examples:

- Finding maximum
- Sorting
- Expression evaluation
- Finding shortest path in a graph

P is the class of *tractable* (i.e., efficiently solvable) problems

- Problem can be solved exactly
- Solution will scale reasonably well as input size grows
- In principle (asymptotically), $O(n)$ is better than $O(n^2)$

NP-Complete Problems

SAT: Given a Boolean expression e , check if there exists an assignment of 0/1 values to its variables for which e evaluates to 1

- No proof that SAT is in P (no known polynomial-time algorithm)
- No proof that SAT is not in P
- SAT is in $NP = \{ \text{problems where every candidate solution is checkable in polynomial time} \}$
- SAT is *NP-complete* (Cook, 1972)
- Hundreds of problems equivalent to SAT

Hamiltonian Path: Is there a path in a graph from source to destination that visits each vertex exactly once

Max Clique: Given a graph, find largest subset of vertices such that there is an edge between every pair of vertices in this set

Grand Challenge Open Problem: Is $P = NP$?

- If you find a polynomial-time algorithm for SAT, then $P = NP$, and many other problems will have polynomial-time algorithms
- If you prove SAT is not in P , then $P \neq NP$, and many other problems then provably don't have efficient algorithms

NP-Completeness Continued

Known algorithms for SAT are exponential-time in the worst-case, but

- Highly efficient implementations, SAT solvers, exist
- They can handle tens of millions of variables for real-world problems
- Many practical problems solved by encoding into SAT

Key feature of NP problems such as SAT: it suffices to find one satisfying assignment

This does not hold for all intractable problems

- **Boolean Validity:** Given a Boolean expression e , is it the case that e evaluates to 1 no matter what values we give to its variables

There are many complexity classes beyond NP: coNP , PSPACE , EXPTIME , ...

- Problems may require exponential-time (or more) to solve

What we know

- $P \subseteq NP \subseteq \text{PSPACE} \subseteq \text{EXPTIME} \subseteq \text{NEXPTIME} \subseteq \text{EXPSPACE}$
- $P \subsetneq \text{EXPTIME}$, $NP \subsetneq \text{NEXPTIME}$ and $\text{PSPACE} \subsetneq \text{EXPSPACE}$

(Un)Decidability

Some general problems cannot be solved by a computer at all!

Decidable Problem: There exists a program, or Turing machine, that solves all instances of the problem correctly (i.e., gives the right answer and stops)

- Includes problems in **P** as well as intractable classes such as **NP**, **Exptime**, etc.

Fundamental Theorem of CS (Turing, 1936): The *Halting problem* for Turing machines is **undecidable**

- There is no program that takes as its input an **arbitrary** program **C** and an **arbitrary** input **x**, and determines if **C** terminates on **x**

Intuition: If a program could analyze other programs exactly, then it can analyze itself, and this suffices to set up a logical contradiction!

A surprisingly undecidable problem: Does a given polynomial (e.g., $x^3 + 2xy^2 - 15xy + 16$) have integer roots?

Back to Invariant Verification Problem



Theorem: The invariant verification problem is **undecidable**

Proof idea: undecidable problems for Turing machines can be recast as invariant verification problems for transition systems with integer state variables

Finite-State Invariant Verification Problem




Theorem: The invariant verification problem for finite-state systems is **decidable**

Proof sketch: If T has k Boolean state vars, then total number of states is 2^k .

Verifier can systematically search through all possible states.

Complexity is **exponential**. More precisely, it is **PSPACE-complete**, and so harder in practice than **NP-complete** problems such as SAT



Credits

Notes based on Chapter 3 of

Principles of Cyber-Physical Systems

by Rajeev Alur

MIT Press, 2015