



APIS TODO - ENTRANCE TEST

POST Sign-up

http://localhost:3000/register

BODY raw

```
{
  "username": "test789",
  "password": "123456"
}
```

Example Request

Sign-up

```
curl --location --request POST 'http://localhost:3000/register' \
--data-raw '{
  "username": "test789",
  "password": "123456"
}'
```

POST Sign-in

http://localhost:3000/login

BODY raw

```
{
  "username": "test789",
  "password": "123456"
}
```



Example Request

Sign-in

```
curl --location --request POST 'http://localhost:3000/login' \  
--data-raw '{  
  "username": "test789",  
  "password": "123456"  
'
```

POST Add-todo

AUTHORIZATION

Bearer Token

Token

<token>

BODY raw

```
{  
  "id": "3",  
  "name": "Thêm chức năng đăng nhập/đăng ký",  
  "descript": "Implementation chức năng đăng nhập/đăng ký cho website",  
  "status": "New",  
  "UserId": "",  
  "Date_complete": "2022-02-28"  
}
```

Example Request

Add-todo

```
curl --location --request POST 'http://localhost:3000/todo' \  
--data-raw '{  
  "id": "3",  
  "name": "Thêm chức năng đăng nhập/đăng ký",  
  "descript": "Implementation chức năng đăng nhập/đăng ký cho website",  
  "status": "New",  
  "UserId": "",  
  "Date_complete": "2022-02-28"  
}'
```

```
"Date_complete": "2022-02-28"
```

```
}'
```

Documentation Settings ▼

PUT UPDATE-TODO

```
http://localhost:3000/todo_update
```

AUTHORIZATION

Bearer Token

Token

<token>

BODY raw

```
{
  "id": "3",
  "Date_complete": "2022-02-25"
}
```

Example Request

UPDATE-TODO

```
curl --location --request PUT 'http://localhost:3000/todo_update' \
--data-raw '{
  "id": "3",
  "Date_complete": "2022-02-25"
}'
```

GET GET-ALL-TODO

```
http://localhost:3000/get-all-user
```

AUTHORIZATION

Bearer Token

Token

<token>

BODY raw

Documentation Settings ▼

```
{
  "userId": "621212d6da9fa410c0aae175"
}
```

Example Request

GET-ALL-TODO

```
curl --location --request GET 'http://localhost:3000/get-all-user' \
--data-raw ' {
  "userId": "621212d6da9fa410c0aae175"
}'
```

DEL REMOVE-TODO

```
http://localhost:3000/del/2
```

AUTHORIZATION

Bearer Token

Token

<token>

Example Request

REMOVE-TODO

```
curl --location --request DELETE 'http://localhost:3000/del/2'
```

GET GET-TODO-BYID

```
http://localhost:3000/todo/2
```

AUTHORIZATION

Bearer Token

Token

Documentation Settings ▼

<token>

Example Request

GET-TODO-BYID

```
curl --location --request GET 'http://localhost:3000/todo/2'
```

GET GET-ALL-USER**AUTHORIZATION**

Bearer Token

Token

<token>

Example Request

GET-ALL-USER

```
curl --location --request GET 'http://localhost:3000/get-all-user'
```

PUT ASSIGN-TODO**AUTHORIZATION**

Bearer Token

Token

<token>

BODY raw



```
{  
  "userId": "6212133a215dc40c58864d76"  
}
```

Example Request

ASSIGN-TODO

```
curl --location --request PUT 'http://localhost:3000/assign_todo/1' \  
--data-raw '{  
  "userId": "6212133a215dc40c58864d76"  
}'
```

GET GET-ALL-TASK-BY-USER

```
http://localhost:3000/get-all-task/6212133a215dc40c58864d76
```

AUTHORIZATION

Bearer Token

Token

<token>

Example Request

GET-ALL-TASK-BY-USER