

Hierarchical Modelling

Complete guide for Section 6 + Lab 2 coding

Includes: Subroutines, Scene Graphs, Transformations, Save/Restore, Animation

Tips: Use subroutines for simple hierarchies; scene graphs for reuse/complexity. Always save/restore to isolate transforms. Test incrementally.

1. Introduction to Hierarchical Modelling

Break complex objects into simpler parts in a tree structure.

- **Benefits:** Reuse, easy animation, modular code.
 - **Coding Tip:** Start from leaf nodes (basic shapes) and build up to root (full scene).
 - **Example Scene:** Windmill (base + rotating blades), Cart (body + wheels).
 - **Common Mistake:** Forgetting to isolate transforms – leads to unwanted propagation (e.g., rotating blades rotate the ground).
-

2. Subroutine Hierarchy (Section 6.2)

Build with functions – each draws a part, calls sub-parts.

2.1 Basic Subroutine Example

```
function drawRectangle(g, x, y, width, height, color) {  
    g.fillStyle = color;  
    g.fillRect(x, y, width, height);  
}
```

Tip: Parameters for flexibility (position, size, color).

Technique: Define basics first (rect, circle, triangle).

2.2 Creating Hierarchical Structure

Parent calls children.

```
function drawHouseBase(g, x, y, width, height) {  
    drawRectangle(g, x, y, width, height, 'brown'); // Walls  
    drawRectangle(g, x + width/3, y + height/2, width/3, height/2, 'black'); //  
    Door  
}  
  
function drawRoof(g, x, y, width, height) {  
    g.fillStyle = 'red';  
    g.beginPath();
```

```

    g.moveTo(x, y);
    g.lineTo(x + width / 2, y - height);
    g.lineTo(x + width, y);
    g.closePath();
    g.fill();
}

function drawHouse(g, x, y, width, height) {
    drawHouseBase(g, x, y, width, height * 0.75);
    drawRoof(g, x, y, width, height * 0.25);
}

```

Tip: Use relative coords (0,0 center) for easy transforms.

Technique: Test each function alone in draw().

2.3 Applying Transformations

Modify coordinate system for positioning.

```

function drawHouse(g, x, y, width, height, angle) {
    g.save();
    g.translate(x, y);          // Position
    g.rotate(angle);           // Orientation
    g.scale(width/100, height/100); // Assume base size 100
    drawHouseBase(g, -50, -50, 100, 75); // Centered at 0,0
    drawRoof(g, -50, -50, 100, 25);
    g.restore();
}

```

Order: Scale → Rotate → Translate (fixed in Canvas).

Tip: Use `g.transform(1, shearY, shearX, 1, 0, 0)` for skew.

2.4 Save and Restore (Importance & How-To)

Isolate transforms to prevent leakage.

Importance: Without it, child transforms affect siblings/parents (e.g., wheel rotation rotates cart body).

How-To: `save()` before transforms, `restore()` after drawing sub-object.

Stack Behavior: Push (save) / Pop (restore) – match every save with restore.

Example (Nested):

```

function drawWindmill(g) {
    g.save();                // Save for base
    g.translate(0, 2);       // Position base
    drawBase(g);
    g.restore();
}

```

```

    g.save();                // Save for blades
    g.translate(0, 2);        // Position top
    g.rotate(frameNumber * 0.1); // Animate blades
    drawBlades(g);
    g.restore();
  }

```

Tip: If bugs, log transform state or draw debug axes.

Technique: For animation, update inside subroutine (e.g., rotate based on frameNumber).

3. Scene Graphs (Section 6.3)

Object-oriented data structure – nodes for objects/transforms.

3.1 SceneGraphNode (Base)

Abstract – override `doDraw(g)` for custom drawing.

Example (Line):

```

let line = new SceneGraphNode();
line.doDraw = function(g) {
  g.beginPath();
  g.moveTo(-0.5, 0);
  g.lineTo(0.5, 0);
  g.stroke();
};

```

3.2 CompoundObject (Group Sub-Objects)

```

function CompoundObject() {
  SceneGraphNode.call(this);
  this.subobjects = [];
}
CompoundObject.prototype.add = function(node) {
  this.subobjects.push(node);
  return this; // Chainable
};
CompoundObject.prototype.doDraw = function(g) {
  this.subobjects.forEach(sub => sub.draw(g));
};

```

Tip: Use for groups (e.g., wheel = circle + spokes).

3.3 TransformedObject (Apply Transforms)

```
function TransformedObject(object) {
  SceneGraphNode.call(this);
  this.object = object;
  this.rotationInDegrees = 0;
  this.scaleX = 1; this.scaleY = 1;
  this.translateX = 0; this.translateY = 0;
}
TransformedObject.prototype.setRotation = function(deg) {
  this.rotationInDegrees = deg;
  return this;
};
TransformedObject.prototype.setScale = function(sx, sy) {
  this.scaleX = sx; this.scaleY = sy;
  return this;
};
TransformedObject.prototype.setTranslation = function(dx, dy) {
  this.translateX = dx; this.translateY = dy;
  return this;
};
TransformedObject.prototype.doDraw = function(g) {
  g.save();
  g.translate(this.translateX, this.translateY);
  g.rotate(this.rotationInDegrees * Math.PI / 180);
  g.scale(this.scaleX, this.scaleY);
  this.object.draw(g);
  g.restore();
};
```

Chain example:

```
.setScale(2,2).setRotation(45).setTranslation(100,100)
```

Tip: Transforms auto-isolated with save/restore.

3.4 Building a Scene (Car Example)

```
let world = new CompoundObject();

// Wheel
let wheelTemp = new CompoundObject();
wheelTemp.add( new TransformedObject(filledCircle).setScale(2,2) );
for (let i = 0; i < 12; i++) {
  wheelTemp.add( new TransformedObject(line).setRotation(i*30) );
}
let wheel = new TransformedObject(wheelTemp);

// Cart
let cartTemp = new CompoundObject();
```

```

cartTemp.add( new
TransformedObject(wheel).setScale(0.8,0.8).setTranslation(-1.65,-0.1) );
cartTemp.add( new
TransformedObject(wheel).setScale(0.8,0.8).setTranslation(1.65,-0.1) );
cartTemp.add( new
TransformedObject(filledRect).setScale(6,1.5).setTranslation(0,1) );
let cart = new TransformedObject(cartTemp).setScale(0.3,0.3);

world.add(cart);

```

How to Make Your Own: Define templates (CompoundObject), wrap in TransformedObject for positioning. Add to root.

3.5 Traversal & Stack

Push/Pop: Auto in `doDraw()` (save/restore).

Importance: Ensures child transforms don't affect siblings.

Tip: For complex, visualize tree – draw on paper first.

4. Animation (Section 6.4)

Update in `updateFrame()` – redraw full scene.

Basic Update

```

function updateFrame() {
  frameNumber++;
  cart.setTranslation(Math.sin(frameNumber * 0.05) * 2, 0); // Oscillate
  wheel.setRotation(frameNumber * 3); // Spin
}

```

Tips: Use % for loops, `Math.sin/cos` for smooth motion.

Techniques: Procedural (physics-like), keyframe interpolation (lerp between poses).

Advanced: Inverse Kinematics (IK) for limbs – calculate joint angles from end position.

Example: Ferris Wheel (Ex 3 Idea)

```

let wheel = new TransformedObject(wheelTemp).setRotation(frameNumber * 0.05); //
Spin wheel
for (let i = 0; i < 8; i++) {
  let seat = new TransformedObject(seatTemp)
    .setTranslation(0, r)
    .setRotation(-frameNumber * 0.05) // Counter-rotate seat to stay
horizontal
    .setRotation(i * 45); // Position on wheel
}

```

```
wheel1.add(seat);  
}
```

Make Your Own: Think real-world (sailboat rocking, airplane flying). Add multiple instances (e.g., 2 carts).

5. Exam Tips & Techniques

- **Subroutine vs Scene Graph:** Subroutines for quick/simple; Graphs for reuse/animation (easier updates).
- **Save/Restore Importance:** Prevents "bleed" – always bracket transforms.
- **How to Code Your Own:**
 1. Sketch hierarchy tree.
 2. Define basics (leaf nodes).
 3. Build composites (parents call children).
 4. Add transforms/animation last.
 5. Test: Comment out parts, draw one level at a time.

Common Errors: Mismatched save/restore, wrong order (translate last), forgetting relative coords.

Lab 2 Style Questions: Build cart/windmill, animate rotation/translation, create custom scene (ferris wheel, swing).