AP Physics 1

Name _____

Period _____ Date _____

Practice Test – Introductory Dynamics (Version 6)


On any problems, you must show all work, include units, round properly, and box your final answer. Do the algebra first, before plugging in values.

Rewrite the following statement in the space below: On my honor, before God, I have neither given, nor received, any aid on this test.


For all questions:


- Use g = 9.8 m/s² (9.8 N/kg). Air resistance is negligible unless the question says it is not.
- Free-body diagrams: draw the forces themselves, not components, each as an arrow starting on the dot.
- Round answers to the significant figures of the given values.
- 50 minutes. Four questions, 50 points total.

1. (12 pts) A 64-gram jellyfish normally rests on the sea bed of an aquarium. However, it can hover in the water by generating 0.12 newtons of upward thrust by pulsing its bell. What is the magnitude of the buoyant force on the jellyfish?




2. (12 pts) Draw a free-body diagram for a crate sliding down a long ramp. Friction and drag are **NOT** negligible. Label each vector you draw.





3. (12 pts) A rescue crew fires a 0.60-kilogram line weight horizontally from a 42-kilogram line launcher. The line weight experiences constant acceleration while inside the 0.60-meter-long tube, exiting at a speed of 32 meters per second. If the line launcher were not bolted to the dock and if friction with the dock were negligible, what would be the magnitude of the line launcher's acceleration?




4. (14 pts) Students measure the drag force F_D on a model rocket in a wind tunnel at several air speeds v. The drag force is modeled by $F_D = Kv^2$, where K is a constant.

Speed v (m/s)	**Drag force F_D (N)**	
20.0	1.84	
30.0	4.34	
40.0	7.77	
50.0	11.9	
60.0	17.4	
70.0	24.3	

(a) Using $F_D = Kv^2$, state the quantity you will plot on the vertical axis and the quantity you will plot on the horizontal axis so the data form a straight line, each with its units. State what the slope equals.

(b) Use the blank column in the table to calculate the values you will plot on the horizontal axis.

(c) Plot the data on the grid. Label each axis with the quantity and units, choose a scale, and draw the best-fit line.




(d) Calculate the slope of your best-fit line using two well-separated points on the line. Then give K with its units.

Answer Key – Practice Test, Version 6 – Introductory Dynamics

Worked step by step: diagram, symbolic equations and algebra first, then numbers with units. $g = 9.8\ m/s^2$ does not limit significant figures.

Numerical problems: diagram first, then a = ΣF/m (equation sheet), written a = F_{net}/m. Replace F_{net} with the actual forces and their signs, swap $F_g = mg$, solve in letters, then plug in numbers with units.
Kinematics: #1 $v = v_0 + at$ · #2 $\Delta x = v_0 t + \frac{1}{2}at^2$ · #3 $v^2 = v_0^2 + 2a\Delta x$. Pick the one that leaves out the variable you don't know and don't need.

1. Thrust and buoyancy (12 pts)



Step 1 **Diagram of the jellyfish while it hovers.**

F_g down (Earth). Thrust F_t up (the water it pushes down pushes back up on it). Buoyancy F_b up (the surrounding water).

No normal force: it is off the bottom. Hovering means not moving, so $a = 0$ and the two up arrows together match F_g.

Step 2 **Newton's second law, up is +, letters first.**

$a = \frac{F_{net}}{m} \rightarrow F_b + F_t - mg = ma$, with $a = 0$

$$\boxed{F_b = mg - F_t}$$


Step 3 **Numbers, units in every parenthesis.**

$m = 64\ g = 0.064\ kg$

$F_b = (0.064\ kg)(9.8\ m/s^2) - 0.12\ N = 0.627\ N - 0.12\ N = 0.507\ N \rightarrow$ **$F_b = 0.51\ N$**

Watch out: thrust and buoyancy both point up. Writing $F_b - F_t - mg = ma$ (thrust down) flips the sign of the thrust.

2. Free-body diagram (12 pts)



Step 1 **Every force on the crate: exactly four.**

Earth pulls on it: F_g. The ramp pushes on it two ways: F_N (perpendicular to the surface) and kinetic friction F_f (along the surface). The air pushes on it: drag F_D.

Step 2 **Directions. No angle is needed.**

F_g: straight down, vertical.

F_N: perpendicular to the slope, out of the surface, so it leans toward the left.


F_f: along the slope, uphill (up and to the right), opposite the sliding.

F_D: opposite the motion through the air. In still air the crate moves downhill through the air, so drag also points uphill, as its own arrow beside F_f.

Lengths are not graded: the motion (speeding up or not) is not stated. Every arrow starts on the dot and is labeled.

Watch out: no components of F_g drawn as extra arrows, no fifth "air resistance" arrow on top of drag, and no arrow pointing down the slope.

3. Recoil (12 pts)



Step 1 **Diagram of the line launcher while the line weight is inside.**

Horizontal: only the line weight pushing back on it (F_{weight}). Vertical: F_N up, F_g down and the line weight pressing down ($F_{weight,\ down}$), all balanced, so they stay out of the horizontal equation. Not to scale.

Step 2 **Kinematics for the line weight: no time given, so use #3.**

$v_0 = 0$, $v = 32$ m/s, $\Delta x = 0.60$ m (the tube length)

$$v^2 = v_0^2 + 2a\Delta x \rightarrow a_{line\ weight} = \frac{v^2}{2\Delta x} = \frac{(32\ \text{m/s})^2}{2(0.60\ \text{m})} =$$

$853.3\ \text{m/s}^2 \approx \boxed{8.5 \times 10^2\ \text{m/s}^2}$

Step 3 **Second law on the line weight, then the third law.**

$F_{net} = ma \rightarrow F = (0.60\ kg)(853.3\ m/s^2) = 512\ N \approx$ **5.1×10^2 N**

$F_{\text{line weight on line launcher}} = -F_{\text{line launcher on line weight}}$: the same 5.1×10^2 N, backward.

Step 4 **Second law on the line launcher.**

$$a_{\text{line launcher}} = \frac{F}{M} = \frac{512\ N}{42\ kg} = 12.19\ m/s^2 \rightarrow$$ **12 m/s², magnitude (it points backward)**

Using the tube length as the line weight's distance is fine here: the line launcher moves back only about 0.9 cm while the line weight is inside.

Watch out: equal and opposite forces, unequal accelerations: divide the same F by the much bigger mass.

4. Drag linearization (14 pts)

Step 1 **(a) Match $F_D = Kv^2$ to $y = mx + b$.**

$F_D = K \cdot (v^2) + 0$

vertical (y)	horizontal (x)	slope	intercept
F_D (N)	v^2 (m^2/s^2)	K	0

Vertical: F_D in N. Horizontal: v^2 in m^2/s^2. Slope = K.


Watch out: v^2 is speed squared, in m^2/s^2. It is not an acceleration (m/s^2).

Step 2 **(b) Square each speed; the units square too.**

Example: $(20.0\ m/s)^2 = 400\ m^2/s^2$

v (m/s)	F_D (N)	v^2 (m^2/s^2)
20.0	1.84	400
30.0	4.34	900
40.0	7.77	1600
50.0	11.9	2500
60.0	17.4	3600
70.0	24.3	4900

Step 3 **(c) Graph: labeled axes with units, a scale that uses more than half the grid, one straight line through the middle of the points.**



The best-fit line is not forced through any data point. The red squares are points read off the line, not data points.

Step 4 **(d) Slope from two well-separated points on the line, units carried.**

Points read off the line, away from data points: (600 m²/s², 2.7 N) and (4700 m²/s², 23.1 N)

$$\text{slope} = \frac{23.1\ \text{N} - 2.7\ \text{N}}{4700\ \text{m}^2/\text{s}^2 - 600\ \text{m}^2/\text{s}^2} = \frac{20.4\ \text{N}}{4100\ \text{m}^2/\text{s}^2} = 0.0049756\ \text{N}\cdot\text{s}^2/\text{m}^2$$

$K \approx 0.00498\ \text{N}\cdot\text{s}^2/\text{m}^2\ (= \text{kg/m})$. Any value from 0.00456 to 0.00535 N·s²/m² from a reasonable line earns credit.

Units: N ÷ (m²/s²) = N·s²/m², and N = kg·m/s², so N·s²/m² = kg/m.

1. Thrust and buoyancy

Suggested partial credit	pts
Diagram: F_g down, thrust and buoyancy up, no normal force	3
Hovering, so a = 0	2
$F_b + F_t - mg = ma$ with correct signs	3
Solved in letters: $F_b = mg - F_t$	1
Grams to kg; units in every parenthesis	2
$F_b = 0.51$ N	1
Total	**12**

2. Free-body diagram

Suggested partial credit	pts
F_g straight down, labeled	3
F_N perpendicular to the slope, out of the surface, labeled	3
F_f uphill along the slope, labeled	2
F_D uphill, opposite the motion, labeled, its own arrow	2
Arrows start on the dot; no components and no extra forces	2
Total	**12**

3. Recoil

Suggested partial credit	pts
#3 with $v_0 = 0$, solved for a in letters	2
$a = 8.5 \times 10^2$ m/s² for the line weight	2
$F = ma = 5.1 \times 10^2$ N	3
Third law: same force, opposite direction, on the line launcher	2
$a = F/M = 12$ m/s² (magnitude), units and sig figs	3
Total	**12**

4. Drag linearization

Suggested partial credit	pts
(a) F_D (N) vertical, v^2 (m^2/s^2) horizontal	3
(a) Slope = K	1
(b) v^2 column correct, with units	2
(c) Axes labeled with quantity and units	2
(c) Scale uses more than half the grid; points plotted	1
(c) One straight best-fit line	1
(d) Two well-separated points read off the line	2
(d) K from 0.00456 to 0.00535, with units $N \cdot s^2/m^2$ (or kg/m)	2
Total	**14**