



Ambisonic Speaker Collection

Hardscape Loudspeaker System



6510P Loudspeaker



True Coaxial Drivers



Composite Woofer

6510P Hardscape Loudspeaker System

Description

The 6510P is a *uniquely* designed, *all-weather, hardscape system*, which features a *two-way woofer coaxial, high output* loudspeaker with integrated *10" band pass subwoofer* in an *aesthetically pleasing* convenient planter box design.

The 6501P comprises of a *high definition, ultra-high fidelity* full range loudspeaker featuring a *6" Planar Magnetic Ribbon* and a *6.5" woofer* in a true coaxial configuration. *True coaxial drivers* produce a *perfectly symmetrical coverage pattern* and *lower distortion*, due to the alignment's acoustic filter effect. Designed with unique waveguides delivering excellent dispersion and fidelity, this results in an *evenly dispersed, audiophile-quality* sound even at the highest output levels.

Meanwhile, the subwoofer delivers the punch, impact and clean tight bass necessary for hardscape installations, featuring a high power *10" long throw low frequency transducer*. The perfect compliment to our Immersive HD loudspeaker, it delivers the ultimate in "High Definition" audio for any outdoor environment. Backyard landscapes, patio and pool areas *will come alive with unparalleled clarity and detailed sound*, engineered to give you years of listening satisfaction and pleasure. The all weather enclosures offer an *"IP-65" rating*, and all components are designed to withstand the harshest of environmental conditions in any permanent outdoor installation.

Scan the QR Code for full instructions for this product.





Ferrite Motor



70V / 300W Toroidal Transformer

Available in either 8 Ohm or 70 Volt versions, the 70 Volt version arrives with a high-performance, custom built 70 Volt | 300 Watt custom Toroidal Transformer for the subwoofer, and a 70 Volt | 100 Watt custom Toroidal Transformer for the full range loud speaker.

Speaker Features

- Ultra-fast transient response and higher instantaneous peak level for faithful signal
- Wide horizontal dispersion for excellent stereo imaging and larger listening area
- Well controlled vertical dispersion reduces floor and ceiling reflections and yields longer listening distances
- Unique woofer and ribbon wave guides for better dispersion and fidelity

Subwoofer Features

- Internal cylindrical design to reduce standing waves.
- All weather long throw woofer featuring the highest quality stiff composite cone and large half roll rubber surround.
- Massive internal ferrite motor structure secured in a tuned, down firing enclosure.
- Wire pigtail Input, water tight strain relief and vented port with internal mesh grille.

Specifications

SPECIFICATIONS	COAXIAL DRIVER
System Type	Hybrid Coaxial, Ribbon, Woofer, Two-Way Full Range Loudspeaker
Driver Components	All Weather 6" Ribbon Driver + 6.5" Composite Cone Woofer
Frequency Response	50 Hz - 20 kHz (-10db) 78Hz - 20kHz +/- 3dB
Maximum SPL	109dB Continuous, 115dB Peak
System Coverage	110 degree horizontal, 60 degree vertical (averaged from 1k to 8k)
Sensitivity, 2.83V @ 1m	89 dB
Power Handling	100W AES, 200W Program 400W Peak
Recommended Amplifier Power	100W - 400W (FTC) @ 8 Ω
Rated Impedance OR Transformer	8 Ω nominal, 5.7 Ω min @ 160Hz OR 70V 100W
Crossover	Passive, Custom. Recommended HPF 45Hz, 12dB Butterworth
Input Connectors	12GA x 2ft. Pigtail

SPECIFICATIONS	SUBWOOFER DRIVER
System Type	Vented Alignment Subwoofer
Driver Components	All Weather 10" Long Throw Woofer
Crossover	Recommended HPF = 37Hz 12dB per octave Butterworth
Frequency Response	35Hz - 300Hz (-10dB) 50Hz - 300Hz +/- 3dB
Maximum SPL	118 dB Continuous, 124 dB Peak
Sensitivity, 2.83V @ 1m	93 dB
Power Handling	300W AES, 600W Max Power Handling, 1200W Peak
Rated Impedance	8 Ω OR 70V 300W
Input Connectors	24" x 12AWG Pigtail with Waterproof Wire Nuts
Warranty	Limited 5 Year Warranty

*All product specifications are subject to change. Please refer to ambisonicsystems.com for latest information.