

Practical - 9

AIM : Performing basics commands to interact with Kubernetes.

The objective of this lab is to familiarize yourself with basic commands to interact with a Kubernetes cluster. You will learn how to perform essential operations such as deploying pods, checking cluster status, and inspecting resources.

Step 1: Verify 'kubectl' Configuration

kubectl config current-context

```
PS E:\7sem\MLOPS\practicals\wordfiles\practical_9> kubectl config current-context
docker-desktop
```

Step 2: List Nodes

kubectl get nodes

```
PS E:\7sem\MLOPS\practicals\wordfiles\practical_9> kubectl get nodes
NAME                STATUS    ROLES    AGE   VERSION
docker-desktop      Ready    control-plane   14m   v1.28.2
```

Step 3: Create a Deployment

kubectl create deployment nginx-deployment--image=nginx

```
PS E:\7sem\MLOPS\practicals\wordfiles\practical_9> kubectl create deployment nginx-deployment --image=nginx
deployment.apps/nginx-deployment created
```

kubectl get deployments

```
PS E:\7sem\MLOPS\practicals\wordfiles\practical_9> kubectl get deployments
NAME                READY   UP-TO-DATE   AVAILABLE   AGE
nginx-deployment    1/1     1             1           21s
```

Step 4: List Pods

kubectl get pods

```
PS E:\7sem\MLOPS\practicals\wordfiles\practical_9> kubectl get pods
NAME                                READY   STATUS    RESTARTS   AGE
nginx-deployment-6d6565499c-cg6bc  1/1     Running   0           66s
```

Step 5: Access Pod Logs

kubectl logs nginx-deployment-6d6565499c-rxvct

```
PS E:\7sem\MLOPS\practicals\wordfiles\practical_9> kubectl logs nginx-deployment-6d6565499c-cg6bc
/docker-entrypoint.sh: /docker-entrypoint.d/ is not empty, will attempt to perform configuration
/docker-entrypoint.sh: Looking for shell scripts in /docker-entrypoint.d/
/docker-entrypoint.sh: Launching /docker-entrypoint.d/10-listen-on-ipv6-by-default.sh
10-listen-on-ipv6-by-default.sh: info: Getting the checksum of /etc/nginx/conf.d/default.conf
10-listen-on-ipv6-by-default.sh: info: Enabled listen on IPv6 in /etc/nginx/conf.d/default.conf
/docker-entrypoint.sh: Sourcing /docker-entrypoint.d/15-local-resolvers.envsh
/docker-entrypoint.sh: Launching /docker-entrypoint.d/20-envsubst-on-templates.sh
/docker-entrypoint.sh: Launching /docker-entrypoint.d/30-tune-worker-processes.sh
/docker-entrypoint.sh: Configuration complete; ready for start up
2023/12/02 06:57:21 [notice] 1#1: using the "epoll" event method
2023/12/02 06:57:21 [notice] 1#1: nginx/1.25.3
2023/12/02 06:57:21 [notice] 1#1: built by gcc 12.2.0 (Debian 12.2.0-14)
2023/12/02 06:57:21 [notice] 1#1: OS: Linux 5.10.102.1-microsoft-standard-WSL2
2023/12/02 06:57:21 [notice] 1#1: getrlimit(RLIMIT_NOFILE): 1048576:1048576
2023/12/02 06:57:21 [notice] 1#1: start worker processes
2023/12/02 06:57:21 [notice] 1#1: start worker process 29
2023/12/02 06:57:21 [notice] 1#1: start worker process 30
2023/12/02 06:57:21 [notice] 1#1: start worker process 31
2023/12/02 06:57:21 [notice] 1#1: start worker process 32
2023/12/02 06:57:21 [notice] 1#1: start worker process 33
2023/12/02 06:57:21 [notice] 1#1: start worker process 34
2023/12/02 06:57:21 [notice] 1#1: start worker process 35
2023/12/02 06:57:21 [notice] 1#1: start worker process 36
```

Step 6: Expose Deployment as a Service

```
kubectl expose deployment nginx-deployment --port=80 --type=NodePort --
name=nginx-service
```

```
kubectl expose deployment nginx-deployment --port=80 --type=NodePort
```

```
PS E:\7sem\MLOPS\practicals\wordfiles\practical_9> kubectl expose deployment nginx-deployment --port=80 --type=NodePort
service/nginx-deployment exposed
```

Step 7: List Services

```
kubectl get services
```

```
PS E:\7sem\MLOPS\practicals\wordfiles\practical_9> kubectl get services
```

NAME	TYPE	CLUSTER-IP	EXTERNAL-IP	PORT(S)	AGE
kubernetes	ClusterIP	10.96.0.1	<none>	443/TCP	100m
nginx-deployment	NodePort	10.96.22.226	<none>	80:30584/TCP	22s

Step 8: Access the NGINX Service

```
kubectl describe service nginx-deployment
```

```
PS E:\7sem\MLOPS\practicals\wordfiles\practical_9> kubectl describe service nginx-deployment
```

```
Name: nginx-deployment
Namespace: default
Labels: app=nginx-deployment
Annotations: <none>
Selector: app=nginx-deployment
Type: NodePort
IP Family Policy: SingleStack
IP Families: IPv4
IP: 10.96.22.226
IPs: 10.96.22.226
LoadBalancer Ingress: localhost
Port: <unset> 80/TCP
TargetPort: 80/TCP
NodePort: <unset> 30584/TCP
Endpoints: 10.1.0.6:80
Session Affinity: None
External Traffic Policy: Cluster
Events: <none>
```

Step 9: Delete Resources

```
kubectl delete deployment nginx-deployment
```

```
PS E:\7sem\MLOPS\practicals\wordfiles\practical_9> kubectl delete deployment nginx-deployment
deployment.apps "nginx-deployment" deleted
```

```
kubectl delete service nginx-deployment
```

```
PS E:\7sem\MLOPS\practicals\wordfiles\practical_9> kubectl delete service nginx-deployment
service "nginx-deployment" deleted
```

Step 10: Scale Deployment

```
kubectl scale deployment nginx-deployment --replicas=3
```

```
PS C:\Users\Wakul\Downloads\MLOPS\Practicals\Practical_9> kubectl scale deployment nginx-deployment --replicas=3
deployment.apps/nginx-deployment scaled
```

```
kubectl get pods
```

```
PS E:\7sem\MLOPS\practicals\wordfiles\practical_9> kubectl get pods
```

```
No resources found in default namespace.
```

Step 11: Update Deployment

kubectl set image deployment/nginx-deployment nginx=nginx:1.21

```
PS E:\7sem\MLOPS\practicals\wordfiles\practical_9> kubectl set image deployment/nginx-deployment nginx=nginx:1.21
Error from server (NotFound): deployments.apps "nginx-deployment" not found
```

kubectl rollout status deployment/nginx-deployment

```
PS C:\Users\Nakul\Downloads\MLOPS\Practicals\Practical_9> kubectl rollout status deployment/nginx-deployment
Waiting for deployment "nginx-deployment" rollout to finish: 1 out of 3 new replicas have been updated...
Waiting for deployment "nginx-deployment" rollout to finish: 1 out of 3 new replicas have been updated...
Waiting for deployment "nginx-deployment" rollout to finish: 1 out of 3 new replicas have been updated...
Waiting for deployment "nginx-deployment" rollout to finish: 2 out of 3 new replicas have been updated...
Waiting for deployment "nginx-deployment" rollout to finish: 2 out of 3 new replicas have been updated...
Waiting for deployment "nginx-deployment" rollout to finish: 2 out of 3 new replicas have been updated...
Waiting for deployment "nginx-deployment" rollout to finish: 1 old replicas are pending termination...
Waiting for deployment "nginx-deployment" rollout to finish: 1 old replicas are pending termination...
deployment "nginx-deployment" successfully rolled out
```

Step 12: Rollback Deployment

kubectl rollout undo deployment/nginx-deployment

```
PS E:\7sem\MLOPS\practicals\wordfiles\practical_9> kubectl rollout undo deployment/nginx-deployment
Error from server (NotFound): deployments.apps "nginx-deployment" not found
```

In this lab, we've learned basic Kubernetes commands to interact with a Kubernetes cluster. We've performed operations like creating deployments, services, scaling, updating, and rolling back deployments. These fundamental commands are essential for managing and working with Kubernetes resources in a real-world cluster.