



Milestone-1 Cheatsheet

◆ VS Code & What is HTML

- **HTML** stands for *HyperText Markup Language*.
- Used to **structure content** on the web (text, links, images, etc).
- **VS Code**: Popular code editor. Use **!** + **Tab** for HTML boilerplate.

◆ HTML Text — Paragraphs & Text Formatting

Tag	Description
<code><p></code>	Paragraph
<code></code>	Bold (no importance)
<code><i></code>	Italic (no emphasis)
<code></code>	Important and bold
<code></code>	Emphasized and italic



Example:

`<p>This is <strong>important</strong> and <em>emphasized</em>.</p>`

◆ Headings, `<small>`, Block vs Inline

Tag	Use
<code><h1></code> to <code><h6></code>	Headings (h1 is largest)
<code><small></code>	Smaller font text
<code><div></code>	Block-level container

← Milestone-1 Cheatsheet

BLOCK vs inline.

- **Block:** Starts on a new line, takes full width (`<div>`, `<p>`, `<h1>`)
- **Inline:** Flows within text (`<span>`, `<b>`, `<i>`)

◆ Lists, `<br>`, `<button>`

Tag	Description
<code></code>	Ordered list (numbered)
<code></code>	Unordered list (bulleted)
<code></code>	List item
<code>
</code>	Line break
<code><button></code>	Clickable button

Example:

```
<ul>
  <li>Item 1</li>
  <li>Item 2<br>Line break here</li>
</ul>
<button>Click Me</button>
```

◆ Links with `<a>`

Attribute	Description
<code>href</code>	Destination URL
<code>target="_blank"</code>	Opens in new tab

Example:

```
<a href="https://example.com" target="_blank">Visit Example</a>
```



Milestone-1 Cheatsheet

Attribute	Description
<code>src</code>	Image source (URL or path)
<code>alt</code>	Description if image doesn't load

Examples:

```


```

◆ Forms & Inputs

Tag/Attribute	Description
<code><form></code>	Form container
<code><input type="text"></code>	Text input
<code><input type="password"></code>	Password field
<code><select><option></code>	Dropdown menu
<code><button type="submit"></code>	Submit form

Example (Login Form):

```
<form>
  <input type="text" placeholder="Username">
  <input type="password" placeholder="Password">
  <button type="submit">Login</button>
</form>
```

◆ Basic HTML Structure

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="UTF-8">
    <title>Page Title</title>
  </head>
  <body>
    <!-- Your visible content here -->
  </body>
</html>
```



Milestone-1 Cheatsheet

- `<html>` = Root of HTML page.
- `<head>` = Metadata, title, external links.
- `<meta>` = Charset and other info.
- `<title>` = Title on browser tab.
- `<body>` = Page content (text, images, etc).



Learn and Explore CSS

◆ Introduction to CSS & Types

CSS (Cascading Style Sheets) is used to **style** HTML elements.

Types of CSS:

Type	How to Use
Inline	<code><h1 style="color: red;">Hello</h1></code>
Internal	Inside <code><style></code> in <code><head></code> of HTML
External	Link <code>.css</code> file using <code><link rel="stylesheet" href="style.css"></code>

◆ CSS Text Styling & Units

Property	Example
<code>color</code>	<code>color: blue;</code>
<code>font-size</code>	<code>font-size: 16px;</code>
<code>text-align</code>	<code>text-align: center;</code>
<code>font-weight</code>	<code>font-weight: bold;</code>

← Milestone-1 Cheatsheet

- **px** = Fixed pixels
- **em** = Relative to parent
- **%** = Percentage of parent
- **rem** = Root em (relative to root font-size)

◆ Basic Selectors

Selector	Example	Selects
Type	<code>h1 {}</code>	All <code><h1></code> elements
Class	<code>.box {}</code>	All elements with <code>class="box"</code>
ID	<code>#header {}</code>	Element with <code>id="header"</code>
Universal	<code>* {}</code>	All elements
Grouping	<code>h1, p {}</code>	All <code><h1></code> and <code><p></code> elements
Attribute	<code>input[type="text"] {}</code>	Text input fields

📄 Class vs ID:

- **Class**: reusable across elements (`.`)
- **ID**: unique per page (`#`)

◆ Mixed Selectors

Selector	Description
<code>.btn.primary</code>	Element with both <code>btn</code> and <code>primary</code> class
<code>div span</code>	All <code></code> inside a <code><div></code>
<code>a[href^="https"]</code>	Attribute selector (starts with)
<code>p > span</code>	Direct child <code>span</code> in <code>p</code>



Milestone-1 Cheatsheet

Property	Description
<code>margin</code>	Space outside the element
<code>padding</code>	Space inside the element
<code>border</code>	Line around element
<code>border-radius</code>	Rounded corners

**Margin Shorthand:**

```
margin: 10px 20px 30px 40px; /* top right bottom left */
```

◆ CSS Box Model

The **Box Model** = `margin` → `border` → `padding` → `content`

Part	Use
<code>padding</code>	Inside space
<code>border</code>	Outer line
<code>margin</code>	Space outside
<code>height/width</code>	Size of content box

**Example:**

```
.box {
  padding: 20px;
  border: 1px solid #000;
  margin: 10px;
  width: 200px;
}
```

◆ CSS Display & Visibility

Value	Description
<code>block</code>	Full width, new line
<code>inline</code>	Inside line, no width/height



Milestone-1 Cheatsheet

<code>visibility: hidden</code>	Hides but keeps the space
<code>box-shadow</code>	Adds shadow around box

 Example:

```
box-shadow: 0 4px 6px rgba(0, 0, 0, 0.2);
```

◆ CSS Backgrounds

Property	Example
<code>background-color</code>	<code>background-color: yellow;</code>
<code>background-image</code>	<code>background-image: url("bg.jpg");</code>
<code>background-repeat</code>	<code>no-repeat, repeat-x, repeat-y</code>
<code>background-size</code>	<code>cover, contain, 100% 100%</code>
<code>background-position</code>	<code>center, top right, 0 0</code>

 Example:

```
body {
  background-image: url("img/bg.jpg");
  background-size: cover;
  background-position: center;
}
```



Git, Source Control, GitHub, and Hosting

◆ What is Version Control?

- **Version Control System (VCS)** = Tracks changes in code over time.
- **Git** = Local version control system.
- **GitHub** = Cloud hosting for Git repositories.



Milestone-1 Cheatsheet

versions

GitHub Platform to store Git repositories online

◆ Create GitHub Repository

1. Go to <https://github.com>
2. Click **"New Repository"**
3. Name the repo → (e.g., **my-portfolio**)
4. Click **Create repository**

→ Copy repo link (HTTPS or SSH)

◆ Basic Git Commands

Command	Description
<code>git init</code>	Initialize local Git repo
<code>git status</code>	Show current state
<code>git add .</code>	Stage all changes
<code>git add filename.ext</code>	Stage specific file
<code>git commit -m "message"</code>	Commit with a message

Example:

```
git init
git add .
git commit -m "Initial commit"
```

◆ GitHub Account Setup

```
git config --global user.name "Your Name"
git config --global user.email "your@email.com"
```




Milestone-1 Cheatsheet

git --version

◆ Send Code to GitHub

1. Link local repo to remote:

```
git remote add origin https://github.com/username/repo.git
```

2. Push code:

```
git push -u origin main
```



For existing GitHub repos:

```
git clone https://github.com/username/repo.git
```

◆ Common Issues for Beginners

Issue	Solution
Wrong branch name	Rename to main or push as new branch
Permission denied	Use HTTPS or SSH keys properly
Not staged	Run git add . before commit
Commit not pushed	Use git push



Check remote:

```
git remote -v
```

◆ Git Workflow Summary



Basic Workflow:

Step 1: Initialize

```
git init
```

Step 2: Track changes

```
git add .
```



Milestone-1 Cheatsheet

```
# Step 4: Connect to GitHub  
git remote add origin <repo link>
```

```
# Step 5: Push to GitHub  
git push -u origin main
```



More About HTML & CSS: Media, Layouts, Forms, and Flex Design

◆ HTML5 vs HTML & Embedding Media

✓ HTML5 Improvements:

- Semantic tags (**header**, **footer**, etc.)
- Supports audio/video tags
- Cleaner syntax, no need for type in script/link



Audio Tag:

```
<audio controls>  
  <source src="audio.mp3" type="audio/mpeg">  
</audio>
```



Video Tag:

```
<video width="320" controls>  
  <source src="video.mp4" type="video/mp4">  
</video>
```



YouTube Embed:

```
<iframe width="560" height="315"  
src="https://www.youtube.com/embed/video_id"  
allowfullscreen></iframe>
```



Milestone-1 Cheatsheet

Tag	Purpose
<code><nav></code>	Navigation menus
<code><main></code>	Main content
<code><header></code>	Page or section header
<code><footer></code>	Page footer
<code><section></code>	Group content by topic
<code><article></code>	Independent content block
<code><time></code>	Represent date/time



Examp



Explain this



Summarize



```

<article>
  <header><h2>Blog Title</h2></header>
  <p>Post content...</p>
  <footer><time>2025-05-27</time></footer>
</article>

```

◆ HTML Forms (Advanced Elements)

Element	Use
<code><label></code>	Label for input
<code><fieldset></code>	Groups related form elements
<code><legend></code>	Title for fieldset
<code><textarea></code>	Multi-line input
<code><input type="radio"></code>	Single selection options
<code><input type="checkbox"></code>	Multiple options
<code><input type="reset"></code>	Clears all fields
<code><input type="submit"></code>	Submit form



Example:

```

<form>
  <fieldset>
    <legend>Survey</legend>
    <label>Name: <input type="text" name="name"></label><br>

```



Milestone-1 Cheatsheet

```
<input type="submit">
</fieldset>
</form>
```

◆ HTML Tables

Tag	Description
<code><table></code>	Start table
<code><tr></code>	Table row
<code><td></code>	Table cell
<code><th></code>	Table heading
<code><caption></code>	Title of table
<code><thead></code>	Header group
<code><tbody></code>	Body group
<code><tfoot></code>	Footer group



Example:

```
<table>
  <caption>Student Marks</caption>
  <thead><tr><th>Name</th><th>Score</th></tr></thead>
  <tbody><tr><td>Ali</td><td>95</td></tr></tbody>
  <tfoot><tr><td>Total</td><td>100</td></tr></tfoot>
</table>
```

◆ CSS Flex Layout Overview

Flexbox = Powerful layout system for 1D alignment

Property	Value Example
<code>display</code>	<code>flex</code>
<code>flex-direction</code>	<code>row, column</code>
<code>justify-content</code>	<code>center, space-between</code>
<code>align-items</code>	<code>center, stretch</code>

← Milestone-1 Cheatsheet

Example.

```
.container {
  display: flex;
  justify-content: space-between;
  align-items: center;
}
```

◆ Box Model Recap + **auto**

Box model = content + padding + border + margin

🗨 **margin: auto;** → centers block-level elements

```
.container {
  width: 500px;
  margin: 0 auto; /* center horizontally */
}
```

◆ Navigation & Internal Linking

```
<nav>
  <a href="index.html">Home</a>
  <a href="about.html">About</a>
</nav>
```

🔗 Internal Navigation (Same Page):

```
<a href="#section1">Go to Section 1</a>
<section id="section1">...</section>
```

◆ Hero Section with Flexbox

```
<section class="hero">
  <div class="hero-text">
    <h1>Welcome</h1>
    <p>Your site starts here.</p>
  </div>
  
</section>
```

```
.hero {
```



Milestone-1 Cheatsheet

```
background: #f0f0f0;  
padding: 50px;  
}
```

Pseudo Classes

Pseudo-classes select elements based on state, position, or interaction.

◆ :hover

- Trigger styles when the mouse is over the element.

```
button:hover {  
  
    background-color: blue;  
  
    color: white;  
  
}
```

◆ :focus

- Applies when an input element is focused (clicked/selected).

```
input:focus {  
  
    border: 2px solid green;  
  
}
```

◆ :visited

- Styles links **after** they've been clicked.



Milestone-1 Cheatsheet

```
color: purple;

}
```



Advanced Pseudo-classes & Pseudo-elements

◆ :first-child / :nth-child(n)

- Target elements based on order in the parent.

```
li:first-child {

    color: red;

}
```

```
li:nth-child(3) {

    font-weight: bold;

}
```

◆ :before and :after (Pseudo-elements)

- Add content before/after an element — useful for decorations, icons, labels.

← Milestone-1 Cheatsheet

```
content: "🔥";

}
```

```
h1::after {

  content: "💡";

}
```

💡 Note: You need **display: block/inline-block** when using pseudo-elements if you apply box styling.

🎯 CSS Positioning

Positioning controls how elements are laid out in relation to others or the browser window.

◆ static (default)

- Normal flow, no special positioning.

```
div {

  position: static;

}
```

◆ relative

- Position relative to itself (you can shift it with **top**, **left**, etc.)



Milestone-1 Cheatsheet

```
position: relative;

top: 10px; /* moves down */

left: 20px; /* moves right */

}
```

◆ absolute

- Positioned relative to **nearest positioned ancestor** (not **static**)

```
.parent {

    position: relative;

}

.child {

    position: absolute;

    top: 0;

    right: 0;

}
```

◆ fixed

- Positioned relative to **browser window** (never moves on scroll)



Milestone-1 Cheatsheet

```
position: fixed;

top: 0;

width: 100%;

}
```

◆ sticky

- Acts like relative **until** a certain scroll point, then sticks like fixed.

```
nav {

position: sticky;

top: 0;

}
```

◆ z-index (Layering elements)

- Controls the **stack order** of overlapping elements.
- Higher **z-index** means closer to the user.



Milestone-1 Cheatsheet

```
position: absolute;

z-index: 1;

}

.box2 {

position: absolute;

z-index: 10; /* Will be on top */

}
```



Bonus Tips:

Concept	Real Use Case Example
<code>:hover</code>	Button or link animation on mouseover
<code>:focus</code>	Highlight active input fields
<code>::before</code>	Add icons before text using <code>content</code>
<code>position: fixed</code>	Floating navbar, sticky buttons
<code>z-index</code>	Dropdowns, modals over other content



Milestone-1 Cheatsheet
