By: Tirth Shah Fullstack Developer

## CRUD Operations using Mongoose and MongoDB

So, in this section, you learned that:

- MongoDB is an open-source document database. It stores data in flexible, JSON-like documents.
- In relational databases we have tables and rows, in MongoDB we have
   collections and documents. A document can contain sub-documents.
- We don't have relationships between documents.
- To connect to MongoDB:

// Connecting to MongoDB

```
const mongoose = require('mongoose');
mongoose.connect('mongodb://localhost/playground')
  .then(() => console.log('Connected...'))
```

```
.catch(err => console.error('Connection failed...'));
```

- To store objects in MongoDB, we need to define a Mongoose **schema** first.

The schema defines the shape of documents in MongoDB.

```
// Defining a schema
```

```
const courseSchema = new mongoose.Schema({
    name: String,
    price: Number
});
```

By: Tirth Shah Fullstack Developer

- We can use a SchemaType object to provide additional details:

```
// Using a SchemaType object
const courseSchema = new mongoose.Schema({
   isPublished: { type: Boolean, default: false }
});
```

- Supported types are: String, Number, Date, Buffer (for storing binary data), Boolean and ObjectID.
- Once we have a schema, we need to compile it into a model. A model is like a class. It's a blueprint for creating objects:

```
// Creating a model
const Course = mongoose.model('Course', courseSchema);
```

## **CRUD Operations**

```
// Saving a document
let course = new Course({ name: '...' });
course = await course.save();

// Querying documents
const courses = await Course
   .find({ author: 'Mosh', isPublished: true })
   .skip(10)
   .limit(10)
   .sort({ name: 1, price: -1 })
   .select({ name: 1, price: 1 });
```

By: Tirth Shah Fullstack Developer

```
// Updating a document (query first)
const course = await Course.findByld(id);
if (!course) return;
course.set({ name: '...' });
course.save();
// Updating a document (update first)
const result = await Course.update({ _id: id }, {
   $set: { name: '...' }
});
// Updating a document (update first) and return it
const result = await Course.findByldAndUpdate({ _id: id }, {
   $set: { name: '...' }
}, { new: true });
// Removing a document
const result = await Course.deleteOne({ _id: id }); const
result = await Course.deleteMany({ _id: id }); const
course = await Course.findByldAndRemove(id);
```