State of AI Data Labs and Human Feedback

PRELAUNCH | research-2026-11-10.prelaunch.1 | Updated 2026-11-10

Preparation snapshot; not a published research edition. No DOI has been registered for this snapshot.

Coverage and publication status

The comprehensive weekly series is in preparation. Historical examples and the research method are available; candidate discoveries do not count as reviewed research. The complete readiness record accompanies this PDF as readiness.json.

Reviewed research	Current	Launch minimum
Existing organization inclusion audits	39	39
Qualifying suppliers	65	60
Full-source paper reviews	152	150
Dataset families	63	60
Benchmark families	21	20

1. Executive assessment

Method: This is the expanded prelaunch State of AI Data Labs and Human Feedback, prepared by ScienceToStartup and published under the identity of Musa Ozdem. It is an evidence-linked analyst synthesis for buyers, research teams and contributors. It is not a published weekly edition. The report ledger contains no published predecessor, DOI or completed archive. The separately versioned evidence graph leaves canonical dataset 2.5.0 and its historical dates unchanged. The purpose is to make decisions inspectable: what a source actually documents, what the analyst concludes from it, what remains unknown and what evidence would change the conclusion.

Method: The pinned synthesis input contains 1,713 approved assertions, 65 qualifying suppliers, 152 distinct reviewed paper works, 63 dataset families and 21 benchmark families, computed with coverage method 1.3.0. All 39 legacy organizations have completed bounded inclusion audits; 38 have conclusive commercial dispositions, while BenchFlow remains commercially pending. The graph also preserves 26 quarantined candidate assertions and 39 historical assertions. These counts describe selected-source coverage. The eligible inventory remains a lower bound, the core is unfrozen, and the formal reference and screening launch audits are unfinished. Individual count floors do not establish completeness or publication readiness.

Analysis: The market is more intelligible when the comparison begins with the unit being bought. A participant platform, a managed annotation program, a licensed dataset, an evaluation service and an executable RL environment leave different responsibilities with the buyer. Prolific distinguishes participant access from managed collection; Snorkel describes refreshed non-exclusive products; Mercor describes expert task construction; Surge describes environments and verifiers. The analytical implication is to compare statements of work and accepted deliverables before comparing brand claims. This evidence supports a responsibility map within this sample, rather than a universal competitive ranking.

Sources: [474], [479], [489], [494]

Analysis: The word human conceals several different supervision arrangements. Human-written source material, human task design, independently collected judgments, correction of model drafts and human review of a model-selected subset are not interchangeable inputs. HelpSteer3, UltraFeedback, FineWeb-Edu and the described DeepSeek-R1 cold-start process demonstrate distinct combinations. A buyer should ask where a person intervenes and what that person can observe. Nothing in this sample establishes that one provenance class always produces better models; the defensible comparison is whether the supervision target and validation design fit the intended task.

Sources: [279], [433], [467], [468]

Analysis: Quality requires denominators and a theory of disagreement. HelpSteer3’s retained consensus, HelpSteer2’s closest-rating aggregation, InstructGPT’s ranked sets and DICES’ repeated safety judgments arise from different observation processes. A pair count can expand from rankings without adding independent people; a post-filter agreement result can improve while excluding difficult items; a majority can erase a meaningful minority. Procurement should preserve raw labels, exclusions and adjudication reasons. These are methodological judgments based on the documented workflows, not measured differences in supplier performance.

Sources: [106], [429], [464], [468]

Analysis: Executable outcomes improve observability but do not eliminate judgment. SWE-bench tests, OSWorld state checks, τ-bench database rewards and PaperBench rubric leaves expose concrete success conditions. Their papers also identify incomplete test coverage, damaging side effects, missed policy violations or judge limitations. A reliable acceptance plan therefore needs both outcome checks and a separate review of constraints, side effects and ambiguous failures. The evidence does not justify treating a passed verifier as a certification of deployment readiness or general professional competence.

Sources: [213], [236], [350], [466]

Analysis: Public financial and workforce numbers answer different questions. Appen's annual group revenue, Proximal's annualized pace, Scale's cumulative contributor payout and Prolific's active-participant disclosure do not form a common revenue, capacity or labor denominator. Labelbox financing combines equity and a credit facility. The report therefore offers a commercial evidence ledger and project-cost methodology rather than market-share estimates or a valuation league table. Missing disclosure remains unknown, and a large advertised pool does not establish current paid availability for a particular language, credential or task.

Sources: [44], [223], [470], [479], [483]

Analysis: Rights, privacy and security must follow the exact material and service boundary. Marketplace terms, a website privacy notice, a training-data license, a worker agreement and a security attestation can cover different subjects. Defined.ai separates marketplace datasets from new collection; AfterQuery excludes customer processor work from its website policy; Mercor directs work-platform users to a separate notice; MathVista retains underlying image and question rights while restricting training use. The analyst judgment is to obtain project-specific evidence for each boundary. Public documentation completeness is useful for diligence, but it is not itself a quality or compliance rating.

Sources: [31], [153], [187], [475]

Method: All nine executive finding identifiers from the previous unpublished synthesis are retained. The additional studies refine their evidence and limits: post-selection agreement differs from raw agreement; model-simulated feedback differs from live expert assistance; disclosure audits describe reporting; and observed costs depend on the counted work and time. These refinements do not create a published weekly comparison or rewrite a historical archive. Confidence remains attached to each scoped judgment and to the evidence that could change it.

Analysis: The added annotation studies strengthen a practical distinction between an improved retained dataset and an improved production process. HelpSteer2 raises agreement after selecting and filtering labels; the surgical-annotation study compares instruction conditions and subsequent QA; LabelAId measures a particular intervention against researcher-adjudicated labels. Those designs answer different questions. A buyer should require raw-input, excluded-item and final-acceptance denominators, plus independent error inspection, before interpreting a high agreement score or a QA stage as evidence of better delivered work.

Sources: [415], [417], [420]

Analytical judgment: delivery-unit-before-provider

In this reviewed sample, a useful supplier comparison begins with the delivery unit: participant access, licensed data, custom tasks or executable environments.

Buyer implication: Specify who owns task design, annotation, QA, rights clearance and acceptance before comparing proposals.

Limitations: First-party offering descriptions do not establish interchangeable services, capacity, realized quality or a market-wide supplier ranking.

Confidence: Moderate for this sample’s disclosed distinctions; low for prevalence outside it.

Reasoning: Prolific distinguishes participant access and managed collection; Snorkel describes refreshed non-exclusive products; Mercor describes custom task construction; Surge offers environments and verifiers. Their responsibilities differ even where capability labels overlap. The expanded corpus also distinguishes engineering teams, managed evaluation, hosted compute and contract-limited talent acquisition; the comparison remains task-specific.

What would change this assessment: Matched statements of work and independently checked deliveries could show that particular offerings meet the same requirement and permit narrower outcome comparisons.

Approved evidence IDs: candidate.supplier.prolific.platform-managed, candidate.supplier.snorkel_ai.data-series, candidate.supplier.mercor.task-construction, candidate.supplier.surge_ai.rl-environments, candidate.cohort4.g2i.contracting-scope-limit, candidate.cohort4.prime_intellect.professional-service-separation

Analytical judgment: human-and-model-provenance

Human content, human labels and human oversight are distinct provenance claims; the selected datasets contain materially different combinations.

Buyer implication: Require a stage-level provenance manifest and test the label target relevant to the intended task.

Limitations: The reviewed methods are source-reported and version-specific. No universal advantage of human or synthetic labels is established.

Confidence: High for the documented provenance distinctions; unestablished for comparative training outcomes.

Reasoning: HelpSteer3 describes independent human preference annotations, UltraFeedback describes GPT-4 labels and FineWeb-Edu describes model-scored educational filtering. Calling these one annotation category would erase the origin of the supervision signal. The expanded methods also include human correction of model responses and model-generated process signals, reinforcing stage-level provenance.

What would change this assessment: Independent task-matched validation with raw annotations and generation logs could support outcome comparisons or expose errors in the reported provenance.

Approved evidence IDs: candidate.paperfull.helpsteer3.independent-human-labels, next.claim.ultrafeedback.model_feedback, candidate.paperfull.fineweb.synthetic-educational-labels, cohort5.claim.deepseekv3.human-check, cohort8.claim.prime.online-prm, cohort9.claim.recodeh.simulated-feedback, cohort9.claim.recodeh.metric-scope, cohort9.claim.ultrafeedback.simultaneous-rubrics, cohort9.claim.ultrafeedback.human-agreement

Analytical judgment: agreement-needs-denominators

Released agreement and preference-pair totals cannot be interpreted without the independent-judgment and exclusion denominators.

Buyer implication: Request raw-to-retained counts, invalid-item rules, repeat labels, disagreement slices and corrected acceptance.

Limitations: The reviewed workflows differ in task and sampling. They cannot rank provider quality, and no common reliability measurement was executed.

Confidence: High for the methodological distinction; low for transferring a numerical agreement result between workflows.

Reasoning: HelpSteer3's retained consensus, HelpSteer2's post-filter closest-rating aggregation, InstructGPT's ranked sets and DICES' repeated judgments have different observation and selection denominators. The added HelpSteer2 paper makes the exclusions explicit; the inference study limits normalized scores to within-pair comparisons; Gilardi excludes trained-rater disagreement from the accuracy reference. These distinctions make raw counts, exclusions and adjudication necessary before comparison.

What would change this assessment: A common held-out task with independent raw judgments and the same exclusion rules could make reliability comparisons meaningful.

Approved evidence IDs: candidate.paperfull.helpsteer3.postfilter-consensus, next.claim.helpsteer2.qa, candidate.paperfull.instructgpt.human-ranking-sets, candidate.paperfull.instructgpt.single-contractor-comparisons, cohort3.claim.dices.expert-crowd-difference, cohort3.claim.disagreement.agreement-not-superiority, cohort9.claim.helpsteer2.agreement-selection, cohort9.claim.inherent.normalization-limit, cohort9.claim.gilardi.gold-denominator

Analytical judgment: artifact-role-is-narrow

Named artifact attribution is strongest when it preserves the exact contribution stage and release rather than extending a brand association across a family.

Buyer implication: Ask for source-supported roles for the specific delivered artifact; keep recruitment, annotation, validation and authorship separate.

Limitations: These examples do not reveal contract values, contribution shares, exhaustive supplier lists or causal provider performance.

Confidence: High for the explicit scoped roles in this sample; incomplete for the broader supplier graph.

Reasoning: HelpSteer3 names Scale and Translated for different subsets; the Prolific case establishes recruitment through a researcher-owned interface; U-MATH credits Toloka AI and

Gradarius with validation of professor-authored problems. These relationships support narrower claims than sole production.

What would change this assessment: Additional artifact-specific acknowledgments, contributor records or contracts could establish further stages or revise the scope.

Approved evidence IDs: candidate.supplier.scale_ai.helpsteer3-contribution, next.claim.helpsteer3.translated, candidate.supplier.prolific.cohere-recruitment, candidate.supplier.toloka.umath-validation

Analytical judgment: benchmark-protocol-before-score

Benchmark family names alone are insufficient for comparing scores or deciding deployment readiness.

Buyer implication: Freeze task version, candidate responses, aggregation and execution environment, then inspect errors on the buyer's actual task.

Limitations: No benchmark was executed for this report. The reviewed sources do not establish a universal deployment-quality ranking.

Confidence: High for protocol differences and stated limitations; unestablished for any new system's performance.

Reasoning: RewardBench versions change scoring structure; TruthfulQA changes answer protocol and separates generation metrics; SWE-bench warns that passing tests does not ensure complete, efficient or readable solutions. The measures answer different questions. OSWorld and τ-bench additionally identify outcome-checking gaps for damaging side effects and policy violations.

What would change this assessment: Reproducible matched-protocol results and independently checked target-task outcomes could support a narrower comparative claim.

Approved evidence IDs: next.claim.rewardbench.v1.scoring, next.claim.rewardbench.v2.scoring, next.claim.truthfulqa.metrics, next.claim.truthfulqa.binary_revision, candidate.paperfull.swebench.regression-test-scoring, cohort4.claim.osworld.side-effect-gap, cohort4.claim.taubench.reward-limit

Analytical judgment: commercial-denominators-stay-separate

The selected commercial disclosures cannot be combined into supplier market shares, production-capacity rankings or a common unit-cost comparison.

Buyer implication: Retain period, currency, organizational scope, active-window definition and acceptance basis; obtain a project-specific quote and availability check.

Limitations: Coverage is selected and incomplete. Missing disclosure is unknown, not zero; the observed figures are not matched measures.

Confidence: High for the incompatibility of these disclosed denominators; no confidence claim is made about market-wide shares.

Reasoning: Appen reports full-year consolidated and geographic-segment revenue, Scale reports cumulative contributor payouts with unspecified period and dollar currency, and Prolific distinguishes active participants from a waitlist without defining the active window. None supplies a matched current paid-work or human-data revenue denominator across suppliers. Proximal's annualized disclosure and Labelbox's mixed financing add further incompatible commercial measures.

What would change this assessment: Comparable segment accounts, audited activity windows and accepted-unit cost records across the same scope could permit limited financial or operational comparisons.

Approved evidence IDs: candidate.supplier.appen.revenue-fy2025, candidate.supplier.appen.segments-fy2025, candidate.supplier.scale_ai.cumulative-payout, candidate.supplier.prolific.active-pool, repair.binding.v1.candidate.cohort4.proximal.annualized-revenue-disclosure, candidate.cohort2.labelbox.financing, cohort9.claim.lmcrowd.cost-boundary, cohort9.claim.earnings.work-unit-wages, cohort9.claim.earnings.causality-limit

Analytical judgment: multilingual-intersections-before-language-counts

Multilingual suitability depends on language-domain-task intersections and native validity, rather than a language count alone.

Buyer implication: Specify every required intersection, preserve translation/review provenance and calibrate the judge in the target locale.

Limitations: These selected studies do not establish universal translation inferiority, global language coverage or a provider ranking.

Confidence: Moderate for these documented methodological distinctions; unmeasured for current supplier performance.

Reasoning: HelpSteer3 records missing intersections, M-IFEval changes language-inappropriate constraints, BenchMAX post-edits translations and MENLO measures localized dimensions.

What would change this assessment: Matched native-authored, translated and post-edited task studies with independent target-locale evaluation could narrow or revise the judgment.

Approved evidence IDs: candidate.paperfull.helpsteer3.missing-domain-intersections, cohort7.claim.mifeval.japanese-filter, cohort7.claim.benchmax.pipeline, cohort7.claim.menlo.dimensions, cohort9.claim.aya.dataset-composition, cohort9.claim.aya.quality-limit, cohort9.claim.helpsteer.language-cultural-limit

Analytical judgment: rights-follow-exact-material-and-service

Rights, privacy and security diligence must follow exact components, services and uses rather than a top-level policy or license label.

Buyer implication: Obtain component rights and the actual project processing/security scope before accepting data or environments.

Limitations: This is public-source evidence and methodological judgment, not legal advice, rights clearance or an assurance audit.

Confidence: High for the documented scope differences; unestablished for legal compliance of particular deployments.

Reasoning: AlpacaEval separates code/data terms, RewardBench retains component obligations, MathVista restricts training use and provider notices distinguish website from customer processing.

What would change this assessment: Project-specific agreements, rights-holder permissions and independent scoped assurance evidence could resolve particular unknowns.

Approved evidence IDs: cohort2.dataset.claim.alpacaeval.component-license, next.claim.rewardbench.terms, cohort4.dataset.claim.mathvista.terms, candidate.cohort4.afterquery.processor-privacy-boundary, cohort9.claim.wildchat.consent-gate, cohort9.claim.wildchat.anonymization

Analytical judgment: verifiable-outcomes-need-side-effect-review

Executable success checks should be paired with independent review of constraints, side effects and verifier error.

Buyer implication: Test valid alternatives, plausible shortcuts, harmful extra actions and infrastructure failures in the acceptance pilot.

Limitations: No environment or provider was independently executed for this report, and no failure-prevalence estimate is claimed.

Confidence: High for the stated benchmark limitations; unmeasured for any new buyer deployment.

Reasoning: SWE-bench passing tests do not guarantee a complete solution; OSWorld identifies damaging-side-effect gaps; τ-bench notes missed policy violations; MBPP documents assertion gaming.

What would change this assessment: A matched evaluation showing that the project verifier reliably detects the buyer’s critical constraints could narrow the need for additional manual review in that scope.

Approved evidence IDs: candidate.paperfull.swebench.regression-test-scoring, cohort4.claim.osworld.side-effect-gap, cohort4.claim.taubench.reward-limit, cohort4.claim.mbpp.test-overfit

2. Weekly developments and edition discipline

Method: Edition status as of 10 November 2026: prelaunch; archive not_published; DOI null; editions empty. Daily preparation targets 16:00 America/Los_Angeles. The planned weekly release check is Monday 09:00 after a Friday 17:00 captured-source cutoff. The next planned cutoff is Friday 13 November 2026 at 17:00 Pacific, represented as 2026-11-13T17:00:00-08:00, and the next planned weekly edition is Monday 16 November. A graph prepared on 10 November cannot demonstrate that this future cutoff has passed or that all later inputs are within it. These dates are a schedule, not a publication receipt.

Method: The weekly change unit is a versioned source-supported claim, not an increase in word count or an older paper newly encountered by the research team. Source publication date, described event date, capture timestamp, assertion as-of date, review timestamp and edition publication date remain separate. A capture performed on 9 November in Los Angeles may be dated 10 November UTC. It does not retroactively satisfy a 6 November cutoff. Later independent review can approve the captured content without changing the time at which the document was captured.

Method: This preparation extends the prior unpublished 1,446-assertion, 132-work synthesis to a pinned input of 1,713 approved assertions and 152 reviewed works. Twenty newly reviewed works add annotation, disagreement, multilingual, worker-time, documentation and interactive-feedback evidence. Twenty-six citation repairs replace quarantined source bindings with fresh approved IDs while preserving scientific values and qualifications. The increase describes research inputs and repairs, not events that all occurred this week, market growth, production capacity or an accuracy score. The planned future cutoff remains separate from this preparation date.

Evidence: The commercial event dates illustrate why review time must not become news time. Labelbox’s financing announcement is dated 14 October 2026; Proximal’s annualized-revenue announcement is dated 29 September 2026; Mercor’s 25 June investigation account describes a March 2026 LiteLLM incident. Their inclusion in this newly expanded preparation does not make them November events. The financing, annualization and incident qualifications remain part of the respective evidence records.

Sources: [44], [223], [476]

Method: The earlier initial calculation counted FineWeb-Edu as a separate family. Current identity review treats it as a FineWeb subset release, so current coverage counts one FineWeb family. The earlier frozen files retain their original exact bytes. The correction is an explicit change in identity accounting, not a disappearance of the educational subset or a retraction of its documented model-scoring workflow. Future change logs should report family identity corrections separately from newly added source observations.

Research gap: No prior published edition exists in this ledger, so a week-over-week market trend is not estimable from these records. The first publishable comparison will need an actual frozen predecessor, a current source cutoff, a claim-level change list and disclosure of whether each change is a new event, a newly captured older source, a corrected scope or a reclassified identity. Scheduled dates, package preparation and website visibility should be reported separately from archive confirmation.

Method: Correction accounting distinguishes claim meaning from the evidence binding used to establish it. The 26 old IDs remain candidate records with earlier positive reviews and later negative/context-reconciliation history. Their new IDs carry fresh author, source-verifier and adversarial source-content receipts. This report uses only the approved replacements. Original source publication, capture and earlier review dates are preserved; the repair does not change the frozen 250-case diagnostic sample, its truth labels, predictions or results, and does not complete either launch audit.

3. Market definition, structure and provider categories

Method: Operational market definition: an AI data lab or human-feedback supplier is included here when an approved public source documents an offering that creates, collects, annotates, curates, validates or evaluates data or executable tasks used in AI development. The category includes services, participant access, software-assisted workflows and environment products. Inclusion means that the scoped offering meets this research definition. It does not assert a legal industry classification, a minimum revenue level, independent ownership, a named downstream contribution or an exclusive business focus.

Analysis: Participant access is one delivery category. Prolific offers selected participants and distinguishes platform access from managed collection; Terac offers verified-expert access with an expert-payout-plus-platform-fee model. Handshake’s contractor agreement describes a Human Data Services program whose onboarding does not guarantee a project. These are useful starting points when the buyer can own task design and acceptance, but the degree of project management and supplier responsibility must be read in the contract. Access to a qualified population is not the same deliverable as an accepted dataset.

Sources: [201], [313], [477], [479]

Analysis: Managed data production combines personnel, instructions, tools and review. Appen describes expert alignment and evaluation; Sama describes an in-house workforce and human-verified data services; iMerit describes expert review and client audits; DataForce describes expert/native-speaker matching and adjudication. These examples are grouped by disclosed responsibility, not presumed equivalence. A managed-service comparison should identify who writes the rubric, who employs or contracts with contributors, who owns correction work and who can reject a disputed final unit.

Sources: [26], [34], [54], [55], [469]

Analysis: Licensed data products are a different procurement path. Snorkel describes non-exclusive dataset and environment products refreshed quarterly; Mercor, Surge, Datacurve and Invisible advertise prebuilt or ready-to-license collections. Defined.ai explicitly separates marketplace or third-party proprietary datasets from new collection and services. The relevant comparison is therefore version, license, overlap with existing training data, refresh entitlement and fitness on the buyer’s task. A catalog listing does not establish the right to redistribute every source component or the availability of exclusive data.

Sources: [31], [36], [196], [474], [489], [494]

Analysis: Environment builders deliver executable tasks, state and reward logic. Abundant describes turning customer workflows into Foundry environments; Refresh describes simulated coding and computer-use worlds; Bespoke describes company-scale simulations; HackerRank Bench offers resettable repository environments and hidden verifiers; Prime Intellect couples environments with managed training and compute. A buyer should separate environment authorship from hosted execution and post-training services. Portability, reset determinism, observability, judge calibration and maintenance obligations can matter as much as the number of tasks in a package.

Sources: [183], [220], [233], [275], [289]

Analysis: Evaluation and safety services may use expert data without selling a general annotation workforce. Giskard offers dynamic evaluation data and adaptive attacks; Alinia describes policy judges and comparison with customer experts; Trajectory describes expert-discovered safety attacks and automated testing of known attacks. Their documented value propositions concern discovery, assessment and iteration. A procurement team should specify whether the output is a test dataset, a report, an integrated judge, a remediation cycle or a continuous service before comparing prices or treating these providers as substitutes for custom training-data production.

Sources: [271], [285], [286], [315]

Analysis: Engineering teams and talent programs can occupy a distinct contractual position. A.Team offers builders for environment and evaluation engineering. G2i advertises engineering data programs and dual-developer review, yet its inspected human-data terms limit the service to talent acquisition and disclaim responsibility for candidate work. Proximal’s MSA instead keeps responsibility for subcontracted services with Proximal. These documents demonstrate why a shared engineering capability label cannot establish who warrants the final artifact. The contract should identify the accountable supplier, the accepted output and the path for defects.

Sources: [197], [199], [226], [268]

Analysis: Annotation software is another distinct responsibility model. Dataloop documents human/AI feedback nodes; Datasaur combines automated NLP pre-labeling with human verification; Kili lets customer specialists author and judge post-training examples and introduces external partners; V7 Darwin supports multistage workflows and advertised specialist access. These products can support human-data production without establishing that the software company directly employs the annotators or warrants every add-on’s delivery. Compare platform controls, expert access and managed-service responsibility as separate line items.

Sources: [325], [328], [344], [363], [364]

Analysis: Modality and domain are independent comparison dimensions. Encord offers physical-AI, multimodal and LLM annotation with role matching; APTO lists image, video, LiDAR, text and audio; Shaip describes credentialed professionals for healthcare, legal, finance and code preference work. A modality claim does not establish specialist expertise, and a credential claim does not establish coverage in every language or format. Buyers should intersect the required domain, locale, tool environment and output type, rather than add separate broad claims into an unsupported statement of complete coverage.

Sources: [109], [132], [273]

Method: Provider categories are overlapping analyst groupings of documented offerings, not mutually exclusive market segments. A supplier can appear in several use-case comparisons without being counted several times. A brand, product, division or contractor platform is not automatically a separate corporate supplier. RWS/TrainAI, Welocalize/Welo Data, HackerRank/Bench and Alegion/SanctifAI retain the scoped identity disclosed in their records. Historical aliases remain searchable without inventing a new ownership transaction or a second supplier.

Analysis: Named delivery strengthens the ability to ask focused diligence questions, but evidence type still matters. DataForce's IBM case, SuperAnnotate's Databricks case, Aya Data's Cydar case and Keymakr's SeeChange case are provider-authored descriptions with different artifacts and dates. They are not matched outcome trials. A supplier without a named public case in this graph may have confidential deliveries; a supplier with one has not thereby demonstrated superior quality. Disclosure completeness and provider performance are distinct objects of study.

Sources: [24], [57], [95], [119]

Research gap: The sample cannot support a commercial quadrant, market size, share estimate, concentration index, price curve or fastest-growing-provider list. Comparable segment revenue, current buyer demand, accepted-unit volume, active paid contributor windows and task-matched outcomes are missing or inconsistent. The report instead makes a narrower, falsifiable judgment: supplier comparison should follow responsibility and deliverable structure. A later study could test that judgment using matched contracts, acceptance logs and common pilot tasks.

Analysis: A managed annotation offer and an annotation method are different comparison objects. CrowdAgent describes routing and hidden-gold aggregation; LMCrowd describes staged model-label purchasing. Neither establishes that a named supplier currently implements those workflows or achieves their results. For managed work, compare responsibility for guidelines, routing, escalation, independent acceptance and full cost. For a method implementation, compare the exact data, models, selection rules and held-out checks. A paper-to-practice connection can suggest questions without becoming an unsupported supplier-contribution edge.

Sources: [408], [419]

4. Technical landscape: from supervision to executable evaluation

Method: This chapter separates stages that are often collapsed into RLHF: source collection; task and rubric authoring; demonstrations for supervised fine-tuning; outcome ratings, preference pairs or ranked sets; reward or judge construction; policy optimization; executable environment design; evaluation; and documentation. The reviewed-work atlas below summarizes approved observations from exact inspected manifestations. A paper’s work identity counts once even when several versions exist. Bounded full_source review covers methods plus main results or worked examples and limitations; it does not claim all appendices, proofs, raw data or experiments were reproduced.

Analysis: Classical human-preference pipelines expose several independent design choices. The original trajectory-comparison study alternates interaction, human clip comparisons and reward fitting. The summarization study uses comparison-trained rewards and PPO with a KL penalty. InstructGPT ranks sets of responses and uses a separate unlabelled prompt pool for PPO. These are not merely different names for pairwise annotation: they differ in task construction, candidate sampling, comparison independence and the distribution exposed to optimization. A data purchase should preserve those distinctions in its manifest.

Sources: [32], [133], [464]

Analysis: Preference optimization changes the training interface, rather than erasing data requirements. DPO fits a direct objective without a separate reward-model/RL loop; IPO studies a direct squared-loss formulation under a narrower experimental setting; ORPO combines chosen-response likelihood and odds-ratio loss without a frozen reference; KTO accepts desirable/undesirable labels. KTO experiments often transform existing pairs, so support for a binary interface is not evidence that all reported data were independently collected as binary judgments. Method comparison must retain label origin, model scale, candidate distribution and evaluation protocol.

Sources: [40], [41], [49], [465]

Analysis: Selection methods consume a candidate budget that is absent from a final retained-pair count. RAFT retains a high-reward fraction; statistical rejection sampling generates 64 candidates and subsamples eight in its standard experiment; SimPO’s instruct setting selects highest/lowest PairRM scores from five candidates; SPPO also uses five responses per prompt in its experiment. Their results cannot be explained by final training-row counts alone. A reproducible data and compute comparison should count generated candidates, judge calls, retained examples, rejected items, training updates and evaluation calls separately.

Sources: [299], [304], [309], [311]

Analysis: Process supervision targets intermediate steps, but step granularity and validation still differ. Let's Verify Step by Step evaluates selection from a fixed generator and flags a large-scale comparison confound; Step-DPO contrasts next steps conditioned on earlier correct steps and warns that correct final answers can conceal bad intermediate reasoning; PRIME learns an online implicit process reward from outcome supervision. A buyer should distinguish human step labels from model-localized errors and from token rewards derived indirectly from final outcomes. None of these method labels alone proves faithful reasoning.

Sources: [51], [312], [398]

Analysis: Optimization papers also change normalization, sampling and infrastructure assumptions. DAPO filters all-correct or all-incorrect sampled groups and changes clipping and token aggregation; Dr. GRPO analyzes response-length and reward-standard-deviation biases; GSPO clips sequence ratios; VAPO adds value pretraining and length-adaptive advantages. These are specific recipes under their inspected experiments, not evidence of a universally best algorithm or a provider's operational advantage. A buyer of training services should ask which recipe, reward definition, sampling budget and failure controls are actually implemented.

Sources: [387], [390], [392], [405]

Analysis: Test-time adaptation needs a different evaluation contract. TTRL uses agreement with a sampled consensus as reward without target ground-truth labels; ReliableTTRL distinguishes population-majority error from finite-rollout variation; SelectTTRL fixes a selection rule without target answers but uses a separately labeled calibration set. Reporting only a final score hides adaptation data access and evaluation-budget differences. A fair comparison should state which test questions drive updates, which labels enter calibration, the total rollout budget, checkpoint-selection rule and whether every target question remains in the denominator.

Sources: [401], [402], [404]

Analysis: Synthetic and hybrid pipelines require stage-level lineage. Constitutional AI mixes human helpfulness with model harmlessness labels; ToolBench combines expert seed examples with ChatGPT instruction and trajectory generation; RLAIF-V uses model claim checking while its evaluation references include human corrections; Llama 3 collects new annotations and synthetic data across rounds. The practical requirement is a manifest identifying generator, prompt, seed material, selection model, correction roles and independent evaluation. A statement that humans were involved somewhere cannot establish that a particular training target is human-authored.

Sources: [23], [130], [237], [294]

Analysis: Executable evaluation spans different abstractions. HumanEval checks short Python functions; SWE-bench checks issue-resolution patches; WebArena combines semantic and state checks; OSWorld uses desktop state evaluators; τ-bench checks database outcomes under interaction policies. Agents can receive different observation modes, budgets and simulator affordances. A single leaderboard column cannot remove these differences. The comparison should first ask whether the measured task and environment resemble the buyer's deployment, then assess whether the scoring protocol detects the failures the buyer cares about.

Sources: [64], [204], [213], [236], [466]

Analysis: Research and professional-work benchmarks add substantial human design and review labor. RE-Bench records expert runs with tools; ScienceAgentBench uses subject-matter validation and separate execution verification; PaperBench aggregates binary rubric leaves and prohibits use of original authors' code; TheAgentCompany records task-creation effort but lacks a professional human comparison in that iteration. These benchmarks make particular research activities observable, but their human baselines, time budgets and allowed resources differ. They cannot establish a general percentage of jobs that an agent can perform.

Sources: [318], [350], [351], [353]

Analysis: Reward hacking and contamination should be studied as separate mechanisms. A learned reward can be overoptimized while human preference worsens; a program can pass supplied assertions by hard-coding tested inputs; a reasoning monitor can lose recall under direct optimization pressure; a public benchmark can be detected in training only under particular access and watermark assumptions. These examples motivate separate checks for objective misspecification, verifier gaming, monitor adaptation and training/test exposure. They do not establish the incidence of those failures in any provider's current production service.

Sources: [133], [207], [378], [403]

Analysis: Feedback-format comparison - ordinal ratings, rankings and binary signals preserve different information. HelpSteer2's attribute ratings can retain multiple dimensions; InstructGPT's ranked sets relate several responses under one prompt; Llama 2 adds preference strength; KTO can use one desirable/undesirable output. Converting all of them to binary pairs can discard attribute structure or strength and create correlated observations. The buyer should decide which information is required by the intended objective before paying for annotation. The reviewed studies do not establish one universally most efficient format, and the matched disagreement study specifically cautions against assuming paired preferences are inherently less ambiguous.

Sources: [41], [107], [293], [429], [464]

Analysis: Feedback-format comparison - rationale text and process labels answer different questions. The natural-language-feedback study uses author-written feedback to select refinements by embedding similarity; Innodata describes explanatory reasons for response scores; Step-DPO localizes the next erroneous step; DeepSeek-R1-Zero uses final accuracy and format rewards without a neural process reward. A rationale can be useful context without being a validated causal explanation or a correct intermediate proof. Procurement should distinguish the requested text artifact, its validation target and whether downstream training actually consumes it. These examples do not show that longer reasoning or more explanation is always better.

Sources: [116], [279], [290], [312]

Analysis: Distribution comparison - offline preferences and current-policy rollouts can differ even when the file schema is identical. SLiC-HF notes mismatch between off-policy human-feedback data and SFT decodes; WPO reweights preference losses using current-policy response weights; REBEL permits a fixed or current-policy response distribution but samples both responses from the current policy in its described experiments. These methods make the candidate-generation distribution a material part of the recipe. A licensed preference dataset should therefore identify generating models, sampling settings and collection period, and a training-service proposal should explain whether fresh responses or labels are required.

Sources: [300], [310], [317]

Analysis: Objective comparison - a scalar reward is a modeling choice, not a property guaranteed by human judgment. SPPO explicitly uses a two-player constant-sum preference game rather than requiring one transitive scalar ordering; WPO’s conceptual labeling construction assumes no conflicting pairs for a prompt; the instruction-tuning disagreement experiment observes task-dependent ambiguity. The analytical lesson is to state the aggregation assumptions and preserve counterexamples before fitting a reward. This does not prove that scalar models are inappropriate in every task; it identifies a condition to test when disagreements are central to the buyer’s use case.

Sources: [107], [311], [317]

Analysis: Budget comparison - optimization improvements can be inseparable from sample selection and validation conditions. Llama 3 rejection sampling generates 10-30 outputs per human-annotation prompt; DeepSeekMath samples 64 outputs per question in its described run; TTRL uses 64 voting responses and a 32-response training subsample. These are different compute and information budgets. A comparison based on retained examples, final model size or optimizer name alone is incomplete. Report total generations, token caps, judge calls and human checking, then distinguish training expenditure from evaluation expenditure. No cross-paper cost-normalized winner is computed here.

Sources: [278], [294], [404]

Analysis: Systems comparison - orchestration describes how computation moves, not whether feedback is valid. OpenRLHF uses separate rollout/training roles with vLLM and DeepSpeed and limits the inspected paper's support to language models. HybridFlow routes data between parallel layouts and generally executes colocated roles sequentially to avoid contention or memory failures. A platform's architectural support is therefore separate from a proof of label provenance, a task's reward soundness or the performance of a trained model. For a systems purchase, ask for reproducible resource and data-flow measurements under the actual recipe while auditing feedback quality through a different protocol.

Sources: [393], [397]

Analysis: Curation comparison - dataset selection can change task composition as well as nominal quality. AlpaGasus retains a model-scored subset of Alpaca and flags disproportionate removal of keyword-defined coding examples; DCLM's classifier retains a top-scoring fraction under a defined positive/negative training set; DataComp permits filtered size to vary under fixed samples-seen compute. The defensible interpretation is that filters select a distribution according to their targets. A buyer should inspect what was removed and the resulting task mix, rather than infer that every discarded example was objectively bad or that a smaller selected set is universally better.

Sources: [94], [104], [105]

Analysis: Evaluation comparison - win rate depends on who judges, what counts as a win and how ties are handled. The natural-language-feedback experiment counts ties as half a win; LIMA reports separate wins, ties and losses against dated responses; Llama 3 excludes slightly-better ratings from wins; RSO uses a three-rater majority. These figures cannot be pooled into a common preference advantage without the underlying protocol. A pilot should freeze the response population, judge rubric, blinding, tie rule and aggregation before comparing candidates, and report enough raw counts to reconstruct the stated metric.

Sources: [124], [290], [294], [304]

Analysis: Human-baseline comparison - the reference population and tools define the comparison. MMLU's approximate expert level is an estimate rather than a measured panel across all subjects; RE-Bench allows human internet and LLM use; VisualWebArena avoids assigning task creators to their own tasks; WebShop gives humans HTML observations while models use simplified text. These are substantive design choices. A claim that an agent exceeds humans should identify which humans, prior task exposure, allowed tools, time limits and observation mode. The reviewed record does not support a general human-versus-AI capability ranking.

Sources: [238], [239], [351], [463]

Analysis: Contamination comparison - tests detect particular kinds of overlap. MBPP's normalized line-overlap analysis concerns eligible reference-program lines; BIG-bench's canary is an intended training-exclusion signal; DeepSeekMath removes benchmark n-grams under its stated matching rules; STAMP requires pre-release watermarking and token-probability access. None of these procedures proves all forms of semantic or strategy-level independence. Buyers using public tasks should record exposure assumptions and run private or freshly authored holdouts where appropriate, while acknowledging that private construction also needs verification and rights review.

Sources: [193], [207], [278], [403]

Analysis: Generalization comparison - different kinds of difficulty should remain separate. GPQA explicitly disclaims representativeness of scientific practice; HLE states that a high score alone would not demonstrate autonomous research; ScienceAgentBench selects Python partly because of annotator familiarity; RE-Bench warns that short clear tasks with supplied resources are unlike open-ended research. A buyer should use these benchmarks to locate specific weaknesses and design target-workflow tests. They do not justify extrapolating an exam score or a short-horizon optimization result into complete professional capability, employment substitution or general intelligence.

Sources: [336], [339], [351], [353]

Analysis: The additional annotation literature changes how the earlier technical methods should be read. Snow's simplified temporal task and Gilardi's agreed-human subset show that the reference population can change a model-versus-human comparison. HelpSteer2's filtering changes the retained label population, while the label-error study shows that even corrected benchmark labels remain uncertain. A method comparison therefore needs three explicit objects: the items admitted, the rule defining reference truth and the items excluded before the headline result. This report treats those as experimental scope, rather than evidence of a universal labor or model advantage.

Sources: [413], [415], [418], [422]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: Consent in Crisis: The Rapid Decline of the AI Data Commons. The audited corpus sources are C4, RefinedWeb and Dolma. The head sample unions the top 2,000 domains by token count from each corpus into 3,950 domains. The random sample draws 10,000 domains from the 10,136,147-domain intersection and uses a random 2,000-domain subset for human annotation. The study reports inconsistencies between robots.txt signals and Terms of Service statements. Reading boundary: The study describes their differing crawl windows and filtering; paper version 2407.14933v1 is historical, not a current web-policy census.

Sources: [368]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: CrowdWorkSheets: Accounting for Individual and Collective Identities Underlying Crowdsourced Dataset Annotation. The toxicity-labeling case study is explicitly hypothetical and presents its documentation responses as non-prescriptive and non-comprehensive. The framework recommends a dataset maintenance plan and consideration of when annotations can become outdated as language or standards change. CrowdWorkSheets organize documentation questions around stages of dataset construction, from task formulation to dissemination. The framework asks developers to connect annotator-pool selection to intended dataset uses and potentially impacted communities. Reading boundary: Its pay, risk disclosures and platform capabilities are illustrative assumptions, not observed operational facts or supplier relationships.

Sources: [386]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: Data Cards: Purposeful and Transparent Dataset Documentation for Responsible AI. Data Cards document critical dataset information across its life cycle and allow tailored templates rather than one fixed schema for every dataset. The design principles organize cards into self-contained modular sections and support multiple granularities and content types. The authors develop a participatory workshop approach that engages cross-functional stakeholders when creating transparent dataset metadata schemas. In the reported cases, Google Docs card templates supported collaboration but field-level iteration caused fragmentation and limited automation of collection. Reading boundary: Framework design; flexibility does not establish that a particular card is complete or accurate.

Sources: [388]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: Data Statements for Natural Language Processing: Toward Mitigating System Bias and Enabling Better Science. The proposed Annotator Demographic field includes relevant training of annotators and guideline developers. The proposed Language Variety field combines a BCP-47 tag with a prose description. For datasets assembled from existing datasets, the schema proposes an appendix containing the source datasets’ data statements. The proposed short-form data statement is a 60-100 word summary pointing to the long form. Reading boundary: Demographic and educational attributes are proposed documentation items; privacy and availability constrain collection/disclosure.

Sources: [371]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: Datasheets for Datasets. The authors propose documenting a dataset’s motivation, composition, collection process and recommended uses. The questions and workflow were refined over roughly two years with multiple rounds of feedback. The paper states that datasheets alone are not a complete mitigation for unwanted societal bias or potential dataset harms. The authors intend datasheet creation to involve reflective human documentation rather than an automated creation process. For infrequently changing datasets, the authors recommend accompanying updated dataset versions with updated datasheets. The proposed collection-process documentation asks dataset creators to identify collection participants and their compensation. Reading boundary: Subsequent paragraphs describe example datasheets, product teams, researcher/practitioner/policy comments and legal feedback; this is author-reported development, not a controlled effectiveness trial.

Sources: [453], [462]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: Documenting Large Webtext Corpora: A Case Study on the Colossal Clean Crawled Corpus. The contamination analysis uses exact matches normalized for capitalization and punctuation and treats multi-component benchmark inputs separately. The authors leave quantification or removal of likely personally identifiable and copyrighted text in C4 for future work. C4 is derived from the April2019 Common Crawl snapshot with English identification and content filters, including a blocklist. The audit recommends documenting web metadata, the text included in a corpus, and the text excluded by filtering. Reading boundary: Exact input overlap does not alone establish that a benchmark label was present or that a trained model memorized it.

Sources: [389]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: Extracting Training Data from Large Language Models. The evaluation generates three pools of 200,000 samples, each sample 256 tokens long. The study identifies 604 unique memorized examples among its 1,800 selected candidates, reported as a 33.5% aggregate true-positive rate. For each of 18 generation-strategy/metric configurations, the study selects 100 samples from the metric’s top 1,000. The paper distinguishes training-data extraction of verbatim examples from inversion that reconstructs representative examples. Reading boundary: GPT-2 XL (1.5B parameters); strategies are top-n empty-sequence sampling, temperature sampling and Internet-conditioned sampling. Additional model identity support: physical p3 lines1-9.

Sources: [372]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: How do data owners say no? A case study of data consent mechanisms in web-scraped vision-language AI training datasets. Copyright-notice detection applies regular expressions to captions and PaddleOCR-extracted image text. The study operationalizes a data owner as the actor embedding the image on a webpage. Two coders annotate domain category, license type and scraping policy, resolving disagreements through annotation or codebook changes. The study audits CommonPool small and medium scales, restricting to English captions using fastText. Reading boundary: Signal-detection method; notices and their absence are not a legal authorization determination.

Sources: [369]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: Improving Task Instructions for Data Annotators: How Clear Rules and Higher Pay Increase Performance in Data Annotation in the AI Economy. The experiment uses a 2×3 between-subjects design crossing instruction type with presence of an incentive. Besides image-label accuracy, the study measures perceived instruction helpfulness and perceived task difficulty separately. The study recruits 307 participants who completed the experiment through Prolific Academic. The payment design compares £4.50 base pay with a condition offering an additional single £3 incentive. Reading boundary: Instructions: rules, incomplete rules, standards. Task: classify 100 building-entrance images as barrier-free or not for a wheelchair user.

Sources: [374]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: Minority Reports: Balancing Cost and Quality in Ground Truth Data Annotation. The pruning rule retains assignments involving unseen workers or tasks; otherwise it prunes when estimated minority-report probability exceeds a fixed threshold. Simulation quality is measured by comparing post-pruning majority votes against the counterfactual unpruned majority, using yes/no accuracy and F1. The paper defines a minority report as an annotator response that differs from the final majority-vote consensus for an image-crop question. The discussion cautions that RLHF ranked preferences can have high variability without a clear majority or a single notion of ground truth. Reading boundary: Prediction uses previously observed assignments and is recalibrated over time; a pruning decision is not a general worker competence judgment.

Sources: [395]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: Model Cards for Model Reporting. The proposed quantitative analysis reports results by individual factors and their intersections. The proposed Intended Use section records primary uses, primary users and out-of-scope uses. The proposed Metrics section includes performance measures, decision thresholds and variation approaches. Where detailed training-data disclosure is infeasible, the paper advocates basic group-distribution information. Reading boundary: Section 4.7 also recommends confidence intervals where possible and metric variation; no universal fairness guarantee follows.

Sources: [377]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: Sources of Disagreement in Data for LLM Instruction Tuning. On the full human dataset, quadratic-weighted kappa is 0.48 for SINGLE ratings and 0.43 for PREFERENCE combined scores; the authors find no evidence in this setup that preference annotation is easier or less ambiguous. Across the two human task formulations, the study reports instance-level disagreement correlation R=0.2 and ambiguity-set overlap 0.25, despite using the same annotators and data points. The zero-shot annotation experiment uses four instruction-tuned models from 1B to 8B; the 1B model has no reported human-label correlation, while the other three have correlation in 0.2-0.25. The human experiment selects720 Anthropic context/two-response instances, evenly split between helpful and harmless, and recruits 33 graduate-course annotators to perform both individual 1-5 quality ratings and paired preference/magnitude tasks. Reading boundary: This is a result for the studied population, generic quality instructions and sample; it does not establish all disagreement as noise.

Sources: [107]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: The Data Provenance Initiative: A Large Scale Audit of Dataset Licensing & Attribution in AI. The initial audit covers 44 instruction/alignment finetuning collections comprising 1,858 individual datasets selected by experts for widespread use; overlapping datasets are intentionally not deduplicated to preserve collection design choices. The license protocol searches for creator-attributable licenses explicitly applying to data, distinguishes them from code licenses, and records permitted-use, attribution and share-alike categories with the strictest feature across multiple licenses. The provenance audit combines linked public metadata, human legal-expert annotation and GPT-4-assisted annotation; its topic annotation uses GPT-4 on a sample of 100 examples for up to 10 topics. The authors explicitly characterize their collection as best-effort categorization of self-reported licenses for research/transparency, not legal advice or a determination that the listed licenses are enforceable.

Sources: [128]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: The Data-Production Dispositif. Both authors analyze the instruction documents through structural, detailed-fragment and synoptic discourse-analysis stages. The investigation combines 55 interviews, participant observation and analysis of 210 instruction documents collected during 2019-2021 fieldwork. The Venezuela worker recruitment starts with convenience sampling and expands through snowball sampling. Fieldwork covers three crowdsourcing platforms operating in Venezuela and a data-work BPO in Buenos Aires. Reading boundary: Iterative interpretive analysis is contrasted with interview/observation material; not a controlled experiment or automated annotation-quality measurement.

Sources: [370]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: The Dataset Nutrition Label: A Framework To Drive Higher Data Quality Standards. The paper warns that the validity of a ground-truth comparison module depends on its reference dataset and can be harmed by a flawed comparator. The label uses stand-alone modules that can be combined to fit dataset type, information availability and specialist expertise. The Dollars-for-Docs demonstration combines metadata, provenance and variable information with statistical and interactive comparison modules. The initial Nutrition Label prototype restricts exploration to tabular datasets with fewer than ten thousand rows. Reading boundary: Labels for comparator datasets and community feedback are suggested mitigations, not proof that bias has been eliminated.

Sources: [396]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: The Problems with Proxies: Making Data Work Visible through Requester Practices. The authors distinguish proxies for worker identity/suitability from proxies for ability to produce desired data, observing combined filtering in requester accounts. The study interviews 52 requesters from academic and industry settings between November 2022 and January 2023. The paper limits its findings to US requester perspectives and warns that reported experiences may differ from behavior in practice. Interviews include a task walkthrough and questions on payment calibration, worker perceptions and qualification metrics, followed by demographic and follow-up-consent forms. Reading boundary: Qualitative thematic finding in this US requester sample; no prevalence estimate or global ranking of platforms is asserted.

Sources: [399]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: The digital labour of artificial intelligence in Latin America: a comparison of Argentina, Brazil, and Venezuela. Recorded worker interviews are transcribed, accompanied by debriefing reports and coded using both descriptive categories and literature-informed theoretical categories. Spanish-language questionnaires and interviews are fielded as paid platform tasks, with later follow-up and cross-platform re-fielding to examine pandemic-specific conditions. The authors state that statistical representativeness is difficult to apply because the boundaries and characteristics of platform populations are unknown. The article combines a Spanish-language platform-worker study with a Portuguese-language Brazilian study, including questionnaires, follow-up interviews and online ethnography. Reading boundary: Topics include task types, trajectories, informality and social protections; this methodology does not itself verify reported pay or any named supplier’s contribution.

Sources: [394]

Evidence: Reviewed-work atlas - Documentation, labor and evidence quality: “Everyone wants to do the model work, not the data work”: Data Cascades in High-Stakes AI. COVID-era video/phone interviews prevent workflow shadowing and contextual inquiry; the findings are self-reported practices in high-stakes projects, with sampling and gender-distribution limitations. The study groups cascades into physical-world brittleness, inadequate application-domain expertise, conflicting reward systems and poor cross-organizational documentation. Between May and July 2020, the authors conduct semi-structured interviews with 53 high-stakes AI practitioners: 23 in India, 16 in the US and 14 in East/West African countries, using purposive and snowball recruitment. The authors report that 92% of their 53 interview participants experienced at least one data cascade, defined as compounding data-related events producing negative downstream effects and technical debt. Reading boundary: Percentages are coded self-reports in the selected interview sample and are not population prevalence.

Sources: [101]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: A General Theoretical Paradigm to Understand Learning from Human Preferences. IPO is an identity-mapping special case of ΨPO that learns directly from preferences without a reward-modeling stage or the Bradley-Terry pairwise-to-pointwise assumption. The sampled-preference comparisons use three-action bandits, softmax parameterizations, 18,000 Adam steps and ten seeds; reported curves include means and 95% confidence intervals. The paper leaves scaling IPO experiments to more complex settings, including training language models on human preference data, to future work. IPO optimizes an empirical squared loss on the policy/reference log-likelihood ratio of preferred versus dispreferred actions, targeting one-half the inverse regularization coefficient. Reading boundary: These are illustrative bandit experiments, not LLM benchmark results.

Sources: [40]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Back to Basics: Revisiting REINFORCE Style Optimization for Learning from Human Feedback in LLMs. The study does not measure correlation between its simulated preference judgments and final human evaluation preferences. RLOO uses the other k−1 sampled-completion rewards as the baseline for each completion in a prompt’s group. Across the reported datasets/models, online rollout uses the same prompts as the SFT stage. For Pythia 6.9B TLDR, Table 1 reports GPT-4-simulated win rates 77.9 for RLOO(k=4) and 67.6 for PPO against original completions. REINFORCE/RLOO treat the entire completion as one action in the paper’s deterministic bandit formulation. Reading boundary: Values are percentages. Each method uses its checkpoint with highest test reward; test-reward selection is part of this historical comparison.

Sources: [302]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: DAPO: An Open-Source LLM Reinforcement Learning System at Scale. DAPO separates lower and upper clipping ranges, increasing the upper range while retaining the lower range to encourage low-probability-token exploration. Dynamic sampling oversamples and excludes prompts whose sampled response group has all-correct or all-incorrect answers, continuing until the effective batch is filled. Soft overlong punishment adds a length-dependent penalty to correctness rewards within a configured interval near the generation limit. DAPO aggregates the policy loss over tokens across the sampled batch, replacing equal weighting of response-level average losses. Reading boundary: Mechanism described in the selected version; the candidate makes no universal entropy or quality guarantee.

Sources: [387]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Deep Reinforcement Learning from Human Preferences. The method asynchronously alternates environment interaction/policy updates, eliciting human trajectory-pair comparisons, and supervised fitting of a learned reward predictor. Human raters compare 1-2 second trajectory clips and may prefer either clip, mark them equal, or mark them incomparable; incomparable judgments are omitted from the comparison database. The evaluation separates real human comparisons, synthetic oracle comparisons derived from environment reward, and RL with the real reward. Real-human MuJoCo and Atari curves each represent a single run. In the offline-only reward-predictor ablation, optimizing a predictor fitted only at the start can exploit incomplete reward estimates, including Pong policies that avoid losses without scoring. Reading boundary: Curve averaging differs by condition: five runs for other MuJoCo curves and three for other Atari curves.

Sources: [32]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning. Table 6 reports AIME 2024 pass@1 of 72.6 for DeepSeek-R1-Distill-Qwen-32B versus 47.0 for DeepSeek-R1-Zero-Qwen-32B. The six described Qwen/Llama distilled models are fine-tuned with the approximately 800,000 curated samples using SFT, without a distillation-stage RL step. R1 cold-start collection includes model-generated or R1-Zero responses refined through post-processing by human annotators. The rejection-sampling stage retains correct responses and collects approximately 600,000 reasoning training samples. DeepSeek-R1-Zero uses accuracy and format rewards and does not use an outcome or process neural reward model in the described training. Reading boundary: Scores are percentages estimated with nonzero-temperature sampling, not cons@64. The RL-only comparison is a specific Qwen 32B training run exceeding 10,000 steps (p14).

Sources: [279]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: DeepSeek-V3 Technical Report. In the DeepSeek-V2.5 distillation ablation, MATH-500 pass@1 rises from 74.6 to 83.2 while average response length rises from 769 to 1,510. DeepSeek-V3 uses GRPO, estimating the baseline from group scores instead of a separate critic model. For non-reasoning SFT data, DeepSeek-V2.5 generates responses and human annotators verify accuracy and correctness. DeepSeek-V3 instruction tuning uses 1.5 million curated instances with domain-specific creation procedures. Table 6 reports DeepSeek-V3 MATH-500 exact match of 90.2 under greedy decoding and an 8,192-token output cap. Reading boundary: This is the report's V2.5 ablation, not a direct causal estimate for the final V3 system. Length units are not named in the cited table.

Sources: [280]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: DeepSeekMath: Pushing the Limits of Mathematical Reasoning in Open Language Models. Math-corpus decontamination removes segments matching benchmark 10-grams; shorter benchmark texts with at least three grams use exact matching. Outcome-supervised GRPO normalizes sampled response rewards by their group mean and standard deviation and assigns that normalized reward to all response tokens. DeepSeekMath-RL 7B reports chain-of-thought accuracy of 88.2% on GSM8K and 51.7% on MATH. The reported DeepSeekMath RL run samples 64 outputs per question with maximum length 1,024 and one policy update after each exploration stage. The authors identify geometry and theorem proving as relatively weak areas and suggest pretraining/fine-tuning data-selection bias as a possible contributor. The mathematical SFT collection contains 776,000 English/Chinese examples with chain-of-thought, program-of-thought or tool-integrated solutions. Reading boundary: These are benchmark-specific no-tool CoT results, not tool-integrated accuracy or pass@multiple-samples.

Sources: [278]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Direct Preference Optimization: Your Language Model is Secretly a Reward Model. The authors derive a classification objective for learning from preferences. DPO fits an implicit reward through a direct policy objective without fitting a separate reward model and running an RL training loop. The summarization experiment reuses human preference annotations collected by Stiennon et al. The controlled IMDb sentiment experiment generates preference pairs using a pretrained sentiment classifier. The paper's empirical evaluation covers models up to 6 billion parameters. The GPT-4 summary-judgment validation study recruits 25 volunteer human raters. Reading boundary: The equivalence uses the paper's KL-constrained objective and preference-model assumptions. Preference-labelled pairs are still required.

Sources: [457], [465]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Evaluating Large Language Models Trained on Code. The paper finds overlapping BLEU-score distributions for unit-test-correct and incorrect HumanEval completions and cautions that higher BLEU need not imply better functional correctness. The study generates 200 samples per HumanEval task and estimates pass@k for k at most 100 using the count of samples that pass the unit tests. The authors report that the studied code model struggles with increasingly long, higher-level or system-level specifications, limiting interpretation of success on the short HumanEval tasks. HumanEval contains 164 hand-written Python programming problems, each with a function signature, docstring, body and unit tests; the paper reports a mean of 7.7 tests per problem. Reading boundary: The estimator and its proof were read descriptively; no proof verification or experiment reproduction is claimed.

Sources: [204]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: GDPval: Evaluating AI Model Performance on Real-World Economically Valuable Tasks. Model-based screening does not autonomously alter tasks; human experts retain responsibility for accuracy and completeness. The experimental automated grader agrees with expert graders 66% of the time, compared with 71% human inter-rater agreement. The authors report an average of five human reviews per task and a minimum of three across all 1,320 tasks. The authors identify precisely specified, one-shot tasks as a limitation relative to contextual, interactive work. Reading boundary: Reported gold-subset pairwise-grading agreement, not task-completion accuracy.

Sources: [335]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: GPT-4 Technical Report. The report states that GPT-4 uses public and third-party licensed pretraining data but withholds dataset construction, model size and training-compute details. Formal-essay exam responses were graded by one or two qualified third-party contractors with relevant essay-grading experience. The authors report GPT-4 accuracy 19 percentage points above their latest GPT-3.5 on nine internal adversarial factuality evaluations. In the system-card pipeline, human demonstrations train SFT, human rankings train a reward model, and PPO optimizes the SFT policy using that reward. Rule-based reward models are zero-shot GPT-4 classifiers conditioned on human-written rubrics and supply an additional PPO reward on selected prompts. Reading boundary: Accuracy is agreement with human ideal responses; per-category sample denominators are not specified in the cited passage. This historical internal evaluation is not a general provider-performance estimate.

Sources: [288]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Group Sequence Policy Optimization. The authors propose using inference-engine sequence likelihoods directly as a possible way to avoid old-policy likelihood recomputation in the training engine. The GSPO comparison begins with a cold-start model fine-tuned from Qwen3-30B-A3B-Base and evaluates AIME24, LiveCodeBench from October 2024 to February 2025, and CodeForces. GSPO clips entire responses, with length normalization intended to control ratio variance and numerical range across response lengths. GSPO defines its importance ratio from sequence likelihood, using a length-normalized likelihood ratio rather than individual token ratios. Reading boundary: Presented as an engineering possibility based on tolerance of precision discrepancies, not a demonstrated universal guarantee for every engine or workflow.

Sources: [392]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: HelpSteer3-Preference: Open Human-Annotated Preference Data across Diverse Tasks and Languages. The approved record attributes the specific documents relationship to HelpSteer3.

Sources: [460]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: If in a Crowdsourced Data Annotation Pipeline, a GPT-4. Against Bio Expert reference labels, combining GPT4 at temperature 0.2 with advanced-interface crowd labels surpasses GPT4 alone under the One-Coin Dawid-Skene and MACE settings. The advanced crowd interface includes visual click feedback, a color-coded overview and a time lock, while the basic interface emphasizes task simplicity. The study uses CODA19 to label abstract sentence segments as Background, Purpose, Method, Finding/Contribution or Other. The test set samples 200 papers from an English-language CORD19 pool restricted to 2022 or later publications, producing 3,177 abstract segments. Reading boundary: Only those two tested aggregation settings beat GPT4 in this study; outcomes depend on cleaning/aggregation and task, and worker LLM use cannot be excluded.

Sources: [391]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Instruction-Following Evaluation for Large Language Models. Table 3 reports GPT-4 prompt-level strict accuracy of 76.89%. The authors warn that loose response transformations can introduce false positives. Humans manually check and edit every rephrased prompt after model-assisted generation, screening and rephrasing. Prompt-level strict accuracy requires every verifiable instruction in a prompt to be followed. Reading boundary: November 2023 API responses; approximately 500 prompts in the inspected v1. This is constraint compliance rather than holistic answer quality.

Sources: [340]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Is It Thinking or Cheating? Detecting Implicit Reward Hacking by Measuring Reasoning Effort. TRACE truncates a response’s CoT,forces an answer and computes the area under verifier pass rate versus retained-CoT percentage. A hacking response is defined as passing the verifier with the loophole present but failing when it is removed. The authors state that TRACE is designed for reasoning tasks requiring inference-time exploration. The study trains hacking and nonhacking instruction-tuned models with RLOO. Reading boundary: Instance-level early-answering evaluation generalizes same-answer faithfulness checks to verifier passing; high area is interpreted as a possible low-effort shortcut,not definitive intent.

Sources: [383]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: KTO: Model Alignment as Prospect Theoretic Optimization. KTO directly uses a binary signal indicating whether a given output is desirable or undesirable for its input, instead of requiring a preferred/dispreferred pair. The paper's PPO comparator is an explicitly offline variant with a fixed reference/old policy and dummy +1/-1 rewards, differing from standard online reward-model-based PPO. For most experiments, the authors convert existing HH, SHP and OpenAssistant preference pairs into desirable and undesirable examples; separate experiments subsample one output per input. KTO can ignore examples that are difficult to learn, which may help with noisy feedback but can also discard necessary information and produce underfitting. Reading boundary: The data requirement is binary; these principal experiments nevertheless reuse preference datasets.

Sources: [41]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Learning from Natural Language Feedback. Two authors wrote feedback on initial summaries while seeing the title, post and initial summary. One author conducted the human evaluation for the fine-tuned-model comparisons in Figures 2 and 5. Fine-tuning GPT-3 on feedback-selected refinements reports 51±5.0% win rate against Reddit-user reference summaries. The method chooses among 20 generated refinements by maximum embedding cosine similarity to the natural-language feedback. The summarization test uses 100 unseen Reddit posts, ranks summaries with ties allowed and counts a tie as half a win. Reading boundary: The± value is standard error;100 test posts and the one-author evaluation apply. This does not establish parity with professional summarizers or humans generally.

Sources: [290]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Learning to summarize from human feedback. The authors report about 320 GPU-days for 6.7B RL fine-tuning and thousands of labeler hours, and state that they did not collect an equivalent amount of high-quality supervised human demonstrations as a baseline. After controlling for summary length, the paper reports that its 6.7B human-feedback model summaries remain preferred to the TL;DR reference summaries about 65% of the time. An experiment using an earlier reward-model version finds that more PPO optimization initially improves human preferences but eventually worsens them even as the reward-model prediction rises. The paper fine-tunes a TL;DR summarization baseline, collects human comparisons of candidate summaries, trains a scalar reward model from those comparisons and optimizes a policy with PPO plus a KL penalty. The study explicitly states that its summary-comparison labelers are hired from Upwork and the labeling services Scale and Lionbridge, with paid onboarding and researcher calibration. Reading boundary: The outcome is this experiment’s human preference against dataset reference summaries, not objective universal summary accuracy.

Sources: [133]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Let's Verify Step by Step. The study evaluates reward models by best-of-N selection from a fixed generator and deliberately does not improve that generator with reinforcement learning. The evaluation uses a uniformly selected 500-problem subset of MATH's test split; 4,500 other test-split problems are included in reward-model training. Large-scale PRM and ORM training sets are not directly comparable: active PRM selection biases toward wrong answers and uses an order of magnitude fewer examples; small-scale ablations use model-generated supervision on matched data. Reading boundary: Do not describe these results as evaluation on all 5,000 MATH test problems.

Sources: [51]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Llama 2: Open Foundation and Fine-Tuned Chat Models. The authors state that their human evaluation prompt set contains no coding- or reasoning-related prompts. On the paper’s helpfulness prompt set, Llama 2-Chat 70B has a reported 36% win rate and 31.5% tie rate relative to ChatGPT. Preference annotators write prompts, choose between responses from two model variants, and label four levels of preference strength. Iterative reward-ranked sampling selects the best-scoring answer per prompt; later iterations reuse top samples from earlier rounds to mitigate observed forgetting. The authors stopped their vendor-based SFT annotation collection at 27,540 annotations and state that it excludes Meta user data. Reading boundary: ChatGPT is gpt-3.5-turbo-0301; approximately 4,000 helpfulness prompts, three raters per prompt. This is a historical prompt-set comparison.

Sources: [293]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: On the Reliability of Majority-Vote Pseudo-Labels in Test-Time Reinforcement Learning. When all sampled rollouts for a prompt share one answer, the method caches them; if a later majority conflicts with that answer, it discards the new pseudo-pairs and uses a cache loss. PC-Dr.DPO sets each prompt's robust temperature from its observed majority fraction, with weaker majorities receiving sharper within-prompt weighting. The analysis separates population-majority bias, where the policy's modal answer is wrong, from finite-rollout variation, where sampled majorities differ from that mode. The evaluation adapts on each full evaluation set or official test split using fixed benchmark budgets and reports the final checkpoint rather than the best intermediate checkpoint. Reading boundary: The safeguard preserves earlier self-consistency, which can itself be wrong; it does not correct population-majority bias.

Sources: [401]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Process Reinforcement through Implicit Rewards. PRIME can initialize its PRM from the starting SFT/base policy and filters prompts by their sampled accuracy range during training. PRIME updates an implicit PRM online using policy rollouts and outcome supervision and uses token-level dense rewards for policy training. The instantiated advantage estimator computes implicit-process and outcome returns separately before combining them, using leave-one-out baselines. The implicit PRM parameterizes reward with the log likelihood ratio of a reward language model to a reference model, yielding token-level process rewards. Reading boundary: The described filtering aims at intermediate difficulty and PRM data balance; exact selected accuracy bounds are not specified by this claim.

Sources: [398]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Proximal Policy Optimization Algorithms. On 49 Atari games with metrics averaged over three trials, PPO wins 30 games by average reward across training and 19 by average reward over the final 100 episodes; ACER wins 18 and 28 respectively. PPO proposes a surrogate that takes the minimum of an unclipped probability-ratio advantage term and its clipped counterpart, removing incentive for some excessively large policy updates. The continuous-control surrogate comparison uses seven Gym MuJoCo -v1 tasks, one million timesteps per run, three random seeds per task, and a normalized aggregate over 21 runs. The actor-critic PPO algorithm collects rollout data from parallel actors, computes advantage estimates, then optimizes a surrogate on those samples for multiple minibatch epochs. Reading boundary: Game-win counts depend on the specified metric and compared A2C/ACER implementations.

Sources: [50]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: RAFT: Reward rAnked FineTuning for Generative Foundation Model Alignment. RAFT selects the batch's highest-reward fraction for supervised fine-tuning at each stage. For IMDB, the study measures perplexity on 500 test samples and constrains its increase to at most 5%. The IMDB table reports LLaMA 7B-RAFT mean sentiment reward 0.4293 and mean perplexity 9.9375, versus the unaligned row's 0.0993 and 9.5. The authors identify sparse desirable samples as a failure mode in which RAFT may stall without enough favorable outputs to select. The RAFT algorithm optionally mixes an expert generator with the current generator during data collection. Reading boundary: The reward is a learned sentiment-model score; this result is not a general helpfulness/safety gain.

Sources: [299]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: REBEL: Reinforcement Learning via Regressing Relative Rewards. REBEL permits its base response distribution to be either a fixed offline dataset or the current policy. The TLDR evaluation compares generated summaries against human references using GPT-4 on a randomly sampled 600-example test subset. In the described experiments, both responses in each REBEL regression pair are generated by the current policy. REBEL regresses response-pair reward differences against policy log-ratio differences, removing the prompt-only partition term. The 6.9B TLDR table reports 78.0% win rate for REBEL and 77.6% for PPO. Reading boundary: The PPO result is imported from Huang et al.; the table is not a jointly rerun paired comparison. GPT-4 is the preference judge, not a human panel.

Sources: [300]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: REINFORCE++: Stabilizing Critic-Free Policy Optimization with Global Advantage Normalization. REINFORCE++ replaces prompt-local advantage normalization with global normalization and describes a single-response configuration for general RLHF. The baseline variant first subtracts the within-prompt mean reward and then normalizes using global batch statistics. The baseline variant uses a separate KL regularization loss with the k2 estimator. The best-practice discussion distinguishes baseline variants that support binary 0/1 or symmetric −1/1 rewards from plain REINFORCE++, which the authors recommend with symmetric rewards. Reading boundary: Single-response mode means one sampled response per prompt. Selected v9 also evaluates plain REINFORCE++ with k > 1 for reasoning (section 4.2). The baseline variant adds group-mean reshaping and is particularly advised for sample filtering and complex tasks such as multi-turn tool use (sections 3.2 and 5.1); multiple responses alone do not require it.

Sources: [400]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: RLAIF-V: Aligning MLLMs through Open-Source AI Feedback for Super GPT-4V Trustworthiness. RLAIF-V generates candidate responses with the same model/distribution, decomposes factual response content into atomic claims, queries an open-source multimodal labeler with yes/no questions and constructs preference pairs for iterative DPO training. RefoMB descriptions start with GPT-4V drafts merged by GPT-4, then human additions/corrections and verification by at least two graduate students; GPT-4 uses descriptions to judge response pairs against GPT-4V. The authors acknowledge training costs and remaining hallucination despite improvements, and leave further trustworthiness gains for future methods. For the 146-sample MHumanEval response-level hallucination measure in v1, Table 1 reports 50.7% for OmniLMM 12B, 29.5% after RLAIF-V, and 45.9% for the compared GPT-4V condition. The 7B setting uses LLaVA 1.5 as instruction model and LLaVA-NeXT as labeler; the 12B setting uses OmniLMM as both instruction model and labeler, with four 4k-instruction iterations described for each. Reading boundary: Open-source training feedback does not mean the complete benchmark/evaluation workflow excludes humans or proprietary models. Table 4 defines99 dev and 261 test instructions; the prose’s images wording is inconsistent.

Sources: [130]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: RLAIF: Scaling Reinforcement Learning from Human Feedback with AI Feedback. In this v1 summarization study, PaLM2 Large generates preference labels and PaLM2 Extra-Small initializes the models; RL uses modified A2C rather than PPO. Human policy evaluation uses 1,200 ratings: evaluators rank RLAIF, RLHF, SFT and human-reference summaries without ties for held-out TL;DR posts. For each summary pair, the AI labeler is queried twice with reversed candidate order and the resulting preference distributions are averaged to mitigate position bias. Human evaluators prefer RLAIF summaries to SFT 71% of the time and RLHF to SFT 73%; the paper reports the difference as not statistically significant and RLAIF versus RLHF as 50%. Reading boundary: The study is summarization-only v1; longer outputs are a reported confound and comparative monetary costs were not estimated (conclusion p9).

Sources: [52]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: RRHF: Rank Responses to Align Language Models with Human Feedback without tears. The experiments use the HH preference corpus with the Dahoas/gptj-rm-static proxy reward model. RRHF scores each response with length-normalized conditional log probability. Table 2 reports Alpaca-RRHF with diverse-beam sampling mean proxy reward −1.02 and GPT-2-medium perplexity 14.75 on HH. The pinned RRHF study does not experiment with refreshing the sampling policy at every training step. RRHF adds ranking loss to cross-entropy training on the highest-reward response. Reading boundary: Reward units are model-specific; a high proxy reward is not an independent measure of helpfulness or safety.

Sources: [303]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: ReMax: A Simple, Effective, and Efficient Method for Aligning Large Language Models. The reported GPT-4 model comparison uses 300 LIMA test samples. ReMax subtracts the reward of a current-model greedy response from the reward of its sampled response when forming the policy-gradient loss. ReMax does not resolve reward bias or reward hacking; the authors identify data collection and reward-learning design as remaining requirements. The authors report no substantial training-speed acceleration for models on the scale of OPT 1.3B after DeepSpeed optimization. The authors report about 2.2× training acceleration for ReMax in a GPT-2-137M IMDB positive-sentiment continuation experiment without DeepSpeed. The rm-static experiments randomly split the public dataset 20% for SFT,40% for reward learning and 40% for reward maximization. Reading boundary: OPT win/tie/loss counts in one displayed comparison sum to 299 rather than 300; that mismatch is retained as an issue and no corrected count is inferred.

Sources: [301]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Reference-free Monolithic Preference Optimization with Odds Ratio. The paper uses GPT-4 as judge in AlpacaEval1.0 and MT-Bench, and GPT-4-turbo in AlpacaEval2.0, with text-davinci-003 and GPT-4 references respectively for the two AlpacaEval versions. ORPO combines supervised chosen-response NLL loss with a weighted log-sigmoid odds-ratio loss comparing chosen and rejected responses. ORPO updates the model directly without retaining a separate frozen reference model; the paper compares this computation to its stated RLHF/DPO training setup. The paper leaves scaling beyond 7B parameters, broader preference-method comparisons and more diverse fine-tuning domains to future work. Reading boundary: These are automated evaluation outcomes, distinct from human preference annotation.

Sources: [49]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: SLiC-HF: Sequence Likelihood Calibration with Human Feedback. The sample-rank experiments generate eight SFT-model decodes per example at temperature 0.7 and top-k 40. SLiC-HF-direct calibrates directly on preferred/rejected human-feedback sequences without training a ranking or reward model. SLiC-HF-direct can face mismatch between the off-policy human-feedback distribution and the SFT model’s decode distribution. In a 100-validation-example four-way human comparison, the sample-rank SLiC-HF model is chosen best 73% of the time. SLiC-HF combines a margin-based sequence ranking calibration loss with cross-entropy regularization. Reading boundary: Three raters per task; choice uses majority vote, with 4% same/no-preference. This is a four-way selection rate, not pairwise win rate against every baseline.

Sources: [310]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: STAMP Your Content: Proving Dataset Membership via Watermarked Rephrasings. STAMP requires watermarking before online release and access to model token probabilities; it does not retroactively mark previously published content. The method uses a one-sided paired t-test for lower public-version perplexity relative to private versions. STAMP compares a public keyed paraphrase collection with privately held differently keyed paraphrases using paired perplexity differences. STAMP can compare each public paraphrase against the average perplexity over multiple differently keyed private paraphrases to reduce individual-document bias. Reading boundary: The paper also warns about paraphrase errors and evaluates continual pretraining rather than models trained from scratch.

Sources: [403]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: SWE-Lancer: Can Frontier LLMs Earn $1 Million from Real-World Freelance Software Engineering?. SWE-Lancer Diamond contains 502 tasks: 237 implementation tasks and 265 managerial tasks. Table 1 reports Claude 3.5 Sonnet passing 26.2% of the 237 Diamond implementation tasks with the user tool enabled. The implementation-task prompt tells the agent to edit code without running the app. The authors state that evaluated models cannot ask clarifying or follow-up questions. The task-selection process reports 100 professional software engineers reviewing tasks, proposals and code for clarity and executability. Reading boundary: Historical single-attempt task success; not the dollar-weighted earnings rate and not the managerial score.

Sources: [358]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: SelectTTRL: Representation-Guided Data Selection for Efficient Test-Time Reinforcement Learning. Percentile selection is fixed before adaptation without target ground-truth answers, while all target questions remain in the evaluation set. SelectTTRL constructs a frozen correctness-related activation direction from paired correct and incorrect answers in a separate TruthfulQA-derived labeled calibration set. In the reported experiment, subset baselines retain the same question fraction and vary the selection rule while keeping the TTRL procedure, budget and hyperparameters fixed. Initial target responses are scored and ranked, then only a prescribed percentile interval receives standard TTRL multi-response sampling and policy updates. Reading boundary: The selected subset is defined by floor-based percentile ranks and fixed-identifier tie breaking, not post-hoc selection of only correctly answered targets.

Sources: [402]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Self-Play Preference Optimization for Language Model Alignment. The authors report that general leaderboard performance for DPO, IPO and SPPO declines after the first or second alignment iteration. SPPO formulates alignment as a two-player constant-sum preference game rather than assuming one transitive scalar reward for all comparisons. The experiment uses three SPPO iterations, advancing a first-epoch model trained on 20,000 prompts each iteration. Table 1 reports 28.53% length-controlled AlpacaEval 2 win rate for SPPO Iter 3 versus 17.11% for Mistral 7B-Instruct-v0.2. The experiment samples five responses per prompt and retains the highest- and lowest-PairRM-scoring responses for preference data. The SPPO convergence theorem assumes realizability of the ideal optimization problem and concerns the mixture policy across iterations. Reading boundary: 805 prompts; GPT-4-Turbo judging/reference protocol. These are ordinary decoding rows, separate from best-of 16 reranking. Table score 28.53 differs from prose 28.52.

Sources: [311]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Self-Refine: Iterative Refinement with Self-Feedback. The reported blind human A/B evaluation is conducted by the paper authors; Table 6 describes150 examples for each evaluated dataset. The paper limits its main experiments to English and proprietary base models, requires sufficient few-shot/instruction-following ability, and reports that erroneous feedback dominates the analyzed failed refinements. In Table 1, GPT-4 code-optimization performance rises from 27.3% to 36.0%, while math solve rate changes from 92.9% to 93.1%; the paper uses task-specific, human-preference and GPT-4-preference metrics rather than one common accuracy measure. Self-Refine uses the same language model for initial generation, natural-language feedback and refinement, appending prior feedback/output history without additional model training. Reading boundary: These values are reported under this paper’s task setups and are not a general hallucination or correctness improvement.

Sources: [131]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: SimPO: Simple Preference Optimization with a Reference-Free Reward. For Instruct setups, five responses per UltraFeedback prompt are generated from the starting model and PairRM selects the highest/lowest-scoring pair. SimPO introduces a positive target reward margin in the Bradley-Terry preference objective. For Llama 3-8B-Instruct, Table 4 reports AlpacaEval 2 length-controlled win rate 44.7% for SimPO versus 40.3% for DPO. SimPO uses length-normalized policy log-likelihood as an implicit reward and removes the reference-policy term. The authors state that their experiments focus on helpfulness and do not evaluate safety, honesty and fairness comprehensively. Reading boundary: 805 questions and the benchmark’s automatic evaluation protocol;44.7 is length-controlled, not raw win rate (40.5).

Sources: [309]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Statistical Rejection Sampling Improves Preference Optimization. The standard RSO experiment generates 64 SFT-policy candidates and rejection-subsamples eight. The CNN/DailyMail experiment assumes no training access to CNN/DailyMail targets or preference texts, testing transfer from TLDR training. The HH experiments use the helpfulness task rather than the entire mixed helpfulness/harmlessness task set. Human evaluation uses three raters per task, anonymized/shuffled responses and majority choice;47 distinct raters participated. For TLDR sigmoid-normalized optimization, the three-way human comparison selects rso-sample-rank 48% of the time versus 21% for direct optimization. The empirical RSO sampler accepts candidates according to an exponential function of reward relative to the maximum remaining candidate reward. Reading boundary: All-same outcomes mean percentages need not sum to 100; this is three-way best-choice frequency, not a 48% pairwise win rate.

Sources: [304]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Step-DPO: Step-wise Preference Optimization for Long-chain Reasoning of LLMs. On MATH, the Qwen2-7B-SFT ablation reports 54.8% baseline,55.0% with DPO and 55.8% with Step-DPO. The proposed localization procedure permits humans or GPT-4 to find the first erroneous reasoning step. The described data construction produces 10,000 pairwise preference records for Step-DPO. The authors caution that outputs with correct final answers can still contain erroneous intermediate steps, requiring additional preferred-step filtering. Step-DPO contrasts preferred and rejected next reasoning steps conditioned on the prompt and preceding correct steps. Reading boundary: Both preference methods use 5,000 training records in this ablation; MATH evaluation has 5,000 problems. These values do not describe the full 10,000-record main run.

Sources: [312]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: TTRL: Test-Time Reinforcement Learning. The example reward function extracts final answers and gives reward one for matching the most frequent sampled answer and zero otherwise. TTRL samples multiple candidate outputs, derives a consensus answer and uses agreement with that answer to construct its reward signal. TTRL is defined as reinforcement-learning adaptation of a pretrained model during test time without ground-truth labels for the target data. The implementation samples 64 responses for voting and downsamples 32 per prompt for policy training. Reading boundary: This exact rule is answer-frequency agreement; it does not validate the intermediate reasoning.

Sources: [404]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: The Llama 3 Herd of Models. The Llama 3 DPO recipe masks header and termination tokens from both chosen and rejected response losses to stabilize training. Some preference records contain three ranked responses: human-improved edited response, chosen response, and rejected response. The authors report that Llama 3 405B and GPT-4-0125 win rates are within the margin of error on nearly all capabilities in their human evaluation. The human evaluation counts a model win only when an annotator rates its response better or much better, excluding slightly-better ratings from wins. Llama 3 post-training applies six rounds, collecting new preference annotations and SFT data and sampling synthetic data from the latest models each cycle. Rejection sampling typically generates 10 to 30 outputs per human-annotation prompt and uses the reward model to choose one candidate. Reading boundary: About 7,000 prompts across capability sets; pairwise seven-point preference ratings. This is not an across-provider or present-day ranking.

Sources: [294]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: ToolLLM: Facilitating Large Language Models to Master 16000+ Real-world APIs. ToolEval measures pass rate through completion and exclusion rules and win rate through ChatGPT path comparisons; its judge-validation study uses four human preference annotations for each of 600 solution pairs. For API responses exceeding 2,048 tokens, ToolBench applies a ChatGPT-derived compression schema and, if necessary, retains only the first 2,048 tokens. The ToolBench construction pipeline uses ChatGPT gpt-3.5-turbo-16k for API collection, instruction generation and solution-path annotation, while human experts provide in-context seed examples. After filtering, the pinned ToolLLM paper reports 3,451 retained tools containing 16,464 APIs; these are different counting units.

Sources: [237]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Training Verifiers to Solve Math Word Problems. For the paper's 6B verifier, increasing candidate completions helps up to 400 and then reduces performance; the authors attribute this to the risk of finding solutions that fool the verifier. Verifier targets label model-generated solutions by whether their final answer is correct; the paper explicitly notes false positives when flawed reasoning reaches the right answer. Reading boundary: This is the tested model/setup; the usual reported verification evaluation uses 100 completions.

Sources: [63]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Training a Helpful and Harmless Assistant with Reinforcement Learning from Human Feedback. For RLHF training, the paper combines 137k prompts from the static human-feedback dataset with 369k model-generated prompts; the synthetic prompts are distinct from the human comparison labels used to train preference models. The authors emphasize average-case rather than worst-case behavior, unresolved honesty and subtle-bias issues, and RL stability limitations. A controlled 52B helpfulness experiment uses equal-sized data and identical hyperparameters and finds that a base/rejection-sampling/online mixture is preferred by crowdworkers to all-base data. The study collects helpfulness dialogues by choosing the more helpful response and red-team dialogues by choosing the more harmful response; retained comparisons are treated as equally weighted binary labels without ties. Workers are recruited through US MTurk and Upwork; the authors select workers using writing/dialogue spot checks rather than agreement-based label filtering, and explicitly note that the worker distribution changes over the project. Reading boundary: In this paper, online iterations retrain new models rather than continually updating one model. This is not a guarantee of worst-case safety.

Sources: [112]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Training language models to follow instructions with human feedback. The authors describe collecting human rankings of model outputs as part of their instruction-following training method. Reward-model data collection presents human labelers with 4 to 9 model responses to rank for a prompt. The paper’s prompt dataset primarily uses prompts submitted to early InstructGPT through the OpenAI API Playground. Most comparisons in this workflow are labelled by one contractor for cost reasons. The PPO prompt dataset is used as RLHF input without per-prompt human labels. Reading boundary: Pairwise comparisons derived from a single ranked set are correlated; they are not independent human judgements for each pair.

Sources: [456], [464]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: TruthfulQA: Measuring How Models Mimic Human Falsehoods. The human generation-evaluation procedure blinds evaluators to the model name and prompt that produced an answer. The paper recruits two external researchers for separate reference-label validation and a human-answer baseline. GPT-judge training includes about 6,900 true/false-labelled author reference answers and about 15,500 human-evaluated model answers. Reading boundary: Section 3.2 (p.6) says the authors carried out all main-generation evaluations. A predefined qualitative rubric maps to scalar truth scores; it does not remove all judgment or disagreement.

Sources: [450]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: Understanding R1-Zero-Like Training: A Critical Perspective. Dr. GRPO replaces response-dependent loss normalization with a constant and uses a Monte Carlo return baseline in the recovered objective. The authors identify within-question reward-standard-deviation normalization as reweighting questions and introducing difficulty bias. The authors identify response-length normalization as a bias favoring shorter correct responses and longer incorrect responses in their GRPO objective analysis. The optimizer experiment assigns reward one when Math-Verify accepts the final answer and zero otherwise, training on MATH questions and evaluating on AIME2024, AMC, MATH500, Minerva Math and OlympiadBench. Reading boundary: The preceding method also removes group standard-deviation normalization (physical p6 lines150-151); unbiasedness is reported by the paper and not independently proved.

Sources: [390]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: VAPO: Efficient and Reliable Reinforcement Learning for Advanced Reasoning Tasks. VAPO separates GAE parameters for value targets and policy advantages, using lambda one for the value-network returns. VAPO adjusts policy GAE lambda as a function of output length and a bias-variance control parameter. VAPO combines policy-gradient loss with an additional negative-log-likelihood loss on correctly sampled outcomes. VAPO pretrains the value model on Monte Carlo returns from a fixed policy before saving and loading that value checkpoint for policy training. Reading boundary: Policy lambda is separately length-adaptive in this recipe; no general unbiasedness theorem is asserted by this candidate.

Sources: [405]

Evidence: Reviewed-work atlas - Feedback, rewards and policy optimization: WPO: Enhancing RLHF with Weighted Preference Optimization. The conceptual WPO preference-labeling construction assumes there are no conflicting pairwise preferences for a prompt. The authors state that their preference dataset does not include safety aspects and that they do not study preference optimization for multi-turn conversations. The hybrid experiment labels five SFT-model outputs plus one GPT-4-Turbo output using GPT-4-Turbo additive scoring. In the off-policy Llama 3-8B-Instruct setting, WPO reports AlpacaEval 2 length-controlled win rate 33.8(1.3)% versus DPO 28.2(0.5)%. WPO weights each preference-pair loss by the product of current-policy response weights, detached from backpropagation; sequence probabilities are length-normalized in practice. Reading boundary: Parentheses are standard deviations across five random-seed runs;805 evaluation instructions. This is the off-policy row, separate from hybrid results.

Sources: [317]

Evidence: Reviewed-work atlas - Multilingual supervision and evaluation: BenchMAX: A Comprehensive Multilingual Evaluation Suite for Large Language Models. For IFEval, BenchMAX removes language-specific instructions and retains 429 samples. BenchMAX selects 17 languages spanning multiple language families and writing systems. The construction pipeline translates English data, has three human annotators post-edit each sample, then selects a final translation. All benchmark translations except long-context data are post-edited by native human experts. Reading boundary: Selection applies to the BenchMAX IFEval component, not all tasks or the original IFEval corpus.

Sources: [366]

Evidence: Reviewed-work atlas - Multilingual supervision and evaluation: How Reliable is Multilingual LLM-as-a-Judge?. Cross-language consistency is measured using Fleiss' Kappa,treating each language-specific output as a rater's judgment. The experiments use datasets with parallel data and treat ground-truth answers as the answers being judged. The experiments use pointwise judgments with both binary Yes/No and1-5 score criteria. The main setup uses an English instruction prompt with the target language specified through an eval_language placeholder. Reading boundary: The paper separately considers accuracy/grade because high consistency alone can reflect uniformly incorrect judgments. No kappa-to-accuracy conversion is made.

Sources: [381]

Evidence: Reviewed-work atlas - Multilingual supervision and evaluation: M-IFEval: Multilingual Instruction-Following Evaluation. For Japanese,the construction removes word-count length constraints and uppercase/lowercase instructions from the English IFEval list. The benchmark selects French,Japanese and Spanish with one native-speaker language lead for each. Language leads design objectively evaluable instructions that include language-specific linguistic and textual controls. The constructed prompt sets contain 115 Spanish,172 Japanese and235 French prompts. Reading boundary: Writing-system-specific adaptation, not evidence that all translated English constraints transfer unchanged.

Sources: [376]

Evidence: Reviewed-work atlas - Multilingual supervision and evaluation: M-RewardBench: Evaluating Reward Models in Multilingual Settings. The translation component draws from MAPLE, which supplies five human-rated translations per source with scores 1-6. The experiment setup describes selecting 25 reward models spanning 3 B-104 B parameters and generative, classifier and implicit-DPO types. General-task instances are translated from RewardBench into 23 languages with Google Translate and human-reviewed filtering. The benchmark constructs 100 easy and 100 hard chosen/rejected translation pairs for each of four translation directions. Reading boundary: MAPLE derives from WMT20/21 and covers de→en,zh→en,en→de,en→zh. Describes the paper's source material, not a separate dataset review.

Sources: [379]

Evidence: Reviewed-work atlas - Multilingual supervision and evaluation: MENLO: From Preferences to Proficiency -- Evaluating and Modeling Native-like Quality Across 47 Languages. Each generated response pair is shown in randomized order and rated by at least three annotators. MENLO measures fluency, tone, localized tone and localized factuality. MENLO contains 6,423 prompt-response preference pairs and reports 81,014 human annotations. The design selects 47 language varieties and uses human-written parametric English prompt templates to evoke local contexts. Reading boundary: Responses use GPT-4o, Llama4-Maverick, Llama4-Maverick with Search and Gemini1.5 with Search; 1-5 Likert ratings allow ties and final scores use majority vote. Expert annotators provide language-specific feedback and subset gold labels.

Sources: [375]

Evidence: Reviewed-work atlas - Safety, feedback and verification: Constitutional AI: Harmlessness from AI Feedback. For the current comparison tests, workers were instructed to prefer nuanced, transparent and thoughtful responses over evasive ones when similarly harmless, changing the harmlessness evaluation from prior work. The RL-CAI preference model mixes human-feedback labels for helpfulness with model-feedback labels for harmlessness; the RL pipeline then optimizes this hybrid preference model. The supervised CAI stage samples responses to red-team prompts, asks the model to critique and revise those responses under constitutional principles, and finetunes on revised responses. The paper explicitly reports that current comparison tests were performed with Surge AI workers; reused preference-model data came from an earlier period working primarily with Upwork and MTurk. Reading boundary: Current Elo comparisons inherit this preference rubric and are not directly interchangeable with the prior paper's Elo results.

Sources: [23]

Evidence: Reviewed-work atlas - Safety, feedback and verification: Constitutional Classifiers: Defending against Universal Jailbreaks across Thousands of Hours of Red Teaming. The approach uses separate input-only and streaming output-only classifiers. The authors identify preset chatbot queries, incomplete adversary coverage and rubric difficulty distinguishing benign knowledge from actionable uplift as evaluation limitations. The improved chemistry-focused classifier system reports an absolute 0.38 percentage-point production refusal-rate increase on 5,000 sampled Claude.ai conversations. None of the 113 submitted prototype jailbreak reports answered all ten target questions at the half-helpful-only-detail rubric threshold. Constitution-guided data generation uses a helpful-only model for queries/outputs and a prompted model to remove inadvertent refusals. The automated-evaluation classifiers omit automated-red-teaming training data, unlike the bug-bounty prototype classifiers. Reading boundary: This is the improved system guarding Claude 3.5 Sonnet(New), not the earlier human-red-teamed prototype.

Sources: [277]

Evidence: Reviewed-work atlas - Safety, feedback and verification: DICES Dataset: Diversity in Conversational AI Evaluation for Safety. For DICES-350, a trust/safety gold rating is first assigned by one rater and verified by a pool of five experts; the paper reports disagreement with the crowd-majority label in 34% of examples. The paper identifies small conversation count, restricted demographic categories and unresolved separation of sincere belief differences from task/rater noise as limitations, despite high replication of ratings. DICES-350 rater quality assessment considers unusually short annotation time and invariant conversation labels; the paper removes 19 raters before its 104-rater analysis. DICES-990 recruits 173 US/India raters with partial conversation coverage; DICES-350 recruits a different 123-rater US pool, then excludes 19 raters and reports results from 104 raters who each annotate all 350 conversations. Reading boundary: Counts of raters recruited, retained, ratings and safety-question annotations must not be conflated.

Sources: [106]

Evidence: Reviewed-work atlas - Safety, feedback and verification: Deliberative Alignment: Reasoning Enables Safer Language Models. The StrongREJECT human review uses at least two reviewers per prompt/answer pair, with an expert third reviewer arbitrating disagreements. AppendixA reports mean human assistance grade 1.020 for o1 and 1.335 for GPT-4o on its StrongREJECT review. For SFT filtering, completions are judged repeatedly and assigned the minimum judge score before high-score retention. SFT trains on original prompts with specification text removed, while keeping the generated reasoning/output as targets. During RL, the safety judge sees the policies but not the model’s chain-of-thought; this particular RL reward is used for o1 and o3-mini. Training completions are generated by a specification-agnostic base reasoning model prompted with category-relevant safety specifications. Reading boundary: 2,100 adversarial prompts per model,35 trained reviewers, assistance grades 1/3/5. Gemini API-blocked prompts are scored 1.

Sources: [281]

Evidence: Reviewed-work atlas - Safety, feedback and verification: Monitoring Reasoning Models for Misbehavior and the Risks of Promoting Obfuscation. For two systemic hacks,the study uses string-regex detections as retrospective ground truth for monitor evaluation. A prompted GPT-4o monitor looks for reward hacking in coding environments where an agent implements functionality to pass unit tests. In the direct CoT-pressure experiment, a non-frontier agent still hacks while its GPT-4o monitor recall falls near zero. The CoT monitor observes reasoning,tool calls and final outputs,while the action monitor sees only tool calls and final outputs. Reading boundary: Hacks are exit(0) early termination and raise SkipTest outside the testing framework. Ground truth covers these identifiable hacks,not every potential exploit.

Sources: [378]

Evidence: Reviewed-work atlas - Safety, feedback and verification: Red Teaming Language Models to Reduce Harms: Methods, Scaling Behaviors, and Lessons Learned. The authors state that they do not know whether crowdworkers have expertise needed to assess some technical harms and that attack coverage is incomplete; the review workflow includes warnings, opt-out previews, support communication and a voluntary well-being survey. Self-reported attack success shows no clear model-size trend, while minimum harmlessness-model scores show RLHF models becoming harder to red-team with scale; harmful outputs still occur. At each dialogue turn, participants see two model responses and select the more harmful; after the conversation they rate attack success on a 0-4 scale, separately from the learned preference-model harmlessness score. A follow-up sample of 500 attacks each on 52B prompted and RLHF models receives three reviewer ratings per transcript; agreement including the attack author is Fleiss kappa0.32 on Likert ratings and 0.49 after binarization. The study’s red team comprises 324 US-based crowdworkers: 307 recruited through MTurk and 17 through Upwork; about 80% of attacks come from roughly 50 workers. Reading boundary: Worker-support descriptions do not establish absence of harm, and reduced average harmfulness does not establish a perfectly safe model.

Sources: [129]

Evidence: Reviewed-work atlas - Source curation and demonstrations: AlpaGasus: Training A Better Alpaca with Fewer Data. The study evaluates on Koala, Vicuna, WizardLM and Self-Instruct prompts with an API LLM judge such as GPT-4, comparing both response orders to mitigate position bias. The initial study is limited to 7B/13B models and the Alpaca instruction dataset, and explicitly states that it performs no human evaluation. The initial AlpaGasus study grades Alpaca instruction-input-response triplets with ChatGPT for accuracy and retains scores at least 4.5, selecting 9,229 of 52,002 samples. The 7B WizardLM-test analysis reports better-or-equal performance on 22 of 29 skills, but flags weaker coding categories and a keyword-defined coding-data removal rate of 88.16%, versus 82.25% overall. Reading boundary: This evaluation is automatic preference scoring, not human preference ground truth.

Sources: [94]

Evidence: Reviewed-work atlas - Source curation and demonstrations: DataComp-LM: In search of the next generation of training sets for language models. For the reported 2.6T-token 7B model, the authors augment DCLM-Baseline with StarCoder and ProofPile2, use a math-enriched annealing phase and extend context; Table 9 reports 63.7% MMLU. The human-quality study samples 499 rule-filtered/deduplicated documents and obtains three labels per document from 16 English-speaking AI graduate students/professors; 281 documents have unanimous labels. DCLM's first evaluation suite omits fairness, multilinguality and safety; compute limits prevent joint exploration of all curation dimensions, sufficient random-seed variation and testing beyond 7B models. The DCLM-Baseline quality filter uses fastText trained with OpenHermes 2.5 plus high-scoring ELI5 positives and RefinedWeb-sampled negatives, retaining the top 10% by classifier score. DCLM provides an unfiltered Common-Crawl-derived pool of 240T GPT-NeoX tokens and five fixed-recipe compute scales; evaluation separates 53-task extended performance, 22-task core performance and five-shot MMLU. Reading boundary: The result is not attributable to raw Common Crawl or the baseline filter alone. The paper's headline64% is rounded.

Sources: [105]

Evidence: Reviewed-work atlas - Source curation and demonstrations: DataComp: In search of the next generation of multimodal datasets. DataComp's filtering track fixes the candidate pool and training compute by total samples seen while allowing the filtered dataset size to vary; it also offers a separate bring-your-own-data track and four compute scales. The paper warns that ImageNet performance is not representative of every task and reports demographic biases in face classification; some tested BYOD sources can increase misclassification risk. At xlarge scale, the image-based/CLIP-score intersection baseline named DataComp-1B contains 1.4B samples and reports 79.2% zero-shot ImageNet accuracy after 12.8B samples seen, versus 72.3% for no filtering under the table's matched scale. CommonPool generation starts from Common Crawl image URLs with nonempty alt-text, uses unsafe-content filtering and evaluation-image near-duplicate removal to construct the 12.8B xlarge pool, and provides face bounding-box metadata for default blurring during participant image download. Reading boundary: These are described preprocessing steps, not a verified guarantee of absence of unsafe content or personal information.

Sources: [104]

Evidence: Reviewed-work atlas - Source curation and demonstrations: Dolma: an Open Corpus of Three Trillion Tokens for Language Model Pretraining Research. The paper introduces Dolma as approximately 3T tokens across 5B documents from seven public data sources, alongside an open-source curation toolkit; its design primarily targets English text. Dolma's general deduplication is within each source subset rather than across sources; its web pipeline uses URL, exact-document and exact-paragraph Bloom-filter stages, while code starts from The Stack's prior near-deduplicated version. The paper's Olmo-1b comparison is trained on roughly 3T tokens from preliminary Dolma v1.5; the table explicitly notes unequal training-token budgets for some comparator models and unknown StableLM2 data composition. The web pipeline uses regular-expression PII detection for email addresses, IP addresses and phone numbers; its 1B-model ablation reports no discernible performance difference from the studied masking/removal strategies. The release discussion acknowledges residual incorrect, toxic, hateful, personal and copyrighted content in web-derived corpora despite mitigation, and says the project's decisions may be revisited. Reading boundary: This is a model-performance observation, not a privacy guarantee or a full PII-recall measurement. The prose and Figure 4 differ on the boundary count, so no exact boundary count is proposed here.

Sources: [108]

Evidence: Reviewed-work atlas - Source curation and demonstrations: LIMA: Less Is More for Alignment. The quality/diversity/quantity ablations fine-tune 7B models and use ChatGPT scores; the paper explicitly acknowledges possible confounding when using Stack Exchange versus wikiHow as a diversity proxy. In the paper's human preference evaluation over 300 test prompts, LIMA versus April-2023 GPT-4 responses records 18% wins, 25% ties and 57% losses. The discussion identifies substantial manual curation effort and limited robustness: unlucky decoding samples or adversarial prompts can produce weak LIMA responses. LIMA fine-tunes pretrained LLaMa 65B on exactly 1,000 curated demonstration sequences; Table 1 separates community-derived examples, 50 Natural Instructions examples and 200 paper-author training examples. Reading boundary: The source comparison does not isolate diversity alone, and the result does not establish universal diminishing returns to instruction data.

Sources: [124]

Evidence: Reviewed-work atlas - Source curation and demonstrations: SELF-INSTRUCT: Aligning Language Model with Self Generated Instructions. For user-oriented evaluation, the authors create 252 new instructions with one instance each, and the instruction authors judge model outputs on a four-level quality rubric. Reading boundary: This differs from the SuperNI ROUGE-L evaluation and is not a representative or independently recruited user sample.

Sources: [56]

Evidence: Reviewed-work atlas - Source curation and demonstrations: Scaling Instruction-Finetuned Language Models. The CoT mixture reuses nine prior datasets with human-written reasoning annotations and manually composed instruction templates; its ablation reports that omitting CoT data degrades performance on held-out CoT evaluations. The paper's finetuning collection comprises 473 datasets, 146 task categories and 1,836 dataset/task-category tasks from Muffin, T0-SF, NIV2 and a CoT mixture; templates do not create separate tasks. The Flan-T5 model card states that it has not been tested in real-world applications; the responsible-AI appendix also notes limited identity/language coverage and noise/bias in automated toxicity measures. At 540B parameters, Table 3 reports a normalized six-score held-out average of 49.1 without finetuning and 58.5 with all 1,836 tasks, a 9.4-point difference. Reading boundary: The normalized macro-average is not raw overall accuracy. Section2.2 selects checkpoints using periodic evaluations of held-out tasks.

Sources: [111]

Evidence: Reviewed-work atlas - Source curation and demonstrations: The Common Pile v0.1: An 8TB Dataset of Public Domain and Openly Licensed Text. Common Pile v0.1 is described as an 8 TB text corpus curated from 30 sources. The curation definition excludes Creative Commons NonCommercial and NoDerivatives material. Source inclusion requires confidence that license information comes from the copyright holder. The curators take a conservative stance against including LLM-generated synthetic content. Reading boundary: Raw corpus description in version 2506.05209v1;8TB is not a token count or a claim that every component independently meets a legal standard.

Sources: [367]

Evidence: Reviewed-work atlas - Source curation and demonstrations: WizardLM: Empowering Large Pre-Trained Language Models to Follow Complex Instructions. Evol-Instruct separates instruction evolution, response generation and elimination of failed evolutions; in-depth prompts add difficulty while in-breadth prompts expand instruction diversity. The WizardEval human study uses 218 instructions spanning 29 skills and domains and recruits 10 annotators for source-hidden, shuffled-response comparison using five listed evaluation aspects. The paper acknowledges scalability and reliability limitations of its GPT-4 and human evaluations and warns that its test set may not cover every application scenario or domain. WizardLM v3 starts from 52k Alpaca instructions, runs four evolution rounds using Azure OpenAI ChatGPT, obtains a 250k instruction pool, and samples 70k examples for main LLaMA 13B fine-tuning.

Sources: [134]

Evidence: Reviewed-work atlas - Task construction and evaluation: τ^2-Bench: Evaluating Conversational Agents in a Dual-Control Environment. Telecom task success is evaluated only with assertion functions. The authors manually refine LLM-generated telecom implementations until their unit tests pass. The reported GPT-4.1 pass^1 falls to 34% on telecom from 74% on retail and 56% on airline. Table 2 records three critical simulator errors in 50 telecom conversations. The telecom evaluation subsamples 114 tasks from 2,285 programmatically composed tasks. Reading boundary: Historical four-run temperature-zero function-calling configuration with GPT-4.1 user simulation; not live customer accuracy.

Sources: [361]

Evidence: Reviewed-work atlas - Task construction and evaluation: AgentBench: Evaluating LLMs as Agents. AgentBench's overall score averages heterogeneous task metrics after weighting each by the reciprocal of its mean across the evaluated models. The initial AgentBench evaluation includes 25 API or open models; the open-model population is limited to models no larger than 30B. Reading boundary: The aggregate is population-dependent normalization, not percent of all tasks completed.

Sources: [20]

Evidence: Reviewed-work atlas - Task construction and evaluation: AgentGym: Evolving Large Language Model-based Agents across Diverse Environments. For its main evolution experiments, AgentGym converts rewards below one to zero and retains reward one as success, even when an environment originally provides dense rewards. AgentGym collects model-generated and crowdsourced trajectories, filters them by reward or correctness, and forms the 6,130-trajectory AgentTraj training collection. AgentGym describes 14 environments and 89 task types, while its main self-evolution experiments use 11 environments. AgentGym evaluates models without trajectory fine-tuning with few-shot prompts and trajectory-trained models with zero-shot prompts; evaluation uses temperature zero and exploration uses 0.7.

Sources: [189]

Evidence: Reviewed-work atlas - Task construction and evaluation: BenchGuard: Who Guards the Benchmarks? Automated Auditing of LLM Agent Benchmarks. The intended workflow surfaces findings with evidence for expert adjudication rather than autonomously deciding benchmark truth. The five-model union exactly aligns with 20 of 24 atomic BIXBench issues, reported as 83.3%. BenchGuard cross-verifies task instructions, reference programs, evaluation scripts and environment configurations. The authors identify hallucinated audit findings as a reason to retain expert review. ScienceAgentBench precision is conditioned on findings inside tasks with confirmed defects. Reading boundary: The 24 issues come from 17 expert-revised tasks within Verified-50; this is neither 83.3% of all tasks nor all possible defects.

Sources: [321]

Evidence: Reviewed-work atlas - Task construction and evaluation: Beyond the Imitation Game: Quantifying and extrapolating the capabilities of language models. BIG-bench task-definition files include a canary identifier intended to help exclude benchmark text from web-scraped training corpora and diagnose training-on-test use. The study reports mean and best average task scores from expert evaluators but cautions that heterogeneous expertise, task subsampling and timed sessions constrain interpretation of these human reference scores. BIG-bench Lite is the paper's 24-task lightweight subset and contains only JSON tasks. The paper describes at least 204 BIG-bench tasks, intended principally for zero- and few-shot evaluation without task-specific fine-tuning, with JSON and Python programmatic task interfaces. Reading boundary: The mechanism does not establish exclusion by a particular model.

Sources: [193]

Evidence: Reviewed-work atlas - Task construction and evaluation: BrowseComp: A Simple Yet Challenging Benchmark for Browsing Agents. The grading prompt instructs the judge to compare against the supplied answer rather than solve the question or argue for alternatives. The paper states that BrowseComp questions were collected entirely by human trainers. Human trainers solved 367 of the 1,255 attempted questions, reported as 29.2%. The authors cannot guarantee that every valid answer is represented by the reference answer. Reading boundary: Creators could not attempt their own questions, and AI assistance was disallowed; 11 of 1,266 questions were not attempted.

Sources: [322]

Evidence: Reviewed-work atlas - Task construction and evaluation: Fair human-centric image dataset for ethical AI benchmarking. Most annotations are self-reported by image subjects; observable labels such as pixel annotations,head pose and camera distance are exceptions. Vendors must obtain signed informed consent from primary and secondary image subjects and a copyright agreement for each image. Reported dataset terms restrict use to fairness/bias evaluation and mitigation,with training allowed only for bias-mitigation tools. Image subjects may withdraw consent for inclusion without losing their compensation. Reading boundary: Demographics are not inferred from images in this protocol. Annotation-guideline and raw-data compliance remain unaudited.

Sources: [373]

Evidence: Reviewed-work atlas - Task construction and evaluation: GAIA: A Benchmark for General AI Assistants. GAIA is designed for zero-shot concise factoid answers and grades final answers using type-dependent normalization followed by quasi-exact match to a unique reference answer. GAIA question creators provide answers and tool/step metadata; two new annotators independently answer each question, with ambiguous items repaired or removed. The paper calls its manually selected GPT-4-plugin configuration an oracle estimate because plugins changed and no stable automatically selected set was available. The pinned GAIA paper evaluates the final answer and explicitly leaves evaluation of the reasoning or action trace to future work. Reading boundary: This is a historical evaluation-setup limitation, not a statement about current products or current performance.

Sources: [200]

Evidence: Reviewed-work atlas - Task construction and evaluation: GPQA: A Graduate-Level Google-Proof Q&A Benchmark. The authors hire 61 contractors through Upwork to write and validate the dataset. GPT-4 with few-shot chain-of-thought scores 39.7% on the 448-question main split. The authors make no claim that GPQA represents questions arising in scientific practice. The authors flag expert and non-expert validator accuracies on main and Diamond splits as selection-biased. Reading boundary: Historical baseline; the separate search-plus-backoff configuration scores 41.0% and is not this result.

Sources: [336]

Evidence: Reviewed-work atlas - Task construction and evaluation: HarmBench: A Standardized Evaluation Framework for Automated Red Teaming and Robust Refusal. The pinned HarmBench paper describes 510 behaviors: 400 textual and 110 multimodal, split into 100 development/validation and 410 test behaviors. The paper identifies target-model generation length as a major ASR comparison confounder and standardizes evaluation output length to 512 tokens. The HarmBench authors used GPT-4 to summarize several providers' acceptable-use policies and manually designed behaviors with that summary as guidance. HarmBench separates development and test classifiers and prohibits direct optimization on its test metric; the development classifier uses a different base model and half the fine-tuning set used for the test classifier. Reading boundary: The prose labels this output budget N while the equation uses N for test-case count; this assertion describes the prose-defined output condition.

Sources: [203]

Evidence: Reviewed-work atlas - Task construction and evaluation: Humanity's Last Exam. The authors say high HLE accuracy would not alone demonstrate autonomous research or artificial general intelligence. Table 1 reports o1 accuracy of 9.1% on the inspected HLE evaluation. Approximately 13,000 questions that stumped the checked models were forwarded to expert human review. The appendix describes two rounds of human review for submitted questions. Reading boundary: The inspected v1 describes 3,000 questions; this is a January 2025 snapshot, not current leaderboard performance.

Sources: [339]

Evidence: Reviewed-work atlas - Task construction and evaluation: JailbreakBench: An Open Robustness Benchmark for Jailbreaking Large Language Models. The JailbreakBench paper states that proper test-time-defense evaluation should use attacks adapted to the defense; transfer attacks from undefended models give only a lower bound on worst-case attack success. Appendix H of the pinned JailbreakBench paper states that all code and data are released under the MIT license. The study compares automatic jailbreak judges on 200 jailbreak prompt-response pairs labeled by three experts, using majority labels, plus 100 benign XS-Test examples. JBB-Behaviors contains 100 harmful behaviors and 100 corresponding topic-matched benign behaviors used to assess excessive refusal. Reading boundary: This records the paper's statement; separate current repository and upstream-rights checks were not performed.

Sources: [205]

Evidence: Reviewed-work atlas - Task construction and evaluation: MLE-bench: Evaluating Machine Learning Agents on Machine Learning Engineering. The authors state that reuse of high-level solution strategies is difficult to detect. Manual screening selects 75 Kaggle competitions, with seven additional development competitions. The headline metric is the proportion of attempts earning at least a bronze medal under the applied private-leaderboard thresholds. o1-preview with AIDE earns any medal on 16.9% ± 1.1 standard error of attempts. Submissions with Dolos similarity above 60% are surfaced for human plagiarism review. Reading boundary: 75 competitions with 16 seeds; 24-hour/A10 main setup. This is a historical normalized competition comparison, not awarded Kaggle medals.

Sources: [348]

Evidence: Reviewed-work atlas - Task construction and evaluation: MMMU-Pro: A More Robust Multi-discipline Multimodal Understanding Benchmark. GPT-4o (0513) scores 51.9 overall, averaging 54.0 in ten-option standard form and 49.7 in vision form. Human experts use GPT-4o assistance to augment answer options and review original question-image relevance. The final 3,460 presentations comprise 1,730 standard questions and 1,730 screenshot/photo forms. The main results select the higher score from Direct and chain-of-thought prompting. Reading boundary: Paired underlying questions; the authors report the higher result from Direct and CoT prompts, so this is not a single fixed-prompt evaluation.

Sources: [349]

Evidence: Reviewed-work atlas - Task construction and evaluation: MMMU: A Massive Multi-discipline Multimodal Understanding and Reasoning Benchmark for Expert AGI. The MMMU study extracts answers using response-processing workflows; if no valid answer is found, it randomly selects an option for multiple-choice questions and marks open-ended responses incorrect. MMMU annotation guidance favors questions whose answers are less directly accessible, such as in separate documents or textbook endings, as a contamination-risk precaution. MMMU flags potential duplicates using lexical overlap and source-URL similarity, has authors review them, checks formatting and typos, and excludes questions classified as very easy. MMMU selects thirty subjects across six disciplines and recruits over fifty university students specializing in those majors to collect multimodal questions and create new questions where needed. Reading boundary: The guidance is a precaution, not an audit establishing absence of training contamination.

Sources: [212]

Evidence: Reviewed-work atlas - Task construction and evaluation: MathVista: Evaluating Mathematical Reasoning of Foundation Models in Visual Contexts. MathVista uses heuristic filtering of nineteen VQA datasets followed by three expert annotators and majority voting to identify mathematical-reasoning examples, capping each source at 400 examples. MathVista uses an LLM-based answer extractor such as GPT-4, normalizes the extracted answer into the required format, and computes accuracy against reference answers. Each MathVista testmini question is assigned to five AMT annotators with over 5,000 HITs and acceptance above 0.99; included workers must pass qualification questions and have at least a high-school diploma. The pinned MathVista paper defines 6,141 examples partitioned into a 1,000-example testmini and a 5,141-example test, and states that test answer labels will be withheld to reduce contamination.

Sources: [206]

Evidence: Reviewed-work atlas - Task construction and evaluation: Measuring Massive Multitask Language Understanding. The paper estimates expert-level accuracy at approximately 89.8%. GPT-3 evaluation selects the A/B/C/D answer token with the highest model probability. The paper reports 34.5% accuracy for unspecialized human respondents from Amazon Mechanical Turk. Reading boundary: This is an author estimate combining 95th-percentile examination scores with educated guesses where unavailable, not a measured expert panel across every subject.

Sources: [463]

Evidence: Reviewed-work atlas - Task construction and evaluation: MultiChallenge: A Realistic Multi-Turn Conversation Evaluation Benchmark Challenging to Frontier LLMs. MultiChallenge contains 273 test conversations across four challenge categories. Construction first generates synthetic candidate data and then has human experts review and edit it. Human raters provide an instance-level binary rubric question answerable using the final model response. Self-coherence tests whether a model remains reasonably consistent with its earlier responses. Reading boundary: Categories/counts:inference memory113,instruction retention69,reliable version editing41,self-coherence50; average5 turns and1231.7 words per conversation. Counts describe this benchmark version.

Sources: [380]

Evidence: Reviewed-work atlas - Task construction and evaluation: OSWorld: Benchmarking Multimodal Agents for Open-Ended Tasks in Real Computer Environments. OSWorld tasks pair instructions with initial-state setup and manually crafted evaluation scripts; the paper reports nine computer-science student authors spending over three months and about 1,800 person-hours on construction and checking. The paper reports 134 unique evaluation functions that use getters to extract final-state information and evaluators to assess task completion. The OSWorld human evaluation uses computer-science-major college students with basic software skills who had not previously seen the samples or software; their time and correctness are measured for each example. The paper states that its evaluation functions mainly assess task-completion correctness and do not efficiently detect latent unnecessary damaging side effects. Reading boundary: A successful task score is not a safety certification.

Sources: [213]

Evidence: Reviewed-work atlas - Task construction and evaluation: PaperBench: Evaluating AI's Ability to Replicate AI Research. Claude 3.5 Sonnet with BasicAgent obtains a mean Replication Score of 21.0% ± 0.8 standard error. The paper reports that Code-Dev performance is weakly correlated with full PaperBench performance. JudgeEval reports o3-mini-high SimpleJudge macro F1 of 0.83 overall and 0.72 for Code Development. PaperBench prohibits agents from using or viewing the original paper authors' codebases. The final Replication Score is computed by propagating weighted averages from binary rubric leaf decisions to the root. Reading boundary: 20 papers, three runs each, at most 12 hours per run; score measures weighted rubric credit, not percentage of fully replicated papers.

Sources: [350]

Evidence: Reviewed-work atlas - Task construction and evaluation: Program Synthesis with Large Language Models. The authors manually inspected, edited and pruned MBPP into a 426-question edited subset; their original-versus-edited evaluation compares 100 overlapping questions. MBPP was constructed by an internal pool of crowdworkers with basic Python knowledge who supplied a problem statement, a self-contained reference function and three semantic test cases per problem; the original collection has 974 problems. The authors' whitespace-normalized line-overlap analysis found 32 of 974 MBPP reference programs with more than half their eligible lines matched in a pretraining document. The paper documents a generated MBPP program that hard-codes a tested input and passes the supplied assertions without implementing the intended function. Reading boundary: The edited subset and original dataset are separate manifestations within one benchmark family.

Sources: [207]

Evidence: Reviewed-work atlas - Task construction and evaluation: RE-Bench: Evaluating frontier AI R&D capabilities of language model agents against human experts. The authors report o1-preview with AIDE matching the 36th percentile of human experts in their best-of-k comparison. The human baseline includes 71 eight-hour runs by 61 distinct experts. Human participants are allowed to browse the internet and use LLMs and other tools. The authors warn that clear instructions, short progress horizons and supplied resources make these environments less representative of real research. The normalization sets the starting solution's score to zero and the author reference solution's score to one. Reading boundary: Seven environments; sampled shorter attempts use a shared total time budget. This percentile does not establish end-to-end research automation.

Sources: [351]

Evidence: Reviewed-work atlas - Task construction and evaluation: Reinforcement Learning on Web Interfaces Using Workflow-Guided Exploration. The Alaska flight-form experiment ports a web page into the MiniWoB framework, replaces its server backend with a JavaScript surrogate and fixes the environment date to March 1, 2017. The paper introduces MiniWoB++ tasks to test longer horizons, soft natural-language reasoning and stochastically varying layouts. The workflow-guided-exploration study selects forty tasks from the then-public eighty-task MiniWoB distribution and collects ten demonstrations per selected task using Amazon Mechanical Turk. For the paper main MiniWoB experiments, partial rewards are disabled so tasks use sparse end-of-episode success or failure feedback. The method induces workflows from demonstrations using a compositional language that constrains click/type actions and adds shortcut steps for unnecessary or collapsible demonstration actions. Reading boundary: This experiment does not demonstrate successful live flight booking or purchase.

Sources: [211]

Evidence: Reviewed-work atlas - Task construction and evaluation: RewardBench 2: Advancing Reward Model Evaluation. Non-Ties subsets score selection of one correct response among four completions, with a 25% random baseline. The authors manually verify every example in the math subset after model-based answer selection and matching. The authors conclude that reward-model benchmark accuracy is not sufficient for strong RLHF training. Section 3 construction prose reports that manual verification and filtering reduce an initial pool of about 3,000 prompts to 1,876 final prompts. Table 3 reports QRM-Gemma-2-27B averaging 76.7 on RewardBench 2. Reading boundary: The same version’s Table 2 caption reports 1,865 prompts, and its six printed domain counts sum to 1,865 (475+160+183+450+495+102). This is an unreconciled source-internal discrepancy. The 1,876 figure is attributed specifically to construction prose, not an independently recounted or resolved corpus total.

Sources: [352]

Evidence: Reviewed-work atlas - Task construction and evaluation: SWE-Bench Pro: Can AI Agents Solve Long-Horizon Software Engineering Tasks?. Human augmentation adds task requirements grounded in original sources and gold-patch/test expectations. Table 1 reports GPT-5 resolving 23.3% of the 731 public tasks with SWE-Agent. The inspected version releases a public split of 731 problems. The authors acknowledge that valid software solutions may fail the original verification tests. The reported test-verification pipeline removes tests judged irrelevant to the task or too broad. Reading boundary: Historical Pass@1 result with augmented problem statements, requirements and interface; no present-day ranking.

Sources: [360]

Evidence: Reviewed-work atlas - Task construction and evaluation: SWE-bench Multimodal: Do AI Systems Generalize to Visual Software Domains?. The authors report an average of ten hours of manual environment construction per repository. Table 3 reports SWE-agent M with GPT-4o resolving 12.2% of task instances. Human participants manually inspect and categorize all images using categories derived from a random 50-image sample. The limitations identify expansion beyond JavaScript as future work rather than measured coverage. Appendix B.2 describes running tests five consecutive times and filtering inconsistent task instances. Reading boundary: The body describes 517 test tasks and specifies gpt-4o-2024-08-06; total collection counts conflict elsewhere in the source.

Sources: [359]

Evidence: Reviewed-work atlas - Task construction and evaluation: SWE-bench: Can Language Models Resolve Real-World GitHub Issues?. The authors manually create per-release executable contexts by examining repository source and documentation. The authors state that SWE-bench collection, evaluation and experiments do not use crowdsourcing or recruited human task workers. Reading boundary: This manual configuration supports the automated collection/evaluation pipeline. It is not crowdsourced task annotation or an external supplier contribution.

Sources: [466]

Evidence: Reviewed-work atlas - Task construction and evaluation: ScienceAgentBench: Toward Rigorous Assessment of Language Agents for Data-Driven Scientific Discovery. Nine subject-matter experts validate the tasks before a separate annotator execution-verification round. The authors select Python programs because their annotators are not familiar with R, Stata or Matlab. Table 3 reports Claude 3.5 Sonnet Self-Debug success of 32.4% without expert knowledge and 34.3% with it. Success Rate is zero when a generated program fails execution or does not save the required output. Reading boundary: 102 task goals; SR differs from valid-execution rate and rubric score; historical model/framework comparison.

Sources: [353]

Evidence: Reviewed-work atlas - Task construction and evaluation: ScienceWorld: Is your Agent Smarter than a 5th Grader?. The study reports all agent results using easy-mode simplifications and provides gold trajectories from thirty hand-coded oracle agents representing canonical solution methods. ScienceWorld tasks combine method-agnostic required goals with two to fifteen optional reward-shaping subgoals; task scores are normalized between zero and one. ScienceWorld is an object-oriented interactive text simulator implemented in Scala with a Python interface, with explicit object, action and simulation-engine abstractions. Within each ScienceWorld subtask, generated variations are split 50% training, 25% development and 25% test, with critical unseen variations placed in development and test.

Sources: [235]

Evidence: Reviewed-work atlas - Task construction and evaluation: ShieldAgent: Shielding Agents via Verifiable Safety Policy Reasoning. At inference,the system extracts the invoked action and retrieves corresponding action-rule circuits for verification. Circuit weights are learned from safety-labeled real-world data or simulated pseudo-learning. The policy-construction process extracts and refines rules to make them concrete,accurate and atomic. The decision thresholds the probability difference between invoking an action and taking no action,with an adjustable safety threshold. Reading boundary: A shielding plan assigns Boolean state-predicate values through tools/operations; correctness depends on those assignments.

Sources: [382]

Evidence: Reviewed-work atlas - Task construction and evaluation: SkillsBench: Benchmarking How Well Agent Skills Work Across Diverse Tasks. The authors say observed skill gains may partly reflect added context and call for length-matched controls. The complete task list contains 86 tasks, with two exclusions leaving 84 evaluated tasks. Table 3 reports Gemini CLI with Gemini 3 Flash at 31.3% without Skills and 48.7% with curated Skills. The quality criteria reject tasks judged solvable without procedural guidance. The task-quality rules require deterministic programmatic verification rather than an LLM judge. Reading boundary: 84-task evaluation, five trials per task; result belongs to the model-harness pair.

Sources: [354]

Evidence: Reviewed-work atlas - Task construction and evaluation: Terminal-Bench: Benchmarking Agents on Hard, Realistic Tasks in Command Line Interfaces. During auditing, an author manually inspects the exploit agent trajectories regardless of pass or failure. The paper identifies internet access as a source of changing dependencies and potential oracle-solution leakage. Each task has an oracle solution script used to demonstrate that its tests can pass. The reported construction process selects 89 Terminal-Bench 2.0 tasks from 229 contributions by 93 contributors. The experiments report 32,155 single-task trials, with at least five benchmark runs per supported model-agent combination.

Sources: [362]

Evidence: Reviewed-work atlas - Task construction and evaluation: The FineWeb Datasets: Decanting the Web for the Finest Text Data at Scale. The paper’s controlled data ablation models have 1.71 billion parameters. Reading boundary: They are trained on equal token budgets, commonly 28B or 350B, and compared on selected academic benchmarks. The conclusion (p.10) notes scale and unaligned benchmark-only evaluation limitations.

Sources: [467]

Evidence: Reviewed-work atlas - Task construction and evaluation: TheAgentCompany: Benchmarking LLM Agents on Consequential Real World Tasks. Claude 3.5 Sonnet with the common OpenHands CodeAct scaffold achieves 24.0% full task success. The authors report approximately 3,000 person-hours from 20 task creators over two months. Full completion is a binary score requiring every checkpoint to pass. The authors state that resource limits prevented a human-professional performance comparison in this iteration. Reading boundary: 175 tasks; this is full completion, not the 34.4% partial-credit aggregate. Simulated colleagues and evaluators use a fixed Claude backbone.

Sources: [318]

Evidence: Reviewed-work atlas - Task construction and evaluation: VerifiAgent: a Unified Verification Agent in Language Model Reasoning. The framework returns a Correct/Incorrect result and can provide an error reason and a possible revision method. VerifiAgent uses frozen LLMs and does not require a verifier training process. Meta verification rewrites a solution into known conditions,the final objective and explicit logical steps. Adaptive verification selects external tools,solves the problem and compares resulting answers against the original solution. Reading boundary: A separate confidence score is described but its mathematical derivation is outside this extraction. Feedback incorporates tool observations when requested by the prompt.

Sources: [384]

Evidence: Reviewed-work atlas - Task construction and evaluation: Video-MME: The First-Ever Comprehensive Evaluation Benchmark of Multi-modal LLMs in Video Analysis. Gemini 1.5 Pro scores 75.7% without subtitles and 81.6% with subtitles on the overall Video-MME evaluation. Authors annotate three four-option questions for each of 900 videos, producing 2,700 question-answer pairs. Gemini 1.5 Pro receives all subtitles while other evaluated models use subtitles corresponding to sampled frames. A different annotator reviews each question-answer pair before model-based question-only filtering and revision. Reading boundary: 2,700 questions; the model has denser video-frame sampling and full subtitles under the reported settings. This is not an equal-input causal comparison to other models.

Sources: [365]

Evidence: Reviewed-work atlas - Task construction and evaluation: VisualWebArena: Evaluating Multimodal Agents on Realistic Visual Web Tasks. The VisualWebArena human evaluation uses seven college students familiar with commercial site analogues; participants who helped create tasks were not assigned their own tasks. VisualWebArena tasks and reward functions were curated by six graduate-student coauthors from intent templates; the paper reports 314 templates and includes 46 unachievable tasks. VisualWebArena reward primitives combine exact/inclusion/exclusion string checks, LLM semantic matching, VLM question answering, image similarity and final-webpage-state evaluation. VisualWebArena baseline settings vary observation budgets: the study generally uses 1280-by-2048 viewports and 3,840 text tokens, but shorter-context models use 1280-by-720 and 640 tokens.

Sources: [238]

Evidence: Reviewed-work atlas - Task construction and evaluation: WebArena: A Realistic Web Environment for Building Autonomous Agents. Information-seeking evaluation uses exact-match, required-key-concept and GPT-3.5-turbo-0613 fuzzy-match functions; navigation/content evaluation checks relevant website states programmatically. Reading boundary: Functional evaluation is not uniformly model-free, and information-answer scoring emphasizes key-concept recall.

Sources: [64]

Evidence: Reviewed-work atlas - Task construction and evaluation: WebShop: Towards Scalable Real-World Web Interaction with Grounded Language Agents. WebShop instructions are written by human annotators from target-product attributes, options and price constraints; reward compares the selected product against these fields. The WebShop paper divides 12,087 instructions into an iid train/development/test split of 10,587, 1,000 and 500 instructions. In the pinned WebShop study, human scores are collected in HTML mode while models are trained and evaluated in simplified text mode. WebShop manual reward verification finds that automatic exact matching can over-penalize lexically similar or synonymous product attributes compared with human re-scoring.

Sources: [239]

Evidence: Reviewed-work atlas - Task construction and evaluation: World of Bits: An Open-Domain Platform for Web-Based Agents. In FormWoB, an unseen HTTP request terminates the episode with zero reward. The WoB agent observes rendered pixels, localized DOM elements and a scalar reward, and acts through keyboard or pointer events. MiniWoB comprises 100 web tasks with manually constructed reward functions. QAWoB contains 11,650 queries instantiated from 521 templates. Reading boundary: Proxy records demonstration HTTP requests/responses; reward otherwise measures the fraction of request key-value pairs matching demonstrations. This is an offline approximation, not a live-site task success guarantee.

Sources: [385]

Evidence: Reviewed-work atlas - Task construction and evaluation: τ-bench: A Benchmark for Tool-Agent-User Interaction in Real-World Domains. τ-bench combines manually designed schemas, APIs and policies with GPT-4-generated data-sampling code, human code refinement, and manually annotated tasks iteratively checked with agent runs. τ-bench agents interact with database APIs and a simulated user under a domain-specific policy; database transitions are deterministic Python functions. τ-bench defines pass-hat-k as the probability that all k independent trials succeed, averaged across tasks, whereas pass@k measures at least one successful trial. The τ-bench rule-based reward checks the final database and required output strings, but the paper notes that a positive reward can still miss policy violations such as absent user confirmation.

Sources: [236]

Evidence: Reviewed-work atlas - Training systems and orchestration: HybridFlow: A Flexible and Efficient RLHF Framework. The single controller passes data futures between roles, while required output data is transferred directly between GPUs according to parallel ranks. Although ResourcePool supports parallel execution of colocated roles, HybridFlow generally uses sequential execution to avoid contention or out-of-memory failures. HybridFlow's ResourcePool virtualizes GPU sets; models sharing a pool are colocated, while different pool instances map to distinct GPU sets. HybridFlow attaches collect/distribute transfer protocols to model operations so data can be reshaped between models with different parallelism layouts. Reading boundary: The example is actor generation to critic inference; actual transfer and scheduling behavior depends on the chosen protocols.

Sources: [393]

Evidence: Reviewed-work atlas - Training systems and orchestration: OpenRLHF: An Easy-to-use, Scalable and High-performance RLHF Framework. The selected OpenRLHF paper limits its support scope to language models and states that vision-language or other multimodal architectures are not supported. OpenRLHF uses Ray to schedule separate response-generation and model-training roles and manage their workflow and data flow. OpenRLHF uses ring attention for sequence parallelism, distributing long-sequence attention computation across GPUs. The described pipeline uses vLLM for rollouts and DeepSpeed for actor/value training, transferring model slices between training and rollout engines. Reading boundary: This is a dated limitation of the pinned version, not a live audit of current source code; Ray/vLLM/DeepSpeed updates may also require compatibility work.

Sources: [397]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: AutoLibra: Agent Metric Induction from Open-Ended Human Feedback. AutoLibra turns open-ended feedback into a metric-and-judge pipeline. The inspected v3 uses 197 CoGym end-user trajectories with feedback and paper-author experts elsewhere; five authors act as expert annotators. Sotopia, WebArena and WebVoyager each contribute 100 GPT-4-based trajectories, with 20% held out for the Section 4 analysis. GPT-4o grounds feedback into signed behavioral aspects, o3-mini high clusters those aspects, and o3-mini medium rates trajectories +1, −1 or N/A against definitions and positive/negative examples.

Sources: [406]

Evidence: Study result - AutoLibra: Agent Metric Induction from Open-Ended Human Feedback. The human-alignment check samples 40 instances per validated step and task for binary judgments of complete correctness. Table 1 reports averages across five environments of 0.95 for grounding, 0.92 for LLM judging and 0.90 for meta-evaluation. These are step-specific validation summaries. Behavior clustering itself was not directly manually validated because reviewing more than 400 aspects was considered too costly.

Sources: [406]

Analysis: Study limitations and buyer implications - AutoLibra: Agent Metric Induction from Open-Ended Human Feedback. For a buyer, the deliverable is an induced rubric and trajectory judge whose intermediate transformations need their own checks. The demonstrated protocol collects one feedback element per complete text-rendered trajectory. Live or direct step feedback, generated programmatic evaluators and dense-reward RL remain future directions. The validation figures therefore cannot be transferred to those proposed products or read as an end-to-end accuracy guarantee for every induced metric.

Sources: [406]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: Aya Dataset: An Open-Access Collection for Multilingual Instruction Tuning. The inspected Aya v1 describes a sequence of original contribution, re-annotation and annotation-feedback tasks. Original examples receive review during re-annotation, and the resulting re-annotations receive feedback. Contributor leaderboard quality averages reviewer ratings. Inclusion also has distinct rules: all original annotations enter, while re-annotations need a summed prompt/completion character-level Levenshtein distance of at least five; a language needs at least 50 contributions.

Sources: [407]

Evidence: Study result - Aya Dataset: An Open-Access Collection for Multilingual Instruction Tuning. The paper reports 204,114 prompt/completion instances in 65 languages: 138,844 original annotations and 65,270 re-annotations. Its resource grouping is 22 high-resource, 12 mid-resource and 31 low-resource languages. These are statistics of the dataset described by that exact paper, rather than a count independently recomputed from a current downloadable artifact. Original contributions and revised versions remain distinguishable components of the total.

Sources: [407]

Analysis: Study limitations and buyer implications - Aya Dataset: An Open-Access Collection for Multilingual Instruction Tuning. Multilingual breadth does not establish equal validation depth in each language. The authors identify contributor concentration in some languages, no dedicated toxic/offensive-speech flags and no language-relabeling component; peer review does not guarantee removal of every unsafe or misclassified example. A proposed purchase should inspect language-specific contributor concentration and error samples. The paper review adds one reviewed work here without independently adding another inspected dataset family or implying a named commercial supplier.

Sources: [407]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: CrowdAgent: Multi-Agent Managed Multi-Source Annotation System. CrowdAgent combines cheap model annotation, small-model denoising and human routing. Core-Set selection sends low-confidence, diverse cases to humans, while budget, round and confidence conditions govern stopping. A hidden golden set informs the QA agent’s Bayesian confusion-matrix estimates; the source says these labels are neither exposed to annotators nor supplied as in-context examples. Difficult residual cases are flagged for final human verification.

Sources: [408]

Evidence: Study result - CrowdAgent: Multi-Agent Managed Multi-Source Annotation System. The main table places CrowdAgent above its listed baselines on six multimodal classification tasks at fixed human-label proportions: 5% on MM-IMDb and COV-CTR, and 15% on the three CrisisMMD subtasks and V-SNLI. The matched quantity is the human annotation proportion. It is not a controlled equality of total operating cost, model computation or all system-selection effort; appendix training and budget details were not fully examined in this bounded review.

Sources: [408]

Analysis: Study limitations and buyer implications - CrowdAgent: Multi-Agent Managed Multi-Source Annotation System. A buyer can use this design to ask how uncertain cases reach people and how hidden checks remain hidden. Confidence-threshold convergence is an internal stopping condition, rather than proof of error-free output. The authors acknowledge residual errors and dependence on underlying models. Acceptance should retain independent error inspection after convergence and a separately stated total-cost boundary before any efficiency claim is adopted.

Sources: [408]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: CrowdTruth 2.0: Quality Metrics for Crowdsourcing with Disagreement. CrowdTruth 2.0 represents a worker response as a binary annotation vector. Closed tasks share a predefined answer space; an open task instead builds each media unit’s answer space from the workers’ unique keywords. Its worker, media-unit and annotation scores are mutually dependent, start at one and are repeatedly recalculated until total variation falls below a selected threshold, using disagreement-weighted cosine agreement.

Sources: [409]

Evidence: Study result - CrowdTruth 2.0: Quality Metrics for Crowdsourcing with Disagreement. The worker-quality definition multiplies worker-worker agreement by worker-media-unit agreement. Peer consistency and consistency with the aggregate of other workers both affect the score. The inspected paper supplies this operational definition rather than a new controlled accuracy improvement. In open-ended tasks, annotation quality cannot be estimated across multiple media units and is set to one; the model therefore has different information in open and closed settings.

Sources: [409]

Analysis: Study limitations and buyer implications - CrowdTruth 2.0: Quality Metrics for Crowdsourcing with Disagreement. The useful comparison is between assumptions about disagreement. A low consistency score can prompt examination of the worker, the item or the answer space; the formula alone cannot decide which is defective. Further comparative validation across tasks remains future work in this source. Buyers should test whether a proposed weighting rule preserves intended minority interpretations and improves independently checked outcomes before using it to exclude contributors or certify labels.

Sources: [409]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: A Data-Driven Analysis of Workers' Earnings on Amazon Mechanical Turk. This earnings study uses plugin logs from September 2014 through January 2017: 3,808,020 HIT records from 2,676 workers before duration-outlier removal, and 3,471,580 HITs from 2,666 workers afterward. Zero-reward qualification tasks remain included. Its accounting compares reward over accept-to-submit intervals with temporal clustering at D=0 and D=1 minute to address overlapping queued work and between-task time; returned HITs contribute zero reward.

Sources: [410]

Evidence: Study result - A Data-Driven Analysis of Workers' Earnings on Amazon Mechanical Turk. For the filtered data, Table 1 reports median work-unit hourly rates of $2.54 per HIT, $3.18 per D=0 cluster and $1.77 per D=1-minute cluster. Their denominators are respectively 3,471,580 HITs, 2,560,066 clusters and 635,198 clusters. These are medians across task or cluster units, not a median across workers. They are historical study figures and do not describe current compensation at any supplier in this report.

Sources: [410]

Analysis: Study limitations and buyer implications - A Data-Driven Analysis of Workers' Earnings on Amazon Mechanical Turk. The operational lesson is to expose the time denominator, including unpaid qualification, returned work and between-task intervals where the project records them. Plugin selection, unknown demographics and script use limit population inference, while elapsed intervals need not equal active effort. Associations between work patterns and earnings are not causal. Neither the historical rates nor a selected plugin sample establishes current worker welfare or a commercial service’s labor cost.

Sources: [410]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: Experts Rise Where LLMs Disagree: Using Cross-Model Disagreement to Target Expert Effort in LLM Codebook Revision for Large-Scale Annotation. Experts Rise Where LLMs Disagree prioritizes expert attention using normalized vote entropy from six model predictions and a vote-weighted mean by label across 6,595 unlabeled tutoring utterances. Disagreement is a routing signal, not a determination that any label is wrong. Two experts each supply rationales for 60 selected utterances; GPT 5.6 Sol uses the resulting 120 annotations to revise 24 codebook entries. Mean reported Rationale Labeling time is 169.0 minutes per expert.

Sources: [411]

Evidence: Study result - Experts Rise Where LLMs Disagree: Using Cross-Model Disagreement to Target Expert Effort in LLM Codebook Revision for Large-Scale Annotation. On the same 4,032 expert-consensus held-out utterances, Rationale Labeling reaches 64.9% accuracy and 0.658 weighted F1, compared with 57.8% and 0.583 for the final expert-only codebook. The summary averages eight alternative aggregation methods using one temperature-zero run per codebook from each of six models. Aggregators reuse predictions, so they are not independent trials; 6.1% multi-label references are reduced to the first recorded label.

Sources: [411]

Analysis: Study limitations and buyer implications - Experts Rise Where LLMs Disagree: Using Cross-Model Disagreement to Target Expert Effort in LLM Codebook Revision for Large-Scale Annotation. The result supports a scoped codebook-revision comparison against the chosen reference label. One longitudinal project, two experts, unequal workflow effort/exposure, differing target-label assignments and possible carryover prevent isolation of input format as the cause. Transcript errors were not systematically measured or corrected. A buyer should preserve selection rules, rationale time and held-out label conventions before expecting similar returns from expert disagreement review in another domain.

Sources: [411]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: Garbage In, Garbage Out? Do Machine Learning Application Papers in Social Computing Report Where Human-Labeled Training Data Comes From?. This reporting audit began with five students independently coding the same papers and weekly discussion of disagreements; the team leader decided unresolved cases. After schema changes, at least two team members independently re-examined each of the 164 papers and the team reconciled them again. The repeated examination documents how this audit established its own coded reporting reference rather than assuming an initial extraction was gold.

Sources: [412]

Evidence: Study result - Garbage In, Garbage Out? Do Machine Learning Application Papers in Social Computing Report Where Human-Labeled Training Data Comes From?. Within the 74 papers coded for original human annotation, Table 5 finds no original-annotator identity information in 18 (24.32%) and paper-author annotation in 22 (29.73%). Table 7 finds no formal-instruction information in 35 (47.30%), formal definitions/examples in 32 (43.24%), and only question text as instructions in seven (9.46%). These are categories of publication disclosure in the sampled literature.

Sources: [412]

Analysis: Study limitations and buyer implications - Garbage In, Garbage Out? Do Machine Learning Application Papers in Social Computing Report Where Human-Labeled Training Data Comes From?. The study audits what publications report, rather than observing the underlying labor process. Its Twitter-classification focus and mostly arXiv sampling limit transfer to other fields; it did not record actual agreement values or adjudication/reconciliation processes in those projects. The procurement implication is a request for missing evidence, not an inference that undocumented instruction, compensation or QA never occurred. Disclosure completeness and delivered label quality require different measurements.

Sources: [412]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: ChatGPT Outperforms Crowd-Workers for Text-Annotation Tasks. The inspected v2 compares the same codebook wording across trained political-science students, screened US MTurk workers and gpt-3.5-turbo. Model annotations were collected in March-May 2023, using a fresh chat and one tweet per query, with two runs at each temperature of 1 and 0.2. Crowd recruitment required Masters status, over 90% approval, at least 50 approved HITs, two workers per tweet and no worker labeling over 20% of a task’s tweets.

Sources: [413]

Evidence: Study result - ChatGPT Outperforms Crowd-Workers for Text-Annotation Tasks. Across the four study datasets, the paper reports ChatGPT accuracy about 25 percentage points above MTurk on average, defining accuracy against trained-human labels only where both trained annotators agreed. The difficult items with trained-rater disagreement are outside that gold denominator. Mean within-group agreement is about 56% for MTurk, 79% for trained annotators, 91% for ChatGPT at temperature 1 and 97% at 0.2.

Sources: [413]

Analysis: Study limitations and buyer implications - ChatGPT Outperforms Crowd-Workers for Text-Annotation Tasks. This is a dated, task-specific model-versus-recruitment comparison, not a universal replacement rule for annotation labor. Repeated model consistency does not establish truth or independence. The source records a relevance-task failure caused by missing prompt examples and leaves other languages and models for future evaluation. A buyer should inspect excluded disagreement cases and prompt sensitivity alongside the retained-set accuracy before deciding how much human review can be removed.

Sources: [413]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: HelpSteer: Multi-attribute Helpfulness Dataset for SteerLM. HelpSteer v1 independently rates each response on helpfulness, correctness, coherence, complexity and verbosity using a 0-4 Likert scale. It collects scalar attributes rather than pairwise preferences. The paper describes approximately 200 US-based annotators engaged through Scale AI, English screening, training ending in 35 sample responses, at least two human QA reviews per annotation, automated checks and later research-team QA. This documents a reported workflow rather than an independent supplier audit.

Sources: [414]

Evidence: Study result - HelpSteer: Multi-attribute Helpfulness Dataset for SteerLM. Within the final 37,120 annotated samples, Table 2 reports Pearson correlation with helpfulness of 0.8525 for correctness and 0.6348 for coherence. These are descriptive associations among the collected 0-4 ratings. They do not estimate how helpfulness would change if a buyer causally changed correctness or coherence, and they should not be substituted for an independently measured improvement from any individual QA stage.

Sources: [414]

Analysis: Study limitations and buyer implications - HelpSteer: Multi-attribute Helpfulness Dataset for SteerLM. A multi-attribute contract can retain distinctions hidden by a single preference label, but its scales still need task and population calibration. All annotations here concern English prompts/responses and all annotators are US-based; the authors state uncertainty about other cultural judgments and non-English gains. The exact recruitment statement can support the scoped role it names, without extending it to every HelpSteer release, sole artifact authorship or current provider performance.

Sources: [414]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: HelpSteer2: Open-source dataset for training top-performing reward models. HelpSteer2 v1 initially assigns three raters per response, adding two if the helpfulness range exceeds two points; it reports 3.41 annotators per sample and approximately 1,000 US-based annotators engaged through Scale AI. The pipeline retains the three most-agreeing ratings from up to five, adds QA and removes responses still exceeding the spread rule. About half of collected annotations are excluded overall, leaving 21,362 responses for 10,681 prompts.

Sources: [415]

Evidence: Study result - HelpSteer2: Open-source dataset for training top-performing reward models. Helpfulness quadratic-weighted Cohen κ rises from 0.465 initially to 0.791 after postprocessing, a multistage selection-and-QA comparison. The two-epoch regression reward models use batch size 128, validation-loss checkpoint selection and model-specific learning-rate search. Reported RewardBench overall accuracy is 88.8% for Llama 3 70B and 92.0% for Nemotron-4 340B: the mean of four categories over 2,985 tasks, excluding optional Prior Sets. These are unreproduced results of the selected version, not current ranks.

Sources: [415]

Analysis: Study limitations and buyer implications - HelpSteer2: Open-source dataset for training top-performing reward models. Higher retained-set agreement cannot be read as a randomized estimate of one QA intervention or evidence that excluded preferences were invalid. English-only, exclusively US-based annotation, possible cultural bias, uneven attribute combinations and compute-dependent tuning narrow transfer. Buyers should cost the discarded annotations, preserve disagreement reasons and validate a new target population. Conclusions from the large models do not automatically extend to smaller models.

Sources: [415]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: Inherent Disagreements in Human Textual Inferences. This study samples 100 short premise/hypothesis pairs from each of RTE2, SNLI, MNLI, JOCI and DNC, requesting 50 independent AMT ratings per pair on a −50 to 50 likelihood slider. Sentences have at most 20 words. After removing specified sparse/outlier workers, does-not-make-sense responses and pairs with fewer than 15 judgments, it retains 496 pairs averaging 39 labels each. Ratings are z-normalized within worker assignments.

Sources: [416]

Evidence: Study result - Inherent Disagreements in Human Textual Inferences. Using ten held-out judgments per pair and averaging ten random splits, the Gaussian-mixture analysis finds a second component with weight above 0.2 for about 20% of pairs; most pairs remain consistent with a single component. That is a model-based description of these collected, normalized judgments. It is not a universal estimate of linguistic ambiguity or an accuracy rate against an independently established single true interpretation.

Sources: [416]

Analysis: Study limitations and buyer implications - Inherent Disagreements in Human Textual Inferences. A buyer can preserve distributions for ambiguous tasks rather than force all cases into a single scale. The authors explicitly warn that normalized scores are not comparable across batches containing different pairs; the meaningful analysis compares raters within the same pair. A data pipeline that merges these normalized numbers across batches without the assignment structure would change the measurement. Recruitment and filtering rules also remain part of the population being described.

Sources: [416]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: LabelAId: Just-in-time AI Interventions for Improving Human Labeling Quality and Domain Knowledge in Crowdsourcing Systems. LabelAId combines domain-coded labeling functions in a Snorkel probabilistic label model, pretrains an FT-Transformer and fine-tunes on expert-validated city labels to infer image-label correctness. Its proof of concept concerns urban-accessibility imagery. The 34-person university/snowball study obtains consent and pays $30 per hour; two researchers independently validate all 3,574 participant labels, with a third resolving 74 disagreements to define the precision reference.

Sources: [417]

Evidence: Study result - LabelAId: Just-in-time AI Interventions for Improving Human Labeling Quality and Domain Knowledge in Crowdsourcing Systems. The between-subjects Project Sidewalk study reports higher overall precision in the intervention group by Mann-Whitney U ($p \leq 0.01$). Route-completion time does not differ significantly at $p=0.693$; reported means are 2,303.3 seconds for control and 2,801.4 for intervention. The nonsignificant test does not establish equal speed. The experiment and its label adjudication were not reproduced for this report.

Sources: [417]

Analysis: Study limitations and buyer implications - LabelAId: Just-in-time AI Interventions for Improving Human Labeling Quality and Domain Knowledge in Crowdsourcing Systems. The useful intervention target is a likely labeling mistake at the moment of work. The implementation cannot identify the exact cause and supplies neither explainability features nor global accuracy differences by label type. Its small university/snowball sample may differ from the wider user population. A buyer should separately test precision, time, error categories and participant representativeness rather than infer a general productivity gain from this one proof of concept.

Sources: [417]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: Pervasive Label Errors in Test Sets Destabilize Machine Learning Benchmarks. The inspected v4 first screens possible benchmark-label errors using confident learning with out-of-sample class probabilities and observed labels. Its noise model assumes class-conditional noise; datasets without test splits use whole-dataset cross-validation. Five MTurk workers then independently choose the given label, predicted label, both or neither. Fewer than three accepting the given label triggers the study's error rule; QuickDraw and Amazon Reviews use random samples of flagged cases, while the other flagged sets are fully checked.

Sources: [418]

Evidence: Study result - Pervasive Label Errors in Test Sets Destabilize Machine Learning Benchmarks. For ILSVRC 2012, unavailable ImageNet test labels are replaced by the 50,000-image validation set. Table 1 reports 5,440 screened and checked examples, of which 2,916 meet the five-worker rule, or 5.83% of that validation set. These validated issues include ambiguous categories. They are not all cases with a uniquely recoverable replacement label, and they do not give an error estimate for a newly purchased dataset.

Sources: [418]

Analysis: Study limitations and buyer implications - Pervasive Label Errors in Test Sets Destabilize Machine Learning Benchmarks. Gold-label review is itself a measurement process. The authors caution that even unanimous five-worker corrections can be wrong. Corrected-accuracy experiments remove unknown-label cases and change only the consensus alternative-label set, producing a different denominator from initial validated issues. Buyers should retain the screening candidate, uncertainty, adjudication and final usable correction as separate states rather than present every flagged example as a confirmed, correctable error.

Sources: [418]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: Efficient Data Labeling by Hierarchical Crowdsourcing with Large Language Models. LMCrowd starts with Llama2-7B, FLAN-T5-base, Zephyr-7B and Qwen-7B labels, then buys GPT-4 relabeling for uncertain distributions. The evaluated models use four-shot prompts, and the paid labels remain uncertain inputs rather than unquestioned gold. The main RTE, BoolQ and COPA experiments use majority voting, approximate query selection and two relabeled tasks per iteration; BoolQ is sampled to 1.5K cases.

Sources: [419]

Evidence: Study result - Efficient Data Labeling by Hierarchical Crowdsourcing with Large Language Models. The paper plots annotation accuracy against budget and describes its reported results as maximum achieved accuracy across configurations, rather than repeated-trial averages. Tariff comparisons count API or annotation charges, excluding model selection, GPT-4 prompt selection and worker-selection overhead. The human comparators are three university and six graduate students. Historical tariff assumptions are not current verified prices and do not establish compute-cost parity for local deployment.

Sources: [419]

Analysis: Study limitations and buyer implications - Efficient Data Labeling by Hierarchical Crowdsourcing with Large Language Models. The study can inform a staged-label purchasing rule, but its cost boundary cannot be used as a complete service quote. Wider domains, datasets and model choices remain future evaluation beyond the three tasks and limited generic-model set. A buyer should reproduce selection overhead, human qualifications and uncertainty handling within the intended workload, then compare accepted-unit costs under a common end-to-end scope.

Sources: [419]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: Quality Assured: Rethinking Annotation Strategies in Imaging AI. The inspected surgical-instrument segmentation study collects 57,648 instance masks on 4,050 unique laparoscopic frames, using 216 annotators and 34 QA workers at four unnamed annotation companies plus 708 MTurk workers. Masks are repeated annotation units, not distinct images. Its three instruction conditions contain 168 words/seven slides, 446 words/ten slides and 961 words/16 slides with pictures. Annotators and company QA workers see the same instructions.

Sources: [420]

Evidence: Study result - Quality Assured: Rethinking Annotation Strategies in Imaging AI. The researchers compare outputs before and after QA with Dice, normalized surface distance and severe-error counts. Under extended text or text-plus-picture instructions, two companies have no median-Dice change after QA and the other two have relative gains below 2%; the main figure describes larger gains from better instructions than additional QA in this project. Figure pixels were not separately inspected in this bounded review.

Sources: [420]

Analysis: Study limitations and buyer implications - Quality Assured: Rethinking Annotation Strategies in Imaging AI. QA headcount alone is an inadequate comparison when instructions and acceptance constructs differ. The reported effects are conditional on one safety-critical domain and these project conditions; costs can change elsewhere. Confidential company identities prevent any mapping to the named suppliers profiled here. The study cannot establish their service quality or working conditions, and it does not show that QA is generally unnecessary.

Sources: [420]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: RECODE-H: A Benchmark for Research Code Development with Interactive Human Feedback. RECODE-H uses 26 PhD-level researchers with relevant top-conference publications to review Gemini-2.5-Pro drafts of code comments, instructions and tests. Included research implementations must execute and require less than 24 GB GPU memory. At evaluation time GPT-o4-mini simulates an expert using execution results, canonical code and annotated comments. Its five feedback levels progress from logs through diagnosis and repair guidance to the correct code snippet.

Sources: [421]

Evidence: Study result - RECODE-H: A Benchmark for Research Code Development with Interactive Human Feedback. The seven-model study fixes temperature 0 and top-p 1, permits at most ten feedback rounds and three agent actions per turn, and reports correctness and task-solve gains with richer feedback. Those gains are conditional on the added information, including answer-code snippets at the highest level. MRR depends on the first test-correct turn; Recall@n counts tasks solved within n turns; CodeBLEU and CodeBERTScore compare to canonical implementations.

Sources: [421]

Analysis: Study limitations and buyer implications - RECODE-H: A Benchmark for Research Code Development with Interactive Human Feedback. Expert-reviewed task construction and live expert feedback are distinct provenance claims. The evaluated feedback is model-generated, and the conclusion leaves actual human-in-the-loop feedback and broader research stages for future work. Temperature zero is a decoding setting, not proof of deterministic remote responses. A buyer should specify what the feedback provider can see, whether it reveals solution material, and which task-success metric is being purchased before comparing assistance levels.

Sources: [421]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: Cheap and Fast - But is it Good? Evaluating Non-Expert Annotations for Natural Language Tasks. Across five selected NLP tasks, this study obtains ten independent annotations per item with multiple-choice or fixed-range numeric responses. Its temporal-order experiment deliberately narrows the original noun-and-verb, fourteen-relation problem to verb events and two relations. Expert interannotator-agreement figures are unavailable for that simplified task. The restriction changes the comparison that a headline expert-versus-crowd result might otherwise suggest.

Sources: [422]

Evidence: Study result - Cheap and Fast - But is it Good? Evaluating Non-Expert Annotations for Natural Language Tasks. On 462 TimeBank verb-event pairs restricted to strictly before versus strictly after, ten-label voting yields 0.94 agreement with dataset labels from 4,620 annotations. The cited 0.77 expert agreement comes from the broader task and is not a matched comparator. Separately, a unigram affect predictor trained on 100 headlines and tested on 900 reaches mean Pearson correlation 0.191 with ten-annotator-averaged non-expert training labels versus 0.122 with one expert, using five other experts as reference.

Sources: [422]

Analysis: Study limitations and buyer implications - Cheap and Fast - But is it Good? Evaluating Non-Expert Annotations for Natural Language Tasks. Redundancy, task simplification and reference construction explain the actionable scope. These results support testing pooled labels for similarly bounded tasks; they do not establish that ten general annotators outperform specialists on arbitrary work. A procurement comparison should hold the ontology and evaluation reference fixed and cost all repeated labels. The historical experiment is not a current provider or platform performance measurement.

Sources: [422]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: UltraFeedback: Boosting Language Models with Scaled AI Feedback. UltraFeedback v2 samples four different models per instruction from a 17-model pool, yielding 255,864 completions for 63,967 instructions. Family/size diversity and varied system principles are intended to reduce style-quality confounding. GPT-4 jointly scores each prompt’s four completions on 1-5 instruction-following, truthfulness, honesty and helpfulness rubrics with rationales; a separate tutor-style prompt creates an overall critique per completion.

Sources: [423]

Evidence: Study result - UltraFeedback: Boosting Language Models with Scaled AI Feedback. For a 400-comparison check-100 each from UltraFeedback, AlpacaEval, Evol-Instruct and UltraChat-three independent student judges give win/tie/lose labels. GPT-4 agreement averages 59.7% with individual judges and 68.6% with their majority, including ties. Agreement assesses consistency with these judgments rather than verified factual correctness. A later 266-pair evaluation uses a separate filtered denominator and should not be merged with this check.

Sources: [423]

Analysis: Study limitations and buyer implications - UltraFeedback: Boosting Language Models with Scaled AI Feedback. Rubric-rich synthetic feedback still needs independent calibration. The impact statement identifies answer-position, length and style biases that can cause inaccurate or unfair annotation and evaluation. Model diversity is an intended safeguard rather than a proof those biases disappear. Buyers should retain the joint-scoring context and test order/style perturbations; neither the label volume nor majority agreement establishes universal truthfulness or equivalence to independent human judgments.

Sources: [423]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: Who Annotates in NLP? A Large-scale Assessment of Human Annotation Reporting between 2018 and 2025. The inspected study extracts one structured record per annotation experiment using a 26-category taxonomy from keyword-selected 2018-2025 ACL-family main/Findings papers. The selected corpus has 1,603 papers and 2,667 tasks, separate from its human-adjudicated gold set. Gold construction compares two independent annotations, discusses disagreements and uses a third annotator for unresolved cases before evaluating extraction.

Sources: [424]

Evidence: Study result - Who Annotates in NLP? A Large-scale Assessment of Human Annotation Reporting between 2018 and 2025. For the final Gemini-3.1-Pro-extracted corpus, reported information appears for recruitment in 90.4% of tasks, expertise in 86.5% and item volume in 86.0%, compared with training in 18.7%, language proficiency in 24.0% and released guidelines in 34.1%. These percentages describe automated extraction of publication reporting. Their denominator is annotation tasks in the selected corpus, rather than workers, suppliers or all ACL research.

Sources: [424]

Analysis: Study limitations and buyer implications - Who Annotates in NLP? A Large-scale Assessment of Human Annotation Reporting between 2018 and 2025. Documentation omissions are prompts for follow-up, not findings that the underlying practices were absent. Keyword selection is not fully representative, model extraction can misclassify papers or categories, and the released records lack calibrated per-instance confidence. The study makes disclosure comparison useful while preserving uncertainty about the actual work. Its reconciliation design also illustrates why an independently established reference should precede scoring a research extraction system.

Sources: [424]

Evidence: Reviewed-work atlas - Annotation, feedback and evidence design: WildChat: 1M ChatGPT Interaction Logs in the Wild. The inspected WildChat v1 describes public GPT-3.5-Turbo/GPT-4 chat services collected from 9 April 2023 to 1 May 2024. Users must accept a collection/use/sharing agreement and a second confirmation before opening the chat interface. The authors report multilingual PII removal using Presidio, spaCy and custom rules, followed by GeoLite2 country/state mapping and hashed IP release. This is a description of their process, not an independently tested de-identification guarantee.

Sources: [425]

Evidence: Study result - WildChat: 1M ChatGPT Interaction Logs in the Wild. The exact v1 PDF contains an unresolved count discrepancy: its public-release statement gives 1,039,785 conversations after reserving 14,743 for WildBench, while the following Basic Statistics paragraph gives 1,009,245. This report preserves both statements instead of choosing a canonical artifact count. Neither figure has been recomputed from corpus bytes here, and this paper review does not independently add a dataset-family inspection.

Sources: [425]

Analysis: Study limitations and buyer implications - WildChat: 1M ChatGPT Interaction Logs in the Wild. Consent gates and filtering do not establish population representativeness or zero privacy risk. The authors warn that hashed IPs and request headers can still link conversations from the same user; Hugging Face hosting and subreddit dissemination can favor IT communities, while anonymous access may select more toxic discourse. Buyers should inspect the actual release and linkage risk under their use case rather than treat conversational realism, anonymization or a headline million count as a certification.

Sources: [425]

5. Provider dossiers: offerings, delivery, differentiation and limits

Method: Dossier format: offering and scope; disclosed delivery and operating model; buyer assessment and limits. Every qualifying supplier in the approved input is covered. First-party marketing is evidence of what is offered or reported, not an independently observed delivery. A named case is preserved at its actual attribution, task and date. A dossier with no named customer artifact established here is not evidence that the supplier has never delivered one. Unrecorded language, modality, security or commercial facets are unknown, not negative capabilities. Differentiation means a documented design or responsibility distinction, not a score for provider quality.

Evidence: A.Team - offering and scope. Its RL engineering offer includes graders, rubrics, harnesses and rollout infrastructure. A.Team lists golden trajectories, expert data and RLHF/RFT support within post-training pipeline work. A.Team offers senior engineers to build and validate training environments, tasks and evaluations.

Sources: [268]

Evidence: A.Team - disclosed delivery and operating model. A.Team offers hourly, contract-to-hire, ongoing and advisory builder engagements. Its RL page says builders work within customer access controls, reviews and governance.

Sources: [268]

Evidence: A.Team - source-specific boundaries. These are engagement models, not client prices, worker compensation amounts or evidence of completed named-artifact delivery. Provider disclosure; no security audit report, scope or project execution was independently inspected.

Sources: [268]

Analysis: A.Team - buyer assessment and unknowns. The useful comparison is engineering accountability: request a concrete environment, grader or harness milestone and clarify whether the buyer is purchasing individual time or a warranted deliverable. Customer access controls should appear in the project specification. Builder engagement models alone do not establish delivered data quality, a fixed completion price or current specialist availability.

Sources: [268]

Evidence: Abundant - offering and scope. Abundant lists coding, sciences, engineering, RSI, alignment and robotics as focus areas. Foundry offers to turn Fireworks customers’ own product data and workflows into RL environments. Abundant advertises creation of environments and datasets for reinforcement learning.

Sources: [182], [183]

Evidence: Abundant - disclosed delivery and operating model. Abundant says every Foundry task version receives human sign-off after automated and adversarial QA. Abundant says Foundry starts from customer product data including user sessions, tools and golden test cases. Abundant describes Oddish as tooling for trials, trace capture, scheduling and environment revision before human review.

Sources: [183], [184]

Evidence: Abundant - source-specific boundaries. Listed focus areas do not establish named customer work, linguistic coverage or worker headcount. The article separately describes baseline, adversarial and multi-agent stress tests; the execution of those checks was not independently audited.

Sources: [182], [183], [184]

Analysis: Abundant - buyer assessment and unknowns. The differentiating disclosed workflow starts from customer product traces and golden cases and closes with task-version sign-off. A pilot should inspect trace permissions, reset behavior and the recorded transition from automated stress tests to human acceptance. A list of scientific and coding focus areas does not establish task coverage or operational throughput in each domain.

Sources: [182], [183], [184]

Evidence: AfterQuery - offering and scope. AfterQuery offers human demonstrations across browser and desktop environments as computer-use trajectories. AfterQuery offers SFT prompt-response pairs and reasoning traces for complex tasks. AfterQuery offers expert-designed prompts and grading frameworks for reasoning and code generation.

Sources: [185]

Evidence: AfterQuery - disclosed delivery and operating model. AfterQuery attributes office-task input for NVIDIA Nemotron 3 Ultra to its own delivery account. The linked NVIDIA report was not independently retrieved; this does not establish GDPval authorship or a share of all training data. AfterQuery’s website privacy policy excludes personal-information processing performed as a processor or service provider for customers. AfterQuery’s terms place service fees in separate agreements or order forms.

Sources: [186], [187], [188]

Evidence: AfterQuery - source-specific boundaries. Evidence is AfterQuery’s first-party delivery account, including its quoted NVIDIA-report passage; the linked NVIDIA PDF was not retrieved or independently read. It attributes office-task input, not GDPval authorship, all training data or model performance. The policy’s general security statement does not establish customer-processing contractual safeguards, certifications or specific worker protections.

Sources: [185], [186], [187], [188]

Analysis: AfterQuery - buyer assessment and unknowns. The buyer can distinguish demonstrations, prompt-response data and grading frameworks as separate outputs. The named office-task account is useful for requesting an artifact-specific sample, but its first-party attribution cannot be extended to all NVIDIA data or GDPval authorship. Obtain the customer-processing agreement and project order because the general website policy and terms leave those details elsewhere.

Sources: [185], [186], [187], [188]

Evidence: Alegion / SanctifAI data services - offering and scope. Alegion offers data collection, annotation and quality control through managed workforce experts.

Sources: [92]

Evidence: Alegion / SanctifAI data services - disclosed delivery and operating model. Alegion’s official page describes Alegion as a division of SanctifAI. Alegion describes training and qualifying project annotators using ground-truth annotations before enrollment. Alegion describes a workforce-partner network supported by its project managers, data engineers and QA teams. Alegion describes QA review of submitted annotations with client acceptance or feedback. Alegion reports that Sportlogiq used its end-to-end managed service to scale annotation for a player-tracking system.

Sources: [92], [93]

Evidence: Alegion / SanctifAI data services - source-specific boundaries. Provider business-structure disclosure; legal ownership and corporate registry have not been independently checked. The same page also uses rebrand wording, so no separate SanctifAI supplier is counted. Access-to-workforce language is not a current paid-active count or assignment total; the source’s large pool figure is not adopted.

Sources: [92], [93]

Analysis: Alegion / SanctifAI data services - buyer assessment and unknowns. The disclosed model joins workforce partners with project management and QA. For a comparable bid, freeze the project ground truth, qualification gate, escalation path and client acceptance rule. The Sportlogiq account supports a scoped annotation case, not an independently verified accuracy gain or a current contract. Treat SanctifAI identity wording as one supplier boundary rather than an additional market participant.

Sources: [92], [93]

Evidence: Alinia AI - offering and scope. Alinia advertises adversarial evaluation against a customer’s policy red lines. Alinia offers policy judges trained on internal and external policies to check AI outputs.

Sources: [271]

Evidence: Alinia AI - disclosed delivery and operating model. Its engagement process compares judge decisions with customer experts on real data. Alinia describes each engagement as a forward deployed legal and engineering project inside the customer environment. The website privacy policy names Alinia AI, Inc. as data controller.

Sources: [271], [272]

Evidence: Alinia AI - source-specific boundaries. This describes a proposed validation stage; it is not independent evidence of accuracy, legal compliance or expert sign-off for a particular deployment. Website-controller identity does not prove equity ownership or recertify every historical alias. The policy’s website scope does not replace a customer processing agreement.

Sources: [271], [272]

Analysis: Alinia AI - buyer assessment and unknowns. This is a policy-judge and integrated validation proposition. Require a customer-specific policy-to-test mapping and a blinded expert comparison before using judge outputs for operational decisions. The website controller identity is not a customer-data protection agreement, and an engagement description involving legal expertise is not a finding that a deployment complies with law.

Sources: [271], [272]

Evidence: Appen - offering and scope. Appen offers repository tasks with verified patches, debugging traces, code preference pairs, and test-generation data. Appen offers expert alignment data, agentic workflows, multimodal data, physical-AI data, model evaluation, and research services.

Sources: [469]

Evidence: Appen - disclosed delivery and operating model. Appen describes project-level agreement metrics, continuous gold questions, and adjudication of disagreement. Appen's FY2025 report describes a global crowd of more than one million experts and identifies CrowdGen as a platform. The 2025 annual report identifies Appen Limited as the parent entity. Appen says its model-evaluation work is run by teams separate from the training-data producers. Appen's privacy statement permits service-provider processing and describes access controls and confidentiality duties for contractors. Appen markets consent records, licensing terms, and data lineage as delivery documentation. Appen reports FY2025 consolidated revenue from customer contracts of USD 230.774 million. Appen's security page describes SOC 2 Type II attestation, a HIPAA-specific solution, and named secure-facility options. Appen reports FY2025 revenue of USD 127.874 million for Appen Global and USD 102.900 million for Appen China.

Sources: [469], [470], [471], [472]

Evidence: Appen - source-specific boundaries. Crowd/network scope; no activity window, paid-contributor denominator, or paid assignment count is established. Report footnotes on geography/language need retention if those counts are used. Published privacy terms; the actual project subcontractor list, consent evidence, and contract-specific IP ownership were not inspected.

Sources: [469], [470], [471], [472]

Analysis: Appen - buyer assessment and unknowns. The breadth of disclosed modalities makes scope discipline central. A software-patch pilot and a physical-AI collection pilot should have separate acceptance units. Ask for evidence that the promised training/evaluation team separation and adjudication process operate on the proposed project. Group and geographic-segment revenue cannot identify the size or performance of expert generative-AI delivery.

Sources: [469], [470], [471], [472]

Evidence: APTO - offering and scope. APTO offers commissioned solutions from data collection through model and system development. APTO offers its harBest platform with crowd-worker and in-house collection and annotation. Its homepage lists image, video, LiDAR, natural-language and audio data formats. APTO sells ready-made datasets in image/video, voice and natural-language categories.

Sources: [273]

Evidence: APTO - disclosed delivery and operating model. APTO's official company-information page names APTO, Inc. and a January 20, 2020 founding date.

Sources: [274], [452]

Evidence: APTO - source-specific boundaries. The English privacy page separately uses APTO Corporation; these official renderings are retained without inventing a name-change or ownership event. Listed domains are advertised formats and applications, not delivered-language coverage or independently tested capability.

Sources: [273], [274], [452]

Analysis: APTO - buyer assessment and unknowns. The documented comparison has two purchase paths: ready-made data and commissioned collection-to-system work. Require separate version, rights and acceptance schedules for each. A broad modality menu supports asking for representative image, LiDAR or audio samples; it does not establish domain-specific expert qualifications or a named completed customer delivery in the inspected dossier.

Sources: [273], [274], [452]

Evidence: Aya Data - offering and scope. Aya Data offers expert-annotator feedback for conversational-model evaluation and domain-specific AI annotation. Aya Data describes using human preference rankings to build reward models.

Sources: [97]

Evidence: Aya Data - disclosed delivery and operating model. Aya Data’s homepage describes measuring inter-annotator agreement on every delivery. Aya Data reports labeling aorta images for Cydar Medical and expanding the engagement to thrombus and stent labeling. Aya Data’s RLHF page describes stable contracts and protection from harmful content as worker-wellbeing practices.

Sources: [95], [96], [97]

Evidence: Aya Data - source-specific boundaries. Process assertion only; no measured agreement value, universal achieved quality score or independent audit is established. Provider-authored named case with no engagement calendar window or public dataset release identity. Clinical-outcome and diagnostic-accuracy claims are omitted.

Sources: [95], [96], [97]

Analysis: Aya Data - buyer assessment and unknowns. The Cydar account offers a concrete medical-image annotation case, while the conversational-feedback offering is a different task type. Do not transfer medical-image experience into a claim of superior preference data. A pilot should inspect how agreement is calculated, how difficult cases are retained and how harmful-content protection is implemented for the actual conversational task.

Sources: [95], [96], [97]

Evidence: BasicAI - offering and scope. BasicAI offers human-powered training data to fine-tune foundational language models. BasicAI’s RLHF service offers human-preference datasets formed by ranking multiple SFT-model responses.

Sources: [99]

Evidence: BasicAI - disclosed delivery and operating model. BasicAI's security page requires every employee to sign a confidentiality agreement that survives employment. BasicAI states each labeling project undergoes multi-level inspections and validations. BasicAI states its labeling service maintains specialist teams with industry-specific knowledge rather than using crowdsourcing.

Sources: [98], [100]

Evidence: BasicAI - source-specific boundaries. Employee policy disclosure, not proof of a particular contractor's terms or independent certification. The adjacent 99%+ headline is not adopted as a measured quality rating or universal guarantee.

Sources: [98], [99], [100]

Analysis: BasicAI - buyer assessment and unknowns. The stated specialist-team model differs from open participant access, but the buyer still needs project-specific staffing and review evidence. Request independent raw judgments before ranking aggregation, the definition of each inspection level and an escalation sample. A confidentiality agreement is one control; it does not by itself establish access isolation, secure deletion or regulatory scope.

Sources: [98], [99], [100]

Evidence: Bespoke Labs - offering and scope. Bespoke advertises automated prompt and policy optimization using GEPA. Bespoke Labs offers RL environments and infrastructure for long-horizon agent training. Its environment offering includes company-scale simulations with real codebases and microservices.

Sources: [275]

Evidence: Bespoke Labs - disclosed delivery and operating model. Bespoke invites domain experts to build RL environments and data pipelines. Its November 5, 2026 website terms reserve product, customer-service and data-acquisition engagements to separate agreements.

Sources: [275], [276]

Evidence: Bespoke Labs - source-specific boundaries. A product capability description; no comparative accuracy or speed claim is carried forward. An expert invitation does not establish paid project availability, participant counts, rates or contributor agreements.

Sources: [275], [276]

Analysis: Bespoke Labs - buyer assessment and unknowns. The comparison centers on long-horizon environment engineering and optimization infrastructure. Test a resettable multi-service workflow with known failure states and independently reviewed rewards. Expert intake is a recruitment route, not a count of paid contributors. The separately contracted customer and data-acquisition services need explicit rights, maintenance and delivery obligations.

Sources: [275], [276]

Evidence: Centific - offering and scope. Centific's OneForma page describes connecting model labs and enterprises with vetted contributors and domain experts for data, human feedback and model evaluation. Centific offers human preference signals suitable for training and refining reward models.

Sources: [102], [103]

Evidence: Centific - disclosed delivery and operating model. OneForma describes conflict-resolution and consensus review workflows supported by automated labeling-error checks. Centific's OneForma description states contributors are screened, identity-verified and continuously evaluated through quality checks. Centific describes trained evaluators ranking model outputs against nuanced criteria in its preference-optimization service. OneForma describes access-controlled environments and encrypted workflows for sensitive data.

Sources: [102], [103]

Evidence: Centific - source-specific boundaries. Provider process claim; no paid-active population or independent screening audit is inferred. Self-reported controls, not an independently inspected certification report.

Sources: [102], [103]

Analysis: Centific - buyer assessment and unknowns. OneForma's screening, consensus and automated checks should be evaluated as a sequence rather than one quality score. Request the domain-language qualification test, conflict-resolution rubric and accepted-unit audit trail. Access-controlled facilities are a disclosed option, not proof that the quoted delivery will use them. No public pool description establishes paid availability for a specific project.

Sources: [102], [103]

Evidence: CloudFactory - offering and scope. CloudFactory's Accelerated Annotation combines a skilled workforce and ML automation for computer-vision data labeling.

Sources: [21]

Evidence: CloudFactory - disclosed delivery and operating model. CloudFactory reports delivering a first training dataset for an unnamed global AgTech company's computer-vision model. CloudFactory's AgTech case reports quality checks on all labeled data in that engagement. CloudFactory states its optional Endpoint offering uses centrally managed company-provisioned workstations with disk encryption. CloudFactory describes Network Security as included in each client engagement, with Endpoint Security offered as an additional tier.

Sources: [21], [22]

Evidence: CloudFactory - source-specific boundaries. The client remains unnamed. Timing is not dated to a calendar window, and comparative cost/speed claims are omitted. Project-specific provider disclosure; it does not establish an accuracy rate or a universal all-project guarantee.

Sources: [21], [22]

Analysis: CloudFactory - buyer assessment and unknowns. The reviewed case concerns computer-vision annotation, so it is most useful as a diligence reference for a similar labeling workflow. Confirm which controls are included in the quoted tier: the network baseline and optional managed endpoint are different promises. The unnamed AgTech case cannot establish current capacity, a generic model-performance gain or capability on unrelated expert preference tasks.

Sources: [21], [22]

Evidence: Cogito Tech - offering and scope. Cogito describes expert-verified prompt-response pairs and SME ratings of model responses for RLHF. Cogito Tech offers managed annotation across text, audio, image and video.

Sources: [323]

Evidence: Cogito Tech - disclosed delivery and operating model. Cogito offers customized annotation workflows with project-specific quality checks, labeling schemes and reviewer trees. Cogito’s data-labeling page describes a human workforce of subject-matter experts, quality controllers and annotators. Cogito’s official registration page identifies Cogito Tech LLC.

Sources: [323], [324]

Evidence: Cogito Tech - source-specific boundaries. Evidence is the exact saved official web.run extracted-page snapshot; origin HTML and live HTTP status were not exposed. No workforce size, pay, audit or project-level performance is inferred.

Sources: [323], [324]

Analysis: Cogito Tech - buyer assessment and unknowns. The disclosed distinction is a managed multimodal workforce with project-specific reviewer trees and expert response ratings. A pilot should inspect who authors guidelines, who reviews corrections and how a response becomes accepted. The pinned evidence is an official extracted-page snapshot, not an origin-HTML capture or live-status check. Website registration identifies an operator without resolving current ownership or project contracts.

Sources: [323], [324]

Evidence: Datacurve - offering and scope. Datacurve offers full traces of expert execution including tool calls, checks, pivots and recoveries. Datacurve offers prebuilt datasets described as curated, quality-reviewed and structured for customers’ training stacks. Datacurve offers durable RL environments with long horizons, realistic tools, domain-specific judgment and partial progress.

Sources: [196]

Evidence: Datacurve - disclosed delivery and operating model. Datacurve presents DeepSWE as its published software-engineering benchmark; this is an artifact-specific first-party attribution. DeepSWE states that its tasks are written from scratch rather than adapted from existing commits or pull requests. The DeepSWE site describes hand-written verifiers that test software behavior rather than implementation details.

Sources: [194], [195]

Evidence: Datacurve - source-specific boundaries. An owned evaluation artifact; no supplier-to-third-party-training edge is inferred. Task-creation method is self-reported. This does not prove model-training contamination is absent.

Sources: [194], [195], [196]

Analysis: Datacurve - buyer assessment and unknowns. Expert traces and durable environments should be compared using recovery behavior, verifier coverage and reproducibility. DeepSWE’s from-scratch task origin is a documented construction choice, not proof of no training overlap. Ask for a task sample that exercises realistic tools and partial progress, plus a negative case showing how the verifier rejects a superficially plausible but incorrect completion.

Sources: [194], [195], [196]

Evidence: DataForce by TransPerfect - offering and scope. DataForce offers RLHF services incorporating human evaluation feedback into LLM fine-tuning.

Sources: [25]

Evidence: DataForce by TransPerfect - disclosed delivery and operating model. DataForce reports generating scenarios and annotating safe/unsafe prompts for IBM’s Granite Guardian 3.0 dataset work. In the IBM case, DataForce describes jointly testing dataset groups and refining annotation protocols through feedback as model development progressed. DataForce identifies itself as part of TransPerfect and its platform as a proprietary TransPerfect solution. DataForce describes matching projects to domain experts/native speakers and using automated checks, multi-annotator consensus and expert adjudication. DataForce’s vendor privacy notice states vendors must sign the applicable data-processing agreement before handling EU personal data and process it only under TransPerfect instructions.

Sources: [24], [26], [27]

Evidence: DataForce by TransPerfect - source-specific boundaries. A named delivery contribution is explicitly claimed by the provider. No public dataset release identity, complete dataset size, or independent model-performance result is inferred. A provider process disclosure, not an audited quality rating or evidence of a specific active contributor count.

Sources: [24], [25], [26], [27]

Analysis: DataForce by TransPerfect - buyer assessment and unknowns. The IBM case supplies an artifact-specific safety-data reference and an iterative protocol-design account. A pilot should separate scenario creation, safe/unsafe labels and expert adjudication, preserving IBM-specific claims within that case. The vendor privacy notice addresses EU-personal-data processing obligations; it does not establish every downstream dataset's consent chain or a current operational audit.

Sources: [24], [25], [26], [27]

Evidence: Dataloop - offering and scope. Dataloop provides data curation, cleaning, versioning and management tools for unstructured data selection. Dataloop offers software that integrates human feedback into AI data pipelines. Its human-feedback page offers prebuilt reinforcement-learning workflows containing human and AI feedback nodes for RLHF/RLAIF.

Sources: [325]

Evidence: Dataloop - disclosed delivery and operating model. Dataloop lists AI Annotation Assistant, Consensus, Honeypot and JavaScript validations as annotation automation features. The July 2025 privacy notice names Dataloop Ltd. as controller for the processing activities described there.

Sources: [325], [326]

Evidence: Dataloop - source-specific boundaries. Available controls do not establish project-level annotation accuracy. This establishes platform functionality, not a managed human workforce.

Sources: [325], [326]

Analysis: Dataloop - buyer assessment and unknowns. Treat the offering as data-pipeline and human-feedback software rather than infer a managed annotator workforce. A buyer should test routing between human and AI feedback nodes, versioning and the relationship between consensus, honeypots and corrections. Software feature availability does not establish project-level accuracy. Clarify which party recruits experts and warrants the final accepted data.

Sources: [325], [326]

Evidence: Dataocean AI / Speechocean - offering and scope. Dataocean AI offers off-the-shelf datasets and customized data collection and labeling services. Dataocean AI offers speech-data collection and transcription using linguists and native speakers.

Sources: [355]

Evidence: Dataocean AI / Speechocean - disclosed delivery and operating model. The DOTS platform description offers automated pre-labeling, interactive assisted annotation, automated quality control and assisted quality inspection. The current people.speechocean.com login page is branded DATAOCEAN AI. Dataocean AI's March 31, 2024 website privacy policy reserves project and product personal-data rules to the corresponding services or products.

Sources: [355], [356], [357]

Evidence: Dataocean AI / Speechocean - source-specific boundaries. Available software controls do not establish actual delivered accuracy or certification. No catalog count, customer count, delivered volume or dataset license is established by this general offer.

Sources: [355], [356], [357]

Analysis: Dataocean AI / Speechocean - buyer assessment and unknowns. Dataocean AI and Speechocean remain one conservative brand/domain cluster. The login association does not resolve a dated rename, exact contracting company or ultimate ownership. Compare licensed datasets and custom speech collection separately, with native-speaker qualification and DOTS correction logs. The general offer does not establish dataset licenses or current workforce-language intersections; obtain the service-specific privacy terms.

Sources: [355], [356], [357]

Evidence: Datasaur - offering and scope. Datasaur’s current Data Studio offers automated NLP data annotation with configurable project interfaces and quality-control workflows.

Sources: [328]

Evidence: Datasaur - disclosed delivery and operating model. Datasaur’s terms limit customer-data processing to providing the service, with an additional deidentified or aggregate improvement-use permission for free-access subscriptions. Datasaur describes its NLP labeling interface as intended for subject-matter experts and data scientists. Data Studio describes automated pre-labeling combined with human-in-the-loop verification. Datasaur’s terms identify Datasaur, Inc. as the contracting service provider.

Sources: [327], [328]

Evidence: Datasaur - source-specific boundaries. This records the published terms and free-access exception, not a claim about every customer’s negotiated agreement. The main company homepage also advertises private AI deployments; Data Studio is retained as a product, not a separate supplier.

Sources: [327], [328]

Analysis: Datasaur - buyer assessment and unknowns. Data Studio’s expert-facing interface and human verification are product functions, not evidence of an internally employed expert pool. Test automated pre-labels and the correction audit trail on the buyer’s NLP task. Review the free-access exception for deidentified or aggregate improvement use separately from paid or negotiated terms. Private AI deployment marketing is a separate scope from Data Studio annotation.

Sources: [327], [328]

Evidence: Deepen AI - offering and scope. Deepen offers managed Annotate as a Service separately from customer-operated Annotate software. Deepen’s managed annotation scope includes 2D image/video, 3D LiDAR/radar, fused-sensor labels and scenario or behavior tags.

Sources: [329]

Evidence: Deepen AI - disclosed delivery and operating model. Deepen describes batch sampling with inter-annotator agreement, in-tool correction routing and geometry/taxonomy/consistency validation. The August 2025 data-protection addendum names Deepen AI Inc. and forms part of its customer service agreement. Deepen describes its annotation service as staffed by specialists hired, trained, managed and quality-checked directly rather than crowdsourced.

Sources: [329], [330]

Evidence: Deepen AI - source-specific boundaries. No accuracy percentage, certification or completed project outcome is adopted. Provider process disclosure; no active paid headcount, labor-term compliance or staffing audit is established.

Sources: [329], [330]

Analysis: Deepen AI - buyer assessment and unknowns. The documented service/software separation is useful for procurement: managed specialists and a customer-operated tool allocate work differently. A multisensor pilot should examine geometry, taxonomy and temporal consistency, then inspect the batch sample and correction routing. Directly managed staffing is a disclosed process, not an independently audited headcount or labor-compliance result. The DPA identifies a customer-service boundary to verify.

Sources: [329], [330]

Evidence: Defined.ai - offering and scope. Defined.ai offers custom AI-training data collection across audio, image, video, text and multimodal inputs.

Sources: [28]

Evidence: Defined.ai - disclosed delivery and operating model. The robotics case describes standardized calibration/collection documentation and weekly delivery reports as quality controls. Defined.ai’s Ethical AI page commits to explicit contributor consent and provenance clearance for AI-training data. Defined.ai says its crowd members must accept a community agreement, terms and privacy policy before work, and that jobs have their own statements of work and applicable transparency sheets. Defined.ai’s supplier terms distinguish marketplace or third-party proprietary datasets from new collection, crowd services, evaluation and RLHF services. Defined.ai reports delivering 225 hours of synchronized multimodal robotics sensor recordings for an unnamed AI research and deployment company.

Sources: [29], [30], [31]

Evidence: Defined.ai - source-specific boundaries. This is a provider policy commitment, not proof that every offered dataset has legally sufficient consent or a certification of individual projects. Linked agreements were not separately captured; exact pay, rejection, dispute and IP conditions remain unknown.

Sources: [28], [29], [30], [31]

Analysis: Defined.ai - buyer assessment and unknowns. Marketplace licensing and custom collection require different diligence. For a robotics pilot, request synchronization tolerances, calibration records, participant permissions and an acceptance sample rather than infer quality from delivered recording hours. The 225-hour case is an unnamed-customer historical delivery account, not a current throughput guarantee. Ethical commitments need record-level implementation evidence.

Sources: [28], [29], [30], [31]

Evidence: Deploy / Hive - offering and scope. Deploy’s current schedule separately offers data annotation and sourcing using Hive Workers.

Sources: [337]

Evidence: Deploy / Hive - disclosed delivery and operating model. The October 26, 2026 Deploy terms identify Castle Global, Inc. as the company providing the covered AI-related services. The official Hive landing page says Hive is now Deploy and existing customer logins are unchanged. Deploy’s AI-service terms provide for manual Hive Worker review of customer content to confirm model predictions unless the parties agree otherwise in writing. The Labeling Service terms describe Hive Workers as independent globally distributed workers and disclaim a guarantee that all task performance is accurate.

Sources: [337], [338]

Evidence: Deploy / Hive - source-specific boundaries. Hive and Deploy are retained as one supplier identity, not two companies. The labeling service is distinct from model API access and the customer-operated Arbiter moderation platform.

Sources: [337], [338]

Analysis: Deploy / Hive - buyer assessment and unknowns. Deploy/Hive is one supplier cluster with Castle Global named in the inspected terms. Separate labeling and sourcing through Hive Workers from model API access and customer-operated moderation software. The default manual-review clause is consequential for data access: confirm any written exception and downstream worker exposure. Contractual worker characterization and an accuracy disclaimer do not establish actual employment status or realized task quality.

Sources: [337], [338]

Evidence: Digital Divide Data - offering and scope. Digital Divide Data offers ML data operations and training-data solutions for language and computer-vision systems. DDD’s service offering includes human preference optimization and large-language-model fine-tuning. DDD offers human-in-the-loop sensor-data annotation for robots, autonomous vehicles, drones and smart machines.

Sources: [331], [333]

Evidence: Digital Divide Data - disclosed delivery and operating model. The published DDD Terms of Use name DDD Ventures LLC and include investment and real-estate language. DDD says it can integrate with the customer's existing technology stack rather than require its own tools. DDD's physical-AI annotation page says safety data receives enhanced quality assurance and subject-matter-expert review matched to the customer's risk profile.

Sources: [331], [332], [333]

Evidence: Digital Divide Data - source-specific boundaries. An impact-sourcing mission does not make the explicit commercial offer an adjacent grant program. No legal nonprofit status is inferred. The apparent mismatch with the AI-data business is unresolved. This records the page's contents and does not identify DDD Ventures LLC as the settled AI-data contracting entity.

Sources: [331], [332], [333]

Analysis: Digital Divide Data - buyer assessment and unknowns. The offering is commercial AI data work despite its impact-sourcing mission; the mission does not establish a nonprofit legal classification or measured worker outcomes. A pilot should specify physical-AI safety review and platform integration responsibilities. Resolve the published terms-page mismatch before using it to name the AI-data contracting party; the record preserves uncertainty rather than treating DDD Ventures LLC as settled.

Sources: [331], [332], [333]

Evidence: Encord - offering and scope. Encord offers managed annotation projects using vetted domain experts for physical AI, multimodal systems and LLMs.

Sources: [109]

Evidence: Encord - disclosed delivery and operating model. Encord describes role-based platform permissions restricting team members to the information needed for their role. Encord describes matching medical imagery to clinicians, robotics tasks to specialist operators and LLM evaluation to native speakers with subject-matter backgrounds. Encord describes human experts reviewing and correcting AI-generated first-pass annotations. Encord describes starting annotation projects with a small pilot to identify guideline gaps and document edge cases with visual examples. Encord states that annotation decisions are logged and visible in real time for project monitoring.

Sources: [109], [110]

Evidence: Encord - source-specific boundaries. Platform control disclosure; no independently inspected assurance report or project-specific deployment is established. This is a disclosed workflow, not a measured accuracy or cost advantage.

Sources: [109], [110]

Analysis: Encord - buyer assessment and unknowns. The relevant proposition combines expert matching, model-assisted first passes and visible annotation decisions. Inspect a pilot’s guideline revisions and who can override generated labels, then verify role permissions on the actual workspace. A match between clinician, operator or native speaker and task is a starting condition, not an independently measured accuracy result.

Sources: [109], [110]

Evidence: G2i - offering and scope. G2i advertises senior engineering teams for evaluations, RL environments, agent workflows and training-data programs.

Sources: [199]

Evidence: G2i - disclosed delivery and operating model. G2i human-data terms state that services are limited to talent acquisition and disclaim responsibility for candidate work. G2i describes independent review by two developers per task and selective follow-up quality checks by senior engineers. G2i advertises SOC 2 Type II controls and documented encryption, monitoring, access reviews and incident response. G2i describes its bench as vetted senior and staff-level engineers with 10+ years building production systems. The inspected G2i account attributes TypeScript task verification for a Multi-SWE workflow, without establishing authorship of the entire benchmark or a measured contribution to model performance.

Sources: [197], [198], [199]

Evidence: G2i - source-specific boundaries. The same terms include contractor engagement, statements of work and work-product provisions. This unresolved legal/marketing scope tension prevents assuming managed-delivery responsibility. Selective senior checks are described separately in the same annotation-pipeline section; this is not a universal double-adjudication guarantee.

Sources: [197], [198], [199]

Analysis: G2i - buyer assessment and unknowns. The contract boundary is unusually important here: marketing describes data programs, while the inspected human-data terms describe talent acquisition. Establish who owns instructions, review, rework and acceptance before comparing the offer with a managed service. The TypeScript verification account remains a scoped workflow contribution; dual-developer review and advertised security controls are not independently audited outcomes.

Sources: [197], [198], [199]

Evidence: Giskard - offering and scope. Giskard’s red-team product generates adaptive multi-turn attacks using customer business context. Giskard offers software to build and maintain dynamic evaluation datasets for AI agents. The evaluation product lets business experts set ground truths, qualify failures and collaborate on tests. Giskard advertises structured assessment reports and a managed remediation and retesting process.

Sources: [285], [286], [287]

Evidence: Giskard - disclosed delivery and operating model. Its evaluation software can add detected vulnerabilities to a golden dataset.

Sources: [286]

Evidence: Giskard - source-specific boundaries. Service description does not certify a customer’s safety or show every vulnerability was found. No certification/audit report was accessed.

Sources: [285], [286], [287]

Analysis: Giskard - buyer assessment and unknowns. The output can be evaluation software, an evolving golden set or a managed assessment/remediation cycle. Specify which of these is being bought and who owns expert ground truths. For an adaptive attack pilot, hold out business scenarios and measure both discovered failures and false alarms. Tool-generated attacks are not evidence of exhaustive safety coverage or completed remediation.

Sources: [285], [286], [287]

Evidence: HackerRank Bench - offering and scope. HackerRank Bench offers private benchmarking and long-horizon task creation tuned to client objectives. Bench offers executable repository-scale RL environments with resettable workspaces, hidden verifiers and per-step evidence.

Sources: [289]

Evidence: HackerRank Bench - disclosed delivery and operating model. Its off-the-shelf data section says the offering concerns community submissions and excludes customer data. Bench says its benchmark verifiers are hand-written to test software behavior. HackerRank presents Bench as its software-engineering data, evaluation and environment service.

Sources: [289]

Evidence: HackerRank Bench - source-specific boundaries. The source commitment is not a dataset-license review, individual consent audit, proof of ownership of each submission or permission for every reuse. Benchmark-method disclosure; no benchmark ranking, lack of contamination or verifier soundness is independently established.

Sources: [289]

Analysis: HackerRank Bench - buyer assessment and unknowns. Bench offers a repository-scale environment package rather than only a problem list. Test resets, hidden verifiers, per-step evidence and behavior-based rejection on a small private repository. The stated exclusion of customer data from community submissions is a source boundary, not a record-level rights audit. Benchmark soundness and contamination require their own checks.

Sources: [289]

Evidence: Handshake AI - offering and scope. Handshake operates a contractor program for annotated data and related Human Data Services.

Sources: [201]

Evidence: Handshake AI - disclosed delivery and operating model. The Handshake AI Contractor Agreement names Handshake AI Solutions, LLC as the contracting entity. Successful onboarding does not guarantee a Handshake AI project; contractor selection depends on expertise and project demand. Handshake sets payment amount, type and timing in each project invitation, including task, time or milestone payment bases. The contractor agreement permits technical and operational quality, integrity and compliance monitoring, including remote monitoring and automated tools. The global privacy policy defines Handshake as Stryder Corp. d/b/a Handshake and its affiliates and subsidiaries.

Sources: [201], [202]

Evidence: Handshake AI - source-specific boundaries. The July 2026 privacy policy separately defines Handshake as Stryder Corp. d/b/a Handshake and affiliates; corporate ownership shares are not established. This contractor-program scope does not identify a named customer or downstream model contribution.

Sources: [201], [202]

Analysis: Handshake AI - buyer assessment and unknowns. The dossier documents a contractor program and project invitation terms. For buyers, confirm delivery responsibility and acceptance separately from recruiting access. For contributors, onboarding and project availability are different states, and payment basis varies by invitation. Contractual monitoring rights do not establish actual project audit coverage, current paid headcount or the quality of accepted outputs.

Sources: [201], [202]

Evidence: Humans in the Loop - offering and scope. Humans in the Loop offers managed data-labeling teams, including specialized healthcare and real-time monitoring projects.

Sources: [114]

Evidence: Humans in the Loop - disclosed delivery and operating model. Humans in the Loop describes a two-hour annotation trial on sample data and instructions before final guideline and setup adjustments. Humans in the Loop describes delivering annotated data followed by a client post-mortem meeting to inform subsequent batches. Humans in the Loop’s Fair Work Policy applies to contractors performing paid work who are not full-time or part-time employees. The Fair Work Policy says annotators receive adequate training for every project. The Fair Work Policy calculates payments from the project unit price and units delivered on time and approved by the project supervisor.

Sources: [113], [115]

Evidence: Humans in the Loop - source-specific boundaries. The page calls the annotation-guideline stage “Fine Tuning”; it is not evidence of model fine-tuning services. Policy scope, not a current worker-count, legal employment classification or independently verified compliance finding.

Sources: [113], [114], [115]

Analysis: Humans in the Loop - buyer assessment and unknowns. The two-hour sample trial and post-mortem batch loop are useful mechanisms to inspect rather than performance guarantees. Require written guideline changes, rejected-unit treatment and the supervisor approval rule before scaling. The page’s annotation setup label Fine Tuning should not be read as evidence of model-training services. Worker-policy commitments require separate execution evidence.

Sources: [113], [114], [115]

Evidence: iMerit - offering and scope. iMerit offers domain-expert feedback for model fine-tuning through RLHF services.

Sources: [34]

Evidence: iMerit - disclosed delivery and operating model. The same case study describes manual data correction involving iMerit experts and reviewers during persona-based prompt generation. iMerit states that employees, vendors and contractors are screened and sign NDAs, with project data restricted to the assigned team. iMerit’s case study reports that its annotators manually generated persona-based multilingual prompts for an unnamed Asian technology company’s LLM chatbot corpus. iMerit describes secondary-expert task review followed by sampled client audits and return of rejected tasks to review.

Sources: [33], [34], [35]

Evidence: iMerit - source-specific boundaries. Provider security disclosure is not a current independent certification report. The source’s nine-centre description is not adopted as current footprint. The case PDF is undated. Its later ranking exercises are a roadmap, not established delivered preference rankings. No client/model identity is inferred.

Sources: [33], [34], [35]

Analysis: iMerit - buyer assessment and unknowns. The multilingual prompt case establishes an authoring and expert-correction workflow for an unnamed customer. Keep the stated later ranking roadmap separate from delivered work. A comparable pilot should trace rejected items through secondary review and client audit, and inspect the assigned-team access rule. Domain-expert RLHF marketing alone does not establish measured downstream model gains.

Sources: [33], [34], [35]

Evidence: Innodata - offering and scope. Innodata offers expert human-in-the-loop feedback for RLHF and direct preference optimization.

Sources: [116]

Evidence: Innodata - disclosed delivery and operating model. Innodata describes explaining response scores with details such as factual errors or logical inconsistencies. Innodata describes feedback types including thumbs-up/down, rating scales and nominal classifications in its RLHF service. Innodata describes a multi-pass assessment process for vetting model responses. Innodata states it provides documented annotation guidelines covering challenging edge cases.

Sources: [116]

Evidence: Innodata - source-specific boundaries. The provider’s absolute quality language is not adopted as an independently measured quality guarantee.

Sources: [116]

Analysis: Innodata - buyer assessment and unknowns. The disclosed signal menu distinguishes binary reactions, scales, categories and explanatory feedback. Select the label type that matches the intended learning or evaluation objective, then inspect multi-pass review on edge cases. A multi-pass process can add review stages without making judgments independent; request raw labels, reviewer roles and resolution reasons.

Sources: [116]

Evidence: Invisible Technologies - offering and scope. Invisible offers model-ready off-the-shelf datasets spanning professional work, code and customer interactions.

Sources: [36]

Evidence: Invisible Technologies - disclosed delivery and operating model. Invisible describes access to vetted domain experts across technical and specialized fields. Invisible reports hiring, training and coordinating expert teams for an unnamed AI developer’s adversarial NLI and RLHF processes. Invisible’s delivery case describes comprehensive onboarding and cross-training operators to move between processes. Invisible’s privacy policy states its software can collect keystrokes, mouse clicks, screenshots and webcam pictures from agents, with collection notices and possible loss of project access if declined.

Sources: [37], [38], [39]

Evidence: Invisible Technologies - source-specific boundaries. The larger “access to global experts” pool is not a count of paid or active workers. The client and model remain unnamed. The headline launch-time and accuracy comparisons are omitted rather than treated as independent measurements.

Sources: [36], [37], [38], [39]

Analysis: Invisible Technologies - buyer assessment and unknowns. The catalog and the expert-team case represent different purchase units. Ask whether a proposed program includes recruitment, onboarding, cross-training and accepted outputs, or a fixed licensed artifact. Agent monitoring disclosures create a concrete question about worker notices, proportionality and project access. They do not establish worker consent quality or production acceptance rates.

Sources: [36], [37], [38], [39]

Evidence: isahit - offering and scope. isahit offers a managed workforce for annotation and LLM fine-tuning projects.

Sources: [118]

Evidence: isahit - disclosed delivery and operating model. isahit states each project has a dedicated delivery manager supporting the workforce daily. isahit's contributor page requires proof of self-employed status and describes collecting identity, residence and self-employment documents during onboarding. isahit states it provides continuous coaching and at least four hours of training per person per project. isahit's contributor page advertises remuneration above the SMIC of the contributor's country plus bonuses.

Sources: [117], [118]

Evidence: isahit - source-specific boundaries. Public onboarding requirements, not a determination of employment status under any jurisdiction or proof of an individual's enrollment. Provider-described training minimum; completion by any individual contributor has not been audited.

Sources: [117], [118]

Analysis: isahit - buyer assessment and unknowns. The disclosed model combines a delivery manager, project training and self-employed contributor onboarding. A pilot should measure training completion, revision handling and accepted output under the promised coaching structure. The remuneration statement is a provider policy, not measured earnings in a defined currency, country and time window; request a project-specific compensation and unpaid-time accounting.

Sources: [117], [118]

Evidence: iSoftStone - offering and scope. iSoftStone lists search and advertising relevance as a managed service alongside in-person, remote and crowdsourced collection or labeling modes. iSoftStone offers voice-data collection, transcription, segmentation, ambient-noise processing, virtual-assistant tuning and text-to-speech services. iSoftStone's computer-vision offer includes image/video labeling, boxes, categorization, facial-recognition data collection and human-gesture annotation.

Sources: [341]

Evidence: iSoftStone - disclosed delivery and operating model. iSoftStone describes quality assurance through error avoidance, early detection and correction, and continuous improvement during the project lifecycle. The current website privacy policy identifies iSoftStone, Inc. as its operator.

Sources: [341], [342]

Evidence: iSoftStone - source-specific boundaries. A process description, not independent validation of accuracy, annual volumes or labor conditions. This identifies the website-scoped US entity. Current ultimate ownership and group-wide contracting responsibility remain unresolved.

Sources: [341], [342]

Analysis: iSoftStone - buyer assessment and unknowns. The inspected US website supports speech, vision and relevance services with several workforce modes. Confirm the contracting entity, ultimate group responsibility and the project’s delivery mode rather than extend the website operator to every affiliate. A pilot should test error correction and task-specific quality on the relevant voice or vision data. No annual volume or labor-condition inference is warranted.

Sources: [341], [342]

Evidence: Keymakr - offering and scope. Keymakr offers human-in-the-loop review for specialized AI through verified industry professionals.

Sources: [120]

Evidence: Keymakr - disclosed delivery and operating model. The SeeChange case identifies Keylabs as Keymakr’s proprietary annotation platform used for that project. Keymakr’s SeeChange case states that standardized annotation guidelines were drafted and followed to maintain consistency. Keymakr reports a core team of 30 annotators that scaled to 50 at stages of the SeeChange project. Keymakr reports delivering structured annotated video datasets for SeeChange’s retail behavior-analysis model development.

Sources: [119]

Evidence: Keymakr - source-specific boundaries. Historical project-team disclosure without a calendar-defined paid-active window. It is not company headcount, recruitable pool, or paid assignment total. Provider-authored named case. No public dataset release, model identity, independent performance result or current contract is inferred.

Sources: [119], [120]

Analysis: Keymakr - buyer assessment and unknowns. The named retail-video case is useful for inspecting guidelines, video units and team scaling on a similar project. Its reported 30-to-50-person team belongs to that case, not a current active workforce. Request a reproducible clip-level acceptance sample and distinguish the Keylabs software role from Keymakr’s managed annotation responsibility.

Sources: [119], [120]

Evidence: Kili Technology - offering and scope. Kili offers software for customer specialists to write post-training examples and judge AI evaluation data. Kili’s image annotation tool offers boxes, polygons and masks with SAM drafting segmentations for experts to refine.

Sources: [344]

Evidence: Kili Technology - disclosed delivery and operating model. Kili’s quality product supports specialist agreement checks, honeypot scoring and reviewer corrections. Kili’s EULA distinguishes SaaS, customer-storage hybrid and customer-managed on-premise software, with selected services governed by the order form. Kili offers introductions to external specialist partners who work inside the customer’s project and review workflow. Kili’s May 29, 2025 legal notice names MYAI SAS as website editor with Paris registration 843 210 014.

Sources: [343], [344], [345], [346]

Evidence: Kili Technology - source-specific boundaries. Product controls are not audited project outcomes. Customer experts are not automatically Kili employees or a Kili managed annotation workforce.

Sources: [343], [344], [345], [346]

Analysis: Kili Technology - buyer assessment and unknowns. Kili’s software lets customer specialists author and judge data, while partner introductions remain distinct from direct staffing. A pilot should test consensus, honeypots, reviewer authority and the selected SaaS, hybrid or on-premise deployment. Resolve the legal-notice/EULA name inconsistency under the same registration number in the actual order. The discrepancy is not evidence of two independent suppliers.

Sources: [343], [344], [345], [346]

Evidence: Label Your Data - offering and scope. Label Your Data offers data labeling by a trained workforce managed by experienced QA specialists.

Sources: [122]

Evidence: Label Your Data - disclosed delivery and operating model. Label Your Data describes tailored QA workflows in which specialists review outputs for accuracy, consistency and alignment with client requirements. Label Your Data’s notice effective 16 July 2024 identifies SupportYourApp, Inc. as the entity using the Label Your Data name. The same notice says Label Your Data processes client-submitted personal data for labeling services under client instructions or contractual requirements. Label Your Data reports providing polygon annotations to support Searidge Technologies’ computer-vision development. In the Searidge engagement, Label Your Data reports handling video-frame selection, polygon annotation and annotation-tool management using the client’s FTP for exchange.

Sources: [121], [122], [123]

Evidence: Label Your Data - source-specific boundaries. This is the notice’s identification, not a fresh corporate-registry or current ownership finding. Limited to the notice’s processor scope; no independently verified privacy compliance or certification status is asserted.

Sources: [121], [122], [123]

Analysis: Label Your Data - buyer assessment and unknowns. The Searidge case supplies a specific video-frame and polygon-annotation workflow. For a comparable project, define frame selection, polygon geometry, tool administration and transfer responsibilities before pricing. The processor notice identifies a contractual instruction boundary; it does not establish complete source rights, current secure transfer practice or downstream model quality.

Sources: [121], [122], [123]

Evidence: Labelbox - offering and scope. Labelbox’s Alignerr offering delivers structured expert signal as preference pairs, ranked trajectories and rubric-graded assessments.

Sources: [42]

Evidence: Labelbox - disclosed delivery and operating model. Labelbox describes routing Alignerr tasks according to contributor credentials, experience and domain background. Labelbox’s 14 October 2026 announcement reports more than $100 million in Series E financing, comprising equity and a credit facility, at a $1.25 billion pre-money valuation. Labelbox’s privacy notice permits sharing personal information with service providers, consultants and Workforce Partners needing access to provide services. Labelbox describes continuously calibrating contributor performance against ground truth and validating outputs before pipeline delivery. Labelbox reports that Alignerr produced expert-graded speech signal for an unnamed text-to-speech company’s post-training work.

Sources: [42], [43], [44], [45]

Evidence: Labelbox - source-specific boundaries. The source uses dollar symbols without explicitly naming an ISO currency. Financing and valuation are not revenue; the credit facility is not equity funding. This notice covers the stated services scope and explicitly excludes employee and job-applicant personal information. It is not a contributor pay or IP agreement.

Sources: [42], [43], [44], [45]

Analysis: Labelbox - buyer assessment and unknowns. The disclosed deliverables are structured expert signals, including preference pairs, trajectories and rubric assessments, with a separate speech case. Request domain-specific calibration and raw-to-accepted counts. Financing is not evidence of delivered capacity or revenue, and a pre-money valuation does not measure data quality. Workforce-partner privacy provisions need project-specific access and subprocessing detail.

Sources: [42], [43], [44], [45]

Evidence: LXT - offering and scope. LXT offers structured human-feedback workflows including pairwise output ranking, scaled ratings and open-ended feedback.

Sources: [48]

Evidence: LXT - disclosed delivery and operating model. LXT describes gold-task calibration, reviewer overlap scoring, audit sampling and performance tracking in its RLHF process. LXT reports contributors ranked, rated, categorized and rewrote model responses for an unnamed technology company's foundational-LLM fine-tuning program. LXT's privacy policy states client-submitted files are processed under client instructions and offers a data-processing agreement. LXT's case reports qualifying and onboarding 4,000 contributors across 50 languages in one week. LXT states that RLHF data is handled under NDAs and role-based access, with secure-facility execution available for sensitive projects.

Sources: [46], [47], [48]

Evidence: LXT - source-specific boundaries. Client/model identity and public dataset release remain unspecified. These tasks do not establish that LXT trained the client's model itself. The policy's effective date is 19 April 2020; a newer update date is not stated. This is a captured current page, not proof of current legal compliance.

Sources: [46], [47], [48]

Analysis: LXT - buyer assessment and unknowns. The reviewed case combines multilingual onboarding with ranking, rating, categorization and rewriting. The 4,000-contributor, 50-language, one-week account belongs to that engagement and cannot be a current hiring or throughput guarantee. A pilot should test each required language-domain intersection and inspect calibration, overlap scoring and rejected-unit correction under the proposed security setting.

Sources: [46], [47], [48]

Evidence: Mercor - offering and scope. Mercor markets ready-to-license datasets across professional work, coding, search, research, and multimodal reasoning. Mercor offers custom datasets and research partnerships including model evaluation, failure-mode analysis, and post-training.

Sources: [474]

Evidence: Mercor - disclosed delivery and operating model. Mercor documents the APEX-Agents 1.1 release; the attribution is to that named release and its stated construction scope. Mercor's website privacy notice identifies Mercor.io Corporation as the operator of the website. Mercor's catalog advertises a network of more than five million domain experts. Mercor discloses hand-labeling rubric items for a revised APEX judge and an increased false-negative rate versus its naive grader. Mercor disclosed being affected by compromised LiteLLM versions in March 2026. Mercor says catalog tasks are created, vetted, and peer-reviewed by domain experts with automated quality controls. Mercor's website notice explicitly excludes the work.mercor.com service and directs experts to a separate notice. Mercor describes expert-written prompts, rubrics, golden solutions, workplace environments, and long-horizon workflows.

Sources: [473], [474], [475], [476]

Evidence: Mercor - source-specific boundaries. Scoped source statement: Mercor reports releasing APEX-Agents 1.1 with 80 tasks per professional domain, refined through three expert audits. No denominator definition, active-period window, currently paid contributors, or paid assignment count is given in this catalog. Do not equate pool size with production capacity.

Sources: [473], [474], [475], [476]

Analysis: Mercor - buyer assessment and unknowns. The disclosed catalog and custom programs center on expert-written tasks, rubrics, solutions and workplace environments. A pilot should inspect grader false negatives and long-horizon edge cases rather than treat a published benchmark as universal validation. The expert-network figure is not a paid-active count. Security diligence should use the actual work-service notice and scoped incident/remediation evidence.

Sources: [473], [474], [475], [476]

Evidence: micro1 - offering and scope. Flow is described as the environment where experts create, review and deliver datasets in healthcare, legal and finance. micro1 Realm advertises human-in-the-loop data production for AI labs.

Sources: [208]

Evidence: micro1 - disclosed delivery and operating model. micro1 states that experts see a project pay rate before acceptance and are paid twice monthly. micro1 presents MissionReport as its named benchmark artifact, without an independently reproduced performance finding. Realm describes real-time tracking of data-production velocity, error rates, cost per task and quality. micro1 describes Zara as its AI recruiter that sources and vets domain experts.

Sources: [208], [209], [210]

Evidence: micro1 - source-specific boundaries. Public support-program commitments do not independently establish payment execution; active paid expert counts are not audited. Self-published benchmark construction; no government customer contract or downstream model-training contribution is inferred.

Sources: [208], [209], [210]

Analysis: micro1 - buyer assessment and unknowns. Separate recruitment through Zara, production within Realm/Flow and the named MissionReport artifact. The operational dashboard metrics are a disclosed tracking design, not audited velocity or error rates. A pilot should make each metric’s denominator visible and test review authority. The twice-monthly pay statement is a schedule disclosure, not proof of realized earnings or project continuity.

Sources: [208], [209], [210]

Evidence: Mindy Support - offering and scope. Mindy’s FAQ offers image, text, speech-recognition, video and 3D point-cloud annotation services.

Sources: [347]

Evidence: Mindy Support - disclosed delivery and operating model. Mindy’s FAQ says client KPIs and measurement are discussed before project start, with the client ultimately determining the KPIs. Mindy says its R&D department selects and adapts annotation tooling to project needs. Mindy’s FAQ describes phone screening, a recruiter interview, written tests and an interview with the project manager. Mindy’s official FAQ offers a trial to assess deliverables before a longer engagement.

Sources: [347]

Evidence: Mindy Support - source-specific boundaries. Exact official web.run extraction is retained; direct site GET returned403. The FAQ is undated, so workforce and operating-location numbers are not treated as current. Evidence is the exact saved official web.run extracted-page snapshot; origin HTML and live HTTP status were not exposed.

Sources: [347]

Analysis: Mindy Support - buyer assessment and unknowns. The undated FAQ supplies an annotation, screening and trial-process disclosure, not current staffing, office footprint or active openings. Ask for the client-defined KPIs, adapted tool setup and paid trial terms in a current proposal. The exact saved official extraction is the reviewed evidence; it does not establish direct origin-HTML retrieval or a live availability result. The footer outside the frozen read range is not adopted.

Sources: [347]

Evidence: Objectways - offering and scope. Objectways offers expert human-in-the-loop labeling for text, image, audio, video and LiDAR training data.

Sources: [126]

Evidence: Objectways - disclosed delivery and operating model. Objectways describes client review of sample outputs and feedback before finalizing annotation guidelines. Objectways states employees are onboarded after an NDA and background checks. Objectways describes a test annotation job to estimate effort, timelines and output quality before scaling. Objectways offers expert annotation capacity from pilot to production for outsourcing or team augmentation.

Sources: [125], [127]

Evidence: Objectways - source-specific boundaries. Provider-reported employee onboarding control; no independent implementation audit, contractor coverage or named-project compliance is established. Availability language is not a paid-active workforce count or guaranteed individual assignment.

Sources: [125], [126], [127]

Analysis: Objectways - buyer assessment and unknowns. The sample-run and client-feedback loop provide a concrete way to test guideline ambiguity before scale. Choose a pilot with hard examples and inspect how sample feedback changes production instructions. NDA and background checks are onboarding disclosures; they do not establish complete access controls or acceptance quality. Team augmentation and outsourced accepted delivery should be priced and warranted separately.

Sources: [125], [126], [127]

Evidence: Ooak Data - offering and scope. Ooak Data offers RL environments built from real enterprise data and workflows.

Sources: [295]

Evidence: Ooak Data - disclosed delivery and operating model. Ooak describes sourcing enterprise material, anonymizing it into digital twins and generating expert-level tasks. Its October 27, 2026 process essay describes human QA, raw-copy deletion and source-company approval before dataset release. Its privacy policy names Ooak Data, Inc. for US website processing and Ooak Data SAS for European operations. Ooak’s website terms reserve data acquisition partnerships to separately negotiated written agreements.

Sources: [295], [296], [297], [298]

Evidence: Ooak Data - source-specific boundaries. A vendor process disclosure, not independent proof that a dataset is anonymous or every release received valid authorization. Controller roles are not proof of group equity ownership or a separate supplier count for the European entity.

Sources: [295], [296], [297], [298]

Analysis: Ooak Data - buyer assessment and unknowns. The distinctive disclosed pipeline converts enterprise material into anonymized digital twins and tasks, with source-company approval and raw-copy deletion described before release. A pilot should inspect one transformation end to end, including residual identifiers and the approval record. Website terms reserve partnership detail to separate contracts; they do not establish transferable rights for every underlying business document.

Sources: [295], [296], [297], [298]

Evidence: Pareto AI - offering and scope. Pareto advertises specialist projects built around judgment, reasoning and domain knowledge for training models.

Sources: [215]

Evidence: Pareto AI - disclosed delivery and operating model. Pareto documents the AttuneBench artifact and its human-label contribution, under the specific release account. The Pareto site terms identify Pareto Inc., doing business as Pareto. Pareto says strong expert performance leads to more projects and specialized work across its network. Pareto reviews expert applications on a rolling basis and says it will reach out when there is a strong background match. Pareto's website terms grant customers a nonexclusive, perpetual license to original work product created for them.

Sources: [214], [215], [216]

Evidence: Pareto AI - source-specific boundaries. This is an owned evaluation artifact. The paper, code and dataset license were not independently reviewed in this pass. Forte and Hello Pareto are historical alias hints only; this pass does not verify a current separate product, employer or subsidiary under those names.

Sources: [214], [215], [216]

Analysis: Pareto AI - buyer assessment and unknowns. The reviewed scope combines specialist projects, matching and an AttuneBench artifact. The customer work-product license is nonexclusive and perpetual in the inspected terms, so exclusivity and underlying-source rights require explicit treatment. Rolling applications and performance-based project allocation do not guarantee work or establish a paid-active pool. Compare accepted expert judgments on the intended domain.

Sources: [214], [215], [216]

Evidence: Polymath - offering and scope. Polymath describes building simulation environments for training and evaluating autonomous agents.

Sources: [219]

Evidence: Polymath - disclosed delivery and operating model. Polymath's terms identify Polymath AI Labs, Inc. and cover both polymathlabs.ai and anthologyresearch.ai. Applying to or joining Anthology Fellows does not create employment; a separate contractor agreement is required before work or payment. Polymath presents Horizon-SWE as its named benchmark artifact; that does not establish the effectiveness of every simulation engagement. Polymath's terms say interview voice recordings and transcripts will not be used to train AI models. Horizon-SWE describes assessing agents on verifiable outcomes with partial credit.

Sources: [217], [218]

Evidence: Polymath - source-specific boundaries. A stated operator relationship is not proof of share ownership, acquisition history or a separate supplier count for Anthology. Community membership is not an active paid-worker count; the separate contractor agreement was not available in this source set.

Sources: [217], [218], [219]

Analysis: Polymath - buyer assessment and unknowns. The simulation offer and Horizon-SWE outcome checks should be inspected as a particular environment product. Test the partial-credit logic and negative cases before using it for training or evaluation. Anthology Fellows membership is not employment or paid work; a separate agreement is required. The interview-data restriction should not be extended to unrelated customer processing without a contract.

Sources: [217], [218], [219]

Evidence: Prime Intellect - offering and scope. Prime Intellect provides an open-source environment framework and an environment hub for RL. Prime Intellect offers managed SFT/RL training, inference and compute as an integrated platform.

Sources: [220]

Evidence: Prime Intellect - disclosed delivery and operating model. Model Factory terms meter hosted training per GPU-hour allocated to a run, prorated to the second; rates come from the order or platform. The NVIDIA case attributes verified enterprise tasks to the specific Prime Intellect workflow. It does not establish all NVIDIA training input or a causal share of model gains. The NVIDIA case study says enterprise tasks are scored on changes to simulated applications and files, with objectives and guardrails. Model Factory terms distinguish platform services from any personnel-performed post-training work, which needs a separate professional-services order.

Sources: [221], [222]

Evidence: Prime Intellect - source-specific boundaries. Pricing basis is distinct from quoted public compute example prices, data-service pricing, company revenue and customer spend. No commercial amount is asserted. Platform capability alone is not evidence of human-data staffing or bespoke task generation.

Sources: [220], [221], [222]

Analysis: Prime Intellect - buyer assessment and unknowns. Separate open framework access, hosted compute/training and personnel-performed professional services. GPU-hours allocated to a run are a billing unit, not accepted data units or actual productive compute. For an enterprise-task pilot, inspect objective and guardrail checks in addition to final file/application changes. The named case does not establish all downstream model input or causal performance gains.

Sources: [220], [221], [222]

Evidence: Prolific - offering and scope. Prolific’s AI tasker groups cover image, video, audio, comparative reasoning, fact-checking, and structured writing. Prolific offers both researcher-managed participant access and managed complete-dataset collection with multi-stage quality assurance.

Sources: [477], [479]

Evidence: Prolific - disclosed delivery and operating model. Prolific's pricing page reports more than 300,000 active participants and separately over one million on its waitlist. Prolific offers participants selected through verified experience or targeted assessments for AI training and evaluation tasks. The inspected research case establishes recruitment through Prolific into a researcher-owned labeling interface, rather than Prolific authorship of all study data or analysis. Prolific's captured pricing FAQ states usual platform fees of 42.8% for corporate customers and 33.3% for academic or nonprofit customers. Prolific states minimum permitted participant rates of GBP 6 or USD 8 per hour and recommends GBP 9 or USD 12. Prolific forbids under-18 recruitment and ordinarily disallows collection of directly identifying participant information. Prolific describes identity checks, ongoing pool monitoring, in-study checks, researcher approval history, and human appeals. Prolific states ISO 27001 and Cyber Essentials certification while describing SOC 2 Type 2 as a future plan. The case reports L1 English participants in the UK or US with at least 100 completed experiments and a representative-sample option.

Sources: [477], [478], [479], [480], [481], [482]

Evidence: Prolific - source-specific boundaries. The page explicitly says active, but does not define its activity window. Waitlisted people are not active participants. No currently paid workforce or assignment count is established. Role is recruitment. Researchers used their own modified Potato annotation interface; no evidence here that Prolific authored the labels, adjudicated them, or supplied a production model training set.

Sources: [477], [478], [479], [480], [481], [482]

Analysis: Prolific - buyer assessment and unknowns. Participant access can be appropriate when the research team owns the interface and judgment protocol; managed collection changes that responsibility. Define expertise and sampling rather than treating a representative-sample option as universal coverage. Active-participant, waitlist, tariff and reward-floor disclosures use different denominators. The inspected fee FAQ leaves the percentage denominator unspecified, so obtain a complete project quote.

Sources: [477], [478], [479], [480], [481], [482]

Evidence: Proximal - offering and scope. Proximal describes a data research and engineering organization rather than a recruiting firm or talent marketplace. Proximal says it turns real-world traces and human-workflow artifacts into evaluations and targeted post-training data.

Sources: [223], [225]

Evidence: Proximal - disclosed delivery and operating model. In its September 29, 2026 announcement, Proximal reports scaling to $200M in annualized revenue. Proximal's privacy policy requires prior written consent and an executed agreement before using customer material to improve generalized models. Proximal's MSA identifies Proximal AI, Inc. and requires executed order forms for customer services. Proximal documents its scoped FrontierSWE collaboration; no broader customer contribution or exclusive production role is inferred. Proximal's MSA permits independent contractors and keeps Proximal responsible for subcontracted services.

Sources: [223], [224], [226], [227]

Evidence: Proximal - source-specific boundaries. Self-reported annualized pace, not an audited annual revenue total, recognized revenue, profit, bookings, valuation or contractor payout. The source does not specify the annualization window, currency code, gross-versus-net accounting, or revenue by business line. This applies to generalized model training; it does not prohibit customer-authorized training services or prove compliance in individual projects.

Sources: [223], [224], [225], [226], [227]

Analysis: Proximal - buyer assessment and unknowns. The disclosed organization takes responsibility for data research and engineering rather than presenting itself as a recruiting marketplace. The MSA’s subcontractor responsibility is relevant to acceptance accountability. Inspect one trace-to-task transformation and consent boundary. The $200M announcement is self-reported annualized pace with undisclosed annualization window, currency code and gross/net basis, not audited annual or segment revenue.

Sources: [223], [224], [225], [226], [227]

Evidence: Refresh - offering and scope. Refresh offers simulation environments that turn enterprise workflows into measurable and trainable tasks. Refresh offers simulated worlds for coding and computer use with verifiable rewards.

Sources: [233]

Evidence: Refresh - disclosed delivery and operating model. Refresh presents BlenderBench as its published benchmark artifact; the associated verifier description remains source-reported. Refresh says it sources real tasks by partnering with expert engineers, reproduces failures and codifies verifiable tasks. Refresh’s website terms state that benchmarks, datasets and research may have separate licensing terms. Refresh says BlenderBench uses versioned verifiers checking saved scenes, protected starting content and rendered outputs, with task-specific rubrics.

Sources: [232], [233], [234]

Evidence: Refresh - source-specific boundaries. An owned benchmark and evaluation offering; its stated longer-term RL aspiration is not evidence of completed RL-training delivery. No named enterprise customer, completed contract or specific downstream training artifact is established by the homepage.

Sources: [232], [233], [234]

Analysis: Refresh - buyer assessment and unknowns. Versioned task verifiers and saved-scene checks make BlenderBench useful for asking concrete reproduction questions. For a computer-use or visual-editing pilot, test protected starting content and rendered outputs alongside task success. Expert-sourced tasks and separate artifact licenses do not establish unrestricted rights or complete contamination resistance. Maintenance and version migration should be part of the contract.

Sources: [232], [233], [234]

Evidence: RWS / TrainAI - offering and scope. TrainAI offers response rating, transcription, image segmentation and object-tracking data services. TrainAI offers automated and human-in-the-loop validation of AI training data.

Sources: [305], [308]

Evidence: RWS / TrainAI - disclosed delivery and operating model. The FAQ describes expert review, repeated-annotation consensus and golden-answer comparisons. The February 28, 2023 RWS announcement introduces TrainAI as an RWS brand. Its community FAQ describes language, general ML and project-specific screening tests.

Sources: [306], [307]

Evidence: RWS / TrainAI - source-specific boundaries. This records described QA techniques, not a measured error rate or independent verification of their application on each project. Historical brand launch, not a current separate legal-entity or ownership registry check. RWS group/Generate financials are not TrainAI standalone revenue.

Sources: [305], [306], [307], [308]

Analysis: RWS / TrainAI - buyer assessment and unknowns. TrainAI's disclosed service menu spans response rating and perception tasks, with language and project-specific screening. A pilot should test the relevant signal type and inspect how repeated annotation and gold answers interact. The RWS brand relationship prevents double counting; it does not establish uniform staffing, security or acceptance performance across all programs.

Sources: [305], [306], [307], [308]

Evidence: Sama - offering and scope. Sama offers human-verified annotation, validation and evaluation services for computer vision, NLP and multimodal AI.

Sources: [54]

Evidence: Sama - disclosed delivery and operating model. Sama describes maintaining annotation consistency through written guides and continuing calibration of labeling instructions as data changes. Sama reports its in-house data team reviewed and rewrote image captions to produce fine-tuning data for an unnamed Fortune 500 company. Sama describes using a full-time in-house workforce in a secure facility and states it does not keep or share customer datasets for training or other purposes. Sama states that project rooms and data are restricted to the assigned employees and production staff undergo background checks. In the same engagement, Sama says its team evaluated prompt-response turns and supplied rewritten prompts and rationale for preferred responses.

Sources: [53], [54], [55]

Evidence: Sama - source-specific boundaries. The client is anonymous; no named company, model, or public dataset is attributed. Published workforce/data-use representation, not a guarantee for all contracts or a verified pay/welfare finding. No wage rate or current paid headcount is disclosed here.

Sources: [53], [54], [55]

Analysis: Sama - buyer assessment and unknowns. The in-house secure-facility model is a disclosed delivery arrangement, while the caption and prompt cases describe specific authoring/rewrite work for an unnamed customer. A comparable pilot should preserve originals, edits and rationales and examine how calibration changes over batches. A statement about not reusing customer datasets requires confirmation in the actual project agreement and execution evidence.

Sources: [53], [54], [55]

Evidence: Scale AI - offering and scope. Scale offers tailored generative-AI training datasets curated by vetted subject-matter experts. Scale publicly offers model evaluation including targeted red-teaming.

Sources: [485]

Evidence: Scale AI - disclosed delivery and operating model. The HelpSteer3 source names Scale as an annotation contributor, with the more specific reviewed subset claims defining its scope. The HelpSteer3 paper assigns Scale recruitment to the general, STEM and code preference workflow. The InstructGPT paper names Scale as a recruitment channel for that study, without making Scale the author of every prompt, comparison or model component. Scale reports nearly $1 billion paid cumulatively to hundreds of thousands of contributors across more than 150 countries. The FY2025 modern-slavery statement is made on behalf of Scale AI, Inc. and its wholly owned subsidiaries. HelpSteer3 explicitly attributes Scale annotation to its general, STEM and code subset, separately from the multilingual subset. Scale says contributor-project matching uses background, skills, profile, and work performed on Outlier. Scale describes automated task review with human experts setting standards and reviewing edge cases. Scale publicly states it has a SOC 2 Type 2 report and ISO/IEC 27001:2022 certification. Scale describes Data Infrastructure and AI Applications as two primary business segments.

Sources: [461], [464], [468], [483], [484], [486], [487]

Evidence: Scale AI - disclosed delivery and operating model. For sensitive-content AI safety projects, Scale describes advance notice, ability to decline, and wellness resources as standard practice. Scale states contributors can access work through third-party BPOs or other service providers and proprietary platforms including Outlier. The pinned HelpSteer2 release attributes annotation to Scale under that release’s stated workflow. The pinned HelpSteer3 release records Scale annotation for its specified subset.

Sources: [429], [440], [483]

Evidence: Scale AI - source-specific boundaries. NVIDIA dataset-card attribution, limited to General, STEM and Code domains of HelpSteer3-Preference. The dataset card does not establish contract value, payment terms, an exhaustive supplier list, or contributions to other datasets.

Sources: [429], [440], [461], [464], [468], [483], [484], [485], [486], [487]

Analysis: Scale AI - buyer assessment and unknowns. The strongest artifact examples are release- and subset-specific: HelpSteer annotation and recruitment claims do not make Scale the sole creator of all related data. A pilot should inspect expert matching, automated review and human escalation on the proposed domain. Cumulative payouts and broad platform/BPO channels cannot establish present paid capacity, wages or the revenue of a specific business segment.

Sources: [429], [440], [461], [464], [468], [483], [484], [485], [486], [487]

Evidence: Shaip - offering and scope. Shaip offers end-to-end RLHF preference datasets, rewrites and rationales produced by its own experts.

Sources: [132]

Evidence: Shaip - disclosed delivery and operating model. Shaip says experts calibrate on 100-200 items and enter production only after meeting its agreement threshold. Shaip offers preference-data delivery in JSONL or CSV with a summary of rejection-driving failure modes. Shaip describes matching evaluators to domain and language, with healthcare, legal, finance and code work assigned to credentialed professionals. Shaip describes sampled blind double-labeling, seeded gold pairs and weekly agreement reports during preference collection.

Sources: [132]

Evidence: Shaip - source-specific boundaries. A described onboarding gate, not a measured inter-rater agreement result. Delivery-format offering, not evidence of a completed named engagement.

Sources: [132]

Analysis: Shaip - buyer assessment and unknowns. The disclosed offer specifies preference files, rationales and rejection summaries, with credential matching and a calibration gate. Ask for calibration denominators and raw blind-double-label samples before reading weekly agreement as quality across all attempts. The stated 100-200-item calibration is a process description, not proof of current performance or an independently validated threshold.

Sources: [132]

Evidence: Snorkel AI - offering and scope. Snorkel says it supports text, code, image, audio, video, long-context, and vision-language datasets.

Sources: [489]

Evidence: Snorkel AI - disclosed delivery and operating model. Snorkel Data Series is described as non-exclusive, documented dataset and environment products refreshed quarterly. Snorkel's privacy policy identifies Snorkel AI, Inc. Snorkel's expert community offers authoring, peer review, and comparative evaluation under project instructions and rubrics. Snorkel documents its finance-reasoning benchmark at the captured release; no other financial benchmark relationship is inferred. Snorkel describes screening before project matching and typically advanced-degree, geographic, and independent-contractor eligibility. Snorkel says payment is project-based, accepted contributions are processed weekly through HireArt, and experts may opt into matching projects. Snorkel describes calibration, dual-expert review, consensus, sampling, provenance, and programmatic quality checks. Snorkel states SOC 2 Type 2 compliance and scopes data-access and security controls at engagement start. Snorkel's privacy policy contemplates staffing and workforce partners and client disclosure needed for an expert engagement.

Sources: [488], [489], [490], [491]

Evidence: Snorkel AI - source-specific boundaries. Exact captured page version only; no immutable release identifier or publication date is shown. Its LLM-judge evaluation is separate from expert creation of the questions. Scoped source statement: Snorkel says its Finance Reasoning benchmark contains 79 question-answer pairs co-created with financial experts.

Sources: [488], [489], [490], [491]

Analysis: Snorkel AI - buyer assessment and unknowns. The comparison must distinguish non-exclusive refreshed products from project-specific expert work. Request the exact quarterly version, review rubric, consensus treatment and security scope at engagement start. Expert opt-in and weekly processing of accepted contributions describe participation and payment administration, not guaranteed assignments or realized pay. A finance benchmark attribution does not generalize to all financial data.

Sources: [488], [489], [490], [491]

Evidence: SuperAnnotate - offering and scope. SuperAnnotate provides data-annotation project expertise and service-team support for customized RAG evaluation workflows.

Sources: [57]

Evidence: SuperAnnotate - disclosed delivery and operating model. SuperAnnotate's Databricks case attributes creation of golden datasets for benchmarking LLM judges to their partnership. SuperAnnotate's case describes testing agreement between human evaluators and the model as part of feedback collection. SuperAnnotate reports developing a customized grading rubric with Databricks, including examples and dynamic annotation rules for evaluator consistency. SuperAnnotate's Trust Center lists third-party platform support services, including cloud infrastructure, business communication, analytics and customer support. SuperAnnotate's Trust Center reports SOC 2 Type II assurance and an ISO 27001:2022-certified information-security management system.

Sources: [57], [58]

Evidence: SuperAnnotate - source-specific boundaries. The attribution is a provider-published customer quote and case narrative. It does not identify a public benchmark dataset release or a training contribution to a named foundation model. No numerical accuracy or cost/speed result is adopted as an independent performance finding.

Sources: [57], [58]

Analysis: SuperAnnotate - buyer assessment and unknowns. The Databricks case is a focused reference for human/model-judge calibration and golden dataset construction. A buyer should hold out examples when refining the rubric and measure error types rather than only aggregate agreement. Trust-center statements and platform-support subprocessors describe disclosed controls and dependencies; underlying assurance scope and customer deployment still require diligence.

Sources: [57], [58]

Evidence: Surge AI - offering and scope. Surge offers RLHF data, SFT demonstrations, and human model evaluation. Surge offers data for text, images, audio, and video. Surge offers agentic reinforcement-learning environments and behavior verifiers.

Sources: [494]

Evidence: Surge AI - disclosed delivery and operating model. Surge’s privacy policy identifies the service operator as Surge Labs, Inc. The pinned GSM8K documentation names Surge as a data-collection contributor; re-solving and repair are separately documented stages. The GSM8K card describes re-solving by different workers and repairing or discarding disagreements. Surge markets prebuilt datasets covering RL environments, coding, and core model capabilities. Surge’s privacy policy permits personal-information sharing with service providers including data-labeling providers. Surge’s published 2021 terms grant it a perpetual internal-business and service-improvement license for labeling User Data.

Sources: [492], [493], [494], [495]

Evidence: Surge AI - source-specific boundaries. The card quotes Appendix A of the original paper. It supports expanded collection, not sole authorship of every problem or all initial recruitment. Full paper was not read in this supplier invocation. Scoped source statement: OpenAI’s pinned GSM8K card says Surge AI helped scale data collection after an initial Upwork-collected set.

Sources: [492], [493], [494], [495]

Analysis: Surge AI - buyer assessment and unknowns. The disclosed portfolio combines feedback, demonstrations, licensed data and agent environments. GSM8K is a specific attributed collection and checking case, not evidence that Surge produced every later math dataset. Inspect rights terms closely: the captured 2021 User Data license concerns internal business and service improvement, and its applicability to a new engagement needs contract confirmation.

Sources: [492], [493], [494], [495]

Evidence: TaskUs - offering and scope. TaskUs offers domain-specific data sourcing, structuring and labeling for training sets. TaskUs offers human review that ranks model outputs and refines prompts within model lifecycles.

Sources: [61]

Evidence: TaskUs - disclosed delivery and operating model. TaskUs's Global AI Policy prohibits processing client data or personal information through an AI system without explicit client approval. TaskUs policy requires qualified human review of internal AI recommendations affecting employment and disallows automation as the sole basis for high-stakes employment decisions. TaskUs reports redesigning inconsistent RLHF response reviews for an unnamed European AI company through shared review guidelines and audit/feedback loops.

Sources: [59], [60]

Evidence: TaskUs - source-specific boundaries. A policy obligation does not certify every operation complies. The June 2026 update date is a source label, not a new audit date. This describes the company's AI-use policy; it does not establish contractor pay, assignment continuity or data-labeling labor outcomes.

Sources: [59], [60], [61]

Analysis: TaskUs - buyer assessment and unknowns. The scoped European-client case describes review-process redesign, while policy disclosures require client approval for AI processing and human review of employment recommendations. A pilot should test the actual review loop and approval log. An internal AI policy does not establish a customer dataset's rights, a model's safety or the performance of every delivery team.

Sources: [59], [60], [61]

Evidence: TELUS Digital - offering and scope. The brochure offers crowd-sourced digital data collection, on-site moderated projects and complex field operations. TELUS Digital's AI Data Solutions brochure offers human-aligned datasets generated by domain experts sourced programmatically from Experts Engine, for use with Fine-Tune Studio.

Sources: [62]

Evidence: TELUS Digital - disclosed delivery and operating model. The brochure labels more than one million people as AI Community members across more than 450 global locales. TELUS Digital describes software/process checks, expert human reviews, and contributor qualification and verification as its AI-data quality-assurance approach. The brochure describes secure data handling, SOC 2/TISAX-compliant platforms and ISO 27001-certified labeling facilities. TELUS Digital describes flexible AI-data workforce models including managed crowd, remote, secure in-facility and hybrid delivery.

Sources: [62]

Evidence: TELUS Digital - source-specific boundaries. Community membership is not paid-active headcount, completed assignments, or a current reporting-window labor denominator. Provider-reported compliance/certification; actual certificates, scope and audit reports were not inspected.

Sources: [62]

Analysis: TELUS Digital - buyer assessment and unknowns. The brochure distinguishes crowd, remote, secure-facility and hybrid arrangements. Obtain a proposal specifying which applies, with locale-domain qualifications and review responsibilities. Community membership and locale counts are pool descriptions, not active paid assignments. Security and facility certifications in a brochure should be matched to the particular legal entity, location, platform and project scope.

Sources: [62]

Evidence: Terac - offering and scope. Terac offers verified expert access to human-data companies and frontier labs for post-training, evaluations and red teaming. Terac offers business-workflow partnerships producing training and verification examples within agreed anonymization and approval boundaries.

Sources: [313], [314]

Evidence: Terac - disclosed delivery and operating model. Terac says pay-as-you-go buyers pay expert payout plus its platform fee, with negotiated enterprise packages available. Its partnership page says businesses receive monthly USD payments per verified completion and set worker/business allocation. Terac describes identity, credential and conversational domain checks with ongoing performance scoring.

Sources: [313], [314]

Evidence: Terac - source-specific boundaries. Billing basis only; no actual fee, revenue, gross-versus-net accounting or guaranteed expert income is established. This is business-partner payout policy, not a worker’s stated rate, actual payment proof or promised earnings.

Sources: [313], [314]

Analysis: Terac - buyer assessment and unknowns. The expert-access and workflow-partnership offers have different acceptance units. Clarify the meaning of verified completion, platform fee, worker/business allocation and monthly USD payment before calculating project economics. Screening is a disclosed process, not a credential audit or a guarantee of availability. Agreed anonymization and approval boundaries need record-level tests.

Sources: [313], [314]

Evidence: Toloka - offering and scope. Toloka offers SFT demonstrations, preference data, evaluation datasets, and hybrid synthetic/human data workflows.

Sources: [497]

Evidence: Toloka - disclosed delivery and operating model. Toloka’s notice describes anti-fraud access restrictions and a right to human review of automated decisions. Toloka’s notice bases biometric identity matching on explicit consent and warns that declining verification can prevent onboarding. Toloka discloses that some client coding deliverables may include contributor authorship metadata used in model development, evaluation, or training. Toloka’s notice applies to Toloka AI B.V. and relevant affiliates and covers the Toloka and Mindrift platforms. Toloka says its vetted experts have advanced degrees and industry experience. Toloka’s task guidelines state different conditions for public-space images, third-party personal information, and personal information collected from Tolokers; the third-party rule lists both anonymization before upload and consent agreements. Toloka’s January 2026 self-serve launch describes an AI-assisted pipeline with client-calibrated quality rules and revision routing. Toloka’s task guidelines require advance sensitive-content disclosure and an acknowledgement checkbox before labeling. Toloka describes taxonomy design by domain experts and data architects, followed by human verification of generated data.

Sources: [496], [497], [498], [499]

Evidence: Toloka - disclosed delivery and operating model. The pinned U-MATH card says math experts at Toloka AI and Gradarius validated university-curriculum problems authored by professors. Toloka’s platform distinguishes general annotators, trained AI tutors, and domain experts.

Sources: [498], [500]

Evidence: Toloka - source-specific boundaries. Specific-project policy category; not proof that any named person or particular repository was delivered. No personal contact data is included in these dossiers. These are published platform requirements, not evidence that any particular dataset complied. Conditions are kept separate by task category; third-party anonymization and consent are conjunctive. The linked Guidelines on data collection were not separately captured, so their additional requirements remain unknown.

Sources: [496], [497], [498], [499], [500]

Analysis: Toloka - buyer assessment and unknowns. The disclosed workflow distinguishes general annotators, AI tutors and domain experts and combines synthetic generation with human verification. Keep U-MATH validation separate from professor authorship. A pilot should inspect category-specific personal-data conditions, sensitive-content notice and automated-decision appeals. Biometric consent with onboarding consequences is a documented condition, not evidence of workers’ experience or universal compliance.

Sources: [496], [497], [498], [499], [500]

Evidence: Trajectory Labs, PBC - offering and scope. Trajectory Labs describes creating safety tasks, environments and adversarial examples exposing agent failures. It describes building tools and agent workflows for labs to train and evaluate models.

Sources: [315]

Evidence: Trajectory Labs, PBC - disclosed delivery and operating model. Trajectory describes connecting red teamers, researchers and engineers to frontier-lab projects. Its privacy policy names Trajectory Labs, Public Benefit Corporation and describes the website as informational. Its homepage distinguishes novel expert-discovered attacks from automated testing of known attacks.

Sources: [315], [316]

Evidence: Trajectory Labs, PBC - source-specific boundaries. No named customer contribution, active paid contractor count, pay rate or hiring guarantee is inferred. Website privacy provisions do not resolve customer safety-data contracts, contributor terms or operational security controls.

Sources: [315], [316]

Analysis: Trajectory Labs, PBC - buyer assessment and unknowns. The documented distinction between novel expert attacks and automated known attacks is useful for safety pilot design. Specify threat model, protected information, finding adjudication and retesting, then hold out attack families. Website informational status does not establish customer-processing safeguards. A connection to frontier-lab projects does not identify an unnamed customer or prove comprehensive adversary coverage.

Sources: [315], [316]

Evidence: TrustScale / e2f - offering and scope. Humanus advertises text, audio, image, video and 3D labeling to specification with batch quality review. Humanus offers supervised fine-tuning examples written and reviewed by domain experts in the customer’s field and language. Humanus offers responses ranked and rated by qualified reviewers against customer criteria for RLHF and preference data.

Sources: [334]

Evidence: TrustScale / e2f - disclosed delivery and operating model. The June 16, 2026 official announcement says e2f becomes TrustScale. Humanus describes expert qualification against golden data, reviewer agreement tracking, versioned guidelines and second-reviewer sampling. TrustScale’s published investor page describes it as management-owned and independent, without institutional investor backing. TrustScale’s privacy summary assigns it a processor role for organizational Humanus use, governed by the organization’s agreement including its DPA.

Sources: [334]

Evidence: TrustScale / e2f - source-specific boundaries. The old e2f domain redirects to TrustScale. Both names are one proposed supplier identity. The article is decoded from the exact current public app bundle, not a rendered-page execution. Published process description, not proof it was followed for every task or of any achieved accuracy.

Sources: [334]

Analysis: TrustScale / e2f - buyer assessment and unknowns. TrustScale, e2f and Humanus are retained within one supplier cluster: a disclosed rebrand, organization and product relationship, rather than three competing firms. A pilot should inspect expert-written examples, second-reviewer sampling and golden-data qualification. Management-owned and independent are provider disclosures, not a cap-table audit. The organizational processing summary requires the actual agreement and DPA for customer-specific diligence.

Sources: [334]

Evidence: Turing - offering and scope. Turing Frontier is offered as a platform connecting AI labs with verified US-based scientific and professional experts.

Sources: [503]

Evidence: Turing - disclosed delivery and operating model. Turing describes both AI-lab data and RL-environment work and enterprise agent-development work. Turing’s privacy policy identifies Turing Enterprises, Inc. and its affiliates and subsidiaries. Turing’s experts page advertises more than five million experts and coverage across more than 250 domains. Turing’s California incentive notice describes opt-in participation and withdrawal that applies to future incentive offerings. Turing’s privacy policy lists developing, training, fine-tuning, and prompting AI systems among uses of personal information. The same Turing case reports over 120,000 RLHF preference pairs contrasting compliant actions with named failure modes. Turing describes human-driven sessions in isolated cloud sandboxes with step-level capture across over 150 tools and skills. Turing says Frontier applies identity, background, and work-history verification to experts.

Sources: [501], [502], [503], [504]

Evidence: Turing - source-specific boundaries. Two described lines of activity; not independently reported financial segments. A talent-pool claim, without the number currently active, hired, assigned, or paid. The US-specific Frontier program is not equated with the entire global pool.

Sources: [501], [502], [503], [504]

Analysis: Turing - buyer assessment and unknowns. Separate AI-lab data/environment work from enterprise agent development, and isolate the named case’s sandbox capture and preference-pair deliverables. Step-level traces are useful only if acceptance checks the relevant failure modes and rights. The advertised expert pool and domain count do not establish current paid activity; personal-data uses and opt-in incentive terms require service-specific interpretation.

Sources: [501], [502], [503], [504]

Evidence: V7 / Darwin - offering and scope. Darwin offers AI-assisted labeling with Auto-Annotate and SAM2, video tracking and external-model pre-labeling. Darwin advertises access to specialist annotators including radiologists, pathologists, language experts and native speakers.

Sources: [363]

Evidence: V7 / Darwin - disclosed delivery and operating model. V7's December 17, 2025 Darwin MSA names V7 Ltd. and defines Darwin as its SaaS platform for structuring, labeling, processing, sharing and analyzing customer input data. The Darwin MSA says V7 acts as a reseller for some platform add-on services and does not itself deliver those services. Darwin lets users design multistage review workflows with roles, task assignment and conditional routing.

Sources: [363], [364]

Evidence: V7 / Darwin - source-specific boundaries. Advertised features; comparative speed and accuracy numbers are omitted. Darwin is a V7 product and is not a separate organization.

Sources: [363], [364]

Analysis: V7 / Darwin - buyer assessment and unknowns. Darwin is a V7 product, with software workflow controls and advertised specialist access. The MSA's reseller clause applies to some add-ons, so identify the actual party delivering any annotator service before assigning acceptance responsibility. A pilot should inspect AI drafting, role routing and specialist correction. Advertised radiologist or language access is not evidence that V7 employs that workforce or completed a named delivery.

Sources: [363], [364]

Evidence: Welocalize / Welo Data - offering and scope. Welo Data offers expert-authored instruction-response pairs for supervised fine-tuning and human pairwise preference ranking.

Sources: [67]

Evidence: Welocalize / Welo Data - disclosed delivery and operating model. Welocalize's December 2023 case reports Welo Data rewrote unacceptable LLM outputs and graded model responses for an unnamed foundational-model developer. The 2023 case reports mobilizing more than 9,500 remote workers across more than 35 locales for LLM evaluation workflows. Welo Data describes continuous session monitoring through NIMO and tracking inter-annotator agreement in its managed programs. Welocalize's information-security policy requires security/privacy training for relevant parties and makes adherence mandatory for employees and contractors. The 2023 case says workers were informed about sensitive content and their consent obtained before exposure.

Sources: [65], [66], [67]

Evidence: Welocalize / Welo Data - source-specific boundaries. Historical 2023 engagement, not a current customer or a named model/dataset attribution. Mobilization is not a current paid-active count, annual employment headcount or paid-assignment total. The case has no paid-active reporting window.

Sources: [65], [66], [67]

Analysis: Welocalize / Welo Data - buyer assessment and unknowns. The December 2023 case supports a dated multilingual evaluation and rewriting workflow, including informed sensitive-content exposure. Its mobilized-worker and locale figures are not current workforce totals. A pilot should inspect how NIMO monitoring, agreement metrics and expert-authored SFT interact on the intended locale. Policy training commitments do not substitute for execution or worker-wellbeing evidence.

Sources: [65], [66], [67]

Method: The supplier count applies the graph's offering-based qualification rule. It requires an approved, included, full_source supplier record with its own approved has_capability assertion; it does not count a supplier only because a paper names a contribution. This distinction explains why the following narrow contributor observation can be discussed without becoming another broadly qualified provider dossier.

Evidence: Translated - narrow artifact contribution. The reviewed HelpSteer3 records identify Translated's multilingual annotation and recruitment role. They do not establish the rest of a current general supplier profile, its security controls, commercial terms, staffing availability or responsibility for other HelpSteer subsets. That scoped contribution is retained without inferring a general service catalog or counting a second broad offering from the paper relationship alone.

Sources: [440], [468]

Evidence: BenchFlow - reviewed adjacent software, commercial qualification pending. The pinned README at commit a61a26f4db4d566de16928565ea58abf3dbaf064 describes BenchFlow 0.10, lists task sandbox backends and documents run rewards, token usage, trajectories and a JSONL training-export interface. Its repository LICENSE is Apache-2.0, without licensing every task, dataset or model. The available software does not by itself establish a commercial data-production offer or a delivered customer corpus. Separate captured documentation retains its own earlier version scope; no old receipt is retargeted.

Sources: [319], [320]

Analysis: Dossier-reading qualification: the newly reviewed HelpSteer and HelpSteer2 papers explicitly describe recruitment through Scale AI in their respective pinned versions. They support those scoped reported recruitment/workflow roles, rather than sole artifact authorship, other releases or measured current service quality. Conversely, the surgical QA study keeps its four companies anonymous, so its results cannot be assigned to any named dossier. Software used inside a paper, including LabelAId's Snorkel label model, does not by itself establish a commercial data-service contribution.

Sources: [414], [415], [417], [420]

6. Dataset and benchmark landscape: provenance, versions and use limits

Method: The atlas below covers the qualifying dataset and benchmark families in the approved graph, retaining exact-release observations beneath each family. A family is an intellectual or curation identity, not a sum of files, splits, formats, subsets or every upstream component. Family roll-up supports coverage only; it does not propagate licenses, supplier roles or quality claims across versions. Construction, supervision origin, review process, task unit, access and rights are read together. A benchmark artifact can also be a dataset in ordinary usage, but this coverage calculation keeps its declared family type consistent.

Analysis: For human preference data, compare the actual judgment unit. HelpSteer3 combines task/language configurations and independent preference judgments; HelpSteer2 uses attribute ratings and a closest-rating aggregation process; HH-RLHF preserves chosen/rejected dialogue structure; WebGPT comparisons carry evidence-bearing response material and a documented label convention. A conversion to one chosen/rejected JSONL schema may be technically convenient while losing rating strength, disagreement, evidence or contributor-level independence. Preserve the source fields before transformation and document each derived training view.

Sources: [178], [429], [430], [440], [468]

Analysis: For broad text curation, the lineage unit differs from the label unit. FineWeb documents crawl lineage, filtering and per-crawl deduplication; its educational subset uses model-scored supervision. Dolma reports source-specific deduplication and residual-risk limits. Common Pile applies a distinct inclusion definition for public-domain and openly licensed sources and excludes NonCommercial and NoDerivatives material under that definition. These are contrasting curation choices, not evidence that all three corpora have the same rights or that any one eliminates every privacy or copyright risk.

Sources: [108], [367], [467]

Analysis: For task-rich and composite collections, preserve upstream identity and new contribution separately. DataComp distinguishes a candidate pool, a filtered dataset and training samples seen; FLAN distinguishes datasets, task categories and dataset/category tasks; MathVista combines existing datasets with new sources; MuSiQue’s human-composed questions constitute one family rather than a new family per seed source or answerability serialization. Counting all these units as independent datasets would distort both coverage and an apparent cost-per-example calculation.

Sources: [104], [111], [153], [255], [256]

Analysis: Benchmark protocol is part of the artifact identity. AlpacaEval changes annotator and reference models across versions and provides a length-controlled measure; MT-Bench supports different grading/comparison modes; RewardBench 1 and 2 use different scoring structures; HumanEval's pass@k depends on sample counts. Freeze the exact task set, model outputs, judge, prompt, aggregation and budget when comparing systems. A family name and a headline score alone are insufficient for reproduction or a purchase decision.

Sources: [1], [12], [146], [427], [442]

Analysis: Access and declared license do not automatically establish full rights. GAIA asks against crawlable redistribution and preserves private test information; MathVista restricts training use while retaining underlying source rights; RewardBench requires component-license compliance; MMMU's creator card and collection guidance address different layers of rights. An approved catalogue observation describes what the inspected source says. It is not permission from every underlying rights holder, a legal opinion, or authorization for this report to redistribute the original corpus.

Sources: [142], [153], [160], [161], [427]

Evidence: Dataset-family atlas - AgentInstruct (AgentTuning): construction, signal and protocol. AgentTuning selects six held-in tasks from AgentBench and warns current AgentBench can diverge from the old evaluation code used for paper results. AgentInstruct describes new GPT-4 interaction trajectories filtered with strict task rewards and ReAct-style thought explanations. AgentInstruct card schema stores an id and conversation entries with from, value and boolean loss fields. AgentInstruct reports 1,866 filtered trajectories across ALFWorld, WebShop, Mind2Web, knowledge graph, operating system and database tasks.

Sources: [240], [241]

Evidence: Dataset-family atlas - AgentInstruct (AgentTuning): access, version and interpretation boundaries. AgentInstruct card task table reports an overall 5.24 average turns and per-task averages from 1.00 to 13.52, differing from its broad 5-35 range prose.

Sources: [241]

Evidence: Dataset-family atlas - Align-Anything: construction, signal and protocol. Align-Anything root card describes mixed text, image, video and audio inputs and outputs. Align-Anything reports annotation by GPT-4o, Gemini-1.5-Pro and human crowds. Align-Anything responses include self-constructed methods, open/closed-source model outputs and human-generated answers. Align-Anything uses general and modality-specific fine-grained annotation constitutions. Align-Anything language feedback includes critique and refinement suggestions for responses. Align-Anything root card declares CC-BY-NC-4.0 in metadata.

Sources: [68]

Evidence: Dataset-family atlas - Align-Anything: inspected-source qualification. Reviewed scope: Partial read of the1527-line root creator card: license metadata and complete narrative lines1319-1527. The remaining root YAML schemas and eight captured modality READMEs are unread; no full-family schema or per-subset read is claimed.

Sources: [68]

Evidence: Dataset-family atlas - APPS: construction, signal and protocol. APPS creator-linked card says authors manually curated problems from sites including Codewars, AtCoder, Kattis and Codeforces. APPS card lists 10,000 problems divided into 5,000 training and 5,000 test samples. APPS records contain an English problem, Python solutions, input-output test cases, difficulty, source URL and optional starter code.

Sources: [242]

Evidence: Dataset-family atlas - APPS: access, version and interpretation boundaries. APPS card reports 195 training samples without test cases and 1,235 test samples without ground-truth solutions. The APPS repository MIT file licenses software and associated documentation.

Sources: [242], [243]

Evidence: Dataset-family atlas - Aya Dataset: construction, signal and protocol. Aya reports 138,844 original annotations and 65,270 re-annotations, totaling 204,114 prompt-completion instances. Aya Dataset contains original human-written prompts/completions and human edits of automatically generated prompts/completions, plus anonymized annotator demographics. Aya describes volunteer crowd annotations followed by quality assessment on samples collected during May-December 2023.

Sources: [135]

Evidence: Dataset-family atlas - Aya Dataset: access, version and interpretation boundaries. Aya reports lack of toxic-speech flags and relabeling capabilities, with possible offensive data, incorrect language assignments and instruction-format violations. The Aya Dataset card permits academic or commercial use under Apache 2.0.

Sources: [135]

Evidence: Dataset-family atlas - BeaverTails: construction, signal and protocol. The captured BeaverTails card defines 14 harm categories. BeaverTails is described as human-labeled question-answer data with harm categories, allowing multiple categories per QA pair. The creators describe a safer-AI research purpose and advise against using the dataset to train dialogue agents because of harmful behavior risk. The default distribution lists 330k_train, 330k_test, 30k_train and 30k_test files within round0.

Sources: [2]

Evidence: Dataset-family atlas - BeaverTails: access, version and interpretation boundaries. The card states that BeaverTails and its family are released under CC BY-NC 4.0.

Sources: [2]

Evidence: Dataset-family atlas - BeaverTails: inspected-source qualification. Category labels are scoped to this version and are not interchangeable with the 19-category PKU-SafeRLHF scheme.

Sources: [2]

Evidence: Dataset-family atlas - Capybara: construction, signal and protocol. Capybara uses Amplify-Instruct to extend single-turn seeds into multi-turn synthetic conversations. Capybara creator reports personally vetting many single-turn seed datasets. Capybara filters conversations containing specified AI boilerplate and moralizing phrases. Capybara reports minhash comparisons down to 97% similarity against listed benchmarks. Capybara describes domain-expert volunteer correctness review as a future plan. The pinned Capybara card declares Apache-2.0 in metadata.

Sources: [69]

Evidence: Dataset-family atlas - Capybara: inspected-source qualification. Reviewed scope: Pinned official LDJnr/Capybara card. The metadata pretty_name differs from its official Capybara heading, so identity follows the creator description and repository.

Sources: [69]

Evidence: Dataset-family atlas - Civil Comments / Jigsaw toxicity annotations: construction, signal and protocol. Civil Comments source documentation distinguishes archived comment text from Jigsaw-added toxicity, identity-mention and covert-offensiveness labels. Civil Comments basic seven scores are fractions of crowd annotators assigning each attribute, on a 0-1 scale. The Civil Comments HF basic-label card lists 1,804,874 train, 97,320 validation and 97,320 test examples.

Sources: [244], [245]

Evidence: Dataset-family atlas - Civil Comments / Jigsaw toxicity annotations: access, version and interpretation boundaries. Civil Comments warns parent_text can leak information because splits ignored parent links and original annotators did not see parent text. TFDS warns of a potential CivilCommentsCovert quality issue and says underlying data may change. Civil Comments documentation declares CC0 for both the released dataset and underlying comment text.

Sources: [244]

Evidence: Dataset-family atlas - Code-Feedback: construction, signal and protocol. The Code-Feedback creator card says part of its data is generated by GPT-4-0613 and GPT-3.5-turbo-0613. The OpenCodeInterpreter repository describes Code-Feedback as 68K multi-turn interactions for dynamic code refinement. CodeFeedback seed queries aggregate Magicoder-OSS-Instruct, Python ShareGPT, Magicoder-Evol-Instruct and Evol-Instruct-Code sources. CodeFeedback seed selection uses Qwen-72B-Chat complexity scores from 1-5 and retains 4 or 5.

Sources: [136], [137], [138]

Evidence: Dataset-family atlas - Code-Feedback: access, version and interpretation boundaries. The final Code-Feedback card declares Apache-2.0 and directs users to OpenAI usage policy for generated content.

Sources: [136]

Evidence: Dataset-family atlas - CodeContests: construction, signal and protocol. CodeContests draws programming problems from CodeNet, description2code and Codeforces, with correct and incorrect human solutions. CodeContests distributes ContestProblem protocol buffers in Riegeli files with training, validation and test splits. CodeContests schema defines generated tests as modifications of public/private inputs validated using known correct solutions. CodeContests marks public tests as acceptable model inputs and private tests as unavailable before submission.

Sources: [246], [247]

Evidence: Dataset-family atlas - CodeContests: access, version and interpretation boundaries. CodeContests declares Apache 2.0 for code and CC BY 4.0 for non-code materials, while acknowledging separate component terms. CodeContests warns stored correct/incorrect solutions may compile or execute differently from original contest sites because of compiler, flags or library differences.

Sources: [246]

Evidence: Dataset-family atlas - CoT Collection: construction, signal and protocol. CoT Collection reports 1.84 million chain-of-thought rationales augmented across 1,060 tasks from FLAN. CoT Collection card lists 1,837,928 training rows and trains rationale followed by RESULT and target, parsing predictions after RESULT. CoT Collection repository describes per-subset rationale augmentation scripts using OpenAI API keys and storing rationale outputs separately from merged source data. CoT Collection separates source inputs, ground-truth target answers, explanatory rationales and source-task identifiers.

Sources: [248], [249]

Evidence: Dataset-family atlas - CoT Collection: access, version and interpretation boundaries. The CoT Collection HF card metadata lists CC BY 4.0. The creator CoT Collection repository restricts use to noncommercial purposes and applies OpenAI terms to generated data.

Sources: [248], [249]

Evidence: Dataset-family atlas - Daring-Anteater: construction, signal and protocol. The majority of Daring-Anteater is generated using NVIDIA proprietary models and Mixtral-8x7B-Instruct-v0.1. Daring-Anteater also sources examples from FinQA, WikiTableQuestions and commercially-friendly Open-Platypus subsets. Daring-Anteater is used for SFT before further preference tuning in the HelpSteer2 work. Daring-Anteater exposes conversations, mask, system and dataset-source columns. Daring-Anteater licenses synthetic subsets under CC-BY-4.0 and lists multiple permissive component licenses for Open-Platypus.

Sources: [71]

Evidence: Dataset-family atlas - Daring-Anteater: inspected-source qualification. Reviewed scope: Pinned NVIDIA creator card, including source-by-source license table and schema.

Sources: [71]

Evidence: Dataset-family atlas - Databricks Dolly 15k: construction, signal and protocol. The Dolly card describes more than 15,000 records across eight instruction categories. Dolly contributors were Databricks employees instructed to write prompts and responses without generative AI. Dolly states its succinct guidelines may trade rigorous rubric compliance for high task completion. Dolly uses contributor-selected Wikipedia passages for information extraction, closed QA and summarization; no passage-selection guidance was given.

Sources: [139]

Evidence: Dataset-family atlas - Databricks Dolly 15k: access, version and interpretation boundaries. Dolly declares CC BY-SA 3.0 for the collection and credits Wikipedia editors/contributors for included material.

Sources: [139]

Evidence: Dataset-family atlas - FineWeb: construction, signal and protocol. The paper-described FineWeb release is produced from 96 Common Crawl snapshots and contains about 15 trillion GPT-2-tokenized tokens. The FineWeb datasheet states that the released dataset still includes significant numbers of documents that may be toxic or harmful. The final FineWeb pipeline uses individual per-crawl MinHash deduplication. The FineWeb-Edu classifier is trained on 410,000 model-scored pages, with 50,000 held out for validation against the synthetic scores. Llama-3-70B-Instruct assigns educational-quality scores from zero to five to 460,000 sampled webpages used to develop FineWeb-Edu filtering.

Sources: [467]

Evidence: Dataset-family atlas - FineWeb: inspected-source qualification. This is the release described by the pinned 2024 paper, not a current mutable Hub snapshot. Common Crawl sourcing does not establish a commercial supplier contract.

Sources: [467]

Evidence: Dataset-family atlas - GSM8K: construction, signal and protocol. The initial thousand GSM8K problems and solutions were collected through freelance contractors on Upwork; the authors then worked with Surge AI to scale data collection. The paper describes GSM8K as math problems and natural-language solutions created by human writers, with optional GPT-3-generated seed questions available to those writers. After collection, workers re-solved GSM8K problems they had not originally written; answer disagreements were repaired or discarded, followed by another agreement check on a smaller subset. Released problems use question and answer fields; calculation annotations occur in answers and the final numeric solution follows ####. The README describes 8.5K grade-school mathematics problems created by human problem writers, segmented into 7.5K training and 1K test problems. The separate Socratic format inserts model-generated subquestions before contractor-provided solution steps; the creators say it was not used in paper experiments.

Sources: [7], [63]

Evidence: Dataset-family atlas - GSM8K: access, version and interpretation boundaries. The provided example model solutions retain occasional calculator errors because earlier implementation bugs were fixed without regenerating the samples. The pinned Grade School Math repository contains an MIT license.

Sources: [6], [7]

Evidence: Dataset-family atlas - GSM8K: inspected-source qualification. These exact collection roles do not establish a provider-specific fraction beyond the stated initial pool or a current commercial contract.

Sources: [6], [7], [63]

Evidence: Dataset-family atlas - HelpSteer2: construction, signal and protocol. Human ratings cover helpfulness, correctness, coherence, complexity and verbosity on a 0-4 scale; dedicated preference labels and justifications complement the ratings. The card describes 3-5 independent annotators, aggregation of the three closest ratings and subsequent vendor and creator quality assurance. Prompts are mostly user-contributed ShareGPT, with approximately 5% human generated by Scale AI; responses come from ten early in-house LLMs.

Sources: [429]

Evidence: Dataset-family atlas - HelpSteer2: inspected-source qualification. Agreement filtering removes some disagreement; released disagreement annotations are separately identified.

Sources: [429]

Evidence: Dataset-family atlas - HelpSteer3: construction, signal and protocol. Each HelpSteer3-Preference sample is assigned to 3 to 5 independent human annotators for preference feedback. Postprocessing retains the three most agreeing preference annotations and excludes samples when their remaining disagreement is greater than two preference-strength points. The pinned collection contains Preference, Feedback, Edit, Edit-Quality and Principle configurations. Preference contains 40,476 samples with pairwise preference scores and individual concise reasons; card specifies a 95%/5% train/validation split.

Sources: [440], [468]

Evidence: Dataset-family atlas - HelpSteer3: access, version and interpretation boundaries. HelpSteer3-Preference does not contain samples at intersections of its General, STEM, Code and Multilingual areas.

Sources: [468]

Evidence: Dataset-family atlas - HelpSteer3: inspected-source qualification. Humans choose preference direction/strength or invalidity and provide brief justifications. The paper permits internet fact-checking but prohibits LLM tools during annotation.

Sources: [440], [468]

Evidence: Dataset-family atlas - HH-RLHF: construction, signal and protocol. Preference modeling artifacts contain chosen/rejected response pairs; helpfulness includes base, rejection-sampled and online tranches while harmlessness uses base-model data. Creator intends preference data for reward-model RLHF training and distinguishes red-team transcripts from preference-model and dialogue-agent fine-tuning data. The study recruited US master-qualified MTurk workers and Upwork contractors, using writing spot-checks and lightweight vetting.

Sources: [430], [446]

Evidence: Dataset-family atlas - HH-RLHF: access, version and interpretation boundaries. The study did not select workers by direct label-agreement metrics and reports approximately 63% researcher-worker agreement retrospectively.

Sources: [446]

Evidence: Dataset-family atlas - HH-RLHF: inspected-source qualification. Historical study-specific measurement, not a general platform quality claim.

Sources: [430], [446]

Evidence: Dataset-family atlas - HotpotQA: construction, signal and protocol. HotpotQA creators ask MTurk workers to write questions requiring reasoning over introductions of two Wikipedia articles. HotpotQA fullwiki dev context replaces gold paragraphs with the baseline retriever top ten, which may omit gold evidence. HotpotQA JSON defines question, answer, supporting title/sentence IDs and paragraph contexts, with answers/support omitted from test. HotpotQA creators separately collect supporting facts so QA models can learn from explicit evidence annotations.

Sources: [250], [251]

Evidence: Dataset-family atlas - HotpotQA: access, version and interpretation boundaries. HotpotQA declares CC BY-SA 4.0 for the dataset and Apache 2.0 for code.

Sources: [251]

Evidence: Dataset-family atlas - Human Preference Dataset (HPD/HPS): construction, signal and protocol. HPD v2 reports about 798k pairwise comparisons over 430k images/107k prompts, including 645k training pairs and 153k test pairs. HPD v2 asks human annotators to rank images generated by different models for the same prompt. HPD v2 sources prompts from DiffusionDB and MSCOCO Captions and cleans DiffusionDB prompts with ChatGPT. HPD v2 test schema includes averaged image ranks and per-annotator raw rank/user_hash records; training schema has human_preference, prompt and file paths.

Sources: [252]

Evidence: Dataset-family atlas - Human Preference Dataset (HPD/HPS): access, version and interpretation boundaries. The official HPDv2 card declares Apache 2.0 for the dataset. HPS v2 documentation says image-score comparisons are meaningful only for the same prompt and v2.0/v2.1 scores cannot be directly compared.

Sources: [252], [253]

Evidence: Dataset-family atlas - ImageRewardDB: construction, signal and protocol. All ImageRewardDB images are collected from DiffusionDB and grouped by their shared prompt. ImageRewardDB describes 137k expert comparison pairs over DiffusionDB prompts and model outputs, with its own assessment, annotator-training and quality-validation pipeline. ImageRewardDB metadata rows describe one image with prompt linkage, relative rank, overall rating, image-text alignment rating and fidelity rating. ImageRewardDB provides four train scales while keeping validation and test fixed across them.

Sources: [254]

Evidence: Dataset-family atlas - ImageRewardDB: access, version and interpretation boundaries. The ImageRewardDB card declares Apache 2.0 for the dataset and separately links MIT for Python code.

Sources: [254]

Evidence: Dataset-family atlas - Intel Orca DPO Pairs: construction, signal and protocol. Intel assigns OpenOrca completions generated by GPT-4 or GPT-3.5 as chosen responses. Intel generates corresponding rejected completions automatically with Llama-2-13b-chat. Intel documents selecting 12K examples from OpenOrca for the preference dataset. Intel documents DPO as a second stage after supervised fine-tuning for Neural Chat v3-1.

Sources: [148], [149]

Evidence: Dataset-family atlas - Intel Orca DPO Pairs: access, version and interpretation boundaries. The Intel Orca DPO Pairs card declares Apache-2.0.

Sources: [149]

Evidence: Dataset-family atlas - LMSYS-Chat-1M: construction, signal and protocol. LMSYS-Chat-1M logs conversations from the Vicuna demo and Chatbot Arena between April and August 2023. LMSYS-Chat-1M reports obtaining user consent through the collection website terms of use. LMSYS-Chat-1M reports PII removal and person-name redaction that can introduce incorrect redactions. LMSYS-Chat-1M explicitly states that benchmark decontamination was not run. LMSYS-Chat-1M has a custom agreement with model-specific terms and restrictions on third-party dataset transfer.

Sources: [72]

Evidence: Dataset-family atlas - LMSYS-Chat-1M: inspected-source qualification. Reviewed scope: Pinned lmsys/lmsys-chat-1m card, with full custom agreement and explicit non-decontamination statement.

Sources: [72]

Evidence: Dataset-family atlas - Magpie: construction, signal and protocol. Magpie generates queries and responses from aligned LLM pre-query templates without seed questions. The reviewed Magpie-Pro-300K-Filtered release is generated by Llama 3 70B Instruct. The reviewed Magpie Pro release filters quality, instruction reward, repetition and incomplete instructions, then selects long responses. The Magpie card warns against jointly fine-tuning its Pro filtered and Pro multi-turn releases because first turns largely overlap. The reviewed Magpie Pro release card declares llama3 in metadata. The official Magpie repository advertises a CC BY NC 4.0 data license badge.

Sources: [73], [74]

Evidence: Dataset-family atlas - Magpie: inspected-source qualification. Reviewed scope: Pinned release card plus pinned official magpie-align/magpie README and code license. Card-specific claims are limited to Llama-3 70B Pro filtered data.

Sources: [73], [74]

Evidence: Dataset-family atlas - Math-Shepherd: construction, signal and protocol. Math-Shepherd defines label as the problem and solution with automatic step labels. Math-Shepherd uses plus for a good step that can lead to the correct answer and minus for a bad step. Math-Shepherd instances have input, label and task fields, with input comprising problem plus step-by-step solution. Math-Shepherd PRM loss is computed only at the special ки step-score positions.

Sources: [152]

Evidence: Dataset-family atlas - Math-Shepherd: access, version and interpretation boundaries. The Math-Shepherd card says its internal step-wise PPO training code cannot be open sourced, while SFT/PRM/RL checkpoints are provided.

Sources: [152]

Evidence: Dataset-family atlas - MedInstruct: construction, signal and protocol. MedInstruct describes 52,000 synthetic instruction/response pairs and a separate set of 217 clinical free-form evaluation tasks. The MedInstruct creator card says GPT-3.5-turbo synthesizes a response for each instruction. MedInstruct creator card describes 167 clinician-crafted seed tasks for GPT-4 instruction generation. AlpaCare documents clinician-evaluated 1-5 medical difficulty only for MedInstruct-test.

Sources: [158], [159]

Evidence: Dataset-family atlas - MedInstruct: access, version and interpretation boundaries. The MedInstruct creator card declares CC BY-NC 4.0. The AlpaCare repository schema names text-davinci-003 for output, while its response-generation section names GPT-3.5-turbo.

Sources: [158], [159]

Evidence: Dataset-family atlas - MuSiQue: construction, signal and protocol. MuSiQue README says its questions are composed from SQuAD, T-REx, Natural Questions, MLQA and Zero Shot RE seed questions. MuSiQue uses MTurk workers to write coherent new multi-hop questions from DAGs of source single-hop questions after checking bridge-entity identity. MuSiQue downloads contain train/dev/test for answerable and full configurations plus dev/test source single-hop IDs. MuSiQue authors selected 17 workers after a 100-worker, 20-example qualification round and sampled 10-20 examples per worker across nine annotation batches. MuSiQue says its model-development raw format differs from official released data only in field names/format, not qualitative content.

Sources: [255], [256]

Evidence: Dataset-family atlas - MuSiQue: access, version and interpretation boundaries. MuSiQue warns dev/test seed single-hop questions may already appear in seed training sets and releases exclusion IDs to mitigate leakage. MuSiQue README declares CC BY 4.0 for the dataset.

Sources: [255]

Evidence: Dataset-family atlas - MuSiQue: inspected-source qualification. Creator original methods statement, pinned by exact PDF body SHA256; method-page partial read only. TACL section5 stepS7, printedp545/PDFpage7. New human wording and entity checks support distinct annotation/content construction; single-hop text/paragraphs remain inherited.

Sources: [255], [256]

Evidence: Dataset-family atlas - Nectar: construction, signal and protocol. The card describes Nectar response rankings as GPT-4-generated seven-way comparisons. The good_natured prompt label is parsed from GPT-4 classification and is described as an approximation. The ranking rubric prioritizes harmlessness and also helpfulness for prompts classified as good natured. The card reports 182,954 prompts with seven responses per prompt.

Sources: [13]

Evidence: Dataset-family atlas - Nectar: access, version and interpretation boundaries. The card combines an Apache-2.0 declaration conditioned against competing with OpenAI with a later non-commercial research-preview statement and upstream model/data terms.

Sources: [13]

Evidence: Dataset-family atlas - Nectar: inspected-source qualification. GPT-4 ranking is generated supervision; human-origin source prompts do not make these preference labels human annotations.

Sources: [13]

Evidence: Dataset-family atlas - No Robots: construction, signal and protocol. No Robots is described as 10,000 instructions and demonstrations created by skilled human annotators, mostly single-turn. No Robots exposes prompt, prompt_id, role/content messages and category. The No Robots card lists 9,500 training and 500 test examples.

Sources: [163]

Evidence: Dataset-family atlas - No Robots: access, version and interpretation boundaries. No Robots leaves the annotation-process and annotator-identity sections as More Information Needed. No Robots declares CC BY-NC 4.0.

Sources: [163]

Evidence: Dataset-family atlas - NuminaMath: construction, signal and protocol. NuminaMath-CoT collects problems and reference solutions from exam PDFs and mathematics forums before OCR, translation and CoT processing. NuminaMath uses GPT-4o to translate and realign extracted solutions into CoT format with final-answer formatting. Some NuminaMath World Olympiad PDFs were manually segmented before OCR. NuminaMath reports exact-match and embedding decontamination with exceptions for MATH training and synthetic data. NuminaMath acknowledges challenges validating synthetic problem correctness and incomplete CoT detail on hard problems. The NuminaMath-CoT card declares Apache License 2.0.

Sources: [75], [76]

Evidence: Dataset-family atlas - NuminaMath: inspected-source qualification. Reviewed scope: Full pinned CoT card; partial textual read of pinned 16-page creator report (pages1-8 and12). Remaining experiment pages, references and visuals are not claimed fully reviewed.

Sources: [75], [76]

Evidence: Dataset-family atlas - OpenAI Summarize from Feedback: construction, signal and protocol. The OpenAI repository reports 64,832 TL;DR summary comparisons plus TL;DR comparison/Likert evaluation and CNN/DM Likert evaluations. The repository reserves valid2 labels for final evaluation because valid1 posts/articles were used for model selection. Summary comparisons are JSONL records of two summaries with choice, worker, batch and split metadata. The comparison note fields contain worker-written naive interpretations before seeing the post, with possible later edits.

Sources: [171]

Evidence: Dataset-family atlas - OpenAI Summarize from Feedback: access, version and interpretation boundaries. The repository attributes the original TL;DR source dataset to Syed et al. and declares it CC BY 4.0.

Sources: [171]

Evidence: Dataset-family atlas - OpenAssistant Conversations (OASST1 reviewed release): construction, signal and protocol. The ready-for-export subset has 88,838 messages in 10,364 trees and excludes spam/deleted messages; the all export contains 161,443 messages in 66,497 trees. Project guidance distinguishes writing, classifying and ranking tasks, with factual accuracy and helpfulness prioritized when judging assistant replies. The card describes 161,443 messages in 35 languages and 461,292 quality ratings from more than 13,500 volunteers in the full April 2023 corpus.

Sources: [431], [436]

Evidence: Dataset-family atlas - OpenAssistant Conversations (OASST1 reviewed release): inspected-source qualification. Guidelines are documented instructions, not independent proof every annotator complied.

Sources: [431], [436]

Evidence: Dataset-family atlas - OpenCodeInstruct: construction, signal and protocol. The OpenCodeInstruct card characterizes both data collection and labeling as automated/synthetic. OpenCodeInstruct reports five million coding question-answer pairs for supervised fine-tuning. OpenCodeInstruct defines generic/algorithmic domains and self-instruct/evol-instruct generation_algorithm values. OpenCodeInstruct stores LLM response judgments, assertion-list unit tests, pass/fail execution status and fraction of tests passed.

Sources: [164]

Evidence: Dataset-family atlas - OpenCodeInstruct: access, version and interpretation boundaries. NVIDIA declares OpenCodeInstruct under CC BY 4.0 and assigns users responsibility to check fitness of each dataset license for intended use.

Sources: [164]

Evidence: Dataset-family atlas - OpenHermes: construction, signal and protocol. The listed mixture sources include Airoboros 2.2, GPT-4-only ChatBot Arena and ShareGPT, Evol Instruct, MetaMath, and SlimOrca. The dataset is documented in ShareGPT-style conversations with from and value fields, with source metadata present in many examples. The card describes OpenHermes 2.5 as a continuation of OpenHermes 1 reaching about one million primarily synthetically generated instruction and chat samples.

Sources: [14]

Evidence: Dataset-family atlas - OpenHermes: access, version and interpretation boundaries. For the CoT Alpaca GPT4 component, the card says the source page was lost.

Sources: [14]

Evidence: Dataset-family atlas - OpenHermes: inspected-source qualification. This is creator-reported component provenance; source inclusion does not establish procurement or supplier contribution.

Sources: [14]

Evidence: Dataset-family atlas - OpenMathInstruct: construction, signal and protocol. OpenMathInstruct-1 problems come from the GSM8K and MATH training subsets. OpenMathInstruct-1 solutions are generated by Mixtral using text reasoning and Python code blocks. OpenMathInstruct-1 is_correct records final-answer correctness according to a grading script. OpenMathInstruct-1 train and validation subsets jointly cover the GSM8K and MATH training sets. The NVIDIA license requires its license text and existing notices to accompany redistribution of the work.

Sources: [77], [78]

Evidence: Dataset-family atlas - OpenMathInstruct: inspected-source qualification. Reviewed scope: Pinned NVIDIA OpenMathInstruct-1 card plus full NVIDIA LICENSE. No OpenMathInstruct-2 corpus or documentation is claimed reviewed.

Sources: [77], [78]

Evidence: Dataset-family atlas - OpenOrca: construction, signal and protocol. OpenOrca questions are sourced from the FLAN Collection. OpenOrca response fields contain GPT-3.5 or GPT-4 completions. The OpenOrca card reports approximately 1M GPT-4 completions and 3.2M GPT-3.5 completions. The pinned OpenOrca card states that the data are unsplit. The pinned OpenOrca card declares MIT in dataset metadata.

Sources: [79]

Evidence: Dataset-family atlas - OpenOrca: inspected-source qualification. Reviewed scope: Pinned Open-Orca/OpenOrca creator card; it calls the dataset a partial, ongoing completion of its intended distribution.

Sources: [79]

Evidence: Dataset-family atlas - OpenR1-Math: construction, signal and protocol. OpenR1-Math card metadata lists 225,129 all, 93,733 default and 131,396 extended training examples. OpenR1-Math describes prompting R1 on 400k source problems with two solutions per problem, sometimes four, and a 16k token generation limit. OpenR1-Math generates two-to-four DeepSeek-R1 reasoning traces for NuminaMath 1.5 problems. OpenR1-Math uses Math Verify for most answer checks and Llama-3.3-70B-Instruct as judge for 12% of samples.

Sources: [257]

Evidence: Dataset-family atlas - OpenR1-Math: access, version and interpretation boundaries. OpenR1-Math says its extended configuration adds sources such as cn_k12 and performed worse after SFT than default in creator experiments. OpenR1-Math declares Apache 2.0 for the dataset.

Sources: [257]

Evidence: Dataset-family atlas - OpenThoughts: construction, signal and protocol. The 114k card metadata lists 113,957 training examples in both default and metadata configurations. OpenThoughts metadata separates problem, ground_truth_solution, deepseek_reasoning, deepseek_solution, domain, source and code-only test_cases/starter_code. OpenThoughts-114k generates reasoning traces with DeepSeek-R1 from a curated source mixture and reports correctness verification. OpenThoughts-114k lists code collections, NuminaMath-CoT, CAMEL science and RiddleSense as sources.

Sources: [165]

Evidence: Dataset-family atlas - OpenThoughts: access, version and interpretation boundaries. The OpenThoughts-114k card declares Apache-2.0.

Sources: [165]

Evidence: Dataset-family atlas - Pick-a-Pic: construction, signal and protocol. Pick-a-Pic collects real users’ prompts and preferences over two generated images, allowing a tie. Pick-a-Pic paper identifies Stable Diffusion2.1, Dreamlike Photoreal2.0 and Stable Diffusion XL variants as image generators. Pick-a-Pic reports user authentication, activity monitoring, bans and NSFW phrase filters as data-quality controls. Pick-a-Pic paper forms validation/test data from unique-user prompts and excludes their prompts from training. Pick-a-Pic creator distinguishes original v1 data from v2 with more than one million examples. PickScore repository MIT terms apply to software and associated documentation.

Sources: [80], [81], [82]

Evidence: Dataset-family atlas - Pick-a-Pic: inspected-source qualification. Reviewed scope: Full pinned creator family card, PickScore README and code LICENSE; partial textual read of NeurIPS2023paper pages1-6and10. Dataset v1 API endpoint returned401; v1/v2 data access is not established.

Sources: [80], [81], [82]

Evidence: Dataset-family atlas - PKU-SafeRLHF: construction, signal and protocol. The card defines 19 harm categories and labels each question-answer pair with one or more categories. The card describes 83.4K preference entries with two responses per question, safety meta-labels, and separate human-preference dimensions of helpfulness and harmlessness. Helpfulness and harmlessness are ranked separately, with harmless responses always ranked above harmful responses in the harmlessness ranking. The documented responses come from Alpaca-7B, Alpaca2-7B and Alpaca3-8B; the latter two are described as Llama2-7B and Llama3-8B fine-tuned with Alpaca 52K.

Sources: [17]

Evidence: Dataset-family atlas - PKU-SafeRLHF: access, version and interpretation boundaries. The current card declares CC-BY-NC-4.0.

Sources: [17]

Evidence: Dataset-family atlas - PKU-SafeRLHF: inspected-source qualification. The 19-category current scheme must not be silently substituted for BeaverTails 14-category scheme.

Sources: [17]

Evidence: Dataset-family atlas - PRISM Alignment Dataset: construction, signal and protocol. PRISM participants complete a demographic/preference survey, then write prompts, rate LLM responses and give fine-grained conversational feedback. PRISM terms prohibit re-identification and warn that raw conversations can be unsafe or offensive. PRISM randomly selects four of 21 backend LLMs for the opening turn and asks participants to score responses from 1 to 100. PRISM utterance JSONL is a long-format presentation of the same conversations and repeats user inputs across candidate responses. PRISM reports 8,011 conversation trees and 68,371 rated human-prompt/model-response/score utterances.

Sources: [258]

Evidence: Dataset-family atlas - PRISM Alignment Dataset: access, version and interpretation boundaries. PRISM licenses human-written text under CC BY 4.0 and model responses under CC BY-NC 4.0, with original model-provider terms also applying.

Sources: [258]

Evidence: Dataset-family atlas - PRM800K: construction, signal and protocol. The paper describes the full unfiltered PRM800K release as 1,085,590 step-level labels over 101,599 solutions; the filtered training data contains about 800,000 labels over 75,000 solutions. Human labelers provide positive, negative or neutral judgments on steps in model-generated MATH solutions. The repository documents a nonstandard MATH split adding 4,500 original test problems to training and evaluating on the remaining 500 held-out problems. PRM800K is documented as 800,000 step-level correctness labels on model-generated solutions to MATH problems. The README describes human step ratings of -1, 0 or +1 and permits a human-written replacement step in phase 1 when all completions were rated -1. The documented annotation schema reserves common gold-labeled solutions for quality control and 30 initial screening questions for base task performance.

Sources: [16], [51]

Evidence: Dataset-family atlas - PRM800K: access, version and interpretation boundaries. The pinned PRM800K repository contains an MIT license.

Sources: [15]

Evidence: Dataset-family atlas - PRM800K: inspected-source qualification. These are paper-described raw versus filtered populations, not an independently counted downloaded release.

Sources: [15], [16], [51]

Evidence: Dataset-family atlas - ProsocialDialog: construction, signal and protocol. ProsocialDialog reports 58K dialogues, 331K utterances, 160K unique rules of thumb and 497K safety labels with free-form rationales. ProsocialDialog creator repo says HF dataframe and direct list-of-dialogues downloads differ only in format and contain the same content. ProsocialDialog creates new dialogues by having GPT-3 generate unsafe utterances and crowdworkers write prosocial responses. ProsocialDialog schema keeps final safety verdicts, three workers raw safety annotations and each workers free-form reasons. ProsocialDialog source field identifies socialchemistry, SBIC, ethics_amt and ethics_reddit seed text origins.

Sources: [259], [260]

Evidence: Dataset-family atlas - ProsocialDialog: access, version and interpretation boundaries. ProsocialDialog card declares CC BY 4.0 for the dataset.

Sources: [259]

Evidence: Dataset-family atlas - RichHF-18K: construction, signal and protocol. RichHF-18K reports 17,760 TensorFlow Examples: 15,810 training, 995 development and 955 test. RichHF-18K annotates generated images from Pick-a-Pic v1 and ships filenames rather than original image files. RichHF-18K releases newly collected subjective scores, human-labeled artifact heatmaps and prompt misalignment-token labels. RichHF examples contain filename, four scalar scores, artifact_map, misalignment_map and prompt_misalignment_label. RichHF defines all scores so higher is better; a higher artifact score means fewer artifacts.

Sources: [261]

Evidence: Dataset-family atlas - RLAIF-V: construction, signal and protocol. RLAIF-V metadata identifies a labeling model providing feedback for chosen and rejected answer pairs. RLAIF-V instructions draw from MSCOCO, ShareGPT-4V, MovieNet, Google Landmark v2, VQA v2, OKVQA and TextVQA. RLAIF-V also uses RLHF-V image-description prompts for long-form captioning. RLAIF-V card reports 83,132 preference pairs. The RLAIF-V card declares CC-BY-NC-4.0.

Sources: [83]

Evidence: Dataset-family atlas - RLAIF-V: inspected-source qualification. Reviewed scope: Pinned openbmb/RLAIF-V-Dataset card, including2024release and2025usage updates. Linked paper and source datasets were not read.

Sources: [83]

Evidence: Dataset-family atlas - RLHF-V: construction, signal and protocol. RLHF-V collects fine-grained segment-level human corrections for visual description and question-answering instructions. The RLHF-V card reports 5,733 preference pairs. RLHF-V January2024 expansion adds outputs from stronger models and image domains including WikiArt, landmarks and scene text. RLHF-V text data contains question, chosen and rejected entries. The RLHF-V card declares CC-BY-NC-4.0.

Sources: [84]

Evidence: Dataset-family atlas - RLHF-V: inspected-source qualification. Reviewed scope: Pinned openbmb/RLHF-V-Dataset creator card and its update history, including January2024 expanded correction release.

Sources: [84]

Evidence: Dataset-family atlas - Self-Instruct: construction, signal and protocol. The filtered GPT-3 davinci Self-Instruct corpus in this paper contains 52,445 instructions and 82,439 input/output instances. Self-Instruct starts with 175 author-written seed tasks and prompts the language model to generate further instructions and input/output instances. A single expert coauthor evaluates one randomly selected instance for each of 200 randomly sampled instructions; Table2 reports 54% with all fields valid.

Sources: [56]

Evidence: Dataset-family atlas - Self-Instruct: inspected-source qualification. These are distinct units and a paper-described corpus, not an independently recounted download.

Sources: [56]

Evidence: Dataset-family atlas - Social Bias Inference Corpus (SBIC): construction, signal and protocol. SBIC reports 82.4% pairwise agreement and average Krippendorff alpha of 0.45. SBIC adds structured categorical and free-text bias-implication annotations to social-media posts, with over 150k annotations and over 34k implications in its summary. SBIC splits posts together with their three annotation sets to keep a post from appearing across train/validation/test. SBIC card describes three MTurk annotations per post, with conditional target-group questions and two-to-four written stereotypes per selected group.

Sources: [262]

Evidence: Dataset-family atlas - Social Bias Inference Corpus (SBIC): access, version and interpretation boundaries. SBIC warns that predominantly White-aligned English and dialect/identity labeling bias should constrain deployment. The SBIC card declares Creative Commons Attribution 4.0.

Sources: [262]

Evidence: Dataset-family atlas - Stanford Alpaca: construction, signal and protocol. The Alpaca datasheet reports 52,002 instances and defines instruction, optional input, and text-davinci-003 output fields. Stanford Alpaca modifies Self-Instruct by using text-davinci-003 and generating one instance per instruction. The Alpaca datasheet warns that some generated instructions may be nonsensical and admit no good response. The Alpaca datasheet says all 52K examples were used for its models and recommends no dataset split.

Sources: [169], [170]

Evidence: Dataset-family atlas - Stanford Alpaca: access, version and interpretation boundaries. The same-revision Alpaca datasheet instead describes distribution under ODC-By. The pinned Alpaca README declares CC BY-NC 4.0 and research-only use for the dataset and models trained on it.

Sources: [169], [170]

Evidence: Dataset-family atlas - Stanford Human Preferences (SHP): construction, signal and protocol. SHP uses naturally occurring human-written Reddit posts/comments and collectively inferred preference labels rather than separately elicited individual pairwise ratings. SHP splits by post ID and includes 385,563 preference pairs across 18 subreddits, with 348,718 train, 18,436 validation and 18,409 test pairs in the card table.

Sources: [432]

Evidence: Dataset-family atlas - Stanford Human Preferences (SHP): access, version and interpretation boundaries. The card documents Reddit scraping terms and user ownership but does not grant a standard permissive dataset license.

Sources: [432]

Evidence: Dataset-family atlas - Stanford Human Preferences (SHP): inspected-source qualification. Do not assert the disputed timestamp-ordering direction.

Sources: [432]

Evidence: Dataset-family atlas - Super-NaturalInstructions: construction, signal and protocol. Natural Instructions documents a community effort to create tasks and natural-language definitions/instructions. The contribution instructions require JSON formatting tests and a maximum of 6.5K instances per task. Natural Instructions task JSON includes contributor/source fields, definitions, positive/negative examples and input-output instances. The official benchmark split trains on a subset of tasks and evaluates remaining unseen tasks for cross-task generalization.

Sources: [172]

Evidence: Dataset-family atlas - Super-NaturalInstructions: access, version and interpretation boundaries. Natural Instructions releases data other than task instances under Apache-2.0; instances retain original-dataset licenses in Instance License fields.

Sources: [172]

Evidence: Dataset-family atlas - TabMWP: construction, signal and protocol. TabMWP creators describe a new dataset containing 38,431 tabular math word problems. Each TabMWP question has a table represented as an image, semi-structured text and a structured table. TabMWP provides free-text/multiple-choice questions and gold solutions intended to reveal multistep reasoning.

Sources: [263]

Evidence: Dataset-family atlas - TabMWP: access, version and interpretation boundaries. TabMWP project documentation distinguishes 38,431 problems from 28,876 different questions and 35,442 different solutions. The TabMWP README explicitly licenses the dataset under CC BY-NC-SA 4.0.

Sources: [263], [264]

Evidence: Dataset-family atlas - TACO: construction, signal and protocol. TACO credits APPS and CodeContests for some source material while also describing manual curation from additional programming sites. TACO reports 26,443 problems with 25,443 training and 1,000 test samples. TACO schema describes tags as manually annotated algorithms needed to solve the problem and skill_types as mapped programming skills. TACO card says some test-set test cases were removed or modified and asks users to update to the newest version.

Sources: [265]

Evidence: Dataset-family atlas - TACO: access, version and interpretation boundaries. TACO declares Apache 2.0 for authored dataset contributions while acknowledging MIT/CC BY 4.0 material and explicitly unknown HackerRank legal rights/data license.

Sources: [265]

Evidence: Dataset-family atlas - ToxicChat: construction, signal and protocol. ToxicChat adds toxicity annotations to about 10K user prompts from the Vicuna demo through a human-AI collaborative annotation framework. ToxicChat 0124 reports 10,165 user prompts and 5,654 human annotations. For ToxicChat 0124, creator-reported error-analysis fixes were each checked by two annotators, and 20 additional examples received human annotation. ToxicChat schema separately stores user_input, model_output, human_annotation, toxicity, jailbreaking and OpenAI moderation output.

Sources: [266]

Evidence: Dataset-family atlas - ToxicChat: access, version and interpretation boundaries. ToxicChat warns that some personal information may remain despite creator removal attempts and prohibits identifying individuals. ToxicChat licenses both user prompts and model outputs under CC BY-NC 4.0.

Sources: [266]

Evidence: Dataset-family atlas - Tülu 3 SFT Mixture: construction, signal and protocol. The card prose reports 939,344 samples, while its dataset_info train metadata declares 939,343 examples. The card lists crowdsourced, expert-generated and machine-generated annotation creators and multiple source datasets. The card states that the Tülu 3 SFT mixture was used to train the Tülu 3 model series. Each documented mixture example contains an id, messages with user prompts and assistant responses, and a source dataset field.

Sources: [18]

Evidence: Dataset-family atlas - Tülu 3 SFT Mixture: access, version and interpretation boundaries. The collection declares ODC-BY-1.0, with different subset licenses, some non-commercial portions, and separate terms for third-party model outputs.

Sources: [18]

Evidence: Dataset-family atlas - Tülu 3 SFT Mixture: inspected-source qualification. The collection declaration must not be flattened into permission for every component; the card presents a research artifact.

Sources: [18]

Evidence: Dataset-family atlas - UltraChat: construction, signal and protocol. UltraChat uses separate ChatGPT Turbo APIs for generated user queries and assistant responses. UltraChat says Internet-available data are not directly used as prompts. UltraChat reports post-processing and filtering of generated dialogues. UltraChat covers world questions, writing and creation, and assistance on existing materials. The pinned UltraChat card declares MIT in dataset metadata.

Sources: [85]

Evidence: Dataset-family atlas - UltraChat: inspected-source qualification. Reviewed scope: Original creator card at stingning/ultrachat; multi-round conversations. No corpus files or linked repository implementation were read.

Sources: [85]

Evidence: Dataset-family atlas - UltraFeedback: construction, signal and protocol. GPT-4 annotates completions for instruction-following, truthfulness, honesty and helpfulness, providing numerical and textual feedback. The creator samples instructions from UltraChat, ShareGPT, Evol-Instruct, TruthfulQA, FalseQA and FLAN, then samples four models from a 17-model pool per instruction.

Sources: [433]

Evidence: Dataset-family atlas - UltraFeedback: access, version and interpretation boundaries. The repository documents a December 2023 correction of faulty overall-score values using fine-grained-score thresholds and re-annotation for remaining cases.

Sources: [449]

Evidence: Dataset-family atlas - UltraFeedback: inspected-source qualification. README-level evidence only; named implementation path returned 404 at this commit.

Sources: [433], [449]

Evidence: Dataset-family atlas - UltraInteract: construction, signal and protocol. The pinned pairwise distribution declares 219,522 training examples with trajectory, chosen, rejected, id and parent_id fields. The card reports approximately 86K instructions, 286K correct answers and 219K preference pairs. Correct actions and correct-ending trajectories are described as SFT material; paired correct and incorrect nodes or trajectories support preference learning. UltraInteract is documented as reasoning preference trees combining reasoning chains, environment interaction trajectories, critique and pairwise data.

Sources: [19]

Evidence: Dataset-family atlas - UltraInteract: access, version and interpretation boundaries. The pairwise card declares an MIT license.

Sources: [19]

Evidence: Dataset-family atlas - UltraInteract: inspected-source qualification. The declaration is scoped to this distribution; linked source-dataset licenses were not exhaustively reviewed.

Sources: [19]

Evidence: Dataset-family atlas - UltraMedical: construction, signal and protocol. UltraMedical combines adapted public sources with customized synthetic MedQA-Evol, TextBookQA and WikiInstruct data. UltraMedical card metadata lists 409,593 training examples, while narrative rounds the collection to 410,000 samples. UltraMedical documents manual or GPT-4 synthetic questions, GPT-4 responses, original answer keys and GPT-3.5-turbo instruction scores.

Sources: [177]

Evidence: Dataset-family atlas - UltraMedical: access, version and interpretation boundaries. UltraMedical authors acknowledge hallucinations/GPT-4 bias and describe verifying factual accuracy as future research. The UltraMedical card declares MIT.

Sources: [176], [177]

Evidence: Dataset-family atlas - VideoFeedback: construction, signal and protocol. VideoFeedback includes text-video pairs from eleven video-generative models plus real-world video augmentation. VideoFeedback creator describes human-provided multiaspect video scores. VideoFeedback ratings cover visual quality, temporal consistency, dynamic degree, text-video alignment and factual consistency on a 1-4 scale. VideoFeedback is used to train the VideoScore evaluator. The VideoFeedback dataset card declares Apache-2.0.

Sources: [86], [87], [451]

Evidence: Dataset-family atlas - VideoFeedback: inspected-source qualification. Reviewed scope: Pinned TIGER-Lab/VideoFeedback card and pinned official VideoScore README/LICENSE. Corrected the initial mistaken PKU-Alignment repository path; no source identity substitution in final claims.

Sources: [86], [87], [451]

Evidence: Dataset-family atlas - VLFeedback: construction, signal and protocol. VLFeedback preference annotations are produced by GPT-4V. VLFeedback samples have four responses selected from a pool of twelve LVLMs. VLFeedback annotations cover helpfulness, visual faithfulness and ethical considerations. VLFeedback card schema stores ratings and rationales under each completion annotation. The VLFeedback creator uses its dataset for DPO on a Qwen-VL-Chat backbone to obtain Silkie.

Sources: [88], [89]

Evidence: Dataset-family atlas - VLFeedback: inspected-source qualification. Reviewed scope: Pinned MMInstruction/VLFeedback card and pinned vlf-silkie/VLFeedback README. Embedded workflow/source diagrams and linked paper were not inspected.

Sources: [88], [89]

Evidence: Dataset-family atlas - WebGPT Comparisons: construction, signal and protocol. WebGPT quotes fields store model-found browsing extracts and source-page titles, while answers are composed using those quotes. WebGPT examples pair model answers to a question with human preference scores. WebGPT score_0 ranges from -1 to 1, sums to zero with score_1, uses zero as a soft 50% label and other scores by sign as hard labels. The WebGPT card describes all comparisons marked suitable for reward modeling by project end, totaling 19,578 comparisons. WebGPT token fields use GPT-2 tokenization of a truncated question-plus-quotes prefix and final answer completion for reward modeling.

Sources: [178]

Evidence: Dataset-family atlas - WildChat: construction, signal and protocol. WildChat collects human user conversations by offering free GPT-3.5 and GPT-4 access. The reviewed WildChat-1M variant removes conversations flagged toxic by OpenAI Moderation or Detoxify. WildChat de-identifies data using Microsoft Presidio and author-written rules. WildChat uses ODC-BY, whose license does not cover independent rights in individual database contents. WildChat documents empty user inputs that can cause hallucinated assistant responses.

Sources: [90], [91]

Evidence: Dataset-family atlas - WildChat: inspected-source qualification. Reviewed scope: Pinned allenai/WildChat-1M card and full LICENSE.md. Version changes include July 2024 toxic-content removal and October 2024 PII-related removals.

Sources: [90], [91]

Evidence: Dataset-family atlas - WildJailbreak: construction, signal and protocol. WildJailbreak transforms vanilla harmful prompts with 2-7 mined tactics using Mixtral-8×7B/GPT-4, filters low-risk/off-topic results and reuses counterpart vanilla refusals. WildJailbreak separately documents 210 adversarial benign and 2,000 adversarial harmful evaluation examples. WildJailbreak training schema exposes vanilla, adversarial, tactics, completion and four-way data_type fields. WildJailbreak describes 262K synthetic vanilla/adversarial prompt-response pairs with both harmful and superficially harmful-looking benign queries. WildJailbreak uses GPT-4 for vanilla harmful/benign prompts and GPT-3.5 for refusal or complying responses.

Sources: [267]

Evidence: Dataset-family atlas - WildJailbreak: access, version and interpretation boundaries. WildJailbreak public card declares ODC-BY and conditions dataset access on AI2 Responsible Use acceptance and completion of identity/intended-use fields.

Sources: [267]

Evidence: Benchmark-family atlas - AgentBench: construction, signal and protocol. For the Mind2Web browsing component, the reported primary metric is step success from element/action matching rather than whole-task success; this paper uses top-10 candidates and CoT few-shot prompts. The initial AgentBench paper defines eight environment families: operating systems, databases, knowledge graphs, digital card games, lateral-thinking puzzles, house-holding, web shopping and web browsing. For OS tasks, about half of instructions are human-created or collected; the other half are mainly GPT-4-generated QA tasks filtered by execution-based checks. Eight programming annotators select and construct human tasks.

Sources: [20]

Evidence: Benchmark-family atlas - AgentBench: inspected-source qualification. The setup differs from the antecedent top-50 Mind2Web setting.

Sources: [20]

Evidence: Benchmark-family atlas - AlpacaEval: construction, signal and protocol. The release documents about 20K human preference annotations, including 2.5K cross-annotations from four annotators over roughly 650 examples. AlpacaEval 2.0 uses weighted_alpaca_eval_gpt4_turbo as annotator with gpt4_turbo reference outputs; the original uses alpaca_eval_gpt4 with text_davinci_003. Length-controlled win rates fit a preference model including output-length difference and average counterfactual preferences at zero length difference.

Sources: [1]

Evidence: Benchmark-family atlas - AlpacaEval: access, version and interpretation boundaries. The README declares Apache-2.0 for code and CC BY-NC 4.0 for data. The creators caution that the instruction set may miss advanced usage, automatic evaluators can favor style over factuality, and AlpacaEval does not measure model harms.

Sources: [1]

Evidence: Benchmark-family atlas - AlpacaEval: inspected-source qualification. The code/data declarations are separate; this is not an audit of every upstream output provider term.

Sources: [1]

Evidence: Benchmark-family atlas - GAIA: construction, signal and protocol. The October 2025 GAIA format update replaces former JSONL-backed loading with Parquet splits and per-level views. GAIA describes more than 450 questions divided into three levels, with public validation/dev and tests having private answers and metadata. GAIA preserves task_id, Question, Level, Final answer, file_name, file_path and Annotator Metadata columns, with relative attachment paths. GAIA is documented as evaluating LLMs augmented with tools, prompting and search access.

Sources: [142]

Evidence: Benchmark-family atlas - GAIA: access, version and interpretation boundaries. GAIA public metadata asks users not to reshare the dataset outside gated/private HF repositories and the card asks against crawlable validation/test redistribution.

Sources: [142]

Evidence: Benchmark-family atlas - GPQA: construction, signal and protocol. The creator baseline code instructions distinguish closed-book prompting from Bing-based retrieval modes and expose a seed for shuffling answer choices. GPQA questions are written by domain experts in biology, physics and chemistry, with experts defined as people having or pursuing a PhD in the field. The original study describes 546 Extended questions, 448 main questions and 198 Diamond questions, with the latter two curated subsets. The collection pipeline uses first expert validation, writer revision, second expert validation and three non-expert validators from other domains with web access but no LM assistants.

Sources: [4], [5]

Evidence: Benchmark-family atlas - GPQA: access, version and interpretation boundaries. The pinned GPQA creator repository contains an MIT license.

Sources: [3]

Evidence: Benchmark-family atlas - GPQA: inspected-source qualification. Prompt type, subset, retrieval access and answer-order seed must be matched for comparison; no evaluation was run.

Sources: [3], [4], [5]

Evidence: Benchmark-family atlas - HarmBench: construction, signal and protocol. HarmBench evaluates whether each completion instantiates its corresponding behavior using separate text and multimodal classifier models. The HarmBench protocol uses max_new_tokens=512 for target completions and warns other limits can hinder comparisons. HarmBench accepts a behavior-dataset CSV and saves test cases under method/experiment directories with optional behavior-ID selection. HarmBench evaluates attack success rate through test-case generation, target-model completions and completion evaluation.

Sources: [143]

Evidence: Benchmark-family atlas - HarmBench: access, version and interpretation boundaries. The HarmBench repository contains an MIT license.

Sources: [144]

Evidence: Benchmark-family atlas - Helpful, Honest & Harmless alignment evaluation: construction, signal and protocol. HHH examples were written by contributors and each evaluation received discussion and approval from at least one other co-author. The pinned task evaluates binary response comparisons in helpfulness, honesty, harmlessness and other categories using multiple_choice_grade.

Sources: [426], [445]

Evidence: Benchmark-family atlas - Helpful, Honest & Harmless alignment evaluation: inspected-source qualification. Approval denotes the historical benchmark authors process, not independent ScienceToStartup review.

Sources: [426], [445]

Evidence: Benchmark-family atlas - HumanEval: construction, signal and protocol. HumanEval computes per-problem pass@k estimates from generated-sample counts and correct counts, then averages only when each problem has at least k samples. HumanEval predictions are JSONL records with task_id and completion-only text excluding the prompt. The pinned HumanEval evaluation function defaults to k=[1,10,100], four workers and a three-second correctness timeout. The OpenAI repository identifies HumanEval as a hand-written evaluation set with a harness for problem solving.

Sources: [146], [147]

Evidence: Benchmark-family atlas - HumanEval: access, version and interpretation boundaries. The pinned HumanEval repository contains an MIT license.

Sources: [145]

Evidence: Benchmark-family atlas - Humanity’s Last Exam: construction, signal and protocol. The documented simple evaluation defaults to temperature zero and advises at least 8,192 completion tokens for reasoning models. The pinned evaluator defaults to o3-mini-2025-01-31 and asks the judge to extract the final answer and compare it with the provided correct answer. The creator README describes HLE as a multimodal benchmark with 2,500 expert-developed multiple-choice and short-answer questions across dozens of subjects.

Sources: [8], [10]

Evidence: Benchmark-family atlas - Humanity’s Last Exam: access, version and interpretation boundaries. The pinned HLE repository contains an MIT license. The README overview describes 2,500 questions, while its sample evaluation output displays n = 2700.

Sources: [9], [10]

Evidence: Benchmark-family atlas - Humanity’s Last Exam: inspected-source qualification. This code/repository declaration does not establish the license of unretrieved HLE question content.

Sources: [8], [9], [10]

Evidence: Benchmark-family atlas - JailbreakBench: construction, signal and protocol. JailbreakBench provides a Llama3 70B jailbreak judge and a Llama3 8B refusal judge. JailbreakBench curates original behaviors and behaviors from TDC/HarmBench and AdvBench against a usage-policy taxonomy. JailbreakBench describes 300 judge-comparison examples with three human judge labels, majority labels and model-judge labels. JailbreakBench submissions record attack success rate and hyperparameters such as target, attacker, judge and token budgets. JailbreakBench documents 100 harmful behaviors and 100 thematically similar benign behaviors.

Sources: [150]

Evidence: Benchmark-family atlas - JailbreakBench: access, version and interpretation boundaries. The pinned JBB-Behaviors card says the dataset, like the code, is released under MIT.

Sources: [151]

Evidence: Benchmark-family atlas - MathVista: construction, signal and protocol. The official MathVista pipeline generates responses, extracts short answers using an LLM such as GPT-4, then calculates scores. MathVista reports 6,141 examples from 28 existing multimodal datasets plus newly created IQTest, FunctionQA and PaperQA. The pinned MathVista scorer normalizes extracted answers by answer type, compares to references, and computes correct/total accuracy. The MathVista card documents testmini with 1,000 development/validation examples and test with 5,141 standard-evaluation examples whose answers are not publicly released.

Sources: [153], [154], [155]

Evidence: Benchmark-family atlas - MathVista: access, version and interpretation boundaries. MathVista warns the third-party EvalScope workflow can differ in prompts, extraction and normalization and lacks a same-prediction parity report. MathVista declares CC BY-SA 4.0 for new contributions while original authors retain image/question copyright; it permits commercial test use and prohibits training use.

Sources: [153]

Evidence: Benchmark-family atlas - MBPP: construction, signal and protocol. MBPP describes around 1,000 crowdsourced entry-level Python problems, each with task description, solution and three automated tests. The MBPP study used three-shot prompts from task IDs 2, 3 and 4, with tests in the prompt and BEGIN/DONE solution delimiters. MBPP says a subset was hand verified by the creators and distributed as sanitized-mbpp.json. MBPP assigns task IDs 11-510 to testing, 1-10 to prompting, 511-600 to validation and 601-974 to training.

Sources: [156]

Evidence: Benchmark-family atlas - MBPP: access, version and interpretation boundaries. The pinned google-research monorepo LICENSE is Apache License 2.0.

Sources: [157]

Evidence: Benchmark-family atlas - MMLU: construction, signal and protocol. Graduate and undergraduate students manually collected the benchmark’s questions from freely available online sources. The paper designs MMLU as a text-only academic and professional question benchmark. The pinned HF distribution describes 57 multiple-choice subjects with a five-example development set per subject.

Sources: [441], [463]

Evidence: Benchmark-family atlas - MMLU: inspected-source qualification. Sources include examination practice questions and educational material; the paper does not identify a commercial annotation supplier for this collection.

Sources: [441], [463]

Evidence: Benchmark-family atlas - MMMU: construction, signal and protocol. MMMU reports 11.5K multimodal questions collected from college exams, quizzes and textbooks across 30 subjects and 183 subfields. MMMU permits either final-answer files with user parsing or creator response parsing, and warns results can differ due to random selection for failed responses. MMMU documents 150 development samples for few-shot learning, 900 validation samples for model/debug tuning and 10,500 test samples. At the pinned 2026 repository revision, MMMU says test answers/explanations are released for local evaluation with answer_dict_test.json.

Sources: [160], [162]

Evidence: Benchmark-family atlas - MMMU: access, version and interpretation boundaries. MMMU says annotator guidelines required obeying source copyright/license rules and avoiding sites forbidding copying/redistribution, with removal after verified complaints. The MMMU creator HF card declares Apache-2.0.

Sources: [160], [161]

Evidence: Benchmark-family atlas - MT-Bench: construction, signal and protocol. The creators report releasing 3.3K human annotations for six models answering 80 MT-Bench questions. FastChat also supports pairwise comparisons against a baseline and across all model pairs. The recommended default is GPT-4 single-answer grading on a ten-point scale per turn, averaged over all turns. MT-Bench is documented as challenging multi-turn open-ended chat-assistant questions evaluated using an LLM judge.

Sources: [12]

Evidence: Benchmark-family atlas - MT-Bench: access, version and interpretation boundaries. The pinned FastChat repository LICENSE is Apache License 2.0.

Sources: [11]

Evidence: Benchmark-family atlas - MT-Bench: inspected-source qualification. This records the repository license; separate dataset-specific or upstream-content terms were not established.

Sources: [11], [12]

Evidence: Benchmark-family atlas - OSWorld: construction, signal and protocol. OSWorld evaluate() fetches result/expected state and invokes configured metric functions; multiple metrics use configured and/or combination. OSWorld warns missing Google-account/OAuth or proxy configuration can cause task execution failures and lower scores. OSWorld screenshot-baseline examples specify screenshot observations, a 15-step limit and a three-second post-action wait. OSWorld loads task id, instruction, setup config and an evaluator defining metric functions and result/expected getters.

Sources: [166], [167]

Evidence: Benchmark-family atlas - OSWorld: access, version and interpretation boundaries. The OSWorld repository declares Apache License 2.0. OSWorld announces OSWorld-Verified fixes and asks comparisons against new results when using the latest version.

Sources: [167], [168]

Evidence: Benchmark-family atlas - RewardBench (additional family): construction, signal and protocol. V1 succeeds when a chosen response receives a higher score than its rejected alternative; section aggregation weights prompts and balances math against code. V2 averages six categories; five compare one chosen response against three rejected responses while Ties uses a distinct correctness-and-margin metric.

Sources: [427], [442]

Evidence: Benchmark-family atlas - RewardBench (additional family): access, version and interpretation boundaries. RewardBench declares ODC-BY aggregation while requiring users to follow the licenses of its components, including listed noncommercial sources.

Sources: [427]

Evidence: Benchmark-family atlas - RewardBench (additional family): inspected-source qualification. Not comparable to v1 pairwise scores without a matched protocol.

Sources: [427], [442]

Evidence: Benchmark-family atlas - SWE-bench: construction, signal and protocol. Candidate task instances must include at least one test changing from fail before the reference solution to pass after it. The original full SWE-bench evaluation set contains 2,294 issue/PR-derived task instances from 12 Python repositories. The benchmark’s task instances in this paper are all in Python. A submitted patch counts as solved only when all reference FAIL TO PASS and PASS TO PASS tests pass. The original dataset tests repository issue resolution with 2,294 test issue/PR pairs from twelve Python repositories and uses test verification against post-PR behavior. The repository describes SWE-bench Verified as 500 engineer-confirmed solvable problems in collaboration with OpenAI Preparedness.

Sources: [443], [447], [466]

Evidence: Benchmark-family atlas - SWE-bench: inspected-source qualification. The pipeline also removes installation/runtime failures; tests come from the corresponding merged PR. This is execution-based benchmark filtering, not fresh human preference labels.

Sources: [443], [447], [466]

Evidence: Benchmark-family atlas - TruthfulQA: construction, signal and protocol. TruthfulQA's 817 benchmark questions were written by the paper's authors. TruthfulQA combines 437 questions filtered against GPT-3-175B with 380 additional questions not tested on that target model. The creator repository describes a January 2025 binary multiple-choice setting using Best Answer and Best Incorrect Answer with randomized A/B order. The pinned HF distribution has generation and multiple_choice configurations of the same 817 questions. Generation evaluates truthfulness and informativeness separately; original MC1 accuracy and MC2 probability-mass metrics measure different behaviors.

Sources: [444], [448], [450]

Evidence: Benchmark-family atlas - TruthfulQA: access, version and interpretation boundaries. TruthfulQA questions were authored rather than collected from a deployed system. Creator documentation says some questions were removed or revised and full validation of the remaining questions and sources was not completed.

Sources: [448], [450]

Evidence: Benchmark-family atlas - TruthfulQA: inspected-source qualification. Questions are designed to elicit imitative falsehoods across 38 categories; this is authored challenge material, not sampled deployment traffic.

Sources: [444], [448], [450]

Evidence: Benchmark-family atlas - WebArena: construction, signal and protocol. Authors contribute intents; authors and an external annotator curate information-seeking answers with two annotations and a third annotator resolving disagreement. Three authors contribute programmatic checks for the remaining tasks. The original paper-described benchmark contains 812 instantiated intents derived from 241 templates. WebArena uses standalone self-hosted website implementations with sampled real-world data to support reproducible evaluation without depending on live website changes.

Sources: [64]

Evidence: Benchmark-family atlas - WebArena: inspected-source qualification. Section3.2 also permits ChatGPT inspiration for intents; this is not an exclusively unaided-human task-generation claim.

Sources: [64]

Evidence: Benchmark-family atlas - WebShop: construction, signal and protocol. WebShop defaults to loading 1,000 products for preview and documents changing paths to load all products. WebShop reports 1.18 million real-world products and 12,087 crowdsourced text instructions in a simulated e-commerce task. WebShop setup downloads 50 randomly chosen MTurk-worker trajectories, and session logs store one instruction/web session with search/click steps. WebShop supports HTML and simple observation modes; simple removes extraneous metadata to ease training/evaluation.

Sources: [179]

Evidence: Benchmark-family atlas - WebShop: access, version and interpretation boundaries. The WebShop LICENSE.md is MIT for software and associated documentation.

Sources: [179], [180]

Evidence: Benchmark-family atlas - τ-bench: construction, signal and protocol. τ-bench also requires listed task outputs to appear case-insensitively in agent responses after removing commas, or sets reward to zero. The pinned τ-bench evaluator compares the final database hash with the hash produced by replaying reference task actions, assigning zero when they differ. τ-bench emulates conversations between a model-simulated user and a language agent with domain-specific APIs and policy guidelines. τ-bench defaults to gpt-4o as an llm-strategy user simulator and permits other models/strategies.

Sources: [174], [175]

Evidence: Benchmark-family atlas - τ-bench: access, version and interpretation boundaries. The pinned τ-bench repository contains an MIT license. The τ-bench README marks its airline/retail tasks outdated and directs users to successor repositories for fixed tasks.

Sources: [173], [175]

Method: Atlas interpretation: a source can document a dataset’s declared license, retained record count or human-checking procedure without this study inspecting every row or reproducing a training run. Unknown or restrictive licensing is a catalogue finding rather than an instruction to retrieve or redistribute the corpus. Empty taxonomy facets remain unknown. A release’s disclosed aggregate count can coexist with a README/example inconsistency; both are retained instead of silently manufacturing a reconciled number.

Analysis: Reference-label provenance should accompany benchmark protocol. The label-error study uses model screening followed by five-worker judgments and distinguishes ambiguous or unknown cases from correctable alternatives. Gilardi evaluates only texts on which two trained annotators agree; HelpSteer2 removes remaining high-spread responses. These are different decisions about which items enter a score. A buyer should retain the original denominator, review-selection rule and accepted reference rather than compare the resulting percentages as if they measured the same difficulty distribution.

Sources: [413], [415], [418]

Analysis: A paper’s dataset statistics are evidence about its described release, rather than independent confirmation of a current download. Aya separates original annotations from re-annotations and imposes a language inclusion threshold. WildChat v1 contains two unreconciled conversation totals, which this synthesis preserves. These additional paper reviews do not add another dataset family here. A future artifact inspection should bind the exact bytes, reconcile paper/card/repository counts and preserve component lineage before changing family or release accounting.

Sources: [407], [425]

7. Human expertise, recruitment, disagreement and labor

Analysis: Expertise has at least four operational components: eligibility, task familiarity, calibrated judgment and permission to perform the work. The inspected sources use different proxies: Turing describes identity/background/work-history verification; Shaip describes credentials and a calibration gate; Encord describes task-to-domain matching; Prolific offers verified experience or targeted assessments. These are not one standardized credential. For each task, ask which evidence predicts successful completion and which screening merely establishes identity or administrative eligibility.

Sources: [109], [132], [477], [503]

Analysis: Recruitment and contribution remain separate stages. HelpSteer3 names different recruitment/annotation roles for Scale and Translated; Prolific’s studied role is recruitment into a researcher-owned interface; U-MATH credits Toloka AI and Gradarius with validation of professor-authored problems. A contributor manifest should record authoring, recruitment, labeling, review, adjudication and final release authority separately. Affiliation, acknowledgments or a capability page alone should not be used to infer a contribution edge.

Sources: [468], [478], [500]

Analysis: The human experiment on instruction-tuning disagreement uses the same annotators and items for individual ratings and paired preferences, yet reports different ambiguity patterns and no evidence in that setup that preference annotation is easier. This cautions against assuming that a change from scales to pairs resolves judgment ambiguity. A pilot should test the intended formulation with representative difficult items, retain task-specific reasons and distinguish unclear instructions from legitimate preference diversity.

Sources: [107]

Analysis: DICES separates two rater pools and applies explicit quality exclusions, while its expert reference can disagree with crowd majority. The Minority Reports paper defines a minority relative to final majority consensus and warns that RLHF preference tasks may lack a single clear ground truth. Together these sources support keeping minority labels inspectable. They do not establish that every disagreement is valuable or that a majority is always wrong. The analyst recommendation is to adjudicate the reason for disagreement before filtering the person who expressed it.

Sources: [106], [395]

Evidence: The approved Minority Reports pruning observation is scoped to the §5.1 prose: unseen workers or tasks are retained, while otherwise the estimated minority-report probability is compared with a threshold. The reviewed Algorithm 1 line and surrounding prose have a documented consistency concern in the source review. This report does not certify that pseudocode and prose are equivalent. The simulation reference compares post-pruning majority votes with the counterfactual unpruned majority, rather than establishing an external truth label for every judgment.

Sources: [395]

Analysis: Calibration and adjudication should have separate logs. Appen describes gold questions and adjudication; DataForce describes automated checks, consensus and expert adjudication; Snorkel describes calibration and dual-expert review; Shaip describes sampled blind double-labeling and weekly agreement reports. Request the raw judgments before consensus, the rule for escalation, the adjudicator’s independence and the number of corrected accepted units. A final agreement percentage is a process output whose meaning depends on those rules, not a universal reliability score.

Sources: [26], [132], [469], [489]

Analysis: Training instructions are themselves a research input. The reviewed factorial study crosses instruction design with incentives and measures accuracy, helpfulness and difficulty separately. Data Cascades examines high-stakes data-work failures; CrowdWorkSheets asks why an annotator pool fits intended uses and impacted communities. These works motivate testing guideline clarity and the consequences of exclusion before scaling. They do not establish a universal wage or training-duration effect for all suppliers. Intervention results should retain task, sample, payment and outcome definitions.

Sources: [101], [374], [386]

Analysis: Multilingual coverage must be tested at the intersection of language, domain, rubric and modality. HelpSteer3 identifies missing domain intersections; M-IFEval removes language-inappropriate constraints and uses native-speaker leads; BenchMAX uses human post-editing of translations; MENLO separates fluency, tone and localized factuality. Translation of a single English benchmark is not evidence that every language variant measures the same construct. A buyer should sample required intersections and use native-domain review before claiming coverage.

Sources: [366], [375], [376], [468]

Analysis: Model-judge agreement is also conditional. The multilingual-judge study uses parallel ground-truth answers, pointwise criteria and a particular prompting setup, with cross-language consistency measured by treating language-specific judgments as raters. M-RewardBench translates general-task instances with human-reviewed filtering and separately uses human-rated translation pairs. These are different validation designs. Neither supports an unqualified conclusion that an English-calibrated judge is reliable in every locale or that translated evaluation is equivalent to native task authoring.

Sources: [379], [381]

Analysis: Pool statistics should not become labor statistics. Appen’s global crowd, Mercor’s advertised expert network, Turing’s advertised pool, TELUS Digital’s community membership and Prolific’s active/waitlist figures have different definitions. None should be converted into the number of people who earned money this week, the number available for a specific assignment or the number of accepted tasks. A useful labor ledger distinguishes registered profiles, screened people, matched people, active paid contributors, attempted units, accepted units and paid units under explicit windows.

Sources: [62], [470], [474], [479], [502]

Analysis: Workforce arrangement changes the questions to ask. Sama describes full-time in-house delivery; TELUS Digital lists several workforce modes; Alegion describes workforce partners; Scale describes BPOs and proprietary platforms; isahit describes self-employed onboarding. These descriptions cannot establish legal status or worker experience across jurisdictions. For a project, record the contracting entity, subcontracting chain, training obligation, supervision, payment authority and appeal channel rather than assume the same conditions from a shared annotation label.

Sources: [55], [62], [93], [117], [483]

Analysis: Compensation disclosures concern different units and conditions. Prolific publishes permitted minimum and recommended participant hourly rates; Handshake puts amount, type and timing in project invitations; Humans in the Loop uses supervisor-approved delivered units; Snorkel processes accepted contributions weekly; micro1 states a twice-monthly schedule. These are rules or schedules, not comparable realized wages. Any labor analysis should count qualification, waiting, revisions, rejections and administrative time separately and retain the project's currency and payment basis.

Sources: [113], [201], [209], [479], [488]

Analysis: Sensitive-content and monitoring rules deserve operational evidence. Scale describes notice, the ability to decline and wellness resources; Toloka requires disclosure and acknowledgement before labeling; the dated Welo case describes informed consent; Invisible discloses keystroke, screenshot and webcam collection with possible access consequences if declined. These sources describe different settings. They do not prove that every worker could safely refuse, obtained support or experienced proportionate monitoring. A buyer should request project notices, escalation handling and aggregate worker-feedback evidence without seeking unnecessary personal records.

Sources: [39], [65], [483], [496]

Analysis: Labor research has its own sampling limits. The Data-Production Dispositif combines interviews, observation and instruction-document analysis in specific Latin American settings; the Latin American labor article states that unknown platform-population boundaries limit statistical representativeness; the requester-proxy study limits its conclusions to US requester perspectives and self-reports. These studies illuminate mechanisms and research questions. They should not become global percentages, a census of all workers or evidence that a named supplier currently practices every behavior described.

Sources: [370], [394], [399]

Research gap: Important labor unknowns remain: independently measured effective pay, qualification rejection and appeal outcomes, subcontractor payment reconciliation, harmful-content exposure, contributor retention and the relation between monitoring and acceptance. The public-source corpus does not resolve these for the covered market. Research can progress through consented worker studies, project-level anonymized logs and comparable definitions, while avoiding inference from registered pools or recruitment advertisements.

Analysis: Disagreement routing should distinguish uncertainty from error. Experts Rise uses cross-model entropy to select expert attention, while Inherent Disagreements models multiple interpretations of the same short sentence pairs. CrowdTruth defines mutually dependent consistency scores but leaves broader comparative validation open. The practical choice is whether the task seeks one verifiable answer, a distribution of valid interpretations or a codebook revision. Record that choice before using disagreement to exclude workers, remove items or declare a quality improvement.

Sources: [409], [411], [416]

Analysis: Instruction design and assistance need separate acceptance checks. The surgical study's comparison is conditional on instruction richness and project-specific QA; LabelAId's intervention improves precision within a 34-person study without an equivalence finding on time. Neither supports a general staffing reduction. In a proposed pilot, log instruction revisions, assistance shown, human corrections and downstream acceptance, then inspect whether the intervention changes errors or merely which cases remain. Preserve any effect on contributor effort and disagreement as part of the operating record.

Sources: [417], [420]

8. Commercial evidence and procurement economics

Evidence: Appen - reported revenue. The audited FY2025 statements report consolidated customer-contract revenue of USD 230.774 million for 1 January-31 December 2025, including Appen Global USD 127.874 million and Appen China USD 102.900 million. These geographic operating segments do not isolate expert generative-AI data or the market definition used in this report. The figures are full-year reported revenue, not annualized pace, gross transaction volume, contributor pay or a comparable human-feedback segment across suppliers.

Sources: [470]

Evidence: Proximal - annualized pace. Its 29 September 2026 announcement reports $200 million in annualized revenue. The inspected disclosure does not specify an ISO currency code, annualization window, gross-versus-net basis or revenue split by business line. It is self-reported pace, not an audited annual revenue total, profit, bookings, valuation or contractor payout. No annual recognized-revenue amount is calculated from it in this report.

Sources: [223]

Evidence: Scale - cumulative contributor payout. Its FY2025 statement, approved in June 2026, reports nearly $1 billion paid to hundreds of thousands of contributors across more than 150 countries to date. The statement does not define a start/end period or a dollar currency code for that aggregate, and payment reconciliation was not inspected. The number is not annual revenue, annual labor cost, a current paid-active workforce total or a wage estimate.

Sources: [483]

Evidence: Labelbox - financing and valuation. The 14 October 2026 company announcement reports more than $100 million in Series E financing comprising equity and a credit facility, at a $1.25 billion pre-money valuation. The inspected source uses dollar symbols without an explicit ISO currency. The facility is not equity, and financing and valuation are not revenue or evidence of accepted data volume. No implied annual growth or provider-performance score is calculated.

Sources: [44]

Evidence: Prolific - tariff and reward rules. The captured FAQ states usual platform fees of 42.8% for corporate customers and 33.3% for academic/nonprofit customers, but the bound passage does not explicitly state the percentage denominator. It separately sets minimum participant rewards of GBP 6 or USD 8 per hour and recommends GBP 9 or USD 12, with higher expert compensation recommended. Managed services are custom-priced. These are published rules and tariff disclosures rather than realized earnings, margins or a complete specialist-project quote.

Sources: [479]

Evidence: Other disclosed billing units differ. Prime Intellect’s Model Factory terms meter allocated GPU-hours prorated to the second, with rates in the order or platform; personnel post-training needs a separate professional-services order. A.Team lists hourly and other builder-engagement models. Terac describes expert payout plus a platform fee and separately monthly USD payment per verified completion for partnerships. AfterQuery reserves fees to order forms or separate agreements. These documents describe commercial structure, not a comparable price per accepted preference pair or environment.

Sources: [188], [221], [268], [313], [314]

Analysis: The analytical rule is to keep commercial denominators separate. A company-wide annualized rate cannot be divided by a benchmark count to estimate task price; cumulative payouts cannot identify a current take rate; financing cannot measure demand; a broad expert pool cannot be a capacity denominator. The selected disclosures support questions for diligence, not supplier market shares. A defensible future comparison would need the same reporting period, currency, gross/net basis, organizational segment and accepted-unit definition across every included provider.

Sources: [44], [223], [470], [474], [483]

Method: Reproducible buyer calculation: accepted-unit cost equals all attributable project cash costs divided by independently accepted units. The numerator should state whether it includes recruitment, qualification, paid training, tool licenses, compute, project management, review, rework and buyer-side acceptance. The denominator should identify the unit: independent judgment, resolved item, trajectory, verified environment, recorded hour or licensed release. This is a proposed accounting method; the report does not insert hypothetical numbers or claim observed costs for suppliers.

Method: Reproducible review calculation: first-pass acceptance equals accepted units on first submission divided by all submitted units; final acceptance equals accepted units after permitted rework divided by all submitted units. Keep attempt, exclusion and unresolved counts. For expert-time projects, report both accepted outputs per paid hour and buyer QA effort per accepted output, without interpreting either as worker wages. For environment projects, separate authoring, maintenance, execution and recurring license costs, and preserve the term of access.

Method: Procurement comparison procedure: issue the same task brief and acceptance rubric, obtain responsibility and rights schedules, run a paid calibration sample, then quote a frozen production scope. Compare totals only after normalizing included review/rework and access terms. Log scope changes as new versions rather than treating a renegotiated specification as supplier underperformance. Proposed service-level thresholds should come from the buyer's loss tolerance and pilot uncertainty; they are not reported market standards.

Research gap: The commercial research gap is task-matched economics. This corpus does not supply comparable current contracts, realized gross/net human-data revenue, project margins, cancellation/rework charges or accepted-unit costs across suppliers. Missing financial disclosure is unknown rather than zero. No financial forecast, market-size projection, provider-return model or inferred valuation multiple is warranted by this evidence.

Analysis: Cost comparisons must include the measured boundary. LMCrowd excludes model, prompt and worker selection from its tariff comparison; CrowdAgent holds human annotation proportions rather than all computation or operating cost equal. HelpSteer2 discards about half of collected annotations overall, so accepted responses and purchased ratings have different denominators. Request setup, failed/rejected work, QA, adjudication, model calls, compute and accepted-unit totals explicitly. These studies inform accounting questions; they do not provide current service prices or a cross-provider cost ranking.

Sources: [408], [415], [419]

Analysis: Worker-time accounting is also distinct from project billing. The historical MTurk log study produces different work-unit rates under accept-to-submit and temporal-cluster definitions; its task/cluster medians are not median worker wages. Selected plugin users, unknown active effort and noncausal associations constrain inference. For a new project, request consented, task-appropriate compensation and time evidence rather than convert historical platform figures or supplier revenue into a claim about present worker earnings.

Sources: [410]

9. Rights, security, privacy and attribution governance

Analysis: Dataset rights should be modeled as a chain of permissions rather than a single badge. The Data Provenance Initiative distinguishes creator-attributable data licenses from code licenses and explicitly limits itself to best-effort self-reported categorization. Common Pile requires confidence that license information originates with a rights holder. These methods support asking who can grant which rights for each component, transformation and release. They do not establish enforceability or replace project-specific legal review.

Sources: [128], [367]

Analysis: Web availability and collection permission are distinct. Consent in Crisis reports inconsistencies between robots.txt signals and terms of service in selected corpora. Documenting C4 recommends documenting included and excluded text and leaves some PII/copyright auditing to future work. FineWeb and Dolma acknowledge residual harmful or sensitive content despite filtering. A buyer should retain capture-time permissions, exclusion rules and removal paths, while treating a crawlable page as a source observation rather than automatic authorization to train or redistribute.

Sources: [108], [368], [389], [467]

Analysis: License scope can change within a research artifact. AlpacaEval declares different code and data licenses; RewardBench aggregation remains subject to component terms; MathVista retains original image/question copyright and prohibits training use; GAIA asks against public redistribution. The correct unit for diligence is the exact component and use, not a repository's top-level license string. A restrictive finding does not imply that this report possesses or can redistribute the underlying data.

Sources: [1], [142], [153], [427]

Analysis: Customer material and website visitor data have different policy boundaries. AfterQuery explicitly excludes processor/service-provider customer processing from its website policy; Mercor excludes its work platform; Label Your Data and LXT describe client-instruction processing; Proximal requires written consent and an executed agreement for generalized-model use of customer material. Obtain the project processing agreement, subprocessors, retention and secondary-use terms. A public policy's existence does not establish that the proposed delivery is covered by every described safeguard.

Sources: [47], [123], [187], [224], [475]

Evidence: Entity names and terms require exact scope. Kili's May 2025 legal notice names MYAI SAS, while its same-date EULA names KILI-TECHNOLOGY SAS under the same Paris registration number; the public inconsistency is unresolved. DDD's published Terms of Use name DDD Ventures LLC and use investment/real-estate language, so that page does not settle the AI-data contracting identity. iSoftStone's privacy policy identifies a website-scoped US operator without resolving ultimate ownership or group-wide contracting responsibility. These findings preserve uncertainty rather than invent corporate transactions or additional suppliers.

Sources: [332], [342], [346]

Analysis: Secondary use and human access can be explicit commercial conditions. Datasaur's terms contain a free-access deidentified/aggregate improvement exception; Deploy's terms default to manual Hive Worker review of customer content unless otherwise agreed in writing; Dataocean's website policy leaves product/project rules to the corresponding services. None of these clauses alone establishes what happened to a particular customer's records. A buyer should identify the applicable subscription, written exceptions, worker exposure, use permissions and service-specific privacy terms before choosing a delivery path.

Sources: [327], [337], [357]

Evidence: Toloka's published task guidelines distinguish public-space images, third-party personal information and personal information collected from Tolokers. For third-party information, the listed conditions include both anonymization before upload and consent agreements. Collection from Tolokers also carries lawful-collection, administering-entity, purpose and policy conditions. These are category-specific platform rules, not a finding that every dataset complies. The linked additional collection guidelines were not separately captured in the reviewed scope.

Sources: [496]

Analysis: Biometric and authorship metadata deserve separate consent and use records. Toloka's notice bases identity matching on explicit consent and says refusal can prevent onboarding; it also discloses authorship metadata in some coding deliverables. Turing's policy lists AI development/training uses of personal information, while Polymath excludes interview voice recordings and transcripts from model training. These statements concern different records and services. Preserve which person, purpose, data type and downstream use each notice covers rather than combine them into a general permission claim.

Sources: [217], [499], [504]

Analysis: Security disclosure must retain attestation type and scope. Scale states SOC 2 Type 2 and ISO/IEC 27001:2022; Appen describes SOC 2 Type II, a HIPAA-specific solution and facility options; Snorkel states SOC 2 Type 2 and engagement-start scoping; Prolific describes ISO 27001 and Cyber Essentials while treating SOC 2 Type 2 as a future plan. Underlying reports, certificate scopes and customer deployments were not inspected here. These statements should not be flattened into equivalent independently verified controls.

Sources: [471], [481], [487], [489]

Analysis: Operational controls can be tiered or project-specific. CloudFactory distinguishes included network controls from optional endpoint controls; Sama describes assigned-employee project rooms; Encord describes role permissions; DataForce's vendor notice requires an applicable DPA before EU-personal-data processing. A buyer should verify the selected tier, location, legal entity, access matrix and actual data flow. The report records disclosed controls, without certifying that all personnel or projects implement them.

Sources: [22], [27], [55], [110]

Analysis: Incidents and remediation should be compared on evidence, not on whether one company has a public disclosure. Mercor's company investigation account describes the March 2026 compromised LiteLLM event and is explicitly not an independently audited impact/remediation finding. This report has no common incident-discovery process or equal disclosure window across suppliers. It therefore cannot rank relative security from the presence of that one record or assume that an unrecorded incident never occurred elsewhere.

Sources: [476]

Analysis: Artifact attribution is nontransitive. Scale's HelpSteer annotation, Translated's multilingual role, Prolific's recruitment case, Toloka's U-MATH validation and Surge's GSM8K collection are specific relationships. A paper citing a dataset, an author's affiliation, a supplier's general service menu or a benchmark family's parent link does not establish another supplier contribution. The graph is sparse in explicit object relationships; many approved observations are typed text. A reader should not confuse catalogue richness with an exhaustive supplier-to-artifact map.

Sources: [440], [478], [484], [492], [500]

Method: Research governance: the publisher's public identity discloses applications for paid work at some covered companies, membership in A.Team's talent network and a separate proposed AI research lab. No profiled company has paid for coverage or is a customer, investor or affiliate of the publisher under that disclosure. External reviewer credit requires consent. This preparation claims actual separate AI source review and will require separate exact-report evidence-auditor and adversarial review; it does not claim human peer review or an external operational certification.

Research gap: Governance unknowns include project-specific contracts, current assurance-report scopes, removal-request outcomes, consent withdrawals, subprocessor execution and worker appeal effectiveness. These cannot be resolved by treating a top-level license, policy statement or source-content review as an operational audit. Buyer diligence should obtain the relevant documents and test the actual project boundary; future research should record both support and unresolved limitations.

Analysis: Disclosure completeness is an observable governance input, while actual conduct remains a separate question. GIGO audits publication reporting in a selected literature; Who Annotates extracts task-level disclosures with an automated model and a separately adjudicated reference. Both reject equating missing reporting with absent practice. Their results justify asking for training, language proficiency, instructions and reconciliation records. They do not justify ranking a supplier's ethics or data quality from how many public fields are filled.

Sources: [412], [424]

Analysis: A documented consent workflow does not finish privacy diligence. WildChat reports an agreement plus secondary confirmation and multilingual PII filtering, yet warns that hashed IPs and request headers can link conversations. The reported process was not independently tested here. For a proposed conversational-data use, examine the exact released fields, linkage routes, permissions and intended population; preserve the difference between a source's stated control and demonstrated residual risk reduction.

Sources: [425]

10. Buyer decision guides: use cases, pilot designs and acceptance

Method: The following are proposed buyer procedures derived from the reviewed evidence, not reports of completed supplier trials. They do not recommend a universal winner. Each use case states the required deliverable, a candidate responsibility model, a paid pilot and acceptance evidence. The buyer should pre-register critical errors, slices, exclusions, rework limits and decision rules before seeing outputs. Numeric targets should follow the buyer's risk and uncertainty requirements; no universal accuracy threshold is invented here.

Analysis: Buyer use case 1 - Expert preference data for a specialized assistant: requirement and comparison. Specify prompts, candidate responses, domain credentials, language, independent judgments per item, preference strength and rationale fields. Compare a managed preference program with participant access only after assigning task design, recruitment, adjudication and acceptance. HelpSteer3, HelpSteer2 and InstructGPT show why final pair counts conceal different repetition and aggregation structures.

Sources: [429], [464], [468]

Analysis: Buyer use case 1 - Expert preference data for a specialized assistant: proposed paid pilot. Use a paid calibration batch spanning routine, ambiguous and deliberately difficult cases. Freeze the raw-label schema before consensus. Have a separate reviewer inspect disagreements and rejected items without knowing the supplier or initial majority. Keep duplicate prompts and ranked-set expansion identifiable, then hold out a second batch for acceptance.

Sources: [429], [464], [468]

Analysis: Buyer use case 1 - Expert preference data for a specialized assistant: proposed acceptance and limits. Accept only against the predeclared target: valid independent judgments, traceable exclusions, correct domain-language intersections and adjudication supported by reasons. Report first-pass and final acceptance with all submitted items in the denominator. Do not let post-filter agreement substitute for coverage of difficult cases. Reject an unsupported claim that more released pairs necessarily means more independent human evidence.

Sources: [429], [464], [468]

Analysis: Buyer use case 2 - Repository engineering and coding-agent environments: requirement and comparison. Define repository language/version, issue requirements, permitted tools, test suite, reset behavior, task horizon and artifact rights. Compare custom environment builders, engineering teams and licensed task packages on the same accepted unit. G2i's contract boundary and A.Team's engagement models require special attention when responsibility for the final environment could remain with the buyer.

Sources: [197], [207], [268], [289], [438], [466]

Analysis: Buyer use case 2 - Repository engineering and coding-agent environments: proposed paid pilot. Run known-correct, known-incorrect and superficially passing patches in isolated copies. Repeat resets and tests, record installation/network failures separately and sample passing changes for completeness, readability and unintended behavior. Freeze the environment image, dependencies, time limits and verifier version. Inspect a hidden test that catches a plausible shortcut rather than merely reproducing the reference implementation.

Sources: [197], [207], [268], [289], [438], [466]

Analysis: Buyer use case 2 - Repository engineering and coding-agent environments: proposed acceptance and limits. Accept reproducible environments and task-scoped outcomes under the agreed protocol, with infrastructure failures explicitly adjudicated. Require pass/fail consistency, regression protection and side-effect review. SWE-bench cautions that passing tests does not guarantee complete solutions, while MBPP shows hard-coded-input gaming. A supplier’s benchmark authorship or engineering credentials alone does not satisfy these tests.

Sources: [197], [207], [268], [289], [438], [466]

Analysis: Buyer use case 3 - Enterprise browser and desktop workflow training: requirement and comparison. Specify an initial state, user goal, authorized actions, protected data and prohibited side effects. Decide whether the deliverable is human demonstrations, a simulated environment, a verifier or all three. AfterQuery’s demonstrations, Abundant’s customer-workflow conversion and Refresh’s versioned visual checks represent different disclosed units. A recording without an outcome specification is not yet an accepted RL task.

Sources: [64], [167], [183], [185], [213], [232], [239]

Analysis: Buyer use case 3 - Enterprise browser and desktop workflow training: proposed paid pilot. Use synthetic or approved nonproduction accounts and fixed starting documents. Capture action traces, final state and constraint violations. Include recoverable mistakes, irreversible actions, ambiguous requests and tasks that should be refused. Test evaluator behavior on completed tasks with a deliberately harmful extra action, and on valid alternate solutions that differ from the reference sequence.

Sources: [64], [167], [183], [185], [213], [232], [239]

Analysis: Buyer use case 3 - Enterprise browser and desktop workflow training: proposed acceptance and limits. Require reproducible resets, authorized-state transitions and preservation of protected content, alongside end-goal success. OSWorld explicitly identifies side-effect detection limits and configuration failures; WebShop documents lexical reward errors; WebArena uses mixed semantic and state checks. Acceptance should distinguish environment, policy, model and judge failures so a low score does not silently become a provider-quality claim.

Sources: [64], [167], [183], [185], [213], [232], [239]

Analysis: Buyer use case 4 - Multilingual assistant and localization evaluation: requirement and comparison. State language variety, script, locale, domain, task type and whether native authoring or translation is required. Compare native task creation, post-edited translation and multilingual judging as different workflows. HelpSteer3's missing intersections and M-IFEval's language-specific constraint changes make a broad language count an inadequate specification.

Sources: [366], [375], [376], [381], [468]

Analysis: Buyer use case 4 - Multilingual assistant and localization evaluation: proposed paid pilot. Construct a matrix of required language-domain pairs and sample every promised intersection. Use native-domain reviewers, preserve original and translated prompts and test local factuality, tone and instructions separately. Include constraints whose English formulation is invalid in the target script. Blind model identity and candidate order, then compare judge decisions with held-out human decisions under the actual target-language protocol.

Sources: [366], [375], [376], [381], [468]

Analysis: Buyer use case 4 - Multilingual assistant and localization evaluation: proposed acceptance and limits. Accept documented coverage and calibrated errors within each required slice, with no unsupported extrapolation from an overall average. Report translation revisions and unresolved dialect disagreements. MENLO's dimensions, BenchMAX's post-editing and the multilingual-judge setup show why aggregate cross-language consistency cannot replace validity on the buyer's real conversations.

Sources: [366], [375], [376], [381], [468]

Analysis: Buyer use case 5 - Medical, legal or financial expert data: requirement and comparison. Specify the permitted professional task, jurisdiction or clinical context, credential evidence, privacy boundary and intended model use. Shaip's credential matching and Encord's clinician/task matching are offering disclosures, while Aya Data's Cydar case concerns specific image labels. Do not transfer evidence from image annotation to clinical advice quality or from general finance work to jurisdiction-specific legal accuracy.

Sources: [95], [109], [132], [336]

Analysis: Buyer use case 5 - Medical, legal or financial expert data: proposed paid pilot. Use de-identified or consented material under a project processing agreement. Have qualified reviewers build an independent reference and define cases requiring escalation rather than forced answers. Record source authority, uncertainty and conflicting professional opinions. Separate rubric authoring from acceptance where feasible, and hold out difficult or out-of-scope cases that test whether annotators recognize the boundary.

Sources: [95], [109], [132], [336]

Analysis: Buyer use case 5 - Medical, legal or financial expert data: proposed acceptance and limits. Accept only the defined artifact under the qualified review protocol, with provenance and privacy records and no unresolved critical error in the buyer's predeclared category. Credentials establish eligibility, not correctness of every output. GPQA's authors reject representativeness of scientific practice and flag selection-biased validator accuracies, illustrating why expert benchmark performance cannot certify a professional service.

Sources: [95], [109], [132], [336]

Analysis: Buyer use case 6 - Safety evaluation, red teaming and policy judges: requirement and comparison. Choose a threat model, target policies, allowed attack surfaces, severity taxonomy, benign near-neighbors and remediation owner. Compare novel expert attack discovery, automated attack generation and an integrated policy judge separately. Giskard, Alinia and Trajectory document different approaches; a single attack-success rate is not a common deliverable or a claim of exhaustive safety.

Sources: [129], [203], [205], [271], [285], [315]

Analysis: Buyer use case 6 - Safety evaluation, red teaming and policy judges: proposed paid pilot. Run attacks adapted to the actual defense, with fixed generation budgets and held-out attack families. Ask independent reviewers to adjudicate both successful attacks and benign refusals. Record severity and plausible impact separately from whether a classifier marks harmful content. Inspect worker notice, opt-out and support arrangements before exposure to sensitive material.

Sources: [129], [203], [205], [271], [285], [315]

Analysis: Buyer use case 6 - Safety evaluation, red teaming and policy judges: proposed acceptance and limits. Accept a reproducible finding set, false-positive accounting and verified remediation/retest evidence under the scoped threat model. HarmBench shows budget confounds; JailbreakBench distinguishes adaptive defense evaluation and paired benign behaviors; the human red-team study flags incomplete expertise and coverage. No finite pilot proves absence of all harmful behavior.

Sources: [129], [203], [205], [271], [285], [315]

Analysis: Buyer use case 7 - RAG evaluation and LLM-judge calibration: requirement and comparison. Define the evidence corpus, query distribution, answer criteria, citation validity and abstention behavior. A human golden set, a tuned judge and an operational dashboard are distinct deliverables. SuperAnnotate's Databricks account documents rubric construction and human/model agreement, while Giskard's tooling permits expert ground truths and qualification of failures. The buyer still owns the intended-use definition.

Sources: [1], [57], [286], [352]

Analysis: Buyer use case 7 - RAG evaluation and LLM-judge calibration: proposed paid pilot. Sample answerable, unanswerable, misleading and conflicting-evidence questions. Keep calibration examples separate from final acceptance. Blind source model and response order, test stylistic/length variation and examine errors by failure type. Have an independent reviewer inspect whether a plausible citation actually supports the answer, rather than treating a judge's high scalar rating as evidence fidelity.

Sources: [1], [57], [286], [352]

Analysis: Buyer use case 7 - RAG evaluation and LLM-judge calibration: proposed acceptance and limits. Accept the frozen judge only within the measured scope, documenting thresholds, abstentions and known blind spots. RewardBench 2 warns that reward benchmark accuracy alone is insufficient for strong RLHF training; AlpacaEval warns style can outweigh factuality and that harms are not measured. A judge calibrated on one response population needs renewed testing when the generator or domain changes.

Sources: [1], [57], [286], [352]

Analysis: Buyer use case 8 - Licensed or off-the-shelf training data: requirement and comparison. Specify exact release, use rights, exclusivity, refresh entitlement, permitted transformations, deletion/removal obligations and overlap exclusions. Snorkel's non-exclusive refreshed products, Mercor's catalog and Defined.ai's marketplace/service separation show why a dataset purchase needs its own license and provenance schedule. A quantity quote should identify rows, tokens, hours or tasks rather than use examples as an undefined unit.

Sources: [1], [31], [153], [427], [474], [489]

Analysis: Buyer use case 8 - Licensed or off-the-shelf training data: proposed paid pilot. Inspect a representative sample and the component/source manifest before full acceptance. Check format validity, duplicates, contamination against the buyer's holdouts, sensitive information and the documented origin of labels. Review a random sample as well as hard cases so cherry-picked examples cannot define the result. Resolve license conflicts and restricted components before using the data for the intended training or redistribution.

Sources: [1], [31], [153], [427], [474], [489]

Analysis: Buyer use case 8 - Licensed or off-the-shelf training data: proposed acceptance and limits. Accept the versioned artifact only if source rights and technical fitness meet the agreed project scope. RewardBench component terms, AlpacaEval's code/data split and MathVista's training restriction demonstrate why a top-level license label is insufficient. A public source or approved catalogue entry is not a rights clearance or a warrant for downstream commercial use.

Sources: [1], [31], [153], [427], [474], [489]

Analysis: Buyer use case 9 - Multimodal and physical-AI data collection: requirement and comparison. Specify sensors, synchronization, environment, participant permissions, modality alignment, annotation ontology and the accepted recording unit. Defined.ai’s robotics case, TELUS Digital’s collection modes and APTO’s modality menu are starting points for scope, not a common measured service. A recorded hour can contain different usable-event density, missing streams or annotation depth.

Sources: [29], [62], [109], [273]

Analysis: Buyer use case 9 - Multimodal and physical-AI data collection: proposed paid pilot. Run a controlled collection with calibration records, known synchronization events and independent inspection of unusable segments. Test edge conditions, privacy redaction and the linkage between raw recording and derived labels. Keep human review of model-generated first passes traceable, as Encord describes, and include downstream consumers when deciding which errors invalidate a unit.

Sources: [29], [62], [109], [273]

Analysis: Buyer use case 9 - Multimodal and physical-AI data collection: proposed acceptance and limits. Accept usable synchronized units with documented rights, calibration and error handling, rather than raw storage volume or gross duration. Report discarded or repaired recordings and modality-specific failure rates. The reviewed robotics hours and collection brochure do not establish success rates for the buyer’s sensors, field conditions or safety requirements.

Sources: [29], [62], [109], [273]

Analysis: Buyer use case 10 - Research-agent and long-horizon professional-task evaluation: requirement and comparison. Define task horizon, starting resources, permitted external code, human/tool assistance, time budget and the difference between partial and complete success. PaperBench, RE-Bench, ScienceAgentBench and TheAgentCompany expose different research-work abstractions. Their results should inform test design, not be translated into a general claim about replacing a profession or performing an arbitrary research project.

Sources: [318], [350], [351], [353]

Analysis: Buyer use case 10 - Research-agent and long-horizon professional-task evaluation: proposed paid pilot. Freeze a small private task set with independently authored rubrics and executable checks. Record intermediate artifacts and final outputs; have reviewers inspect whether a claimed replication actually reproduces results under the permitted resources. Match human and agent tool access where the comparison requires it, and report wall time, compute and expert-review effort separately.

Sources: [318], [350], [351], [353]

Analysis: Buyer use case 10 - Research-agent and long-horizon professional-task evaluation: proposed acceptance and limits. Accept a reproducible task-scoped result with transparent leaf decisions, execution failures and uncertainty. PaperBench's Code-Dev correlation limit, RE-Bench's representativeness warning and ScienceAgentBench's language selection boundary show that even a well-defined score can be narrow. A complete-success claim must not be substituted for partial credit or a rubric-weighted average.

Sources: [318], [350], [351], [353]

Method: Common pilot record: versioned brief; source and rights manifest; task/environment version; contributor qualification rule; raw judgments or trajectories; review and exclusion log; adjudication reasons; acceptance denominator; cost inclusions; and residual risks. Separate supplier process errors from buyer guideline defects, environment failures and model failures. The final purchase decision should state which evidence established suitability and which assumptions remain conditional. Keep unsuccessful pilots and rejected examples in the internal learning record so later comparisons do not inherit survivorship bias.

Analysis: Pilot refinement for expert preference and multilingual data: retain an unfiltered calibration sample alongside the accepted sample. Score raw agreement, exclusions, adjudication and acceptance separately; inspect whether difficult but relevant cases disappear. HelpSteer2's κ change is conditional on multistage filtering, Aya's language total does not guarantee uniform contributor diversity or safety review, and Inherent Disagreements warns against pooling batch-normalized scales. Predeclare whether the buyer needs consensus labels, calibrated scalar attributes or a distribution of valid preferences before requesting a price per example.

Sources: [407], [415], [416]

Analysis: Pilot refinement for research agents and feedback services: freeze the feedback visibility contract. RECODE-H's richest condition supplies correct code and its evaluated expert is simulated; AutoLibra collects one feedback element for a complete trajectory and does not demonstrate live step-level guidance. Compare these against the buyer's actual need: post-hoc diagnosis, interactive help or verifiable task scoring. Count feedback rounds, solution material disclosed, human effort and independent final success separately so richer assistance is not mistaken for better unaided agent capability.

Sources: [406], [421]

Analysis: Pilot refinement for label automation and judge calibration: establish reference labels independently before comparing the system under test. Who Annotates resolves two independent annotations through discussion and third-person adjudication; the benchmark-label study retains uncertainty even after five-worker review. Include easy, ambiguous and rejected cases, then state whether the metric measures agreement with a chosen reference or verified outcome correctness. This proposed acceptance design should document disagreements and confidence rather than silently discard cases that challenge either the reference or the evaluated system.

Sources: [413], [418], [424]

11. Research outlook: testable judgments and open questions

Analysis: Hypothesis - stage-level provenance will become a more useful comparison than a binary human/synthetic label. The sample already contains human-authored preferences, model-generated feedback, synthetic educational scores and human correction of model responses. Confidence is moderate for the usefulness of this distinction and unestablished for its effect on procurement outcomes. The hypothesis would strengthen if provenance-complete manifests predict fewer acceptance surprises on matched tasks; it would weaken if those details fail to add information beyond ordinary samples and contracts. This is a research proposition, not a forecast of market adoption.

Sources: [280], [433], [467], [468]

Analysis: Hypothesis - environment and verifier maintenance will be a distinct recurring delivery burden. Refresh describes versioned verifiers, OSWorld announces a verified-version change, and SWE-bench Multimodal reports repeated-test filtering. Confidence is moderate that version and stability matter within these examples, but the corpus supplies no market-wide maintenance cost. A longitudinal study should record environment breakage, verifier corrections and acceptance changes under frozen agents. If stable tasks require little upkeep across relevant software changes, the hypothesized burden would be narrower than suggested.

Sources: [167], [232], [359]

Analysis: Hypothesis - multilingual validity will require native task design as well as translation quality. M-IFEval modifies constraints, MENLO isolates local dimensions and BenchMAX post-edits translated data. Confidence is moderate for the methodological distinction, without an estimated commercial premium. A useful experiment would match translated, post-edited and native-authored tasks on intended constructs and independently score local failures. Equal validity under those controlled conditions would weaken the need for a separate native-authoring stage in that particular use case.

Sources: [366], [375], [376]

Analysis: Hypothesis - reliability reporting will need both repeated execution and disagreement preservation. τ-bench distinguishes all-trials reliability from at-least-one success, while DICES and the disagreement study expose meaningful variation in human labels. Confidence is high that these are different denominators; the effect on supplier selection remains untested. A matched pilot should compare decisions made from aggregate success alone with decisions using repeated trials, raw labels and adjudication reasons. The hypothesis would weaken if added detail does not change acceptance or predict deployment errors.

Sources: [106], [107], [236]

Analysis: Hypothesis - reward-model and monitor evaluations will need adversarial separation from the optimization loop. Summarization overoptimization, verifier search exploitation and the reasoning-monitor study demonstrate specific mechanisms by which optimization can outpace a proxy. Confidence is moderate for the need to test this risk, not for its prevalence in current services. Hold out failure classes and reviewer inputs when optimizing the system, then measure independent outcome errors. A robust matched study showing stable external validity across optimization intensity would narrow this concern.

Sources: [63], [133], [378]

Analysis: Hypothesis - labor and documentation quality should be evaluated as operating processes, not only disclosure artifacts. CrowdWorkSheets asks for maintenance and pool-selection rationale; Datasheets asks about collection participants and compensation; the labor study warns about unknown population boundaries. Confidence is moderate for the research value of these fields, with no causal claim that publishing them improves wages or model quality. Follow-up research should compare documentation with consented worker evidence and project logs, retaining discrepancies and avoiding a disclosure-completeness score that masquerades as performance.

Sources: [386], [394], [462]

Research gap: Priority evidence gaps: comparable accepted-unit economics; contributor-level paid-active windows; independent project outcomes; version-specific rights clearance; non-English and non-text coverage intersections; benchmark side-effect detection; and a complete source-supported supplier contribution map. The current graph’s richer catalogue does not resolve these automatically. Research should prioritize decision-changing evidence rather than optimize counts, and should document negative findings and unresolved cases alongside additions.

Method: The weekly outlook should be revised through falsifiable change conditions. Each stable executive finding records confidence, reasoning, limitations and what would change the assessment. New primary evidence can strengthen, narrow or supersede a finding; a changed source version should not silently overwrite its predecessor. A meaningful revision will identify which observed assumption changed and whether the effect is task-specific or supports a broader conclusion. No growth, revenue, employment or technology-adoption forecast is produced from this selected corpus.

Analysis: Hypothesis - a stronger documentation audit will improve diligence only if reporting signals are checked against project evidence. GIGO and Who Annotates observe disclosure, not undisclosed practice; the latter also exposes extraction uncertainty. Confidence is moderate in the need to distinguish those objects and unmeasured in the commercial value of an audit score. A follow-up could compare disclosed instructions, training and compensation fields with consented project records and independently sampled outputs. If completeness fails to predict agreement between disclosure and practice, its role should remain a transparency measure rather than a performance proxy.

Sources: [412], [424]

12. Methods, coverage, bibliography and reproducible appendices

Method: Evidence boundary and source hierarchy. The factual boundary is the approved, validated merged graph selected by the explicit partition index. Discovery candidates, provisional reviews, search snippets and unpinned working files do not become report facts. Primary creator papers, official repository/card versions, provider policies, audited statements and first-party case accounts retain their source type. Provider marketing is reported as a disclosure. A source-content review checks whether an exact claim is supported; it does not transform self-reported operations into an independent audit.

Method: Assertion approval and review identity. Each approved assertion has exact-content author, source-verifier and adversarial receipts from separate actual AI invocations. Approval binds wording, subject, predicate, object or typed value, qualifications, source version, locator and excerpt digest. Report-level evidence-auditor and adversarial reviews are separate requirements bound to the exact report digest and complete graph digest. Prior report or graph reviews cannot approve this expanded synthesis. No fabricated human reviewer, honorific, institutional endorsement or review receipt is added.

Method: Original-stage notes and current status. Frozen source records retain historical author-only or proposal-stage wording where it was part of the original packet. Those notes describe that earlier stage and do not replace current status. This report reads approval from exact-digest three-role receipts while retaining source-depth and substantive limitations. Twenty-six later-disputed bindings remain candidate/history records; approved replacements use new IDs after fresh independent review. The original scientific values and qualifications are unchanged, and earlier positive or negative receipts and actual capture/review dates are not erased.

Method: Reading depth. full_source is a bounded editorial category: methods plus main results or worked examples and limitations, with separately recorded spans. It does not mean all appendices or proofs were read, every experiment reproduced or all corpus records checked. A truthful full_document_read false is compatible with adequate bounded main-section review. Abstract-only material cannot be promoted through a claim count. Dataset construction may be reviewed through creator methods and documentation without adding the original paper work as a fully reviewed paper or establishing corpus-byte identity.

Method: Capture-specific evidence. Cogito and Mindy observations bind the exact saved official extracted-page snapshots available to the reviewers; origin HTML and live HTTP status were not exposed by that extraction. Separate direct retrieval attempts had their own failures and do not turn the extraction into a verified live-origin response. The Mindy FAQ is undated, so current staffing/location figures are not adopted. TrustScale’s rebrand article was decoded from the pinned public application bundle rather than established by rendered-page execution. These capture boundaries remain attached to the underlying source records and dossier limitations.

Method: Version and identity accounting. A paper work counts once through its reviewed manifestation; a dataset or benchmark family counts once through approved family/release evidence. Formats, configs, splits and subset releases do not add families. FineWeb-Edu is currently one FineWeb subset release, correcting the initial eight-family baseline's separate-family treatment without changing that archive's bytes. MuSiQue's new human-composed questions support one family; inherited seed corpora and answerability/serialization variants do not add families. Corporate aliases and product brands do not automatically add suppliers.

Method: Reproduction snapshot. This refreshed synthesis binds the validated merged graph with canonical JSON SHA-256 044a17dc52ae6e70d684e18fbf9dc6273be657aa6b80c1074a963f33513160d8. Canonical dataset version 2.5.0 and its exact-file SHA-256 948e69229fa24a4a1e6b5eed6d9c11570568a3c05bf9512e442d19611061a061 remain unchanged. Recompute the graph digest with research_report.canonical_hash after research_graph.load_graph validates indexed partitions and canonical bytes. This is a pinned synthesis input, not a frozen eligible-core inventory or a published archive. Any later graph change requires a new synthesis binding and actual separate report reviews.

Method: Computed coverage appendix. Coverage method 1.3.0 counts 1,713 approved assertions, 26 quarantined candidate assertions and 39 historical assertions. There are 1,790 scoped source records, of which 1,789 are captured; those captured records represent 503 distinct document versions under the version/response-hash rule. Multiple excerpts or locators can refer to one version and are not independent documents. The selected qualifying corpus contains 65 suppliers, 152 distinct paper works, 63 dataset families and 21 benchmark families. All 39 legacy organizations have completed bounded inclusion audits; 38 have conclusive commercial dispositions and BenchFlow remains commercially pending. These are separate measures, and no pending qualification contributes a qualifying supplier or frozen-core disposition.

Method: Relationship appendix. Exactly 216 approved assertions in this input use explicit object relationships. Other observations use source-bound typed values. Every predicate is nontransitive: parent links support work/family accounting only. A paper mentioning a company, using its software or documenting expert recruitment does not authorize an unstated supplier edge, exclusive authorship, contract value or causal performance attribution. Paper versions, dataset releases, formats, aliases and mirrors remain identity evidence rather than automatically creating additional counted objects.

Method: Launch gate appendix. The fixed floors require 39 completed legacy inclusion audits, 60 qualifying suppliers, 150 reviewed paper works, 60 dataset families, 20 benchmark families and disposition of at least 90% of a frozen eligible core. Commercial dispositions are separately reported; BenchFlow’s pending status does not invalidate its completed inclusion audit. The eligible core remains unfrozen. The formal reference and screening audits each require completed non-fixture holdouts and their source-bound, independently adjudicated provenance. Reference precision must reach 98% and recall 95% with no critical false attribution; screening needs at least 190 of 200 eligible records and at least 90% recall in each major stratum. Meeting numerical thresholds in a separate diagnostic does not complete these audits.

Method: Audit status and limitations. Formal reference and screening launch audits are incomplete; no approval count, schema pass or diagnostic threshold comparison changes that state. The eligible inventory remains a lower bound under active independent boundary-policy review. Open discovery partitions, unresolved identities and mandatory deep-review gaps prevent a final denominator, census claim or core disposition rate. Accessible and well-documented sources can remain overrepresented despite a large approved corpus. A pinned authoring graph and a frozen diagnostic sample are distinct from a completed, frozen eligible inventory.

Method: Search and selection bias. This is a selected public-source corpus rather than a probability sample. English-language material, public research artifacts and providers with detailed documentation are easier to discover and inspect. Confidential contracts, unavailable or blocked documents, undocumented suppliers and unobserved language/domain intersections can be missing. Unknown fields are preserved as unknown and do not count as evidence of absence. The report’s comparisons are sample-limited and should not be extrapolated into the entire market.

Method: Source dates and weekly cutoff. published_on records a document’s publication date when established; the event described may be older; captured_on records retrieval; reviewed_on records actual review; assertion as_of records its declared observation date; an edition needs an actual publication confirmation. The planned 13 November 17:00 Pacific cutoff and 16 November weekly check remain future schedule points in this 10 November prelaunch preparation. A later capture cannot be moved into an earlier window, and a delayed run is catch-up rather than a backdated publication.

Method: Interpretation and reproducible calculations. Approved counts are computed from qualifying identities and current approved assertions. Sample ratios should identify numerator and denominator before rounding. Project cost and acceptance formulas in chapter 8 are proposed methods with no invented inputs. Paper-reported results in the atlas retain the exact task, version and measurement condition described by the approved statement; they are not independently reproduced results, current model rankings or estimates of supplier performance. No metric is averaged across incompatible benchmark protocols.

Method: Public reuse and downloads. The research hub is https://sciencetostartup.com/research/; the living report route is https://sciencetostartup.com/research/state-of-ai-data-labs/; the evidence and download index is https://sciencetostartup.com/research/data/; source-backed review and correction entry is https://sciencetostartup.com/review/. Download links in the prepared publication must bind its own JSON/CSV/SQLite, schemas, bibliography, checksum manifest, offline evidence appendix, PDF and reproduction package. This source report does not assert that the expanded matching package, DOI, Zenodo archive or Hugging Face mirror already exists.

Method: Publication and corrections. Website preparation, deployment, archive confirmation and mirror synchronization have separate states and receipts. Accounts remain prepare-only under the current policy. A source-backed correction should identify the claim or report block, the source version and locator, the proposed wording and the reason. The research workflow reviews support, privacy and identity before integrating changes. Historical frozen packages retain pinned bytes; a correction belongs in a new version and change log rather than an invisible replacement.

Method: Bibliography reading guide. The entries below provide the reviewed paper-work title, a source URL from its bound evidence and the inspected source version. Claim links carry the exact locator, excerpt hash, qualifications and review identities. A source URL can resolve to a later page; the recorded version and response digest define the reviewed content. Dataset and supplier bibliography records are available through each atlas/dossier’s claim bindings and the evidence ledger; no external affiliation is used as a substitute for a documented contribution.

Method: Reference diagnostic, not launch audit. A private constructed challenge retains all 250 frozen cases sampled from the previously approved corpus. Two independent AI truth workers using the same requested model family established judgments with a third tie-breaker before comparison with the system under test; locator-context boundaries were clarified during adjudication. Under the strict consensus key, the unchanged run records 184 true positives, three false positives, two false negatives and 61 true negatives: precision 184/187 = 98.3957% and recall 184/186 = 98.9247%. These are challenge-specific results, not production accuracy, discovery recall, human peer review or completed reference-audit evidence.

Method: Diagnostic run binding and repair separation. The private reference-holdout-v1/diagnostic-results.v1.json run receipt has file SHA-256 870e45072181561da4203d256f97803b26a9ac0376573cb2024bd57d47b5f46e. Its consensus freeze is 1d6b81a6bf1cf80cc326ced6a3671ea0b100078d48d876360f6e8a63efddba3a and its evaluated-predictions digest is 7fe7d94ff17aa1f60c9339b72b85c33cea9a3df7baef0589cfa36a0b8ececb5c. Source-binding repairs are subsequent remediation. They do not remove or relabel challenge cases, replace the recorded predictions or revise the frozen diagnostic scores. Threshold comparisons leave unresolved formal audit provenance and protocol conditions held.

Method: Source-binding correction ledger. The 26 old-to-new mappings are preserved in the authoring correction ledger with file SHA-256 0ce874b0aacd4fbe9bd70a5074e28b8da0fdb8077bfbac65484344de70cd131c, bound to this exact graph. The ledger records newly approved replacement IDs and their 78 fresh three-role review IDs. This report remaps citations to those approved IDs while retaining the underlying scientific text and substantive qualifications. Original candidate IDs and earlier positive/negative review history remain available in the graph; fresh source review does not serve as an exact-report synthesis review.

Method: Locator reproduction. A locator identifies pinned source bytes and an extraction convention. One-based physical PDF pages differ from printed labels; global marked-text lines count markers and blank lines, while per-page pdftotext-layout coordinates use their declared physical page and tool convention. Preserve source versions, raw-response hashes and supplied derived-text hashes before interpreting a line range. Dataset-card revisions document the inspected card and do not automatically identify every corpus shard. A successful re-extraction is reproducibility evidence, rather than a new capture, scientific finding or independent content review.

Evidence: Reviewed-work bibliography - τ^2-Bench: Evaluating Conversational Agents in a Dual-Control Environment. Source: https://arxiv.org/pdf/2506.07982v1. Inspected version: 2506.07982v1.

Sources: [361]

Evidence: Reviewed-work bibliography - A General Theoretical Paradigm to Understand Learning from Human Preferences. Source: https://arxiv.org/pdf/2310.12036v1. Inspected version: 2310.12036v1.

Sources: [40]

Evidence: Reviewed-work bibliography - AgentBench: Evaluating LLMs as Agents. Source: https://arxiv.org/pdf/2308.03688v1. Inspected version: 2308.03688v1.

Sources: [20]

Evidence: Reviewed-work bibliography - AgentGym: Evolving Large Language Model-based Agents across Diverse Environments. Source: https://arxiv.org/pdf/2406.04151v1. Inspected version: 2406.04151v1.

Sources: [189]

Evidence: Reviewed-work bibliography - AlpaGasus: Training A Better Alpaca with Fewer Data. Source: https://arxiv.org/pdf/2307.08701v1. Inspected version: 2307.08701v1.

Sources: [94]

Evidence: Reviewed-work bibliography - Back to Basics: Revisiting REINFORCE Style Optimization for Learning from Human Feedback in LLMs. Source: https://arxiv.org/pdf/2402.14740v1. Inspected version: 2402.14740v1.

Sources: [302]

Evidence: Reviewed-work bibliography - BenchGuard: Who Guards the Benchmarks? Automated Auditing of LLM Agent Benchmarks. Source: https://arxiv.org/pdf/2604.24955v1. Inspected version: 2604.24955v1.

Sources: [321]

Evidence: Reviewed-work bibliography - BenchMAX: A Comprehensive Multilingual Evaluation Suite for Large Language Models. Source: https://arxiv.org/pdf/2502.07346v1. Inspected version: 2502.07346v1.

Sources: [366]

Evidence: Reviewed-work bibliography - Beyond the Imitation Game: Quantifying and extrapolating the capabilities of language models. Source: https://arxiv.org/pdf/2206.04615v1. Inspected version: 2206.04615v1.

Sources: [193]

Evidence: Reviewed-work bibliography - BrowseComp: A Simple Yet Challenging Benchmark for Browsing Agents. Source: https://arxiv.org/pdf/2504.12516v1. Inspected version: 2504.12516v1.

Sources: [322]

Evidence: Reviewed-work bibliography - Consent in Crisis: The Rapid Decline of the AI Data Commons. Source: https://arxiv.org/pdf/2407.14933v1. Inspected version: 2407.14933v1.

Sources: [368]

Evidence: Reviewed-work bibliography - Constitutional AI: Harmlessness from AI Feedback. Source: https://arxiv.org/pdf/2212.08073v1. Inspected version: 2212.08073v1.

Sources: [23]

Evidence: Reviewed-work bibliography - Constitutional Classifiers: Defending against Universal Jailbreaks across Thousands of Hours of Red Teaming. Source: https://arxiv.org/pdf/2501.18837v1. Inspected version: 2501.18837v1.

Sources: [277]

Evidence: Reviewed-work bibliography - CrowdWorkSheets: Accounting for Individual and Collective Identities Underlying Crowdsourced Dataset Annotation. Source: https://arxiv.org/pdf/2206.08931v1. Inspected version: 2206.08931v1.

Sources: [386]

Evidence: Reviewed-work bibliography - DAPO: An Open-Source LLM Reinforcement Learning System at Scale. Source: https://arxiv.org/pdf/2503.14476v2. Inspected version: 2503.14476v2.

Sources: [387]

Evidence: Reviewed-work bibliography - Data Cards: Purposeful and Transparent Dataset Documentation for Responsible AI. Source: https://arxiv.org/pdf/2204.01075v1. Inspected version: 2204.01075v1.

Sources: [388]

Evidence: Reviewed-work bibliography - Data Statements for Natural Language Processing: Toward Mitigating System Bias and Enabling Better Science. Source: https://aclanthology.org/Q18-1041.pdf. Inspected version: ACL-Q18-1041-published-2018; anthology metadata commit ba3130005282c6474307cceec936373fe55d15ff.

Sources: [371]

Evidence: Reviewed-work bibliography - DataComp-LM: In search of the next generation of training sets for language models. Source: https://arxiv.org/pdf/2406.11794v1. Inspected version: 2406.11794v1.

Sources: [105]

Evidence: Reviewed-work bibliography - DataComp: In search of the next generation of multimodal datasets. Source: https://arxiv.org/pdf/2304.14108v1. Inspected version: 2304.14108v1.

Sources: [104]

Evidence: Reviewed-work bibliography - Datasheets for Datasets. Source: https://arxiv.org/abs/1803.09010v8. Inspected version: 1803.09010v8.

Sources: [453], [462]

Evidence: Reviewed-work bibliography - Deep Reinforcement Learning from Human Preferences. Source: https://arxiv.org/pdf/1706.03741v1. Inspected version: 1706.03741v1.

Sources: [32]

Evidence: Reviewed-work bibliography - DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning. Source: https://arxiv.org/pdf/2501.12948v1. Inspected version: 2501.12948v1.

Sources: [279]

Evidence: Reviewed-work bibliography - DeepSeek-V3 Technical Report. Source: https://arxiv.org/pdf/2412.19437v1. Inspected version: 2412.19437v1.

Sources: [280]

Evidence: Reviewed-work bibliography - DeepSeekMath: Pushing the Limits of Mathematical Reasoning in Open Language Models. Source: https://arxiv.org/pdf/2402.03300v1. Inspected version: 2402.03300v1.

Sources: [278]

Evidence: Reviewed-work bibliography - Deliberative Alignment: Reasoning Enables Safer Language Models. Source: https://arxiv.org/pdf/2412.16339v1. Inspected version: 2412.16339v1.

Sources: [281]

Evidence: Reviewed-work bibliography - DICES Dataset: Diversity in Conversational AI Evaluation for Safety. Source: https://arxiv.org/pdf/2306.11247v1. Inspected version: 2306.11247v1.

Sources: [106]

Evidence: Reviewed-work bibliography - Direct Preference Optimization: Your Language Model is Secretly a Reward Model. Source: https://arxiv.org/abs/2305.18290v3. Inspected version: 2305.18290v3.

Sources: [457], [465]

Evidence: Reviewed-work bibliography - Documenting Large Webtext Corpora: A Case Study on the Colossal Clean Crawled Corpus. Source: https://arxiv.org/pdf/2104.08758v2. Inspected version: 2104.08758v2.

Sources: [389]

Evidence: Reviewed-work bibliography - Dolma: an Open Corpus of Three Trillion Tokens for Language Model Pretraining Research. Source: https://arxiv.org/pdf/2402.00159v1. Inspected version: 2402.00159v1.

Sources: [108]

Evidence: Reviewed-work bibliography - Evaluating Large Language Models Trained on Code. Source: https://arxiv.org/pdf/2107.03374v1. Inspected version: 2107.03374v1.

Sources: [204]

Evidence: Reviewed-work bibliography - Extracting Training Data from Large Language Models. Source: https://arxiv.org/pdf/2012.07805v2. Inspected version: 2012.07805v2.

Sources: [372]

Evidence: Reviewed-work bibliography - Fair human-centric image dataset for ethical AI benchmarking. Source: https://www.cs.utexas.edu/~pstone/Papers/bib2html-links/peter_nature_2025.pdf. Inspected version: institutional-copy-sha256-66ac69cbb2d33c170f14ff64072c07c51ab5d3ff66c2357a69dbb59d64fcaf78.

Sources: [373]

Evidence: Reviewed-work bibliography - GAIA: A Benchmark for General AI Assistants. Source: https://arxiv.org/pdf/2311.12983v1. Inspected version: 2311.12983v1.

Sources: [200]

Evidence: Reviewed-work bibliography - GDPval: Evaluating AI Model Performance on Real-World Economically Valuable Tasks. Source: https://arxiv.org/pdf/2510.04374v1. Inspected version: 2510.04374v1.

Sources: [335]

Evidence: Reviewed-work bibliography - GPQA: A Graduate-Level Google-Proof Q&A Benchmark. Source: https://arxiv.org/pdf/2311.12022v1. Inspected version: 2311.12022v1.

Sources: [336]

Evidence: Reviewed-work bibliography - GPT-4 Technical Report. Source: https://arxiv.org/pdf/2303.08774v1. Inspected version: 2303.08774v1.

Sources: [288]

Evidence: Reviewed-work bibliography - Group Sequence Policy Optimization. Source: https://arxiv.org/pdf/2507.18071v2. Inspected version: 2507.18071v2.

Sources: [392]

Evidence: Reviewed-work bibliography - HarmBench: A Standardized Evaluation Framework for Automated Red Teaming and Robust Refusal. Source: https://arxiv.org/pdf/2402.04249v1. Inspected version: 2402.04249v1.

Sources: [203]

Evidence: Reviewed-work bibliography - HelpSteer3-Preference: Open Human-Annotated Preference Data across Diverse Tasks and Languages. Source: https://arxiv.org/abs/2505.11475v2. Inspected version: 2505.11475v2.

Sources: [460]

Evidence: Reviewed-work bibliography - How do data owners say no? A case study of data consent mechanisms in web-scraped vision-language AI training datasets. Source: https://arxiv.org/pdf/2511.08637v1. Inspected version: 2511.08637v1.

Sources: [369]

Evidence: Reviewed-work bibliography - How Reliable is Multilingual LLM-as-a-Judge?. Source: https://aclanthology.org/2025.findings-emnlp.587.pdf. Inspected version: ACL-2025.findings-emnlp.587-published; anthology metadata commit ba3130005282c6474307cceec936373fe55d15ff.

Sources: [381]

Evidence: Reviewed-work bibliography - Humanity's Last Exam. Source: https://arxiv.org/pdf/2501.14249v1. Inspected version: 2501.14249v1.

Sources: [339]

Evidence: Reviewed-work bibliography - HybridFlow: A Flexible and Efficient RLHF Framework. Source: https://arxiv.org/pdf/2409.19256v2. Inspected version: 2409.19256v2.

Sources: [393]

Evidence: Reviewed-work bibliography - If in a Crowdsourced Data Annotation Pipeline, a GPT-4. Source: https://arxiv.org/pdf/2402.16795v2. Inspected version: 2402.16795v2.

Sources: [391]

Evidence: Reviewed-work bibliography - Improving Task Instructions for Data Annotators: How Clear Rules and Higher Pay Increase Performance in Data Annotation in the AI Economy. Source: https://arxiv.org/pdf/2312.14565v2. Inspected version: 2312.14565v2.

Sources: [374]

Evidence: Reviewed-work bibliography - Instruction-Following Evaluation for Large Language Models. Source: https://arxiv.org/pdf/2311.07911v1. Inspected version: 2311.07911v1.

Sources: [340]

Evidence: Reviewed-work bibliography - Is It Thinking or Cheating? Detecting Implicit Reward Hacking by Measuring Reasoning Effort. Source: https://arxiv.org/pdf/2510.01367v1. Inspected version: 2510.01367v1.

Sources: [383]

Evidence: Reviewed-work bibliography - JailbreakBench: An Open Robustness Benchmark for Jailbreaking Large Language Models. Source: https://arxiv.org/pdf/2404.01318v5. Inspected version: 2404.01318v5.

Sources: [205]

Evidence: Reviewed-work bibliography - KTO: Model Alignment as Prospect Theoretic Optimization. Source: https://arxiv.org/pdf/2402.01306v1. Inspected version: 2402.01306v1.

Sources: [41]

Evidence: Reviewed-work bibliography - Learning from Natural Language Feedback. Source: https://arxiv.org/pdf/2204.14146v1. Inspected version: 2204.14146v1.

Sources: [290]

Evidence: Reviewed-work bibliography - Learning to summarize from human feedback. Source: https://arxiv.org/pdf/2009.01325v3. Inspected version: 2009.01325v3.

Sources: [133]

Evidence: Reviewed-work bibliography - Let's Verify Step by Step. Source: https://arxiv.org/pdf/2305.20050v1. Inspected version: 2305.20050v1.

Sources: [51]

Evidence: Reviewed-work bibliography - LIMA: Less Is More for Alignment. Source: https://arxiv.org/pdf/2305.11206v1. Inspected version: 2305.11206v1.

Sources: [124]

Evidence: Reviewed-work bibliography - Llama 2: Open Foundation and Fine-Tuned Chat Models. Source: https://arxiv.org/pdf/2307.09288v1. Inspected version: 2307.09288v1.

Sources: [293]

Evidence: Reviewed-work bibliography - M-IFEval: Multilingual Instruction-Following Evaluation. Source: https://aclanthology.org/2025.findings-naacl.344.pdf. Inspected version: ACL-2025.findings-naacl.344-published; anthology metadata commit ba3130005282c6474307cceec936373fe55d15ff.

Sources: [376]

Evidence: Reviewed-work bibliography - M-RewardBench: Evaluating Reward Models in Multilingual Settings. Source: https://aclanthology.org/2025.acl-long.3.pdf. Inspected version: ACL-2025.acl-long.3-published; anthology metadata commit ba3130005282c6474307cceec936373fe55d15ff.

Sources: [379]

Evidence: Reviewed-work bibliography - MathVista: Evaluating Mathematical Reasoning of Foundation Models in Visual Contexts. Source: https://arxiv.org/pdf/2310.02255v1. Inspected version: 2310.02255v1.

Sources: [206]

Evidence: Reviewed-work bibliography - Measuring Massive Multitask Language Understanding. Source: https://arxiv.org/pdf/2009.03300v3. Inspected version: 2009.03300v3.

Sources: [463]

Evidence: Reviewed-work bibliography - MENLO: From Preferences to Proficiency -- Evaluating and Modeling Native-like Quality Across 47 Languages. Source: https://arxiv.org/pdf/2509.26601v1. Inspected version: 2509.26601v1.

Sources: [375]

Evidence: Reviewed-work bibliography - Minority Reports: Balancing Cost and Quality in Ground Truth Data Annotation. Source: https://arxiv.org/pdf/2504.09341v1. Inspected version: 2504.09341v1.

Sources: [395]

Evidence: Reviewed-work bibliography - MLE-bench: Evaluating Machine Learning Agents on Machine Learning Engineering. Source: https://arxiv.org/pdf/2410.07095v1. Inspected version: 2410.07095v1.

Sources: [348]

Evidence: Reviewed-work bibliography - MMMU-Pro: A More Robust Multi-discipline Multimodal Understanding Benchmark. Source: https://arxiv.org/pdf/2409.02813v1. Inspected version: 2409.02813v1.

Sources: [349]

Evidence: Reviewed-work bibliography - MMMU: A Massive Multi-discipline Multimodal Understanding and Reasoning Benchmark for Expert AGI. Source: https://arxiv.org/pdf/2311.16502v1. Inspected version: 2311.16502v1.

Sources: [212]

Evidence: Reviewed-work bibliography - Model Cards for Model Reporting. Source: https://arxiv.org/pdf/1810.03993v2. Inspected version: 1810.03993v2.

Sources: [377]

Evidence: Reviewed-work bibliography - Monitoring Reasoning Models for Misbehavior and the Risks of Promoting Obfuscation. Source: https://arxiv.org/pdf/2503.11926v1. Inspected version: 2503.11926v1.

Sources: [378]

Evidence: Reviewed-work bibliography - MultiChallenge: A Realistic Multi-Turn Conversation Evaluation Benchmark Challenging to Frontier LLMs. Source: https://arxiv.org/pdf/2501.17399v1. Inspected version: 2501.17399v1.

Sources: [380]

Evidence: Reviewed-work bibliography - On the Reliability of Majority-Vote Pseudo-Labels in Test-Time Reinforcement Learning. Source: https://arxiv.org/pdf/2611.09872v1. Inspected version: 2611.09872v1.

Sources: [401]

Evidence: Reviewed-work bibliography - OpenRLHF: An Easy-to-use, Scalable and High-performance RLHF Framework. Source: https://arxiv.org/pdf/2405.11143v6. Inspected version: 2405.11143v6.

Sources: [397]

Evidence: Reviewed-work bibliography - OSWorld: Benchmarking Multimodal Agents for Open-Ended Tasks in Real Computer Environments. Source: https://arxiv.org/pdf/2404.07972v1. Inspected version: 2404.07972v1.

Sources: [213]

Evidence: Reviewed-work bibliography - PaperBench: Evaluating AI's Ability to Replicate AI Research. Source: https://arxiv.org/pdf/2504.01848v1. Inspected version: 2504.01848v1.

Sources: [350]

Evidence: Reviewed-work bibliography - Process Reinforcement through Implicit Rewards. Source: https://arxiv.org/pdf/2502.01456v2. Inspected version: 2502.01456v2.

Sources: [398]

Evidence: Reviewed-work bibliography - Program Synthesis with Large Language Models. Source: https://arxiv.org/pdf/2108.07732v1. Inspected version: 2108.07732v1.

Sources: [207]

Evidence: Reviewed-work bibliography - Proximal Policy Optimization Algorithms. Source: https://arxiv.org/pdf/1707.06347v1. Inspected version: 1707.06347v1.

Sources: [50]

Evidence: Reviewed-work bibliography - RAFT: Reward rAnked FineTuning for Generative Foundation Model Alignment. Source: https://arxiv.org/pdf/2304.06767v1. Inspected version: 2304.06767v1.

Sources: [299]

Evidence: Reviewed-work bibliography - RE-Bench: Evaluating frontier AI R&D capabilities of language model agents against human experts. Source: https://arxiv.org/pdf/2411.15114v1. Inspected version: 2411.15114v1.

Sources: [351]

Evidence: Reviewed-work bibliography - REBEL: Reinforcement Learning via Regressing Relative Rewards. Source: https://arxiv.org/pdf/2404.16767v1. Inspected version: 2404.16767v1.

Sources: [300]

Evidence: Reviewed-work bibliography - Red Teaming Language Models to Reduce Harms: Methods, Scaling Behaviors, and Lessons Learned. Source: https://arxiv.org/pdf/2209.07858v1. Inspected version: 2209.07858v1.

Sources: [129]

Evidence: Reviewed-work bibliography - Reference-free Monolithic Preference Optimization with Odds Ratio. Source: https://arxiv.org/pdf/2403.07691v1. Inspected version: 2403.07691v1.

Sources: [49]

Evidence: Reviewed-work bibliography - REINFORCE++: Stabilizing Critic-Free Policy Optimization with Global Advantage Normalization. Source: https://arxiv.org/pdf/2501.03262v9. Inspected version: 2501.03262v9.

Sources: [400]

Evidence: Reviewed-work bibliography - Reinforcement Learning on Web Interfaces Using Workflow-Guided Exploration. Source: https://arxiv.org/pdf/1802.08802v1. Inspected version: 1802.08802v1.

Sources: [211]

Evidence: Reviewed-work bibliography - ReMax: A Simple, Effective, and Efficient Method for Aligning Large Language Models. Source: https://arxiv.org/pdf/2310.10505v1. Inspected version: 2310.10505v1.

Sources: [301]

Evidence: Reviewed-work bibliography - RewardBench 2: Advancing Reward Model Evaluation. Source: https://arxiv.org/pdf/2506.01937v1. Inspected version: 2506.01937v1.

Sources: [352]

Evidence: Reviewed-work bibliography - RLAIF-V: Aligning MLLMs through Open-Source AI Feedback for Super GPT-4V Trustworthiness. Source: https://arxiv.org/pdf/2405.17220v1. Inspected version: 2405.17220v1.

Sources: [130]

Evidence: Reviewed-work bibliography - RLAIF: Scaling Reinforcement Learning from Human Feedback with AI Feedback. Source: https://arxiv.org/pdf/2309.00267v1. Inspected version: 2309.00267v1.

Sources: [52]

Evidence: Reviewed-work bibliography - RRHF: Rank Responses to Align Language Models with Human Feedback without tears. Source: https://arxiv.org/pdf/2304.05302v1. Inspected version: 2304.05302v1.

Sources: [303]

Evidence: Reviewed-work bibliography - Scaling Instruction-Finetuned Language Models. Source: https://arxiv.org/pdf/2210.11416v5. Inspected version: 2210.11416v5.

Sources: [111]

Evidence: Reviewed-work bibliography - ScienceAgentBench: Toward Rigorous Assessment of Language Agents for Data-Driven Scientific Discovery. Source: https://arxiv.org/pdf/2410.05080v1. Inspected version: 2410.05080v1.

Sources: [353]

Evidence: Reviewed-work bibliography - ScienceWorld: Is your Agent Smarter than a 5th Grader?. Source: https://arxiv.org/pdf/2203.07540v1. Inspected version: 2203.07540v1.

Sources: [235]

Evidence: Reviewed-work bibliography - SelectTTRL: Representation-Guided Data Selection for Efficient Test-Time Reinforcement Learning. Source: https://arxiv.org/pdf/2610.16104v1. Inspected version: 2610.16104v1.

Sources: [402]

Evidence: Reviewed-work bibliography - SELF-INSTRUCT: Aligning Language Model with Self Generated Instructions. Source: https://arxiv.org/pdf/2212.10560v1. Inspected version: 2212.10560v1.

Sources: [56]

Evidence: Reviewed-work bibliography - Self-Play Preference Optimization for Language Model Alignment. Source: https://arxiv.org/pdf/2405.00675v1. Inspected version: 2405.00675v1.

Sources: [311]

Evidence: Reviewed-work bibliography - Self-Refine: Iterative Refinement with Self-Feedback. Source: https://arxiv.org/pdf/2303.17651v2. Inspected version: 2303.17651v2.

Sources: [131]

Evidence: Reviewed-work bibliography - ShieldAgent: Shielding Agents via Verifiable Safety Policy Reasoning. Source: https://arxiv.org/pdf/2503.22738v1. Inspected version: 2503.22738v1.

Sources: [382]

Evidence: Reviewed-work bibliography - SimPO: Simple Preference Optimization with a Reference-Free Reward. Source: https://arxiv.org/pdf/2405.14734v1. Inspected version: 2405.14734v1.

Sources: [309]

Evidence: Reviewed-work bibliography - SkillsBench: Benchmarking How Well Agent Skills Work Across Diverse Tasks. Source: https://arxiv.org/pdf/2602.12670v1. Inspected version: 2602.12670v1.

Sources: [354]

Evidence: Reviewed-work bibliography - SLiC-HF: Sequence Likelihood Calibration with Human Feedback. Source: https://arxiv.org/pdf/2305.10425v1. Inspected version: 2305.10425v1.

Sources: [310]

Evidence: Reviewed-work bibliography - Sources of Disagreement in Data for LLM Instruction Tuning. Source: https://aclanthology.org/2025.comedi-1.3.pdf. Inspected version: acl.2025.comedi-1.3.

Sources: [107]

Evidence: Reviewed-work bibliography - STAMP Your Content: Proving Dataset Membership via Watermarked Rephrasings. Source: https://arxiv.org/pdf/2504.13416v2. Inspected version: 2504.13416v2.

Sources: [403]

Evidence: Reviewed-work bibliography - Statistical Rejection Sampling Improves Preference Optimization. Source: https://arxiv.org/pdf/2309.06657v1. Inspected version: 2309.06657v1.

Sources: [304]

Evidence: Reviewed-work bibliography - Step-DPO: Step-wise Preference Optimization for Long-chain Reasoning of LLMs. Source: https://arxiv.org/pdf/2406.18629v1. Inspected version: 2406.18629v1.

Sources: [312]

Evidence: Reviewed-work bibliography - SWE-bench Multimodal: Do AI Systems Generalize to Visual Software Domains?. Source: https://arxiv.org/pdf/2410.03859v1. Inspected version: 2410.03859v1.

Sources: [359]

Evidence: Reviewed-work bibliography - SWE-Bench Pro: Can AI Agents Solve Long-Horizon Software Engineering Tasks?. Source: https://arxiv.org/pdf/2509.16941v1. Inspected version: 2509.16941v1.

Sources: [360]

Evidence: Reviewed-work bibliography - SWE-bench: Can Language Models Resolve Real-World GitHub Issues?. Source: https://arxiv.org/pdf/2310.06770v3. Inspected version: 2310.06770v3.

Sources: [466]

Evidence: Reviewed-work bibliography - SWE-Lancer: Can Frontier LLMs Earn $1 Million from Real-World Freelance Software Engineering?. Source: https://arxiv.org/pdf/2502.12115v1. Inspected version: 2502.12115v1.

Sources: [358]

Evidence: Reviewed-work bibliography - Terminal-Bench: Benchmarking Agents on Hard, Realistic Tasks in Command Line Interfaces. Source: https://arxiv.org/pdf/2601.11868v1. Inspected version: 2601.11868v1.

Sources: [362]

Evidence: Reviewed-work bibliography - The Common Pile v0.1: An 8TB Dataset of Public Domain and Openly Licensed Text. Source: https://arxiv.org/pdf/2506.05209v1. Inspected version: 2506.05209v1.

Sources: [367]

Evidence: Reviewed-work bibliography - The Data Provenance Initiative: A Large Scale Audit of Dataset Licensing & Attribution in AI. Source: https://arxiv.org/pdf/2310.16787v1. Inspected version: 2310.16787v1.

Sources: [128]

Evidence: Reviewed-work bibliography - The Data-Production Dispositif. Source: https://arxiv.org/pdf/2205.11963v1. Inspected version: 2205.11963v1.

Sources: [370]

Evidence: Reviewed-work bibliography - The Dataset Nutrition Label: A Framework To Drive Higher Data Quality Standards. Source: https://arxiv.org/pdf/1805.03677v1. Inspected version: 1805.03677v1.

Sources: [396]

Evidence: Reviewed-work bibliography - The digital labour of artificial intelligence in Latin America: a comparison of Argentina, Brazil, and Venezuela. Source: https://arxiv.org/pdf/2502.06317v1. Inspected version: 2502.06317v1.

Sources: [394]

Evidence: Reviewed-work bibliography - The FineWeb Datasets: Decanting the Web for the Finest Text Data at Scale. Source: https://arxiv.org/pdf/2406.17557v2. Inspected version: 2406.17557v2.

Sources: [467]

Evidence: Reviewed-work bibliography - The Llama 3 Herd of Models. Source: https://arxiv.org/pdf/2407.21783v1. Inspected version: 2407.21783v1.

Sources: [294]

Evidence: Reviewed-work bibliography - The Problems with Proxies: Making Data Work Visible through Requester Practices. Source: https://arxiv.org/pdf/2408.11667v1. Inspected version: 2408.11667v1.

Sources: [399]

Evidence: Reviewed-work bibliography - TheAgentCompany: Benchmarking LLM Agents on Consequential Real World Tasks. Source: https://arxiv.org/pdf/2412.14161v1. Inspected version: 2412.14161v1.

Sources: [318]

Evidence: Reviewed-work bibliography - ToolLLM: Facilitating Large Language Models to Master 16000+ Real-world APIs. Source: https://arxiv.org/pdf/2307.16789v1. Inspected version: 2307.16789v1.

Sources: [237]

Evidence: Reviewed-work bibliography - Training a Helpful and Harmless Assistant with Reinforcement Learning from Human Feedback. Source: https://arxiv.org/pdf/2204.05862v1. Inspected version: 2204.05862v1.

Sources: [112]

Evidence: Reviewed-work bibliography - Training language models to follow instructions with human feedback. Source: https://arxiv.org/abs/2203.02155v1. Inspected version: 2203.02155v1.

Sources: [456], [464]

Evidence: Reviewed-work bibliography - Training Verifiers to Solve Math Word Problems. Source: https://arxiv.org/pdf/2110.14168v1. Inspected version: 2110.14168v1.

Sources: [63]

Evidence: Reviewed-work bibliography - TruthfulQA: Measuring How Models Mimic Human Falsehoods. Source: https://arxiv.org/pdf/2109.07958v2. Inspected version: 2109.07958v2.

Sources: [450]

Evidence: Reviewed-work bibliography - TTRL: Test-Time Reinforcement Learning. Source: https://arxiv.org/pdf/2504.16084v3. Inspected version: 2504.16084v3.

Sources: [404]

Evidence: Reviewed-work bibliography - Understanding R1-Zero-Like Training: A Critical Perspective. Source: https://arxiv.org/pdf/2503.20783v2. Inspected version: 2503.20783v2.

Sources: [390]

Evidence: Reviewed-work bibliography - VAPO: Efficient and Reliable Reinforcement Learning for Advanced Reasoning Tasks. Source: https://arxiv.org/pdf/2504.05118v3. Inspected version: 2504.05118v3.

Sources: [405]

Evidence: Reviewed-work bibliography - VerifiAgent: a Unified Verification Agent in Language Model Reasoning. Source: https://arxiv.org/pdf/2504.00406v1. Inspected version: 2504.00406v1.

Sources: [384]

Evidence: Reviewed-work bibliography - Video-MME: The First-Ever Comprehensive Evaluation Benchmark of Multi-modal LLMs in Video Analysis. Source: https://arxiv.org/pdf/2405.21075v1. Inspected version: 2405.21075v1.

Sources: [365]

Evidence: Reviewed-work bibliography - VisualWebArena: Evaluating Multimodal Agents on Realistic Visual Web Tasks. Source: https://arxiv.org/pdf/2401.13649v1. Inspected version: 2401.13649v1.

Sources: [238]

Evidence: Reviewed-work bibliography - WebArena: A Realistic Web Environment for Building Autonomous Agents. Source: https://arxiv.org/pdf/2307.13854v1. Inspected version: 2307.13854v1.

Sources: [64]

Evidence: Reviewed-work bibliography - WebShop: Towards Scalable Real-World Web Interaction with Grounded Language Agents. Source: https://arxiv.org/pdf/2207.01206v1. Inspected version: 2207.01206v1.

Sources: [239]

Evidence: Reviewed-work bibliography - WizardLM: Empowering Large Pre-Trained Language Models to Follow Complex Instructions. Source: https://arxiv.org/pdf/2304.12244v3. Inspected version: 2304.12244v3.

Sources: [134]

Evidence: Reviewed-work bibliography - World of Bits: An Open-Domain Platform for Web-Based Agents. Source: https://proceedings.mlr.press/v70/shi17a/shi17a.pdf. Inspected version: PMLR-v70-shi17a-2017.

Sources: [385]

Evidence: Reviewed-work bibliography - WPO: Enhancing RLHF with Weighted Preference Optimization. Source: https://arxiv.org/pdf/2406.11827v1. Inspected version: 2406.11827v1.

Sources: [317]

Evidence: Reviewed-work bibliography - τ-bench: A Benchmark for Tool-Agent-User Interaction in Real-World Domains. Source: https://arxiv.org/pdf/2406.12045v1. Inspected version: 2406.12045v1.

Sources: [236]

Evidence: Reviewed-work bibliography - “Everyone wants to do the model work, not the data work”: Data Cascades in High-Stakes AI. Source: https://storage.googleapis.com/gweb-research2023-media/pubtools/pdf/0d556e45afc54afeb2eb6b51a9bc1827b9961ff4.pdf. Inspected version: doi.10.1145.3411764.3445518.

Sources: [101]

Evidence: Reviewed-work bibliography - AutoLibra: Agent Metric Induction from Open-Ended Human Feedback. Source: https://arxiv.org/pdf/2505.02820v3. Inspected version: 2505.02820v3.

Sources: [406]

Evidence: Reviewed-work bibliography - Aya Dataset: An Open-Access Collection for Multilingual Instruction Tuning. Source: https://arxiv.org/pdf/2402.06619v1. Inspected version: 2402.06619v1.

Sources: [407]

Evidence: Reviewed-work bibliography - CrowdAgent: Multi-Agent Managed Multi-Source Annotation System. Source: https://aclanthology.org/2025.emnlp-demos.72.pdf. Inspected version: ACL-Anthology-2025.emnlp-demos.72-captured-copy.

Sources: [408]

Evidence: Reviewed-work bibliography - CrowdTruth 2.0: Quality Metrics for Crowdsourcing with Disagreement. Source: https://arxiv.org/pdf/1808.06080v1. Inspected version: 1808.06080v1.

Sources: [409]

Evidence: Reviewed-work bibliography - A Data-Driven Analysis of Workers' Earnings on Amazon Mechanical Turk. Source: https://arxiv.org/pdf/1712.05796v2. Inspected version: 1712.05796v2.

Sources: [410]

Evidence: Reviewed-work bibliography - Experts Rise Where LLMs Disagree: Using Cross-Model Disagreement to Target Expert Effort in LLM Codebook Revision for Large-Scale Annotation. Source: https://arxiv.org/pdf/2609.26926v1. Inspected version: 2609.26926v1.

Sources: [411]

Evidence: Reviewed-work bibliography - Garbage In, Garbage Out? Do Machine Learning Application Papers in Social Computing Report Where Human-Labeled Training Data Comes From?. Source: https://arxiv.org/pdf/1912.08320v1. Inspected version: 1912.08320v1.

Sources: [412]

Evidence: Reviewed-work bibliography - ChatGPT Outperforms Crowd-Workers for Text-Annotation Tasks. Source: https://arxiv.org/pdf/2303.15056v2. Inspected version: 2303.15056v2.

Sources: [413]

Evidence: Reviewed-work bibliography - HelpSteer: Multi-attribute Helpfulness Dataset for SteerLM. Source: https://arxiv.org/pdf/2311.09528v1. Inspected version: 2311.09528v1.

Sources: [414]

Evidence: Reviewed-work bibliography - HelpSteer2: Open-source dataset for training top-performing reward models. Source: https://arxiv.org/pdf/2406.08673v1. Inspected version: 2406.08673v1.

Sources: [415]

Evidence: Reviewed-work bibliography - Inherent Disagreements in Human Textual Inferences. Source: https://aclanthology.org/Q19-1043.pdf. Inspected version: ACL-Anthology-Q19-1043-captured-copy.

Sources: [416]

Evidence: Reviewed-work bibliography - LabelAId: Just-in-time AI Interventions for Improving Human Labeling Quality and Domain Knowledge in Crowdsourcing Systems. Source: https://arxiv.org/pdf/2403.09810v1. Inspected version: 2403.09810v1.

Sources: [417]

Evidence: Reviewed-work bibliography - Pervasive Label Errors in Test Sets Destabilize Machine Learning Benchmarks. Source: https://arxiv.org/pdf/2103.14749v4. Inspected version: 2103.14749v4.

Sources: [418]

Evidence: Reviewed-work bibliography - Efficient Data Labeling by Hierarchical Crowdsourcing with Large Language Models. Source: https://aclanthology.org/2025.coling-main.748.pdf. Inspected version: ACL-Anthology-2025.coling-main.748-captured-copy.

Sources: [419]

Evidence: Reviewed-work bibliography - Quality Assured: Rethinking Annotation Strategies in Imaging AI. Source: https://arxiv.org/pdf/2407.17596v2. Inspected version: 2407.17596v2.

Sources: [420]

Evidence: Reviewed-work bibliography - RECODE-H: A Benchmark for Research Code Development with Interactive Human Feedback. Source: https://arxiv.org/pdf/2510.06186v2. Inspected version: 2510.06186v2.

Sources: [421]

Evidence: Reviewed-work bibliography - Cheap and Fast - But is it Good? Evaluating Non-Expert Annotations for Natural Language Tasks. Source: https://aclanthology.org/D08-1027.pdf. Inspected version: ACL-Anthology-D08-1027-captured-copy.

Sources: [422]

Evidence: Reviewed-work bibliography - UltraFeedback: Boosting Language Models with Scaled AI Feedback. Source: https://arxiv.org/pdf/2310.01377v2. Inspected version: 2310.01377v2.

Sources: [423]

Evidence: Reviewed-work bibliography - Who Annotates in NLP? A Large-scale Assessment of Human Annotation Reporting between 2018 and 2025. Source: https://arxiv.org/pdf/2606.02255v3. Inspected version: 2606.02255v3.

Sources: [424]

Evidence: Reviewed-work bibliography - WildChat: 1M ChatGPT Interaction Logs in the Wild. Source: https://arxiv.org/pdf/2405.01470v1. Inspected version: 2405.01470v1.

Sources: [425]

Bibliography and source versions

References group identical URL, version and response digest. Multiple evidence bindings to the same pinned document share a reference number; all source IDs, precise locators and review receipts remain separate in evidence.html and the dataset.

[1] AlpacaEval README.md. tatsu-lab/alpaca_eval; cd543a149df89434d8a54582c0151c0b945c3d20
https://raw.githubusercontent.com/tatsu-lab/alpaca_eval/cd543a149df89434d8a54582c0151c0b945c3d20/README.md
Response SHA-256: 27576663fb6f13adf5b3adea8d7840f47ffe366fca74177fe6aac92e8b6ff11c
Scoped evidence bindings: 6

[2] BeaverTails README.md. PKU-Alignment/BeaverTails; 8401fe609d288129cc684a9b3be6a93e41cfe678
https://huggingface.co/datasets/PKU-Alignment/BeaverTails/raw/8401fe609d288129cc684a9b3be6a93e41cfe678/README.md
Response SHA-256: 92bce76909c3abb6e7ca2bbb1240f6b03da0a531cde8c03b3bbf7cb20c9a7bef
Scoped evidence bindings: 6

[3] GPQA LICENSE. Idavidrein/gpqa; 56686c06f5e19865c153de0fdb11be3890014df7
https://raw.githubusercontent.com/Idavidrein/gpqa/56686c06f5e19865c153de0fdb11be3890014df7/LICENSE
Response SHA-256: 09c64e279464e54aa88696bcb73dc77722f905a028313c48a17e16572db00d8a
Scoped evidence bindings: 1

[4] GPQA arXiv HTML. GPQA paper authors / arXiv; 2311.12022v1
https://arxiv.org/html/2311.12022v1
Response SHA-256: 6c4a6426771956afd4b61176bfaecce0d773f4c1fa8dc76e87de33b2081905a9
Scoped evidence bindings: 3

[5] GPQA README.md. Idavidrein/gpqa; 56686c06f5e19865c153de0fdb11be3890014df7
https://raw.githubusercontent.com/Idavidrein/gpqa/56686c06f5e19865c153de0fdb11be3890014df7/README.md
Response SHA-256: 0be2cf410fecf82fb811f02e2314ecc5a19decc1515014498e59bae4680d4d81
Scoped evidence bindings: 2

[6] GSM8K LICENSE. openai/grade-school-math; 3101c7d5072418e28b9008a6636bde82a006892c
https://raw.githubusercontent.com/openai/grade-school-math/3101c7d5072418e28b9008a6636bde82a006892c/LICENSE
Response SHA-256: 86bbb73e855821d7c401912fd4bf82e34313e6e3b6fd6f909f2b6cc9e209a53b
Scoped evidence bindings: 1

[7] GSM8K README.md. openai/grade-school-math; 3101c7d5072418e28b9008a6636bde82a006892c
https://raw.githubusercontent.com/openai/grade-school-math/3101c7d5072418e28b9008a6636bde82a006892c/README.md
Response SHA-256: 27e1676d572f2289210170ff6dbb8c2ef7d9f6950c0f08c978ea8ee6b39dca29
Scoped evidence bindings: 4

[8] Humanity’s Last Exam hle_eval/run_judge_results.py. centerforaisafety/hle; 22ed3074b1e7b134bcbc09028d0ba320839b0655
https://raw.githubusercontent.com/centerforaisafety/hle/22ed3074b1e7b134bcbc09028d0ba320839b0655/hle_eval/run_judge_results.py
Response SHA-256: a796e74d6e58beab3bd88f46182f599443a102308b2d1c7e0b4b22f578468446
Scoped evidence bindings: 2

[9] Humanity’s Last Exam LICENSE. centerforaisafety/hle; 22ed3074b1e7b134bcbc09028d0ba320839b0655
https://raw.githubusercontent.com/centerforaisafety/hle/22ed3074b1e7b134bcbc09028d0ba320839b0655/LICENSE
Response SHA-256: f402878026b8008bd53f2f038b5c9e3e6b7c1a690e05e2ca6ddbc9019aa3c08e
Scoped evidence bindings: 1

[10] Humanity’s Last Exam README.md. centerforaisafety/hle; 22ed3074b1e7b134bcbc09028d0ba320839b0655
https://raw.githubusercontent.com/centerforaisafety/hle/22ed3074b1e7b134bcbc09028d0ba320839b0655/README.md
Response SHA-256: fd3bd0049e1a2b39244d8240a63d0ccfe037b0b6e5979d5826e1d1cf4203ee88
Scoped evidence bindings: 4

[11] MT-Bench LICENSE. lm-sys/FastChat; 587d5cfa1609a43d192cedb8441cac3c17db105d
https://raw.githubusercontent.com/lm-sys/FastChat/587d5cfa1609a43d192cedb8441cac3c17db105d/LICENSE
Response SHA-256: c71d239df91726fc519c6eb72d318ec65820627232b2f796219e87dcf35d0ab4
Scoped evidence bindings: 1

[12] MT-Bench fastchat/llm_judge/README.md. lm-sys/FastChat; 587d5cfa1609a43d192cedb8441cac3c17db105d
https://raw.githubusercontent.com/lm-sys/FastChat/587d5cfa1609a43d192cedb8441cac3c17db105d/fastchat/llm_judge/README.md
Response SHA-256: 4104f9e877fe04a4a87a5b6618114adc8604f09ceca09be198f96189c4c2238e
Scoped evidence bindings: 5

[13] Nectar README.md. berkeley-nest/Nectar; 3c6b4c47fa1cc38869f9f32dce1699f7abad8b06
https://huggingface.co/datasets/berkeley-nest/Nectar/raw/3c6b4c47fa1cc38869f9f32dce1699f7abad8b06/README.md
Response SHA-256: dfd3ff7efc6cf425eb9846a5f49ad4d3997655b45ee0f0b147a7afa59c3a1d9a
Scoped evidence bindings: 8

[14] OpenHermes README.md. teknium/OpenHermes-2.5; b82037821055c377bed0d495e72e46de3bc72e84
https://huggingface.co/datasets/teknium/OpenHermes-2.5/raw/b82037821055c377bed0d495e72e46de3bc72e84/README.md
Response SHA-256: 92fd711b9f0f6f8c7312d18d93ad412af415cd25a207584554c8e72c0cfe9f64
Scoped evidence bindings: 5

[15] PRM800K LICENSE. openai/prm800k; 7ecc794703b2877f63226f2477a49b34f9b25163
https://raw.githubusercontent.com/openai/prm800k/7ecc794703b2877f63226f2477a49b34f9b25163/LICENSE
Response SHA-256: 22d61a2226e035da51c56149c3358c36d1f61716435866bc6e6fe0e54c7270db
Scoped evidence bindings: 1

[16] PRM800K README.md. openai/prm800k; 7ecc794703b2877f63226f2477a49b34f9b25163
https://raw.githubusercontent.com/openai/prm800k/7ecc794703b2877f63226f2477a49b34f9b25163/README.md
Response SHA-256: a721d8d35cd77c128352acb3378dd32c223a41b5d0f6ca2e8b85fb4bfe88b5fe
Scoped evidence bindings: 5

[17] PKU-SafeRLHF README.md. PKU-Alignment/PKU-SafeRLHF; 9421ffafec3fa40a1f1a7d567b4d525079477ecb
https://huggingface.co/datasets/PKU-Alignment/PKU-SafeRLHF/raw/9421ffafec3fa40a1f1a7d567b4d525079477ecb/README.md
Response SHA-256: 77ce394a7406b94e7ebe04b63e25850733286369db2d038936a6114502923579
Scoped evidence bindings: 7

[18] Tülu 3 SFT Mixture README.md. allenai/tulu-3-sft-mixture; b14afda60f1bbebe55d5d2fa1e4df5042f97f8be
https://huggingface.co/datasets/allenai/tulu-3-sft-mixture/raw/b14afda60f1bbebe55d5d2fa1e4df5042f97f8be/README.md
Response SHA-256: 1b6fff37d3f206b70086d9d65015a75dfb98b603a99af7330b0d44cd198464d6
Scoped evidence bindings: 9

[19] UltraInteract README.md. openbmb/UltraInteract_pair; 3692843c72c3a297c7914cdf76c0ffce5e38a234
https://huggingface.co/datasets/openbmb/UltraInteract_pair/raw/3692843c72c3a297c7914cdf76c0ffce5e38a234/README.md
Response SHA-256: 016a683bb4e42f14a8a96963ed541d6be23710a6e9c7c5c0f0bd4bcf7038ee91
Scoped evidence bindings: 7

[20] AgentBench: Evaluating LLMs as Agents. arXiv (author-deposited preprint); 2308.03688v1
https://arxiv.org/pdf/2308.03688v1
Response SHA-256: 5cd8a5ddbbb95a8d156bc167ee640e4338ac56ec2de574c08276cb8bad27eb4e
Scoped evidence bindings: 7

[21] A Global AgTech Company + CloudFactory Partnership. CloudFactory; Exact response sha256:16b1a273e45d983cde6502f101f1af08575d909c089773b94a0db9eab7bae524
https://www.cloudfactory.com/client-stories/global-agtech-company
Response SHA-256: 16b1a273e45d983cde6502f101f1af08575d909c089773b94a0db9eab7bae524
Scoped evidence bindings: 3

[22] Data Security | CloudFactory. CloudFactory; Exact response sha256:9f1252fa9e8074fe3a58cd2dae995b32e212f2ed55eb5f3cbabd56aa1ff09a93
https://www.cloudfactory.com/data-security
Response SHA-256: 9f1252fa9e8074fe3a58cd2dae995b32e212f2ed55eb5f3cbabd56aa1ff09a93
Scoped evidence bindings: 2

[23] Constitutional AI: Harmlessness from AI Feedback. arXiv (author-deposited preprint); 2212.08073v1
https://arxiv.org/pdf/2212.08073v1
Response SHA-256: 9a456a07ad346e3372f9867d346f69f5b0f68b4c65f060aca0b8a13fa9d98e83
Scoped evidence bindings: 5

[24] Empowering Safer AI with IBM | DataForce. DataForce by TransPerfect; Exact response sha256:2de55055344325226fc7e18496f00f74cc0bc83e9af18928370f2da0dba7f6c1
https://www.dataforce.ai/success-stories/empowering-safer-ai-ibm
Response SHA-256: 2de55055344325226fc7e18496f00f74cc0bc83e9af18928370f2da0dba7f6c1
Scoped evidence bindings: 2

[25] Generative AI Training | DataForce. DataForce by TransPerfect; Exact response sha256:3dd24bbc3853acc05871aa870eb98bf4600eeea279bffb191b295c2c86484dd9
https://www.dataforce.ai/services/generative-ai-training
Response SHA-256: 3dd24bbc3853acc05871aa870eb98bf4600eeea279bffb191b295c2c86484dd9
Scoped evidence bindings: 1

[26] AI Home | DataForce. DataForce by TransPerfect; Exact response sha256:45bce3c67c97c278e6a3c7a2479905f354b2c4fb062417c37e1707984a8933ae
https://www.dataforce.ai/
Response SHA-256: 45bce3c67c97c278e6a3c7a2479905f354b2c4fb062417c37e1707984a8933ae
Scoped evidence bindings: 3

[27] DataForce - Data Privacy Notice for Vendors | DataForce. DataForce by TransPerfect; Exact response
sha256:562ebd06e7967fd3ffb2d120f642d7577d4f9eeb7747eb4d44f14ad69d5f7646
https://www.dataforce.ai/data-privacy-notice-vendors
Response SHA-256: 562ebd06e7967fd3ffb2d120f642d7577d4f9eeb7747eb4d44f14ad69d5f7646
Scoped evidence bindings: 1

[28] Data Collection Services for AI Training | Defined.ai. Defined.ai; Exact response
sha256:54e3d276bb3b02dbc277951ebe12a659ad6363501aa3e502ddc96682e94ca82d
https://defined.ai/solutions/data-collection
Response SHA-256: 54e3d276bb3b02dbc277951ebe12a659ad6363501aa3e502ddc96682e94ca82d
Scoped evidence bindings: 1

[29] Sensor Data Collection for Scalable Robotics | Defined.ai. Defined.ai; Exact response
sha256:f545e30e2f798bcdd8ae1f2f4d6d938f22bfcd422a5ee314d5a3b49be79f7e52
https://defined.ai/case-study/sensor-data-collection-robotics
Response SHA-256: f545e30e2f798bcdd8ae1f2f4d6d938f22bfcd422a5ee314d5a3b49be79f7e52
Scoped evidence bindings: 2

[30] Ethical AI: Consent, Provenance & Fair Data | Defined.ai. Defined.ai; Exact response
sha256:80aefeebc5a8249da3650cc76788eaa59d02ce96b2c9b657264cff213c5e994f
https://defined.ai/about-us/ethical-ai
Response SHA-256: 80aefeebc5a8249da3650cc76788eaa59d02ce96b2c9b657264cff213c5e994f
Scoped evidence bindings: 2

[31] Supplier Program - General Terms & Conditions | Defined.ai. Defined.ai; Exact response
sha256:ed1d419012a62a80ec3acedf945cdc49e5f8cce77db18623349dd37148418ccc
https://defined.ai/supplier-program
Response SHA-256: ed1d419012a62a80ec3acedf945cdc49e5f8cce77db18623349dd37148418ccc
Scoped evidence bindings: 1

[32] Deep Reinforcement Learning from Human Preferences. arXiv (author-deposited preprint); 1706.03741v1
https://arxiv.org/pdf/1706.03741v1
Response SHA-256: 10d47f151dcc7cb891899e14b8c4bf9e076cb120fbfc95a178cd631b25462f31
Scoped evidence bindings: 5

[33] iMerit: Improving Model Output with RLHF - Case Study. iMerit; Exact response
sha256:47995b478f4083f6615ca09fc079f72ba00ca724a1c96fd964830d672b31f010
https://7583693.fs1.hubspotusercontent-na2.net/hubfs/7583693/Case-Studies/iMerit_Improving%20Model%20Output%20with%20RLHF_Case%20Study.pdf
Response SHA-256: 47995b478f4083f6615ca09fc079f72ba00ca724a1c96fd964830d672b31f010
Scoped evidence bindings: 2

[34] RLHF Services for Expert AI Model Alignment | iMerit. iMerit; Exact response
sha256:5320c7d847e36828809a1eec081c5b3d7c9bac60d59c8f1478ab0990a15c7e20
https://imerit.ai/solutions/generative-ai-data-solutions/rlhf-services/
Response SHA-256: 5320c7d847e36828809a1eec081c5b3d7c9bac60d59c8f1478ab0990a15c7e20
Scoped evidence bindings: 2

[35] How iMerit Ensures Data Security | iMerit. iMerit; Exact response
sha256:a93411cbf2a750204aa771e88ae778cef4c54cc40d5b57ccc4f6498a12a9c692
https://imerit.ai/insights/how-imerit-ensures-data-security/
Response SHA-256: a93411cbf2a750204aa771e88ae778cef4c54cc40d5b57ccc4f6498a12a9c692
Scoped evidence bindings: 1

[36] Model-Ready AI Training Datasets | Invisible Technologies. Invisible Technologies Inc.; Exact response sha256:e8ea411895933ecb5d491ff8048f35c08d1fb22a60ed1b70a2c1cabffca6b903
https://invisibletech.ai/data-lab/data
Response SHA-256: e8ea411895933ecb5d491ff8048f35c08d1fb22a60ed1b70a2c1cabffca6b903
Scoped evidence bindings: 1

[37] Launching a Leading LLM 6 Months Faster with Invisible AI. Invisible Technologies Inc.; Exact response sha256:c5eb8ca481d14643c9d75c9d8f927b42a86dd2a3bc7ba13d11cf779c9ddce477
https://www.invisible.co/case-studies/launching-a-leading-llm-6-months-faster
Response SHA-256: c5eb8ca481d14643c9d75c9d8f927b42a86dd2a3bc7ba13d11cf779c9ddce477
Scoped evidence bindings: 2

[38] Human Experts for AI Training | Invisible Technologies. Invisible Technologies Inc.; Exact response sha256:2fd7d13864ae3f26327bb534ca19b62468fd3dffea9227bded3db3bcc25646b8
https://invisibletech.ai/data-lab/experts
Response SHA-256: 2fd7d13864ae3f26327bb534ca19b62468fd3dffea9227bded3db3bcc25646b8
Scoped evidence bindings: 1

[39] Privacy policy | Invisible Technologies. Invisible Technologies Inc.; Exact response sha256:ab2a19999e1d1e9aa87963299ee34b67ebc82bb872883ae4e42e4b4211c08378
https://invisibletech.ai/privacy-policy
Response SHA-256: ab2a19999e1d1e9aa87963299ee34b67ebc82bb872883ae4e42e4b4211c08378
Scoped evidence bindings: 1

[40] A General Theoretical Paradigm to Understand Learning from Human Preferences. arXiv (author-deposited preprint); 2310.12036v1
https://arxiv.org/pdf/2310.12036v1
Response SHA-256: 01461de3b0bcb07b069bb7f233785ad719cacb71cfad842867cc79099e02f81a
Scoped evidence bindings: 5

[41] KTO: Model Alignment as Prospect Theoretic Optimization. arXiv (author-deposited preprint); 2402.01306v1
https://arxiv.org/pdf/2402.01306v1
Response SHA-256: 64214b766a9f59bec5fb11cd65412648114a12d32f942e416c694791d9bc2293
Scoped evidence bindings: 5

[42] Alignerr Expert Network - Labelbox. Labelbox, Inc.; Exact response sha256:c64a07a0f7e2ab31d2d21f06868043b0f7d77b1f2c6ff6b0146ea8742dc00145
https://labelbox.com/products/alignerr/
Response SHA-256: c64a07a0f7e2ab31d2d21f06868043b0f7d77b1f2c6ff6b0146ea8742dc00145
Scoped evidence bindings: 3

[43] How a leading text-to-speech AI lab harnesses human-generated data to deliver generative AI faster. Labelbox, Inc.; Exact response sha256:c4c5831c89b4eda8fab3a9d6908a96bbfe9c8058a5508c3e59f00949bb403a24
https://labelbox.com/customers/text-to-speech-app-customer-story/
Response SHA-256: c4c5831c89b4eda8fab3a9d6908a96bbfe9c8058a5508c3e59f00949bb403a24
Scoped evidence bindings: 1

[44] Labelbox raises $100M+ Series E. Labelbox, Inc.; Exact response sha256:fe5502ed3564c6dd9eed2e57ef0113c006442a3a92e9438d0e4206b8d5df143a; 2026-10-14
https://labelbox.com/blog/labelbox-series-e/
Response SHA-256: fe5502ed3564c6dd9eed2e57ef0113c006442a3a92e9438d0e4206b8d5df143a
Scoped evidence bindings: 1

[45] Privacy Notice - Labelbox. Labelbox, Inc.; Exact response
sha256:66ec60b1d22a6eb140d6d54608222e1b4dd1600b7bf98e4652b88eb510d845c0
https://docs.labelbox.com/page/privacy-notice
Response SHA-256: 66ec60b1d22a6eb140d6d54608222e1b4dd1600b7bf98e4652b88eb510d845c0
Scoped evidence bindings: 2

[46] Enhancing foundational Large Language Models for a global technology leader | High-Quality AI Data to Power Innovation | LXT. LXT; Exact response
sha256:e500e7e30ef8b189268c456e82d50a6f54d90f32f7d6faf60d463ea3a6464149
https://www.lxt.ai/case-studies/enhancing-foundational-large-language-models-for-a-global-technology-leader/
Response SHA-256: e500e7e30ef8b189268c456e82d50a6f54d90f32f7d6faf60d463ea3a6464149
Scoped evidence bindings: 2

[47] Privacy Policy: High-Quality AI Data | LXT. LXT; Exact response
sha256:d13d553b535e4d30ee2b0f57387aa7572951b6997a8bcb9941de66385d84843d
https://www.lxt.ai/privacy-policy
Response SHA-256: d13d553b535e4d30ee2b0f57387aa7572951b6997a8bcb9941de66385d84843d
Scoped evidence bindings: 1

[48] RLHF Services for AI: Scalable Human Feedback for Alignment. LXT; Exact response
sha256:0e7273806c5265e4042f162d4e15c2ad2d532ea29f351a3da19b2752f1ec0fff
https://www.lxt.ai/services/rlhf-services/
Response SHA-256: 0e7273806c5265e4042f162d4e15c2ad2d532ea29f351a3da19b2752f1ec0fff
Scoped evidence bindings: 3

[49] Reference-free Monolithic Preference Optimization with Odds Ratio. arXiv (author-deposited preprint); 2403.07691v1
https://arxiv.org/pdf/2403.07691v1
Response SHA-256: 595b1bbc563473ba171744d3b7c242e9ad65f5930d654aa49d3d3b31228b52d4
Scoped evidence bindings: 5

[50] Proximal Policy Optimization Algorithms. arXiv (author-deposited preprint); 1707.06347v1
https://arxiv.org/pdf/1707.06347v1
Response SHA-256: c4f1b8b8b2e2a976c2cae67c05a347dac44ae6e63eebed9a66bfb0241bd45c93
Scoped evidence bindings: 5

[51] Let's Verify Step by Step. arXiv (author-deposited preprint); 2305.20050v1
https://arxiv.org/pdf/2305.20050v1
Response SHA-256: fbd170e2042c32950c3fe97d3a558d89e8a8dffaadc942e774ccb4b751abc123
Scoped evidence bindings: 6

[52] RLAIF: Scaling Reinforcement Learning from Human Feedback with AI Feedback. arXiv (author-deposited preprint); 2309.00267v1
https://arxiv.org/pdf/2309.00267v1
Response SHA-256: afac8f42dd040e213e0af9a6efd6a5608477c9b9270dbdfb884122aaf9b88207
Scoped evidence bindings: 5

[53] How a Fortune 500 Tech Leader Accelerated Gen AI Model Performance in the U.S. with Sama | Sama. Samasource Impact Sourcing, Inc.; Exact response
sha256:90ba08fd22c2368bb2815001a1d533064e6dc1ed27fc1d8f3eb8558659de6365
https://www.sama.com/case-studies/how-a-fortune-500-tech-leader-accelerated-gen-ai-model-performance-with-sama
Response SHA-256: 90ba08fd22c2368bb2815001a1d533064e6dc1ed27fc1d8f3eb8558659de6365
Scoped evidence bindings: 2

[54] Data Annotation & Labeling Company | Sama. Samasource Impact Sourcing, Inc.; Exact response sha256:f93112f4673178fea7d3710123a40e409bdc41e056757759705fabfb2b7580a5
https://www.sama.com/
Response SHA-256: f93112f4673178fea7d3710123a40e409bdc41e056757759705fabfb2b7580a5
Scoped evidence bindings: 2

[55] Sama Delivers High-quality & Secure Annotated Data | Sama. Samasource Impact Sourcing, Inc.; Exact response sha256:73c6dfb759025c07dfcbfcee8f39244695027e5acf8d659a229db6cb1085367c
https://www.sama.com/data-security-and-trust
Response SHA-256: 73c6dfb759025c07dfcbfcee8f39244695027e5acf8d659a229db6cb1085367c
Scoped evidence bindings: 2

[56] SELF-INSTRUCT: Aligning Language Model with Self Generated Instructions. arXiv (author-deposited preprint); 2212.10560v1
https://arxiv.org/pdf/2212.10560v1
Response SHA-256: 08dba30c0ff241ac17b2f7ac31d4202faca0f847d77bc215f9e03dc905da8553
Scoped evidence bindings: 6

[57] Databricks optimizes model evaluation with SuperAnnotate's expertise. SuperAnnotate; Exact response sha256:928302955a172e1d905bf62d2e375ae2824cc413c70b3c03f2796ef201c5fd5a
https://www.superannotate.com/blog/databricks-case-study
Response SHA-256: 928302955a172e1d905bf62d2e375ae2824cc413c70b3c03f2796ef201c5fd5a
Scoped evidence bindings: 4

[58] Trust Center | SuperAnnotate. SuperAnnotate; Exact response sha256:447b8c199555677d168ff1e84c534d8c45bb2c862c054c1cc5c7c1b7aa376c8b
https://www.superannotate.com/trust-center
Response SHA-256: 447b8c199555677d168ff1e84c534d8c45bb2c862c054c1cc5c7c1b7aa376c8b
Scoped evidence bindings: 2

[59] Global AI Policy Guidelines for TaskUs Employees. TaskUs, Inc.; Exact response sha256:63b2e4cb771bea3088f13e6690997afbc173c68cd51cacfc3571fa7a30655108
https://www.taskus.com/global-ai-policy/
Response SHA-256: 63b2e4cb771bea3088f13e6690997afbc173c68cd51cacfc3571fa7a30655108
Scoped evidence bindings: 2

[60] Smarter Data Review for Safer LLMs. TaskUs, Inc.; Exact response sha256:8c2211ab586fccb3a07ac60deea0fc1303cd71f007d23bb4e0961f754bce75ab
https://www.taskus.com/insights/smarter-data-review-for-safer-llms/
Response SHA-256: 8c2211ab586fccb3a07ac60deea0fc1303cd71f007d23bb4e0961f754bce75ab
Scoped evidence bindings: 1

[61] Data Feedback and Evaluations | TaskUs. TaskUs, Inc.; Exact response sha256:b45593e9e4cacaef67c1d49f3d6e072676e31f181537298eda16bac1ef634ac8
https://www.taskus.com/services/ai-data-services/data-feedback-evaluations/
Response SHA-256: b45593e9e4cacaef67c1d49f3d6e072676e31f181537298eda16bac1ef634ac8
Scoped evidence bindings: 2

[62] TELUS Digital AI Data Solutions: High-quality data and human intelligence to test, train and improve AI models. TELUS Digital; Exact response sha256:8e3cde27bf4a0b8b8870af7439d576929aaaedd0dc076e1f7374305aec284243
https://assets.ctfassets.net/3viuren4us1n/7Is3KTyGYuK6wG4BYlfa9C/08840fef56e4eb58b47562b1106dbb62/TELUS_Digital_AI_Data_Solutions_Brochure_2025.pdf
Response SHA-256: 8e3cde27bf4a0b8b8870af7439d576929aaaedd0dc076e1f7374305aec284243
Scoped evidence bindings: 6

[63] Training Verifiers to Solve Math Word Problems. arXiv (author-deposited preprint); 2110.14168v1
https://arxiv.org/pdf/2110.14168v1
Response SHA-256: 9d829ca79818d2d8ddc9c9809348718856789a0f52c143165c8fa5a065948774
Scoped evidence bindings: 6

[64] WebArena: A Realistic Web Environment for Building Autonomous Agents. arXiv (author-deposited preprint); 2307.13854v1
https://arxiv.org/pdf/2307.13854v1
Response SHA-256: 10161cf3b90868aa5564b123103d0fed2fe8babf0a8f3a576d112877a0b7d141
Scoped evidence bindings: 6

[65] CASE STUDY: Accelerating LLM Development & Fine-Tuning - Welocalize. Welocalize / Welo Global; Exact response sha256:88aab62743399d78b8798281e5874427ad31326ec8f2cf1d9252fa7011839928; 2023-12-11
https://www.welocalize.com/insights/case-study-accelerating-llm-development-fine-tuning/
Response SHA-256: 88aab62743399d78b8798281e5874427ad31326ec8f2cf1d9252fa7011839928
Scoped evidence bindings: 3

[66] Information Security Policy | Welo Global. Welocalize / Welo Global; Exact response sha256:1a24478fee68339224094e31d22c6291e942f49a3643ff301eb5e7c242a4df61
https://www.weloglobal.com/information-security-policy/
Response SHA-256: 1a24478fee68339224094e31d22c6291e942f49a3643ff301eb5e7c242a4df61
Scoped evidence bindings: 1

[67] Enterprise AI Training Data & Human-in-the-Loop Evaluation | Welo Data. Welo Data; Exact response sha256:a83856615cb35badea714cfabffd4efbc42185f5a69764e806891ffff09eab80
https://welodata.ai/
Response SHA-256: a83856615cb35badea714cfabffd4efbc42185f5a69764e806891ffff09eab80
Scoped evidence bindings: 3

[68] Align-Anything creator README.md. PKU-Alignment/align-anything; eb9f03cbc9e15d2c6129034d30f77540be386acb
https://huggingface.co/datasets/PKU-Alignment/align-anything/resolve/eb9f03cbc9e15d2c6129034d30f77540be386acb/README.md
Response SHA-256: 35648aab416222f034d4cec17482c9762549256b68e30273edda168e228f93b9
Scoped evidence bindings: 6

[69] Capybara creator README.md. LDJnr/Capybara; c2bc39ac72f24748f60f5fb55b77e08fb0660ba6
https://huggingface.co/datasets/LDJnr/Capybara/resolve/c2bc39ac72f24748f60f5fb55b77e08fb0660ba6/README.md
Response SHA-256: 51459380b8e4f5074fe07d545cd278261443de669aa5c5daffcfabd107152370
Scoped evidence bindings: 6

[70] Chatbot Arena Conversations creator README.md. lmsys/chatbot_arena_conversations; 1b6335d42a1d2c7e34870c905d03ab964f7f2bd8
https://huggingface.co/datasets/lmsys/chatbot_arena_conversations/resolve/1b6335d42a1d2c7e34870c905d03ab964f7f2bd8/README.md
Response SHA-256: 53ef9f134991f1c75a81cd24c7b77a602e78d2bc01c6d9666cac53d4e101c50d
Scoped evidence bindings: 6

[71] Daring-Anteater creator README.md. nvidia/Daring-Anteater; ae79f8ac44cf185fbd3250dbe46057a7f7c4ec40
https://huggingface.co/datasets/nvidia/Daring-Anteater/resolve/ae79f8ac44cf185fbd3250dbe46057a7f7c4ec40/README.md
Response SHA-256: 2fd55bcb2d32a8fa19c3d6ab5f5ea5992c8cbb1cd5f9d511be39a07c2ec69fd3
Scoped evidence bindings: 5

[72] LMSYS-Chat-1M creator README.md. lmsys/lmsys-chat-1m; 200748d9d3cddcc9d782887541057aca0b18c5da
https://huggingface.co/datasets/lmsys/lmsys-chat-1m/resolve/200748d9d3cddcc9d782887541057aca0b18c5da/README.md
Response SHA-256: 02e1793a3f45ac262f56c5b092b3d16e0239ba55d92a76e0e979519bff1c45de
Scoped evidence bindings: 5

[73] Magpie creator README.md. magpie-align/magpie; b734a36818e4ba7ef7f0f582fc55f7e860407d26
https://raw.githubusercontent.com/magpie-align/magpie/b734a36818e4ba7ef7f0f582fc55f7e860407d26/README.md
Response SHA-256: d4f626c9fca26a262cb240b5f201ac7ba8be4d66b86ecea4d90a3a69e9a17903
Scoped evidence bindings: 2

[74] Magpie creator README.md. Magpie-Align/Magpie-Pro-300K-Filtered; 523df96eb7474e97bca6f378b3baa372a4735fcc
https://huggingface.co/datasets/Magpie-Align/Magpie-Pro-300K-Filtered/resolve/523df96eb7474e97bca6f378b3baa372a4735fcc/README.md
Response SHA-256: ee617bdb7e1c45f5980e98aadb6258bb295ceef54aa1aea7384152cbd6bbf6de
Scoped evidence bindings: 4

[75] NuminaMath creator README.md. AI-MO/NuminaMath-CoT; 9d8d210c9f6a36c8f3cd84045668c9b7800ef517
https://huggingface.co/datasets/AI-MO/NuminaMath-CoT/resolve/9d8d210c9f6a36c8f3cd84045668c9b7800ef517/README.md
Response SHA-256: 2e6fead04b0c3a7eb3d219267ca84d81f91d9b90830cfbb1fde73ddd7118a149
Scoped evidence bindings: 2

[76] NuminaMath creator report/numina_dataset.pdf. project-numina/aimo-progress-prize; 712e1abbcbcf870dccf4c6a3e7837e2967bd7d7f
https://raw.githubusercontent.com/project-numina/aimo-progress-prize/712e1abbcbcf870dccf4c6a3e7837e2967bd7d7f/report/numina_dataset.pdf
Response SHA-256: 613b93a38d0fdc24bc2bf4866a9b78a1eaab3855956d273253b461982054c4f6
Scoped evidence bindings: 5

[77] OpenMathInstruct creator README.md. nvidia/OpenMathInstruct-1; 4627efae6bd2ddcebb8acac00d513ffd8e00775c
https://huggingface.co/datasets/nvidia/OpenMathInstruct-1/resolve/4627efae6bd2ddcebb8acac00d513ffd8e00775c/README.md
Response SHA-256: 5839c59deabebeca12291f74706f2cfd67d762948b979177a88700dac5978e75
Scoped evidence bindings: 4

[78] OpenMathInstruct creator LICENSE. nvidia/OpenMathInstruct-1; 4627efae6bd2ddcebb8acac00d513ffd8e00775c
https://huggingface.co/datasets/nvidia/OpenMathInstruct-1/resolve/4627efae6bd2ddcebb8acac00d513ffd8e00775c/LICENSE
Response SHA-256: 117fbe0cc466811cac9488b009a7e5712bb5673c15cbc4f7ab343afcaaccde75
Scoped evidence bindings: 1

[79] OpenOrca creator README.md. Open-Orca/OpenOrca; e9c87b4abb2609913751f9b26553fdb9c061796c
https://huggingface.co/datasets/Open-Orca/OpenOrca/resolve/e9c87b4abb2609913751f9b26553fdb9c061796c/README.md
Response SHA-256: 119592215b487c63f92cdc46c85cdbf5eb1ecf4ce463396c54bec7bc403c96f9
Scoped evidence bindings: 5

[80] Pick-a-Pic creator paper.pdf. NeurIPS 2023 proceedings; NeurIPS2023-73aacd8b3b05b4b503d58310b523553c-Paper-Conference
https://papers.neurips.cc/paper_files/paper/2023/file/73aacd8b3b05b4b503d58310b523553c-Paper-Conference.pdf
Response SHA-256: b83f0f8b9bc43413a8a9d2a3e2d511a7ef13bd847e7d735f961f8caa79562b9a
Scoped evidence bindings: 6

[81] Pick-a-Pic creator README.md. yuvalkirstain/PickScore; f79607ff68609c1e6dfa78cba38afeea4c248df1
https://raw.githubusercontent.com/yuvalkirstain/PickScore/f79607ff68609c1e6dfa78cba38afeea4c248df1/README.md
Response SHA-256: d519113238e7c440ce623ef8732010ecc377e6e39ca7ee2cce519353d4a9effa
Scoped evidence bindings: 1

[82] Pick-a-Pic creator LICENSE. yuvalkirstain/PickScore; f79607ff68609c1e6dfa78cba38afeea4c248df1
https://raw.githubusercontent.com/yuvalkirstain/PickScore/f79607ff68609c1e6dfa78cba38afeea4c248df1/LICENSE
Response SHA-256: 26f64c803b07dfcea82ea31790b87fcf5bfc764d63513cfec6af817b62d6bebc
Scoped evidence bindings: 1

[83] RLAIF-V creator README.md. openbmb/RLAIF-V-Dataset; cdfc8c13778434e38afd538b0641ea942df4af78
https://huggingface.co/datasets/openbmb/RLAIF-V-Dataset/resolve/cdfc8c13778434e38afd538b0641ea942df4af78/README.md
Response SHA-256: 1c19c25807b2b68729210ef2ac6178ffb8ab11413afa5c0edb58100d8bc1c1cc
Scoped evidence bindings: 5

[84] RLHF-V creator README.md. openbmb/RLHF-V-Dataset; 1d8e9804b59e9da64ad7b1e17d505869ab9b2ad3
https://huggingface.co/datasets/openbmb/RLHF-V-Dataset/resolve/1d8e9804b59e9da64ad7b1e17d505869ab9b2ad3/README.md
Response SHA-256: 133d98d77de1b5f57691d10121f0f2fdfc81e5902b88f2d6e5c08614e4a095c6
Scoped evidence bindings: 5

[85] UltraChat creator README.md. stingning/ultrachat; f220fe796ce3ed62fbe1681b45ce6cbc9c6cabe0
https://huggingface.co/datasets/stingning/ultrachat/resolve/f220fe796ce3ed62fbe1681b45ce6cbc9c6cabe0/README.md
Response SHA-256: 1a8af8055f71acc69bac07fb06d0d2de2a1695e8cb590223f5d993c5c20db8e5
Scoped evidence bindings: 5

[86] VideoFeedback creator README.md. TIGER-Lab/VideoFeedback; 4557cb71595098e68790bb35253225c2fe797dcf
https://huggingface.co/datasets/TIGER-Lab/VideoFeedback/resolve/4557cb71595098e68790bb35253225c2fe797dcf/README.md
Response SHA-256: ae697b66418407ba534066f80252f7a9c9553e977755edfa5dfc80be4a9f96ed
Scoped evidence bindings: 5

[87] VideoFeedback creator README.md. TIGER-AI-Lab/VideoScore; f87faf4647e637066bcb74721670cd579e0f4349
https://raw.githubusercontent.com/TIGER-AI-Lab/VideoScore/f87faf4647e637066bcb74721670cd579e0f4349/README.md
Response SHA-256: 0e5765f6e0da01cc47bf8674218e07206da99ed40d39d644510e16ef067e3643
Scoped evidence bindings: 2

[88] VLFeedback creator README.md. MMInstruction/VLFeedback; 137dcea93e7667decc117c54b60f7401c6903310
https://huggingface.co/datasets/MMInstruction/VLFeedback/resolve/137dcea93e7667decc117c54b60f7401c6903310/README.md
Response SHA-256: 457def2f3e4ce7c209c5bfc02d6f78a92aaed7f72d3e5ca07538647b9d9382d6
Scoped evidence bindings: 4

[89] VLFeedback creator README.md. vlf-silkie/VLFeedback; de0bff35dbc6432ccfc214ab6bda61f42d79613f
https://raw.githubusercontent.com/vlf-silkie/VLFeedback/de0bff35dbc6432ccfc214ab6bda61f42d79613f/README.md
Response SHA-256: 1d75774e34d28ebd7ab94a86dcc357a27da565131a6a52cab5f86bdc1b4385ee
Scoped evidence bindings: 1

[90] WildChat creator README.md. allenai/WildChat-1M; 7d6490e462285cf85d91eabea0f9a954fbddcd1f
https://huggingface.co/datasets/allenai/WildChat-1M/resolve/7d6490e462285cf85d91eabea0f9a954fbddcd1f/README.md
Response SHA-256: 0bbf0494bdf60a3d8f644c155cb3c5f8fb21cb247045008f99bfc261e7e15162
Scoped evidence bindings: 4

[91] WildChat creator LICENSE.md. allenai/WildChat-1M; 7d6490e462285cf85d91eabea0f9a954fbddcd1f
https://huggingface.co/datasets/allenai/WildChat-1M/resolve/7d6490e462285cf85d91eabea0f9a954fbddcd1f/LICENSE.md
Response SHA-256: a7c7f6bdb20d261b8726c7594afb5832b36926e0cabfa116c41f58625bbc776c
Scoped evidence bindings: 1

[92] Data Annotation & Collection Services for your AI/ML projects - Alegion. Alegion; Exact response sha256:e932b217d29b716fa0ab1b4b5e81d03769868d9650dbd89b8d2a3ec5a6a29c41
https://www.alegion.com/
Response SHA-256: e932b217d29b716fa0ab1b4b5e81d03769868d9650dbd89b8d2a3ec5a6a29c41
Scoped evidence bindings: 3

[93] Better Annotation Services via our Approach, Process & Workforce - Alegion. Alegion; Exact response sha256:76009ea75c4f25ccd6f8a842936b15653a34bb3c5b2c1e02b003530cc74066ae
https://alegion.com/annotation-services-approach-process/
Response SHA-256: 76009ea75c4f25ccd6f8a842936b15653a34bb3c5b2c1e02b003530cc74066ae
Scoped evidence bindings: 3

[94] AlpaGasus: Training A Better Alpaca with Fewer Data. arXiv (author-deposited preprint); 2307.08701v1
https://arxiv.org/pdf/2307.08701v1
Response SHA-256: 8ce75ae2f13ee4d18d3789f99627137d7c4f2f458c52989a44c079c5dc126157
Scoped evidence bindings: 5

[95] Expert Medical Image Data Labeling - Aya Data. Aya Data; Exact response sha256:f14489b15b890569a7f17740b1ffdff5865a5494b848763ec791fd4f7ba119ef
https://www.ayadata.ai/case-study/precision-medical-labeling-a-cydar-success-story/
Response SHA-256: f14489b15b890569a7f17740b1ffdff5865a5494b848763ec791fd4f7ba119ef
Scoped evidence bindings: 1

[96] Aya Data: Your Trusted Global AI Data & Annotation Company. Aya Data; Exact response sha256:57be9bb32191746c12a72c84bd377f6a62d3d23546721160b20dc661bbbe62e7
https://www.ayadata.ai/
Response SHA-256: 57be9bb32191746c12a72c84bd377f6a62d3d23546721160b20dc661bbbe62e7
Scoped evidence bindings: 1

[97] Trusted RLHF Services and Solution Providers - Aya Data. Aya Data; Exact response sha256:8c7540874f8d4d2af6a3b65cd0d9f5012e1012465b965e122e71e127483a9f69
https://www.ayadata.ai/service/rlhf-services/
Response SHA-256: 8c7540874f8d4d2af6a3b65cd0d9f5012e1012465b965e122e71e127483a9f69
Scoped evidence bindings: 3

[98] BasicAI | AI Data Annotation Services & Platform. BasicAI; Exact response sha256:0c73bde5150b43e4b51a3a70ab8b04768a3c4b00b0e2cb44b328d81f6d055609
https://www.basic.ai/
Response SHA-256: 0c73bde5150b43e4b51a3a70ab8b04768a3c4b00b0e2cb44b328d81f6d055609
Scoped evidence bindings: 2

[99] Large Language Models Data Solution | BasicAI. BasicAI; Exact response sha256:9e7ddee701889f6faf99783c139db01683d1740766231a4088a6ef174ada1843
https://www.basic.ai/data-annotation-service/large-language-models-data-solution
Response SHA-256: 9e7ddee701889f6faf99783c139db01683d1740766231a4088a6ef174ada1843
Scoped evidence bindings: 2

[100] Data Processing and Security | BasicAI. BasicAI; Exact response
sha256:8656dd153cb409b101a68f344b93f3f15c6eb60aa474ea78da9f109ab120a97e
https://www.basic.ai/data-processing-and-security
Response SHA-256: 8656dd153cb409b101a68f344b93f3f15c6eb60aa474ea78da9f109ab120a97e
Scoped evidence bindings: 1

[101] “Everyone wants to do the model work, not the data work”: Data Cascades in High-Stakes AI. ACM CHI2021 paper, creator Google Research public PDF; doi.10.1145.3411764.3445518
https://storage.googleapis.com/gweb-research2023-media/pubtools/pdf/0d556e45afc54afeb2eb6b51a9bc1827b9961ff4.pdf
Response SHA-256: a449fda9f0673f071fe5e4de5770a29935ed39807d34514d431123cbff36ed3e
Scoped evidence bindings: 5

[102] OneForma | Centific. Centific; Exact response
sha256:2e5a9114d043f8b021103346d06cbc3b9c79ceeb9e0483a35b71d0b818edb027
https://www.centific.com/products/oneforma
Response SHA-256: 2e5a9114d043f8b021103346d06cbc3b9c79ceeb9e0483a35b71d0b818edb027
Scoped evidence bindings: 4

[103] RLHF & Preference Optimization | Centific. Centific; Exact response
sha256:1fce95030f645be3e5173a1fdf791275acc9f9faa1aae7408e696bba1edc36a3
https://www.centific.com/solution/rlhf-preference-optimization
Response SHA-256: 1fce95030f645be3e5173a1fdf791275acc9f9faa1aae7408e696bba1edc36a3
Scoped evidence bindings: 2

[104] DataComp: In search of the next generation of multimodal datasets. arXiv (author-deposited preprint); 2304.14108v1
https://arxiv.org/pdf/2304.14108v1
Response SHA-256: b001791ad499b7aed924de73226bfdcb366bf1c407ff1aa912f8cf78f08363ee
Scoped evidence bindings: 5

[105] DataComp-LM: In search of the next generation of training sets for language models. arXiv (author-deposited preprint); 2406.11794v1
https://arxiv.org/pdf/2406.11794v1
Response SHA-256: f19ea7fda1bf30fd9fe877ef6996c2dbc7f84538d813903b66a7bb7ff8f38bc0
Scoped evidence bindings: 9

[106] DICES Dataset: Diversity in Conversational AI Evaluation for Safety. arXiv (author-deposited preprint); 2306.11247v1
https://arxiv.org/pdf/2306.11247v1
Response SHA-256: 13bacc2af1b33bc79d2b5c0e888e17523885a4f9bfea38bb6ce94d57afb0be77
Scoped evidence bindings: 5

[107] Sources of Disagreement in Data for LLM Instruction Tuning. International Committee on Computational Linguistics / ACL Anthology; acl.2025.comedi-1.3
https://aclanthology.org/2025.comedi-1.3.pdf
Response SHA-256: 3dac1d018c58110a74f757800d4631f213e0871a361f1748c77373db297befe4
Scoped evidence bindings: 5

[108] Dolma: an Open Corpus of Three Trillion Tokens for Language Model Pretraining Research. arXiv (author-deposited preprint); 2402.00159v1
https://arxiv.org/pdf/2402.00159v1
Response SHA-256: d4aa2060184ca64aa2ad81596b94c11ac555ff2420f2fc9f743d0e0ada4f3dbb
Scoped evidence bindings: 6

[109] Data Annotation | Encord. Encord; Exact response
sha256:4cd535bd3e778f6a421c5c9afa3f62bf3eda7fc70cbbe8e6747edc8227e0fd90
https://encord.com/data-annotation/
Response SHA-256: 4cd535bd3e778f6a421c5c9afa3f62bf3eda7fc70cbbe8e6747edc8227e0fd90
Scoped evidence bindings: 5

[110] Security at Encord | Encord. Encord; Exact response
sha256:26504e2a514903ce694a321e2afe71869794bbeb10137100ccf029598abf596a
https://encord.com/security/
Response SHA-256: 26504e2a514903ce694a321e2afe71869794bbeb10137100ccf029598abf596a
Scoped evidence bindings: 1

[111] Scaling Instruction-Finetuned Language Models. arXiv (author-deposited preprint); 2210.11416v5
https://arxiv.org/pdf/2210.11416v5
Response SHA-256: 771f758c1b711c2a63ca2439e80ab90751351d721632897a058c0205ba9e2a22
Scoped evidence bindings: 5

[112] Training a Helpful and Harmless Assistant with Reinforcement Learning from Human Feedback. arXiv (author-deposited preprint); 2204.05862v1
https://arxiv.org/pdf/2204.05862v1
Response SHA-256: 26e390d4f76938d2e2591225603637c643cc108e94afb756c65f5d2e0fc9037b
Scoped evidence bindings: 6

[113] Fair work policy | Humans in the Loop. Humans in the Loop; Exact response
sha256:8e79584334a9dbefc2f6354124bb950cb29eddd1d857b8312b9fdc2c3be077a4
https://humansintheloop.org/impact/fair-work-policy/
Response SHA-256: 8e79584334a9dbefc2f6354124bb950cb29eddd1d857b8312b9fdc2c3be077a4
Scoped evidence bindings: 3

[114] Humans in the Loop | Ethical AI with 95% Data Accuracy. Humans in the Loop; Exact response
sha256:1cfadf2999fda4ea003c6f4d363781f0d866eb911eff4f81cc273f14acb72921
https://humansintheloop.org/
Response SHA-256: 1cfadf2999fda4ea003c6f4d363781f0d866eb911eff4f81cc273f14acb72921
Scoped evidence bindings: 1

[115] How it works | Humans in the Loop | HITL. Humans in the Loop; Exact response
sha256:df843974948316b9dd24a55e0c0ca148547ab0839d88a7cc4a5127a3a9899e24
https://humansintheloop.org/how-it-works/
Response SHA-256: df843974948316b9dd24a55e0c0ca148547ab0839d88a7cc4a5127a3a9899e24
Scoped evidence bindings: 2

[116] Human Preference Optimization: RLHF & DPO Services | Innodata. Innodata; Exact response
sha256:11d3c6dedc0a8b0854bdf5b91c9ed9fcc35898336fb0aa93cefa9cadcf523613
https://innodata.com/generative-ai/human-preference-optimization/
Response SHA-256: 11d3c6dedc0a8b0854bdf5b91c9ed9fcc35898336fb0aa93cefa9cadcf523613
Scoped evidence bindings: 5

[117] Work for isahit, an impact sourcing platform. isahit; Exact response
sha256:61eae5f760696f9f468a3267e9b1e0cf3a6ddca4b80c7f0fd5ad34d54650d17a
https://www.isahit.com/work-for-us
Response SHA-256: 61eae5f760696f9f468a3267e9b1e0cf3a6ddca4b80c7f0fd5ad34d54650d17a
Scoped evidence bindings: 2

[118] Isahit - Diverse and Qualified Workforce to Scale Your Projects. isahit; Exact response
sha256:f4a67f380a9014f5d1c0698145fe964d8a96e629d33d20473827506cb6a62077
https://www.isahit.com/workforce
Response SHA-256: f4a67f380a9014f5d1c0698145fe964d8a96e629d33d20473827506cb6a62077
Scoped evidence bindings: 3

[119] SeeChange Retail Theft Detection AI Training Data | Keymakr. Keymakr; Exact response
sha256:9e3a75a85e4ec3af0ca468770e796c1a421bd88e4a6db25c5de4521aee07bdc6
https://keymakr.com/seechange-case.html
Response SHA-256: 9e3a75a85e4ec3af0ca468770e796c1a421bd88e4a6db25c5de4521aee07bdc6
Scoped evidence bindings: 4

[120] Image & Video Annotation, Data Collection | Keymakr. Keymakr; Exact response
sha256:30a3fbd7cf38a0a058899258de08caa12a54cbbca69d67a64a940ce48f13b545
https://keymakr.com/
Response SHA-256: 30a3fbd7cf38a0a058899258de08caa12a54cbbca69d67a64a940ce48f13b545
Scoped evidence bindings: 1

[121] Aviation Polygon Annotation Case Study: Searidge | Label Your Data. Label Your Data; Exact response
sha256:5d3bff6e47e88ae53c0f55e53735dc172ba1965ae7a5f835fcc5dd1c4a489b9c
https://labelyourdata.com/resources/case-study/searidge-polygon-annotation
Response SHA-256: 5d3bff6e47e88ae53c0f55e53735dc172ba1965ae7a5f835fcc5dd1c4a489b9c
Scoped evidence bindings: 2

[122] Data Annotation Company for Complex AI | Label Your Data. Label Your Data; Exact response
sha256:8ab461a563055575956f4bcff9a84f560eeff674aa2d7617660b2a787e067bb1
https://labelyourdata.com/
Response SHA-256: 8ab461a563055575956f4bcff9a84f560eeff674aa2d7617660b2a787e067bb1
Scoped evidence bindings: 2

[123] Label Your Data’s Notice of Certification Under the Data Privacy Framework. Label Your Data; Exact response
sha256:e8351f6a590dc22ad1b03d911426c00befbeb1ae5ee99fb1da3e71cb838474de
https://labelyourdata.com/data-privacy-framework-notice
Response SHA-256: e8351f6a590dc22ad1b03d911426c00befbeb1ae5ee99fb1da3e71cb838474de
Scoped evidence bindings: 2

[124] LIMA: Less Is More for Alignment. arXiv (author-deposited preprint); 2305.11206v1
https://arxiv.org/pdf/2305.11206v1
Response SHA-256: 759ddebaa24a03ee772a70d3a0ecc546f53310f209de0f8f6052a3dddb289144
Scoped evidence bindings: 5

[125] Data Annotation & Labeling Services for AI and ML Projects. Objectways; Exact response
sha256:5fc4ddac5b14ded16d540056b69383a372b23830740648c2f5b197402bc320aa
https://objectways.com/services/data-annotation/
Response SHA-256: 5fc4ddac5b14ded16d540056b69383a372b23830740648c2f5b197402bc320aa
Scoped evidence bindings: 3

[126] AI Data Solutions | AI Data Services | Objectways. Objectways; Exact response
sha256:2379a296f99b5f81626c6530ce151d0d550b834598634c38146773f127809d5b
https://objectways.com/
Response SHA-256: 2379a296f99b5f81626c6530ce151d0d550b834598634c38146773f127809d5b
Scoped evidence bindings: 1

[127] Data Processing and Security | Objectways. Objectways; Exact response sha256:80c3d3e59ddac97adb57ef27fe6ccb311ec2f516f38258c4d868c48fa1dea6d2 https://objectways.com/data-security/
Response SHA-256: 80c3d3e59ddac97adb57ef27fe6ccb311ec2f516f38258c4d868c48fa1dea6d2
Scoped evidence bindings: 1

[128] The Data Provenance Initiative: A Large Scale Audit of Dataset Licensing & Attribution in AI. arXiv (author-deposited preprint); 2310.16787v1 https://arxiv.org/pdf/2310.16787v1
Response SHA-256: 8a68980a962a3638cb8f52a47f8b05c95820ad9555655ffce6c610bd5bd3e4c4
Scoped evidence bindings: 5

[129] Red Teaming Language Models to Reduce Harms: Methods, Scaling Behaviors, and Lessons Learned. arXiv (author-deposited preprint); 2209.07858v1 https://arxiv.org/pdf/2209.07858v1
Response SHA-256: a0b0eb43b178435dcc1eb0dd8faf5aff8d637c4842664eeb8907db3abd3b12f1
Scoped evidence bindings: 6

[130] RLAIF-V: Aligning MLLMs through Open-Source AI Feedback for Super GPT-4V Trustworthiness. arXiv (author-deposited preprint); 2405.17220v1 https://arxiv.org/pdf/2405.17220v1
Response SHA-256: c9caa5fae980118176a7b3f06a55751110da6de5ed79bcb89784930e759f8ba3
Scoped evidence bindings: 6

[131] Self-Refine: Iterative Refinement with Self-Feedback. arXiv (author-deposited preprint); 2303.17651v2 https://arxiv.org/pdf/2303.17651v2
Response SHA-256: 81e44592314d80218ad108d3490cd0b84ba5962fefd5c84819987afd77a57087
Scoped evidence bindings: 5

[132] RLHF Services: Human Feedback Data from Domain Experts | Shaip. Shaip; Exact response sha256:b1f8d9dbfd04dfbb107b0d71430fe171442b6c4909e16fb31798ee2cfdad04db https://www.shaip.com/generative-ai/rlhf-solutions/
Response SHA-256: b1f8d9dbfd04dfbb107b0d71430fe171442b6c4909e16fb31798ee2cfdad04db
Scoped evidence bindings: 6

[133] Learning to summarize from human feedback. arXiv (author-deposited preprint); 2009.01325v3 https://arxiv.org/pdf/2009.01325v3
Response SHA-256: 6bb15be37338385cae1d910bcb46bb2cc99e599918a0625c9c1d0a57f90e5224
Scoped evidence bindings: 6

[134] WizardLM: Empowering Large Pre-Trained Language Models to Follow Complex Instructions. arXiv (author-deposited preprint); 2304.12244v3 https://arxiv.org/pdf/2304.12244v3
Response SHA-256: e5fc7a244d34703bd77c4cc73b2bf1daa8d84160a90af37cacabfa8573bdd538
Scoped evidence bindings: 5

[135] Aya Dataset - README.md. CohereForAI/aya_dataset; f9ea04583f02a8f86404ff6c58bf75fe637df8a2 https://huggingface.co/datasets/CohereForAI/aya_dataset/raw/f9ea04583f02a8f86404ff6c58bf75fe637df8a2/README.md
Response SHA-256: 3ac54f63eec84100c155571945da01c7c18cd8ec97ea94639e2b94a6860e8573
Scoped evidence bindings: 6

[136] Code-Feedback - README.md. m-a-p/Code-Feedback; f411b16a97c910ac9acf8b0d0948e340aa77cc34 https://huggingface.co/datasets/m-a-p/Code-Feedback/raw/f411b16a97c910ac9acf8b0d0948e340aa77cc34/README.md
Response SHA-256: 0c77b55d450a864e9e2c5f69ce266e8e2061f52b6c6f8c2c7710dff034f2b70f
Scoped evidence bindings: 2

[137] Code-Feedback - README.md. OpenCodeInterpreter/OpenCodeInterpreter; 9674d8a521df7f92becd8a7a8e60a8792e71869a
https://raw.githubusercontent.com/OpenCodeInterpreter/OpenCodeInterpreter/9674d8a521df7f92becd8a7a8e60a8792e71869a/README.md
Response SHA-256: 43ec99edb44440d79ca2229d64c3b1a165f039eada68647b6f34f9757da9eba1
Scoped evidence bindings: 2

[138] Code-Feedback - README.md. m-a-p/CodeFeedback-Filtered-Instruction; a08c213a9748c66c15d0225814be80a2e77adf4a
https://huggingface.co/datasets/m-a-p/CodeFeedback-Filtered-Instruction/raw/a08c213a9748c66c15d0225814be80a2e77adf4a/README.md
Response SHA-256: 1842787cdd4c324bacbc7e44239af3561d70e32a82b4ff27c2506ebaf1392de8
Scoped evidence bindings: 2

[139] Databricks Dolly 15k - README.md. databricks/databricks-dolly-15k; bdd27f4d94b9c1f951818a7da7fd7aeea5dbff1a
https://huggingface.co/datasets/databricks/databricks-dolly-15k/raw/bdd27f4d94b9c1f951818a7da7fd7aeea5dbff1a/README.md
Response SHA-256: db06c60090a11b20e79d1933b2f316f781605f07761ff2ae2795d6523e3e960b
Scoped evidence bindings: 6

[140] The Flan Collection - flan/v2/README.md. google-research/FLAN; e9e4ec6e2701182c7a91af176f705310da541277
https://raw.githubusercontent.com/google-research/FLAN/e9e4ec6e2701182c7a91af176f705310da541277/flan/v2/README.md
Response SHA-256: bc1037acf7fea6c913352785fd24080bc223336bf21d6617aaa44dcd95794042
Scoped evidence bindings: 4

[141] The Flan Collection - README.md. google-research/FLAN; e9e4ec6e2701182c7a91af176f705310da541277
https://raw.githubusercontent.com/google-research/FLAN/e9e4ec6e2701182c7a91af176f705310da541277/README.md
Response SHA-256: 38a12f7b33784ebcf385436fa9a592074c3ba8d7eaacacf28e6a682786988273
Scoped evidence bindings: 1

[142] GAIA - README.md. gaia-benchmark/GAIA; 682dd723ee1e1697e00360edccf2366dc8418dd9
https://huggingface.co/datasets/gaia-benchmark/GAIA/blob/682dd723ee1e1697e00360edccf2366dc8418dd9/README.md
Response SHA-256: 8a160e2df36b843c33ec12fdecd731ae8281e0dae553375207707b506a36c11e
Scoped evidence bindings: 6

[143] HarmBench - docs/evaluation_pipeline.md. CenterForAISafety/HarmBench; 8e1604d1171fe8a48d8febecd22f600e462bdcdd
https://raw.githubusercontent.com/CenterForAISafety/HarmBench/8e1604d1171fe8a48d8febecd22f600e462bdcdd/docs/evaluation_pipeline.md
Response SHA-256: d900abc3ef8ca94179ba247da3a40fcafe4c26bfb6ddcbc5af797ef7f73d6cec
Scoped evidence bindings: 5

[144] HarmBench - LICENSE. CenterForAISafety/HarmBench; 8e1604d1171fe8a48d8febecd22f600e462bdcdd
https://raw.githubusercontent.com/CenterForAISafety/HarmBench/8e1604d1171fe8a48d8febecd22f600e462bdcdd/LICENSE
Response SHA-256: fe29c68dd1216e81e98a6069165e1c720757b23bbcaa6c0cb8f9a957bdaaca80
Scoped evidence bindings: 1

[145] HumanEval - LICENSE. openai/human-eval; b9453e8f1865df0a0057a1383767caa400acfbcf
https://raw.githubusercontent.com/openai/human-eval/b9453e8f1865df0a0057a1383767caa400acfbcf/LICENSE
Response SHA-256: bcba3de214851cce46ed5af42d6698044616eeace887c3231bc7a20474ab639e
Scoped evidence bindings: 1

[146] HumanEval - human_eval/evaluation.py. openai/human-eval; b9453e8f1865df0a0057a1383767caa400acfbcf
https://raw.githubusercontent.com/openai/human-eval/b9453e8f1865df0a0057a1383767caa400acfbcf/human_eval/evaluation.py
Response SHA-256: e926d5e9b8f1ec040096cd5952e8cf79f8dc0b7fb80ba6667ce604ffea0397bc
Scoped evidence bindings: 2

[147] HumanEval - README.md. openai/human-eval; b9453e8f1865df0a0057a1383767caa400acfbcf
https://raw.githubusercontent.com/openai/human-eval/b9453e8f1865df0a0057a1383767caa400acfbcf/README.md
Response SHA-256: a6a3741a64527ae20026b7880e37af5de88e8ae4dcfed81eb19620c674b6e272
Scoped evidence bindings: 3

[148] Intel Orca DPO Pairs - intel_extension_for_transformers/neural_chat/examples/finetuning/finetune_neuralchat_v3/README.md. intel/intel-extension-for-transformers; 087056c348f3321a78bffde6fc35c81a6aaf19d9
https://raw.githubusercontent.com/intel/intel-extension-for-transformers/087056c348f3321a78bffde6fc35c81a6aaf19d9/intel_extension_for_transformers/neural_chat/examples/finetuning/finetune_neuralchat_v3/README.md
Response SHA-256: 32fa604aba553e57270297b868074d87babb1dbcebd16b9c3f6d7e26415c678e
Scoped evidence bindings: 4

[149] Intel Orca DPO Pairs - README.md. Intel/orca_dpo_pairs; 624952e3f420ae18d88b31977ee2ea436c833abb
https://huggingface.co/datasets/Intel/orca_dpo_pairs/raw/624952e3f420ae18d88b31977ee2ea436c833abb/README.md
Response SHA-256: 3059107fa3f36cb558142b2b80e6dfdbaa5d8d6d3a26564487420fe402eceb52
Scoped evidence bindings: 2

[150] JailbreakBench - README.md. JailbreakBench/jailbreakbench; 23dbdf6b19650521604456229bc1d9c4156c85c1
https://raw.githubusercontent.com/JailbreakBench/jailbreakbench/23dbdf6b19650521604456229bc1d9c4156c85c1/README.md
Response SHA-256: aa7d1c4154ac4defadb533a7c686a720a808022f24c73763567e028cd5825d8a
Scoped evidence bindings: 6

[151] JailbreakBench - README.md. JailbreakBench/JBB-Behaviors; 886acc352a31533ffbcf4ef22c744658688086fc
https://huggingface.co/datasets/JailbreakBench/JBB-Behaviors/raw/886acc352a31533ffbcf4ef22c744658688086fc/README.md
Response SHA-256: fc84ea5865e60ba15f3776ff43ace47cbbf3470775f389afbb6bdb4d6333618a
Scoped evidence bindings: 1

[152] Math-Shepherd - README.md. peiyi9979/Math-Shepherd; ae6b0c54fca9fa26096f7de175c747e4b262e01a
https://huggingface.co/datasets/peiyi9979/Math-Shepherd/raw/ae6b0c54fca9fa26096f7de175c747e4b262e01a/README.md
Response SHA-256: 5cd51153b70134d08a71362c29c3d7b8788e14700ff7917bfcc7f172039a2065
Scoped evidence bindings: 6

[153] MathVista - README.md. lupantech/MathVista; 5f6b4deca69ecd1b8a1a4f338cee085e50524e4b
https://raw.githubusercontent.com/lupantech/MathVista/5f6b4deca69ecd1b8a1a4f338cee085e50524e4b/README.md
Response SHA-256: f55ef5c9f27869c73cb180d93cb9ea5681eca056b9312970a8620e27329ddc19
Scoped evidence bindings: 5

[154] MathVista - evaluation/calculate_score.py. lupantech/MathVista; 5f6b4deca69ecd1b8a1a4f338cee085e50524e4b
https://raw.githubusercontent.com/lupantech/MathVista/5f6b4deca69ecd1b8a1a4f338cee085e50524e4b/evaluation/calculate_score.py
Response SHA-256: abcd0ff68ec3ed76c3f343be4d01d0f4b88238b660a64e6b998b5f15e3ef56d1
Scoped evidence bindings: 1

[155] MathVista - README.md. AI4Math/MathVista; 2b6ad69445fbb5695c9b165475e8decdbeb97747
https://huggingface.co/datasets/AI4Math/MathVista/raw/2b6ad69445fbb5695c9b165475e8decdbeb97747/README.md
Response SHA-256: b2c1784e13e6a4bf1935930e20a7472a04b40e2d47b7509508266352d0e121ed
Scoped evidence bindings: 1

[156] MBPP - mbpp/README.md. google-research/google-research; 03ac4dca9776084a3a002d4513a55dc7348f680e
https://raw.githubusercontent.com/google-research/google-research/03ac4dca9776084a3a002d4513a55dc7348f680e/mbpp/README.md
Response SHA-256: 02d63a4ffdad806c3c87b5ea2aa91e946f6eec0c2869643b09831650883f41be
Scoped evidence bindings: 5

[157] MBPP - LICENSE. google-research/google-research; 03ac4dca9776084a3a002d4513a55dc7348f680e
https://raw.githubusercontent.com/google-research/google-research/03ac4dca9776084a3a002d4513a55dc7348f680e/LICENSE
Response SHA-256: cfc7749b96f63bd31c3c42b5c471bf756814053e847c10f3eb003417bc523d30
Scoped evidence bindings: 1

[158] MedInstruct - README.md. xz97/MedInstruct; 2934ad53c8250ba4e4130464a6dae3139d1053de
https://huggingface.co/datasets/xz97/MedInstruct/raw/2934ad53c8250ba4e4130464a6dae3139d1053de/README.md
Response SHA-256: d6a1ca0c60549f9c01b92a316681c527d7f94d94e76c10f6d53e46b2b2445f30
Scoped evidence bindings: 5

[159] MedInstruct - README.md. XZhang97666/AlpaCare; b469c41bcd7ddd57dd0bc072ef99d017c5cb0e4b
https://raw.githubusercontent.com/XZhang97666/AlpaCare/b469c41bcd7ddd57dd0bc072ef99d017c5cb0e4b/README.md
Response SHA-256: 39477f146c3bbae7e8a41601f78ef9b73d14e3c029ee76595dceab533cf63c6b
Scoped evidence bindings: 2

[160] MMMU - README.md. MMMU-Benchmark/MMMU; 268471d0d488258990025331c7528359c324aa25
https://raw.githubusercontent.com/MMMU-Benchmark/MMMU/268471d0d488258990025331c7528359c324aa25/README.md
Response SHA-256: a4e89dd389f9b4c82b92e54b5d50a58e55a53c077a5009f7d4b4e53c09bdcc3a
Scoped evidence bindings: 5

[161] MMMU - README.md. MMMU/MMMU; 876ce5cb130f7f7e290ce4d9984357737d4db5cf
https://huggingface.co/datasets/MMMU/MMMU/raw/876ce5cb130f7f7e290ce4d9984357737d4db5cf/README.md
Response SHA-256: 0c9190b5582c5798f5744d37215858de0df51c74de49fc4e64f925c3efd725a8
Scoped evidence bindings: 1

[162] MMMU - mmmu/README.md. MMMU-Benchmark/MMMU; 268471d0d488258990025331c7528359c324aa25
https://raw.githubusercontent.com/MMMU-Benchmark/MMMU/268471d0d488258990025331c7528359c324aa25/mmmu/README.md
Response SHA-256: 8f0cbea394ed36ce16c5cf92c18247df188c1158590ed56697e506684ed4dfa5
Scoped evidence bindings: 1

[163] No Robots - README.md. HuggingFaceH4/no_robots; e6f9a4ac5c37faeb744ba9ecf0473184d7f8105b
https://huggingface.co/datasets/HuggingFaceH4/no_robots/raw/e6f9a4ac5c37faeb744ba9ecf0473184d7f8105b/README.md
Response SHA-256: 22b642520e082ba1a6c4a93047bd5946aeca099763c6f2d11b59d91e61e79186
Scoped evidence bindings: 7

[164] OpenCodeInstruct - README.md. nvidia/OpenCodeInstruct; 8f3ba5bafe4d6e8db46082cf7ae6741bc370604d
https://huggingface.co/datasets/nvidia/OpenCodeInstruct/raw/8f3ba5bafe4d6e8db46082cf7ae6741bc370604d/README.md
Response SHA-256: 2449b70191f455f0e904ff78fabfd7185f20dbe89165ce70ca39a8193241ebd4
Scoped evidence bindings: 6

[165] OpenThoughts - README.md. open-thoughts/OpenThoughts-114k; bd093c3994fd54d2390985b66988ddf282a55eb6
https://huggingface.co/datasets/open-thoughts/OpenThoughts-114k/raw/bd093c3994fd54d2390985b66988ddf282a55eb6/README.md
Response SHA-256: 87dd0984b1ae912cd50507327d1358e378b3de07740600895734c939d0a55946
Scoped evidence bindings: 6

[166] OSWorld - desktop_env/desktop_env.py. xlang-ai/OSWorld; 8903ebeb0efdf74331bd7dc37ed91ccbbff22317
https://raw.githubusercontent.com/xlang-ai/OSWorld/8903ebeb0efdf74331bd7dc37ed91ccbbff22317/desktop_env/desktop_env.py
Response SHA-256: 169f0f196bfa8083e1e3eba329a64c7a2c00284705afc7d47c381f4b4fd1033c
Scoped evidence bindings: 2

[167] OSWorld - README.md. xlang-ai/OSWorld; 8903ebeb0efdf74331bd7dc37ed91ccbbff22317
https://raw.githubusercontent.com/xlang-ai/OSWorld/8903ebeb0efdf74331bd7dc37ed91ccbbff22317/README.md
Response SHA-256: 9a01ccee12ac531c0a86d54e0d4399cdaae7774eef33c5a0d5a019317471e814
Scoped evidence bindings: 4

[168] OSWorld - LICENSE. xlang-ai/OSWorld; 8903ebeb0efdf74331bd7dc37ed91ccbbff22317
https://raw.githubusercontent.com/xlang-ai/OSWorld/8903ebeb0efdf74331bd7dc37ed91ccbbff22317/LICENSE
Response SHA-256: a8d1d88a0f9cce3cdbff73b03a80dc5e5d69e3ba2443946c268815a550c9e0ec
Scoped evidence bindings: 1

[169] Stanford Alpaca - datasheet.md. tatsu-lab/stanford_alpaca; 761dc5bfbdeeffa89b8bff5d038781a4055f796a
https://raw.githubusercontent.com/tatsu-lab/stanford_alpaca/761dc5bfbdeeffa89b8bff5d038781a4055f796a/datasheet.md
Response SHA-256: 341433dc5888bba8f2492350f3ef9b21afe4aeb5f78e9568bb9c4dc2e0cb2394
Scoped evidence bindings: 4

[170] Stanford Alpaca - README.md. tatsu-lab/stanford_alpaca; 761dc5bfbdeeffa89b8bff5d038781a4055f796a
https://raw.githubusercontent.com/tatsu-lab/stanford_alpaca/761dc5bfbdeeffa89b8bff5d038781a4055f796a/README.md
Response SHA-256: bc335b356f6de0a3294cf65d0a389edc4a796764e31e777b7a8d61a7cb7aa551
Scoped evidence bindings: 3

[171] OpenAI Summarize from Feedback - README.md. openai/summarize-from-feedback; 700967448d10004279f138666442bf1497d0e705
https://raw.githubusercontent.com/openai/summarize-from-feedback/700967448d10004279f138666442bf1497d0e705/README.md
Response SHA-256: 5c5c30159193e8d5d104fa0aeda27cbfdee1ba7053ca43807cc7d59b5af917d0
Scoped evidence bindings: 6

[172] Super-NaturalInstructions - README.md. allenai/natural-instructions; 55a365637381ce7f3748fa2eac7aef1a113bbb82
https://raw.githubusercontent.com/allenai/natural-instructions/55a365637381ce7f3748fa2eac7aef1a113bbb82/README.md
Response SHA-256: bd5c0768d317f0184c00afd3233d166672aa63a6fee52fa368f3aa117111ccd7
Scoped evidence bindings: 6

[173] τ-bench - LICENSE. sierra-research/tau-bench; 59a200c6d575d595120f1cb70fea53cef0632f6b
https://raw.githubusercontent.com/sierra-research/tau-bench/59a200c6d575d595120f1cb70fea53cef0632f6b/LICENSE
Response SHA-256: 243d23d45b80122b5ac575586ccef352fdc9c45e6d7d2605449aca8a17478b42
Scoped evidence bindings: 1

[174] τ-bench - tau_bench/envs/base.py. sierra-research/tau-bench; 59a200c6d575d595120f1cb70fea53cef0632f6b
https://raw.githubusercontent.com/sierra-research/tau-bench/59a200c6d575d595120f1cb70fea53cef0632f6b/tau_bench/envs/base.py
Response SHA-256: 1ad0402073f0ac9ca6b527efa0706e2aa8836dd2e5c1d453ed414ecb768c6d21
Scoped evidence bindings: 2

[175] τ-bench - README.md. sierra-research/tau-bench; 59a200c6d575d595120f1cb70fea53cef0632f6b
https://raw.githubusercontent.com/sierra-research/tau-bench/59a200c6d575d595120f1cb70fea53cef0632f6b/README.md
Response SHA-256: 1a4b1b00634fe46fd677dd11dfa25a9bf357b5d7c3d726ff83025e8f104329f9
Scoped evidence bindings: 4

[176] UltraMedical - README.md. TsinghuaC3I/UltraMedical; e53eab0a5d0bf981c8cb9c55744d61dc0b4d56a9
https://raw.githubusercontent.com/TsinghuaC3I/UltraMedical/e53eab0a5d0bf981c8cb9c55744d61dc0b4d56a9/README.md
Response SHA-256: 479f472c4f06fc4ed9aaeffae3c12b28271b3540806033dea0947860d0071fb6
Scoped evidence bindings: 2

[177] UltraMedical - README.md. TsinghuaC3I/UltraMedical; 8930b349985de8345df14d65eb894cf8fce36d9c
https://huggingface.co/datasets/TsinghuaC3I/UltraMedical/raw/8930b349985de8345df14d65eb894cf8fce36d9c/README.md
Response SHA-256: d1f52a4de8b015cae1386ceee29568855fe229128292d3aaa4d362a0d0026228
Scoped evidence bindings: 4

[178] WebGPT Comparisons - README.md. openai/webgpt_comparisons; f30e1bd2f0a51535b493de36d3686cfcfff47abe
https://huggingface.co/datasets/openai/webgpt_comparisons/raw/f30e1bd2f0a51535b493de36d3686cfcfff47abe/README.md
Response SHA-256: 50ea5bd9737deb4ea6275b7ec9b6080233d4cf10fe1a46fe89c473aa2aca1502
Scoped evidence bindings: 6

[179] WebShop - README.md. princeton-nlp/WebShop; 64fa2a5c15c7daa698b9ac93f5bb5437b634c9bd
https://raw.githubusercontent.com/princeton-nlp/WebShop/64fa2a5c15c7daa698b9ac93f5bb5437b634c9bd/README.md
Response SHA-256: 79b7a90a1413a52deb53142b5bbd81ecf40f61743bd4601c2835e91375898ec0
Scoped evidence bindings: 6

[180] WebShop - LICENSE.md. princeton-nlp/WebShop; 64fa2a5c15c7daa698b9ac93f5bb5437b634c9bd
https://raw.githubusercontent.com/princeton-nlp/WebShop/64fa2a5c15c7daa698b9ac93f5bb5437b634c9bd/LICENSE.md
Response SHA-256: 8872dbf8660b00890b5e07ce1ea1f7a44fa7ae4e1857da56caba172b51dab3cb
Scoped evidence bindings: 2

[181] xP3 - README.md. bigscience/xP3; 0ab0411dca6e222e62d210bc681dbcb476d6fe4c
https://huggingface.co/datasets/bigscience/xP3/raw/0ab0411dca6e222e62d210bc681dbcb476d6fe4c/README.md
Response SHA-256: b037cb4eac19ccc852b6570dda2ca0cc5017298407fbcc4aaaebef6382e110ea
Scoped evidence bindings: 6

[182] abundant. Abundant;
response-sha256:6de358eee32fb49a45f1e3ac038016017405529bdd84b54f33dc56f697b177b2
https://www.abundant.ai/
Response SHA-256: 6de358eee32fb49a45f1e3ac038016017405529bdd84b54f33dc56f697b177b2
Scoped evidence bindings: 2

[183] Introducing Foundry - Abundant. Abundant;
response-sha256:7647c497db91cecb3b8df0857d31ec839b77bf178654e4f530250bd215e9f7c2
https://www.abundant.ai/blog/fireworks/
Response SHA-256: 7647c497db91cecb3b8df0857d31ec839b77bf178654e4f530250bd215e9f7c2
Scoped evidence bindings: 3

[184] RL environment creation is becoming continuous QA - Abundant. Abundant;
response-sha256:6d837ab47a1cc210ffca01dca18fcfba7aa84cd48b498ab963408045878492cd
https://www.abundant.ai/blog/env-creation-loop/
Response SHA-256: 6d837ab47a1cc210ffca01dca18fcfba7aa84cd48b498ab963408045878492cd
Scoped evidence bindings: 1

[185] Expert Data for Frontier AI - AfterQuery. AfterQuery;
response-sha256:f778907ba417eb9d8689afe5bc99caf62e3024e3bfe671cfa5815741d8f53a53
https://www.afterquery.com/
Response SHA-256: f778907ba417eb9d8689afe5bc99caf62e3024e3bfe671cfa5815741d8f53a53
Scoped evidence bindings: 3

[186] How AfterQuery Helped NVIDIA Hill-Climb GDPval - AfterQuery. AfterQuery;
response-sha256:4e2a2dbec0e136088751239cb3246c1569b828a3d840ddd051de28042d93b979
https://www.afterquery.com/blog/how-afterquery-helped-nvidia-hill-climb-gdpval
Response SHA-256: 4e2a2dbec0e136088751239cb3246c1569b828a3d840ddd051de28042d93b979
Scoped evidence bindings: 1

[187] AfterQuery. AfterQuery;
response-sha256:c07887aa70f6e967c8e84fd7187568539656ee57b1d8269ad1ce9e6a661bdbaf
https://www.afterquery.com/privacy
Response SHA-256: c07887aa70f6e967c8e84fd7187568539656ee57b1d8269ad1ce9e6a661bdbaf
Scoped evidence bindings: 1

[188] AfterQuery. AfterQuery;
response-sha256:ee69548cbd324b741688409f60bfd38707b9d9552d7e6945eeebe5eabb23063a
https://www.afterquery.com/terms
Response SHA-256: ee69548cbd324b741688409f60bfd38707b9d9552d7e6945eeebe5eabb23063a
Scoped evidence bindings: 1

[189] AgentGym: Evolving Large Language Model-based Agents across Diverse Environments. arXiv (author-deposited preprint); 2406.04151v1
https://arxiv.org/pdf/2406.04151v1
Response SHA-256: 0950510830b43a850bc21763af9a240e83e69ef7efff5258f07d66bc99412b60
Scoped evidence bindings: 5

[190] BenchFlow documentation - BenchFlow. BenchFlow;
response-sha256:824bdc43ad23c0d6f327d7bc75d9392759dcd201f438650a5e6d04de13c863ac
https://www.benchflow.ai/docs/benchflow
Response SHA-256: 824bdc43ad23c0d6f327d7bc75d9392759dcd201f438650a5e6d04de13c863ac
Scoped evidence bindings: 4

[191] BenchFlow - A frontier environment lab for AI agents. BenchFlow;
response-sha256:0b28242ccbca607761c3bbcf5649b82aa240e8a8c3d731085816a6f739a14be0
https://www.benchflow.ai/
Response SHA-256: 0b28242ccbca607761c3bbcf5649b82aa240e8a8c3d731085816a6f739a14be0
Scoped evidence bindings: 2

[192] About - BenchFlow. BenchFlow;
response-sha256:c837863807a9e968ed8c70bf8e9c95a547add56db6073656eafd0190290d1a43
https://www.benchflow.ai/about
Response SHA-256: c837863807a9e968ed8c70bf8e9c95a547add56db6073656eafd0190290d1a43
Scoped evidence bindings: 1

[193] Beyond the Imitation Game: Quantifying and extrapolating the capabilities of language models. arXiv (author-deposited preprint); 2206.04615v1
https://arxiv.org/pdf/2206.04615v1
Response SHA-256: 5e9388ec6aca9dd0dfa58b78ed056a27ceca1641356dde3e1b79de41af3b0569
Scoped evidence bindings: 5

[194] Research | Datacurve. Datacurve;
response-sha256:fbe545268ac1da5d7665c2edfa8d5d2d9e295bc69318f4dc5709356680b499f5
https://datacurve.ai/research
Response SHA-256: fbe545268ac1da5d7665c2edfa8d5d2d9e295bc69318f4dc5709356680b499f5
Scoped evidence bindings: 1

[195] DeepSWE. Datacurve;
response-sha256:4ad6365bf7625f9fe176a5c6c709855ecaa74d3c829dadfb407546d0aefcfae2
https://deepswe.datacurve.ai/
Response SHA-256: 4ad6365bf7625f9fe176a5c6c709855ecaa74d3c829dadfb407546d0aefcfae2
Scoped evidence bindings: 2

[196] Products | Datacurve. Datacurve;
response-sha256:05381109abef3561e6766112e54720d357560b6d8ce81976da1ddf74c99388fb
https://datacurve.ai/products
Response SHA-256: 05381109abef3561e6766112e54720d357560b6d8ce81976da1ddf74c99388fb
Scoped evidence bindings: 3

[197] Human Data Terms of Service · G2i.ai. G2i;
response-sha256:10739415ead464d17cbf43336d82b181a624558ff8a1caaa68fa6a8702d28b29
https://www.g2i.ai/human-data-terms-of-service
Response SHA-256: 10739415ead464d17cbf43336d82b181a624558ff8a1caaa68fa6a8702d28b29
Scoped evidence bindings: 1

[198] Verifying Multi-SWE-bench TypeScript: Quality Analysis of 210 Tasks · G2i.ai. G2i;
response-sha256:d1f7fa03606e6910e4227d4019d29a4fb0ed5df8fc34d9b2e0cc1aa2b8d774f8
https://www.g2i.ai/research/multi-swe-bench-typescript
Response SHA-256: d1f7fa03606e6910e4227d4019d29a4fb0ed5df8fc34d9b2e0cc1aa2b8d774f8
Scoped evidence bindings: 2

[199] G2i.ai. G2i; response-sha256:13e8221994b3d11ed14fa57b8140e4ad7da0c87ecd5e3b6912c8531762463946
https://www.g2i.ai/
Response SHA-256: 13e8221994b3d11ed14fa57b8140e4ad7da0c87ecd5e3b6912c8531762463946
Scoped evidence bindings: 3

[200] GAIA: A Benchmark for General AI Assistants. arXiv (author-deposited preprint); 2311.12983v1
https://arxiv.org/pdf/2311.12983v1
Response SHA-256: 5bf6f968d4f5cd20acdfca6e81e3c9f5277bb66061fad7a02e35442dff812ba0
Scoped evidence bindings: 5

[201] Handshake AI Contractor Agreement | Handshake. Handshake AI;
response-sha256:1f5cbe6b5a3db39b2971605385f43d222d94453c94639415ef58fccbaa39c40b
https://joinhandshake.com/legal/contractor-agreement/
Response SHA-256: 1f5cbe6b5a3db39b2971605385f43d222d94453c94639415ef58fccbaa39c40b
Scoped evidence bindings: 5

[202] Join Handshake | Handshake. Handshake AI;
response-sha256:6ada18100ee3b7bda86680cd48d94f59ee5ebcae59078fb63f7492f350a8496c
https://joinhandshake.com/privacy-policy/
Response SHA-256: 6ada18100ee3b7bda86680cd48d94f59ee5ebcae59078fb63f7492f350a8496c
Scoped evidence bindings: 1

[203] HarmBench: A Standardized Evaluation Framework for Automated Red Teaming and Robust Refusal. arXiv (author-deposited preprint); 2402.04249v1
https://arxiv.org/pdf/2402.04249v1
Response SHA-256: 2f9ac1c3dad14bc3c562827f4029129f6f6aed1e4d2a4c94649c7c3bfa192493
Scoped evidence bindings: 5

[204] Evaluating Large Language Models Trained on Code. arXiv (author-deposited preprint); 2107.03374v1
https://arxiv.org/pdf/2107.03374v1
Response SHA-256: 7085950bcce34fee8ee1821ed1ac0c2672e13708ec866810f997c0bf467d5009
Scoped evidence bindings: 5

[205] JailbreakBench: An Open Robustness Benchmark for Jailbreaking Large Language Models. arXiv (author-deposited preprint); 2404.01318v5
https://arxiv.org/pdf/2404.01318v5
Response SHA-256: 78c2f251cc101bce36e3dd3138fc0c89f7b73c599099f79ec55318165fe4a981
Scoped evidence bindings: 6

[206] MathVista: Evaluating Mathematical Reasoning of Foundation Models in Visual Contexts. arXiv (author-deposited preprint); 2310.02255v1
https://arxiv.org/pdf/2310.02255v1
Response SHA-256: e6b25f084c455b9657f5e43b73cdf38b2473bc2db7cf198ab261e78d70ef99b0
Scoped evidence bindings: 5

[207] Program Synthesis with Large Language Models. arXiv (author-deposited preprint); 2108.07732v1
https://arxiv.org/pdf/2108.07732v1
Response SHA-256: 820a8de4a9fe8aef947a40d5da13db0d660baf3658b4a9cebf6d30ac5ba351ab
Scoped evidence bindings: 5

[208] Frontier evaluations and RL environments for AI Labs. micro1;
response-sha256:acc1e3e5ba5a0377d2d95bd919d6ed145a7592aabc3c7abfad9f295723884716
https://www.micro1.ai/realm
Response SHA-256: acc1e3e5ba5a0377d2d95bd919d6ed145a7592aabc3c7abfad9f295723884716
Scoped evidence bindings: 4

[209] Expert support program. micro1;
response-sha256:b9ccbd24127eabb603c142d8b45972e9a0d540292c97748dfd8d80e1d1734321
https://www.micro1.ai/experts/support-program
Response SHA-256: b9ccbd24127eabb603c142d8b45972e9a0d540292c97748dfd8d80e1d1734321
Scoped evidence bindings: 1

[210] MissionReport. micro1;
response-sha256:826072b47c4e813fd646132fadbf3efab01a3d65a003f887add4eb0b4ad9fdf7
https://www.micro1.ai/benchmark/mission-report
Response SHA-256: 826072b47c4e813fd646132fadbf3efab01a3d65a003f887add4eb0b4ad9fdf7
Scoped evidence bindings: 1

[211] Reinforcement Learning on Web Interfaces Using Workflow-Guided Exploration. arXiv (author-deposited preprint); 1802.08802v1
https://arxiv.org/pdf/1802.08802v1
Response SHA-256: 7a7ce9d5f8f31c7f7c01a35271c5bdfdf2697dfe17e72ff090a9465d55f7f60d
Scoped evidence bindings: 6

[212] MMMU: A Massive Multi-discipline Multimodal Understanding and Reasoning Benchmark for Expert AGI. arXiv (author-deposited preprint); 2311.16502v1
https://arxiv.org/pdf/2311.16502v1
Response SHA-256: 16c07f7ef6d8aae648ec80fdc71ce97787178e5b6b183de757247908d0e56f4a
Scoped evidence bindings: 5

[213] OSWorld: Benchmarking Multimodal Agents for Open-Ended Tasks in Real Computer Environments. arXiv (author-deposited preprint); 2404.07972v1
https://arxiv.org/pdf/2404.07972v1
Response SHA-256: 8499a6ec06757448687f9e1a4e10bd11a5a561cbe2e52ecc2643e17b17b524a7
Scoped evidence bindings: 5

[214] Introducing AttuneBench. Pareto AI;
response-sha256:bf4c78302ee38c9f64824173a350344e2e0aef04a5f18c4afe576c7952b7b57a
https://pareto.ai/blog/introducing-attunebench
Response SHA-256: bf4c78302ee38c9f64824173a350344e2e0aef04a5f18c4afe576c7952b7b57a
Scoped evidence bindings: 1

[215] Join as an Expert | Pareto AI. Pareto AI;
response-sha256:e4ef0d8001b6eeef89659c5d5b2798f112328de4ef8e60c136a7d08cea8bb3ce
https://pareto.ai/experts
Response SHA-256: e4ef0d8001b6eeef89659c5d5b2798f112328de4ef8e60c136a7d08cea8bb3ce
Scoped evidence bindings: 3

[216] Terms of Use | Pareto AI. Pareto AI;
response-sha256:7a3f9405ba1ed093c649eda943865848d90ab78fb4980109941fdc58f4605392
https://pareto.ai/terms-of-use
Response SHA-256: 7a3f9405ba1ed093c649eda943865848d90ab78fb4980109941fdc58f4605392
Scoped evidence bindings: 2

[217] Polymath. Polymath;
response-sha256:b7ab1966cac11e01639ff17b5e1a21c08d84b85735b3e91c056b39633befae43
https://polymathlabs.ai/terms
Response SHA-256: b7ab1966cac11e01639ff17b5e1a21c08d84b85735b3e91c056b39633befae43
Scoped evidence bindings: 3

[218] Polymath. Polymath; response-sha256:6bee82d9f5b2ed107faa27dc2c26fec39fe768835a299eff04ac154da47c85c7
https://polymathlabs.ai/blog/horizon-swe
Response SHA-256: 6bee82d9f5b2ed107faa27dc2c26fec39fe768835a299eff04ac154da47c85c7
Scoped evidence bindings: 3

[219] Polymath. Polymath;
response-sha256:aa3a25143abb9c828694be185b89ca05c2962ab5b5c994f1ab42d2af4b00be99
https://polymathlabs.ai/
Response SHA-256: aa3a25143abb9c828694be185b89ca05c2962ab5b5c994f1ab42d2af4b00be99
Scoped evidence bindings: 1

[220] Prime Intellect - The Open Superintelligence Stack. Prime Intellect;
response-sha256:612ae3d4551e969e0fdba93a0667d04f6760cd119001d4e050944772dbeb1b82
https://www.primeintellect.ai/
Response SHA-256: 612ae3d4551e969e0fdba93a0667d04f6760cd119001d4e050944772dbeb1b82
Scoped evidence bindings: 2

[221] MODEL FACTORY SERVICE TERMS. Prime Intellect;
response-sha256:2ead413b724508b7ae120dad0e4d668725e0a80c549f2d0779682d6357264bbd
https://www.primeintellect.ai/legal/model-factory-terms
Response SHA-256: 2ead413b724508b7ae120dad0e4d668725e0a80c549f2d0779682d6357264bbd
Scoped evidence bindings: 3

[222] Post-Training Nemotron 3.5 Super VL for Long-Horizon Enterprise Work. Prime Intellect;
response-sha256:0d9737a2b383410e8dae1bb26aecb356162be647a391d36a35bac864a1d33d16
https://www.primeintellect.ai/case-study/nvidia
Response SHA-256: 0d9737a2b383410e8dae1bb26aecb356162be647a391d36a35bac864a1d33d16
Scoped evidence bindings: 2

[223] New Frontiers. Proximal;
response-sha256:d4ef948c0b00467303ac3401c43278ec141920143c28c94b5430ed84500eaf51
https://www.proximal.ai/blog/new-frontiers/
Response SHA-256: d4ef948c0b00467303ac3401c43278ec141920143c28c94b5430ed84500eaf51
Scoped evidence bindings: 3

[224] Privacy Policy • Proximal. Proximal;
response-sha256:c9fd77546736df0e2f706456ca21576cfa67080e3300ca499c2d1101659c058f
https://www.proximal.ai/privacy/
Response SHA-256: c9fd77546736df0e2f706456ca21576cfa67080e3300ca499c2d1101659c058f
Scoped evidence bindings: 1

[225] Proximal. Proximal; response-sha256:49e57cbfc68fcf0cbbccff8db0ad867ced03ac12d319d7d87276f80aedee3a4b
https://www.proximal.ai/
Response SHA-256: 49e57cbfc68fcf0cbbccff8db0ad867ced03ac12d319d7d87276f80aedee3a4b
Scoped evidence bindings: 1

[226] Master Development Services Agreement • Proximal. Proximal;
response-sha256:02ab2281c5999269875868559ee040f15a2a4d89698d9dc38e84fe5c86fb347e
https://www.proximal.ai/msa/
Response SHA-256: 02ab2281c5999269875868559ee040f15a2a4d89698d9dc38e84fe5c86fb347e
Scoped evidence bindings: 2

[227] FrontierSWE. Proximal;
response-sha256:95a6ba12041abf59c10f87d7d1d4482ecac94eda371be4d37eabed37f956f8ba
https://www.proximal.ai/blog/frontierswe/
Response SHA-256: 95a6ba12041abf59c10f87d7d1d4482ecac94eda371be4d37eabed37f956f8ba
Scoped evidence bindings: 3

[228] Compare harnesses, not models: Blitzy vs. GPT-5.4 on SWE-Bench Pro - Quesma Blog. Quesma;
response-sha256:5c44e6b157d66c556a16597a9031c22c95f36f060d42b93b880496953b825090
https://quesma.com/blog/verifying-blitzy-swe-bench-pro/
Response SHA-256: 5c44e6b157d66c556a16597a9031c22c95f36f060d42b93b880496953b825090
Scoped evidence bindings: 2

[229] AI Coding Agent Analytics & Cost Intelligence | Quesma. Quesma;
response-sha256:223fa6e24accbeefdf985052bae8ee4d8565b745feba301bf629c36c0c776ffc
https://quesma.com/
Response SHA-256: 223fa6e24accbeefdf985052bae8ee4d8565b745feba301bf629c36c0c776ffc
Scoped evidence bindings: 2

[230] AI Coding Agent Benchmarks & Evaluations | Quesma. Quesma;
response-sha256:b8e2233698ec81e4515a9385bca254456c6be5b90f3430541283f2b06817c362
https://quesma.com/benchmarks/
Response SHA-256: b8e2233698ec81e4515a9385bca254456c6be5b90f3430541283f2b06817c362
Scoped evidence bindings: 2

[231] Privacy Policy - Quesma. Quesma;
response-sha256:140e90707fe65a6d0aba8a1deac55af6022279854866de61f34388b5e1469d88
https://quesma.com/privacy/
Response SHA-256: 140e90707fe65a6d0aba8a1deac55af6022279854866de61f34388b5e1469d88
Scoped evidence bindings: 1

[232] BlenderBench | Refresh. Refresh;
response-sha256:b2900ee1804bf98405890a9b02b5ae81249e3e34758ff71d06732d026148c8c5
https://refresh.dev/blog/blenderbench
Response SHA-256: b2900ee1804bf98405890a9b02b5ae81249e3e34758ff71d06732d026148c8c5
Scoped evidence bindings: 2

[233] Refresh. Refresh; response-sha256:62c2acc88826f95e5f5f94676c465609df474e0a106ae9be33421f29e94705b3
https://refresh.dev/
Response SHA-256: 62c2acc88826f95e5f5f94676c465609df474e0a106ae9be33421f29e94705b3
Scoped evidence bindings: 3

[234] Terms of Service | Refresh. Refresh;
response-sha256:f3b0b025a49e80523abde67024ef9cfa7180e61b23a9e7aeda698f5d212ecfea
https://refresh.dev/terms
Response SHA-256: f3b0b025a49e80523abde67024ef9cfa7180e61b23a9e7aeda698f5d212ecfea
Scoped evidence bindings: 1

[235] ScienceWorld: Is your Agent Smarter than a 5th Grader?. arXiv (author-deposited preprint); 2203.07540v1
https://arxiv.org/pdf/2203.07540v1
Response SHA-256: c7a60e21ad7bf66a25e04e10d76dc54d26c8dfd2cf776d592554e0b01dc24cde
Scoped evidence bindings: 5

[236] τ-bench: A Benchmark for Tool-Agent-User Interaction in Real-World Domains. arXiv (author-deposited preprint); 2406.12045v1
https://arxiv.org/pdf/2406.12045v1
Response SHA-256: 0ce66a1763d698c61bb311c3c874bf593d1e9a5bfff11bb35f6f72b981f6da56
Scoped evidence bindings: 5

[237] ToolLLM: Facilitating Large Language Models to Master 16000+ Real-world APIs. arXiv (author-deposited preprint); 2307.16789v1
https://arxiv.org/pdf/2307.16789v1
Response SHA-256: 6998d4dc2544f53fc8d1a51e0e76b22e60a31e3fad72bc3991b1d6d26cde6398
Scoped evidence bindings: 5

[238] VisualWebArena: Evaluating Multimodal Agents on Realistic Visual Web Tasks. arXiv (author-deposited preprint); 2401.13649v1
https://arxiv.org/pdf/2401.13649v1
Response SHA-256: c713cb700d2d6c56e2f6b1a76bb1bbef05e6298de31bd116bfb4a4002ab228b2
Scoped evidence bindings: 5

[239] WebShop: Towards Scalable Real-World Web Interaction with Grounded Language Agents. arXiv (author-deposited preprint); 2207.01206v1
https://arxiv.org/pdf/2207.01206v1
Response SHA-256: 43ac6342de3471d4d7ab94397f583b6d769f52cf85c9daf2ba15e55a4b96afee
Scoped evidence bindings: 5

[240] AgentInstruct (AgentTuning) - README.md. THUDM/AgentTuning; e33a45d7eab2b63cac4d1956da1e6377fca9fcc7
https://raw.githubusercontent.com/THUDM/AgentTuning/e33a45d7eab2b63cac4d1956da1e6377fca9fcc7/README.md
Response SHA-256: ad3e0550e3f0ee4c426f89c60de6ec8d2a99292f37ec33619b3cc11352899ee2
Scoped evidence bindings: 2

[241] AgentInstruct (AgentTuning) - README.md. THUDM/AgentInstruct; e252cf78ced8a0ea5f62cfd591784cdbbddbac8a
https://huggingface.co/datasets/THUDM/AgentInstruct/raw/e252cf78ced8a0ea5f62cfd591784cdbbddbac8a/README.md
Response SHA-256: 3ab41d3ba06250f6c8f703b7b16fce7330b402bed8570a70ce3ccd4a49f11788
Scoped evidence bindings: 4

[242] APPS - README.md. codeparrot/apps; 21e74ddf8de1a21436da12e3e653065c5213e9d1
https://huggingface.co/datasets/codeparrot/apps/raw/21e74ddf8de1a21436da12e3e653065c5213e9d1/README.md
Response SHA-256: bc954bda94e94e9ce92d80ec16d69607444fcdff240cae89df6ca84ff497e846
Scoped evidence bindings: 4

[243] APPS - LICENSE. hendrycks/apps; 362aedc3c71cd7d9bd2fc96a6c80e11dbc38c7a5
https://raw.githubusercontent.com/hendrycks/apps/362aedc3c71cd7d9bd2fc96a6c80e11dbc38c7a5/LICENSE
Response SHA-256: 8f6401fb0b1fbfcac17aac8d61e4e1b0d2de9aa190d8aa655fedc5fd783b2ace
Scoped evidence bindings: 1

[244] Civil Comments / Jigsaw toxicity annotations - tensorflow_datasets/text/civil_comments.py. tensorflow/datasets; 9ada602af8ce7c8122cdd749c80453f637531acb
https://raw.githubusercontent.com/tensorflow/datasets/9ada602af8ce7c8122cdd749c80453f637531acb/tensorflow_datasets/text/civil_comments.py
Response SHA-256: 64c981f437bb045e0a61b0ac2742e710c13dec26274ae796c8fe40d287f0ed59
Scoped evidence bindings: 5

[245] Civil Comments / Jigsaw toxicity annotations - README.md. google/civil_comments; f2970eb3a55777454c94069077cc8d9b5866312d
https://huggingface.co/datasets/google/civil_comments/raw/f2970eb3a55777454c94069077cc8d9b5866312d/README.md
Response SHA-256: 8ce0fee0cce0d54ddd5daaad7ba7cd5ed31d78b8e8f2d5cd2345b0dd015932c6
Scoped evidence bindings: 2

[246] CodeContests - README.md. google-deepmind/code_contests; fa7a4f8139aab08362503f3344778eb86901709a
https://raw.githubusercontent.com/google-deepmind/code_contests/fa7a4f8139aab08362503f3344778eb86901709a/README.md
Response SHA-256: a58e6866fa383903939ae85131ab1d294af2392c6faf9789054dd38fcb23210d
Scoped evidence bindings: 5

[247] CodeContests - contest_problem.proto. google-deepmind/code_contests; fa7a4f8139aab08362503f3344778eb86901709a
https://raw.githubusercontent.com/google-deepmind/code_contests/fa7a4f8139aab08362503f3344778eb86901709a/contest_problem.proto
Response SHA-256: c44121c7a16b7b8f0356a8941cee42bf50fa3eb76d4729006f1b25b9f5ec9903
Scoped evidence bindings: 2

[248] CoT Collection - README.md. kaist-ai/CoT-Collection; c9d352cdc119df4a4f7526d100e4acb4a72a7a5c
https://huggingface.co/datasets/kaist-ai/CoT-Collection/raw/c9d352cdc119df4a4f7526d100e4acb4a72a7a5c/README.md
Response SHA-256: 4f7d853300ca337bcb1b1da64713956ed3c18ccc50e0b9d51aa5c8f87b1e5304
Scoped evidence bindings: 5

[249] CoT Collection - README.md. kaistAI/CoT-Collection; afce9fe8291b25b04b497d9a767f358d053786b1
https://raw.githubusercontent.com/kaistAI/CoT-Collection/afce9fe8291b25b04b497d9a767f358d053786b1/README.md
Response SHA-256: 2198fabac4b189287c65e0f9742d9aa11ad85d342f9cc9a2fc1bc2e1f8426361
Scoped evidence bindings: 2

[250] HotpotQA - public project page. HotpotQA creators; body-sha256-8786505bfdd092637429ffc0ed7a8e3bf0948b8f7a73c1b665b9a5684d4dc0f9
https://hotpotqa.github.io/blog
Response SHA-256: 8786505bfdd092637429ffc0ed7a8e3bf0948b8f7a73c1b665b9a5684d4dc0f9
Scoped evidence bindings: 2

[251] HotpotQA - README.md. hotpotqa/hotpot; 3635853403a8735609ee997664e1528f4480762a
https://raw.githubusercontent.com/hotpotqa/hotpot/3635853403a8735609ee997664e1528f4480762a/README.md
Response SHA-256: 2a0a1758bb9a2e52b52e6a6528bbf72d46a5a01e0318cdea0473d0660d555998
Scoped evidence bindings: 4

[252] Human Preference Dataset (HPD/HPS) - README.md. tgxs002/HPSv2; 866735ecaae999fa714bd9edfa05aa2672669ee3
https://raw.githubusercontent.com/tgxs002/HPSv2/866735ecaae999fa714bd9edfa05aa2672669ee3/README.md
Response SHA-256: e57b9518ff21030b354b12857d79530808829d5149afaab24ddc8b4af0ec2e19
Scoped evidence bindings: 6

[253] Human Preference Dataset (HPD/HPS) - README.md. ymhao/HPDv2; bb0f2563e451e11c3f376b2ba93615db00e042e1
https://huggingface.co/datasets/ymhao/HPDv2/raw/bb0f2563e451e11c3f376b2ba93615db00e042e1/README.md
Response SHA-256: 09f4bab376cedcb1fa165a81a31afccb5ee2e816402970adba3c9ffe795b238b
Scoped evidence bindings: 1

[254] ImageRewardDB - README.md. THUDM/ImageRewardDB; c493721e19e296eb615420036f2a2eed08412bb4
https://huggingface.co/datasets/THUDM/ImageRewardDB/raw/c493721e19e296eb615420036f2a2eed08412bb4/README.md
Response SHA-256: 2965f9f966d8aa56ebb070d7b92bf83ea4072a9e34011eddf5e3fcdc690c6b44
Scoped evidence bindings: 6

[255] MuSiQue - README.md. stonybrooknlp/musique; 922ac98f19a201998dbdae6d7f2887a5258dbdeb
https://raw.githubusercontent.com/stonybrooknlp/musique/922ac98f19a201998dbdae6d7f2887a5258dbdeb/README.md
Response SHA-256: 7a3fb6a960f3fa122d2a1a81b73b9cf5a39ac983b11735d158490947960b9359
Scoped evidence bindings: 6

[256] MuSiQue - original dataset construction methods. TACL / MuSiQue authors; ACL-2022.tacl-1.31-body-sha256-c0d8b89636bcbca4972b55ab68f014eb20f74c4b9a4fcf126ca68d7f2ec1e753
https://aclanthology.org/2022.tacl-1.31.pdf
Response SHA-256: c0d8b89636bcbca4972b55ab68f014eb20f74c4b9a4fcf126ca68d7f2ec1e753
Scoped evidence bindings: 2

[257] OpenR1-Math - README.md. open-r1/OpenR1-Math-220k; e4e141ec9dea9f8326f4d347be56105859b2bd68
https://huggingface.co/datasets/open-r1/OpenR1-Math-220k/raw/e4e141ec9dea9f8326f4d347be56105859b2bd68/README.md
Response SHA-256: 87a0390ba632618254d50c1614feb6a5a7803a28710118e1705bab18bda5e64e
Scoped evidence bindings: 7

[258] PRISM Alignment Dataset - README.md. HannahRoseKirk/prism-alignment; 18ab5cfb37456f4ec8cbc00212ce54cf7b1239f6
https://huggingface.co/datasets/HannahRoseKirk/prism-alignment/raw/18ab5cfb37456f4ec8cbc00212ce54cf7b1239f6/README.md
Response SHA-256: 5cfc798de48c958f16605743101c9aee4fc52a5c45a591eed2bb09b417349199
Scoped evidence bindings: 7

[259] ProsocialDialog - README.md. allenai/prosocial-dialog; d77d7ad3c624c51030f2f32c83e892b3d620b3d4
https://huggingface.co/datasets/allenai/prosocial-dialog/raw/d77d7ad3c624c51030f2f32c83e892b3d620b3d4/README.md
Response SHA-256: d472c5e3315b789e545eddc0d21adb4347658ccfa830402ade71446c5472b050
Scoped evidence bindings: 6

[260] ProsocialDialog - README.md. skywalker023/prosocial-dialog; 77a5e2fd363af976c06c4408fc83cd4bb302944d
https://raw.githubusercontent.com/skywalker023/prosocial-dialog/77a5e2fd363af976c06c4408fc83cd4bb302944d/README.md
Response SHA-256: dd8cf4902ab5b9e21a147c81521c1a656e60318ea126af60c009edd11f671d21
Scoped evidence bindings: 1

[261] RichHF-18K - README.md. google-research-datasets/richhf-18k; 65290d3ce0e8c9cd407e25e54574cad8589353b6
https://raw.githubusercontent.com/google-research-datasets/richhf-18k/65290d3ce0e8c9cd407e25e54574cad8589353b6/README.md
Response SHA-256: 2e407495e779761d24073fa3d0d6d2f7daf6cdd5f608f2d41142ea5e35944635
Scoped evidence bindings: 6

[262] Social Bias Inference Corpus (SBIC) - README.md. allenai/social_bias_frames; a73510df3ec15f488636be8b66292077719aaa55
https://huggingface.co/datasets/allenai/social_bias_frames/raw/a73510df3ec15f488636be8b66292077719aaa55/README.md
Response SHA-256: d75fdaf98e26e6e96f55819d25f0c5741a995942473412156724bf54239986a0
Scoped evidence bindings: 7

[263] TabMWP - README.md. lupantech/PromptPG; 5a1a52214521590b075f545b76a4f5ce666345e3
https://raw.githubusercontent.com/lupantech/PromptPG/5a1a52214521590b075f545b76a4f5ce666345e3/README.md
Response SHA-256: dd61c99cca31e38ac48341f8daabe5b834187f76c37ca44ca5f57ff35f32a340
Scoped evidence bindings: 5

[264] TabMWP - public project page. PromptPG creators; body-sha256-cc663a9a827d07b4052940a74fa59dc6b1f73f39cc13d184e45800e45733f1b3
https://promptpg.github.io/
Response SHA-256: cc663a9a827d07b4052940a74fa59dc6b1f73f39cc13d184e45800e45733f1b3
Scoped evidence bindings: 1

[265] TACO - README.md. BAAI/TACO; d593ed0a2becbbc952230bb89be09189bf1056dc
https://huggingface.co/datasets/BAAI/TACO/raw/d593ed0a2becbbc952230bb89be09189bf1056dc/README.md
Response SHA-256: 4d087f7330c80401684459d8b59626d88cdfc5cd36a34c9b39a5cc7241be9b34
Scoped evidence bindings: 6

[266] ToxicChat - README.md. lmsys/toxic-chat; 29df8e4dba60e1f4af4b4075c0705c5b313548a8
https://huggingface.co/datasets/lmsys/toxic-chat/raw/29df8e4dba60e1f4af4b4075c0705c5b313548a8/README.md
Response SHA-256: 70c63cac8fff2a4934c85b3d3b52d2e169b8af9fe893dd9de1ea5e4abdb51441
Scoped evidence bindings: 7

[267] WildJailbreak - README.md (public blob visible text). allenai/wildjailbreak; 5ddc12a7894f842b0619b8e1c7ee496b198af009
https://huggingface.co/datasets/allenai/wildjailbreak/blob/5ddc12a7894f842b0619b8e1c7ee496b198af009/README.md
Response SHA-256: f9e6161b38b2acc5bab0307ee7e835715fb51f2eddbeb130039b47201a4bf28b
Scoped evidence bindings: 7

[268] Hire Senior RL & Environments Engineers | A.Team. A.Team;
response-sha256:7f364b55e5b5caba2342075f21dfd1b93aca81602621fe813af58e705d49e15f
https://www.a.team/hire-rl-engineers
Response SHA-256: 7f364b55e5b5caba2342075f21dfd1b93aca81602621fe813af58e705d49e15f
Scoped evidence bindings: 5

[269] Home | AIXI Labs. AIXI Labs;
response-sha256:7233b124d8fce21906f7520e9f2ed26c5fad8b6cb4d4200dcbacc8377cfa663a
https://www.aixi.uk/
Response SHA-256: 7233b124d8fce21906f7520e9f2ed26c5fad8b6cb4d4200dcbacc8377cfa663a
Scoped evidence bindings: 3

[270] Overview | AIXI Labs. AIXI Labs;
response-sha256:626714452bdba98703697793ce11664baabf1e60043733c344736c07a1244eb2
https://www.aixi.uk/research/
Response SHA-256: 626714452bdba98703697793ce11664baabf1e60043733c344736c07a1244eb2
Scoped evidence bindings: 2

[271] Alinia - Deploy your AI without breaking rules. Alinia AI;
response-sha256:4f1c713b5af4ce21fd68d40b86dec3a21c15cd1e7d6d47d95ec33c866fd8ea0e
https://www.alinia.ai/
Response SHA-256: 4f1c713b5af4ce21fd68d40b86dec3a21c15cd1e7d6d47d95ec33c866fd8ea0e
Scoped evidence bindings: 4

[272] Alinia Privacy Policy - How we protect your data. Alinia AI;
response-sha256:84f15c9004a9b11ba9d051443d1c2b917ae59877b34dd8754ba8991f44e7ffd5
https://www.alinia.ai/privacy-policy
Response SHA-256: 84f15c9004a9b11ba9d051443d1c2b917ae59877b34dd8754ba8991f44e7ffd5
Scoped evidence bindings: 1

[273] APTO | AI Training Data for LLM, Multimodal & Physical AI. APTO;
response-sha256:706156597d85151553cfbd490f4943c42d0de3dfd0296d0d8477f5fbc65c6825
https://apto.co.jp/en/
Response SHA-256: 706156597d85151553cfbd490f4943c42d0de3dfd0296d0d8477f5fbc65c6825
Scoped evidence bindings: 4

[274] About Us | APTO. APTO;
response-sha256:e9e373c333e7a87335b2a2944706aea5b4653f0df94d254804ed0db63e492185
https://apto.co.jp/en/company/
Response SHA-256: e9e373c333e7a87335b2a2944706aea5b4653f0df94d254804ed0db63e492185
Scoped evidence bindings: 2

[275] Bespoke Labs: Ship Reliable AI Agents with SOTA Data Curation. Bespoke Labs;
response-sha256:3ba83e61316e7ceba1a5356e9a8c5310c21fdb040d3be4f9880fd985b033d869
https://bespokelabs.ai/
Response SHA-256: 3ba83e61316e7ceba1a5356e9a8c5310c21fdb040d3be4f9880fd985b033d869
Scoped evidence bindings: 4

[276] Terms of Use · Bespoke Labs. Bespoke Labs;
response-sha256:13305d1ae7ae8e20ebde4a81ea2eb92f718321c45dcd86d99d05e93a67eeabb9
https://bespokelabs.ai/legal/terms-of-use
Response SHA-256: 13305d1ae7ae8e20ebde4a81ea2eb92f718321c45dcd86d99d05e93a67eeabb9
Scoped evidence bindings: 1

[277] Constitutional Classifiers: Defending against Universal Jailbreaks across Thousands of Hours of Red Teaming. arXiv (author-deposited versioned preprint); 2501.18837v1
https://arxiv.org/pdf/2501.18837v1
Response SHA-256: 9eeb537ebf4bf47a76284f5c82fe37c6c71f5ca57d93dedc7a9a269beb3c1a7e
Scoped evidence bindings: 7

[278] DeepSeekMath: Pushing the Limits of Mathematical Reasoning in Open Language Models. arXiv (author-deposited versioned preprint); 2402.03300v1
https://arxiv.org/pdf/2402.03300v1
Response SHA-256: 500ce2fae51dd4e06d27423c9b8ec6ca2013eb577e74e5e15fd87510018c6e53
Scoped evidence bindings: 7

[279] DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning. arXiv (author-deposited versioned preprint); 2501.12948v1
https://arxiv.org/pdf/2501.12948v1
Response SHA-256: 52d8ca3ac93e88cef9944e1fd03b0e04aec5954495a8250fb2fadf8fa20a4dad
Scoped evidence bindings: 6

[280] DeepSeek-V3 Technical Report. arXiv (author-deposited versioned preprint); 2412.19437v1
https://arxiv.org/pdf/2412.19437v1
Response SHA-256: a67e18a4ca6e2c81abc030239a3ee53705f656b79efab8ce1d6b5ac25630c2a5
Scoped evidence bindings: 6

[281] Deliberative Alignment: Reasoning Enables Safer Language Models. arXiv (author-deposited versioned preprint); 2412.16339v1
https://arxiv.org/pdf/2412.16339v1
Response SHA-256: ce80073ea89c3d3ec419fb01c692f3a818fa28ae7709da951820497242f606f7
Scoped evidence bindings: 7

[282] Privacy Policy - Elorian. Elorian;
response-sha256:26d478005d324859eabada8d7e7bf4449025cda01940a165497b8513ad650186
https://elorian.ai/privacy
Response SHA-256: 26d478005d324859eabada8d7e7bf4449025cda01940a165497b8513ad650186
Scoped evidence bindings: 1

[283] Introducing Glimpse - Elorian. Elorian;
response-sha256:ae94606ae312346d7845660314ea3b6211272d54c08af5a032b9d87b6637d8a2
https://elorian.ai/blog/introducing-glimpse
Response SHA-256: ae94606ae312346d7845660314ea3b6211272d54c08af5a032b9d87b6637d8a2
Scoped evidence bindings: 3

[284] Elorian - Frontier Intelligence. Elorian;
response-sha256:ad8d6b8092dad35a18a8b229e07d922b2f63773f6db7ea89a21bd926c60315d4
https://elorian.ai/
Response SHA-256: ad8d6b8092dad35a18a8b229e07d922b2f63773f6db7ea89a21bd926c60315d4
Scoped evidence bindings: 1

[285] Continuous Red Teaming v2026. Giskard;
response-sha256:51fa260e12b111987c760305ed161de53481901eb31d9881232f2f3aeb0c57c4
https://www.giskard.ai/products/continuous-red-teaming
Response SHA-256: 51fa260e12b111987c760305ed161de53481901eb31d9881232f2f3aeb0c57c4
Scoped evidence bindings: 1

[286] LLM Evaluation Platform | Giskard AI Agent Testing. Giskard;
response-sha256:bfab0f50fdb6d40fa09a5d4202254064c4a9212551315c6406b7eb260385744f
https://www.giskard.ai/products/llm-evaluation
Response SHA-256: bfab0f50fdb6d40fa09a5d4202254064c4a9212551315c6406b7eb260385744f
Scoped evidence bindings: 3

[287] AI Red Teaming & LLM Security Platform | Giskard. Giskard;
response-sha256:cc248c0b2d7cc09d50d9876fc3b9c6a7bcbad22458722a1c30dcb38d255022d7
https://www.giskard.ai/
Response SHA-256: cc248c0b2d7cc09d50d9876fc3b9c6a7bcbad22458722a1c30dcb38d255022d7
Scoped evidence bindings: 1

[288] GPT-4 Technical Report. arXiv (author-deposited versioned preprint); 2303.08774v1
https://arxiv.org/pdf/2303.08774v1
Response SHA-256: 053056a10114d22e4c47b6b5be25e54c320b5f1beeae7466e8638dac0f5f5f66
Scoped evidence bindings: 6

[289] HackerRank Bench | Long-horizon evaluation for frontier agents. HackerRank Bench;
response-sha256:c50227b4688a9e11850631e587d959923580fd9bf11f5e56af3027faf0848752
https://www.hackerrank.com/bench
Response SHA-256: c50227b4688a9e11850631e587d959923580fd9bf11f5e56af3027faf0848752
Scoped evidence bindings: 5

[290] Learning from Natural Language Feedback. arXiv (author-deposited versioned preprint); 2204.14146v1
https://arxiv.org/pdf/2204.14146v1
Response SHA-256: 7f0316658554df7a538ca89a6e44438c36cf31c9bc76b0246964b42f4824ee0d
Scoped evidence bindings: 9

[291] Laude Institute // Ship Your Research. Laude Institute / Terminal-Bench;
response-sha256:f19fddb1745d05102a744c883d89f2c2f607c9641d23353739358aa432d02763
https://www.laude.org/about
Response SHA-256: f19fddb1745d05102a744c883d89f2c2f607c9641d23353739358aa432d02763
Scoped evidence bindings: 3

[292] Terms of Service // Laude. Laude Institute / Terminal-Bench;
response-sha256:b2071a240fd98c9d1d01cedc8db721e0bf480832f17104af1c3d7ceaf8145cac
https://www.laude.org/terms
Response SHA-256: b2071a240fd98c9d1d01cedc8db721e0bf480832f17104af1c3d7ceaf8145cac
Scoped evidence bindings: 2

[293] Llama 2: Open Foundation and Fine-Tuned Chat Models. arXiv (author-deposited versioned preprint); 2307.09288v1
https://arxiv.org/pdf/2307.09288v1
Response SHA-256: 03c022db7d7ff846e0a1ada4c8be936416f7f7f9c680c64d9494d7b30ebfdd80
Scoped evidence bindings: 6

[294] The Llama 3 Herd of Models. arXiv (author-deposited versioned preprint); 2407.21783v1
https://arxiv.org/pdf/2407.21783v1
Response SHA-256: d7df3d6f537f025037f32ebe13198e3ea5500ea3e0967abdcceb80e31262d386
Scoped evidence bindings: 7

[295] Ooak Data - Applied AI Research Lab. Ooak Data;
response-sha256:ee41c3b90be07d56a848a933911654b7ac8e620a8e3740baac09ba5ba613dd00
https://ooakdata.com/
Response SHA-256: ee41c3b90be07d56a848a933911654b7ac8e620a8e3740baac09ba5ba613dd00
Scoped evidence bindings: 2

[296] How we protect a company's history when training AI - Ooak Data Research. Ooak Data;
response-sha256:9929aa558f4fabc93cc658e13cef12e156b47849a6ba4825699935d64099f41d
https://ooakdata.com/research/how-we-protect-company-history-when-training-ai
Response SHA-256: 9929aa558f4fabc93cc658e13cef12e156b47849a6ba4825699935d64099f41d
Scoped evidence bindings: 1

[297] Privacy Policy - Ooak Data. Ooak Data;
response-sha256:e863478b7f92280d22b108d6d0a94f61fc5a1c9e818554b90a4ec1e1a18a83b7
https://ooakdata.com/privacy
Response SHA-256: e863478b7f92280d22b108d6d0a94f61fc5a1c9e818554b90a4ec1e1a18a83b7
Scoped evidence bindings: 1

[298] Terms of Service - Ooak Data. Ooak Data;
response-sha256:3deaf0844fb2b61171cc2be615b7f9412122c78b452ea93c24a33e8e36389938
https://ooakdata.com/terms
Response SHA-256: 3deaf0844fb2b61171cc2be615b7f9412122c78b452ea93c24a33e8e36389938
Scoped evidence bindings: 1

[299] RAFT: Reward rAnked FineTuning for Generative Foundation Model Alignment. arXiv (author-deposited versioned preprint); 2304.06767v1
https://arxiv.org/pdf/2304.06767v1
Response SHA-256: 2fdceb79aacdbd845e28af3c336ad3e38e399a2009d0ef5a5cb8a06b5fc8d5a1
Scoped evidence bindings: 6

[300] REBEL: Reinforcement Learning via Regressing Relative Rewards. arXiv (author-deposited versioned preprint); 2404.16767v1
https://arxiv.org/pdf/2404.16767v1
Response SHA-256: cddccef39dde4d25ded91ef5d46e99dd27e313792f92bfa97c583213d3ae0d30
Scoped evidence bindings: 6

[301] ReMax: A Simple, Effective, and Efficient Method for Aligning Large Language Models. arXiv (author-deposited versioned preprint); 2310.10505v1
https://arxiv.org/pdf/2310.10505v1
Response SHA-256: 72f3579fc27190ba9206ce9945bdb396ef6058c0c072b15edbc5fd2482eea234
Scoped evidence bindings: 7

[302] Back to Basics: Revisiting REINFORCE Style Optimization for Learning from Human Feedback in LLMs. arXiv (author-deposited versioned preprint); 2402.14740v1
https://arxiv.org/pdf/2402.14740v1
Response SHA-256: ce67f21ed19ca1084e41539e6798ce91ac7fef5483dd029ed2bc719f68e91611
Scoped evidence bindings: 6

[303] RRHF: Rank Responses to Align Language Models with Human Feedback without tears. arXiv (author-deposited versioned preprint); 2304.05302v1
https://arxiv.org/pdf/2304.05302v1
Response SHA-256: 9ae8beae125e30250c9ff596fcb5b72780adbdbf30be296644b78723bf9ea716
Scoped evidence bindings: 6

[304] Statistical Rejection Sampling Improves Preference Optimization. arXiv (author-deposited versioned preprint); 2309.06657v1
https://arxiv.org/pdf/2309.06657v1
Response SHA-256: c0c82da5528a7b18643dad2052f7ba2544ec74f0ba76dbafaece284ae06823eb
Scoped evidence bindings: 7

[305] Data Annotation and Data Labelling, TrainAI - RWS. RWS / TrainAI;
response-sha256:60998fb956a60ffe0ea2971d583749814ff0808cb45868b7014fa7aa4a6d24e5
https://www.rws.com/artificial-intelligence/train-ai-data-services/data-annotation-and-labeling/
Response SHA-256: 60998fb956a60ffe0ea2971d583749814ff0808cb45868b7014fa7aa4a6d24e5
Scoped evidence bindings: 1

[306] About Train AI - FAQ - TrainAI - RWS Community. RWS / TrainAI;
response-sha256:1a9d36be13cba265451910e5a6500d7a98da3ed2fbd238d3ab840cf76d4e26d3
https://community.rws.com/community-hub/resources/rws-services-train-ai-others/trainai/w/faq/6806/about-train-ai
Response SHA-256: 1a9d36be13cba265451910e5a6500d7a98da3ed2fbd238d3ab840cf76d4e26d3
Scoped evidence bindings: 2

[307] RWS expands AI training data services with launch of TrainAI. RWS / TrainAI;
response-sha256:ab05244659fea82e3a0e23150391007494e67e003c771b706e4d18abd9f348e8
https://www.rws.com/about/news/2023/launches-train-ai/
Response SHA-256: ab05244659fea82e3a0e23150391007494e67e003c771b706e4d18abd9f348e8
Scoped evidence bindings: 1

[308] Human-in-the-Loop Data Validation, TrainAI - RWS. RWS / TrainAI;
response-sha256:d3f5260fa752b621be29fb46e8650bb811f3f7e9317dae095e4b4d4eecdd88ef
https://www.rws.com/artificial-intelligence/train-ai-data-services/human-in-the-loop-data-validation/
Response SHA-256: d3f5260fa752b621be29fb46e8650bb811f3f7e9317dae095e4b4d4eecdd88ef
Scoped evidence bindings: 1

[309] SimPO: Simple Preference Optimization with a Reference-Free Reward. arXiv (author-deposited versioned preprint); 2405.14734v1
https://arxiv.org/pdf/2405.14734v1
Response SHA-256: e295b0f6068088631540502988 29c782647c38dbc2d559fd63bb8fe5c21da0d8
Scoped evidence bindings: 6

[310] SLiC-HF: Sequence Likelihood Calibration with Human Feedback. arXiv (author-deposited versioned preprint); 2305.10425v1
https://arxiv.org/pdf/2305.10425v1
Response SHA-256: fb093c095c211c3d75edf75e7c355573e8772ea0a67f2b0c6720d849f7b44af9
Scoped evidence bindings: 6

[311] Self-Play Preference Optimization for Language Model Alignment. arXiv (author-deposited versioned preprint); 2405.00675v1
https://arxiv.org/pdf/2405.00675v1
Response SHA-256: afd1452ae311176bab821a7386048af15390f7233b95f7ca27f8739e739655f7
Scoped evidence bindings: 7

[312] Step-DPO: Step-wise Preference Optimization for Long-chain Reasoning of LLMs. arXiv (author-deposited versioned preprint); 2406.18629v1
https://arxiv.org/pdf/2406.18629v1
Response SHA-256: b3950e36f4fadb2e4acd69477a8fd410f5a36b98422d21da4fbeb9f37e2fd4fb
Scoped evidence bindings: 6

[313] For Researchers | Terac. Terac;
response-sha256:d11fef543f4e98e1b06f21685ac00c76dbb3d651fd99b01f30137b6aaeade1da
https://terac.com/researchers
Response SHA-256: d11fef543f4e98e1b06f21685ac00c76dbb3d651fd99b01f30137b6aaeade1da
Scoped evidence bindings: 3

[314] Data Partnerships | Turn Your Business Workflows into Revenue | Terac. Terac;
response-sha256:ce2f1ef66cef88f8ff0770e20cf5df2a1b2ef7b2bb54b90834baf52204364194
https://terac.com/data-partnerships
Response SHA-256: ce2f1ef66cef88f8ff0770e20cf5df2a1b2ef7b2bb54b90834baf52204364194
Scoped evidence bindings: 2

[315] Trajectory Labs, PBC | AI safety evals, red teaming, RL environments. Trajectory Labs, PBC;
response-sha256:173c525018408f07cd5445c7165cea3fa9b7620db0ac17eff4b176f3b06be6aa
https://www.trajectorylabs.com/
Response SHA-256: 173c525018408f07cd5445c7165cea3fa9b7620db0ac17eff4b176f3b06be6aa
Scoped evidence bindings: 4

[316] Privacy policy | Trajectory Labs, PBC. Trajectory Labs, PBC;
response-sha256:729207139834bab601560e2a6bc1af9bd3a821db7c1ead01aa6b90de61bb7464
https://www.trajectorylabs.com/privacy
Response SHA-256: 729207139834bab601560e2a6bc1af9bd3a821db7c1ead01aa6b90de61bb7464
Scoped evidence bindings: 1

[317] WPO: Enhancing RLHF with Weighted Preference Optimization. arXiv (author-deposited versioned preprint); 2406.11827v1
https://arxiv.org/pdf/2406.11827v1
Response SHA-256: 3ab2d0145eaeca4eb1d8311dcff2eb30af724e39ae3261d57e54f1a817e86755
Scoped evidence bindings: 6

[318] TheAgentCompany: Benchmarking LLM Agents on Consequential Real World Tasks. arXiv (author-deposited versioned preprint); 2412.14161v1; 2024-12-18
https://arxiv.org/pdf/2412.14161v1
Response SHA-256: 3fd93217ad441ee1dbd3f7195d012093751c6feae50b2547c2891643255b4d15
Scoped evidence bindings: 6

[319] benchflow-07. BenchFlow;
response-sha256:a219db1e4b81ca5ad3b4ebda64993d1f3edd47099a1041806f965c055e17ba1c
https://raw.githubusercontent.com/benchflow-ai/benchflow/a61a26f4db4d566de16928565ea58abf3dbaf064/LICENSE
Response SHA-256: a219db1e4b81ca5ad3b4ebda64993d1f3edd47099a1041806f965c055e17ba1c
Scoped evidence bindings: 1

[320] benchflow-06. BenchFlow;
response-sha256:d033efcc20df1dbc9d6249c877141e61fc5117c788ac06f17ebe385fd9076757
https://raw.githubusercontent.com/benchflow-ai/benchflow/a61a26f4db4d566de16928565ea58abf3dbaf064/README.md
Response SHA-256: d033efcc20df1dbc9d6249c877141e61fc5117c788ac06f17ebe385fd9076757
Scoped evidence bindings: 4

[321] BenchGuard: Who Guards the Benchmarks? Automated Auditing of LLM Agent Benchmarks. arXiv (author-deposited versioned preprint); 2604.24955v1; 2026-04-27
https://arxiv.org/pdf/2604.24955v1
Response SHA-256: 72ea4e0ebe96f5d9f9f24693e1bb16876f559aa2ba2801f8506e4a68de5fd424
Scoped evidence bindings: 8

[322] BrowseComp: A Simple Yet Challenging Benchmark for Browsing Agents. arXiv (author-deposited versioned preprint); 2504.12516v1; 2025-04-16
https://arxiv.org/pdf/2504.12516v1
Response SHA-256: 8de2e7a024b43ff7fbab29e0bb6dbdc131ad07206e6c186c2122502d69477760
Scoped evidence bindings: 5

[323] Data Annotation and Labeling Services for Enterprise AI Models (https://www.cogitotech.com/data-labeling/). Cogito Tech; web-extraction-sha256:dc4fca4750d8b97f168c345c2b43e11fe6495c8bea06a5fbf9bc2970bc4ed409
https://www.cogitotech.com/data-labeling/
Response SHA-256: dc4fca4750d8b97f168c345c2b43e11fe6495c8bea06a5fbf9bc2970bc4ed409
Scoped evidence bindings: 4

[324] Register Now - Cogitotech (https://www.cogitotech.com/register-now/). Cogito Tech; web-extraction-sha256:6e073ec6c1db4cbf211e84f2ecb33e86f8e9f3b8c31dea3fe276546711ec5cc8
https://www.cogitotech.com/register-now/
Response SHA-256: 6e073ec6c1db4cbf211e84f2ecb33e86f8e9f3b8c31dea3fe276546711ec5cc8
Scoped evidence bindings: 1

[325] Human Feedback | Dataloop. Dataloop; response-sha256:dd10226bbb83bd5d6647445d234d536c97bad3345cd5a77026c3a87092bfeb87
https://dataloop.ai/platform/human-feedback/
Response SHA-256: dd10226bbb83bd5d6647445d234d536c97bad3345cd5a77026c3a87092bfeb87
Scoped evidence bindings: 4

[326] Privacy Notice | Dataloop. Dataloop; response-sha256:d91d5f6d2f80736bef295d4a6fd42ef8d32c8ee9847dd42e6cecf6712b01b6a0
https://dataloop.ai/privacy-policy/
Response SHA-256: d91d5f6d2f80736bef295d4a6fd42ef8d32c8ee9847dd42e6cecf6712b01b6a0
Scoped evidence bindings: 1

[327] Datasaur Terms of Service. Datasaur; response-sha256:d79109156cde4979808c22445140f44943f43e01f02c044b593a8fec4bbc9dfd
https://datasaur.ai/terms-of-service
Response SHA-256: d79109156cde4979808c22445140f44943f43e01f02c044b593a8fec4bbc9dfd
Scoped evidence bindings: 2

[328] About NLP Labeling | Datasaur. Datasaur; response-sha256:0e1301e572597808e07dd7d6f7ac0e194c9624910e84b8c29958f2745513b357
https://datasaur.ai/studio
Response SHA-256: 0e1301e572597808e07dd7d6f7ac0e194c9624910e84b8c29958f2745513b357
Scoped evidence bindings: 3

[329] Annotate as a Service | Deepen AI. Deepen AI; response-sha256:467899df84c51b09240f0648471bb47510fbaad15dc66fe20798148664a6ed73
https://www.deepen.ai/services/annotate/
Response SHA-256: 467899df84c51b09240f0648471bb47510fbaad15dc66fe20798148664a6ed73
Scoped evidence bindings: 4

[330] Data Protection Addendum | Deepen AI. Deepen AI;
response-sha256:6dd06c690724ab4e1ded9c47341d7926d427bcc40f24eba099f4ba9a2cbdde93
https://www.deepen.ai/data-protection/
Response SHA-256: 6dd06c690724ab4e1ded9c47341d7926d427bcc40f24eba099f4ba9a2cbdde93
Scoped evidence bindings: 1

[331] AI Data Solutions & Model Fine Tuning Company | DDD. Digital Divide Data;
response-sha256:17abdc61a4c10e2a87c81e4acf6dc624ec85bc0fa41906a8862de200475a70d0
https://www.digitaldividedata.com/
Response SHA-256: 17abdc61a4c10e2a87c81e4acf6dc624ec85bc0fa41906a8862de200475a70d0
Scoped evidence bindings: 3

[332] Terms Of Use - Digitaldividedata.com. Digital Divide Data;
response-sha256:6e4ba2d23425fe4fb219c201c887c42c694cae694989bbddd9d850893ac5ac89
https://www.digitaldividedata.com/terms-of-use
Response SHA-256: 6e4ba2d23425fe4fb219c201c887c42c694cae694989bbddd9d850893ac5ac89
Scoped evidence bindings: 1

[333] Data Annotation Solutions For AI & ML Models | DDD. Digital Divide Data;
response-sha256:e916c9379943948fce543d65a30b5a0f5a072199554e932e06646d9b6df17efa
https://www.digitaldividedata.com/data-annotation-solutions
Response SHA-256: e916c9379943948fce543d65a30b5a0f5a072199554e932e06646d9b6df17efa
Scoped evidence bindings: 2

[334] Human expertise for AI training.. TrustScale / e2f;
response-sha256:4d4794da57f6c656a2b1a6c58156763e7d4a3d26c6135e04690d8e24246c3a19
https://www.trustscale.ai/assets/index-CUMNnpew.js
Response SHA-256: 4d4794da57f6c656a2b1a6c58156763e7d4a3d26c6135e04690d8e24246c3a19
Scoped evidence bindings: 7

[335] GDPval: Evaluating AI Model Performance on Real-World Economically Valuable Tasks. arXiv (author-deposited versioned preprint); 2510.04374v1; 2025-10-05
https://arxiv.org/pdf/2510.04374v1
Response SHA-256: a04cca8451c486d871f8d2c6c57b8bc03b45daf1b5b0269146929bc8bf688dec
Scoped evidence bindings: 5

[336] GPQA: A Graduate-Level Google-Proof Q&A Benchmark. arXiv (author-deposited versioned preprint); 2311.12022v1; 2023-11-20
https://arxiv.org/pdf/2311.12022v1
Response SHA-256: 58a85a21b653a01d5794f84952936f58e6a5218d781588f44ae183bb749bf023
Scoped evidence bindings: 5

[337] Terms of Use | Deploy. Deploy / Hive;
response-sha256:3fbfefc60b83567fb85eeea584e31e71775e34952bb9ca3a2603895d13919847
https://deploy.com/terms-of-use
Response SHA-256: 3fbfefc60b83567fb85eeea584e31e71775e34952bb9ca3a2603895d13919847
Scoped evidence bindings: 4

[338] AI to Understand, Search, and Generate Content | Hive. Deploy / Hive;
response-sha256:293b7cc6b2de23fcc64ea6e12d30d92c0ee453e90c8a78bc19eea591db9d2a17
https://thehive.ai/
Response SHA-256: 293b7cc6b2de23fcc64ea6e12d30d92c0ee453e90c8a78bc19eea591db9d2a17
Scoped evidence bindings: 1

[339] Humanity's Last Exam. arXiv (author-deposited versioned preprint); 2501.14249v1; 2025-01-24
https://arxiv.org/pdf/2501.14249v1
Response SHA-256: 7a91dd3ee597fd64f44053675bc87dfa308b8da538e5e8e48ea115db9db22d8f
Scoped evidence bindings: 5

[340] Instruction-Following Evaluation for Large Language Models. arXiv (author-deposited versioned preprint); 2311.07911v1; 2023-11-14
https://arxiv.org/pdf/2311.07911v1
Response SHA-256: 5d7cedfd762af6d9ad13d8768de64fa65895b8ebc3f5e454454c5ffbd48124f2
Scoped evidence bindings: 5

[341] AI Data Services | iSoftStone. iSoftStone;
response-sha256:edcc4b7486af9db839f150a11e3aa67c62d9aac51515cfbf8ab02eadfa67ae4a
https://www.isoftstoneinc.com/ai-data-services/
Response SHA-256: edcc4b7486af9db839f150a11e3aa67c62d9aac51515cfbf8ab02eadfa67ae4a
Scoped evidence bindings: 4

[342] Privacy Policy | iSoftStone. iSoftStone;
response-sha256:99878b0150530e1a4a31feee69f2fede0b47586d5e7ee99e2f3c9485ebc41dbf
https://www.isoftstoneinc.com/privacy-policy/
Response SHA-256: 99878b0150530e1a4a31feee69f2fede0b47586d5e7ee99e2f3c9485ebc41dbf
Scoped evidence bindings: 1

[343] Quality-First AI Evaluation and Post-Training | Kili. Kili Technology;
response-sha256:e4f0a3493d09bbf71c1ae0b2494d1b0284a4dff7c847e7747b902322db99e313
https://kili-technology.com/product/quality
Response SHA-256: e4f0a3493d09bbf71c1ae0b2494d1b0284a4dff7c847e7747b902322db99e313
Scoped evidence bindings: 1

[344] AI Evaluation, Post-Training and Data Annotation Platform | Kili. Kili Technology;
response-sha256:74abc99e07361cc7ba3ad07be9f3b72c5ff00de7073f9e5d967403aab4a7420d
https://kili-technology.com/
Response SHA-256: 74abc99e07361cc7ba3ad07be9f3b72c5ff00de7073f9e5d967403aab4a7420d
Scoped evidence bindings: 3

[345] Terms and Conditions. Kili Technology;
response-sha256:89e7c218c76aeb3b5c6425173c6ff608c5f37f8df5a5d9c5d7114f124ad562ed
https://kili-technology.com/terms-and-conditions
Response SHA-256: 89e7c218c76aeb3b5c6425173c6ff608c5f37f8df5a5d9c5d7114f124ad562ed
Scoped evidence bindings: 1

[346] Privacy Policy. Kili Technology;
response-sha256:924b3f336da026b5c0d2deb5c2c8a2867700de55ff8f9689533d98f96c9ae804
https://kili-technology.com/legal-notice
Response SHA-256: 924b3f336da026b5c0d2deb5c2c8a2867700de55ff8f9689533d98f96c9ae804
Scoped evidence bindings: 1

[347] Häufig gestellte Fragen zum Outsourcing | Mindy Support (https://mindy-support.com/about-us/faq/). Mindy Support;
web-extraction-sha256:7669e5eba0efaa93d1296034977ed1d65f2ef3f328e23455f53c50447114c583
https://mindy-support.com/about-us/faq/
Response SHA-256: 7669e5eba0efaa93d1296034977ed1d65f2ef3f328e23455f53c50447114c583
Scoped evidence bindings: 5

[348] MLE-bench: Evaluating Machine Learning Agents on Machine Learning Engineering. arXiv (author-deposited versioned preprint); 2410.07095v1; 2024-10-09
https://arxiv.org/pdf/2410.07095v1
Response SHA-256: f5f904e91f28c460397a0d7acbeb40aba19bae561093effd71c7af32cf8b7539
Scoped evidence bindings: 6

[349] MMMU-Pro: A More Robust Multi-discipline Multimodal Understanding Benchmark. arXiv (author-deposited versioned preprint); 2409.02813v1; 2024-09-04
https://arxiv.org/pdf/2409.02813v1
Response SHA-256: a7175191c00a58f7ab5f5c7db047c8e50d7707fb1cf6fe52cb77cbfe9de4acbd
Scoped evidence bindings: 5

[350] PaperBench: Evaluating AI's Ability to Replicate AI Research. arXiv (author-deposited versioned preprint); 2504.01848v1; 2025-04-02
https://arxiv.org/pdf/2504.01848v1
Response SHA-256: 4f2f4a48dd27a1790ec322df759f5e319ece547227fc1b7d307fb36c10d31e79
Scoped evidence bindings: 6

[351] RE-Bench: Evaluating frontier AI R&D capabilities of language model agents against human experts. arXiv (author-deposited versioned preprint); 2411.15114v1; 2024-11-22
https://arxiv.org/pdf/2411.15114v1
Response SHA-256: be1b2037a29da00ec2b6964258e50060a3ff4504703cf4835554cba8f47ed05e
Scoped evidence bindings: 8

[352] RewardBench 2: Advancing Reward Model Evaluation. arXiv (author-deposited versioned preprint); 2506.01937v1; 2025-06-02
https://arxiv.org/pdf/2506.01937v1
Response SHA-256: f6d5781356315a7c33eff8b4810d876961861d7b3494037d31acd36496b43830
Scoped evidence bindings: 7

[353] ScienceAgentBench: Toward Rigorous Assessment of Language Agents for Data-Driven Scientific Discovery. arXiv (author-deposited versioned preprint); 2410.05080v1; 2024-10-07
https://arxiv.org/pdf/2410.05080v1
Response SHA-256: 5b4b8be139d6f88d53acaf89b18938d0c1749fc20f5d50db6989324772d993bc
Scoped evidence bindings: 8

[354] SkillsBench: Benchmarking How Well Agent Skills Work Across Diverse Tasks. arXiv (author-deposited versioned preprint); 2602.12670v1; 2026-02-13
https://arxiv.org/pdf/2602.12670v1
Response SHA-256: fa853b3a44282a28bd816b46572e8fbab945834f01fb5f055ec8847ba1c31dae
Scoped evidence bindings: 6

[355] AI Leading Data Provider | AI Data Solutions | DataOcean AI. Dataocean AI / Speechocean;
response-sha256:61aca77dd331982f847f39c81620ce28ca47d0d69586be82d774ea908469024f
https://dataoceanai.com/
Response SHA-256: 61aca77dd331982f847f39c81620ce28ca47d0d69586be82d774ea908469024f
Scoped evidence bindings: 3

[356] 登录. Dataocean AI / Speechocean;
response-sha256:23205ecaaa52cc56ef62cd411ff69e25c830e41c6db6cba4ce487c78d1141f79
https://people.speechocean.com/login
Response SHA-256: 23205ecaaa52cc56ef62cd411ff69e25c830e41c6db6cba4ce487c78d1141f79
Scoped evidence bindings: 1

[357] Our Privacy Policy | AI Data Solutions | DataOcean AI. Dataocean AI / Speechocean;
response-sha256:25a0666bf1aa7b71f01536280422f109b5d98a624a50c89c3219b9a1debf7f27
https://dataoceanai.com/privacy-policy/
Response SHA-256: 25a0666bf1aa7b71f01536280422f109b5d98a624a50c89c3219b9a1debf7f27
Scoped evidence bindings: 1

[358] SWE-Lancer: Can Frontier LLMs Earn $1 Million from Real-World Freelance Software Engineering?. arXiv (author-deposited versioned preprint); 2502.12115v1; 2025-02-17
https://arxiv.org/pdf/2502.12115v1
Response SHA-256: 428f0f36520a41aad156800c2d0520074dd4ca1d57ea9a4abd8d90807affbd1b
Scoped evidence bindings: 6

[359] SWE-bench Multimodal: Do AI Systems Generalize to Visual Software Domains?. arXiv (author-deposited versioned preprint); 2410.03859v1; 2024-10-04
https://arxiv.org/pdf/2410.03859v1
Response SHA-256: 4fa09c3734547e8ba4a5288e7e8d9273d1136c70295e4f91ef3592df0ead2a71
Scoped evidence bindings: 6

[360] SWE-Bench Pro: Can AI Agents Solve Long-Horizon Software Engineering Tasks?. arXiv (author-deposited versioned preprint); 2509.16941v1; 2025-09-21
https://arxiv.org/pdf/2509.16941v1
Response SHA-256: fa282d00fd32225fced1328838b65bcefb8947b0f5a54b7601f8f2ea27359ebb
Scoped evidence bindings: 6

[361] τ^2-Bench: Evaluating Conversational Agents in a Dual-Control Environment. arXiv (author-deposited versioned preprint); 2506.07982v1; 2025-06-09
https://arxiv.org/pdf/2506.07982v1
Response SHA-256: 0817e3fd33915326180d548caa900dcc5cba42ded27688105d8ce2f7e73aad84
Scoped evidence bindings: 6

[362] Terminal-Bench: Benchmarking Agents on Hard, Realistic Tasks in Command Line Interfaces. arXiv (author-deposited versioned preprint); 2601.11868v1; 2026-01-17
https://arxiv.org/pdf/2601.11868v1
Response SHA-256: 4430e04a507b2442bb7b24a88899b750948fa0a6b3bbc33a8d541d6d4debcc1e
Scoped evidence bindings: 6

[363] V7 Darwin | AI Data Labeling & ML Training Data Platform. V7 / Darwin;
response-sha256:2f20b45d011729f66df22aa79f735c409ab27ce324b4897a2e671a7af6ab8ac1
https://www.v7darwin.com/
Response SHA-256: 2f20b45d011729f66df22aa79f735c409ab27ce324b4897a2e671a7af6ab8ac1
Scoped evidence bindings: 3

[364] Master Service Agreement (MSA) - Darwin - V7. V7 / Darwin;
response-sha256:434dd5f26d86be318c40ded57485b0b1a3f6298e0be9153dfdf82c2d8b07e84c
https://www.v7labs.com/terms/msa-darwin
Response SHA-256: 434dd5f26d86be318c40ded57485b0b1a3f6298e0be9153dfdf82c2d8b07e84c
Scoped evidence bindings: 2

[365] Video-MME: The First-Ever Comprehensive Evaluation Benchmark of Multi-modal LLMs in Video Analysis. arXiv (author-deposited versioned preprint); 2405.21075v1; 2024-05-31
https://arxiv.org/pdf/2405.21075v1
Response SHA-256: 8f86ad54e3017f81b0738ab0a4fa373f63334f2be4e5f0983d401b824f1821aa
Scoped evidence bindings: 5

[366] BenchMAX: A Comprehensive Multilingual Evaluation Suite for Large Language Models. arXiv (author-deposited versioned preprint); 2502.07346v1; 2025-02-11
https://arxiv.org/pdf/2502.07346v1
Response SHA-256: f8e1b140b3eb7d1bf2bd2db8bef76a52179637c11c8ecc533278d7f398eb6f4c
Scoped evidence bindings: 5

[367] The Common Pile v0.1: An 8TB Dataset of Public Domain and Openly Licensed Text. arXiv (author-deposited versioned preprint); 2506.05209v1; 2025-06-05
https://arxiv.org/pdf/2506.05209v1
Response SHA-256: 24b26eb7b9bba731af9746974c452a23f870814d31b7d55cd681b771dfe02fdc
Scoped evidence bindings: 5

[368] Consent in Crisis: The Rapid Decline of the AI Data Commons. arXiv (author-deposited versioned preprint); 2407.14933v1; 2024-07-20
https://arxiv.org/pdf/2407.14933v1
Response SHA-256: 890f0591edfaf9938f9e72046b1d7fe2c476c94a9911712921bde59b5dd9cf38
Scoped evidence bindings: 6

[369] How do data owners say no? A case study of data consent mechanisms in web-scraped vision-language AI training datasets. arXiv (author-deposited versioned preprint); 2511.08637v1; 2025-11-10
https://arxiv.org/pdf/2511.08637v1
Response SHA-256: 4351599edbaa15c5e242a577431760799f6784af2dc983cd5c3f3347b3116ea1
Scoped evidence bindings: 5

[370] The Data-Production Dispositif. arXiv (author-deposited versioned preprint); 2205.11963v1; 2022-05-24
https://arxiv.org/pdf/2205.11963v1
Response SHA-256: 926a27314518a1350d7463d30cc996c6d42f4567b04f2228a0433fca3cfa2746
Scoped evidence bindings: 5

[371] Data Statements for Natural Language Processing: Toward Mitigating System Bias and Enabling Better Science. Association for Computational Linguistics / ACL Anthology; ACL-Q18-1041-published-2018; anthology metadata commit ba3130005282c6474307cceec936373fe55d15ff
https://aclanthology.org/Q18-1041.pdf
Response SHA-256: da123cf0cc7dfb32479066ce01e0d107c312cff0c2818f9abfccb101c6005ff2
Scoped evidence bindings: 5

[372] Extracting Training Data from Large Language Models. arXiv (author-deposited versioned preprint); 2012.07805v2; 2021-06-15
https://arxiv.org/pdf/2012.07805v2
Response SHA-256: a3d1496575fd199e5b8535a78e69b528731c9895c1c0a3304848ef005593b473
Scoped evidence bindings: 5

[373] Fair human-centric image dataset for ethical AI benchmarking. Nature article; institutional PDF copy; institutional-copy-sha256-66ac69cbb2d33c170f14ff64072c07c51ab5d3ff66c2357a69dbb59d64fcaf78
https://www.cs.utexas.edu/~pstone/Papers/bib2html-links/peter_nature_2025.pdf
Response SHA-256: 66ac69cbb2d33c170f14ff64072c07c51ab5d3ff66c2357a69dbb59d64fcaf78
Scoped evidence bindings: 5

[374] Improving Task Instructions for Data Annotators: How Clear Rules and Higher Pay Increase Performance in Data Annotation in the AI Economy. arXiv (author-deposited versioned preprint); 2312.14565v2; 2024-08-16
https://arxiv.org/pdf/2312.14565v2
Response SHA-256: 1cfa3f27249f3c0abc80d1f27ef481ee54283545936c9dd074021ec5bd5dd042
Scoped evidence bindings: 5

[375] MENLO: From Preferences to Proficiency -- Evaluating and Modeling Native-like Quality Across 47 Languages. arXiv (author-deposited versioned preprint); 2509.26601v1; 2025-09-30
https://arxiv.org/pdf/2509.26601v1
Response SHA-256: 91cbda09646ae708e519c49891979a23e88cbcaec880c25e0c2380dce8a944ba
Scoped evidence bindings: 5

[376] M-IFEval: Multilingual Instruction-Following Evaluation. Association for Computational Linguistics / ACL Anthology; ACL-2025.findings-naacl.344-published; anthology metadata commit ba3130005282c6474307cceec936373fe55d15ff
https://aclanthology.org/2025.findings-naacl.344.pdf
Response SHA-256: 1b3f332d3d79359eec16db2b55c8cfd6bb92cdcff973f5df2d87fe17e27fde94
Scoped evidence bindings: 5

[377] Model Cards for Model Reporting. arXiv (author-deposited versioned preprint); 1810.03993v2; 2019-01-14
https://arxiv.org/pdf/1810.03993v2
Response SHA-256: a4049cdc78c3d635bdfb5165e495b0672d85690d66ccd6f149079d6e11e64aa1
Scoped evidence bindings: 5

[378] Monitoring Reasoning Models for Misbehavior and the Risks of Promoting Obfuscation. arXiv (author-deposited versioned preprint); 2503.11926v1; 2025-03-14
https://arxiv.org/pdf/2503.11926v1
Response SHA-256: 2547162c549d70e02beca2687903a8fce75fd950269a3ee479d5b8ebbb53ff38
Scoped evidence bindings: 5

[379] M-RewardBench: Evaluating Reward Models in Multilingual Settings. Association for Computational Linguistics / ACL Anthology; ACL-2025.acl-long.3-published; anthology metadata commit ba3130005282c6474307cceec936373fe55d15ff
https://aclanthology.org/2025.acl-long.3.pdf
Response SHA-256: 2da13cb132c7933424941b495ac9b7a94e9659d04030a79eb78310266be7418e
Scoped evidence bindings: 5

[380] MultiChallenge: A Realistic Multi-Turn Conversation Evaluation Benchmark Challenging to Frontier LLMs. arXiv (author-deposited versioned preprint); 2501.17399v1; 2025-01-29
https://arxiv.org/pdf/2501.17399v1
Response SHA-256: 5046c8bbe1bf77ab61092346d7fdfe05a25875a61b3c6e5a998313909dfd0074
Scoped evidence bindings: 5

[381] How Reliable is Multilingual LLM-as-a-Judge?. Association for Computational Linguistics / ACL Anthology; ACL-2025.findings-emnlp.587-published; anthology metadata commit ba3130005282c6474307cceec936373fe55d15ff
https://aclanthology.org/2025.findings-emnlp.587.pdf
Response SHA-256: 3c7c41868590e6b1d97123127e362036ae031bd315b0734e665202ee43cad137
Scoped evidence bindings: 5

[382] ShieldAgent: Shielding Agents via Verifiable Safety Policy Reasoning. arXiv (author-deposited versioned preprint); 2503.22738v1; 2025-03-26
https://arxiv.org/pdf/2503.22738v1
Response SHA-256: 2bfa433e30445ff10a687413891d5e132498e5e3715834574b023d614c6a6bb8
Scoped evidence bindings: 5

[383] Is It Thinking or Cheating? Detecting Implicit Reward Hacking by Measuring Reasoning Effort. arXiv (author-deposited versioned preprint); 2510.01367v1; 2025-10-01
https://arxiv.org/pdf/2510.01367v1
Response SHA-256: 3d87b2a6c49cce0adefcccdbfa54f8f101d1c87c69c131768086a8971c7eb1a6
Scoped evidence bindings: 5

[384] VerifiAgent: a Unified Verification Agent in Language Model Reasoning. arXiv (author-deposited versioned preprint); 2504.00406v1; 2025-04-01
https://arxiv.org/pdf/2504.00406v1
Response SHA-256: 2ffccf4b668733a49bf375e7836419f3447fda6a8c28d19110b6b024f1aa64f5
Scoped evidence bindings: 5

[385] World of Bits: An Open-Domain Platform for Web-Based Agents. Proceedings of Machine Learning Research; PMLR-v70-shi17a-2017; 2017-07-17
https://proceedings.mlr.press/v70/shi17a/shi17a.pdf
Response SHA-256: 087008efb9d056df5fd9fbc724413d6a3f20cb14c7f1597d00bacac53d8342d6
Scoped evidence bindings: 5

[386] CrowdWorkSheets: Accounting for Individual and Collective Identities Underlying Crowdsourced Dataset Annotation. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2206.08931v1; 2022-06-09
https://arxiv.org/pdf/2206.08931v1
Response SHA-256: 5249ebf13529cc89a0e72c4c19833355d1b4811104a0102c807d2ce2e13bef89
Scoped evidence bindings: 5

[387] DAPO: An Open-Source LLM Reinforcement Learning System at Scale. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2503.14476v2; 2025-05-20
https://arxiv.org/pdf/2503.14476v2
Response SHA-256: f01e4fd347530cadd68e5c36b1998532a6d1adb272c817e73b927453c26e9d79
Scoped evidence bindings: 5

[388] Data Cards: Purposeful and Transparent Dataset Documentation for Responsible AI. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2204.01075v1; 2022-04-03
https://arxiv.org/pdf/2204.01075v1
Response SHA-256: ffe747c69935602e9a721480310f0ab8d70a590e4f7fc9ab3edaa2ab10b18118
Scoped evidence bindings: 5

[389] Documenting Large Webtext Corpora: A Case Study on the Colossal Clean Crawled Corpus. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2104.08758v2; 2021-09-30
https://arxiv.org/pdf/2104.08758v2
Response SHA-256: 721d817b6e6743ae7829bc4b77ea518cd585b18520ee716d3a11781d750d920c
Scoped evidence bindings: 5

[390] Understanding R1-Zero-Like Training: A Critical Perspective. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2503.20783v2; 2025-10-06
https://arxiv.org/pdf/2503.20783v2
Response SHA-256: 98243d51297f011fb5baad8a70a972d061ffbef618f1d7cfc10deea37c5887d0
Scoped evidence bindings: 5

[391] If in a Crowdsourced Data Annotation Pipeline, a GPT-4. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2402.16795v2; 2024-06-28
https://arxiv.org/pdf/2402.16795v2
Response SHA-256: ba747597683b1f80c2fbbfbb07308baa5bd206f13aa61e8d493e6f74c81b96f8
Scoped evidence bindings: 6

[392] Group Sequence Policy Optimization. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2507.18071v2; 2025-07-28
https://arxiv.org/pdf/2507.18071v2
Response SHA-256: 67221ec313f42d8b3029686b604b2621a311ae0d74e38524092e7c7a94613bd0
Scoped evidence bindings: 5

[393] HybridFlow: A Flexible and Efficient RLHF Framework. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2409.19256v2; 2024-10-02
https://arxiv.org/pdf/2409.19256v2
Response SHA-256: 4807a008bdea448c7a6aecc3b0aa65ffc45f1f4ca83c056bfe562b5e2397ce98
Scoped evidence bindings: 5

[394] The digital labour of artificial intelligence in Latin America: a comparison of Argentina, Brazil, and Venezuela. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2502.06317v1; 2025-02-10
https://arxiv.org/pdf/2502.06317v1
Response SHA-256: 457d52643f47daa6634839c2a3bf1c8e7289709f8453d4741acc14d37b6b996b
Scoped evidence bindings: 5

[395] Minority Reports: Balancing Cost and Quality in Ground Truth Data Annotation. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2504.09341v1; 2025-04-12
https://arxiv.org/pdf/2504.09341v1
Response SHA-256: b27178636b4cc8f56b7a65247e3ba6ee9ec6d9b4905f67d32802ba036721db19
Scoped evidence bindings: 5

[396] The Dataset Nutrition Label: A Framework To Drive Higher Data Quality Standards. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 1805.03677v1; 2018-05-09
https://arxiv.org/pdf/1805.03677v1
Response SHA-256: 8be208360982f7b916b3e259b08d8cd3c4f93e5e9a8fae2425a1912c5ff4a331
Scoped evidence bindings: 5

[397] OpenRLHF: An Easy-to-use, Scalable and High-performance RLHF Framework. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2405.11143v6; 2025-10-09
https://arxiv.org/pdf/2405.11143v6
Response SHA-256: b9797d8cb971705064d2aec706671cf44457d90b860910b9aae4cf5839e8750c
Scoped evidence bindings: 5

[398] Process Reinforcement through Implicit Rewards. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2502.01456v2; 2025-09-26
https://arxiv.org/pdf/2502.01456v2
Response SHA-256: b9b0d4ee041d5f21dec9489a67582e3775c3900a61bad979814522ab8b3faef6
Scoped evidence bindings: 5

[399] The Problems with Proxies: Making Data Work Visible through Requester Practices. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2408.11667v1; 2024-08-21
https://arxiv.org/pdf/2408.11667v1
Response SHA-256: 41f6aff403ca4cff9622bcec6e366b0530e074a5bf9e69b62d7895ce2f14fefe
Scoped evidence bindings: 5

[400] REINFORCE++: Stabilizing Critic-Free Policy Optimization with Global Advantage Normalization. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2501.03262v9; 2025-11-10
https://arxiv.org/pdf/2501.03262v9
Response SHA-256: b868a07e9d068dd4bc13eca28e7ce4afc380e26380b05c741d5dd2cc6821a59f
Scoped evidence bindings: 5

[401] On the Reliability of Majority-Vote Pseudo-Labels in Test-Time Reinforcement Learning. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2611.09872v1; 2026-11-06
https://arxiv.org/pdf/2611.09872v1
Response SHA-256: 6ae04bce5f0f268407f8d96ed4e16e6ffa39e0c193cb2e2b91c709c96cd7ba77
Scoped evidence bindings: 5

[402] SelectTTRL: Representation-Guided Data Selection for Efficient Test-Time Reinforcement Learning. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2610.16104v1; 2026-10-12
https://arxiv.org/pdf/2610.16104v1
Response SHA-256: 598550ad70ebfc786fd27b18f2383d54d433bee3c7a6d2abb82f72060d2b94f1
Scoped evidence bindings: 5

[403] STAMP Your Content: Proving Dataset Membership via Watermarked Rephrasings. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2504.13416v2; 2025-06-08
https://arxiv.org/pdf/2504.13416v2
Response SHA-256: 0c48ba4d0980e7fbd9b79b63333965ebf2dbb117580d4c0c080ecee4397c24fd
Scoped evidence bindings: 5

[404] TTRL: Test-Time Reinforcement Learning. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2504.16084v3; 2025-06-30
https://arxiv.org/pdf/2504.16084v3
Response SHA-256: 3828cc886a0133749fe857dc12fff190f76c17dd7421dccfca01c96ec1dd5882
Scoped evidence bindings: 7

[405] VAPO: Efficient and Reliable Reinforcement Learning for Advanced Reasoning Tasks. arXiv (author-deposited versioned preprint; not publisher VoR byte-verified); 2504.05118v3; 2025-04-11
https://arxiv.org/pdf/2504.05118v3
Response SHA-256: a10387626b86a8f9a6a80d17e727eb5a5036dc237a81d370c26e60d7c4168457
Scoped evidence bindings: 6

[406] AutoLibra: Agent Metric Induction from Open-Ended Human Feedback. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 2505.02820v3; 2025-10-29
https://arxiv.org/pdf/2505.02820v3
Response SHA-256: 584079f8651492bceb2bb86fdf8ae9f3cb36633833eb7b3551761ac099a620cc
Scoped evidence bindings: 4

[407] Aya Dataset: An Open-Access Collection for Multilingual Instruction Tuning. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 2402.06619v1; 2024-02-09
https://arxiv.org/pdf/2402.06619v1
Response SHA-256: 521d8a1c9cdfc466def9745499de330c6bc4d5b4e7c48609437462b18410b6a6
Scoped evidence bindings: 4

[408] CrowdAgent: Multi-Agent Managed Multi-Source Annotation System. ACL Anthology (exact captured publication copy); ACL-Anthology-2025.emnlp-demos.72-captured-copy
https://aclanthology.org/2025.emnlp-demos.72.pdf
Response SHA-256: db55042820e04c3c7ffd5d0b62aaffde024486f1811f9b0508f08a791218500e
Scoped evidence bindings: 4

[409] CrowdTruth 2.0: Quality Metrics for Crowdsourcing with Disagreement. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 1808.06080v1; 2018-08-18
https://arxiv.org/pdf/1808.06080v1
Response SHA-256: 5b734de88e5c471eb1017dcc3d25e06a901d7564678fd9c535579d75f2905613
Scoped evidence bindings: 4

[410] A Data-Driven Analysis of Workers' Earnings on Amazon Mechanical Turk. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 1712.05796v2; 2017-12-28
https://arxiv.org/pdf/1712.05796v2
Response SHA-256: 25b098a1baad2d4214dd9c4dac4290fac40d1217231a1d90d6627373c125060c
Scoped evidence bindings: 4

[411] Experts Rise Where LLMs Disagree: Using Cross-Model Disagreement to Target Expert Effort in LLM Codebook Revision for Large-Scale Annotation. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 2609.26926v1; 2026-09-22
https://arxiv.org/pdf/2609.26926v1
Response SHA-256: b227f50171f022ebae29b77f68753a690130c045b7d04bffc2e6cb999c628da1
Scoped evidence bindings: 4

[412] Garbage In, Garbage Out? Do Machine Learning Application Papers in Social Computing Report Where Human-Labeled Training Data Comes From?. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 1912.08320v1; 2019-12-17
https://arxiv.org/pdf/1912.08320v1
Response SHA-256: 68da81c0d496d9b8e1c0dfc43e5ec65f0de83faa38575bbe5f4bfac0cbb61222
Scoped evidence bindings: 4

[413] ChatGPT Outperforms Crowd-Workers for Text-Annotation Tasks. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 2303.15056v2; 2023-07-19
https://arxiv.org/pdf/2303.15056v2
Response SHA-256: da6865c3e57e8a956f2aeeadef0c814b2ab4a2db4753ef50037a4074b6e3d26f
Scoped evidence bindings: 4

[414] HelpSteer: Multi-attribute Helpfulness Dataset for SteerLM. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 2311.09528v1; 2023-11-16
https://arxiv.org/pdf/2311.09528v1
Response SHA-256: af48d77f75761d69e1d083fc5a2168351d81be30b47138bdb9b5178a6bc025f5
Scoped evidence bindings: 4

[415] HelpSteer2: Open-source dataset for training top-performing reward models. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 2406.08673v1; 2024-06-12
https://arxiv.org/pdf/2406.08673v1
Response SHA-256: 9c7754b5d099528a25e99c68c240474da68a1f4b287f753fdcc19139b691c943
Scoped evidence bindings: 4

[416] Inherent Disagreements in Human Textual Inferences. ACL Anthology (exact captured publication copy); ACL-Anthology-Q19-1043-captured-copy
https://aclanthology.org/Q19-1043.pdf
Response SHA-256: 6145dd60a513f3426d50718a2301f4189fce10735935ae86d8c01c826f6a6933
Scoped evidence bindings: 4

[417] LabelAId: Just-in-time AI Interventions for Improving Human Labeling Quality and Domain Knowledge in Crowdsourcing Systems. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 2403.09810v1; 2024-03-14
https://arxiv.org/pdf/2403.09810v1
Response SHA-256: 52030878aded4636165666cbafc58d62dcfe5f76d29fbe94af57f030b63eed4a
Scoped evidence bindings: 4

[418] Pervasive Label Errors in Test Sets Destabilize Machine Learning Benchmarks. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 2103.14749v4; 2021-11-07
https://arxiv.org/pdf/2103.14749v4
Response SHA-256: 605c6a72f3a970dbbdd02622079c32d687862455a1152da9f2075e35fad2bf1d
Scoped evidence bindings: 4

[419] Efficient Data Labeling by Hierarchical Crowdsourcing with Large Language Models. ACL Anthology (exact captured publication copy); ACL-Anthology-2025.coling-main.748-captured-copy
https://aclanthology.org/2025.coling-main.748.pdf
Response SHA-256: bc7719b1a7fa895353df574927de6d585fc654d30c3c181e24bb14c07c3c87ec
Scoped evidence bindings: 4

[420] Quality Assured: Rethinking Annotation Strategies in Imaging AI. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 2407.17596v2; 2024-07-26
https://arxiv.org/pdf/2407.17596v2
Response SHA-256: f196d771167aa4e43d887b59b99c35a8a05d4ffd075b75de60891b1c9ad2665d
Scoped evidence bindings: 4

[421] RECODE-H: A Benchmark for Research Code Development with Interactive Human Feedback. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 2510.06186v2; 2025-10-24
https://arxiv.org/pdf/2510.06186v2
Response SHA-256: 26b048307df93645e02a2eb852b1cb0ea1687c0f8ccd7ec66935fe649f903efb
Scoped evidence bindings: 4

[422] Cheap and Fast - But is it Good? Evaluating Non-Expert Annotations for Natural Language Tasks. ACL Anthology (exact captured publication copy); ACL-Anthology-D08-1027-captured-copy
https://aclanthology.org/D08-1027.pdf
Response SHA-256: 19f42e03a5f3a0d4401c75c7fade0040dd1f890c86fd6b8c1c4fec644bf6b7f4
Scoped evidence bindings: 4

[423] UltraFeedback: Boosting Language Models with Scaled AI Feedback. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 2310.01377v2; 2024-07-16
https://arxiv.org/pdf/2310.01377v2
Response SHA-256: 63a40ed6d1603fc07c09f113042f75619c1c17c0a0c8f1ea421477c0facbc8ca
Scoped evidence bindings: 4

[424] Who Annotates in NLP? A Large-scale Assessment of Human Annotation Reporting between 2018 and 2025. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 2606.02255v3; 2026-09-02
https://arxiv.org/pdf/2606.02255v3
Response SHA-256: 6fb65a7478f3d8a481bd2d97ab980509fc05ce24e3abb466a2752637a09a77b3
Scoped evidence bindings: 4

[425] WildChat: 1M ChatGPT Interaction Logs in the Wild. arXiv (author-deposited versioned preprint; publisher-copy equivalence not asserted); 2405.01470v1; 2024-05-02
https://arxiv.org/pdf/2405.01470v1
Response SHA-256: 932316edcaf09c144358c0c0bf6ad48a82f315c189e944c4afa0f90835bcf85e
Scoped evidence bindings: 4

[426] Helpful, Honest & Harmless pragmatic alignment evaluation README. Creator-maintained repository; 092b196c1f8f14a54bbc62f24759d43bde46dd3b
https://raw.githubusercontent.com/google/BIG-bench/092b196c1f8f14a54bbc62f24759d43bde46dd3b/bigbench/benchmark_tasks/hhh_alignment/README.md
Response SHA-256: a9026f2a9a4c8900ff2c605ba8c7fe5907fc09d36c55d31609ddc214def9c7e2
Scoped evidence bindings: 3

[427] RewardBench 1 evaluation dataset card. Ai2 / RewardBench creators; 168d848cdbbea9764fae4a544dc9ca1e6cca4931
https://huggingface.co/datasets/allenai/reward-bench/resolve/168d848cdbbea9764fae4a544dc9ca1e6cca4931/README.md
Response SHA-256: 819086ae803ffe3d3126eb2c188b8c67e2a0acb91b67096727f59f5aff423256
Scoped evidence bindings: 3

[428] APPS - README.md. hendrycks/apps; 362aedc3c71cd7d9bd2fc96a6c80e11dbc38c7a5
https://raw.githubusercontent.com/hendrycks/apps/362aedc3c71cd7d9bd2fc96a6c80e11dbc38c7a5/README.md
Response SHA-256: 9a301ef59a87611c90441299b114964c126a6112e0074e308d06d60df3981185
Scoped evidence bindings: 1

[429] NVIDIA HelpSteer2 dataset card. NVIDIA; 990b2711a36180dd19d9c94b8627844866f8982a
https://huggingface.co/datasets/nvidia/HelpSteer2/resolve/990b2711a36180dd19d9c94b8627844866f8982a/README.md
Response SHA-256: 835effb9e7d9cd0e8b7b8c1816d1d97a8961a036543108e4a0b6a5e22712ff7b
Scoped evidence bindings: 6

[430] Anthropic HH-RLHF dataset card. Anthropic; 09be8c5bbc57cb3887f3a9732ad6aa7ec602a1fa
https://huggingface.co/datasets/Anthropic/hh-rlhf/resolve/09be8c5bbc57cb3887f3a9732ad6aa7ec602a1fa/README.md
Response SHA-256: f75f40db0268656ba07736ec8e59a9720c1910ce554c85354cec74b1c8bda175
Scoped evidence bindings: 3

[431] OpenAssistant Conversations OASST1 dataset card. OpenAssistant / LAION-AI;
fdf72ae0827c1cda404aff25b6603abec9e3399b
https://huggingface.co/datasets/OpenAssistant/oasst1/resolve/fdf72ae0827c1cda404aff25b6603abec9e3399b/README.md
Response SHA-256: 68483ac2fcc2f3f7779f453352363827678070ef35b6d746ccb2ca6958540fff
Scoped evidence bindings: 4

[432] Stanford Human Preferences dataset card. Stanford NLP / SHP creators;
e94b5f32602712d78ed494fe79105b1959396686
https://huggingface.co/datasets/stanfordnlp/SHP/resolve/e94b5f32602712d78ed494fe79105b1959396686/README.md
Response SHA-256: 533784230dff4330073a69fec9464de80d01f9285f8e88e41f25bb033d407508
Scoped evidence bindings: 4

[433] UltraFeedback dataset card. OpenBMB / UltraFeedback creators; 40b436560ca83a8dba36114c22ab3c66e43f6d5e
https://huggingface.co/datasets/openbmb/UltraFeedback/resolve/40b436560ca83a8dba36114c22ab3c66e43f6d5e/README.md
Response SHA-256: 70a22b5659215ab738b9dfd0dc6bd40d3bb040bf846b4e34955358f30625a4f7
Scoped evidence bindings: 3

[434] ScienceToStartup canonical dataset 2.5.0 (historical local snapshot). ScienceToStartup; 2.5.0
sha256:948e69229fa24a4a1e6b5eed6d9c11570568a3c05bf9512e442d19611061a061
https://sciencetostartup.com/research.json
Response SHA-256: 948e69229fa24a4a1e6b5eed6d9c11570568a3c05bf9512e442d19611061a061
Scoped evidence bindings: 1

[435] MMLU creator repository evaluate.py. Creator-maintained repository;
4450500f923c49f1fb1dd3d99108a0bd9717b660
https://raw.githubusercontent.com/hendrycks/test/4450500f923c49f1fb1dd3d99108a0bd9717b660/evaluate.py
Response SHA-256: 8b7d84e5a2e9290df0d43d1c060aa68ecb638c4666415b3a58d709c18eace4ec
Scoped evidence bindings: 3

[436] OpenAssistant data collection task guidelines. Creator-maintained repository;
f1e6ed9526f5817531f3ab85441a40b3671ddccb
https://raw.githubusercontent.com/LAION-AI/Open-Assistant/f1e6ed9526f5817531f3ab85441a40b3671ddccb/docs/docs/guides/guidelines.md
Response SHA-256: 0ee4c2c2bb3fc94c0221dd2f3b1f1dfd3618c56f4f03afb4a9238157408bd329
Scoped evidence bindings: 4

[437] SWE-bench collection guide. Creator-maintained repository; 02e7a74ffd0b707aab73d203fe87bdc7c76afc8e
https://raw.githubusercontent.com/SWE-bench/SWE-bench/02e7a74ffd0b707aab73d203fe87bdc7c76afc8e/docs/assets/collection.md
Response SHA-256: b8ae0f6ae22121b75437dd8f643382b719aec84f877740d5b062f37490d25ea7
Scoped evidence bindings: 1

[438] SWE-bench evaluation guide. Creator-maintained repository; 02e7a74ffd0b707aab73d203fe87bdc7c76afc8e
https://raw.githubusercontent.com/SWE-bench/SWE-bench/02e7a74ffd0b707aab73d203fe87bdc7c76afc8e/docs/guides/evaluation.md
Response SHA-256: 770c8d6c45d507cd40a74297c2c7d779a5ab1f4f82da8a1a9dfae4d6bb03ff6e
Scoped evidence bindings: 2

[439] SWE-bench collection procedure README. Creator-maintained repository; 02e7a74ffd0b707aab73d203fe87bdc7c76afc8e
https://raw.githubusercontent.com/SWE-bench/SWE-bench/02e7a74ffd0b707aab73d203fe87bdc7c76afc8e/swebench/collect/README.md
Response SHA-256: e859628a4e5a29a12bdef112ca1bd4cb59d9de663dbf5f0247a311115a5e6ba6
Scoped evidence bindings: 1

[440] NVIDIA HelpSteer3 dataset card. NVIDIA; f6d145777bcbde96137596340fab89793acd1031
https://huggingface.co/datasets/nvidia/HelpSteer3/resolve/f6d145777bcbde96137596340fab89793acd1031/README.md
Response SHA-256: d5d46db58e8374937ea284b33b1583a4a465b232bf74b941745d80e3c35fd8ae
Scoped evidence bindings: 3

[441] CAIS MMLU dataset card. CAIS / MMLU creators; c30699e8356da336a370243923dbaf21066bb9fe
https://huggingface.co/datasets/cais/mmlu/resolve/c30699e8356da336a370243923dbaf21066bb9fe/README.md
Response SHA-256: 665eef35ecd8a89037c1e4f1e1a0d7fd4c154edc04c81cea5634ace2d3e96953
Scoped evidence bindings: 2

[442] RewardBench 2 evaluation dataset card. Ai2 / RewardBench creators; 7ff08853b0d5686e79b13fda8677024f566a104a
https://huggingface.co/datasets/allenai/reward-bench-2/resolve/7ff08853b0d5686e79b13fda8677024f566a104a/README.md
Response SHA-256: 4f9f92600767160c6b7b1a3c822361dabfea9ac254f8a152a02cb96ab0650911
Scoped evidence bindings: 1

[443] Original SWE-bench dataset card. SWE-bench creators; e48e2bd1e9fecd5bbd641e9414ac59da9f2e69f6
https://huggingface.co/datasets/princeton-nlp/SWE-bench/resolve/e48e2bd1e9fecd5bbd641e9414ac59da9f2e69f6/README.md
Response SHA-256: f0fb86ca5917025357564e0735f484bcfd340cc10445ca4eac4d866e9a164d52
Scoped evidence bindings: 2

[444] TruthfulQA HF distribution card. TruthfulQA repository creators; HF card community-contributed; 741b8276f2d1982aa3d5b832d3ee81ed3b896490
https://huggingface.co/datasets/truthfulqa/truthful_qa/resolve/741b8276f2d1982aa3d5b832d3ee81ed3b896490/README.md
Response SHA-256: 9e06075e7a580802a227e31cc456b37bdf5a174637f22e142b7609d709dd5f95
Scoped evidence bindings: 2

[445] HHH alignment parent task configuration. Creator-maintained repository; 092b196c1f8f14a54bbc62f24759d43bde46dd3b
https://raw.githubusercontent.com/google/BIG-bench/092b196c1f8f14a54bbc62f24759d43bde46dd3b/bigbench/benchmark_tasks/hhh_alignment/task.json
Response SHA-256: a49a91d541cc917e6d70e9ba7d2462b0609532b550279fccf51f2a0f77a61da5
Scoped evidence bindings: 1

[446] Training a Helpful and Harmless Assistant with Reinforcement Learning from Human Feedback, v1. Paper authors / arXiv; 2204.05862v1
https://arxiv.org/html/2204.05862v1
Response SHA-256: c9a87e489b7059afc0b31288e8f1a7e6ed246d74dcc9409e49ebc004a2b87593
Scoped evidence bindings: 4

[447] SWE-bench creator repository README. SWE-bench creators; 02e7a74ffd0b707aab73d203fe87bdc7c76afc8e
https://raw.githubusercontent.com/SWE-bench/SWE-bench/02e7a74ffd0b707aab73d203fe87bdc7c76afc8e/README.md
Response SHA-256: 06841624d7b5130dfe3cc6714642e9a8fd2a608c95c66ae0180e409f12b73aaa
Scoped evidence bindings: 1

[448] TruthfulQA creator repository README. TruthfulQA repository creators; HF card community-contributed; d71c110897f5d31c5d7f309e7bc316c152f6f031
https://raw.githubusercontent.com/sylinrl/TruthfulQA/d71c110897f5d31c5d7f309e7bc316c152f6f031/README.md
Response SHA-256: 23834ca77c34e909cbdcceeaea89135c65b713a5d0c77be6bced7a637763ea44
Scoped evidence bindings: 3

[449] UltraFeedback creator repository README. OpenBMB / UltraFeedback creators; bf80fd46a8c6ceecc86e8babb1ae8771f26a3cbb
https://raw.githubusercontent.com/OpenBMB/UltraFeedback/bf80fd46a8c6ceecc86e8babb1ae8771f26a3cbb/README.md
Response SHA-256: ecf2a9052bbdcf4630fc97c400866d733643b9084c64b04c7f6bce73dbcc356a
Scoped evidence bindings: 1

[450] TruthfulQA: Measuring How Models Mimic Human Falsehoods. arXiv / paper authors; 2109.07958v2
https://arxiv.org/pdf/2109.07958v2
Response SHA-256: 6e86175861d24d075bbd8fec987cbdabd0d6332700b001a1ccf335fa72f541b2
Scoped evidence bindings: 8

[451] VideoScore repository LICENSE. TIGER-AI-Lab/VideoScore; f87faf4647e637066bcb74721670cd579e0f4349
https://raw.githubusercontent.com/TIGER-AI-Lab/VideoScore/f87faf4647e637066bcb74721670cd579e0f4349/LICENSE
Response SHA-256: 821d038afa755049f68fff5a0bcb4db416f16426b39447c095b80670be795fc8
Scoped evidence bindings: 1

[452] Privacy Policy | APTO. APTO;
response-sha256:769a197c93259fa75670798ac4c3f713cc3a26e833bb93eb3099fcc715984b9c
https://apto.co.jp/en/privacy-policy/
Response SHA-256: 769a197c93259fa75670798ac4c3f713cc3a26e833bb93eb3099fcc715984b9c
Scoped evidence bindings: 1

[453] Datasheets for Datasets. arXiv / paper authors; 1803.09010v8
https://arxiv.org/abs/1803.09010v8
Response SHA-256: 6ff49b1a436386614b2172e351b60d45e01d5a48c678f8731c2b6c0cdd3947a1
Scoped evidence bindings: 1

[454] Measuring Massive Multitask Language Understanding. arXiv / paper authors; 2009.03300v3
https://arxiv.org/abs/2009.03300v3
Response SHA-256: c2f09edccaea2fa2d18edf4c88ebaaa2531d6b6fb4509ef5deb9bf0b55071f93
Scoped evidence bindings: 1

[455] TruthfulQA: Measuring How Models Mimic Human Falsehoods. arXiv / paper authors; 2109.07958v2
https://arxiv.org/abs/2109.07958v2
Response SHA-256: f6076f5fb265c258f41325aa571f25d65ed8c73744c654f60bd9095228141c32
Scoped evidence bindings: 1

[456] Training language models to follow instructions with human feedback. arXiv / paper authors; 2203.02155v1
https://arxiv.org/abs/2203.02155v1
Response SHA-256: 350f6cfe6cd4047f95c8c598839df74f9a13d5441bd75115fd87bd23d9a8174a
Scoped evidence bindings: 1

[457] Direct Preference Optimization: Your Language Model is Secretly a Reward Model. arXiv / paper authors; 2305.18290v3
https://arxiv.org/abs/2305.18290v3
Response SHA-256: 08edfdec10277f58ef5b670abe5d4c12772011b485501756e09527c895948d2b
Scoped evidence bindings: 1

[458] SWE-bench: Can Language Models Resolve Real-World GitHub Issues?. arXiv / paper authors; 2310.06770v3
https://arxiv.org/abs/2310.06770v3
Response SHA-256: 55b7b98eefc6bcc924cd4c4978ba276469e321f521400c345e46abd37f19f5a9
Scoped evidence bindings: 1

[459] The FineWeb Datasets: Decanting the Web for the Finest Text Data at Scale. arXiv / paper authors; 2406.17557v2
https://arxiv.org/abs/2406.17557v2
Response SHA-256: 8b45f0e0560aeba3d03908a052037b79dadc400dd94d9561f64b226826a3909e
Scoped evidence bindings: 1

[460] HelpSteer3-Preference: Open Human-Annotated Preference Data across Diverse Tasks and Languages. arXiv / paper authors; 2505.11475v2
https://arxiv.org/abs/2505.11475v2
Response SHA-256: 68b5071fdac5cd44109bfcbc9dc03d22c15881b22e336ab74c70d5844311a957
Scoped evidence bindings: 1

[461] NVIDIA HelpSteer3 dataset card. NVIDIA; HF dataset card response sha256:827e51e12a2537403f516e7e5299455c9de36994b621deab2b9a7524e01b29b7
https://huggingface.co/datasets/nvidia/HelpSteer3
Response SHA-256: 827e51e12a2537403f516e7e5299455c9de36994b621deab2b9a7524e01b29b7
Scoped evidence bindings: 1

[462] Datasheets for Datasets. arXiv / paper authors; 1803.09010v8
https://arxiv.org/pdf/1803.09010v8
Response SHA-256: c7f595988ee2c109631d5173fdae37ff1774c68ec17add51bd012f2a6e8792d0
Scoped evidence bindings: 5

[463] Measuring Massive Multitask Language Understanding. arXiv / paper authors; 2009.03300v3
https://arxiv.org/pdf/2009.03300v3
Response SHA-256: d3a7b0f8589f5365ebfd34a3876a9a8b3fde83e0adb9ed19ccf8f0034bb48fc1
Scoped evidence bindings: 5

[464] Training language models to follow instructions with human feedback. arXiv / paper authors; 2203.02155v1
https://arxiv.org/pdf/2203.02155v1
Response SHA-256: c1984bb50a5b90fddb895fdc3a0f72e5bc977148c9f63ef6040cbe7a3e1f0d98
Scoped evidence bindings: 6

[465] Direct Preference Optimization: Your Language Model is Secretly a Reward Model. arXiv / paper authors; 2305.18290v3
https://arxiv.org/pdf/2305.18290v3
Response SHA-256: 92cb3a2b71362acda98a789b03d88688fd33cf5fcf13f81d2b1de30ee7d3b67a
Scoped evidence bindings: 5

[466] SWE-bench: Can Language Models Resolve Real-World GitHub Issues?. arXiv / paper authors; 2310.06770v3
https://arxiv.org/pdf/2310.06770v3
Response SHA-256: f7e8e1df64129742b8199a21a042734519a823a1dafd6f48f8f3ddcfb48ee296
Scoped evidence bindings: 6

[467] The FineWeb Datasets: Decanting the Web for the Finest Text Data at Scale. arXiv / paper authors; 2406.17557v2
https://arxiv.org/pdf/2406.17557v2
Response SHA-256: ae632bd6618d2566e708962670f27ab1fbc5ba9bc8de3acaceee8fbda85fbdd4
Scoped evidence bindings: 6

[468] HelpSteer3-Preference: Open Human-Annotated Preference Data across Diverse Tasks and Languages. arXiv / paper authors; 2505.11475v2
https://arxiv.org/pdf/2505.11475v2
Response SHA-256: ced74aea64c773933b2a0c60e4bb76edeff6313944c255f2dba373cc5d343563
Scoped evidence bindings: 5

[469] AI training data services | Appen. Appen Limited; Captured response sha256:2be61f7100fdb4e6cd4d9687fddc37b14b65625cf9f0cf029c099191655d3af5
https://www.appen.com/ai-data
Response SHA-256: 2be61f7100fdb4e6cd4d9687fddc37b14b65625cf9f0cf029c099191655d3af5
Scoped evidence bindings: 5

[470] Appen Annual Report 2025. Appen Limited; Captured response sha256:93d65cd1fff04294c7847f20d6577b7073c5964bb78df7101e5ff44554657b38
https://cdn.prod.website-files.com/656a605609413dfd3feb9d34/699fbc072974a573b2b7a48c_Appen%20Annual%20Report%202025.pdf
Response SHA-256: 93d65cd1fff04294c7847f20d6577b7073c5964bb78df7101e5ff44554657b38
Scoped evidence bindings: 5

[471] AI Data Security & Compliance | Appen. Appen Limited; Captured response sha256:ef83e1b7fbc0dbf662a79e43363cdbde916e75c44523f8ed879dc91c3973d777
https://www.appen.com/data-security
Response SHA-256: ef83e1b7fbc0dbf662a79e43363cdbde916e75c44523f8ed879dc91c3973d777
Scoped evidence bindings: 1

[472] Privacy Statement | Appen. Appen Limited; Captured response sha256:7e7624f5f9e9fe19a478ba600c60bbc81ab303e81bdcdca5d1e993c0a0b63a50
https://www.appen.com/legal-policies/privacy-statement
Response SHA-256: 7e7624f5f9e9fe19a478ba600c60bbc81ab303e81bdcdca5d1e993c0a0b63a50
Scoped evidence bindings: 2

[473] Introducing APEX-Agents 1.1. Mercor.io Corporation; Captured response sha256:43928e13914303e50f832607d4d1b83308beea7b90074f5f9957fdee8a8d9bc0; 2026-09-08
https://www.mercor.com/blog/introducing-apex-agents-1-1/
Response SHA-256: 43928e13914303e50f832607d4d1b83308beea7b90074f5f9957fdee8a8d9bc0
Scoped evidence bindings: 3

[474] Off-The-Shelf AI Training Datasets (Licence Ready) | Mercor. Mercor.io Corporation; Captured response sha256:4e4f3f637d3d9528053ccb9def276e1a17445d50cb51a0f179fb8121c02251bf
https://www.mercor.com/apex/off-the-shelf-data/
Response SHA-256: 4e4f3f637d3d9528053ccb9def276e1a17445d50cb51a0f179fb8121c02251bf
Scoped evidence bindings: 5

[475] Mercor | Website Privacy Notice. Mercor.io Corporation; Captured response sha256:b22118719b4cabf509c51eafe24a3267b68040e4ebb6cd1fb924907f687dd023; 2026-08-26
https://www.mercor.com/privacy-notice/
Response SHA-256: b22118719b4cabf509c51eafe24a3267b68040e4ebb6cd1fb924907f687dd023
Scoped evidence bindings: 2

[476] Mercor Data Breach: Investigation Findings and Updates. Mercor.io Corporation; Captured response sha256:2648cabcf7aca1dd54bf4d2bb1891d05abda335fc32099dd1a8fe423e43659fd; 2026-06-25
https://www.mercor.com/blog/update-on-mercor-security-incident/
Response SHA-256: 2648cabcf7aca1dd54bf4d2bb1891d05abda335fc32099dd1a8fe423e43659fd
Scoped evidence bindings: 1

[477] Participants skilled at AI tasks | Prolific Research. Prolific; Captured response sha256:118c59b6b8c84e52b76decfd3f3efded727244a7e3c4bb7b13a533e5499a9d17; 2026-03-18
https://researcher-help.prolific.com/en/articles/445229-participants-skilled-at-ai-tasks
Response SHA-256: 118c59b6b8c84e52b76decfd3f3efded727244a7e3c4bb7b13a533e5499a9d17
Scoped evidence bindings: 2

[478] Prolific Case Study | Cohere and University of Edinburgh | Prolific. Prolific; Captured response sha256:5546b2dfc28f559910240a410a4d020d8cdc362f7396cdafc5969d5307ae187b; 2024-06-07
https://www.prolific.com/resources/tom-hosking-navigating-biases-in-human-feedback-for-ai-training
Response SHA-256: 5546b2dfc28f559910240a410a4d020d8cdc362f7396cdafc5969d5307ae187b
Scoped evidence bindings: 2

[479] Prolific Pricing | Platform & managed services | Prolific. Prolific; Captured response sha256:0c3c2338fa2ae161efa6c95e62f2830ceefe370da90ad95f7fab7a9759c9acfb
https://www.prolific.com/pricing
Response SHA-256: 0c3c2338fa2ae161efa6c95e62f2830ceefe370da90ad95f7fab7a9759c9acfb
Scoped evidence bindings: 4

[480] Prolific sets standards for authentic human data collection | Prolific. Prolific; Captured response sha256:f7eca38c949ba6dfe1a251ce42579ab97872fd8032a8c8a04c35358e22c4be97; 2026-10-20
https://www.prolific.com/resources/prolific-setting-standards-for-authentic-human-data-collection
Response SHA-256: f7eca38c949ba6dfe1a251ce42579ab97872fd8032a8c8a04c35358e22c4be97
Scoped evidence bindings: 1

[481] Data Security and Privacy at Prolific | Prolific | Prolific. Prolific; Captured response sha256:677597f1729cdd67ea45f172647fa0a8f546bd370712eaf82a01942b0d043061
https://www.prolific.com/prolific-security-overview
Response SHA-256: 677597f1729cdd67ea45f172647fa0a8f546bd370712eaf82a01942b0d043061
Scoped evidence bindings: 1

[482] Are there types of studies that aren't suitable for Prolific? | Prolific Research. Prolific; Captured response sha256:bcb70625ccff5f1c0a530a8534fcf80008310bb91a09bde12d6e1bb9fb5526f6; 2026-08-05
https://researcher-help.prolific.com/en/articles/445105-are-there-types-of-studies-that-aren-t-suitable-for-prolific
Response SHA-256: bcb70625ccff5f1c0a530a8534fcf80008310bb91a09bde12d6e1bb9fb5526f6
Scoped evidence bindings: 1

[483] Modern Slavery Statement | Scale AI. Scale AI; Captured response sha256:70bc87f043c892daa4b7fc963f3139d81325f4ce64f48428ebd3720bfc9a9386
https://scale.com/legal/modern-slavery-statement
Response SHA-256: 70bc87f043c892daa4b7fc963f3139d81325f4ce64f48428ebd3720bfc9a9386
Scoped evidence bindings: 5

[484] scale.helpsteer3-card pinned README.md. NVIDIA; Captured response sha256:d5d46db58e8374937ea284b33b1583a4a465b232bf74b941745d80e3c35fd8ae
https://huggingface.co/datasets/nvidia/HelpSteer3/raw/f6d145777bcbde96137596340fab89793acd1031/README.md
Response SHA-256: d5d46db58e8374937ea284b33b1583a4a465b232bf74b941745d80e3c35fd8ae
Scoped evidence bindings: 1

[485] Generative AI Data Engine | Scale AI. Scale AI; Captured response
sha256:ce5e1dabfafc8a607d1ef7ece805150a6ee0c7b71878ff6b6ed3c8eccdfac2c4
https://scale.com/generative-ai-data-engine
Response SHA-256: ce5e1dabfafc8a607d1ef7ece805150a6ee0c7b71878ff6b6ed3c8eccdfac2c4
Scoped evidence bindings: 2

[486] How We Engineer World-Class Data at Scale | Scale AI. Scale AI; Captured response
sha256:86363dc9d41257758e86093047af5ce76d86b41876149801a21c01a2d198bb36; 2026-06-29
https://scale.com/blog/data-quality
Response SHA-256: 86363dc9d41257758e86093047af5ce76d86b41876149801a21c01a2d198bb36
Scoped evidence bindings: 2

[487] Security at Scale.com | Scale AI. Scale AI; Captured response
sha256:25ddfbad6b4a78b7d787f526ca9fea44811500fd737168a3265926c0afaa37b8
https://scale.com/security
Response SHA-256: 25ddfbad6b4a78b7d787f526ca9fea44811500fd737168a3265926c0afaa37b8
Scoped evidence bindings: 1

[488] Join our Expert Community | Snorkel AI. Snorkel AI, Inc.; Captured response
sha256:0cccfbc0dd20cbfe01b86ff2b1dd6a3bc8922027e43278a35694ea776278da0c
https://snorkel.ai/expert-community/
Response SHA-256: 0cccfbc0dd20cbfe01b86ff2b1dd6a3bc8922027e43278a35694ea776278da0c
Scoped evidence bindings: 4

[489] Frequently Asked Questions | Snorkel AI. Snorkel AI, Inc.; Captured response
sha256:3050d01c8521d07cd613c366efdef416508ce04bccbb91dd1be6829e6060de20; 2026-06-17
https://snorkel.ai/frequently-asked-questions/
Response SHA-256: 3050d01c8521d07cd613c366efdef416508ce04bccbb91dd1be6829e6060de20
Scoped evidence bindings: 4

[490] Snorkel AI Leaderboards | Snorkel AI. Snorkel AI, Inc.; Captured response
sha256:58e9a00deedf172e09f8177d6179f4f08453e24c18041dfaa07fc5eba34ef2d3
https://snorkel.ai/leaderboard/category/financereasoning/
Response SHA-256: 58e9a00deedf172e09f8177d6179f4f08453e24c18041dfaa07fc5eba34ef2d3
Scoped evidence bindings: 1

[491] Privacy Policy | Snorkel AI. Snorkel AI, Inc.; Captured response
sha256:5a1e9296ec15d80d6d7148730b3cc05bd3e7b6abdb08d739fdf8cdeb5a50b0a6; 2026-10-19
https://snorkel.ai/privacy/
Response SHA-256: 5a1e9296ec15d80d6d7148730b3cc05bd3e7b6abdb08d739fdf8cdeb5a50b0a6
Scoped evidence bindings: 3

[492] surge.gsm8k-card pinned README.md. OpenAI; Captured response
sha256:a17e882503578c9e324560630e31017617714ee025c87cf4fea6fd916895f3c1
https://huggingface.co/datasets/openai/gsm8k/raw/740312add88f781978c0658806c59bc2815b9866/README.md
Response SHA-256: a17e882503578c9e324560630e31017617714ee025c87cf4fea6fd916895f3c1
Scoped evidence bindings: 2

[493] Privacy Policy | Surge AI. Surge Labs, Inc.; Captured response
sha256:adc676a5886b92cc0d0375ca66d9136e0b058f26f6963fc89e504aaa6a4cbdf6; 2026-07-01
https://surgehq.ai/privacy-policy
Response SHA-256: adc676a5886b92cc0d0375ca66d9136e0b058f26f6963fc89e504aaa6a4cbdf6
Scoped evidence bindings: 2

[494] Products | Surge AI. Surge Labs, Inc.; Captured response
sha256:26650a8c884ede1498a46b449955dec2fd9166ed844407fa7396319102b32e7d
https://surgehq.ai/products
Response SHA-256: 26650a8c884ede1498a46b449955dec2fd9166ed844407fa7396319102b32e7d
Scoped evidence bindings: 4

[495] Terms of Service | Surge AI. Surge Labs, Inc.; Captured response
sha256:affca92e60b1c466c5c6ca96973171a2a4b7a13503f522566ef4513ccab7421d; 2021-12-07
https://surgehq.ai/terms-of-service
Response SHA-256: affca92e60b1c466c5c6ca96973171a2a4b7a13503f522566ef4513ccab7421d
Scoped evidence bindings: 1

[496] Guidelines for posting compliant tasks | Toloka documentation. Toloka AI B.V.; Captured response
sha256:4ee70477eccc2d50a3a0e14f0d39b3545e363f70ae3d84c02527645e86d94c20
https://toloka.ai/docs/guide/unwanted/
Response SHA-256: 4ee70477eccc2d50a3a0e14f0d39b3545e363f70ae3d84c02527645e86d94c20
Scoped evidence bindings: 4

[497] AI + Humans: Data to Power LLMs & VLMs. Toloka AI B.V.; Captured response
sha256:aa0ae077444a739a14d84d0c9d5abc5f778eb8949e6953af96e5415b8918471f
https://toloka.ai/hybrid-data
Response SHA-256: aa0ae077444a739a14d84d0c9d5abc5f778eb8949e6953af96e5415b8918471f
Scoped evidence bindings: 4

[498] Expert human data is now available to all, introducing the new Toloka Platform. Toloka AI B.V.; Captured response
sha256:9bae9f5ebef0dfa4ce2c5b6454ebe870b62954f02bd0602dc5d157a274242384; 2026-01-19
https://toloka.ai/blog/introducing-the-new-toloka-platform/
Response SHA-256: 9bae9f5ebef0dfa4ce2c5b6454ebe870b62954f02bd0602dc5d157a274242384
Scoped evidence bindings: 2

[499] Privacy Notice. Toloka AI B.V.; Captured response
sha256:1d6d372770d126648c7c347fd4a7b8dfd565046fbc9f1206dd0ea084bf84f212; 2026-10-12
https://toloka.ai/legal/privacy-notice
Response SHA-256: 1d6d372770d126648c7c347fd4a7b8dfd565046fbc9f1206dd0ea084bf84f212
Scoped evidence bindings: 4

[500] toloka.umath-card pinned README.md. Toloka AI B.V.; Captured response
sha256:c13bf3579ababfb2510ca76ca0de6185ef2ff97caaf69ebf6a89d761c8c42871
https://huggingface.co/datasets/toloka/u-math/raw/7210f97b3f21122c3a90126935e966ca7d8951b6/README.md
Response SHA-256: c13bf3579ababfb2510ca76ca0de6185ef2ff97caaf69ebf6a89d761c8c42871
Scoped evidence bindings: 1

[501] 35K+ Agent Trajectories and 120K+ RLHF Pairs Across 150+ Real Tools. Turing Enterprises, Inc.; Captured response
sha256:5b0083910fdb37276d7d65eafb7f6f8b1f93889e0a06bb0f220b7dd8ec9b5891
https://www.turing.com/blog/frontier-ai-newsletter-79
Response SHA-256: 5b0083910fdb37276d7d65eafb7f6f8b1f93889e0a06bb0f220b7dd8ec9b5891
Scoped evidence bindings: 2

[502] Experts: Vetted Domain Talent for Frontier AI Labs | Turing. Turing Enterprises, Inc.; Captured response
sha256:58e8b558b1d70033ab022c8b99aab7c477b88508881ed7bb75b882e7e8e21acb
https://www.turing.com/frontier-ai/experts
Response SHA-256: 58e8b558b1d70033ab022c8b99aab7c477b88508881ed7bb75b882e7e8e21acb
Scoped evidence bindings: 1

[503] Turing announces Turing Frontier, connecting AI labs with elite domain experts. Turing Enterprises, Inc.; Captured response sha256:544ca3d9d1905acc800bd4f5df1992f0eac1591bd044ce96bd0c10498512f085 https://www.turing.com/press/turing-announces-turing-frontier
Response SHA-256: 544ca3d9d1905acc800bd4f5df1992f0eac1591bd044ce96bd0c10498512f085
Scoped evidence bindings: 3

[504] Turing Privacy Policy | For Visitors, Users & Others. Turing Enterprises, Inc.; Captured response sha256:45306dbc6a1f708028e93ca241e5033d8a6b37cbac888df8da001c403fa8e0dd; 2025-06-27 https://www.turing.com/policy
Response SHA-256: 45306dbc6a1f708028e93ca241e5033d8a6b37cbac888df8da001c403fa8e0dd
Scoped evidence bindings: 3

Evidence and reproduction

The complete public evidence graph accompanies this report in the offline archive. Paragraph evidence IDs refer to that graph. The JSON, CSV and SQLite contain equivalent privacy-filtered projection 1.0.0. Canonical dataset 2.5.0 remains unchanged outside this archive. Raw source text and personal contact details are excluded.

Verify MANIFEST.json, then run python3 reproduce.py --write-tables reproduced in the extracted archive. LOCATORS.md documents evidence coordinates. Owned research and text use CC BY 4.0; third-party material retains its rights. Embedded DejaVu fonts and the Noto Sans SC derived CJK subset retain their upstream terms in DejaVu-LICENSE.txt and CJK-OFL.txt and are excluded from the project's CC BY 4.0 and MIT licenses. Review scope and research gaps remain explicit. This PDF's status does not establish website or external mirror publication.