

# NORMAL PROCEDURES CHECKLIST Aircraft: \_\_\_\_\_

Cessna 172 Series | For Training Use Only | Ref: POH Section 4

## FLIGHT INFORMATION

|               |  |                    |  |
|---------------|--|--------------------|--|
| PIC Name      |  | Student / SIC Name |  |
| Aircraft Reg. |  | Date / Time        |  |

**⚠ WARNING:** This checklist is for training use only. Always refer to the current approved POH/AFM for actual flight operations.

| PREFLIGHT INSPECTION                                        |                              |
|-------------------------------------------------------------|------------------------------|
| <input type="checkbox"/> Fuel quantity (both tanks)         | CHECK / QUANTITY             |
| <input type="checkbox"/> Fuel caps                          | SECURE                       |
| <input type="checkbox"/> Fuel type (Avgas 100LL)            | VERIFY                       |
| <input type="checkbox"/> Oil level                          | CHECK (min 4 qt, max 8 qt)   |
| <input type="checkbox"/> Oil filler cap                     | SECURE                       |
| <input type="checkbox"/> Engine compartment — leaks/debris  | CHECK CLEAR                  |
| <input type="checkbox"/> Air intake / filter                | CHECK CLEAR                  |
| <input type="checkbox"/> Propeller                          | NO NICKS / CRACKS            |
| <input type="checkbox"/> Spinner                            | SECURE                       |
| <input type="checkbox"/> Landing gear / tyres               | CONDITION / INFLATION        |
| <input type="checkbox"/> Brake fluid                        | CHECK                        |
| <input type="checkbox"/> Nosewheel shimmy damper            | CHECK CONDITION              |
| <input type="checkbox"/> Static port (both sides)           | UNOBSTRUCTED                 |
| <input type="checkbox"/> Pitot tube / cover removed         | CLEAR                        |
| <input type="checkbox"/> Fuel drains (sump / strainer)      | SAMPLE CLEAR                 |
| <input type="checkbox"/> Control surfaces — free / correct  | CHECK                        |
| <input type="checkbox"/> Flaps — travel and condition       | CHECK                        |
| <input type="checkbox"/> Antennas                           | SECURE / NO DAMAGE           |
| <input type="checkbox"/> Stall warning vane                 | CHECK                        |
| <input type="checkbox"/> Lights (nav/strobes/landing)       | CHECK                        |
| <input type="checkbox"/> Windshield                         | CLEAN / UNOBSTRUCTED         |
| BEFORE ENGINE START                                         |                              |
| <input type="checkbox"/> Aircraft documents (ARROW)         | ON BOARD                     |
| <input type="checkbox"/> Seat, seat belts, shoulder harness | ADJUST / SECURE              |
| <input type="checkbox"/> Doors / windows                    | CLOSED & LATCHED             |
| <input type="checkbox"/> Brakes                             | TEST / HOLD                  |
| <input type="checkbox"/> Circuit breakers                   | IN                           |
| <input type="checkbox"/> Avionics Master Switch             | OFF                          |
| <input type="checkbox"/> Fuel Selector Valve                | BOTH                         |
| <input type="checkbox"/> Master Switch (ALT & BAT)          | ON                           |
| <input type="checkbox"/> Fuel quantity indicators           | CHECK                        |
| <input type="checkbox"/> Fuel pump (AUX BOOST PUMP)         | ON — check pressure then OFF |
| <input type="checkbox"/> Lights — nav / beacon              | ON                           |
| <input type="checkbox"/> Master Switch                      | OFF                          |
| ENGINE START                                                |                              |
| <input type="checkbox"/> Throttle                           | OPEN 1/4 inch                |
| <input type="checkbox"/> Mixture                            | RICH (below 3,000 ft)        |
| <input type="checkbox"/> Fuel selector                      | BOTH                         |
| <input type="checkbox"/> Primer                             | AS REQUIRED / IN & LOCKED    |

|                                                                                     |                          |
|-------------------------------------------------------------------------------------|--------------------------|
| <input type="checkbox"/> Master Switch                                              | ON                       |
| <input type="checkbox"/> Aux fuel pump                                              | ON — check fuel pressure |
| <input type="checkbox"/> PROPELLER AREA                                             | ⚠ CLEAR                  |
| <input type="checkbox"/> Ignition switch                                            | START                    |
| <input type="checkbox"/> Oil pressure                                               | CHECK within 30 sec      |
| <input type="checkbox"/> Throttle (warm up)                                         | 1,000 RPM                |
| <input type="checkbox"/> Avionics Master                                            | ON                       |
| <input type="checkbox"/> Amps/Volts                                                 | CHECK                    |
| <b>BEFORE TAXI</b>                                                                  |                          |
| <input type="checkbox"/> ATIS / Weather                                             | OBTAIN                   |
| <input type="checkbox"/> Altimeter                                                  | SET (QNH)                |
| <input type="checkbox"/> Heading indicator                                          | ALIGN WITH COMPASS       |
| <input type="checkbox"/> Gyros / Attitude Indicator                                 | ERECT                    |
| <input type="checkbox"/> Nav lights                                                 | AS REQUIRED              |
| <input type="checkbox"/> Transponder                                                | ALT / SQUAWK             |
| <input type="checkbox"/> Radios / GPS                                               | SET                      |
| <input type="checkbox"/> Taxi clearance / ATC contact                               | OBTAINED                 |
| <b>TAXI</b>                                                                         |                          |
| <input type="checkbox"/> Brakes — initial test                                      | CHECK                    |
| <input type="checkbox"/> Turns — controls / AI                                      | CHECK                    |
| <input type="checkbox"/> Taxi speed                                                 | SLOW WALKING PACE        |
| <b>BEFORE TAKEOFF (RUNUP)</b>                                                       |                          |
| <input type="checkbox"/> Parking brake                                              | SET                      |
| <input type="checkbox"/> Seats / belts                                              | SECURE                   |
| <input type="checkbox"/> Doors / windows                                            | CLOSED / LATCHED         |
| <input type="checkbox"/> Flight controls — free and correct                         | CHECK                    |
| <input type="checkbox"/> Instruments                                                | CHECK / SET              |
| <input type="checkbox"/> Fuel — sufficient / correct tank                           | BOTH / CHECK             |
| <input type="checkbox"/> Fuel pump (AUX)                                            | ON                       |
| <input type="checkbox"/> Mixture                                                    | RICH (below 3,000 ft)    |
| <input type="checkbox"/> Throttle to 1,800 RPM                                      | SET                      |
| <input type="checkbox"/> Magnetos — L / R check (max 125 RPM drop, max 50 RPM diff) | CHECK                    |
| <input type="checkbox"/> Carb heat — note RPM drop                                  | CHECK                    |
| <input type="checkbox"/> Engine instruments                                         | ALL GREEN                |
| <input type="checkbox"/> Throttle (idle check)                                      | RPM < 700                |
| <input type="checkbox"/> Throttle                                                   | 1,000 RPM                |
| <input type="checkbox"/> Radios / transponder                                       | SET                      |
| <input type="checkbox"/> Lights (landing / strobes)                                 | ON                       |
| <input type="checkbox"/> Flaps                                                      | SET FOR TAKEOFF          |
| <input type="checkbox"/> Brakes                                                     | HOLD FIRM                |
| <input type="checkbox"/> Takeoff clearance                                          | OBTAINED                 |
| <b>NORMAL TAKEOFF</b>                                                               |                          |
| <input type="checkbox"/> Throttle                                                   | FULL SMOOTH              |
| <input type="checkbox"/> Mixture                                                    | RICH                     |
| <input type="checkbox"/> Airspeed indicator                                         | ALIVE (check)            |
| <input type="checkbox"/> Lift-off (Vr)                                              | 55 KIAS                  |
| <input type="checkbox"/> Initial climb speed                                        | 65 KIAS                  |
| <input type="checkbox"/> Flaps                                                      | RETRACT ABOVE 200 ft AGL |

|                                                         |                           |
|---------------------------------------------------------|---------------------------|
| <input type="checkbox"/> Fuel pump (AUX)                | OFF (after positive rate) |
| <b>SHORT-FIELD TAKEOFF</b>                              |                           |
| <input type="checkbox"/> Flaps                          | 10°                       |
| <input type="checkbox"/> Brakes                         | HOLD FIRM                 |
| <input type="checkbox"/> Throttle                       | FULL POWER                |
| <input type="checkbox"/> Brakes                         | RELEASE                   |
| <input type="checkbox"/> Lift-off                       | 53 KIAS                   |
| <input type="checkbox"/> Obstacle clearance speed       | 56 KIAS                   |
| <input type="checkbox"/> Flaps                          | RETRACT ABOVE 200 ft AGL  |
| <b>SOFT-FIELD TAKEOFF</b>                               |                           |
| <input type="checkbox"/> Flaps                          | 10°                       |
| <input type="checkbox"/> Throttle                       | FULL SMOOTH (immediately) |
| <input type="checkbox"/> Nose-high attitude             | MAINTAIN                  |
| <input type="checkbox"/> Lift-off (as soon as possible) | MINIMUM SPEED             |
| <input type="checkbox"/> Accelerate in ground effect    | VX / VY                   |
| <input type="checkbox"/> Flaps                          | RETRACT ABOVE 200 ft AGL  |
| <b>CLIMB</b>                                            |                           |
| <input type="checkbox"/> Airspeed                       | 74 KIAS                   |
| <input type="checkbox"/> Throttle                       | FULL / AS REQUIRED        |
| <input type="checkbox"/> Mixture                        | ADJUST above 3,000 ft     |
| <input type="checkbox"/> Engine instruments             | MONITOR                   |
| <input type="checkbox"/> Fuel pump                      | OFF (cruise climb only)   |
| <b>CRUISE</b>                                           |                           |
| <input type="checkbox"/> Power setting                  | SET (55%–75%)             |
| <input type="checkbox"/> Mixture                        | LEAN (cruise power)       |
| <input type="checkbox"/> Altimeter                      | CHECK / RESET             |
| <input type="checkbox"/> Instruments                    | MONITOR                   |
| <input type="checkbox"/> ATIS/AWOS                      | MONITOR                   |
| <b>DESCENT</b>                                          |                           |
| <input type="checkbox"/> ATIS / current weather         | OBTAIN                    |
| <input type="checkbox"/> Altimeter                      | RESET (QNH)               |
| <input type="checkbox"/> Mixture                        | RICH (below 3,000 ft)     |
| <input type="checkbox"/> Fuel pump (AUX)                | ON                        |
| <input type="checkbox"/> Carb heat                      | ON (if icing conditions)  |
| <input type="checkbox"/> Power                          | REDUCE GRADUALLY          |
| <b>BEFORE LANDING</b>                                   |                           |
| <input type="checkbox"/> Fuel Selector                  | BOTH                      |
| <input type="checkbox"/> Fuel pump (AUX)                | ON                        |
| <input type="checkbox"/> Mixture                        | RICH                      |
| <input type="checkbox"/> Carb heat                      | ON                        |
| <input type="checkbox"/> Seat belts / shoulder harness  | SECURE                    |
| <input type="checkbox"/> Landing lights                 | ON                        |
| <input type="checkbox"/> Airspeed (downwind)            | 90 KIAS                   |
| <b>NORMAL LANDING</b>                                   |                           |
| <input type="checkbox"/> Final approach speed           | 65–75 KIAS                |
| <input type="checkbox"/> Flaps                          | FULL (40°) as required    |
| <input type="checkbox"/> Throttle (short final)         | IDLE                      |

|                                                             |                                                        |
|-------------------------------------------------------------|--------------------------------------------------------|
| <input type="checkbox"/> Touchdown (main wheels first)      | <b>SMOOTH</b>                                          |
| <input type="checkbox"/> Nose wheel                         | <b>HOLD OFF / LOWER GENTLY</b>                         |
| <input type="checkbox"/> Braking                            | <b>MODERATE</b>                                        |
| <input type="checkbox"/> Carb heat                          | <b>OFF</b>                                             |
| <b>SHORT-FIELD LANDING</b>                                  |                                                        |
| <input type="checkbox"/> Flaps                              | <b>40°</b>                                             |
| <input type="checkbox"/> Approach speed                     | <b>61 KIAS</b>                                         |
| <input type="checkbox"/> Throttle                           | <b>IDLE over threshold</b>                             |
| <input type="checkbox"/> Braking (full)                     | <b>MAXIMUM</b>                                         |
| <b>SOFT-FIELD LANDING</b>                                   |                                                        |
| <input type="checkbox"/> Flaps                              | <b>40° (full)</b>                                      |
| <input type="checkbox"/> Approach speed                     | <b>63 KIAS</b>                                         |
| <input type="checkbox"/> Throttle                           | <b>ADD POWER — keep nose high</b>                      |
| <input type="checkbox"/> Touchdown                          | <b>MAIN WHEELS ONLY</b>                                |
| <input type="checkbox"/> Back-pressure                      | <b>MAINTAIN — avoid nosing over</b>                    |
| <b>BALKED LANDING / GO-AROUND</b>                           |                                                        |
| <input type="checkbox"/> Throttle                           | <b>FULL POWER</b>                                      |
| <input type="checkbox"/> Carb heat                          | <b>OFF</b>                                             |
| <input type="checkbox"/> Flaps                              | <b>20° (retract to 10°, then retract above 200 ft)</b> |
| <input type="checkbox"/> Airspeed                           | <b>55 KIAS initially / 65 KIAS climb</b>               |
| <input type="checkbox"/> Fuel pump                          | <b>ON</b>                                              |
| <b>AFTER LANDING</b>                                        |                                                        |
| <input type="checkbox"/> Flaps                              | <b>RETRACT</b>                                         |
| <input type="checkbox"/> Carb heat                          | <b>OFF</b>                                             |
| <input type="checkbox"/> Transponder                        | <b>STBY</b>                                            |
| <input type="checkbox"/> Landing lights                     | <b>OFF</b>                                             |
| <input type="checkbox"/> Fuel pump                          | <b>OFF</b>                                             |
| <b>ENGINE SHUTDOWN &amp; SECURING</b>                       |                                                        |
| <input type="checkbox"/> Throttle                           | <b>1,000 RPM — 1 min cool</b>                          |
| <input type="checkbox"/> Avionics Master                    | <b>OFF</b>                                             |
| <input type="checkbox"/> All other switches                 | <b>OFF</b>                                             |
| <input type="checkbox"/> Mixture                            | <b>IDLE CUT-OFF (pull full out)</b>                    |
| <input type="checkbox"/> Ignition switch (after prop stops) | <b>OFF</b>                                             |
| <input type="checkbox"/> Master Switch                      | <b>OFF</b>                                             |
| <input type="checkbox"/> Fuel Selector                      | <b>BOTH</b>                                            |
| <input type="checkbox"/> Control lock                       | <b>INSTALL</b>                                         |
| <input type="checkbox"/> Logbook                            | <b>COMPLETE</b>                                        |