

EMERGENCY PROCEDURES CHECKLISTAircraft: _____

Cessna 172M | TRAINING USE ONLY | Ref: POH Section 3

FLIGHT INFORMATION

PIC Name		Date / Time	
Aircraft Reg.		Instructor / Examiner	

⚠ **CAUTION:** This checklist is for training purposes only. Procedures are memory aids derived from Cessna 172M POH Section 3. Always use the current approved POH/AFM in actual emergencies.

⚠ **MEMORY ITEMS** — Procedures marked with ⚠ should be memorised by all student pilots. *Engine failure immediately after takeoff, engine fire in flight, and spin recovery are critical memory items.*

ENGINE FAILURE DURING TAKEOFF (on ground)

☐ Throttle	IDLE
☐ Brakes	APPLY FIRMLY
☐ Mixture	IDLE CUT-OFF
☐ Magnetos/Ignition	OFF
☐ Master Switch	OFF

ENGINE FAILURE IMMEDIATELY AFTER TAKEOFF

☐ Airspeed	65 KIAS (best glide)
☐ Throttle	IDLE
☐ Mixture	IDLE CUT-OFF
☐ Fuel Selector Valve	OFF
☐ Ignition switch	OFF
☐ Master Switch	OFF (when landing assured)
☐ Land straight ahead — avoid steep turns	EXECUTE

ENGINE FAILURE IN FLIGHT

☐ Airspeed	65 KIAS (best glide)
☐ Carb heat	ON
☐ Fuel Selector	BOTH
☐ Mixture	RICH
☐ Aux fuel pump	ON
☐ Ignition switch	BOTH (then LEFT / RIGHT to check)
☐ If engine does not restart — primer	IN & LOCKED
☐ Select suitable landing area	EXECUTE FORCED LANDING
☐ Emergency squawk	7700
☐ ATC / MAYDAY call	TRANSMIT if time permits
☐ Mixture (before touchdown)	IDLE CUT-OFF
☐ Master Switch (before touchdown)	OFF
☐ Seat belts / shoulder harness	TIGHT
☐ Doors (before touchdown)	UNLATCH

ENGINE FIRE DURING START

☐ Fuel pump (aux)	OFF
☐ Throttle	FULL OPEN (to clear fuel)
☐ Mixture	IDLE CUT-OFF

LOSS OF OIL PRESSURE

☐ Land as soon as possible	EXECUTE
☐ Throttle	REDUCE (limit RPM)
☐ Nearest suitable airfield	PROCEED

ROUGH ENGINE / PARTIAL POWER LOSS

☐ Carb heat	ON
☐ Mixture	ADJUST (richen)
☐ Fuel Selector	SWITCH TANKS
☐ Ignition switch	BOTH — test L / R
☐ Aux fuel pump	ON

INADVERTENT IMC (VFR INTO CLOUD)

☐ Maintain wings level — straight & level	EXECUTE
☐ DO NOT make steep turns	AVOID
☐ Exit cloud — gentle 180° level turn	EXECUTE
☐ ATC / MAYDAY call	TRANSMIT
☐ Emergency squawk	7700

SPIN RECOVERY (PARE)

☐ P — Power	IDLE
☐ A — Ailerons	NEUTRAL
☐ R — Rudder (FULL OPPOSITE to spin direction)	APPLY
☐ E — Elevator (forward — break stall)	BRISK FORWARD
☐ Rudder (when rotation stops)	NEUTRAL
☐ Pull out of dive (do not exceed Vne)	RECOVER

EMERGENCY LANDING WITHOUT ENGINE POWER

☐ Best glide — 65 KIAS	ESTABLISH
☐ Landing area	SELECT
☐ Squawk 7700 / MAYDAY	TRANSMIT
☐ Fuel Selector	OFF
☐ Mixture	IDLE CUT-OFF
☐ Ignition switch	OFF
☐ Flaps (when field assured)	AS REQUIRED
☐ Master Switch (before touchdown)	OFF
☐ Seat belts	TIGHTEN

☐ Ignition switch (keep cranking if fire continues)	CONTINUE START
☐ If fire continues — Exit aircraft / use extinguisher	EVACUATE
ENGINE FIRE IN FLIGHT	
☐ Mixture	IDLE CUT-OFF
☐ Fuel Selector Valve	OFF
☐ Aux fuel pump	OFF
☐ Throttle	CLOSED
☐ Heater / defrost / cabin air	OFF
☐ Airspeed	100 KIAS (increase to ventilate)
☐ Emergency landing	EXECUTE
ELECTRICAL FIRE IN FLIGHT	
☐ Master Switch	OFF
☐ Avionics Master	OFF
☐ All other switches (except ignition)	OFF
☐ Cabin heat / ventilation	CLOSED
☐ Fire extinguisher	USE if available
☐ Land as soon as possible	EXECUTE
☐ Master Switch (restore only if necessary)	ON — restore only essential
CABIN FIRE	
☐ All air vents / heat / defrost	CLOSED
☐ Fire extinguisher	USE
☐ Airspeed	INCREASE to clear smoke
☐ Land as soon as possible	EXECUTE

☐ Doors	UNLATCH before touchdown
LOSS OF COMMUNICATIONS	
☐ Transponder	SQUAWK 7600
☐ Attempt contact on 121.500 MHz (Guard)	TRANSMIT
☐ Attempt on other known frequencies	TRANSMIT
☐ Light signals from ATC (if near controlled field)	MONITOR
☐ Squawk codes: 7600 = radio failure / 7700 = emergency	NOTE
DITCHING (FORCED WATER LANDING)	
☐ Squawk 7700 / MAYDAY (include position)	TRANSMIT
☐ ELT (if equipped)	ON
☐ Approach (into wind / swells)	SELECT
☐ Gear (not applicable — fixed gear)	N/A
☐ Loose items in cabin	SECURE / STOW
☐ Seat belts / harness	TIGHT
☐ Doors	UNLATCH
☐ After ditching — evacuate upwind side	EXECUTE
BRAKE FAILURE ON LANDING ROLLOUT	
☐ Throttle	IDLE
☐ Carb heat	ON
☐ Full rudder / nosewheel steering	APPLY
☐ Mixture	IDLE CUT-OFF
☐ Master Switch	OFF
☐ Steer onto soft terrain if runway overrun imminent	EXECUTE