

## q2

October 14, 2020

### 0.0.1 Note for question2

- Please follow the template to complete q2
- You may create new cells to report your results and observations

```
[54]: # Import modules
import numpy as np
import matplotlib.pyplot as plt
from sklearn.pipeline import Pipeline
from sklearn.preprocessing import PolynomialFeatures
from sklearn.linear_model import LinearRegression
from sklearn.linear_model import Lasso
from sklearn.linear_model import Ridge
from sklearn.model_selection import cross_val_score
```

### 0.1 P1. Create data and plot

#### 0.1.1 TODO

- implement the true function  $f(x)$  defined in the write-up
- use function name **model()**
- sample 30 random points with noise
- plot sampled points together with the model function

```
[63]: # Define the function to generate data points
def model(x):
    return np.sin((2.2*np.pi*x) + 0.8)

# Initialize random seed
np.random.seed(0)


# Generate noisy data points: (x,y)
n_samples = 30
train_x = np.sort(np.random.rand(n_samples))
train_y = model(train_x) + np.random.randn(n_samples) * 0.1
```

```

test_x = np.linspace(0, 1, 100)
# Plot true model and sampled data points
plt.figure()
plt.scatter(train_x, train_y, c='b', label='samples')
plt.plot(test_x, model(test_x), c='k', label='True function')
plt.xlabel('x')
plt.ylabel('y')
plt.legend()

```

[63]: <matplotlib.legend.Legend at 0x7f39a6260c70>



## 0.2 P2. Fit a linear model

### 0.2.1 TODO

- use sklearn to fit model:  $h(x) = w_0 + w_1x$
- report  $w = [w_0, w_1]$
- plot the fitted model  $h(x)$  together with data points

```

[64]: # Fit a linear model in the original space
model_linear = LinearRegression()
model_linear.fit(train_x.reshape(-1,1), train_y.reshape(-1,1))
w0 = model_linear.intercept_[0]
w1 = model_linear.coef_[0][0]

```


```

# Plot fitted linear model
plt.figure()
plt.scatter(train_x, train_y, c='b', label='samples')
plt.plot(test_x, model(test_x), c='k', label='True function')
plt.plot(test_x, model_linear.predict(test_x.reshape(-1,1)), c='r',
        ↪label='model')
plt.xlabel('x')
plt.ylabel('y')
plt.legend()

w = [w0, w1]
print("w: ", w)

```

w: [0.06038093894619001, -0.19787027099625887]



### 0.3 P3. Fit a polynomial curve

#### 0.3.1 TODO


- augment the original feature to  $[x, x^2, \dots, x^{15}]$
- fit the polynomial curve:  $h(x) = \sum_{i=0}^{15} w_i x^i$
- report  $w = [w_0, w_1, \dots, w_{15}]$
- plot the fitted model  $h(x)$  together with data points

```
[65]: # Augment the original feature to a 15-vector
X = train_x
for i in range(2, 16):
    X = np.vstack((X, np.power(train_x, i)))
```

```
[66]: # Fit linear model to the generated 15-vector features
model_degree = LinearRegression()
model_degree.fit(X.T, train_y)

test_X = test_x
for i in range(2, 16):
    test_X = np.vstack((test_X, np.power(test_x, i)))
# Plot fitted curve and sampled data points
plt.figure()
plt.scatter(train_x, train_y, c='b', label='samples')
plt.plot(test_x, model(test_x), c='k', label='True function')
plt.plot(test_x, model_degree.predict(test_X.T), c='r', label='model')
plt.xlabel('x')
plt.ylabel('y')
plt.legend()
```

[66]: <matplotlib.legend.Legend at 0x7f39a624b340>



## 0.4 P4. Lasso regularization


### 0.4.1 TODO

- use sklearn to fit a 15-degree polynomial model with L1 regularization
- report  $w$
- plot the fitted model  $h(x)$  together with data points

```
[87]: # Fit 15-degree polynomial with L1 regularization
# Start with lambda(alpha) = 0.01 and max_iter = 1e4
lasso = Lasso(alpha=0.0001, max_iter = 1e4)
lasso.fit(X.T, train_y)

# Plot fitted curve and sampled data points
plt.figure()
plt.scatter(train_x, train_y, c='b', label='samples')
plt.plot(test_x, model(test_x), c='k', label='True function')
plt.plot(test_x, lasso.predict(test_X.T), c='r', label='model')
plt.xlabel('x')
plt.ylabel('y')
plt.legend()
w = np.concatenate((np.array([lasso.intercept_]), lasso.coef_))
print("w: ", w )
```

```
/home/tito/anaconda3/lib/python3.8/site-
packages/sklearn/linear_model/_coordinate_descent.py:529: ConvergenceWarning:
Objective did not converge. You might want to increase the number of iterations.
Duality gap: 0.02063625723760909, tolerance: 0.00175155385437781
  model = cd_fast.enet_coordinate_descent(
w: [ 1.06843622  0.2167843 -14.45629376  5.73351697 14.49985714
      0.          0.          -0.          -0.         -5.1753093
     -2.49636651 -0.          -0.          -0.          0.
      1.45189882]
```



Decreasing the alpha value increases the polynomial degree. Decreasing max\_iter decreases the polynomial degree. Based on analysis, Lasso reduces the coefficients of the features to prevent overfitting.

## 0.5 P5. Ridge regularization

### 0.5.1 TODO

- use sklearn to fit a 15-degree polynomial model with L2 regularization
- report  $w$
- plot the fitted model  $h(x)$  together with data points

```
[97]: # Fit 15-degree polynomial with L2 regularization
# Start with lambda(alpha) = 0.01 and max_iter = 1e4
ridge = Ridge(alpha=0.0003, max_iter = 1e4)
ridge.fit(X.T, train_y)


# Plot fitted curve and sampled data points and compare to L1 regularization
# from P4

plt.figure()
plt.scatter(train_x, train_y, c='b', label='samples')
plt.plot(test_x, model(test_x), c='k', label='True function')
plt.plot(test_x, ridge.predict(test_X.T), label='model')
```

```
plt.xlabel('x')
plt.ylabel('y')
plt.legend()

w = np.concatenate((np.array([ridge.intercept_]), ridge.coef_))
print("w: ", w )
```

```
w: [ 1.05451815  0.18540835 -12.58679744  2.63754965  8.86537084
  7.85860742  4.06314768  0.11573308 -2.82296512 -4.4190787
 -4.73235933 -3.9766228  -2.40068539 -0.235759  2.32330082
  5.12086941]
```



Ridge follows a similar trend of decreasing the alpha value increases the polynomial degree. Decreasing `max_iter` decreases the polynomial degree. Ridge is more sensitive and instead of reducing the features, it appears to tweak the features.

[ ]: