

IMPUTACION DE VALORES

Nombre: Steven Chuiza

Fecha: 05/05/2026

```
In [1]: import numpy as np
        from sklearn.impute import SimpleImputer
```

```
In [2]: # Carga de datos
X_train = [[1,      4],
           [np.nan, 3],
           [7,      8]]
```

```
In [3]: # Limpieza de datos: imputación valores ausentes (modelo)
imputer = SimpleImputer(strategy='mean') # Utilizamos la estrategia de la media

# Aplicar los métodos "fit" y "transform" para imputar los valores perdidos de X
X_train_clean = imputer.fit_transform(X_train)
print(X_train_clean)
```

```
[[1.  4.]
 [4.  3.]
 [7.  8.]]
```

```
In [4]: # Imputación de valores ausentes sobre el conjunto de test
X_test = [[np.nan, 10],
          [6,      np.nan],
          [8,      2]]

# Imputar los datos del conjunto de test
X_test_clean=imputer.transform(X_test)
print(X_test_clean)
```

```
[[ 4. 10.]
 [ 6.  5.]
 [ 8.  2.]]
```

Repositorio de

GitHub:https://github.com/tiven29/Fundamentos_Machine_Learning/tree/main/.ipynb_check



```
In [ ]:
```