



File Edit View Insert Cell Kernel Widgets Help

Python 3

You are currently looking at **version 1.0** of this notebook. To download notebooks and datafiles, as well as get help on Jupyter notebooks in the Coursera platform, visit the [Jupyter Notebook FAQ](#) course resource.

Applied Machine Learning: Module 4 (Supervised Learning, Part II)

Preamble and Datasets

```
In [ ]: %matplotlib notebook
import numpy as np
import pandas as pd
import seaborn as sn
import matplotlib.pyplot as plt

from sklearn.model_selection import train_test_split
from sklearn.datasets import make_classification, make_blobs
from matplotlib.colors import ListedColormap
from sklearn.datasets import load_breast_cancer
from adspy_shared_utilities import load_crime_dataset

cmap_bold = ListedColormap(['#FFFF00', '#00FF00', '#0000FF', '#000000'])

# fruits dataset
fruits = pd.read_table('readonly/fruit_data_with_colors.txt')

feature_names_fruits = ['height', 'width', 'mass', 'color_score']
X_fruits = fruits[feature_names_fruits]
y_fruits = fruits['fruit_label']
target_names_fruits = ['apple', 'mandarin', 'orange', 'lemon']

X_fruits_2d = fruits[['height', 'width']]
y_fruits_2d = fruits['fruit_label']

# synthetic dataset for simple regression
from sklearn.datasets import make_regression
plt.figure()
plt.title('Sample regression problem with one input variable')
X_R1, y_R1 = make_regression(n_samples = 100, n_features=1,
                             n_informative=1, bias = 150.0,
                             noise = 30, random_state=0)
plt.scatter(X_R1, y_R1, marker= 'o', s=50)
plt.show()

# synthetic dataset for more complex regression
from sklearn.datasets import make_friedman1
plt.figure()
plt.title('Complex regression problem with one input variable')
X_F1, y_F1 = make_friedman1(n_samples = 100, n_features = 7,
                            random_state=0)

plt.scatter(X_F1[:, 2], y_F1, marker= 'o', s=50)
plt.show()

# synthetic dataset for classification (binary)
plt.figure()
plt.title('Sample binary classification problem with two informative features')
X_C2, y_C2 = make_classification(n_samples = 100, n_features=2,
                                 n_redundant=0, n_informative=2,
                                 n_clusters_per_class=1, flip_y = 0.1,
                                 class_sep = 0.5, random_state=0)
plt.scatter(X_C2[:, 0], X_C2[:, 1], marker= 'o',
            c=y_C2, s=50, cmap=cmap_bold)
plt.show()

# more difficult synthetic dataset for classification (binary)
# with classes that are not linearly separable
X_D2, y_D2 = make_blobs(n_samples = 100, n_features = 2,
                        centers = 8, cluster_std = 1.3,
                        random_state = 4)
y_D2 = y_D2 % 2
plt.figure()
plt.title('Sample binary classification problem with non-linearly separable classes')
plt.scatter(X_D2[:,0], X_D2[:,1], c=y_D2,
            marker= 'o', s=50, cmap=cmap_bold)
plt.show()

# Breast cancer dataset for classification
cancer = load_breast_cancer()
(X_cancer, y_cancer) = load_breast_cancer(return_X_y = True)

# Communities and Crime dataset
(X_crime, y_crime) = load_crime_dataset()
```

Naive Bayes classifiers

```
In [ ]: from sklearn.naive_bayes import GaussianNB
from adspy_shared_utilities import plot_class_regions_for_classifier

X_train, X_test, y_train, y_test = train_test_split(X_C2, y_C2, random_state=0)

nbclf = GaussianNB().fit(X_train, y_train)
plot_class_regions_for_classifier(nbclf, X_train, y_train, X_test, y_test,
                                'Gaussian Naive Bayes classifier: Dataset 1')

In [ ]: X_train, X_test, y_train, y_test = train_test_split(X_D2, y_D2,
                                                       random_state=0)

nbclf = GaussianNB().fit(X_train, y_train)
plot_class_regions_for_classifier(nbclf, X_train, y_train, X_test, y_test,
```

Application to a real-world dataset

```
In [ ]: X_train, X_test, y_train, y_test = train_test_split(X_cancer, y_cancer, random_state = 0)

nbclf = GaussianNB().fit(X_train, y_train)
print('Breast cancer dataset')
print('Accuracy of GaussianNB classifier on training set: {:.2f}'
     .format(nbclf.score(X_train, y_train)))
print('Accuracy of GaussianNB classifier on test set: {:.2f}'
     .format(nbclf.score(X_test, y_test)))
```

Ensembles of Decision Trees

Random forests

```
In [ ]: from sklearn.ensemble import RandomForestClassifier
from sklearn.model_selection import train_test_split
from adspy_shared_utilities import plot_class_regions_for_classifier_subplot

X_train, X_test, y_train, y_test = train_test_split(X_D2, y_D2,
                                                    random_state = 0)
fig, subaxes = plt.subplots(1, 1, figsize=(6, 6))

clf = RandomForestClassifier().fit(X_train, y_train)
title = 'Random Forest Classifier, complex binary dataset, default settings'
plot_class_regions_for_classifier_subplot(clf, X_train, y_train, X_test,
                                         y_test, title, subaxes)

plt.show()
```

Random forest: Fruit dataset

```
In [ ]: from sklearn.ensemble import RandomForestClassifier
from sklearn.model_selection import train_test_split
from adspy_shared_utilities import plot_class_regions_for_classifier_subplot

X_train, X_test, y_train, y_test = train_test_split(X_fruits.as_matrix(),
                                                    y_fruits.as_matrix(),
                                                    random_state = 0)
fig, subaxes = plt.subplots(6, 1, figsize=(6, 32))

title = 'Random Forest, Fruits dataset, default settings'
pair_list = [[0,1], [0,2], [0,3], [1,2], [1,3], [2,3]]

for pair, axis in zip(pair_list, subaxes):
    X = X_train[:, pair]
    y = y_train

    clf = RandomForestClassifier().fit(X, y)
    plot_class_regions_for_classifier_subplot(clf, X, y, None,
                                             None, axis,
                                             target_names_fruits)

    axis.set_xlabel(feature_names_fruits[pair[0]])
    axis.set_ylabel(feature_names_fruits[pair[1]])

plt.tight_layout()
plt.show()

clf = RandomForestClassifier(n_estimators = 10,
                            random_state=0).fit(X_train, y_train)

print('Random Forest, Fruit dataset, default settings')
print('Accuracy of RF classifier on training set: {:.2f}'
     .format(clf.score(X_train, y_train)))
print('Accuracy of RF classifier on test set: {:.2f}'
     .format(clf.score(X_test, y_test)))
```

Random Forests on a real-world dataset

```
In [ ]: from sklearn.ensemble import RandomForestClassifier

X_train, X_test, y_train, y_test = train_test_split(X_cancer, y_cancer, random_state = 0)

clf = RandomForestClassifier(max_features = 8, random_state = 0)
clf.fit(X_train, y_train)

print('Breast cancer dataset')
print('Accuracy of RF classifier on training set: {:.2f}'
     .format(clf.score(X_train, y_train)))
print('Accuracy of RF classifier on test set: {:.2f}'
     .format(clf.score(X_test, y_test)))
```

Gradient-boosted decision trees

```
In [ ]: from sklearn.ensemble import GradientBoostingClassifier
from sklearn.model_selection import train_test_split
from adspy_shared_utilities import plot_class_regions_for_classifier_subplot

X_train, X_test, y_train, y_test = train_test_split(X_D2, y_D2, random_state = 0)
fig, subaxes = plt.subplots(1, 1, figsize=(6, 6))

clf = GradientBoostingClassifier().fit(X_train, y_train)
title = 'GBDT, complex binary dataset, default settings'
plot_class_regions_for_classifier_subplot(clf, X_train, y_train, X_test,
                                         y_test, title, subaxes)

plt.show()
```

Gradient boosted decision trees on the fruit dataset

```
In [ ]: X_train, X_test, y_train, y_test = train_test_split(X_fruits.as_matrix(),
                                                    y_fruits.as_matrix(),
                                                    random_state = 0)
fig, subaxes = plt.subplots(6, 1, figsize=(6, 32))

pair_list = [[0,1], [0,2], [0,3], [1,2], [1,3], [2,3]]

for pair, axis in zip(pair_list, subaxes):
```



```
plt.tight_layout()
```

The effect of different choices of activation function

```
In [ ]: X_train, X_test, y_train, y_test = train_test_split(X_D2, y_D2, random_state=0)

fig, subaxes = plt.subplots(3, 1, figsize=(6,18))

for this_activation, axis in zip(['logistic', 'tanh', 'relu'], subaxes):
    nnclf = MLPClassifier(solver='lbfgs', activation = this_activation,
                          alpha = 0.1, hidden_layer_sizes = [10, 10],
                          random_state = 0).fit(X_train, y_train)

    title = 'Dataset 2: NN classifier, 2 layers 10/10, {} \\\nactivation function'.format(this_activation)

    plot_class_regions_for_classifier_subplot(nnclf, X_train, y_train,
                                              X_test, y_test, title, axis)
    plt.tight_layout()
```

Neural networks: Regression

```
In [ ]: from sklearn.neural_network import MLPRegressor

fig, subaxes = plt.subplots(2, 3, figsize=(11,8), dpi=70)

X_predict_input = np.linspace(-3, 3, 50).reshape(1,1)

X_train, X_test, y_train, y_test = train_test_split(X_R1[0::5], y_R1[0::5], random_state = 0)

for thisaxisrow, thisactivation in zip(subaxes, ['tanh', 'relu']):
    for thisalpha, thisaxis in zip([0.0001, 1.0, 100], thisaxisrow):
        mlpreg = MLPRegressor(hidden_layer_sizes = [100,100],
                              activation = thisactivation,
                              alpha = thisalpha,
                              solver = 'lbfgs').fit(X_train, y_train)
        y_predict_output = mlpreg.predict(X_predict_input)
        thisaxis.set_xlim([-2.5, 0.75])
        thisaxis.plot(X_predict_input, y_predict_output,
                      '^', markersize = 10)
        thisaxis.plot(X_train, y_train, 'o')
        thisaxis.set_xlabel('Input feature')
        thisaxis.set_ylabel('Target value')
        thisaxis.set_title('MLP regression\nalpha={}, activation={}'.format(thisalpha, thisactivation))
    plt.tight_layout()
```

Application to real-world dataset for classification

```
In [ ]: from sklearn.neural_network import MLPClassifier
from sklearn.preprocessing import MinMaxScaler

scaler = MinMaxScaler()

X_train, X_test, y_train, y_test = train_test_split(X_cancer, y_cancer, random_state = 0)
X_train_scaled = scaler.fit_transform(X_train)
X_test_scaled = scaler.transform(X_test)

clf = MLPClassifier(hidden_layer_sizes = [100, 100], alpha = 5.0,
                    random_state = 0, solver='lbfgs').fit(X_train_scaled, y_train)

print('Breast cancer dataset')
print('Accuracy of NN classifier on training set: {:.2f}' .format(clf.score(X_train_scaled, y_train)))
print('Accuracy of NN classifier on test set: {:.2f}' .format(clf.score(X_test_scaled, y_test)))
```