

✓ **Congratulations! You passed!**
TO PASS 80% or higher

Keep Learning

GRADE
100%

AutoGraph

LATEST SUBMISSION GRADE

100%

1. Which of the following statements is *false* about Graph approach?

1 / 1 point

- ☒ Easier debugging
- ☐ Parallelism
- ☐ Faster compilation
- ☐ Portability



Correct

Correct! This statement is false. Since operations don't execute until the Graph is fully designed, it can be tricky to debug.

2. Which of the following statements is *true* for *tf.cond*?

1 / 1 point

- ☒ Graph execution does not support *if/else* statements. To replicate that effect you use *tf.cond*
- ☐ *tf.cond* is an alternative to using *if/else* statements in Graphs, as its execution is much faster than *if/else* statements.



Correct

Correct!

3. Consider the following code:

1 / 1 point

```
def increment_by_two(x):  
    return x + 2  
  
def multiple_increment(x, i):  
    k = x  
    for j in range(i):  
        k = increment_by_two(k)  
    return k
```

How do you convert *both* of these functions to execute in *Graph* mode? Check all that are true.

- ☐ By adding the decorator, `@tf.function`, only above the function definition of *increment_by_two*
- ☒ By adding the decorator, `@tf.function`, only above the function definition of *multiple_increment*



Correct

Correct! If a function is decorated with '`@tf.function`', then the functions that it calls will also be included in graph mode.

- ☒ By adding the decorator, `@tf.function`, above the definitions of both of the functions.



Correct

Correct!

- ☐ By adding the decorator, `@tf.autograph`, above the definitions of both of the functions.

4. Function written in Eager mode when converted to Graph accommodates different data types all in one, so you don't have to define similar functions for different data types.

1 / 1 point

- ☐ False
- ☒ True



Correct

Correct!

5. Which of the following is the correct syntax to display the auto-generated AutoGraph code if your function name is *my_function*?

1 / 1 point

- ☐ tf.autograph.code(my_function)
- ☐ tf.autograph.code(my_function.python_function)
- ☐ tf.autograph.to_code(my_function)
- ☒ tf.autograph.to_code(my_function.python_function)

✓ **Correct**
Correct!

6. Consider the following code, what will be the output?

1 / 1 point

```
def func(str):  
    print(str)  
    tf.print(str)  
  
for i in range(3):  
    func("Hello World!")
```

- ☐ Hello World!
Hello World!
Hello World!
Hello World!
- ☒ Hello World!
Hello World!
Hello World!
Hello World!
Hello World!
Hello World!
Hello World!
- ☐ Hello World!
Hello World!
Hello World!

✓ **Correct**
Correct! Even though tf.print is used, we still get 6 print statements because the function is not decorated to run as a Graph.